# MODIFIED ATTACHMENT FOR DCR422

SHOWNER "APPROVED WORDING" IF DIFFERENT FROM "PROPOSED WORDING":

19/9/08.

1.4.2 Component Type Variants

The component type variants applicable to this specification are as follows:

Variant Number	Based on Type	Case	Lead/Terminal Material and finish	Weight max g
01	2N3700	TO-18	D2	/ 0.4
/02	/ 2N3700 /	TØ-18	D3 or D4	0.4
04	/ 2N3700/	CCP	/ 2 /	0.06
05	/ 2N3700	CCP	4 /	0.06
06	2N3700	/ CCP	2 /	0.06
07	2N3700	Cer	4 / /	0.06/
1				7

See mall-up of Para 1.4.2 attached: \*

1.7 Functional Diagram
see making of Para 1.7 attached.



ISSUE 3

# 1. **GENERAL**

# 1.1 SCOPE

This specification details the ratings, physical and electrical characteristics and test and inspection data for the component type variants and/or the range of components specified below. It supplements the requirements of, and shall be read in conjunction with, the ESCC Generic Specification listed under Applicable Documents.

# 1.2 <u>APPLICABLE DOCUMENTS</u>

The following documents form part of this specification and shall be read in conjunction with it:

- (a) ESCC Generic Specification No. 5000
- (b) MIL-STD-750, Test Methods and Procedures for Semiconductor Devices

# 1.3 TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS

For the purpose of this specification, the terms, definitions, abbreviations, symbols and units specified in ESCC Basic Specification No. 21300 shall apply.

# 1.4 THE ESCC COMPONENT NUMBER AND COMPONENT TYPE VARIANTS

### 1.4.1 The ESCC Component Number

The ESCC Component Number shall be constituted as follows:

Example: 520101901

Detail Specification Reference: 5201019

Component Type Variant Number: 01 (as required)

# X

# 1.4.2 Component Type Variants


The component type variants applicable to this specification are as follows:

	C3Term			)
Variant Number	Based on Type	Case	Lead/Terminal Material and/or Finish	Weight max g
01	2N5551	TO-18	D2	0.4
02	2N5551	TO-18	D3 or D4	0.4
04	2N5551	CCP	2	0.06
05	2N5551	CCP	4	0.06
06	2N5551	TO-39	D2	1.5
07	2N5551	TO-39	D3 or D4	1.5

The lead/terminal material and/or finish shall be in accordance with the requirements of ESCC Basic Specification No. 23500.

ଚଃ	2NSSS1	(4 Terminal)	2	0.06
09	2NSSS1	CCP Cuterminal)	Sangrey.	0.06






	Dimensi		
Symbols	Min	Max	Notes
А	1.15	1.5	
С	0.45	0.56	2
D	0.6	0.91	2
E	0.91	1.12	
F	1.9	2,15	
G	2.9	3.25	
	2.4	2.85	
L	0.4	0.6	2
М	2.4	2.65	
N	1.8	2	
r1	0.3 TYPICAL		1
r2	0.56 TYPICAL		annee



not exceed 0.254mm.

- The details of outline in this zone are optional.
- Measured from the Tab Centreline.

### 1.7 **FUNCTIONAL DIAGRAM**



- 1. Emitter.
- 2. Base.
- Collector.
- 4. Shielding

Steminal

(Variants 04,05)

- For TO-18 and TO-39, the collector is internally connected to the case.
   For CCF, the lid is not connected to any terminal.
- 3. For 4 terminal CCP (Various 08,09), the shielding terminal is connected to the lid.

### MATERIALS AND FINISHES 1.8

Materials and finishes shall be as follows:

### a)

For metal can packages, the case shall be hermetically sealed and have a metal body with hard glass seals.

For the chip carrier package the case shall be hermetically sealed and have a ceramic body with a Kovar lid.

Leads/Terminals

As specified in Component Type Variants.

### 2. REQUIREMENTS

### **GENERAL** 2.1

The complete requirements for procurement of the components specified herein are as stated in this specification and the ESCC Generic Specification. Permitted deviations from the Generic Specification, applicable to this specification only, are listed below.

Permitted deviations from the Generic Specification and this Detail Specification, formally agreed with specific Manufacturers on the basis that the alternative requirements are equivalent to the ESCC requirement and do not affect the component's reliability, are listed in the appendices attached to this specification.

### 2.1.1 Deviations from the Generic Specification

(a) Deviation from Screening Tests - Chart F3