

2.6 BURN-IN CONDITIONS

Characteristics	Symbols	Test Conditions	Units
Heater Temperature Variants 01, 03 Variant 02	T_{HTR}	+150 (Note 1) +200 (Note 1)	°C
Power Density Variants 01, 03 Variant 02	P_n	0.38 (Note 1) 0.54 (Note 1)	W/cm ²

NOTES:

1. Voltage shall be applied until either the specified heater temperature or the power density is reached.

2.7 OPERATING LIFE CONDITIONS

The conditions shall be as specified for Burn-in.

APPENDIX 'A'AGREED DEVIATIONS FOR MINCO

ITEMS AFFECTED	DESCRIPTION OF DEVIATIONS
Deviations from Screening Tests - Chart F3	<p>Serialisation: A 100% serialisation, performed prior to Screening tests with subsequent Electrical Measurements at room, High and Low Temperatures performed read and records, is optional at the Manufacturer's discretion.</p> <p>Para.8.2, Rapid Change of Temperature: Mounting: Heaters may be mounted using any suitable method. Data Points: Electrical measurements during and after testing are optional at the Manufacturer's discretion.</p> <p>Para.8.3, Overload: Data Points: Electrical measurements after testing are optional at the Manufacturer's discretion.</p>