



DOCUMENT CHANGE REQUEST

DCR number 1758 Changes required for: General

Originator: David Preiss

Date: 2025/09/30

Date sent: 2025/08/20

Organisation: IST

Status: IMPLEMENTED

Title: Resistance Temperature Detector Thin Film Platinum Sensor, PTC Range 100 to 2000 Ohms At 0

Number: 4006/015

Issue: 6

Other documents affected:

Page:

10, 11, 14

Paragraph:

1.7.2.1, 1.7.2.2, 1.7.2.5

Original wording:

add a point at notes on corresponding pages

Proposed wording:

4) If the total cable length (TL) is 1 meter or more, additional shrink tubes must be applied at intervals of 20 to 30 cm along the cable. Each shrink tube must be 10 mm in length, with tolerances in accordance with Symbol K.

Justification:

Attachments:

N/A

Modifications:

The following additions & modifications to the original contents of this DCR are implemented:
See attached spec mark-up Draft 7 for details.
Para. 1.7.2.1, 1.7.2.2, 1.7.2.5: wording used is modified for clarification/consistency purposes
Para. 1.9.3: last sub-para is amended to be consistent with the changes w.r.t heat-shrink tubing.

Plus several minor editorial changes in;

Para. 1.4.2 Note 5:

Approval signature:

Date signed:

2025-09-30