



DOCUMENT CHANGE REQUEST

DCR number 961

Changes required for: N/A

Originator: Olivier Masson

Date: 2016/01/15

Date sent: 2015/11/23

Organisation: C&K Components

Status: IMPLEMENTED

Title: Connectors, Electrical, Rectangular, Microminiature, Removable Crimp Contacts, Based on Type

Number: 3401/077

Issue: 5

Other documents affected:

Page:

Pages 6, 7, 9,10,12,15,16 and one new page added.

Paragraph:

See attached draft

Original wording:


See ESCC 3401/077 ISSUE 5

Proposed wording:

See attached draft

Justification:

Page 6: Copper plating specification Not applicable
Pages 7, 9 and 10: Update linked to the increase of rear insulator height
Page 12: wires cross section and maxi weight removed from Figure 2.4
Page 15: Chart II modified to be in accordance with PID
Page 16 and new page: Contact removal tool definition

Attachments:
draft_3401077.pdf, null
Modifications:
<p>the following minor editorial changes (ref. attachment draft_3401077.pdf) are made:</p> <p>1. Pg. 7 Table 1(a) Note 2 - "b" of backshell shall be lower case (not upper case); "Figure" not "Figures".</p> <p>2. Pg. 12 Figure 2.4 - Remove the first two columns and add a single column containing two rows. The content of the upper row shall be "Maximum Conductor Diameter mm"; the content of the lower row shall be "Maximum Wire Diameter mm"</p> <p>3. Pg. 15 Para. 4.2.2 - Add full stops to (b) and (c) i.e. "...applicable." "...equipment."</p> <p>4. Pg. 16 Para. 4.3.8 - The additional text shall be "with removal tool defined in Figure 4."</p> <p>5. New Figure 4 added - In the title, correct "REMOVABLE" to "REMOVAL". This Figure shall be located on Pg. 15, i.e. immediately after Figure 3 (on Pg. 14) and before section 4 REQUIREMENTS</p>
Approval signature:

Date signed:
2016-01-15