

1195 DCR number Changes required for: General Originator: Celine Dumortier Date: 2019/03/25 Date sent: 2018/11/30 Organisation: Radiall Status: IMPLEMENTED Title: RF Coaxial Adaptors and Connecting Pieces, Type SMA 2.9, 50 Ohms Number: 3402/023 Issue: 6 Other documents affected: Page: 19 Paragraph: VARIANT 01 - STRAIGHT MALE-MALE ADAPTOR Original wording: Dimension B min =19.7 and Dimension B max = 20 Proposed wording: Dimension B min =17.1 and Dimension B max = 20.6 Justification:

The dimension B is wrong because there are the gap of the nut and the ring (see drawing attached)



1195 DCR number Changes required for: General Originator: Celine Dumortier Date: 2019/03/25 Date sent: 2018/11/30 Organisation: Radiall Status: IMPLEMENTED Title: RF Coaxial Adaptors and Connecting Pieces, Type SMA 2.9, 50 Ohms Number: 3402/023 Issue: 6 Other documents affected: Page: 21 Paragraph: VARIANT 03 – STRAIGHT MALE-FEMALE ADAPTOR Original wording: Dimension B min =18.82 and Dimension B max = 18.97 Proposed wording: Dimension B min =18.2 and Dimension B max = 19.3 Justification:

The dimension B is wrong because there are the gap of the nut and the ring (see drawing attached)



1195 DCR number Changes required for: General Originator: Celine Dumortier Organisation: Radiall Date: 2019/03/25 Date sent: 2018/11/30 Status: IMPLEMENTED Title: RF Coaxial Adaptors and Connecting Pieces, Type SMA 2.9, 50 Ohms Number: Issue: 3402/023 6 Other documents affected: Page: 24 Paragraph: VARIANT 06 - RIGHT ANGLE MALE-FEMALE ADAPTOR Original wording: Maximum Weight = 4.8 g Proposed wording: Maximum Weight = 7 g

Justification:

The weight of the variant Male-Female (4.8g) is wrong because the variant male – male (variante 4) is of 7, 5g and the variant Female-Female (Variant 5) is 5g. The weight of the variant Male-Female (variante 6) is of 7g.



DCR number 1195 Changes required for: General Originator: Celine Dumortier

Date: 2019/03/25 Date sent: 2018/11/30 Organisation: Radiall

Status: IMPLEMENTED

Title:	RF Coaxial Adaptors and Connecting Pieces, Type SMA 2.9, 50 Ohms			
Number:	3402/023	Issue:	6	
Other documents affected:				
Page:				
19 to 24				
Paragraph:				
VARIANT 01 to 06				
Original wording:				
RF Leakage = -(90 - f (GHz))dB (STRAIGHT connector) and RF Leakage = -(120 - f (GHz))dB (RIGHT ANGLE connector)				
Proposed wording:				
RF Leakage = -(115 - f (GHz))dB (STRAIGHT connector and RIGHT ANGLE connector)				
Justification:				
The RF leakage performance of the straight connector is better than -(90 - f (GHz))dB and the RF leakage performance of the right angle connector is less than -(120 - f (GHz))dB. See attached the performance measured. The same performance of RF leakage could be applied for the straight and right angle connector.				
Attachments:				
mesure_rf_leakage_raccord_sma2.9_maj_28.11.2018(2).pdf, drawinggap_ring_nut(2).docx				
Modifications:				
The following modification has been agreed by supporting Manufacturers: Radiall and Rosenberger.				
Note: Original DCR changes to Dim B for Variant 03, Dim. B for Variant 01, Max. Weight for Variant 06 are not modified and still apply.				

RF Leakage value for only Variants 04, 05, 06 (right angle adaptors) is changed to be: -(115 - f(GHz)) dB

The change to RF leakage value for Variants 01 to 06 (on Pages 19 to 24) is replaced by the following:

[was: -(120 - f(GHz)) dB]				
[Variants 01, 02, 03 are unchanged in this regard)				
Approval signature:				
Luston Resu				
Date signed:				
2019-03-25				