



DOCUMENT CHANGE REQUEST

DCR number 815 Changes required for: General

Date: 2013/12/05

Date sent: 2013/08/22

Originator: Steve Thacker

Organisation: ESCC Executive
Secretariat

Status: IMPLEMENTED

Title: Relays Electromagnetic Latching 28Vdc 1A 2PDT TO5 Can

Number: 3602/002

Issue: 1

Other documents affected:

Page:

See below with reference to 3602/002 draft 2B (per approved but not yet implemented DCR712)

Paragraph:

See below with reference to 3602/002 draft 2B (per approved but not yet implemented DCR712)

Original wording:

See 3602/002 draft 2B (per approved but not yet implemented DCR712)

Proposed wording:

This DCR details various technical plus minor editorial changes made in addition to those detailed in approved but not yet implemented DCR712. See this DCR attachment 3602/002 draft 2D for full details. References in this DCR to changes, are made against the previous draft 3602/002 draft 2B included as part of DCR712.

Note: The attachment to this DCR, 3602/002 draft 2D, includes all the changes contained in this DCR, as detailed below, as well as those per DCR712. In case of conflict this DCR takes precedence over DCR712.

Note: This DCR also implements the use of alternate publishing software for this specification (was: GlobalView; is now: WORD2010).

1) Several minor editorial amendments are made (to be consistent with other ESCC 3601/xxx Detail Specs).

See attachment for details.

Para 1.4.2 & Para 1.8.2, Move Terminal Material & finish requirements to Para 1.8.2.

Para 1.4.2, Note 1;

Para 2.4.1 & 2.4.2, Insulation Resistance test condition

2) Para 1.4.2, Component Type Variants and Range of Components

Maximum weight is amended for each variant (was 2.9g max for all variants) (as requested by REL STPI).

3) Para 1.7, FUNCTIONAL DIAGRAM

Note 1 is clarified to read: "As viewed from the terminal side with coil de-energised."

DCR number 815 Changes required for: General

Date: 2013/12/05

Date sent: 2013/08/22

Originator: Steve Thacker

Organisation: ESCC Executive
Secretariat

Status: IMPLEMENTED

4) Para 1.8.1, Case

Amend case material to be Nickel (was Copper nickel) (as requested by REL STPI)

5) Para 2.4.1 & 2.4.2, Room Temperature Electrical Measurements & High and Low Temperatures Electrical Measurements

Contact Voltage Drop:

The test condition is clarified to be $I_{TEST} = 100\text{mA}$ maximum to be consistent with the generic spec ESCC 3601.

The VD max limit is clarified to be $0.1 \times I_{TEST}$ (was 10mV) (based on 100mOhm value from Table 1(b) in previous spec for contact resistance and the test current of 100mA maximum).

6) Para 2.4.2, High and Low Temperatures Electrical Measurements

For Latch Voltage & Reset Voltage delete all minimum limits. Tests shall be performed at both high (+125C) and low (-65C) temperatures.

7) Para 2.6 INTERMEDIATE AND END-POINT ELECTRICAL MEASUREMENTS

Contact Voltage Drop: The VD max limit for the following tests is amended and clarified as follows to be consistent with the new Para 2.4.1 test conditions; see 5) above):

Low Level Life: $0.2 \times I_{TEST}$ (= 20mV) maximum during final measurements (clarification only; no actual change).

Resistive Life: $0.2 \times I_{TEST}$ (= 20mV) maximum during final measurements (clarification only; no actual change).

Intermediate Current: $0.2 \times I_{TEST}$ (= 20mV) maximum during final measurements (clarification only; no actual change).

Overload: 1.4V (was 400mV) maximum during monitoring (reinstate the original limit specified in 3602/002 issue 2); $0.2 \times I_{TEST}$ (= 20mV) maximum during final measurements (clarification only; no actual change), to make the limit consistent with the other tests and the 100mA test conditions.

9) Appendix A for REL STPI

Add Appendix to detail the following deviations:

- Deviations to Chart F4: Coil Life subgroup test sequence (under Endurance Subgroup 1): Coil Life and the subsequent tests shall only be performed for Qualification. They are not required for Periodic Testing except in the case of any significant change to the design (as requested by REL STPI)

Justification:



DOCUMENT CHANGE REQUEST

DCR number 815 Changes required for: General

Date: 2013/12/05 Date sent: 2013/08/22

Status: IMPLEMENTED

Originator: Steve Thacker

Organisation: ESCC Executive
Secretariat

After several reviews including direct discussions with the Manufacturer (REL STPI) & CNES, the changes to be made to this specification and hence the contents of this DCR have been finalised and agreed (as part of a review of all ESCC 3601/xxx & 3602/xxx specifications).

This DCR implements additional minor editorial corrections and several technical changes resulting from review of 3602002 Draft 2B & DCR712 and other current, open relay DCRs for correction & consistency purposes. This DCR completes the conversion initiated under DCR712.

Attachments:

3602002_issue_2d_in_review.pdf, null

Modifications:

N/A

Approval signature:

Date signed:

2013-12-05