

## DOCUMENT CHANGE REQUEST

DCR number 845 Changes required for: General Originator: Bertrand Marty

Status: IMPLEMENTED

Title:	RF Inductors Fixed Miniature Moulded SMD, based on series MSCI 10K and MSCI 12K			
Number:	3201/008	Issue:	5	
Other documents affected:				

Page:

6

Paragraph:

3. Range of components 10K series

Original wording:

In column (7) Max. DC resistance

line:

- 1L0K (1000 nH)
- 1L2K (1200 nH)
- 2200 nH (2L2K),
- 1800 nH (1LK8)
- 10000 nH (100K).

## Proposed wording:

## Change Value:

- 1000 nH (1L0K): 0.34 Ohm instead of de 0.320 Ohm
- 1200 nH (1L2K): 0.55 Ohm instead of 0.4 Ohm,
- 1500 nH (1L5K): 0.73 Ohm instead of 0.56 Ohm,
- 1800 nH (1LK8): 0.92 Ohm instead of 0.91 Ohm,
- 10000 nH (100K): 2.8 Ohm instead of 3.3 Ohm.

## Justification:

This evolution of values are to reduce the value of RDC max for best detection of problems and non conformity.

Attachments:			
modifications_to_dcr845.docx, mscirdc_maxissue_2(2).xls			
Modifications:			
The original contents and attachment of this DCR845 are replaced with the following in order to clarify the exact changes requested by Microspire:			
Original Wording Section: replace with the following:  See ESCC3201/008 issue 5, Page 6 & 7, Table 1a – Range of Components - 10k Series, column 7: Max DC Resistance Rdc (ohm)(see also original 'was' value in the list/table in the attached file).			
Proposed Wording Section: replace with the following:  Table 1a – Range of Components - 10k Series, column 7: Max DC Resistance Rdc (ohm). Amend the Rdc limits in column 7 for all items in the 10K series to be in accordance with the following list/table in the attached file.			
See new attachment for details of required changes.			
Approval signature:			
12. Carlana			
Date signed:			
2014-10-06			