



**THERMISTORS**  
**(THERMALLY SENSITIVE RESISTORS), NTC,**  
**RANGE 2 000 TO 100 000 OHMS AT +25°C WITH**  
**A TEMPERATURE RANGE OF -40 TO +160 °C**  
**ESCC Detail Specification No. 4006/014**

**ISSUE 1**  
**October 2002**



	ESCC Detail Specification		PAGE ii ISSUE 1
---	---------------------------	--	--------------------

### **LEGAL DISCLAIMER AND COPYRIGHT**

European Space Agency, Copyright © 2002. All rights reserved.

The European Space Agency disclaims any liability or responsibility, to any person or entity, with respect to any loss or damage caused, or alleged to be caused, directly or indirectly by the use and application of this ESCC publication.

This publication, without the prior permission of the European Space Agency and provided that it is not used for a commercial purpose, may be:

- copied in whole in any medium without alteration or modification.
- copied in part, in any medium, provided that the ESCC document identification, comprising the ESCC symbol, document number and document issue, is removed.



europaean space agency  
agence spatiale européenne

Pages 1 to 17

## THERMISTORS

(THERMALLY SENSITIVE RESISTORS), NTC,

RANGE 2 000 TO 100 000 OHMS AT +25°C WITH

A TEMPERATURE RANGE OF -40 TO +160 °C

ESA/SCC Detail Specification No. 4006/014



space components  
coordination group

Issue/Rev.	Date	Approved by	
		SCCG Chairman	ESA Director General or his Deputy
Issue 1	October 1997		
Revision 'A'	June 1999		
Revision 'B'	June 2000		
Revision 'C'	February 2002		



**DOCUMENTATION CHANGE NOTICE**

Rev. Letter	Rev. Date	Reference	CHANGE Item	Approved DCR No.	
'A'	Jun. '99	P1. Cover page	: Page count amended to "17"	221513	
		P2. DCN		None	
		P4. T of C	: Appendix 'A' entry added	221513	
		P7. Table 1(b)	: No. 3, Maximum Rating deleted and "Note 3" added	221513	
			: No. 4, in Remarks, Note number amended to "4"	221513	
			: New Note 3 added and existing Note 3 renumbered as "4"	221513	
			P9. Para. 4.2.4	: Deviation (a) added	221513
			P12. Table 2	: No. 3, Conditions and Limit deleted and "Not applicable" added	221513
		: No. 4, Max. Limit amended to "40"		221513	
		P13. Table 5	: No. 1, Conditions deleted and "Note 1" added	221513	
			: No. 2, Conditions amended to "2.0" and Unit added	221513	
		P15. Table 6	: Note added	221513	
			: No. 2, entry made "Not applicable"	221513	
		New P17.	: No. 3, Max. Limit amended to "40"	221513	
			: Appendix 'A' added as Page 17	221513	
'B'	Jun. '00	P1. Cover page		None	
		P2. DCN		None	
		P10. Para. 4.5.3	: Detail Specification number corrected	23923	
'C'	Feb. '02	P1. Cover Page		None	
		P2. DCN		None	
		P6. Table 1(a)	: New Table 1(a) inserted	221662	
			: Deviations (b) and (c) added	221662	
		P9. Para. 4.2.4	: (a) amended	221662	
			: Paragraph deleted and subsequent paragraphs renumbered	221662	
		P12. Table 2	: No. 3 deleted	221662	
			: "Note 3" added to new No. 3	221662	
		Table 3	: No. 5 deleted	221662	
			: Note 2 deleted	221662	
P13. Table 5	: No. 1, "Note 2" added to Conditions	221662			
	: New Note 2 added	221662			

**SCC**

ESA/SCC Detail Specification

No. 4006/014

Rev. 'C'

PAGE 3

ISSUE 1

**TABLE OF CONTENTS**

	<u>Page</u>
<b>1. <u>GENERAL</u></b>	<b>5</b>
1.1 Scope	5
1.2 Component Type Variants	5
1.3 Maximum Ratings	5
1.4 Parameter Derating Information	5
1.5 Physical Dimensions	5
1.6 Functional Diagram	5
<b>2. <u>APPLICABLE DOCUMENTS</u></b>	<b>5</b>
<b>3. <u>TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS</u></b>	<b>5</b>
<b>4. <u>REQUIREMENTS</u></b>	<b>9</b>
4.1 General	9
4.2 Deviations from Generic Specification	9
4.2.1 Deviations from Special In-process Controls	9
4.2.2 Deviations from Final Production Tests	9
4.2.3 Deviations from Burn-in and Electrical Measurements	9
4.2.4 Deviations from Qualification Tests	9
4.2.5 Deviations from Lot Acceptance Tests	9
4.3 Mechanical Requirements	9
4.3.1 Dimension Check	9
4.3.2 Weight	9
4.3.3 Terminal Strength	9
4.4 Materials and Finishes	10
4.4.1 Case	10
4.4.2 Lead Material and Finish	10
4.5 Marking	10
4.5.1 General	10
4.5.2 The SCC Component Number	10
4.5.3 Traceability Information	10
4.6 Electrical Measurements	11
4.6.1 Electrical Measurements at Room Temperature	11
4.6.2 Electrical Measurements at High and Low Temperatures	11
4.6.3 Circuits for Electrical Measurements	11
4.7 Burn-in Tests	11
4.7.1 Parameter Drift Values	11
4.7.2 Conditions for Burn-in	11
4.7.3 Electrical Circuits for Burn-in	11
4.8 Environmental and Endurance Tests	14
4.8.1 Measurements and Inspections on Completion of Environmental Tests	14
4.8.2 Measurements and Inspections at Intermediate Points during Endurance Tests	14
4.8.3 Measurements and Inspections at on Completion of Endurance Tests	14
4.8.4 Conditions for Operating Life Tests	14
4.8.5 Electrical Circuits for Operating Life Tests	14

**TABLES**

	<u>Page</u>
1(a) Type Variants	6
1(b) Maximum Ratings	7
2 Electrical Measurements at Room Temperature - d.c. Parameters	12
3 Electrical Measurements at High and Low Temperatures	12
4 Parameter Drift Values	13
5 Conditions for Burn-in and Operating Life Tests	13
6 Measurements and Inspections on Completion of Environmental Tests and at Intermediate Points and on Completion of Endurance Testing	15

**FIGURES**

1 Parameter Derating Information	7
2 Physical Dimensions	8
3 Functional Diagram	8
4 Circuits for Electrical Measurements	12
5 Electrical Circuit for Burn-in and Operating Life Tests	13

**APPENDICES (Applicable to specific Manufacturers only)**

'A' Agreed Deviations for Betatherm (IRL)	17
---	----

**1. GENERAL****1.1 SCOPE**

This specification details the ratings, physical and electrical characteristics, test and inspection data for Thermistors, Thermally Sensitive Resistors, NTC, Range 2 000 to 100 000 Ohms at +25°C with a Temperature Range of -40 to +160 °C. It shall be read in conjunction with ESA/SCC Generic Specification No. 4006, the requirements of which are supplemented herein.

**1.2 COMPONENT TYPE VARIANTS**

Variants of the basic type thermistors specified herein, which are also covered by this specification, are given in Table 1(a).

**1.3 MAXIMUM RATINGS**

The maximum ratings, which shall not be exceeded at any time during use or storage, applicable to the thermistors specified herein, are as scheduled in Table 1(b).

**1.4 PARAMETER DERATING INFORMATION (FIGURE 1)**

Not applicable.

**1.5 PHYSICAL DIMENSIONS**

The physical dimensions of the thermistors specified herein are shown in Figure 2.

**1.6 FUNCTIONAL DIAGRAM**

The functional diagram for the thermistors specified herein is shown in Figure 3.

**2. APPLICABLE DOCUMENTS**

The following documents form part of this specification and shall be read in conjunction with it:-

(a) ESA/SCC Generic Specification No. 4006, Thermistors (Resistors, Thermally Sensitive).


(b) MIL-STD-202, Test Methods for Electronic and Electrical Component Parts.

**3. TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS**

For the purpose of this specification, the terms, definitions, abbreviations, symbols and units specified in ESA/SCC Basic Specification No. 21300 shall apply. In addition, the following symbols are used:-

NTC = Negative Temperature Coefficient.

R<sub>Z</sub> = Zero Power Resistance.



ES/SCC Detail Specification

No. 4006/014

PAGE 6

ISSUE 1

**TABLE 1(e) - TYPE VARIANTS**

(1) VARIANT	(2) BASED ON TYPE	(3) R <sub>Z</sub> (Note 1)	RESISTANCE/TEMPERATURE CHARACTERISTICS (NOTES 2 AND 3)										(4)	
			-40°C	-20°C	0°C	+25°C	+50°C	+70°C	+100°C	+125°C	+140°C	+160°C		
01	G2K7D110	NOM. (Ω)	43 362	14 658	5 650	2 000	815	432	187.4	102	-	-	-	-
		TOL. (±%)	2.90	2.54	1.57	1.34	1.17	1.05	0.90	1.13	-	-	-	-
02	G4K7D108	NOM. (Ω)	-	29 316	11 300	4 000	1 630	864	374.8	204	-	-	-	-
		TOL. (±%)	-	2.54	1.57	1.34	1.17	1.05	0.90	1.13	-	-	-	-
03	G4K7D114	NOM. (Ω)	86 724	29 316	11 300	4 000	1 630	864	-	-	-	-	-	-
		TOL. (±%)	2.90	2.54	1.57	1.34	1.17	1.05	-	-	-	-	-	-
04	G15K4D112	NOM. (Ω)	-	-	44 235	15 000	5 840	2 985	1 226	639	447	287.7	-	-
		TOL. (±%)	-	-	1.62	1.41	1.24	1.12	0.97	1.23	1.15	1.06	-	-
05	G100K6D116	NOM. (Ω)	-	-	-	100 000 (4)	-	-	5 574	2 642	1 756	1 059	-	-
		TOL. (±%)	-	-	-	-	-	-	1.11	1.41	1.32	1.21	-	-

**NOTES**

- For test purposes, when zero power is dissipated and the ambient temperature is held as specified, the value is referred to as R<sub>Z</sub> (Zero Power Resistance).
- Temperature Tolerance ranges are as follows:-  
 Variants 01, 02, 03: ±0.5°C from -40°C to -1°C and +101°C to +125°C.  
 ±0.35°C from 0°C to +100°C.  
 Variant 04: ±0.5°C from +101°C to +160°C.  
 ±0.35°C from 0°C to +100°C.  
 Variant 05: ±0.5°C from +101°C to +160°C.  
 ±0.35°C from 0°C to +100°C.
- The reference resistance is specified at +25°C.
- For reference purposes only.





**TABLE 1(b) - MAXIMUM RATINGS**

No.	CHARACTERISTICS	SYMBOL	MAXIMUM RATINGS	UNIT	REMARKS
1	Power Dissipation	$P_D$	2.0	mW	Note 1
2	Operating Temperature Range	$T_{op}$	Note 2	°C	
3	Storage Temperature Range	$T_{stg}$	Note 3	°C	
4	Soldering Temperature	$T_{sol}$	+ 245	°C	Note 4

**NOTES**


1. Never to be exceeded in the temperature measurement mode. The thermistors specified herein shall not be used in the self-heat mode.
2. See Column 4 of Table 1(a).
3. - 65°C to the Maximum Operating Temperature specified in Column 4 of Table 1(a).
4. Duration 10 seconds maximum at a distance of not less than 10mm from the device body and the same lead shall not be resoldered until 3 minutes have elapsed.

**FIGURE 1 - PARAMETER DERATING INFORMATION**

Not applicable.



**FIGURE 2 - PHYSICAL DIMENSIONS**



SYMBOL	MILLIMETRES	
	MIN.	MAX.
A	280.00	330.00
B	6.10	6.60
C	-	2.80
D	-	9.80
E	0.33	0.48
F	-	50.00
G	50.00	80.00

**NOTES**

1. The leads shall not be bent, or the means of fastening them cause bending in any direction from the place of the thermistor fastening disc within a distance of 15mm from the centre of the thermistor.

**FIGURE 3 - FUNCTIONAL DIAGRAM**





#### 4. REQUIREMENTS

##### 4.1 GENERAL

The complete requirements for procurement of the thermistors specified herein are stated in this specification and ESA/SCC Generic Specification No. 4006 for Thermistors (Resistors, Thermally Sensitive). Deviations from the Generic Specification, applicable to this specification only, are listed in Para. 4.2.

Deviations from the applicable Generic Specification and this Detail Specification, formally agreed with specific Manufacturers on the basis that the alternative requirements are equivalent to the ESA/SCC requirements and do not affect the components' reliability, are listed in the appendices attached to this specification.

##### 4.2 DEVIATIONS FROM GENERIC SPECIFICATION

###### 4.2.1 Deviations from Special In-process Controls

None.

###### 4.2.2 Deviations from Final Production Tests (Chart II)

None.

###### 4.2.3 Deviations from Burn-in and Electrical Measurements (Chart III)

None.

###### 4.2.4 Deviations from Qualification Tests (Chart IV)

(a) Para. 9.3.1.2, Dissipation Constant: Not applicable.

(b) Para. 9.15, Short Time Load: Not applicable.

(c) Para. 9.17, High Temperature Storage: Not applicable.

###### 4.2.5 Deviations from Lot Acceptance Tests (Chart V)

None.

##### 4.3 MECHANICAL REQUIREMENTS

###### 4.3.1 Dimension Check

The dimensions of the thermistors specified herein shall be verified in accordance with the requirements set out in Para. 9.4 of ESA/SCC Generic Specification No. 4006 and they shall conform to those shown in Figure 2 of this specification.

###### 4.3.2 Weight

The maximum weight of the thermistors specified herein shall be 4.0 grammes.

###### 4.3.3 Terminal Strength

The requirements for terminal strength testing are specified in Para. 9.13 of ESA/SCC Generic Specification No. 4006. The test conditions shall be as follows:-

Applied Force: 4.45(+ 1.1 - 0)N.

Duration: 5 seconds.



4.4 MATERIALS AND FINISHES

The materials and finishes shall be as specified herein. Where a definite material is not specified, a material which will enable the thermistors specified herein to meet the performance requirements of this specification shall be used. Acceptance or approval of any constituent material does not guarantee acceptance of the finished product.

4.4.1 Case

The housing shall be aluminium filled with a black epoxy encapsulant.

4.4.2 Lead Material and Finish

The lead material shall be in accordance with ESA/SCC Detail Specification No. 3901/012 Variant 04. One lead shall carry an identification sleeve which shall carry all part marking specified in Para. 4.5.

4.5 MARKING

4.5.1 General


The marking of all components delivered to this specification shall be in accordance with the requirements of ESA/SCC Basic Specification No. 21700 and the following paragraphs. When the component is too small to accommodate all of the marking specified, as much as space permits shall be marked and the marking information, in full, shall accompany the component in its primary package.

The information to be marked and the order of precedence, shall be as follows:-

- (a) The ESA Symbol, for qualified components only.
- (b) The SCC Component Number.
- (c) Traceability Information.

4.5.2 The SCC Component Number

The SCC Component Number shall be constituted and marked as follows:



4.5.3 Traceability Information

Each component shall be marked in respect of traceability information in accordance with the requirements of ESA/SCC Basic Specification No. 21700.



#### 4.6 ELECTRICAL MEASUREMENTS

##### 4.6.1 Electrical Measurements at Room Temperature

The parameters to be measured at room temperature are scheduled in Table 2. Unless otherwise specified, the measurements shall be performed at  $T_{amb} = +25 \pm 0.05$  °C.

##### 4.6.2 Electrical Measurements at High and Low Temperatures

The parameters to be measured at high and low temperatures are scheduled in Table 3.

##### 4.6.3 Circuits for Electrical Measurements (Figure 4)

Not applicable.

#### 4.7 BURN-IN TESTS

##### 4.7.1 Parameter Drift Values

The parameter drift values applicable to burn-in are specified in Table 4 of this specification. Unless otherwise stated, measurements shall be performed at  $T_{amb} = +25 \pm 0.05$  °C. The parameter drift values ( $\Delta$ ) applicable to the parameters scheduled, shall not be exceeded. In addition to these drift value requirements for a given parameter, the appropriate limit value specified in Table 2 shall not be exceeded.

##### 4.7.2 Conditions for Burn-in

The requirements for burn-in are specified in Section 7 of ESA/SCC Generic Specification No. 4006. The conditions for burn-in shall be as specified in Table 5 of this specification.

##### 4.7.3 Electrical Circuits for Burn-in (Figure 5)

Not applicable.



**TABLE 2 - ELECTRICAL MEASUREMENTS AT ROOM TEMPERATURE - d.c. PARAMETERS**

No.	CHARACTERISTICS	SYMBOL	ESA/SCC 4006 TEST METHOD AND CONDITION	LIMITS		UNIT
				MIN.	MAX.	
1	Zero Power Resistance	R <sub>Z</sub>	Para. 9.3.1.1 T <sub>amb</sub> = +25°C	Note 1		Ω
2	Insulation Resistance	R <sub>i</sub>	Para. 9.3.1.4 Note 2	100	-	MΩ
4	Thermal Time Constant	KH	Para. 9.3.1.3 In Still Air Note 3	-	40	sec.

**NOTES**

1. See Column 4 of Table 1(a) for resistance values.
2. If more than 20 devices have to be measured, the test shall be performed on a sample basis in accordance with Level II, Table IIA, AQL = 1.0 of MIL-STD-105.
3. Test to be performed on 10 samples during Chart II only.

**TABLE 3 - ELECTRICAL MEASUREMENTS AT HIGH AND LOW TEMPERATURES**

No.	CHARACTERISTICS	SYMBOL	ESA/SCC 4006 TEST METHOD AND CONDITION	LIMITS		UNIT
				MIN.	MAX.	
1	Zero Power Resistance	R <sub>Z</sub>	Para. 9.3.1.1 At each specified temperature, over operating range	Note 1		Ω

**NOTES**

1. See Column 4 of Table 1(a) for resistance values.

**FIGURE 4 - CIRCUITS FOR ELECTRICAL MEASUREMENTS**

Not applicable.

**TABLE 4 - PARAMETER DRIFT VALUES**

No.	CHARACTERISTICS	SYMBOL	SPEC. AND/OR TEST METHOD	TEST CONDITIONS	CHANGE LIMITS ( $\Delta$ )	UNIT
1	Zero Power Resistance Change	$\frac{\Delta R_z}{R_z}$	As per Table 2	As per Table 2	$\pm 0.2$	%

**TABLE 5 - CONDITIONS FOR BURN-IN AND OPERATING LIFE TESTS**

No.	CHARACTERISTICS	SYMBOL	CONDITION	UNIT
1	Ambient Temperature	$T_{amb}$	Note 1 Note 2	$^{\circ}\text{C}$
2	Power Dissipation	$P_D$	2.0	mW

**NOTES**

1. Maximum Operating Temperature specified in Column 4 of Table 1(a).
2. The Temperature Tolerance = (+0-3)  $^{\circ}\text{C}$ .

**FIGURE 5 - ELECTRICAL CIRCUIT FOR BURN-IN AND OPERATING LIFE TESTS**

Not applicable.



- 4.8 ENVIRONMENTAL AND ENDURANCE TESTS (CHARTS IV AND V OF ESA/SCC GENERIC SPECIFICATION No. 4006)
- 4.8.1 Measurements and Inspections on Completion of Environmental Tests  
The parameters to be measured and inspections to be performed on completion of environmental tests are scheduled in Table 2. Unless otherwise stated, the measurements shall be performed at  $T_{amb} = +25 \pm 0.05 \text{ }^{\circ}\text{C}$ .
- 4.8.2 Measurements and Inspections at Intermediate Points during Endurance Tests  
The parameters to be measured and inspections to be performed at intermediate points during endurance tests are scheduled in Table 6. Unless otherwise stated, the measurements shall be performed at  $T_{amb} = +25 \pm 0.05 \text{ }^{\circ}\text{C}$ .
- 4.8.3 Measurements and Inspections on Completion of Endurance Tests  
The parameters to be measured and inspections to be performed on completion of endurance tests are scheduled in Table 6. Unless otherwise stated, the measurements shall be performed at  $T_{amb} = +25 \pm 0.05 \text{ }^{\circ}\text{C}$ .
- 4.8.4 Conditions for Operating Life Tests (Part of Endurance Testing)  
The requirements for operating life testing are specified in Section 9 of ESA/SCC Generic Specification No. 4006. The conditions for operating life testing shall be as specified in Table 5 for the burn-in test.
- 4.8.5 Electrical Circuits for Operating Life Tests  
Not applicable.





**TABLE 6 - MEASUREMENTS AND INSPECTIONS ON COMPLETION OF ENVIRONMENTAL TESTS AND AT INTERMEDIATE POINTS AND ON COMPLETION OF ENDURANCE TESTING**

No.	ESA/SCC GENERIC SPEC. No. 4006		MEASUREMENTS AND INSPECTIONS		SYMBOL	LIMITS		UNIT
	ENVIRONMENTAL AND ENDURANCE TESTS (1)	TEST METHOD AND CONDITIONS	IDENTIFICATION	CONDITIONS		MIN.	MAX.	
01	Thermal Shock	Para. 9.2	-	-	-	-	-	-
02	Dissipation Constant	Para. 9.3.1.2 and Para. 4.2.4 of this spec.	<b>Initial Measurements</b> Zero Power Resistance <b>Final Measurements</b> Dissipation Constant	Not applicable  Not applicable	R <sub>Z</sub>  K <sub>DISS</sub>			
03	Thermal Time Constant	Para. 9.3.1.3 In Still Air	<b>Initial Measurements</b> Zero Power Resistance <b>Final Measurements</b> Thermal Time Constant	Para. 9.3.1.3(c)  Para. 9.3.1.3(f)	R <sub>Z</sub>  KH	Record Values		Ω  sec.
04	External Visual Inspection	Para. 9.5	ESA/SCC 20500	-	-	-	-	-
05	Shock (Specified Pulse)	Para. 9.7	<b>Initial Measurements</b> Zero Power Resistance <b>During Shock</b> Intermittent Contact  <b>After Shock</b> Zero Power Resistance Change Visual Examination	Table 2 Item 1  No Open or Short Circuiting  Table 2 Item 1  No evidence of damage	R <sub>Z</sub>  -  ΔR <sub>Z</sub> /R <sub>Z</sub>  -	Table 2 Item 1  -  -2.0  -	+2.0  -	%  -
06	Vibration	Para. 9.8	<b>Initial Measurements</b> Zero Power Resistance <b>During Vibration</b> Intermittent Contact  <b>After Vibration</b> Zero Power Resistance Change Visual Examination	Table 2 Item 1  No Open or Short Circuiting  Table 2 Item 1  No evidence of damage	R <sub>Z</sub>  -  ΔR <sub>Z</sub> /R <sub>Z</sub>  -	Table 2 Item 1  -  -2.0  -	+2.0  -	%  -
07	Immersion	Para. 9.9	Visual Examination	No evidence of damage	-	-	-	-
08	Dielectric Withstanding Voltage	Para. 9.10	<b>During Test</b> Visual Examination  <b>After Test</b> Visual Examination	No evidence of breakdown or flashover  No evidence of damage, arcing or breakdown	-  -	-  -	-  -	-  -
09	Resistance to Soldering Heat	Para. 9.11	<b>After Test</b>  Zero Power Resistance Visual Examination	After a recovery period of 24 ± 4 hrs Table 2 Item 1 No evidence of damage	R <sub>Z</sub>  -	Table 2 Item 1  -	-  -	-  -
10	Moisture Resistance	Para. 9.12	<b>Initial Measurements</b>  Zero Power Resistance <b>Final Measurements</b>  Zero Power Resistance Change Insulation Resistance	Not less than 1.5 hrs after removal from drying oven Table 2 Item 1 Within 24 hrs of removal from 1.5 to 3.5 hr conditioning Table 2 Item 1  Table 2 Item 2	R <sub>Z</sub>  ΔR <sub>Z</sub> /R <sub>Z</sub>  R <sub>i</sub>	Table 2 Item 1  -2.0  100	+2.0  -	%  MΩ

**NOTES**

1. The tests in this Table refer to either Chart IV or V and shall be used as applicable.



**SCC**

ESA/SCC Detail Specification

No. 4006/014

PAGE 16

ISSUE 1

**TABLE 6 - MEASUREMENTS AND INSPECTIONS ON COMPLETION OF ENVIRONMENTAL TESTS AND AT INTERMEDIATE POINTS AND ON COMPLETION OF ENDURANCE TESTING (CONT'D)**

No.	ESA/SCC GENERIC SPEC. No. 4006		MEASUREMENTS AND INSPECTIONS		SYMBOL	LIMITS		UNIT
	ENVIRONMENTAL AND ENDURANCE TESTS (1)	TEST METHOD AND CONDITIONS	IDENTIFICATION	CONDITIONS		MIN.	MAX.	
11	Terminal Strength	Para. 9.13	<b>Initial Measurements</b> Zero Power Resistance <b>Final Measurements</b> Zero Power Resistance Change Visual Examination	Table 2 Item 1 Table 2 Item 1 No evidence of damage	$R_z$ $\Delta R_z/R_z$ -	Table 2 Item 1 -2.0 -	+2.0 +	% -
12	Operating Life	Para. 9.14	<b>Initial Measurements</b> Zero Power Resistance <b>Intermediate Measurements</b> Zero Power Resistance Change Insulation Resistance <b>Final Measurements</b> Zero Power Resistance Change Insulation Resistance	Table 2 Item 1 Table 2 Item 1 Table 2 Item 2 Table 2 Item 1 Table 2 Item 2	$R_z$ $\Delta R_z/R_z$ $R_i$ $\Delta R_z/R_z$ $R_i$	Table 2 Item 1 -1.0 100 -1.0 100	+1.0 +	% M $\Omega$ %
13	Short Time Load	Para. 9.15	Zero Power Resistance Visual Examination	Table 2 Item 1 No evidence of arcing, burning or charring	$R_z$ -	Table 2 Item 1 -	-	-
14	Low Temperature Storage	Para. 9.16	<b>Initial Measurements</b> Zero Power Resistance <b>Final Measurements</b> Zero Power Resistance Change Visual Examination	Table 2 Item 1 Table 2 Item 1 No evidence of damage	$R_z$ $\Delta R_z/R_z$ -	Table 2 Item 1 -2.0 -	+2.0 +	% -
15	High Temperature Storage	Para. 9.17	<b>Initial Measurements</b> Zero Power Resistance <b>Intermediate Measurements</b> Zero Power Resistance Change Insulation Resistance <b>Final Measurements</b> Zero Power Resistance Change Insulation Resistance	Table 2 Item 1 Table 2 Item 1 Table 2 Item 2 Table 2 Item 1 Table 2 Item 2	$R_z$ $\Delta R_z/R_z$ $R_i$ $\Delta R_z/R_z$ $R_i$	Table 2 Item 1 -1.0 100 -1.0 100	+1.0 +	% M $\Omega$ %
16	Solderability	Para. 9.18	-	-	-	-	-	-
17	Permanance of Marking	Para. 9.20	ESA/SCC 24800	-	-	-	-	-

**NOTES**

1. The tests in this Table refer to either Chart IV or V and shall be used as applicable.



**SCC**

ESA/SCC Detail Specification  
No. 4006/014

Rev. 'A'

PAGE 17

ISSUE 1

**APPENDIX 'A'**

**AGREED DEVIATIONS FOR BETATHERM (IRL)**

Page 1 of 1

ITEMS AFFECTED	DESCRIPTION OF DEVIATION
Para. 4.2.4	(a) Para. 9.2, Thermal Shock: May be performed as follows: "Test Condition 'C' except that the maximum temperature shall be the maximum operating temperature specified in Column 4 of Table 1(a) of this specification."  (b) Para. 9.17, High Temperature Storage: May be omitted.
Para. 4.2.5	(a) Para. 9.2, Thermal Shock: May be performed as follows: "Test Condition 'C' except that the maximum temperature shall be the maximum operating temperature specified in Column 4 of Table 1(a) of this specification."