



Page 1 to 59

**CRYSTAL UNITS IN METAL HOLDER,  
BASED ON TYPE T1507,  
FREQUENCY RANGE 2.5 - 50MHZ**

**ESCC Detail Specification No. 3501/009**

**(Follow-up specification to ESCC Detail Specification Nos. 3501/002)**

**ISSUE 6  
September 2011**



Document Custodian: European Space Agency - see <https://escies.org>

	ESCC Detail Specification No. 3501/009		PAGE ii ISSUE 6
--	---	--	--------------------

### **LEGAL DISCLAIMER AND COPYRIGHT**

European Space Agency, Copyright © 2011. All rights reserved.

The European Space Agency disclaims any liability or responsibility, to any person or entity, with respect to any loss or damage caused, or alleged to be caused, directly or indirectly by the use and application of this ESCC publication.

This publication, without the prior permission of the European Space Agency and provided that it is not used for a commercial purpose, may be:

- copied in whole, in any medium, without alteration or modification.
- copied in part, in any medium, provided that the ESCC document identification, comprising the ESCC symbol, document number and document issue, is removed.

**DOCUMENTATION CHANGE NOTICE**

DCR No.	CHANGE DESCRIPTION
636	Specification upissued to incorporate editorial and technical changes per DCR.

	<p style="text-align: center;">ESCC Detail Specification No. 3501/009</p>		<p>PAGE 3 ISSUE 6</p>
---	---	--	---------------------------

## TABLE OF CONTENTS

		<u>Page</u>
<b>1.</b>	<b><u>GENERAL</u></b>	<b>5</b>
1.1	Scope	5
1.2	Component Type Variants	5
1.3	Maximum Ratings	5
1.4	Physical Dimensions	5
1.5	Functional Diagram	5
<b>2.</b>	<b><u>APPLICABLE DOCUMENTS</u></b>	<b>14</b>
<b>3.</b>	<b><u>TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS</u></b>	<b>14</b>
<b>4.</b>	<b><u>REQUIREMENTS</u></b>	<b>14</b>
4.1	General	14
4.2	Deviations from Generic Specification	14
4.2.1	Deviations from Special In-process Controls	14
4.2.2	Deviations from Final Production Tests	14
4.2.3	Deviations from Burn-in Tests	14
4.2.4	Deviations from Qualification Tests	14
4.2.5	Deviations from Lot Acceptance Tests	14
4.3	Mechanical Requirements	15
4.3.1	Dimension Check	15
4.3.2	Weight	15
4.3.3	Robustness of Terminations	15
4.4	Materials and Finishes	15
4.4.1	Case	15
4.4.2	Lead Material and Finish	15
4.5	Marking	15
4.5.1	General	15
4.5.2	The ESCC Component Number	15
4.5.3	Characteristics	16
4.5.4	Traceability Information	16
4.5.5	Manufacturer's Name, Symbol or Code	16
4.6	Electrical Measurements	16
4.6.1	Electrical Measurements at Reference Temperature	16
4.6.2	Electrical Measurements at High and Low Temperatures	16
4.6.3	Circuits for Electrical Measurements	16
4.7	Burn-in Tests	16
4.7.1	Parameter Drift Values	16
4.7.2	Conditions for Burn-in	16
4.7.3	Electrical Circuits for Burn-in	16
4.8	Environmental and Endurance Tests	19
4.8.1	Measurements and Inspections on Completion of Environmental Tests	19
4.8.2	Measurements and Inspections at Intermediate Points and on Completion of Endurance Tests	19
4.8.3	Conditions for Operating Life Test	19

<b><u>TABLES</u></b>	<u>Page</u>
1(a) Type Variant Summary	6
Type Variant Detailed Information	23
1(b) Maximum Ratings	9
1(c) Format for Individual Tables 1(a)	10
2 Electrical Measurements at Reference Temperature	17
3 Electrical Measurements at High and Low Temperatures	18
4 Parameter Drift Values	18
5 Conditions for Burn-in and Life Test	18
6 Measurements and Inspections on Completion of Environmental Tests and at Intermediate Points and on Completion of Endurance Testing	20

<b><u>FIGURES</u></b>	
1 Parameter Derating Information	N/A
2 Physical Dimensions	13
3 Functional Diagram	13
4 Circuits for Electrical Measurements	N/A
5 Electrical Circuit for Burn-in and Life Test	N/A

**APPENDICES (Applicable to specific Manufacturers only)**

A RAKON (F)	58
B KVG Quartz Crystal Technology GmbH (D)	59

	<p style="text-align: center;">ESCC Detail Specification No. 3501/009</p>		<p>PAGE 5 ISSUE 6</p>
---	---	--	---------------------------

## 1. GENERAL

### 1.1 SCOPE

This specification details the values, physical and electrical characteristics, test and inspection data for Crystal Units in Metal Holder, based on Type T1507, Frequency Range 2.5 - 50MHz.

It shall be read in conjunction with ESCC Generic Specification No. 3501, the requirements for which are supplemented herein.

This is a follow-up specification to ESCC Detail Specification No. 3501/002. ESCC 3501/002 should also be consulted by:-

- (a) Users seeking information concerning the availability of variants additional to those listed in this specification.
- (b) Manufacturers before requesting the introduction of a new variant in accordance with the requirements of Para. 1.2 of this specification.

### 1.2 COMPONENT TYPE VARIANTS

A list of the type variants of the crystal units specified herein, which are also covered by this specification, is given in "Table 1(a) - Type Variant Summary".

For each type variant, the full electrical and physical characteristics are given in individual Tables 1(a) - "Type Variant Detailed Information" at the end of this specification.

The contents of the individual Tables 1(a) shall be as shown in Table 1(c) and the characteristics therein listed shall relate to the design parameters of the individual crystal units, optimised for the intended application.

The specific characteristics shall be negotiated between the Manufacturer and the Orderer. The Manufacturer shall then apply to the ESCC Secretariat for a type variant number for each individual crystal unit concerned, by sending a finalised Table 1(a) which shall also be copied to the ESCC Executive.

### 1.3 MAXIMUM RATINGS

The maximum ratings, which shall not be exceeded at any time during use or storage, applicable to the crystal units specified herein, are as scheduled in Table 1(b).

### 1.4 PHYSICAL DIMENSIONS

The physical dimensions of the crystal units specified herein are shown in Figure 2.

### 1.5 FUNCTIONAL DIAGRAM

The functional diagram showing lead identification of the crystal units specified herein is shown in Figure 3.



**TABLE 1(a) - TYPE VARIANT SUMMARY**

**N.B.** For additional information concerning type variants, see Para. 1.1.

Variant	Resonance Frequency (MHz)	Load Capacitance (C <sub>L</sub> pF)	Reference Temp. (T <sub>0</sub> °C)	Operating Temp. Range (T <sub>op</sub> °C)	Intended Application	Lead Finish
01	4.194304	30	+30	-10 to +80	-	2
02	8.192	50	+25	-25 to +80	-	3 or 4
03	26.0	∞	+25	-25 to +80	-	2
04	7.198	30	+25	-55 to +105	-	2
05	5.0	30	+25	-40 to +80	-	2
06	18.0	30	+25	-45 to +80	-	2
07	10.0	30	+25	-55 to +125	-	2
08	10.0	30	+25	-55 to +100	XO	2
09	50.0	12	+25	-20 to +80	VCXO	2
10	4.0	30	+25	-40 to +80	XO	2
11	10.0	30	+25	-55 to +100	XO	2
12	8.0	∞	+25	-20 to +80	XO	2
13	10.0	∞	+25	-20 to +80	TCXO	2
14	6.4	30	+25	-45 to +80	XO	4
15	12.605	∞	+25	-20 to +60	TCXO	2
16	7.0	30	+25	-35 to +70	TCXO	2
17	12.665	∞	+25	-20 to +80	TCXO	2
18	5.760	30	+25	-40 to +90	XO	2
19	8.602893	30	+60	-40 to +85	XO	2
20	15.104893	∞	+25	-20 to +80	XO	2
21	20.0	30	+25	-30 to +70	XO	2
22	13.0	30	+25	-40 to +80	XO	2
23	10.0	30	+25	-55 to +100	XO	2
24	5.242880	30	+60	-40 to +85	XO	2
25	5.625	30	+25	-40 to +85	XO	2
26	11.250	30	+25	-50 to +100	XO	2
27	8.0	∞	+25	-30 to +70	XO	2
28	3.494400	35	+25	-55 to +100	XO	2
29	3.832	30	+25	-40 to +80	XO	2
30	3.072	30	+25	-40 to +80	XO	2
31	4.0	30	+25	-40 to +80	XO	2
32	16.0	30	+25	-55 to +125	XO	2
33	11.059200	30	+25	-55 to +100	XO	2
34	12.007125	30	+25	-40 to +90	TCXO	2
35	11.059300	50	+25	-55 to +100	XO	2
36						

**NOTES:** See Page 8.



**TABLE 1(a) - TYPE VARIANT SUMMARY CONTINUED**

Variant	Resonance Frequency (MHz)	Load Capacitance (C <sub>L</sub> pF)	Reference Temp. (T <sub>o</sub> °C)	Operating Temp. Range (T <sub>op</sub> °C)	Intended Application	Lead Finish
37						
38						
39						
40						
41						
42						
43						
44						
45						
46						
47						
48						
49						
50						
51						
52						
53						
54						
55						
56						
57						
58						
59						
60						
61						
62						
63						
64						
65						
66						
67						
68						
69						
70						
71						
72						

**NOTES:** See Page 8.



**TABLE 1(a) - TYPE VARIANT SUMMARY CONTINUED**

Variant	Resonance Frequency (MHz)	Load Capacitance (C <sub>L</sub> pF)	Reference Temp. (T <sub>0</sub> °C)	Operating Temp. Range (T <sub>op</sub> °C)	Intended Applicat.	Lead Finish
73						
74						
75						
76						
77						
78						
79						
80						
81						
82						
83						
84						
85						
86						
87						
88						
89						
90						
91						
92						
93						
94						
95						
96						
97						
98						
99						

**NOTES**

1. Full electrical and physical characteristics are given in the individual Tables 1(a) at the end of this specification.

**TABLE 1(b) - MAXIMUM RATINGS**

No.	Characteristic	Symbol	Values	Unit	Remarks
1	Nominal Frequency Range	f	2.5 to 20	MHz	Note 1
2	Drive Level Range	P	0.01 to 0.2	mW	
3	Operating Temperature Range	T <sub>op</sub>	-	°C	Note 2
4	Storage Temperature Range	T <sub>stg</sub>	-65 to +125	°C	Note 3
5	Soldering Temperature	T <sub>sol</sub>	+260	°C	Note 4

**NOTES**

1.

Fundamental and Overtone Order	Approx. Frequency Range (MHz)
Fundamental	2.5 to 20
3	10 to 30
5	15 to 50

2. See Table 1(a).

3. The duration at maximum storage temperature shall not exceed 16 hours.

4. Duration 10 seconds maximum at a distance of not less than 3.0mm from the device body and the same lead shall not be resoldered until 3 minutes have elapsed.


**TABLE 1(c) - FORMAT FOR INDIVIDUAL TABLES 1(a)**

**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. \_\_\_\_\_

No.	Characteristic	Symbol	Limits		Unit	Remarks
			Min.	Max		
1	Resonance Frequency	$f_r$ or $f_L$			MHz	Note 1
2	Reference Temperature	$T_o$			°C	Note 2
3	Overtone Order	-				
4	Load Capacitance	$C_L$			pF	Note 3
5	Rated Drive Level	$P_o$			mW	Note 4
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$			10 <sup>-6</sup>	At $T_o$ °C Note 5
7	Resonance Resistance	$R_r$ or $R_L$			$\Omega$	At $T_o$ °C Note 6
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$			10 <sup>-9</sup>	From frequency measured at $T_o$ °C Note 7
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$			%	From resistance measured at $T_o$ °C Note 7
10	Operating Temperature Range	$T_{op}$			°C	
11	Frequency variation with Drive Level	$\frac{\Delta f}{f}$			10 <sup>-6</sup>	From $P_{S1} =$ mW to $P_{S2} =$ mW Note 8
12	Resistance variation with Drive Level	$\frac{\Delta R}{R}$			%	From $P_{S1} =$ mW to $P_{S2} =$ mW Note 8
13	Motional Inductance	$L_1$			mH	Notes 9 and 10
14	Motional Capacitance	$C_1$			fF	Note 9
15	Static Capacitance	$C_o$			pF	Note 9
16	Q Factor	Q			-	Notes 9 and 11
17	Ratio of unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$				In the frequency range: f - kHz to f + kHz
18	Ageing	$\frac{\Delta f}{f}$			10 <sup>-6</sup>	Note 13
19	Lead Finish	-			-	
20	Intended Application					Note 15

**NOTES:** See Pages 11 and 12.

	<p style="text-align: center;">ESCC Detail Specification No. 3501/009</p>		<p>PAGE 11 ISSUE 6</p>
---	---	--	----------------------------

**NOTES TO TABLE 1(c)**

1. (a) If  $C_L$  is not specified, Symbol and measurement shall be  $f_r$ .  
(b) If  $C_L$  is specified, Symbol and measurement shall be  $f_L$ .
2. Reference Temperature  $T_o$ 
  - (a) For a crystal unit functioning in a non-controlled temperature environment, the reference temperature is normally  $+25 \pm 2$  °C.
  - (b) For a crystal unit functioning in a controlled temperature environment, the reference temperature shall normally be the mid-point of the temperature range of the controlled environment.
3. Load Capacitance  $C_L$ 
  - (a) When a crystal unit must function at its series resonance frequency,  $C_L$  shall be infinite.
  - (b) When a crystal must function with a load capacitance, the  $C_L$  value shall be specified. The standard values of load capacitance are as follows:
    - Fundamental Frequency Operation: 20pF, 30pF, 50pF and 100pF.
    - Overtone Operation: 8pF, 12pF, 15pF, 20pF and 30pF.

**N.B**

The tolerance on the load capacitance shall be that value which results in a frequency change not exceeding 10% of the frequency tolerance at  $T_o$  or 1% of the nominal load capacitance, whichever is smaller.

4. Rated Drive Level  $P_o$ 

The rated drive level shall be selected from the standard drive levels specified below:

  - Preferred values: 2mW, 1mW, 0.5mW, 0.2mW, 0.1mW, 0.05mW, 0.02mW, 0.01mW, 0.001mW or 0.0001mW at  $\pm 20\%$ .
  - Non-preferred values: 10mW, 5mW and 4mW all at  $\pm 20\%$ .
5. Frequency Adjustment Tolerance
  - (a) When a crystal must function at its series resonance frequency, the standard value of the adjustment tolerance shall be  $\pm 10 \times 10^{-6}$ .
  - (b) When a crystal has to function with a load capacitance, the standard value of the adjustment tolerance shall also be  $\pm 10 \times 10^{-6}$ . However, if the load capacitance is adjustable, it is preferable to specify that the nominal frequency be obtained with a load capacitance value between the minimum and maximum value when the crystal is functioning in its fundamental mode.
6. Resonance Resistance
  - (a) Generally, the maximum value only is specified.

(b)  $R_L$  may be calculated by  $R_L = R_r \left( 1 + \frac{C_o}{C_L} \right)^2$ .

	<p style="text-align: center;">ESCC Detail Specification No. 3501/009</p>		<p>PAGE 12 ISSUE 6</p>
---	---	--	----------------------------

**NOTES TO TABLE 1(c) (Continued)**

7. Frequency and Resistance Variation with Temperature

These values shall be specified such that they are consistent with the operating temperature range.

8. Frequency and Resistance Variation with Drive Level

These limits and the Drive Level range ( $P_{S1}$  to  $P_{S2}$ ) shall be specified for very special crystals only (i.e. crystals used in very high stability oscillators).

9. Electrical Values

The electrical values shall be specified only when required for the correct functioning of the equipment in which the crystal is used.

10. Motional Inductance  $L_1$

Because the inductance value may be restricted by other chosen parameters, the Manufacturer shall propose the value of  $L_1$  in accordance with the Customer's requirements.

11. Q Factor

If 'R' and 'L' have been already specified, it will not be necessary to specify the minimum value of the 'Q' factor.

The maximum value of the 'Q' factor is never specified.

12. Ratio of Unwanted Response Resistance to Resonance Resistance

The standard minimum value is 2, but it is possible to obtain higher values.

The frequency range within which the minimum value of the ratio is required shall also be specified.

13. Ageing

Specify limits under appropriate column and ageing period under 'Remarks'.

14. Not applicable Items

For all items where limits are not specified, 'Not applicable' shall be entered in the Limits column.

15. Intended Application


For definitions of the selected symbols to be added, see ESCC Generic Specification No. 3501, Para. 3.

**FIGURE 1 - PARAMETER DERATING INFORMATION**

Not applicable.



**FIGURE 2 - PHYSICAL DIMENSIONS**

SYMBOL	MILLIMETRES		REMARKS
	MIN.	MAX.	
$\varnothing A$	-	15.75	
C	-	6.80	
H	6.90	7.40	Pitch 7.16mm
$\varnothing K$	0.40	0.48	
L	12.70	-	
P	-	0.90	Note 2
Q	-	0.95	Note 2




**NOTES**

1. Lead No. 5 is grounded to case.
2. The tag's position or presence is optional.



**FIGURE 3 - FUNCTIONAL DIAGRAM**



(BOTTOM VIEW)

**2. APPLICABLE DOCUMENTS**

The following documents form part of this specification and shall be read in conjunction with it:-

- (a) ESCC Generic Specification No. 3501 for Quartz Crystal Units.

**3. TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS**

For the purpose of this specification, the terms, definitions, abbreviations, symbols and units specified in ESCC Basic Specification No. 21300 shall apply. In addition, the following symbols are used:-

Resonance Frequency	= $f_r$
Load Resonance Frequency	= $f_L$
Reference Temperature	= $T_o$
Resonance Resistance	= $R_r$
Load Resonance Resistance	= $R_L$
Rated Drive Level	= $P_o$
Static Capacitance	= $C_o$
Load Capacitance	= $C_L$
Motional Capacitance	= $C_1$
Motional Inductance	= $L_1$
Response Resistance	= $R_p$
Response Impedance	= $ Z_p $
Insulation Resistance	= $R_i$

**4. REQUIREMENTS**

**4.1 GENERAL**

The complete requirements for procurement of the crystal units specified herein shall be as stated in this specification and ESCC Generic Specification No. 3501 for Quartz Crystal Units. Deviations from the Generic Specification applicable to this specification only, are detailed in Para. 4.2.

Deviations from the applicable Generic Specification and this Detail Specification, formally agreed with specific Manufacturers on the basis that the alternative requirements are equivalent to the ESCC requirements and do not affect the components` reliability, are listed in the appendices attached to this specification.

**4.2 DEVIATIONS FROM GENERIC SPECIFICATION**

**4.2.1 Deviations from Special In-process Controls**

None.

**4.2.2 Deviations from Final Production Tests (Chart II)**

None.

**4.2.3 Deviations from Burn-in Tests (Chart III)**

None.

**4.2.4 Deviations from Qualification Tests (Chart IV)**

None.

**4.2.5 Deviations from Lot Acceptance Tests (Chart V)**

None.

4.3 MECHANICAL REQUIREMENTS

4.3.1 Dimension Check

The dimensions of the crystal units specified herein shall be checked. They shall conform to those shown in Figure 2.

4.3.2 Weight

The maximum weight of the crystal units specified herein shall be 3.0 grammes.

4.3.3 Robustness of Terminations

The requirements for robustness of termination testing are specified in Section 9 of ESCC Generic Specification No. 3501.

4.4 MATERIALS AND FINISHES

The materials and finishes shall be as specified herein. Where a definite material is not specified, a material which will enable the crystal units specified herein to meet the performance requirements of this specification shall be used. Acceptance or approval of any constituent material does not guarantee acceptance of the finished product.

4.4.1 Case

4.4.1.1 Cap

Copper, nickel plated or nickel and gold plated.

4.4.1.2 Base

Kovar, nickel plated or nickel and gold plated.

4.4.2 Lead Material and Finish

The lead material shall be Type `D` with either Type `2` or Type `3 or 4` finish in accordance with the requirements of ESCC Basic Specification No. 23500. (See Tables 1(a) for Type Variants).

4.5 MARKING

4.5.1 General


The marking of all components delivered to this specification shall be in accordance with the requirements of ESCC Basic Specification No. 21700 and the following paragraphs. When the component is too small to accommodate all of the marking specified, as much as space permits shall be marked and the marking information, in full, shall accompany the component in its primary package.

The information to be marked and the order of precedence, shall be as follows:-

- (a) The ESCC Component Number.
- (b) Characteristics.
- (c) Traceability Information.

4.5.2 The ESCC Component Number

Each component shall bear the SCC Component Number, which shall be constituted and marked as follows:-





	<p style="text-align: center;">ESCC Detail Specification No. 3501/009</p>		<p>PAGE 16 ISSUE 6</p>
---	---	--	----------------------------

#### 4.5.3 Characteristics

The resonance frequency of the crystal units shall be clearly specified in MHz. Where necessary, it shall be specified to 6 decimal places.

#### 4.5.4 Traceability Information

Each component shall be marked in respect of traceability information in accordance with the requirements of ESCC Basic Specification No. 21700.

#### 4.5.5 Manufacturer`s Name, Symbol or Code

The Manufacturer`s marking shall be in accordance with the requirements of ESCC Basic Specification No. 21700.

### 4.6 ELECTRICAL MEASUREMENTS

#### 4.6.1 Electrical Measurements at Reference Temperature

The parameters to be measured in respect of electrical characteristics are scheduled in Table 2. The measurements shall be performed at the temperatures specified in the individual Tables 1(a), Item 2.

#### 4.6.2 Electrical Measurements at High and Low Temperatures

The parameters to be measured at high and low temperatures are scheduled in Table 3. These measurements shall only be performed if values are specified in Table 1(a) Items 8 and/or 9.

#### 4.6.3 Circuits for Electrical Measurements (Figure 4)

Not applicable.

### 4.7 BURN-IN TESTS

#### 4.7.1 Parameter Drift Values

The parameter drift values applicable to burn-in are specified in Table 4 of this specification. Unless otherwise stated, measurements shall be performed at  $T_{amb} = T_o \pm 2 \text{ }^\circ\text{C}$ . The parameter drift values (Delta) applicable to the scheduled parameters shall not be exceeded. In addition to these drift value requirements for a given parameter, the appropriate limit value specified in Table 2 shall not be exceeded.

#### 4.7.2 Conditions for Burn-in

The requirements for burn-in are specified in Section 7 of ESCC Generic Specification No. 3501. The conditions for burn-in shall be as specified in Table 5 of this specification.

#### 4.7.3 Electrical Circuits for Burn-in (Figure 5)

Not applicable.

**TABLE 2 - ELECTRICAL MEASUREMENTS AT REFERENCE TEMPERATURE**

No.	Characteristics	Symbol	ESCC 3501 Test Method	Limits	Unit
1	Resonance frequency at reference temperature and rated drive level - with C <sub>O</sub> - with C <sub>L</sub>	$f_r(T_o, P_o)$ $f_L(T_o, P_o)$	Para. 9.2.1.1	Table 1(a), Item 1 ± Item 6	MHz
2	Resonance resistance at reference temperature and rated drive level - with C <sub>O</sub> - with C <sub>L</sub>	$R_r(T_o, P_o)$ $R_L(T_o, P_o)$	Para. 9.2.1.1	Table 1(a), Item 7	Ω
3	Frequency variation with Drive Level	$\frac{\Delta f}{f}(T_o, \Delta P)$	Para. 9.2.1.1	Table 1(a), Item 11	10 <sup>-6</sup>
4	Resistance variation with Drive Level	$\frac{\Delta R}{R}(T_o, \Delta P)$	Para. 9.2.1.1	Table 1(a), Item 12	%
5	Motional Inductance	L <sub>1</sub>	Para. 9.2.1.3	Table 1(a), Item 13	mH
6	Static Capacitance	C <sub>o</sub>	Para. 9.2.1.4	Table 1(a), Item 15	pF
7	Unwanted response	$R_p/R$ or $I_{Zp}/R$	Para. 9.2.1.5	Table 1(a), Item 17	-
8	Insulation Resistance	R <sub>i</sub>	Para. 9.2.1.6	500 Min.	MΩ

**TABLE 3 - ELECTRICAL MEASUREMENTS AT HIGH AND LOW TEMPERATURES**

No.	Characteristics	Symbol	ESCC 3501 Test Method	Limits	Unit
9	Frequency variation with Temperature over T <sub>op</sub>	$\frac{\Delta f (\Delta T, P_o)}{f}$	Para. 9.2.1.2	Table 1(a) Item 8	10 <sup>-6</sup>
10	Resistance variation with Temperature over T <sub>op</sub>	$\frac{\Delta R (\Delta T, P_o)}{R}$	Para. 9.2.1.2	Table 1(a) Item 9	%

**FIGURE 4 - CIRCUITS FOR ELECTRICAL MEASUREMENTS**

Not applicable.

**TABLE 4 - PARAMETER DRIFT VALUES**

No.	Characteristics	Symbol	Spec. and/or Test Method	Test Conditions	Change Limits ( $\Delta$ )	Unit
1	Resonance frequency drift	$\frac{\Delta f}{f}$	As per Table 2	As per Table 2	± 2.0	10 <sup>-6</sup>
2	Resonance resistance drift	$\frac{\Delta R}{R}$	As per Table 2	As per Table 2	± 10 or (1) ± 1.0	%  $\Omega$

**NOTES** 1. Whichever is the highest value.

**TABLE 5 - CONDITIONS FOR BURN-IN AND LIFE TEST**

No.	Characteristics	Symbol	Condition	Unit
1	Ambient Temperature	T <sub>amb</sub>	+85 ±5	°C

**FIGURE 5 - ELECTRICAL CIRCUIT FOR BURN-IN AND LIFE TEST**

Not applicable.

	ESCC Detail Specification No. 3501/009		PAGE 19 ISSUE 6
--	---	--	--------------------

4.8 ENVIRONMENTAL AND ENDURANCE TESTS (CHARTS IV AND V OF ESCC GENERIC SPECIFICATION NO. 3501)

4.8.1 Measurements and Inspections on Completion of Environmental Tests

The parameters to be measured and inspections to be performed on completion of environmental tests are scheduled in Table 6. Unless otherwise stated, the measurements shall be performed at  $T_{amb} = T_o \pm 2 \text{ }^\circ\text{C}$ .

4.8.2 Measurements and Inspections at Intermediate Points and on Completion of Endurance Tests

The parameters to be measured and inspections to be performed at intermediate points and on completion of endurance tests are scheduled in Table 6. Unless otherwise stated, the measurements shall be performed at  $T_{amb} = T_o \pm 2 \text{ }^\circ\text{C}$ .

4.8.3 Conditions for Operating Life Test (Part of Endurance Testing)

The requirements for the operating life test are specified in Section 9 of ESCC Generic Specification No. 3501. The test shall be performed as a high temperature storage test and the temperature to be applied shall be the maximum operating temperature specified in the individual Tables 1(a) given in this specification.



**TABLE 6 - MEASUREMENTS AND INSPECTIONS ON COMPLETION OF ENVIRONMENTAL TESTS AND AT INTERMEDIATE POINTS AND ON COMPLETION OF ENDURANCE TESTING**

NO.	ESCC GENERIC SPEC. NO. 3501		MEASUREMENTS AND INSPECTIONS		SYMBOL	LIMITS		UNIT
	ENVIRONMENTAL AND ENDURANCE TESTS (1)	TEST METHOD AND CONDITIONS	IDENTIFICATION	CONDITIONS		Min.	Max.	
01	Electrical Measurements at Reference Temperature	Para. 9.2.4	Electrical Measurements	Table 2		Table 1(a)		
02	Shock	Para. 9.3	<b>Initial Measurements</b> Resonance Frequency Resonance Resistance <b>Final Measurements</b> Resonance Frequency Drift Resonance Resistance Drift	Table 2 Item 1 Table 2 Item 2  Table 2 Item 1 Table 2 Item 2	f R  $\frac{\Delta f}{f}$ $\frac{\Delta R}{R}$ $\Delta R$	Table 2 Item 1 Table 2 Item 2  -1.0 -10 -1.0	+1.0  +1.0 +10 +1.0	10 <sup>-6</sup>   %  Ω
03	Vibration	Para. 9.4	<b>Initial Measurements</b> Resonance Frequency Resonance Resistance <b>Final Measurements</b> Resonance Frequency Drift Resonance Resistance Drift	Table 2 Item 1 Table 2 Item 2  Table 2 Item 1 Table 2 Item 2	f R  $\frac{\Delta f}{f}$ $\frac{\Delta R}{R}$ $\Delta R$	Table 2 Item 1 Table 2 Item 2  -1.0 -10 -1.0	+1.0  +1.0 +10 +1.0	10 <sup>-6</sup>   %  Ω
04	Seal Test	Para. 9.5	Fine Leak Gross Leak	Para. 9.5.1 Para. 9.5.2		Para. 9.5.1 Para. 9.5.2		
05	Permanence of Marking	Para. 9.8	<b>Final Measurements</b> Visual Examination	No corrosion or obliteration of marking	-	-	-	-
06	External Visual Inspection	Para. 9.9	<b>Final Measurements</b> Visual Inspection	ESCC No. 20500	-	-	-	-
07	Solderability	Para. 9.13	-	-	-	-	-	-

**NOTES**

1. The tests in this table refer to either Chart IV or V, and shall be used as applicable.
2. Whichever is the highest value.



**TABLE 6 - MEASUREMENTS AND INSPECTIONS ON COMPLETION OF ENVIRONMENTAL TESTS AND AT INTERMEDIATE POINTS AND ON COMPLETION OF ENDURANCE TESTING (Cont.)**

NO.	ESCC GENERIC SPEC. NO. 3501		MEASUREMENTS AND INSPECTIONS		SYMBOL	LIMITS		UNIT
	ENVIRONMENTAL AND ENDURANCE TESTS (1)	TEST METHOD AND CONDITIONS	IDENTIFICATION	CONDITIONS		Min.	Max.	
08	Climatic Sequence Dry Heat	Para. 9.14 Para. 9.14.1	<b>Initial Measurements</b> Resonance Frequency Resonance Resistance <b>Final Measurements</b> Resonance Frequency Drift Resonance Resistance Drift	Table 2 Item 1 Table 2 Item 2 Table 2 Item 1 Table 2 Item 2	f R $\frac{\Delta f}{f}$ $\frac{\Delta R}{R}$ $\Delta R$	Table 2 Item 1 Table 2 Item 2 -2.0 +2.0 -10 +10 -1.0 +1.0	10 <sup>-6</sup> %	$\Omega$
09	Cold	Para. 9.14.3	<b>Initial Measurements</b> Resonance Frequency Resonance Resistance <b>Final Measurements</b> Resonance Frequency Drift Resonance Resistance Drift	Table 2 Item 1 Table 2 Item 2 Table 2 Item 1 Table 2 Item 2	f R $\frac{\Delta f}{f}$ $\frac{\Delta R}{R}$ $\Delta R$	Para. 9.14.1.3 Final Measurements -2.0 +2.0 -10 +10 -1.0 +1.0	10 <sup>-6</sup> %	$\Omega$
10	Damp Heat (Accelerated) Remaining Cycles	Para. 9.14.4	<b>Initial Measurements</b> Resonance Frequency Resonance Resistance <b>Final Measurements</b> Resonance Frequency Drift Resonance Resistance Drift Insulation Resistance	Table 2 Item 1 Table 2 Item 2 Table 2 Item 1 Table 2 Item 2 Table 2 Item 8	f R $\frac{\Delta f}{f}$ $\frac{\Delta R}{R}$ $\Delta R$ Ri	Para. 9.14.3.2 Final Measurements -2.0 +2.0 -10 +10 -1.0 +1.0 500 -	10 <sup>-6</sup> %	$\Omega$ M $\Omega$
11	Rapid Change of Temperature	Para. 9.15	<b>Initial Measurements</b> Resonance Frequency Resonance Resistance <b>Final Measurements</b> Resonance Frequency Drift Resonance Resistance Drift	Table 2 Item 1 Table 2 Item 2 After minimum Recovery of 2 hours Table 2 Item 1 Table 2 Item 2	f R $\frac{\Delta f}{f}$ $\frac{\Delta R}{R}$ $\Delta R$	Para. 9.14.4.2 Final Measurements -2.0 +2.0 -10 +10 -1.0 +1.0	10 <sup>-6</sup> %	$\Omega$
12	Robustness of Terminations	Para. 9.16	Tensile Strength Visual Examination Bending Visual Examination	Gen. 3501 Para. 9.16.1 No visible damage Gen. 3501 Para. 9.16.2 No visible damage				

**NOTES**

1. The tests in this table refer to either Chart IV or V, and shall be used as applicable.
2. Whichever is the highest value.



**TABLE 6 - MEASUREMENTS AND INSPECTIONS ON COMPLETION OF ENVIRONMENTAL TESTS AND AT INTERMEDIATE POINTS AND ON COMPLETION OF ENDURANCE TESTING (Cont.)**

NO.	ESCC GENERIC SPEC. NO. 3501		MEASUREMENTS AND INSPECTIONS		SYMBOL	LIMITS		UNIT
	ENVIRONMENTAL AND ENDURANCE TESTS (1)	TEST METHOD AND CONDITIONS	IDENTIFICATION	CONDITIONS		Min.	Max.	
13	Life Test	Para. 9.17	<b>Initial Measurements</b>					
			Resonance Frequency	Table 2 Item 1	f	Table 2 Item 1		
			Resonance Resistance	Table 2 Item 2	R	Table 2 Item 2		
			<b>Intermediate Measurements</b>	At 500 hours				
			Resonance Frequency	Table 2 Item 1	$\frac{\Delta f}{f}$	-2.0	+2.0	10 <sup>-6</sup>
			Drift					
			Resonance Resistance	Table 2 Item 2	$\frac{\Delta R}{R}$	-10	+10	%
			Drift		$\Delta R$	or (2) -1.0	+1.0	Ω
			<b>Intermediate Measurements (Chart IV) and Final Measurements (Chart V)</b>	At 1000 hours				
			Resonance Frequency	Table 2 Item 1	$\frac{\Delta f}{f}$	-2.5	+2.5	10 <sup>-6</sup>
			Drift					
			Resonance Resistance	Table 2 Item 2	$\frac{\Delta R}{R}$	-10	+10	%
			Drift		$\Delta R$	or (2) -1.0	+1.0	Ω
<b>Final Measurements (Chart IV)</b>	At 2000 hours							
Resonance Frequency	Table 2 Item 1	$\frac{\Delta f}{f}$	-3.0	+3.0	10 <sup>-6</sup>			
Drift								
Resonance Resistance	Table 2 Item 2	$\frac{\Delta R}{R}$	-10	+10	%			
Drift		$\Delta R$	or (2) -1.0	+1.0	Ω			

**NOTES**

1. The tests in this table refer to either Chart IV or V, and shall be used as applicable.
2. Whichever is the highest value.

**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 01

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	4.194304		MHz	
2	Reference Temperature	$T_o$	+28	+32	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	-	30	pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	10	$\underline{\Omega}$	Over $T_{op}$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-20	+20	%	If $R \leq 10\Omega$
			-2.0	+2.0	$\Omega$	
10	Operating Temperature Range	$T_{op}$	-10	+80	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	0	4.0	pF	
16	Q Factor	Q	200 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_{pl}/R$	2:1	-		In the frequency range: $f_L - 200kHz$ to $f_L + 200kHz$
18	Ageing	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	5 years after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		Not applicable			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 02

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	8.192		MHz	
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	50		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	13	Ω	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-15	+15	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	Not applicable		%	
10	Operating Temperature Range	$T_{op}$	-25	+80	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	36.5	49.5	mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	0	4.0	pF	
16	Q Factor	Q	50 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	3:1	-		In the frequency range: $f_L - 100\text{kHz}$ to $f_L + 100\text{kHz}$
18	Ageing	$\frac{\Delta f}{f}$	-30	+30	$10^{-6}$	
19	Lead Finish		Type `3 or 4`			
20	Intended Application		Not applicable			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

**TYPE VARIANT NO. 03**

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_r$	26.0		MHz	
2	Reference Temperature	$T_o$	+20	+30	°C	
3	Overtone Order	-	3		-	
4	Load Capacitance	$C_L$	$\infty$		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_r$	-	40	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	0 -10 -10	+10 +10 0	$10^{-6}$	From T -20 to +10 °C From T +10 to +50 °C From T +50 to +80 °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-20	+20	%	
10	Operating Temperature Range	$T_{op}$	-25	+80	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	0.5	0.5	$10^{-6}$	From $P_{S1}=0mW$ to $P_{S2}=0.1mW$
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	-10	+10	%	From $P_{S1}=0mW$ to $P_{S2}=0.1mW$
13	Motional Inductance	$L_1$	20	-	mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	0	7.0	pF	
16	Q Factor	Q	100 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	5:1	-		In the frequency range: $f_r -2600kHz$ to $f_r +2600kHz$
18	Ageing	$\frac{\Delta f}{f}$	-2.0	+2.0	$10^{-6}$	10 years after Burn-in and ageing
19	Lead Finish		Type 2			
20	Intended Application		Not applicable			

**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 04

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	7.198		MHz	
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	29.7	30.3	pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-50	+50	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	30	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-50	+50	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	Not applicable		%	
10	Operating Temperature Range	$T_{op}$	-55	+105	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	0	7.0	pF	
16	Q Factor	$Q$	Not applicable		-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	7:1	-		In the frequency range: $f_L$ -500kHz to $f_L$ +500kHz
18	Ageing	$\frac{\Delta f}{f}$	-7.5	+7.5	$10^{-6}$	Over 5 years after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		Not applicable			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 05

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	5.0		MHz	
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	29.7	30.3	pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	100	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-40	+40	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	Not applicable		%	
10	Operating Temperature Range	$T_{op}$	-40	+80	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	Q	Not applicable		-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	4:1	-		In the frequency range: $f_L$ -500kHz to $f_L$ +500kHz
18	Ageing	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
19	Lead Finish		Type 2			
20	Intended Application		Not applicable			

**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 06

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	18.0		MHz	
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	29.7	30.3	pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	20	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-20	+20	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-20 -2.0	+20 +2.0	% $\Omega$	From resistance measured at $T_o$ °C If $R \leq 10\Omega$
10	Operating Temperature Range	$T_{op}$	-45	+80	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	Q	70 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_L - 200\text{kHz}$ to $f_L + 200\text{kHz}$
18	Ageing	$\frac{\Delta f}{f}$	-3.0	+3.0	$10^{-6}$	Over 5 years after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		Not applicable			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 07

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	10		MHz	
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	20	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-25	+25	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	Not applicable		%	
10	Operating Temperature Range	$T_{op}$	-55	+100	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	Q	80 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_L$ -500kHz to $f_L$ +500kHz
18	Ageing	$\frac{\Delta f}{f}$	-5.0	+5.0	$10^{-6}$	Over 5 years after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		Not applicable			

**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 08

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	10.0		MHz	
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	30	Ω	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-30	+30	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-10	+10	%	From resistance measured at $T_o$ °C If $R < 10\Omega$
			-2.0	+2.0	Ω	
10	Operating Temperature Range	$T_{op}$	-55	+100	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	Q	100 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_L - 200\text{kHz}$ to $f_L + 200\text{kHz}$
18	Ageing	$\frac{\Delta f}{f}$	-2.0	+2.0	$10^{-6}$	Per year after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 09

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	50		MHz	
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	3		-	
4	Load Capacitance	$C_L$	11.9	12.1	pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-5.0	+5.0	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	40	$\Omega$	Over $T_{op}$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-5.0 -10	+5.0 +10	$10^{-6}$	From T -20°C to +70°C From T -20°C to +80°C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	Not applicable		%	
10	Operating Temperature Range	$T_{op}$	-20	+80	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	1.7	-	fF	
15	Static Capacitance	$C_o$	-	6.0	pF	
16	Q Factor	Q	50 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_{pl}/R$	2.5:1	-		In the frequency range: $f_L -200kHz$ to $f_L +200kHz$
18	Ageing	$\frac{\Delta f}{f}$	-6.0	+6.0	$10^{-6}$	Over 5 years
19	Lead Finish		Type 2			
20	Intended Application		VCXO			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 10

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	4.0		MHz	
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	25	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-30	+30	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	Not applicable		%	
10	Operating Temperature Range	$T_{op}$	-40	+80	°C	
11	Frequency variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	Not applicable		pF	
16	Q Factor	Q	125 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_L$ -500kHz to $f_L$ +500kHz
18	Ageing	$\frac{\Delta f}{f}$	-3.0	+3.0	$10^{-6}$	1 year after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			With 54HC04



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 11

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	10.0		MHz	
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	30	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-30	+30	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-2.0	+2.0	$\Omega$	From resistance measured at $T_o$ °C
10	Operating Temperature Range	$T_{op}$	-55	+100	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	Q	100 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_L - 200\text{kHz}$ to $f_L + 200\text{kHz}$
18	Ageing	$\frac{\Delta f}{f}$	-2.0	+2.0	$10^{-6}$	Per year after Burn-in at $T_o$
19	Lead Finish		Type 2			
20	Intended Application		XO			

**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 12

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_r$	8.0		MHz	
2	Reference Temperature	$T_o$	+20	+30	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	$\infty$		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_r$	-	40	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	0 -9.0 -9.0	+9.0 +9.0 0	$10^{-6}$	From T -20 to +10 °C From T +10 to +50 °C From T +50 to +80 °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-2.0	+2.0	$\Omega$	From resistance measured at $T_o$ °C
10	Operating Temperature Range	$T_{op}$	-20	+80	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	2.0	-	mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	5.0	pF	
16	Q Factor	Q	70 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_r - 10\%$ to $f_r + 10\%$
18	Ageing	$\frac{\Delta f}{f}$	-5.0	+5.0	$10^{-6}$	12 years after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			

TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION

TYPE VARIANT NO. 13

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_r$	10.0		MHz	AT cut
2	Reference Temperature	$T_o$	+20	+30	°C	
3	Overtone Order	-	3		-	
4	Load Capacitance	$C_L$	$\infty$		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_r$	-	40	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-2.0	+2.0	$\Omega$	From resistance measured at $T_o$ °C
10	Operating Temperature Range	$T_{op}$	-20	+80	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	-0.5	+0.5	$10^{-6}$	From $P_{S1}=0.01mW$ to $P_{S2}=0.1mW$
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	-20	+20	%	From $P_{S1}=0.01mW$ to $P_{S2}=0.1mW$
13	Motional Inductance	$L_1$	3.0	-	mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	5.0	pF	
16	Q Factor	Q	70 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	3:1	-		In the frequency range: $f_r -10\%$ to $f_r +10\%$
18	Ageing	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	12 years after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		TCXO			

**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 14

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	6.4		MHz	
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	20	Ω	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-20	+20	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-20	+20	%	From resistance measured at $T_o$ °C If $R < 10\Omega$
			-2.0	+2.0	Ω	
10	Operating Temperature Range	$T_{op}$	-45	+80	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	Q	70 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_L - 200\text{kHz}$ to $f_L + 200\text{kHz}$
18	Ageing	$\frac{\Delta f}{f}$	-3.0	+3.0	$10^{-6}$	Per year after Burn-in
19	Lead Finish		Type 4			
20	Intended Application		XO			

**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 15

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_r$	12.605		MHz	AT cut
2	Reference Temperature	$T_o$	+20	+30	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	$\infty$		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_r$	-	40	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-20	+20	%	From resistance measured at $T_o$ °C
			-2.0	+2.0	$\Omega$	
10	Operating Temperature Range	$T_{op}$	-20	+60	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	2.0	-	mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	$Q$	70 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_r - 10\%$ to $f_r + 10\%$
18	Ageing	$\frac{\Delta f}{f}$	-5.0	+5.0	$10^{-6}$	Operation 12 years
19	Lead Finish		Type 2			
20	Intended Application		TCXO			

**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 16

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	7.0		MHz	AT cut
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	20	Ω	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-12	+12	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-20	+20	%	From resistance measured at $T_o$ °C
			-2.0	+2.0	Ω	
10	Operating Temperature Range	$T_{op}$	-35	+70	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	40	-	mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	Q	100 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	3:1	-		In the frequency range: $f_L -10\%$ to $f_L +10\%$
18	Ageing	$\frac{\Delta f}{f}$	-3.0	+3.0	$10^{-6}$	Per year after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			

**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 17

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_r$	12.665		MHz	AT cut
2	Reference Temperature	$T_o$	+20	+30	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	$\infty$		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_r$	-	40	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-12	+12	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-20	+20	%	From resistance measured at $T_o$ °C
			-2.0	+2.0	$\Omega$	
10	Operating Temperature Range	$T_{op}$	-20	+80	°C	
11	Frequency variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	2.0	-	mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	Q	70 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_r - 10\%$ to $f_r + 10\%$
18	Ageing	$\frac{\Delta f}{f}$	-5.0	+5.0	$10^{-6}$	Over 12 years after 240 hours Burn-in
19	Lead Finish		Type 2			
20	Intended Application		TCXO			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 18

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	5.760		MHz	AT cut
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	29.5	30.5	pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	4.0	15	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-15	+15	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	Not applicable		%	
10	Operating Temperature Range	$T_{op}$	-40	+90	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	Q	100 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_{pl}/R$	3:1	-		In the frequency range: $f_L - 200\text{kHz}$ to $f_L + 200\text{kHz}$
18	Ageing	$\frac{\Delta f}{f}$	-15	+15	$10^{-6}$	Over 10 years after 240 hours Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 19

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	8.602893		MHz	AT cut
2	Reference Temperature	$T_o$	+55	+65	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	30	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-12	+12	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-20 -2.0	+20 +2.0	% $\Omega$	From resistance measured at $T_o$ °C
10	Operating Temperature Range	$T_{op}$	-40	+85	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	-20	+20	%	From $P_{S1}=0.01mW$ to $P_{S2}=0.1mW$
13	Motional Inductance	$L_1$	2.0	-	mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	5.0	pF	
16	Q Factor	Q	100 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_L -10\%$ to $f_L +10\%$
18	Ageing	$\frac{\Delta f}{f}$	-5.0	+5.0	$10^{-6}$	Over 10 years after 240 hours Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			

**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 20

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_r$	15.104893		MHz	AT cut
2	Reference Temperature	$T_o$	+20	+30	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	$\infty$		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_r$	-	40	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-20	+20	%	From resistance measured at $T_o$ °C
			-2.0	+2.0	$\Omega$	
10	Operating Temperature Range	$T_{op}$	-20	+80	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	2.0	-	mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	$Q$	70 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_r - 10\%$ to $f_r + 10\%$
18	Ageing	$\frac{\Delta f}{f}$	-5.0	+5.0	$10^{-6}$	Over 12 years after 240 hours Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 21

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	20.0		MHz	AT cut
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	30	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-15	+15	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-20	+20	%	From resistance measured at $T_o$ °C
			-2.0	+2.0	$\Omega$	
10	Operating Temperature Range	$T_{op}$	-30	+70	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	Q	70 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_L - 200\text{kHz}$ to $f_L + 200\text{kHz}$
18	Ageing	$\frac{\Delta f}{f}$	-1.0	+1.0	$10^{-6}$	Per year after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 22

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	13.0		MHz	AT cut
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	20	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-20	+20	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-20	+20	%	From resistance measured at $T_o$ °C
			-2.0	+2.0	$\Omega$	
10	Operating Temperature Range	$T_{op}$	-40	+80	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	Q	70 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_L$ -200kHz to $f_L$ +200kHz
18	Ageing	$\frac{\Delta f}{f}$	-2.0	+2.0	$10^{-6}$	Per year after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			

**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 23

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	10.0		MHz	AT cut
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	30	Ω	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-30	+30	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-20	+20	%	From resistance measured at $T_o$ °C
			-2.0	+2.0	Ω	
10	Operating Temperature Range	$T_{op}$	-55	+100	°C	
11	Frequency variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	Q	100 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_L$ -200kHz to $f_L$ +200kHz
18	Ageing	$\frac{\Delta f}{f}$	-2.0	+2.0	$10^{-6}$	Per year after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 24

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	5.242880		MHz	AT cut
2	Reference Temperature	$T_o$	+60	+60	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	13	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-15	+15	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	Not applicable		%	
10	Operating Temperature Range	$T_{op}$	-40	+85	°C	
11	Frequency variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	20	-	mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	5.0	pF	
16	Q Factor	Q	50 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	3:1	-		In the frequency range: $f_L -525kHz$ to $f_L +525kHz$
18	Ageing	$\frac{\Delta f}{f}$	-3.0	+3.0	$10^{-6}$	Per year after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 25

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	5.6250		MHz	AT cut
2	Reference Temperature	$T_o$	+20	+30	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	25	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-14	+14	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-20 -2.0	+20 or +2.0	% $\Omega$	From resistance measured at $T_o$ °C
10	Operating Temperature Range	$T_{op}$	-40	+85	°C	
11	Frequency variation with Drive Level	$\frac{\Delta f}{f}$	-0.5	+0.5	$10^{-6}$	From $P_{S1}=0.01mW$ to $P_{S2}=0.1mW$
12	Resistance variation with Drive Level	$\frac{\Delta R}{R}$	-20	+20	%	From $P_{S1}=0.01mW$ to $P_{S2}=0.1mW$
13	Motional Inductance	$L_1$	2.0	-	mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	5.0	pF	
16	Q Factor	Q	10 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	3:1	-		In the frequency range: $f_L -10%$ to $f_L +10%$
18	Ageing	$\frac{\Delta f}{f}$	-5.0	+5.0	$10^{-6}$	Over 10 years after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 26

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	11.250		MHz	AT cut
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	29.7	30.3	pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	20	Ω	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-20	+20	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	Not applicable		%	
10	Operating Temperature Range	$T_{op}$	-50	+100	°C	
11	Frequency variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	Q	50 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	7:1	-		In the frequency range: $f_L$ -200kHz to $f_L$ +200kHz
18	Ageing	$\frac{\Delta f}{f}$	-20	+20	$10^{-6}$	Over 15 years after 240 hours Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 27

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_r$	8.0		MHz	AT cut
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	$\infty$		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_r$	-	30	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-20 -1.0	+20 +1.0	% $\Omega$	From resistance measured at $T_o$ °C
10	Operating Temperature Range	$T_{op}$	-30	+70	°C	
11	Frequency variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	Q	80 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_r - 200\text{kHz}$ to $f_r + 200\text{kHz}$
18	Ageing	$\frac{\Delta f}{f}$	-3.0	+3.0	$10^{-6}$	Per year after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 28

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	3.494400		MHz	AT cut
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	20	50	pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	12	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-20	+20	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	Not applicable		%	
10	Operating Temperature Range	$T_{op}$	-55	+100	°C	
11	Frequency variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	200	-	mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	2.7	pF	
16	Q Factor	Q	400 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_L$ -300kHz to $f_L$ +300kHz
18	Ageing	$\frac{\Delta f}{f}$	-5.0	+5.0	$10^{-6}$	Per year after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			

**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 29

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	3.832		MHz	
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	45	Ω	Over $T_{op}$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-17	+17	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	Not applicable		%	
10	Operating Temperature Range	$T_{op}$	-40	+80	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	230	-	mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	5.0	pF	
16	Q Factor	Q	125 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_L$ -500kHz to $f_L$ +500kHz
18	Ageing	$\frac{\Delta f}{f}$	-3.0	+3.0	$10^{-6}$	Per year after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			

**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 30

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	3.072		MHz	
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	50	$\Omega$	Over $T_{op}$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-20	+20	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	Not applicable		%	
10	Operating Temperature Range	$T_{op}$	-40	+80	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	230	-	mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	5.0	pF	
16	Q Factor	Q	125 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_L$ -500kHz to $f_L$ +500kHz
18	Ageing	$\frac{\Delta f}{f}$	-3.0	+3.0	$10^{-6}$	Per year after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			

**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 31

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	4.0		MHz	
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	25	Ω	Over $T_{op}$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-17	+17	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	Not applicable		%	
10	Operating Temperature Range	$T_{op}$	-40	+80	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	230	-	mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	5.0	pF	
16	Q Factor	Q	125 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_L$ -500kHz to $f_L$ +500kHz
18	Ageing	$\frac{\Delta f}{f}$	-3.0	+3.0	$10^{-6}$	Per year after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 32

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	16.0		MHz	AT cut
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	30	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-50	+50	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	Not applicable		%	
10	Operating Temperature Range	$T_{op}$	-55	+125	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	Q	50 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_L$ -100kHz to $f_L$ +200kHz
18	Ageing	$\frac{\Delta f}{f}$	-3.0	+3.0	$10^{-6}$	Per year after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 33

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	11.059200		MHz	AT cut
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	15	$\Omega$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-25	+25	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-20 -2.0	+20 +2.0	% $\Omega$	From resistance measured at $T_o$ °C
10	Operating Temperature Range	$T_{op}$	-55	+100	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	Not applicable		mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	Q	70 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_L - 200\text{kHz}$ to $f_L + 200\text{kHz}$
18	Ageing	$\frac{\Delta f}{f}$	-1.0	+1.0	$10^{-6}$	Per year after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			



**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 34

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	12.007125		MHz	AT cut
2	Reference Temperature	$T_o$	+20	+30	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	30		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	15	Ω	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-20	+20	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-20	+20	%	From resistance measured at $T_o$ °C
			-2.0	+2.0	Ω	
10	Operating Temperature Range	$T_{op}$	-40	+90	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	-0.5	+0.5	$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	-10	+10	%	
13	Motional Inductance	$L_1$	5.0	-	mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	5.5	pF	
16	Q Factor	$Q$	70 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	3:1	-		In the frequency range: $f_L -10\%$ to $f_L +10\%$
18	Ageing	$\frac{\Delta f}{f}$	-5.0	+5.0	$10^{-6}$	Over 10 years after Burn-in
19	Lead Finish		Type 2			
20	Intended Application		TCXO			

**TABLE 1(a) - TYPE VARIANT DETAILED INFORMATION**

TYPE VARIANT NO. 35

No.	Characteristics	Symbol	Limits		Unit	Remarks
			Min.	Max.		
1	Resonance Frequency	$f_L$	11.0592		MHz	AT cut
2	Reference Temperature	$T_o$	+23	+27	°C	
3	Overtone Order	-	Fundamental		-	
4	Load Capacitance	$C_L$	50		pF	
5	Rated Drive Level	$P_o$	0.1		mW	
6	Frequency Adjustment Tolerance	$\frac{\Delta f}{f}$	-10	+10	$10^{-6}$	At $T_o$ °C
7	Resonance Resistance	$R_L$	-	20	$\underline{\Omega}$	At $T_o$ °C
8	Frequency Variation with Temperature over $T_{op}$	$\frac{\Delta f}{f}$	-30	+30	$10^{-6}$	From frequency measured at $T_o$ °C
9	Resistance Variation with Temperature over $T_{op}$	$\frac{\Delta R}{R}$	-20	+20 or -2.0    +2.0	%  $\underline{\Omega}$	From resistance measured at $T_o$ °C If $R < 10\underline{\Omega}$
10	Operating Temperature Range	$T_{op}$	-55	+100	°C	
11	Frequency Variation with Drive Level	$\frac{\Delta f}{f}$	Not applicable		$10^{-6}$	
12	Resistance Variation with Drive Level	$\frac{\Delta R}{R}$	Not applicable		%	
13	Motional Inductance	$L_1$	7.0	-	mH	
14	Motional Capacitance	$C_1$	Not applicable		fF	
15	Static Capacitance	$C_o$	-	7.0	pF	
16	Q Factor	Q	100 000	-	-	
17	Ratio of Unwanted: Response Resistance to Resonance Resistance or Response Impedance to Resonance Resistance	$R_p/R$ or $ Z_p /R$	2:1	-		In the frequency range: $f_L - 200\text{kHz}$ to $f_L + 200\text{kHz}$
18	Ageing	$\frac{\Delta f}{f}$	-5.0	+5.0	$10^{-6}$	Per year after 240 Hour Burn-in
19	Lead Finish		Type 2			
20	Intended Application		XO			

**APPENDIX `A`**

AGREED DEVIATIONS FOR RAKON (F)

ITEMS AFFECTED	DESCRIPTION OF DEVIATION
Para. 4.2.2	Para. 9.3, Shock: Shall not be performed.
Para. 4.2.3	Para. 9.11, Radiographic Inspection: Shall not be performed.

	<p>ESCC Detail Specification No. 3501/009</p>		<p>PAGE 59 ISSUE 6</p>
---	---	--	----------------------------

**APPENDIX `B`**

Page 1 of 1

AGREED DEVIATIONS FOR KVG Quartz Crystal Technology GmbH (D)

ITEMS AFFECTED	DESCRIPTION OF DEVIATION
Para. 4.2.2 Para. 4.2.3 Para. 4.2.4 Para. 4.2.5	Para. 9.5.1, Seal Test Fine Leak: The crystal units shall be subjected to MIL-STD-202, Method 112, Procedure IIIa.