



Page 1 of 10

**DIODES, POWER RECTIFIER, HIGH EFFICIENCY, FAST  
RECOVERY**

**BASED ON TYPE BYVD-200**

**ESCC Detail Specification No. 0100/000**

Issue 1	January 2011
---------	--------------





## **LEGAL REQUIREMENTS AND COPYRIGHT**

European Space Agency. Copyright ©2011. All rights reserved.

The European Space Agency disclaims any liability or responsibility, in any personal capacity, with respect to any loss or damage caused, or alleged to be caused, directly or indirectly by the use and application of this ESCC publication.

This publication, without the prior permission of the European Space Agency and provided that it is not used for a commercial purpose, may be:

- copied in whole, in any medium, without alteration or modification
- copied in part, in any medium, provided that the ESCC document identification, comprising the ESCC symbol, document number and document issue, is retained.



**Administrative/General Notes**

(Refer to specifications for ESCC 001 series)

Item No.	General Description
101	Administrative/General Notes/Specified ESCC



## TABLE OF CONTENTS

<b>1</b>	<b><u>GENERAL</u></b>	<b>1</b>
1.1	Scope	1
1.2	Applicable Documents	1
1.3	Terms / Definitions, Abbreviations, Symbols and Units	1
1.4	The ESCC Component Number and Component Type Variants	1
1.4.1	The ESCC Component Number	1
1.4.2	Component Type Variants	1
1.5	Maximum Ratings	1
1.6	Handling/Precautions	1
1.7	Physical Dimensions and Terminal Identification	1
1.8	Functional Diagram	2
1.9	Materials and Finish	2
<b>2</b>	<b><u>MECHANICALS</u></b>	<b>3</b>
2.1	General	3
2.1.1	Excitations from the General Specification	3
2.1.1.1	Excitations from Qualification and Periodic Tests „Drawn“	3
2.2	Mating	3
2.3	Terminal Strength	3
2.4	Electrical Measurements at Room / High ambient Temperature	3
2.4.1	Room Temperature/Relative Humidity Measurements	3
2.4.2	High ambient Temperature Electrical Measurements	3
2.4.3	Wave to Electric Measurement Tables	3
2.5	Parameter Extractions	3
2.6	Interactions and End Point Electrical Measurements	3
2.7	High Temperature/High Humidity Measurements	3
2.8	Power/Static Conditions	3
2.9	Operating Life Conditions	3
<b>APPENDIX A</b>		<b>12</b>



## 5. GENERAL

### 5.1 SCOPE

This specification details the ratings, physical and chemical characteristics and test and inspection data for the component type, values within the range of components specified below. It supplements the requirements of associated test result in conjunction with the ESCC Seal Specification listed under applicable documents.

### 5.2 APPLICABLE DOCUMENTS

The following documents form part of the specification and shall be read in conjunction with it:

- ESCC Seal Specification No. 0000
- MS-010-104 Test Methods and Procedures for Semiconductor Devices

### 5.3 SYMBOLS, ABBREVIATIONS, DIMENSIONS AND UNITS

For the purpose of this specification, the terms, definitions, abbreviations, symbols and units specified in ESCC Seal Specifications No. 010000 shall apply.

### 5.4 THE ESCC COMPONENT NUMBERING SYSTEM AND COMPONENT IDENTIFICATION

#### 5.4.1 The ESCC Component Number

The ESCC Component Number shall be constructed as follows:

Example: 0100000

- Seal Specification Reference: 010000
- Component Type (Seal Number 01) (as required)

#### 5.4.2 Component Test Values

The component test values applicable to this specification are as follows:

Seal Number	Component Type	Value	Description	Measurement and Finish	Weight (max g)
01	010000-000	10.000	Single State	MS	0.1

The measurement and finish shall be in accordance with the requirements of ESCC Seal Specification No. 010000.

#### 5.5 MAXIMUM WEIGHT

The maximum ratings shall not be exceeded at any time during use or storage.

Maximum ratings shall only be exceeded during testing to the extent specified in this specification and when stipulated in Test Methods and Procedures of the ESCC Seal Specifications.



Characteristic	Symbol	Maximum Range	Unit	Remarks
Rated Temperature	$T_{nom}$	100	°C	Note 1
Maximum Permitted Service Voltage	$V_{max}$	100	V	Note 2
Average Output Current (Continuous)	$I_a$	10	A	50% Duty Cycle Note 3
Peak Permitted Current	$I_{max}$	10	A	
Operating Temperature Range (Case Temperature)	$T_c$	-20 to +100	°C	Note 4
Storage Temperature	$T_s$	-100	°C	
Storage Temperature Range	$T_{stg}$	-20 to +100	°C	Note 4
Handling Temperature	$T_{hd}$	-200	°C	Note 4
Rated Reliability, Acceleration Case	$R_{acc}$	100	%/hr	Note 5

**Notes:**

1. Operational pulse of 1000 pulses.
2. Pulse isolation time, 1000 pulses.
3. At  $T_{nom} = +25°C$ , duty cycle is 50% at +100°C.
4. For variants with two soldered lead feet, all testing performed at  $T_{nom} = +25°C$  shall be carried out at 100% duty operation.
5. Surface 10 mm wide minimum and distance of not less than 1.5mm from the device body and the parts attached to it shall be completely finished, free of dust.
6. Package mounted on an infinite heat sink.

## 1.2

**General Handling Instructions**

The ESCC package contains Beryllium Oxide (BeO) and therefore it must not be ground, machined, cut/broken or subjected to any mechanical operation which will produce dust. The case must not be subjected to any chemical process (e.g. etching) which will produce fumes.

**6.2 Physical Dimensions and Mechanical Characteristics**
**6.2.1 Seal Cross Section Parameters (See Fig. 6.2.1)**


Symbol	Dimension (mm)		Notes
	Min	Max	
A	1.000	1.000	
B	1.000	1.000	
C	20.00	20.00	
D	0.4	0.7	
E	1	1.00	
F	0.5	0.5	
G	10.00	10.0	
H	0.50 (0.50)		
I	0.80	1.10	1)
J	0.50 (0.50)		
K	0.50 (0.50)		
L	0.200	10.0	
Notes	1) 0.50 typical		1)
M	-	0.20	2)
N	-	1	3)
O	0.50 (typical)		4)

**Footnote:**

1. Transverse identification is specified by the component geometry. See the Flatness Diagram for



- a. the terminal connections;
- b. Spheres;
- c. Radius of transition fillets corner, Spheres;
- d. Radius of fillet corner, if present.

## 2.8 FUNCTIONAL SYMBOL



### NOTES

1. Terminal 3 is not connected in any lead.

## 2.9 TESTING AND FINISHES

Materials and finishes shall be as follows:

- a) Case  
The case shall be hermetically sealed and have a metal finish. The leads pass through ceramic seals located into the frame structure to which be sealed.
- b) Leads  
As specified in Component Type Variants.

## 3. REQUIREMENTS

### 3.1 GENERAL

The complete requirements for components of the components specified herein are as stated in this specification and the ESCC Basic Specification. Particular deviations from the General Specification, applicable to this specification only, are indicated below.

Particular deviations from the General Specification and this Basic Specification, formally agreed with specific Manufacturers on the basis that the alternative requirements are equivalent to the ESCC requirements and do not affect the component's reliability, are listed in the appendices attached to this specification.

### 3.2 Deviations from the General Specification

#### 3.2.1 Deviations from Qualification and Particular Tests - Class P0

- a) Component qualification is not applicable.

### 3.3 REMARKS

The marking and lead construction will be the requirements of ESCC Basic Specification No. 07000 and as follows:





The information to be marked on the component shall be:

- Thick ESCC qualified components symbol for ESCC qualified components only.
- Thick ESCC Component Number.
- Traceability information.
- Marking sign for RoHS-compliance.

#### 2.4.1 Minimum Temperature

The test conditions for Terminal Strength, stated as specified in the ESCC Generic Specification, shall be as follows:

Test Condition 4, reverse, with an applied force of 10N for a duration of 10s.

#### 2.4.2 FUNCTIONAL AND MECHANICAL TESTS PERFORMED AT TEMPERATURES

Electrical measurements shall be performed at room, high and low temperatures. Conditions thereof are given after the Tables.

#### 2.4.3 Room Temperature Electrical Measurements

The measurements shall be performed at  $T_{amb} \pm 0.5^{\circ}\text{C}$ .

Characteristics	Symbol	IEC-60749-501 Test Method	Test Conditions	Limits		Units
				Min	Max	
Reverse Current	$I_{r1}$	501.1	20 Volts $V_{r1} = 200V$	-	20	$\mu\text{A}$
Forward Voltage	$V_{f1}$	501.1	10mA forward 10 Ohm, 10ms	-	1.00	V
	$V_{f2}$	501.1	10mA forward 10 Ohm, 10ms	-	1.75	V
Reverse Voltage	$V_{r100}$	501.1	$I_{r1} = 100\mu\text{A}$	200	-	V
Capacitance	C	501.1	$V_{f1}$ under no current	-	500	$\mu\text{F}$
Reverse Recovery Time	$t_{rr}$	501.1	Test condition as 1.1.1.1 $V_{f1} = 200V$ $I_{f1} = 10\text{mA}$	-	10	ns
Forward Recovery Time as Case	$t_{fr1}$	501.1	$I_{f1} = 10\text{mA}$ $V_{f1} = 200V$ $I_{r1} = 100\mu\text{A}$ Time 2	(Calculate $t_{fr1}$ see Table 2)		ns



## 2.6.2 Minimum and Maximum Electrical Measurements

Characteristic	Symbol	Min. ESCC Seal Test Method	Test Conditions Note 1	Limits		Units
				Min.	Max.	
Electrical Contact	$V_c$	200V	$V_{cmin} = 100\% \pm 0.5\%$ SCC Method $V_{cmax} = 200V$	-	100	Volts
Maximum Voltage	$V_{max}$	200V	$V_{maxmin} = 100\% \pm 0.5\%$ Pulsed Method $V_{maxmax} = 200V$ , Note 1	-	100	V <sup>2</sup>
			$V_{maxmin} = 100\% \pm 0.5\%$ Pulsed Method $V_{maxmax} = 200V$ , Note 1	-	100	V <sup>2</sup>

## 2.6.3 How to Electrical Measurements Taken

1. Pulse width voltage: 50µs Cycle 1:0%
2. Perform test only during increasing time for every test values (initial measurement) go on go
3. Test time for  $v_c$  shall be defined by the manufacturer accuracy for in accordance with IEC 61212-1. The interval of 0.5 seconds provides the  $V_{cmin}$  limits specified in Maximum Ratings.
4. Seal and contact measurements shall be performed on sample of 5 components with 5 values allowed. Alternatively a 100% inspection may be performed.

## 2.6.4 PERMITTED TEST VALUES

Unless otherwise specified, the measurements shall be performed at  $T_{amb} = 20 \pm 0.5^\circ C$ .

The test methods and test conditions shall be as per the corresponding test defined in IEC 61212-1 Temperature Electrical Measurements.

The test values (v) shall not be exceeded for each characteristic specified. The corresponding absolute test values for each characteristic shall not be exceeded.

Characteristic	Symbol	Limits			Units
		Min. Value a	Max.		
			Min.	Max.	
Electrical Contact	$V_c$	100 100% $\pm 0.5\%$	-	100	Volts
Maximum Voltage	$V_{max}$	100	-	100	V <sup>2</sup>

### NOTES

1. Difference is the greater related to the initial value.

**2.6 TEMPERATURE AND HUMIDITY IN ELECTRICAL MEASUREMENTS**

Unless otherwise specified, the measurements shall be performed at  $T_{amb} = 20 \pm 0.5$  °C.

The test methods and test conditions shall be as per the corresponding test defined in IEC60 Temperature Electrical Measurements.

The tolerances for each characteristic shall be as specified.

Characteristic	Symbol	Units		Tol.
		Min.	Max.	
Temperature	$T_c$	-	20	±0.5
Humidity	$H_c$	-	100	±1

**2.7 HIGH TEMPERATURE STORAGE (HUMIDITY) CONDITIONS**

Characteristic	Symbol	Units	Tol.
Storage Temperature	$T_{max}$	°C (per IEC)	±0
Storage Humidity	$H_c$	%	±1
Storage	t	min	±0.01

**2.8 POWER SUPPLY CONDITIONS**

Characteristic	Symbol	Specifications	Tol.
Case Temperature	$T_{case}$	as defined, Item 1	±0
Source Temperature	$T_s$	as per (per IEC)	±0
Average Output Rectifier Current	$I_{avg}$	as per, Item 1	±0

**NOTES**

1. The case temperature and/or output current may be adjusted, within their specified ranges, to attain the specified junction temperature.

**2.9 OPERATIONAL USE CONDITIONS**

The conditions shall be as specified in Power Section.



## APPENDIX

### GENERAL CONDITIONS FOR PURCHASE CONTRACTS

ITEM NUMBER	DESCRIPTION OF CONDITIONS
Condition Item Production - General - Quan 10	General EC Production Item - Item of Good Quality, dimensions equal to 1.1x1.1x1.1mm and compatible for handling with a 0.05mm tool.
Condition Item Sourcing Term - Quan 10	Manufacturer's responsibility under operating Agreement in Item - General Data.