



**POWER WIRES FOR CRIMPING,
LOW FREQUENCY, 600V, -200 TO +200°C**

BASED ON TYPE SPP

ESCC Detail Specification No. 3901/017

Issue 3	March 2013
---------	------------



LEGAL DISCLAIMER AND COPYRIGHT

European Space Agency, Copyright © 2013, All rights reserved.

The European Space Agency disclaims any liability or responsibility, to any person or entity, with respect to any loss or damage caused, or alleged to be caused, directly by the use and application of this ESCC publication.

This publication, without prior permission of the European Space Agency and provided it is not used for a commercial purpose, may be:

- copied in whole, in any medium, without alteration or modification.
- copied in part, in any medium, provided that the ESCC document identification, comprising the ESCC symbol, document number and document issue, is removed.

DOCUMENTATION CHANGE NOTICE

(Refer to <https://escies.org> for ESCC DCR content)

DCR No.	CHANGE DESCRIPTION
750	Specification upissued to incorporate editorial changes per DCR.

TABLE OF CONTENTS

1	GENERAL	6
1.1	SCOPE	6
1.2	TYPE VARIANTS	6
1.3	MAXIMUM RATINGS	6
1.4	PARAMETER DERATING INFORMATION	6
1.5	PHYSICAL CHARACTERISTICS	6
1.6	FUNCTIONAL DIAGRAM	6
2	APPLICABLE DOCUMENTS	9
3	TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS	9
4	REQUIREMENTS	9
4.1	GENERAL	9
4.2	DEVIATIONS FROM GENERIC SPECIFICATION	9
4.2.1	Deviations from Special In-process Controls	9
4.2.2	Deviations from Final Production Tests (Chart II)	9
4.2.3	Deviations from Burn-in and Electrical Measurements (Chart III)	9
4.2.4	Deviations from Qualification Tests (Chart IV)	9
4.2.5	Deviations from Lot Acceptance Tests (Chart V)	9
4.3	MECHANICAL REQUIREMENTS	10
4.3.1	Dimension Check	10
4.3.2	Weight	10
4.4	MATERIALS AND FINISHES	10
4.4.1	Conductor	10
4.4.2	Insulation	11
4.4.3	Colour Coding	11
4.5	MARKING	12
4.5.1	General	12
4.5.2	The ESCC Component Number	12
4.5.3	Characteristics	12
4.5.4	Traceability Information	12
4.5.5	Additional Marking	12
4.6	ELECTRICAL MEASUREMENTS	12
4.6.1	Electrical Measurements at Room Temperature	12
4.6.2	Electrical Measurements at High and Low Temperatures	12
4.6.3	Circuits for Electrical Measurements	12
4.7	BURN-IN TESTS	13

4.8	ENVIRONMENTAL AND ENDURANCE TESTS	13
4.8.1	Mechanical Properties of Conductor	13
4.8.2	Accelerated Ageing	13
4.8.3	Wrap Test at Ambient Temperature	13
4.8.4	Voltage Test	13
4.8.5	Shrinkage	13
4.8.6	Blocking	13
4.8.7	Cold Bend Test	13
4.8.8	Cut-through Resistance	13
4.8.9	Notch Resistance	13
4.8.10	Flammability Resistance	14
4.8.11	Resistance to Fluids	14
4.8.12	Surface Resistance	14
4.8.13	Abrasion Resistance	14
4.8.14	Soldering	14
4.8.15	Solderability	14
4.8.16	Radiation Resistance	14
4.8.17	Overload Resistance	14
4.8.18	Outgassing in Vacuum	14
4.8.19	Long-term Ageing Test	14
4.8.20	Atomic Oxygen Resistance	14

1 GENERAL

1.1 SCOPE

This specification details the ratings, physical and electrical characteristics, test and inspection data for Power Wires for Crimping, Low Frequency, 600V, -200 to +200 °C, Based on Type SPP.

It shall be read in conjunction with ESCC Generic Specification No. 3901, the requirements of which are supplemented herein.

1.2 TYPE VARIANTS

Variants of the basic types of wires specified herein, which are also covered by this specification, are listed in Table 1(a).

1.3 MAXIMUM RATINGS

The maximum ratings, applicable to the finished wires specified herein, which shall not be exceeded at any time during use or storage in controlled space environment, are scheduled in Table 1(b).

1.4 PARAMETER DERATING INFORMATION

The derating information applicable to the finished wires specified herein is as follows:

- The maximum current for each wire used in a bundle shall be:

$$I_{Bmax} = I_{max} \times \frac{29 - n}{28} \quad (\text{for } 1 < n < 15)$$
$$I_{Bmax} = \frac{I_{max}}{2} \quad (\text{for } n > 15)$$

where n = number of wires in the bundle.

- The temperature derating information is shown in Figure 1 with maximum current I_{max} for a single wire.
- The derating factors contained herein indicate maximum stress values and do not preclude further derating.

1.5 PHYSICAL CHARACTERISTICS

The physical characteristics of the wires specified herein are shown in Figure 2 and Table 1(a).

1.6 FUNCTIONAL DIAGRAM

Not applicable.

TABLE 1(a) – TYPE VARIANTS

Variant No.	Wire Size AWG	Stranding No. of Strands x Diameter (mm)	Conductor Characteristics			Finished Wire Characteristics	
			Max Ø (mm)	Nom Sect. (mm ²)	Max Ohmic Resistance (Ω/km)	Max Ø (mm)	Max Weight (kg/km)
01	0	19x55x0.254RC	10.5	53	0.38	11.8	542
02	4	19x7x0.454RU	6.5	22	0.91	7.7	232
03	8	19x7x0.287RC	4.2	8.6	2.38	5.3	98

NOTES:

1. RC = rope lay; RU = rope unilay.

TABLE 1(b) – MAXIMUM RATINGS

No.	Characteristics	Symbol	Maximum Rating	Unit	Remarks
1	Voltage	V _P	600	V _{rms}	
2	Maximum Current (Note 1)	I _{max}	45 81 133	A	For AWG: 8 4 0
3	Operating Temperature Range	T _{amb}	-200 to +200	°C	
4	Storage Temperature Range	T _{stg}	-200 to +200	°C	

NOTES:

1. The above specified current will generate a temperature rise of approximately 50°C above ambient temperature in a vacuum environment. Precautions shall be taken to prevent the total temperature of the wire (ambient plus rise) exceeding the continuous operating temperature of the wire.

FIGURE 1 – PARAMETER DERATING INFORMATION





FIGURE 2 – PHYSICAL CHARACTERISTICS

Dimensions are given in Table 1(a)

FINISHED WIRES



2 APPLICABLE DOCUMENTS

The following documents form part of this specification and shall be read in conjunction with it:

- (a) ESCC Generic Specification No. 3901, Wires and Cables, Electrical, 600V, Low Frequency.
- (b) ASTM-B355, Standard Specification for Nickel-Coated Soft or Annealed Copper Wire.

3 TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS

For the purpose of this specification, the terms, definitions, abbreviations, symbols and units specified in ESCC Basic Specification No. 21300 and ESCC Generic Specification No. 3901 shall apply.

4 REQUIREMENTS

4.1 GENERAL

The complete requirements for procurement of the finished wires specified herein are stated in this specification and ESCC Generic Specification No. 3901. Deviations from the Generic Specification, applicable to this specification only, are listed in Para. 4.2.

Deviations from the applicable Generic Specification and this Detail Specification, formally agreed with specific Manufacturers on the basis that the alternative requirements are equivalent to the ESCC requirements and do not affect the components' reliability, are listed in the Appendices attached to this specification.

4.2 DEVIATIONS FROM GENERIC SPECIFICATION

4.2.1 Deviations from Special In-process Controls

None.

4.2.2 Deviations from Final Production Tests (Chart II)

- (a) Para. 9.25, Solderability: Not applicable.

4.2.3 Deviations from Burn-in and Electrical Measurements (Chart III)

Not applicable.

4.2.4 Deviations from Qualification Tests (Chart IV)

- (a) Para. 9.15, Shrinkage shall be less than 5mm.
- (b) Para. 9.24, Soldering: Not applicable.
- (c) Para. 9.25, Solderability: Not applicable.
- (d) Para. 9.10, Anthony & Brown test: Not applicable.
- (e) Para. 9.12, Accelerated Ageing: Para. 9.12.2 is applicable.
- (f) Para. 9.29, Long-term Ageing: test samples shall be aged as free coils (as per Para. 9.12.2).

4.2.5 Deviations from Lot Acceptance Tests (Chart V)

- (a) Para. 9.24, Soldering: Not applicable.
- (b) Para. 9.10, Anthony & Brown test: Not applicable.
- (c) Para. 9.15, Shrinkage shall be less than 5mm.
- (d) Para. 9.25, Solderability: Not applicable.
- (e) Para. 9.12, Accelerated Ageing: Para. 9.12.2 is applicable.

4.3 MECHANICAL REQUIREMENTS

4.3.1 Dimension Check

The dimensions of the finished wires specified herein shall be checked; they shall conform to those shown in Table 1(a), Figure 2 and Para 4.4 of this specification (see below for the list of parameters to be checked).

LIST OF PARAMETERS TO BE CHECKED

Parameter	Table 1(a)	Figure 2	Para. 4.4
<u>COMPOSITION</u>			
Gauge	X		
Insulation		X	
Jacket		X	
<u>CONDUCTOR</u>			
Nature			X
Outer diameter	X		
Number of strands	X		
Strand diameter	X		
Length of lay			X
Nickel thickness			X
<u>INSULATION</u>			
Composition		X	X
Thickness			X
Concentricity			X
Outer diameter	X		
Core identification			X

4.3.2 Weight

The maximum weight of the finished wires specified herein shall be as specified in Table 1(a).

4.4 MATERIALS AND FINISHES

The materials and finishes shall be as specified herein. Where a definite material is not specified, a material which will enable the wires specified herein to meet the performance requirements of this specification shall be used. Acceptance or approval of any constituent material does not guarantee acceptance of the finished product.

4.4.1 Conductor

4.4.1.1 *Material Characteristics*

All strands used in the manufacture of the conductors shall be nickel-plated oxygen-free copper from AWG 0 to 8. On nickel-plated strands, the thickness of the nickel shall be 1.2µm minimum.

On all nickel-plated copper conductors, any strand shall show a 10% minimum elongation.

4.4.1.2 *Stranding*

The conductors shall be rope lay as specified in Table 1(a). Strand and rope members shall be concentrically stranded using unilay concentric (commonly known as "unilay") or counter directional concentric (commonly known as "concentric") constructions.

Concentric stranding shall be defined as a central core surrounded by one or more layers of helically wound strands in a fixed round geometric arrangement.

In "unilay" constructions the successive layers have the same lay direction and lay length.

In "concentric" constructions the lay direction of successive layers are alternately reversed with increasing lay lengths.

The length of lay of the outer layer of stranded members forming the conductor shall be maximum:

- 127mm for AWG 0.
- 77mm for AWG 4.
- 51mm for AWG 8.

In all cases the standard direction of lay of the outer layer is left hand.

4.4.2 Insulation

4.4.2.1 *Material*

The primary insulating material shall be polyimide over expanded polytetrafluoroethylene, both with only those additives that are necessary for processing.

The secondary insulation material shall be virgin perfluoroalcoxy copolymer with only those additives that are necessary for processing and pigmentation.

4.4.2.2 *Construction*

The insulation shall have a uniform cross-section throughout the length of the wire and the conductor shall be evenly centred in the insulation.

The insulation shall consist of 1 wrapped layer of expanded polytetrafluoroethylene tape and 2 wrapped layers of polyimide tapes as specified in Figure 2.

4.4.3 Colour Coding

The colour of the finished wires shall be the following colours of the secondary insulation.

Colours:

- AWG 8: Red.
- AWG 4: Yellow.
- AWG 0: Blue.

4.5 MARKING

4.5.1 General

The marking of all spools of finished wires delivered to this specification shall be in accordance with the requirements of ESCC Basic Specification No. 21700. Each spool shall be marked in respect of:

- (a) The ESCC Component Number.
- (b) Characteristics.
- (c) Traceability Information.
- (d) Additional Marking.

4.5.2 The ESCC Component Number

Each spool shall bear the ESCC Component Number which shall be constituted and marked as follows:

Example: 390101702B

- Detail Specification Number: 3901017
- Type Variant (see Table 1(a)): 02
- Testing Level (B is mandatory): B

4.5.3 Characteristics

The characteristics shall show the length(s) of finished wire wound on each spool and shall be marked as follows:

Example: 100m

- Length in metres (see Note): 100
- Symbol for metres: m

NOTES:

1. Whenever the length is less than 100 metres, insert a zero in the first block (example: 075m). If more than one length of finished wire is wound on a spool, the characteristics of each length shall be marked as above.

4.5.4 Traceability Information

Each spool shall be marked in respect of traceability information in accordance with the requirements of ESCC Basic Specification No. 21700.

4.5.5 Additional Marking

Each spool shall bear the Manufacturer's Quality Control Inspector's stamp.

4.6 ELECTRICAL MEASUREMENTS

4.6.1 Electrical Measurements at Room Temperature

The parameters to be measured at room temperature are scheduled in Table 2. The measurements shall be performed at $T_{amb} = +22 \pm 3$ °C.

4.6.2 Electrical Measurements at High and Low Temperatures

Not applicable.

4.6.3 Circuits for Electrical Measurements

Not applicable.

4.7 BURN-IN TESTS

Not applicable.

4.8 ENVIRONMENTAL AND ENDURANCE TESTS

4.8.1 Mechanical Properties of Conductor

As detailed in Para. 4.4.1.1 of this Specification.

4.8.2 Accelerated Ageing

Ageing Temperature: +230±5 °C.

4.8.3 Wrap Test at Ambient Temperature

The mandrel diameters and applied loads for wrap testing of finished wires are given in Table A.

TABLE A – MANDREL DIAMETERS AND LOADS FOR FINISHED WIRES

Wire Size AWG	Mandrel Diameter (mm)	Applied Weight (kg)
0	100	3.5
4	75	1.8
8	50	1.3

(Table B is not applicable)

4.8.4 Voltage Test

No particular conditions are applicable.

4.8.5 Shrinkage

The shrinkage temperature shall be +200±5 °C. The shrinkage shall be according to Para. 4.2.4 of this specification.

4.8.6 Blocking

The blocking temperature shall be +230±5 °C. Cooling down to room temperature: 16 hours for AWG 0 and 4.

4.8.7 Cold Bend Test

The mandrel diameters and loads shall be as specified in Table C.

TABLE C – MANDREL DIAMETERS AND LOADS FOR FINISHED WIRES

Wire Size AWG	Mandrel Diameter (mm)	Applied Weight (kg)
0	80	3.5
4	60	1.8
8	30	1.3

4.8.8 Cut-through Resistance

The mean load measured during 9 tests shall not be less than the relevant value specified below:

Wire Size AWG Requirements	0	4	8
Cut-through Load (N)	1200	680	800

4.8.9 Notch Resistance

The depth of notch shall be 0.1mm.

4.8.10 Flammability Resistance
No particular conditions are applicable.

4.8.11 Resistance to Fluids
No particular conditions are applicable.

4.8.12 Surface Resistance
No particular conditions are applicable.

4.8.13 Abrasion Resistance
The weight to be applied to the needle is specified below:

Wire Size AWG Requirements	0	4	8
Scrape Abrasion Load (N)	35	17	12

4.8.14 Soldering
Not applicable.

4.8.15 Solderability
Not applicable.

4.8.16 Radiation Resistance
No particular conditions are applicable.

4.8.17 Overload Resistance
No particular conditions are applicable.

4.8.18 Outgassing in Vacuum
No particular conditions are applicable.

4.8.19 Long-term Ageing Test
The long-term ageing temperature shall be $+200\pm 5^{\circ}\text{C}$.

4.8.20 Atomic Oxygen Resistance
The outer surface of the single insulated wires is resistant against atomic oxygen and shall be verified according to the requirements of the ESCC Executive.

TABLE 2 – ELECTRICAL MEASUREMENTS AT ROOM TEMPERATURE

No.	Characteristics	Specification and Test Method	Test Condition	Limits	Unit
1	Conductor Resistance	ESCC No. 3901, Section 9	Para. 9.5	Table 1(a)	Ω/km
2	Spark Test	ESCC No. 3901, Section 9	Para. 9.6	3	kV
3	Voltage Test	ESCC No. 3901, Section 9	Para. 9.7	Para. 9.7	kV
4	Insulation Resistance	ESCC No. 3901, Section 9	Para. 9.8	750	$\text{M}\Omega.\text{km}$
5	Surface Resistance	ESCC No. 3901, Section 9	Para. 9.22	125	$\text{M}\Omega.\text{mm}$