



**TRANSISTORS, POWER, MOSFET, N-CHANNEL,  
RAD-HARD**

**BASED ON TYPE BUY25CS12J-01**

**ESCC Detail Specification No. 5205/026**

|         |            |
|---------|------------|
| Issue 2 | April 2014 |
|---------|------------|



### **LEGAL DISCLAIMER AND COPYRIGHT**

European Space Agency, Copyright © 2014. All rights reserved.

The European Space Agency disclaims any liability or responsibility, to any person or entity, with respect to any loss or damage caused, or alleged to be caused, directly or indirectly by the use and application of this ESCC publication.

This publication, without the prior permission of the European Space Agency and provided that it is not used for a commercial purpose, may be:

- copied in whole, in any medium, without alteration or modification.
- copied in part, in any medium, provided that the ESCC document identification, comprising the ESCC symbol, document number and document issue, is removed.

**DOCUMENTATION CHANGE NOTICE**

(Refer to <https://escies.org> for ESCC DCR content)

| DCR No. | CHANGE DESCRIPTION   |
|---------|--|
| 849     | Specification upissued to incorporate editorial changes per DCR. |

**TABLE OF CONTENTS**

|         |   |    |
|---------|---|----|
| 1       | GENERAL   | 5  |
| 1.1     | SCOPE   | 5  |
| 1.2     | APPLICABLE DOCUMENTS  | 5  |
| 1.3     | TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS                  | 5  |
| 1.4     | THE ESCC COMPONENT NUMBER AND COMPONENT TYPE VARIANTS                 | 5  |
| 1.4.1   | The ESCC Component Number   | 5  |
| 1.4.2   | Component Type Variants   | 5  |
| 1.5     | MAXIMUM RATINGS   | 6  |
| 1.6     | HANDLING PRECAUTIONS  | 7  |
| 1.7     | PHYSICAL DIMENSIONS AND TERMINAL IDENTIFICATION                       | 8  |
| 1.7.1   | Leadless Chip Carrier Package (SMD0.5) - 3 Terminals                  | 8  |
| 1.8     | FUNCTIONAL DIAGRAM  | 9  |
| 1.9     | MATERIALS AND FINISHES  | 9  |
| 2       | REQUIREMENTS  | 9  |
| 2.1     | GENERAL   | 9  |
| 2.1.1   | Deviations from the Generic Specification                             | 9  |
| 2.1.1.1 | Deviations from Screening Tests - Chart F3                            | 9  |
| 2.1.1.2 | Deviations from Qualification and Periodic Tests - Chart F4           | 10 |
| 2.2     | MARKING   | 10 |
| 2.3     | WAFER LOT ACCEPTANCE  | 10 |
| 2.4     | ELECTRICAL MEASUREMENTS AT ROOM, HIGH AND LOW TEMPERATURES            | 10 |
| 2.4.1   | Room Temperature Electrical Measurements                              | 10 |
| 2.4.2   | High and Low Temperatures Electrical Measurements                     | 12 |
| 2.4.3   | Notes to Room, High and Low Temperatures Electrical Measurements      | 12 |
| 2.5     | PARAMETER DRIFT VALUES  | 12 |
| 2.6     | INTERMEDIATE AND END-POINT ELECTRICAL MEASUREMENTS                    | 13 |
| 2.7     | HIGH TEMPERATURE REVERSE BIAS BURN-IN CONDITIONS                      | 14 |
| 2.8     | HIGH TEMPERATURE STEADY-STATE GATE BIAS BURN-IN CONDITIONS            | 14 |
| 2.9     | OPERATING LIFE CONDITIONS   | 14 |
| 2.10    | TOTAL DOSE RADIATION TESTING  | 15 |
| 2.10.1  | Bias Conditions and Total Dose Level for Total Dose Radiation Testing | 15 |
| 2.10.2  | Electrical Measurements for Total Dose Radiation Testing              | 15 |

## 1 GENERAL

### 1.1 SCOPE

This specification details the ratings, physical and electrical characteristics and test and inspection data for the component type variants and/or the range of components specified below. It supplements the requirements of, and shall be read in conjunction with, the ESCC Generic Specification listed under Applicable Documents.

### 1.2 APPLICABLE DOCUMENTS

The following documents form part of this specification and shall be read in conjunction with it:

- (a) ESCC Generic Specification No. 5000
- (b) MIL-STD-750, Test Methods and Procedures for Semiconductor Devices
- (c) MIL-STD-883, Test Method Standard Microelectronics

### 1.3 TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS

For the purpose of this specification, the terms, definitions, abbreviations, symbols and units specified in ESCC Basic Specification No. 21300 shall apply.

### 1.4 THE ESCC COMPONENT NUMBER AND COMPONENT TYPE VARIANTS

#### 1.4.1 The ESCC Component Number

The ESCC Component Number shall be constituted as follows:

Example: 520502601R

- Detail Specification Reference: 5205026
- Component Type Variant Number: 01
- Total Dose Radiation Level Letter: R (as required)

#### 1.4.2 Component Type Variants

The component type variants applicable to this specification are as follows:

| Variant Number | Based on Type | Case (Note 1) | Weight max (g) | Total Dose Radiation Level Letter (Note 2) |
|----------------|---------------|---------------|----------------|--|
| 01             | BUY25CS12J-01 | SMD0.5        | 1.1            | R [100kRAD(Si)]                            |

#### NOTES:

1. See Physical Dimensions and Terminal Identification.
2. Total dose radiation level letters are defined in ESCC Basic Specification No. 22900. If an alternative radiation test level is specified in the Purchase Order the letter shall be changed accordingly.

1.5 MAXIMUM RATINGS


The maximum ratings shall not be exceeded at any time during use or storage.

Maximum ratings shall only be exceeded during testing to the extent specified in this specification and when stipulated in Test Methods and Procedures of the ESCC Generic Specification.

| Characteristics                      | Symbols       | Maximum Ratings | Units                | Remarks   |
|--------------------------------------|---------------|-----------------|----------------------|---|
| Drain-Source Voltage                 | $V_{DS}$      | 250             | V                    | Note 1  |
| Gate-Source Voltage                  | $V_{GS}$      | $\pm 20$        | V                    |   |
| Drain Current (Continuous)           | $I_{DS}$      | 12.4            | A                    | At $T_{case} \leq +25\text{ }^{\circ}\text{C}$<br>Notes 1, 2, 3 |
| Drain Current (Continuous)           | $I_{DS}$      | 8               | A                    | At $T_{case} = +100\text{ }^{\circ}\text{C}$<br>Notes 2, 3      |
| Drain Current (Pulsed)               | $I_{DM}$      | 50              | Apk                  | At $T_{case} \leq +25\text{ }^{\circ}\text{C}$<br>Notes 1, 2    |
| Power Dissipation                    | $P_{tot}$     | 75              | W                    | Note 4  |
| Avalanche Energy (Single Pulse)      | $E_{AS}$      | 60              | mJ                   |   |
| Operating Temperature Range          | $T_{op}$      | -55 to +150     | $^{\circ}\text{C}$   | $T_{amb}$   |
| Storage Temperature Range            | $T_{stg}$     | -55 to +150     | $^{\circ}\text{C}$   |   |
| Junction Temperature                 | $T_j$         | +150            | $^{\circ}\text{C}$   |   |
| Soldering Temperature                | $T_{sol}$     | +250            | $^{\circ}\text{C}$   | Note 5  |
| Thermal Resistance, Junction-to-Case | $R_{th(j-c)}$ | 1.66            | $^{\circ}\text{C/W}$ |   |

**NOTES:**

1. Safe Operating Area applies as follows:



2.  $T_{case}$  is measured on the PCB at the soldering point to the Drain terminal.
3. For  $T_{case} > +25^{\circ}\text{C}$ , derate as follows:

$$I_{DS} = \sqrt{\frac{T_{jmax} - T_{case}}{(R_{th(j-c)}) \times (r_{DS(on)} \text{ at } T_{jmax})}}$$

where  $(r_{DS(on)} \text{ at } T_{jmax}) = 490\text{m}\Omega$ .

4. For  $T_{case} > +25^{\circ}\text{C}$ , derate linearly to 0W at  $T_{case} = +150^{\circ}\text{C}$ .
5. Duration 10 seconds maximum and the same terminal shall not be resoldered until 3 minutes have elapsed.


#### 1.6 HANDLING PRECAUTIONS

These devices are susceptible to damage by electrostatic discharge. Therefore, suitable precautions shall be employed for protection during all phases of manufacture, testing, packaging, shipment and any handling.

These components are categorised as Class 1 per ESCC Basic Specification No. 23800 with a Minimum Critical Path Failure Voltage of 1000V.

1.7 PHYSICAL DIMENSIONS AND TERMINAL IDENTIFICATION

1.7.1 Leadless Chip Carrier Package (SMD0.5) - 3 Terminals




| Symbols | Dimensions mm |       |
|---------|---------------|-------|
|         | Min           | Max   |
| A       | 7.35          | 7.69  |
| B       | 9.97          | 10.41 |
| C       | -             | 3.3   |
| D       | 7.14          | 7.39  |
| E       | 5.59          | 5.84  |
| F       | 0.76          | -     |
| G       | 2.92          | 3.18  |
| H       | 0.76          | -     |
| I       | 2.29          | 2.54  |

**NOTES:**

1. Terminal identification: terminal 1 = Drain, terminal 2 = Gate, terminal 3 = Source.

## 1.8 FUNCTIONAL DIAGRAM

Terminal 1: Drain  
Terminal 2: Gate  
Terminal 3: Source



### **NOTES:**

1. The case is not connected to any terminal.

## 1.9 MATERIALS AND FINISHES

Materials and finishes shall be as follows:

- (a) Case  
The case shall be hermetically sealed and have a ceramic/metal body.
- (b) Terminals  
The terminal material and finish shall be Q14 in accordance with the requirements of ESCC Basic Specification No. 23500.

## 2 REQUIREMENTS

### 2.1 GENERAL

The complete requirements for procurement of the components specified herein are as stated in this specification and the ESCC Generic Specification. Permitted deviations from the Generic Specification, applicable to this specification only, are listed below.

Permitted deviations from the Generic Specification and this Detail Specification, formally agreed with specific Manufacturers on the basis that the alternative requirements are equivalent to the ESCC requirement and do not affect the component's reliability, are listed in the appendices attached to this specification.

#### 2.1.1 Deviations from the Generic Specification

##### 2.1.1.1 *Deviations from Screening Tests - Chart F3*

- (a) Verification of Safe Operating Area: The Safe Operating Area shall be verified by performing the Thermal Impedance ( $Z_{th(j-s)}$ )  $\Delta V_{SD}$  test specified in Room Temperature Electrical Measurements.
- (b) Particle Impact Noise Detection may be performed at any point after Temperature Cycling, prior to Seal.
- (c) Power Burn-in: A high temperature steady-state gate bias test (HTGB) shall be performed instead of Power Burn-in.

2.1.1.2 *Deviations from Qualification and Periodic Tests - Chart F4*

(a) Terminal Strength is not applicable.

2.2 **MARKING**

The marking shall be in accordance with the requirements of ESCC Basic Specification No. 21700 and as follows.

The information to be marked on the component shall be:

- (a) The ESCC qualified components symbol (for ESCC qualified components only).
- (b) The ESCC Component Number.
- (c) Traceability information.

2.3 **WAFER LOT ACCEPTANCE**

A SEM inspection shall be performed as specified in the ESCC Generic Specification.

2.4 **ELECTRICAL MEASUREMENTS AT ROOM, HIGH AND LOW TEMPERATURES**

Electrical measurements shall be performed at room, high and low temperatures. Consolidated notes are given after the tables.

2.4.1 **Room Temperature Electrical Measurements**

Unless otherwise specified, the measurements shall be performed at  $T_{amb} = +25 \pm 3 \text{ }^\circ\text{C}$ .

| Characteristics                       | Symbols       | MIL-STD-750 Test Method | Test Conditions                                     | Limits |      | Units              |
|---------------------------------------|---------------|-------------------------|---|--------|------|--------------------|
|                                       |               |                         |   | Min.   | Max. |                    |
| Drain-to-Source Breakdown Voltage     | $V_{(BR)DSS}$ | 3407                    | $V_{GS} = 0V, I_D = 0.25mA$<br>Bias condition C     | 250    | -    | V                  |
| Gate-to-Source Threshold Voltage      | $V_{GS(th)}$  | 3403                    | $V_{DS} \geq V_{GS}, I_D = 1mA$                     | 2      | 4    | V                  |
| Gate-to-Source Leakage Current        | $I_{GSS}$     | 3411                    | $V_{GS} = \pm 20V, V_{DS} = 0V$<br>Bias condition C | -100   | +100 | nA                 |
| Drain Current                         | $I_{DSS}$     | 3413                    | $V_{GS} = 0V, V_{DS} = 200V$<br>Bias condition C    | -      | 25   | $\mu A$            |
| Static Drain-to-Source On Resistance  | $r_{DS(on)}$  | 3421                    | $V_{GS} = 10V, I_D = 8A$<br>Note 1                  | -      | 130  | m $\Omega$         |
| Source-to-Drain Diode Forward Voltage | $V_{SD}$      | 4011                    | $V_{GS} = 0V, I_{SD} = 12.4A$<br>Note 1             | -      | 1.2  | V                  |
| Thermal Impedance                     | $Z_{th(j-c)}$ | 3161                    | Note 2  | -      | 1.14 | $^\circ\text{C/W}$ |

| Characteristics              | Symbols      | MIL-STD-750<br>Test Method | Test Conditions  | Limits |      | Units |
|------------------------------|--------------|----------------------------|--|--------|------|-------|
|                              |              |                            |  | Min.   | Max. |       |
| Turn-on Delay Time           | $t_{d(on)}$  | 3472                       | $V_{GS} = 10V, R_G = 4.7\Omega$<br>$V_{DS} = 125V, I_D = 8A$<br>Note 3   | -      | 25   | ns    |
| Rise Time                    | $t_r$        | 3472                       | $V_{GS} = 10V, R_G = 4.7\Omega$<br>$V_{DS} = 125V, I_D = 8A$<br>Note 3   | -      | 25   | ns    |
| Turn-off Delay Time          | $t_{d(off)}$ | 3472                       | $V_{GS} = 10V, R_G = 4.7\Omega$<br>$V_{DS} = 125V, I_D = 8A$<br>Note 3   | -      | 35   | ns    |
| Fall Time                    | $t_f$        | 3472                       | $V_{GS} = 10V, R_G = 4.7\Omega$<br>$V_{DS} = 125V, I_D = 8A$<br>Note 3   | -      | 20   | ns    |
| Reverse Recovery Time        | $t_{rr}$     | 3473                       | $V_{DD} \leq 50V,$<br>$di/dt = 100A/\mu s$<br>$I_{SD} = 12.4A$<br>Note 3 | -      | 400  | ns    |
| Input Capacitance            | $C_{iss}$    | 3431                       | $V_{GS} = 0V, V_{DS} = 100V$<br>$f = 1MHz$<br>Note 3                     | 1.3    | 1.9  | nF    |
| Output Capacitance           | $C_{oss}$    | 3453                       | $V_{GS} = 0V, V_{DS} = 100V$<br>$f = 1MHz$<br>Note 3                     | 90     | 150  | pF    |
| Reverse Transfer Capacitance | $C_{rss}$    | 3433                       | $V_{GS} = 0V, V_{DS} = 100V$<br>$f = 1MHz$<br>Note 3                     | 1      | 6    | pF    |
| Total Gate Charge            | $Q_g$        | 3471                       | $V_{GS} = 10V,$<br>$V_{DS} = 125V, I_D = 12.4A$<br>Note 3                | -      | 42   | nC    |
| Gate-to-Source Charge        | $Q_{gs}$     | 3471                       | $V_{GS} = 10V,$<br>$V_{DS} = 125V, I_D = 12.4A$<br>Note 3                | -      | 15   | nC    |
| Gate-to-Drain Charge         | $Q_{gd}$     | 3471                       | $V_{GS} = 10V,$<br>$V_{DS} = 125V, I_D = 12.4A$<br>Note 3                | -      | 15   | nC    |

2.4.2 High and Low Temperatures Electrical Measurements

| Characteristics                      | Symbols      | MIL-STD-750 Test Method | Test Conditions Note 4   | Limits |      | Units      |
|--------------------------------------|--------------|-------------------------|--|--------|------|------------|
|                                      |              |                         |  | Min    | Max  |            |
| Gate-to-Source Threshold Voltage     | $V_{GS(th)}$ | 3403                    | $T_{amb} = +125 (+0 -5) ^\circ C$<br>$V_{DS} \geq V_{GS}, I_D = 1mA$                     | 1.5    | -    | V          |
|                                      |              |                         | $T_{amb} = -55 (+5 -0) ^\circ C$<br>$V_{DS} \geq V_{GS}, I_D = 1mA$                      | -      | 5    | V          |
| Gate-to-Source Leakage Current       | $I_{GSS}$    | 3411                    | $T_{amb} = +125 (+0 -5) ^\circ C$<br>$V_{GS} = \pm 20V, V_{DS} = 0V$<br>Bias condition C | -200   | +200 | nA         |
| Drain Current                        | $I_{DSS}$    | 3413                    | $T_{amb} = +125 (+0 -5) ^\circ C$<br>$V_{GS} = 0V, V_{DS} = 200V$<br>Bias condition C    | -      | 250  | $\mu A$    |
| Static Drain-to-Source On Resistance | $r_{DS(on)}$ | 3421                    | $T_{amb} = +125 (+0 -5) ^\circ C$<br>$V_{GS} = 10V, I_D = 8A$<br>Note 1                  | -      | 300  | m $\Omega$ |

2.4.3 Notes to Room, High and Low Temperatures Electrical Measurements

1. Pulsed measurement: Pulse Width  $\leq 300\mu s$ , Duty Cycle  $\leq 2\%$ .
2. The  $Z_{th(j-c)}$  limit is guaranteed by performing a  $\Delta V_{SD}$  (go-no-go) test. The following test conditions and limits shall apply:
  - $V_{DS} = 20V$
  - $t_M < 75\mu s$
  - $I_M = 10mA$
  - $t_H = 25ms$
  - $I_H = 1.2A$
  - $V_{SD} = 40mV$  minimum, 60mV maximum
3. Read and record measurements shall be performed on a sample of 32 components with 0 failures allowed. Alternatively a 100% inspection may be performed.
4. Read and record measurements shall be performed on a sample of 5 components with 0 failures allowed. Alternatively a 100% inspection may be performed.

2.5 PARAMETER DRIFT VALUES

Unless otherwise specified, the measurements shall be performed at  $T_{amb} = +25 \pm 3 ^\circ C$ .

The test methods and test conditions shall be as per the corresponding test defined in Room Temperature Electrical Measurements.

The drift values ( $\Delta$ ) shall not be exceeded for each characteristic specified. The corresponding absolute limit values for each characteristic shall not be exceeded.

| Characteristics                               | Symbols      | Limits                            |          |      | Units      |
|---|--------------|-----------------------------------|----------|------|------------|
|   |              | Drift Value $\Delta$              | Absolute |      |            |
|   |              |                                   | Min      | Max  |            |
| Gate-to-Source Threshold Voltage              | $V_{GS(th)}$ | $\pm 20\%$                        | 2        | 4    | V          |
| Gate-to-Source Leakage Current                | $I_{GSS}$    | $\pm 20$<br>or (1)<br>$\pm 100\%$ | -100     | +100 | nA         |
| Drain Current                                 | $I_{DSS}$    | $\pm 10$<br>or (1)<br>$\pm 100\%$ | -        | 25   | $\mu A$    |
| Static Drain-to-Source On Resistance (Note 2) | $r_{DS(on)}$ | $\pm 20\%$ (3)                    | -        | 130  | m $\Omega$ |

**NOTES:**

1. Whichever is the greater.
2. Measured only prior to HTRB Burn-in and after HTGB Burn-in.
3. Referred to the measurement prior to HTRB Burn-in.

2.6 INTERMEDIATE AND END-POINT ELECTRICAL MEASUREMENTS

Unless otherwise specified, the measurements shall be performed at  $T_{amb} = +25 \pm 3 \text{ }^\circ\text{C}$ .

The test methods and test conditions shall be as per the corresponding test defined in Room Temperature Electrical Measurements.

The limit values for each characteristic shall not be exceeded.

| Characteristics                      | Symbols      | Limits                            |          |      | Units      |
|--------------------------------------|--------------|-----------------------------------|----------|------|------------|
|                                      |              | Drift Value $\Delta$              | Absolute |      |            |
|                                      |              |                                   | Min      | Max  |            |
| Gate-to-Source Threshold Voltage     | $V_{GS(th)}$ | $\pm 20\%$                        | 2        | 4    | V          |
| Gate-to-Source Leakage Current       | $I_{GSS}$    | $\pm 20$<br>or (1)<br>$\pm 100\%$ | -100     | +100 | nA         |
| Drain Current                        | $I_{DSS}$    | $\pm 10$<br>or (1)<br>$\pm 100\%$ | -        | 25   | $\mu A$    |
| Static Drain-to-Source On Resistance | $r_{DS(on)}$ | $\pm 20\%$                        | -        | 130  | m $\Omega$ |

**NOTES:**

1. Whichever is greater.

**2.7 HIGH TEMPERATURE REVERSE BIAS BURN-IN CONDITIONS**

HTRB Burn-in shall be performed in accordance with MIL-STD-750, Test Method 1042, Test Condition A with the following conditions:

| Characteristics         | Symbols   | Test Conditions | Units |
|-------------------------|-----------|-----------------|-------|
| Ambient Temperature     | $T_{amb}$ | +150 (+0 -5)    | °C    |
| Drain-to-Source Voltage | $V_{DS}$  | 200 (Note 1)    | V     |
| Gate-to-Source Voltage  | $V_{GS}$  | 0               | V     |
| Duration                | t         | 240 minimum     | hours |

**NOTES:**

1. Voltage may be switched off during cool down.

**2.8 HIGH TEMPERATURE STEADY-STATE GATE BIAS BURN-IN CONDITIONS**

HTGB Burn-in shall be performed in accordance with MIL-STD-750, Test Method 1042, Test Condition B with the following conditions:

| Characteristics         | Symbols   | Test Conditions | Units |
|-------------------------|-----------|-----------------|-------|
| Ambient Temperature     | $T_{amb}$ | +150 (+0 -5)    | °C    |
| Drain-to-Source Voltage | $V_{DS}$  | 0               | V     |
| Gate-to-Source Voltage  | $V_{GS}$  | 16              | V     |
| Duration                | t         | 48 minimum      | hours |

**2.9 OPERATING LIFE CONDITIONS**

Operating Life shall consist of High Temperature Reverse Bias in accordance with MIL-STD-750, Test Method 1042, Test Condition A, followed by High Temperature Steady-State Gate Bias in accordance with MIL-STD-750, Test Method 1042, Test Condition B. The test conditions are as follows:

High Temperature Reverse Bias Conditions

| Characteristics         | Symbols   | Test Conditions | Units |
|-------------------------|-----------|-----------------|-------|
| Ambient Temperature     | $T_{amb}$ | +150 (+0 -5)    | °C    |
| Drain-to-Source Voltage | $V_{DS}$  | 200 (Note 1)    | V     |
| Gate-to-Source Voltage  | $V_{GS}$  | 0               | V     |
| Duration                | t         | 1000 minimum    | Hours |

High Temperature Steady-State Gate Bias Conditions

| Characteristics         | Symbols   | Test Conditions | Units |
|-------------------------|-----------|-----------------|-------|
| Ambient Temperature     | $T_{amb}$ | +150 (+0 -5)    | °C    |
| Drain-to-Source Voltage | $V_{DS}$  | 0               | V     |
| Gate-to-Source Voltage  | $V_{GS}$  | 16              | V     |
| Duration                | t         | 1000 minimum    | hours |

**NOTES:**

1. Voltage may be switched off during cool down.

2.10 TOTAL DOSE RADIATION TESTING

2.10.1 Bias Conditions and Total Dose Level for Total Dose Radiation Testing

The following bias condition shall be used during irradiation testing:

$V_{GS} = +15V$

$V_{DS} = 0V$

The total dose level applied shall be as specified in Component Type Variants herein or in the Purchase Order.

2.10.2 Electrical Measurements for Total Dose Radiation Testing

Prior to irradiation testing the devices shall have successfully met Room Temperature Electrical Measurements specified herein.

Unless otherwise stated the measurements shall be performed at  $T_{amb} = +25 \pm 3 \text{ }^\circ\text{C}$ .

Unless otherwise specified the test methods and test conditions shall be as per the corresponding test defined in Room Temperature Electrical Measurements.

The parameters to be measured during and on completion of irradiation testing are shown below.

| Characteristics                   | Symbols       | Limits                    |          |      | Units         |
|-----------------------------------|---------------|---------------------------|----------|------|---------------|
|                                   |               | Drift Values ( $\Delta$ ) | Absolute |      |               |
|                                   |               |                           | Min      | Max  |               |
| Drain-to-Source Breakdown Voltage | $V_{(BR)DSS}$ | $\pm 20\%$                | 250      | -    | V             |
| Gate-to-Source Threshold Voltage  | $V_{GS(th)}$  | +10%, -50%                | 2        | 4    | V             |
| Gate-to-Source Leakage Current    | $I_{GSS}$     | $\pm 20$                  | -100     | +100 | nA            |
| Drain Current                     | $I_{DSS}$     | -                         | -        | 25   | $\mu\text{A}$ |

| Characteristics                       | Symbols      | Limits                       |          |     | Units      |
|---------------------------------------|--------------|------------------------------|----------|-----|------------|
|                                       |              | Drift Values<br>( $\Delta$ ) | Absolute |     |            |
|                                       |              |                              | Min      | Max |            |
| Static Drain-to-Source On Resistance  | $r_{DS(on)}$ | $\pm 20\%$                   | -        | 130 | m $\Omega$ |
| Source-to-Drain Diode Forward Voltage | $V_{SD}$     | $\pm 10\%$                   | -        | 1.2 | V          |

**APPENDIX 'A'**  
**AGREED DEVIATIONS FOR INFINEON TECHNOLOGIES (D)**

| ITEMS AFFECTED  | DESCRIPTION OF DEVIATIONS  |
|---|--|
| Deviations from Production Control (Chart F2)               | The 3 component sample Dimension Check need only be performed once on each component package production lot.   |
| Deviations from Screening Tests (Chart F3)                  | Temperature Cycling shall be performed in accordance with MIL-STD-883, Test Method 1010, Test Condition C, 20 cycles at maximum storage temperature rating specified in the Detail Specification.  |
|   | High and Low Temperatures Electrical Measurements may be performed at any point after High Temperature Steady-State Gate Bias Burn-in, prior to Seal, but shall still count towards Check for Lot Failure.   |
|   | Radiographic Inspection is not applicable.   |
|   | Seal, Fine Leak shall be performed in accordance with MIL-STD-883, Test Method 1014, Test Condition A1 or A2.  |
|   | Solderability is not applicable unless otherwise stipulated in the Purchase Order.   |
| Deviations from Qualification and Periodic Tests (Chart F4) | Temperature Cycling shall be performed in accordance with MIL-STD-883, Test Method 1010, Test Condition C, 100 cycles at maximum storage temperature rating specified in the Detail Specification.   |
|   | Seal, Fine Leak shall be performed in accordance with MIL-STD-883, Test Method 1014, Test Condition A1 or A2.  |
| Room Temperature Electrical Measurements                    | The read and record 32 component sample electrical measurements for characteristics $t_{d(on)}$ , $t_r$ , $t_{d(off)}$ , $t_f$ , $t_{rr}$ , $C_{iss}$ , $C_{oss}$ , $C_{riss}$ , $Q_g$ , $Q_{gs}$ and $Q_{gd}$ need only be performed once on each wafer lot used to supply components to this specification. Any failure shall result in rejection of the wafer lot. The sample measurement may be performed at any time during production. |
| Marking   | For the purposes of marking of the ESCC Component Number on the body of the component, the Variant Number may be marked as a single digit (e.g. 1 for Variant 01). Otherwise the full ESCC Component Number shall be used.   |

**ADDITIONAL DATA - INFINEON TECHNOLOGIES (D)**

- (a) Derating for Space Application  
These components are susceptible to Single Event Gate Rupture if operated in a space environment unless the following derating is applied:

