



TRANSISTORS, MATCHED DUAL, PNP

BASED ON TYPE 2N3350

ESCC Detail Specification No. 5207/003

Issue 6	February 2026
---------	---------------



LEGAL DISCLAIMER AND COPYRIGHT

European Space Agency, Copyright © 2026. All rights reserved.

The European Space Agency disclaims any liability or responsibility, to any person or entity, with respect to any loss or damage caused, or alleged to be caused, directly or indirectly by the use and application of this ESCC publication.

This publication, without the prior permission of the European Space Agency and provided that it is not used for a commercial purpose, may be:

- copied in whole, in any medium, without alteration or modification.
- copied in part, in any medium, provided that the ESCC document identification, comprising the ESCC symbol, document number and document issue, is removed.

DOCUMENTATION CHANGE NOTICE

(Refer to <https://escies.org> for ESCC DCR content)

DCR No.	CHANGE DESCRIPTION
1788	Specification updated to incorporate changes per DCR.

TABLE OF CONTENTS

1	GENERAL	5
1.1	SCOPE	5
1.2	APPLICABLE DOCUMENTS	5
1.3	TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS	5
1.4	THE ESCC COMPONENT NUMBER AND COMPONENT	5
1.4.1	The ESCC Component Number	5
1.4.2	Component Type Variants	5
1.5	MAXIMUM RATINGS	6
1.6	PHYSICAL DIMENSIONS AND TERMINAL IDENTIFICATION	7
1.6.1	Metal Can Package (TO-77) - 6 lead	7
1.6.2	Chip Carrier Package (CCP) - 6 terminal	8
1.7	FUNCTIONAL DIAGRAM	9
1.8	MATERIALS AND FINISHES	9
2	REQUIREMENTS	9
2.1	GENERAL	9
2.1.1	Deviations from the Generic Specification	9
2.2	MARKING	10
2.3	TERMINAL STRENGTH	10
2.4	ELECTRICAL MEASUREMENTS AT ROOM, HIGH AND LOW TEMPERATURES	10
2.4.1	Room Temperature Electrical Measurements	10
2.4.2	High and Low Temperatures Electrical Measurements	12
2.5	PARAMETER DRIFT VALUES	12
2.6	INTERMEDIATE AND END-POINT ELECTRICAL MEASUREMENTS	13
2.7	HIGH TEMPERATURE REVERSE BIAS BURN-IN CONDITIONS	13
2.8	POWER BURN-IN CONDITIONS	13
2.9	OPERATING LIFE CONDITIONS	13
	APPENDIX A	14

1 GENERAL

1.1 SCOPE

This specification details the ratings, physical and electrical characteristics and test and inspection data for the component type variants and/or the range of components specified below. It supplements the requirements of, and shall be read in conjunction with, the ESCC Generic Specification listed under Applicable Documents.

1.2 APPLICABLE DOCUMENTS

The following documents form part of this specification and shall be read in conjunction with it:

- (a) ESCC Generic Specification No. [5000](#)
- (b) [MIL-STD-750](#), Test Methods and Procedures for Semiconductor Devices

1.3 TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS

For the purpose of this specification, the terms, definitions, abbreviations, symbols and units specified in ESCC Basic Specification No. [21300](#) shall apply.

1.4 THE ESCC COMPONENT NUMBER AND COMPONENT

1.4.1 The ESCC Component Number

The ESCC Component Number shall be constituted as follows:

Example: 520700302

- Detail Specification Reference: 5207003
- Component Type Variant Number: 02 (as required)

1.4.2 Component Type Variants

The component type variants applicable to this specification are as follows:

Variant No.	Based on Type	Case	Lead/Terminal Material and/or Finish	Weight max g
02	2N3350	TO-77	D3 or D4	0.95
03	2N3350	TO-77	D7	0.95
04	2N3350	CCP	2	0.2
05	2N3350	CCP	4	0.2

The lead/terminal material and/or finish shall be in accordance with the requirements of ESCC Basic Specification No. [23500](#).

1.5 MAXIMUM RATINGS

The maximum ratings shall not be exceeded at any time during use or storage.

Maximum ratings shall only be exceeded during testing to the extent specified in this specification and when stipulated in Test Methods and Procedures of the ESCC Generic Specification.


Characteristics	Symbols	Maximum Ratings	Unit	Remarks
Collector-Base Voltage	V_{CBO}	-60	V	Over entire operating temperature range
Collector-Emitter Voltage	V_{CEO}	-45	V	
Emitter-Base Voltage	V_{EBO}	-6	V	
Collector Current	I_C	30	mA	Continuous
Power Dissipation (One Section)				
For TO-77 and CCP	P_{totO1}	0.3	W	At $T_{amb} \leq +25^{\circ}C$
For TO-77	P_{totO2}	0.6	W	At $T_{case} \leq +25^{\circ}C$
Power Dissipation (Both Sections)				
For TO-77 and CCP	P_{totB1}	0.6	W	At $T_{amb} \leq +25^{\circ}C$
For TO-77	P_{totB2}	1.2	W	At $T_{case} \leq +25^{\circ}C$
Thermal Resistance, Junction-to-Ambient	$R_{th(j-a)}$	583.3 291.7	$^{\circ}C/W$	For one section For both sections
Thermal Resistance, Junction-to-Case	$R_{th(j-c)}$	291.7 145.8	$^{\circ}C/W$	For one section For both sections Note 1
Operating Temperature Range	T_{op}	-55 to +200	$^{\circ}C$	Note 2
Storage Temperature Range	T_{stg}	-65 to +200	$^{\circ}C$	Note 2
Soldering Temperature	T_{sol}		$^{\circ}C$	
For TO-77		+260		Note 3
For CCP		+245		Note 4

NOTES:

1. Thermal Resistance, Junction-to-Case only applies to TO-77 packaged Variants.
2. For Variants with tin-lead plating or hot solder dip lead finish all testing, and any handling, performed at $T_{amb} > +125^{\circ}C$ shall be carried out in a 100% inert atmosphere.
3. Duration 10 seconds maximum at a distance of not less than 1.5mm from the device body and the same lead shall not be resoldered until 3 minutes have elapsed.
4. Duration 5 seconds maximum and the same terminal shall not be resoldered until 3 minutes have elapsed.

1.6 PHYSICAL DIMENSIONS AND TERMINAL IDENTIFICATION

1.6.1 Metal Can Package (TO-77) - 6 lead




Symbols	Dimensions mm		Notes
	Min	Max	
A	6.1	6.6	
$\varnothing b$	0.406	0.533	2, 3
$\varnothing b2$	0.406	0.483	2, 3
$\varnothing D$	8.51	9.4	
$\varnothing D1$	7.75	8.51	
e	5.08 BSC		4
e1	2.54 BSC		4
h	-	1.02	
j	0.711	0.864	
k	0.737	1.14	5
L	12.7	-	2
L1	-	1.27	3
L2	6.35	-	3
α	45° BSC		1, 4, 6

NOTES:

- Terminal identification is specified by reference to the tab position where lead 1 = collector 1, lead 2 = base 1, lead 3 = emitter 1, lead 5 = emitter 2, lead 6 = base 2 and lead 7 = collector 2. Lead numbers 4 and 8 are not present on the actual package; they are shown in the drawing for information only.
- Applies to all leads.
- $\varnothing b2$ applies between $L1$ and $L2$. $\varnothing b$ applies between $L2$ and 12.7mm from the seating plane. Diameter is uncontrolled within $L1$ and beyond 12.7mm from the seating plane.
- Leads having maximum diameter 0.483mm measured in the gauging plane 1.37 (+0.025, -0)mm below the seating plane of the device shall be within 0.178mm of their true position relative to a maximum-width-tab.
- Measured from the maximum diameter of the actual device.
- Tab centreline.

1.6.2 Chip Carrier Package (CCP) - 6 terminal




Symbols	Dimensions mm		Notes
	Min	Max	
A	1.53	1.96	
C	0.89 TYPICAL		2
D	1.52	1.78	
D1	2.08	2.49	
E	1.24	1.55	
F	5.76	5.92	
G	4.19	4.45	
I	6.1	6.35	
L	0.55	0.71	2
M	3.86	4.01	
N	1.14	1.4	
N1	2.41	2.67	
N2	0.89 TYPICAL		
r	0.23 TYPICAL		2

NOTES:

- Terminal identification is specified, when viewing the top side of the package, by reference to a black ink dot adjacent to terminal 1 = base 2. Terminal 2 = collector 2, terminal 3 = emitter 2, terminal 4 = emitter 1, terminal 5 = collector 1 and terminal 6 = base 1.
- Applies to all terminals.

1.7 FUNCTIONAL DIAGRAM



NOTES:

1. For TO-77, the case is not connected to any lead.
2. For CCP, the lid is not connected to any terminal.

1.8 MATERIALS AND FINISHES

Materials and finishes shall be as follows:

- (a) Case
For the metal can package the case shall be hermetically sealed and have a metal body with hard glass seals.
For the chip carrier package the case shall be hermetically sealed and have a ceramic body with a Kovar lid.
- (b) Leads/Terminals
As specified in Para. 1.4.2, Component Type Variants.

2 REQUIREMENTS

2.1 GENERAL

The complete requirements for procurement of the components specified herein are as stated in this specification and the ESCC Generic Specification. Permitted deviations from the Generic Specification, applicable to this specification only, are listed below.

Permitted deviations from the Generic Specification and this Detail Specification, formally agreed with specific Manufacturers on the basis that the alternative requirements are equivalent to the ESCC requirement and do not affect the component's reliability, are listed in the appendices attached to this specification.

2.1.1 Deviations from the Generic Specification

None.

2.2 MARKING

The marking shall be in accordance with the requirements of ESCC Basic Specification No. 21700 and as follows.

The information to be marked on the component shall be:

- (a) Terminal identification (see Para. 1.6.2).
- (b) The ESCC qualified components symbol (for ESCC qualified components only).
- (c) The ESCC Component Number (see Para. 1.4.1).
- (d) Traceability information.

2.3 TERMINAL STRENGTH

The test conditions for terminal strength, tested as specified in the ESCC Generic Specification, shall be as follows:

- For TO-77, Test Condition: E, lead fatigue.

2.4 ELECTRICAL MEASUREMENTS AT ROOM, HIGH AND LOW TEMPERATURES

Electrical measurements shall be performed at room, high and low temperatures.

2.4.1 Room Temperature Electrical Measurements

The measurements shall be performed at $T_{amb} = +22 \pm 3^{\circ}C$.

Characteristics	Symbols	MIL-STD-750 Test Method	Test Conditions	Limits		Units
				Min	Max	
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	3001	$I_C = -10\mu A$ Bias Condition D	-60	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	3011	$I_C = -10mA$ Bias Condition D Note 1	-45	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	3026	$I_E = -10\mu A$ Bias Condition D	-6	-	V
Collector-Base Cut-off Current	I_{CBO}	3036	$V_{CB} = -45V$ Bias Condition D	-	-10	nA
Emitter-Base Cut-off Current	I_{EBO}	3061	$V_{EB} = -5V$ Bias Condition D	-	-2	nA
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	3071	$I_C = -10mA, I_B = -500\mu A$ Note 1	-	-500	mV
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	3066	$I_C = -10mA, I_B = -1mA$ Test Condition A Note 1	-	900	mV
Forward-Current Transfer Ratio	h_{FE1}	3076	$I_C = -10\mu A; V_{CE} = -5V$	100	300	-
	h_{FE2}		$I_C = -1mA; V_{CE} = -5V$	150	-	-
Forward-Current Transfer Ratio Comparison	h_{FE1-1}/h_{FE1-2}	3076	$I_C = -10\mu A; V_{CE} = -5V$	0.9	1.1	-
Base-Emitter Voltage Differential	$ V_{BE1} - V_{BE2} $	3066	$I_C = -10\mu A, V_{CE} = -5V$ Test Condition B	-	5	mV

Characteristics	Symbols	MIL-STD-750 Test Method	Test Conditions	Limits		Units
				Min	Max	
Current Gain Bandwidth Product	f_T	3206	$I_C = -1\text{mA}$, $V_{CE} = -5\text{V}$ $f = 30\text{MHz}$ Note 2	60	240	MHz
Small-Signal Short-Circuit Forward-Current Transfer Ratio	h_{fe}	3206	$I_C = -1\text{mA}$, $V_{CE} = -5\text{V}$ $f = 1\text{kHz}$ Note 2	150	600	-
Output Capacitance	C_{obo}	3236	$V_{CB} = -5\text{V}$, $I_E = 0\text{A}$ $f = 1\text{MHz}$ Note 2	-	6	pF
Input Capacitance	C_{ib}	3240	$V_{EB} = -500\text{mV}$ $I_C = 0\text{A}$ $f = 1\text{MHz}$ Note 2	-	12	pF
Small-Signal Input Impedance	h_{ie}	3201	$I_C = -1\text{mA}$, $V_{CE} = -5\text{V}$ $f = 1\text{kHz}$ Note 2	3.7	20	k Ω
Small-Signal Output Impedance	h_{oe}	3216	$I_C = -1\text{mA}$, $V_{CE} = -5\text{V}$ $f = 1\text{kHz}$ Note 2	-	100	μmho
Noise Figure	NF	3246	$I_C = -10\text{mA}$, $V_{CE} = -5\text{V}$ $R_S = 10\text{k}\Omega$ $BW = 15.7\text{kHz}$ Note 2	-	4	dB

NOTES:

1. Pulse measurement: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.
2. For AC characteristics read and record measurements shall be performed on a sample of 32 components with 0 failures allowed. Alternatively a 100% inspection may be performed.

2.4.2 High and Low Temperatures Electrical Measurements

Characteristics	Symbols	MIL-STD-750 Test Method	Test Conditions Note 1	Limits		Units
				Min	Max	
Collector-Base Cut-off Current	I_{CBO}	3036	$T_{amb} = +150 (+0 -5)^{\circ}C$ $V_{CB} = -45V$ Bias Condition D	-	-10	μA
Forward-Current Transfer Ratio 2	h_{FE2}	3076	$T_{amb} = -55 (+5 -0)^{\circ}C$ $I_C = -1mA$ $V_{CE} = -5V$	70	-	-
Forward-Current Transfer Ratio Comparison	$h_{FE1-1}/$ h_{FE1-2}	3076	$T_{amb} = -55$ to $+125^{\circ}C$ $I_C = -10\mu A$; $V_{CE} = -5V$	0.9	1.1	-
Base-Emitter Voltage Differential Change	$ \Delta(V_{BE1}-V_{BE2})\Delta T_{amb} 1$	3066	$T_{amb} = -55 (+5 -0)^{\circ}C$ to $+25 \pm 3^{\circ}C$ $I_C = -10\mu A$, $V_{CE} = -5V$	-	800	mV
	$ \Delta(V_{BE1}-V_{BE2})\Delta T_{amb} 2$	3066	$T_{amb} = +25 \pm 3^{\circ}C$ to $+125 (+5 -0)^{\circ}C$ $I_C = -10\mu A$, $V_{CE} = -5V$	-	1000	

NOTES:

1. Read and record measurements shall be performed on a sample of 5 components with 0 failures allowed. Alternatively a 100% inspection may be performed.

2.5 PARAMETER DRIFT VALUES

Unless otherwise specified, the measurements shall be performed at $T_{amb} = +22 \pm 3^{\circ}C$.

The test methods and test conditions shall be as per the corresponding test defined in Para. 2.4.1, Room Temperature Electrical Measurements.

The drift values (Δ) shall not be exceeded for each characteristic specified. The corresponding absolute limit values for each characteristic shall not be exceeded.

Characteristics	Symbols	Limits			Units
		Drift Value Δ	Absolute		
			Min	Max	
Collector-Base Cut-off Current	I_{CBO}	± 1.5	-	-10	nA
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	± 15 or (1) $\pm 15\%$	-	-500	mV
Forward-Current Transfer Ratio 1	h_{FE1}	$\pm 15\%$	100	300	-

NOTES:

1. Whichever is the greater referred to the initial value.

2.6 INTERMEDIATE AND END-POINT ELECTRICAL MEASUREMENTS

Unless otherwise specified, the measurements shall be performed at $T_{amb} = +22 \pm 3^{\circ}C$.

The test methods and test conditions shall be as per the corresponding test defined in either Para. 2.4.1, Room Temperature Electrical Measurements or Para. 2.4.2, High and Low Temperature Electrical Measurements, as applicable.

The limit values for each characteristic shall not be exceeded.

Characteristics	Symbols	Limits		Units
		Min	Max	
Collector-Base Cut-off Current	I_{CBO}	-	-10	nA
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	-	-500	mV
Forward-Current Transfer Ratio 1	h_{FE1}	100	300	-
Forward-Current Transfer Ratio Comparison	h_{FE1-1}/h_{FE1-2}	0.85	1.15	-
Base-Emitter Voltage Differential	$ V_{BE1}-V_{BE2} $	-	5	mV
Base-Emitter Voltage Differential Change (Note 1)	$ \Delta(V_{BE1}-V_{BE2})\Delta T_{amb} 1$	-	1	mV
	$ \Delta(V_{BE1}-V_{BE2})\Delta T_{amb} 2$	-	1.2	

NOTES:

1. To be measured after Operating Life test only.

2.7 HIGH TEMPERATURE REVERSE BIAS BURN-IN CONDITIONS

Characteristics	Symbols	Test Conditions	Units
Case Temperature	T_{case}	+150 (+0 -5)	$^{\circ}C$
Collector-Base Voltage	V_{CB}	-60	V
Emitter-Base Voltage	V_{EB}	-6	V
Duration	t	72 minimum	hrs

2.8 POWER BURN-IN CONDITIONS

Characteristics	Symbols	Test Conditions	Units
Ambient Temperature	T_{amb}	+25 to +50	$^{\circ}C$
Power Dissipation (Both Sections)	P_{totB}	As per Para. 1.5, Maximum Ratings. Derate P_{totB1} at the chosen T_{amb} using the specified $R_{th(j-a)}$.	W
Collector-Base Voltage	V_{CB}	-30	V

2.9 OPERATING LIFE CONDITIONS

The conditions shall be as specified in Para. 2.8, Power Burn-in Conditions.

APPENDIX A
AGREED DEVIATIONS FOR STMICROELECTRONICS (F)

ITEMS AFFECTED	DESCRIPTION OF DEVIATIONS
Para. 2.1.1, Deviations from the Generic Specification: Para. 8, Test Methods and Procedures	For qualification and qualification maintenance, or procurement of qualified or unqualified components, the following replacement test method specifications shall be used instead of the following ESCC Basic Specifications: <ul style="list-style-type: none"> • No. 20500, External Visual Inspection: replaced by MIL-STD-750 Test Method 2071. • No. 20900, Radiographic Inspection of Electronic Components: replaced by MIL-STD-750 Test Method 2076.
Para. 2.1.1, Deviations from the Generic Specification: Deviations from Production Control - Chart F2	Special In-Process Controls - Internal Visual Inspection. For CCP packages the criteria specified for voids in the fillet and minimum die mounting material around the visible die perimeter for die mounting defects may be omitted providing that a radiographic inspection to verify the die-attach process is performed on a sample basis in accordance with STMicroelectronics procedure 0076637.
Para. 2.1.1, Deviations from the Generic Specification: Deviations from Screening Tests - Chart F3	Solderability is not applicable unless specifically stipulated in the Purchase Order.
Para. 2.4.1, Room Temperature Electrical Measurements	All AC characteristics (Para. 2.4.1, Note 2) may be considered guaranteed but not tested if successful pilot lot testing has been performed on the wafer lot which includes AC characteristic measurements per the Detail Specification. A summary of the pilot lot testing shall be provided if required by the Purchase Order.
Para. 2.4.2, High and Low Temperatures Electrical Measurements	All characteristics specified may be considered guaranteed but not tested if successful pilot lot testing has been performed on the wafer lot which includes characteristic measurements at high and low temperatures per the Detail Specification. A summary of the pilot lot testing shall be provided if required by the Purchase Order.