



Page i

**INTEGRATED CIRCUITS, SILICON MONOLITHIC,
BIPOLAR, ADVANCED LOW POWER SCHOTTKY,
SYNCHRONOUS,
4-BIT, UP/DOWN BINARY COUNTERS
(DUAL CLOCK WITH CLEAR),
BASED ON TYPE 54ALS193
ESCC Detail Specification No. 9204/058**

**ISSUE 1
October 2002**



Document Custodian: European Space Agency - see <https://escies.org>

	ESCC Detail Specification		PAGE ii ISSUE 1
---	---------------------------	--	--------------------------

LEGAL DISCLAIMER AND COPYRIGHT

European Space Agency, Copyright © 2002. All rights reserved.

The European Space Agency disclaims any liability or responsibility, to any person or entity, with respect to any loss or damage caused, or alleged to be caused, directly or indirectly by the use and application of this ESCC publication.

This publication, without the prior permission of the European Space Agency and provided that it is not used for a commercial purpose, may be:

- copied in whole in any medium without alteration or modification.
- copied in part, in any medium, provided that the ESCC document identification, comprising the ESCC symbol, document number and document issue, is removed.



european space agency
agence spatiale européenne

Pages 1 to 32

**INTEGRATED CIRCUITS, SILICON MONOLITHIC,
BIPOLAR, ADVANCED LOW POWER SCHOTTKY,
SYNCHRONOUS,
4-BIT, UP/DOWN BINARY COUNTERS
(DUAL CLOCK WITH CLEAR),
BASED ON TYPE 54ALS193
ESA/SCC Detail Specification No. 9204/058**



**space components
coordination group**

Issue/Rev.	Date	Approved by	
		SCCG Chairman	ESA Director General or his Deputy
Issue 2	January 1992	<i>Pommes</i>	<i>J. Lutz</i>
Revision 'A'	June 1994	<i>Pommes</i>	<i>J. Lutz</i>



ESA/SCC Detail Specification
No. 9204/058

Rev. 'A'

PAGE 2

ISSUE 2



DOCUMENTATION CHANGE NOTICE

Rev. Letter	Rev. Date	Reference	CHANGE Item	Approved DCR No.
		This Issue supersedes Issue 1 and incorporates all modifications defined in Revision 'A' to Issue 1 and the following DCR's:- Cover Page DCN Table 1(a) : Lead Material and/or Finish amended Figures 2 : Imperial dimensions and references deleted Figure 2(c) : In drawing, Note 6 corrected to "10" Notes to Figures : Title amended Figure 3(a) : Note 1, amended to read "...Figure 2(b)" Figure 3(a) : Comparison Table added Para. 4.2.2 : Deviation deleted, "None." added Para. 4.2.4 : Deviation deleted, "None." added Para. 4.2.5 : Deviation deleted, "None." added Para. 4.4.2 : Paragraph amended Para. 4.5.2 : Amended to read "...Figure 2(b)" Para. 4.5.3 : "Type Variant, as applicable" amended to refer to Table 1(a) Para. 4.6.3 : Reference to functional test sequence deleted Para. 4.7.1 : Expanded to identify the stated temperature as T_{amb} Tables 2, 3 : Nos. 10 to 17 and 18 to 25, in Conditions Pins C4 corrected to "5" : Nos. 26 to 31, in Conditions Pins C corrected to "2-12-13-14-18-19" Table 2 a.c. : Nos. 59 to 122, Symbols suffixes added Figures 4(a), (c) : Figures corrected Figure 4(f) : Note 2 added Figure 4(h) : In Note 3, gate corrected to "counter" Para. 4.8 : Title expanded		None None 22881 22881 23456 22881 22881 22881 21048 22919 22919 22881 22881 23455 23455 23455 23456 23456 23456 23456 23455
'A'	June '94	P1. Cover Page P2. DCN P16. Para. 4.3.2	: Weights amended	None None 221047



TABLE OF CONTENTS

	<u>Page</u>
1. <u>GENERAL</u>	5
1.1 Scope	5
1.2 Component Type Variants	5
1.3 Maximum Ratings	5
1.4 Parameter Derating Information	5
1.5 Physical Dimensions	5
1.6 Pin Assignment	5
1.7 Function Sequences	5
1.8 Circuit Schematic	5
1.9 Functional Diagram	5
2. <u>APPLICABLE DOCUMENTS</u>	15
3. <u>TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS</u>	15
4. <u>REQUIREMENTS</u>	15
4.1 General	15
4.2 Deviations from Generic Specification	15
4.2.1 Deviations from Special In-process Controls	15
4.2.2 Deviations from Final Production Tests	15
4.2.3 Deviations from Burn-in Tests	15
4.2.4 Deviations from Qualification Tests	15
4.2.5 Deviations from Lot Acceptance Tests	16
4.3 Mechanical Requirements	16
4.3.1 Dimension Check	16
4.3.2 Weight	16
4.4 Materials and Finishes	16
4.4.1 Case	16
4.4.2 Lead Material and Finish	16
4.5 Marking	16
4.5.1 General	16
4.5.2 Lead Identification	16
4.5.3 The SCC Component Number	17
4.5.4 Traceability Information	17
4.6 Electrical Measurements	17
4.6.1 Electrical Measurements at Room Temperature	17
4.6.2 Electrical Measurements at High and Low Temperatures	17
4.6.3 Circuits for Electrical Measurements	17
4.7 Burn-in Tests	17
4.7.1 Parameter Drift Values	17
4.7.2 Conditions for Power Burn-in	17
4.7.3 Electrical Circuits for Power Burn-in	17
4.8 Environmental and Endurance Tests	30
4.8.1 Electrical Measurements on Completion of Environmental Tests	30
4.8.2 Electrical Measurements at Intermediate Points during Endurance Tests	30
4.8.3 Electrical Measurements on Completion of Endurance Tests	30
4.8.4 Conditions for Operating Life Tests	30
4.8.5 Electrical Circuits for Operating Life Tests	30
4.8.6 Conditions for High Temperature Storage Test	30

 	<p>ESA/SCC Detail Specification No. 9204/058</p>		<p>PAGE 4 ISSUE 2</p>
---	--	--	---------------------------

TABLES



1(a)	Type Variants	6
1(b)	Maximum Ratings	6
2	Electrical Measurements at Room Temperature, d.c. Parameters	18
	Electrical Measurements at Room Temperature, a.c. Parameters	20
3	Electrical Measurements at High and Low Temperatures	22
4	Parameter Drift Values	28
5	Conditions for Power Burn-in and Operating Life Test	28
6	Electrical Measurements on Completion of Environmental Tests and at Intermediate Points and on Completion of Endurance Tests	31

FIGURES

1	Not applicable	
2	Physical Dimensions	7
3(a)	Pin Assignment	11
3(b)	Functional Sequences	12
3(c)	Circuit Schematic	13
3(d)	Functional Diagram	14
4	Circuits for Electrical Measurements	24
5	Electrical Circuit for Power Burn-in and Operating Life Test	29

APPENDICES (Applicable to specific Manufacturers only)

'A'	Agreed Deviations for Texas Instruments (F)	32
-----	---	----

 	<p>ESA/SCC Detail Specification No. 9204/058</p>	<p>PAGE 5 ISSUE 2</p>
---	--	---------------------------

1. GENERAL

1.1 SCOPE

This specification details the ratings, physical and electrical characteristics, test and inspection data for a silicon monolithic, bipolar, advanced low power Schottky, Synchronous, 4-Bit, Up/Down Binary Counter (Dual Clock with Clear), based on Type 54ALS193. It shall be read in conjunction with ESA/SCC Generic Specification No. 9000, the requirements of which are supplemented herein.

1.2 COMPONENT TYPE VARIANTS

Variants of the basic type integrated circuits specified herein, which are also covered by this specification, are given in Table 1(a).

1.3 MAXIMUM RATINGS

The maximum ratings, which shall not be exceeded at any time during use or storage, applicable to the integrated circuits specified herein, are as scheduled in Table 1(b).

1.4 PARAMETER DERATING INFORMATION (FIGURE 1)

Not applicable.

1.5 PHYSICAL DIMENSIONS

The physical dimensions of the integrated circuits specified herein are shown in Figure 2.

1.6 PIN ASSIGNMENT

As per Figure 3(a).

1.7 FUNCTION SEQUENCES

As per Figure 3(b).

1.8 CIRCUIT SCHEMATIC

As per Figure 3(c).

1.9 FUNCTIONAL DIAGRAM

As per Figure 3(d).


	<p>ESA/SCC Detail Specification No. 9204/058</p>		<p>PAGE 6 ISSUE 2</p>
---	--	--	---------------------------

TABLE 1(a) - TYPE VARIANTS

VARIANT	CASE	FIGURE	LEAD MATERIAL AND/OR FINISH
01	FLAT	2(a)	D7
02	FLAT	2(a)	G4
03	CCP	2(b)	7
04	CCP	2(b)	4
05	DIL	2(c)	D7
06	DIL	2(c)	G4

TABLE 1(b) - MAXIMUM RATINGS


NO.	CHARACTERISTICS	SYMBOL	MAXIMUM RATINGS	UNIT	REMARKS
1	Supply Voltage	V_{CC}	- 0.5 to 7.0	V	-
2	Input Voltage	V_{IN}	- 0.5 to 7.0	V	Note 1
3	Device Dissipation	P_D	121	mWdc	Note 2
4	Operating Temperature Range	T_{op}	- 55 to + 125	°C	-
5	Storage Temperature Range	T_{stg}	- 65 to + 150	°C	-
6	Soldering Temperature For FP and DIP For CCP	T_{sol}	+ 265 + 245	°C	Note 3 Note 4

NOTES

1. Input Current limited to - 18mA.
2. Must withstand added P_D due to short circuit conditions (i.e. I_{OS}) at 1 output for 5 seconds.
3. Duration 10 seconds maximum at a distance of not less than 1.5mm from the package and the same lead shall not be resoldered until 3 minutes have elapsed.
4. Duration 5 seconds maximum and the same terminal shall not be resoldered until 3 minutes have elapsed.

FIGURE 2 - PHYSICAL DIMENSIONS

FIGURE 2(a) - FLAT PACKAGE




SYMBOL	MILLIMETRES		NOTES
	MIN	MAX	
A	1.24	2.03	
b	0.38	0.48	8
c	0.08	0.15	8
D	9.65	11.02	
E	6.10	6.60	
E1	-	7.11	4
e	1.27 TYPICAL		5, 9
L	6.35	9.40	
L1	19.05	-	
Q	0.25	0.89	2
S	0.25	0.76	7

NOTES: See Page 10.

FIGURE 2 - PHYSICAL DIMENSIONS (CONTINUED)

FIGURE 2(b) - SQUARE CHIP CARRIER PACKAGE (3 LAYER BASE)




SYMBOL	MILLIMETRES		NOTES
	MIN	MAX	
A	8.687	9.093	
B	7.798	9.093	
C	0.250	0.510	11
D	0.889	1.143	12
E	1.140	1.400	8
F	0.559	0.712	8
G	1.27 TYPICAL		5, 9
H	1.630	2.540	

NOTES: See Page 10.

FIGURE 2 - PHYSICAL DIMENSIONS (CONTINUED)

FIGURE 2(c) - DUAL-IN-LINE PACKAGE



SYMBOL	MILLIMETRES		NOTES
	MIN	MAX	
A	-	5.08	
b	0.38	0.58	8
b1	-	1.78	8
c	0.203	0.356	8
D	19.18	19.94	
E	6.22	7.11	
E1	7.37	7.87	4
e	2.54 TYPICAL		6, 9
G	0.305	-	13
H	0.76	-	14
L	3.30	5.08	
Q	0.51	2.03	3
S	0.38	1.27	7
a	0°	15°	10

NOTES: See Page 10.


	<p>ESA/SCC Detail Specification No. 9204/058</p>	<p>PAGE 10 ISSUE 2</p>
---	--	----------------------------

FIGURE 2 - PHYSICAL DIMENSIONS (CONTINUED)

NOTES TO FIGURES 2(a) TO 2(c) INCLUSIVE

1. Index area; a notch or dot shall be located adjacent to Pin 1 and shall be within the shaded area shown. For chip carrier packages the index shall be as defined in Figure 2(b).
2. Dimension Q shall be measured at the point of exit of the lead from the body.
3. Dimension Q shall be measured from the seating plane to the base plane.
4. This dimension allows for off-centre lids, meniscus and glass overrun.
5. The true position pin or terminal spacing is 1.27mm between centrelines. Each pin centreline shall be located within $\pm 0.13\text{mm}$ of its true longitudinal position relative to Pins 1 and 16.
6. The true position pin spacing is 2.54mm between centrelines. Each pin centreline shall be located within $\pm 0.25\text{mm}$ of its true longitudinal position relative to Pins 1 and the highest pin number.
7. Applies to all 4 corners.
8. All leads or terminals.
9. 14 spaces for dual-in-line packages.
16 spaces for chip carrier packages.
10. Lead centre when α is 0° .
11. Index corner only - 2 dimensions.
12. 3 non-index corners - 6 dimensions.
13. 4 Terminals.
14. 12 Terminals.




FLAT PACKAGE AND DUAL-IN-LINE PIN OUTS	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
CHIP CARRIER PIN OUTS	2	3	4	5	7	8	9	10	12	13	14	15	17	18	19	20

**FIGURE 3(b) - FUNCTION SEQUENCES**

(Typical clear, preset, count and inhibit sequence)

Illustrated below is the following sequence:-

1. Clear outputs to 0.
2. Load (Preset) to binary 13.
3. Count up to 14, 15, carry, 0, 1 and 2.
4. Count down to 1, 0, borrow, 15, 14, and 13.

**NOTES**

1. Clear overrides load, data, and count inputs.
2. When counting up, count-down input must be high; when counting down, count-up input must be high.



FIGURE 3(c) - CIRCUIT SCHEMATIC








FIGURE 3(d) - FUNCTIONAL DIAGRAM



 	<p>ESA/SCC Detail Specification No. 9204/058</p>		<p>PAGE 15 ISSUE 2</p>
---	--	--	----------------------------

2. APPLICABLE DOCUMENTS

The following documents form part of this specification and shall be read in conjunction with it:-

- (a) ESA/SCC Generic Specification No. 9000 for Integrated Circuits.
- (b) MIL-STD-883, Test Methods and Procedures for Micro-electronics.

3. TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS

For the purpose of this specification, the terms, definitions, abbreviations, symbols and units specified in ESA/SCC Basic Specification No. 21300 shall apply. In addition, the following abbreviation is used:-

$I_{OS/2}$ - One half of the true output short circuit current.

4. REQUIREMENTS

4.1 GENERAL

The complete requirements for procurement of the integrated circuits specified herein shall be as stated in this specification and ESA/SCC Generic Specification No. 9000 for Integrated Circuits. Deviations from the Generic Specification, applicable to this specification only, are listed in Para. 4.2.

Deviations from the applicable Generic Specification and this Detail Specification, formally agreed with specific Manufacturers on the basis that the alternative requirements are equivalent to the ESA/SCC requirements and do not affect the components' reliability, are listed in the appendices attached to this specification.

4.2 DEVIATIONS FROM GENERIC SPECIFICATION

4.2.1 Deviations from Special In-process Controls

None.

4.2.2 Deviations from Final Production Tests (Chart II)

None.

4.2.3 Deviations from Burn-in Tests (Chart III)

- (a) Para. 7.1.1(a), "High Temperature Reverse Bias" test and subsequent electrical measurements related to this test shall be omitted.
- (b) Para. 9.9.2, "Electrical Measurements at High and Low Temperatures": Only a test result summary, based on go-no-go tests and presented in histogram form, is required.

4.2.4 Deviations from Qualification Tests (Chart IV)

None.



4.2.5 Deviations from Lot Acceptance Tests (Chart V)

None.

4.3 MECHANICAL REQUIREMENTS

4.3.1 Dimension Check

The dimensions of the integrated circuits specified herein shall be checked. They shall conform to those shown in Figure 2.

4.3.2 Weight

The maximum weight of the integrated circuits specified herein shall be 0.7 grammes for the flat package, 0.6 grammes for the chip carrier package and 2.2 grammes for the dual-in-line package.

4.4 MATERIALS AND FINISHES

The materials and finishes shall be as specified herein. Where a definite material is not specified, a material which will enable the integrated circuits specified herein to meet the performance requirements of this specification shall be used. Acceptance or approval of any constituent material does not guarantee acceptance of the finished product.

4.4.1 Case

The case shall be hermetically sealed and have a metal body with hard glass seals or a ceramic body and the lids shall be welded, brazed, preform-soldered or glass frit-sealed.

4.4.2 Lead Material and Finish

For dual-in-line and flat packages, the material shall be either Type 'D' or Type 'G' with either Type '4' or Type '7' finish in accordance with the requirements of ESA/SCC Basic Specification No. 23500. For chip carrier packages, the finish shall be either Type '4' or Type '7' in accordance with the requirements of ESA/SCC Basic Specification No. 23500. (See Table 1(a) for Type Variants).

4.5 MARKING



4.5.1 General

The marking of all components delivered to this specification shall be in accordance with the requirements of ESA/SCC Basic Specification No. 21700. Each component shall be marked in respect of:-

- (a) Lead Identification.
- (b) The SCC Component Number.
- (c) Traceability Information.

4.5.2 Lead Identification

For dual-in-line and flat packages, an index shall be located at the top of the package in the position defined in Note 1 to Figure 2 or, alternatively, a tab may be used to identify Pin No. 1. The pin numbering must be read with the index or tab on the left-hand side. For chip carrier packages, the index shall be as defined by Figure 2(b).

 	<p>ESA/SCC Detail Specification No. 9204/058</p>		<p>PAGE 17 ISSUE 2</p>
---	--	--	----------------------------

4.5.3 The SCC Component Number

Each component shall bear the SCC Component Number which shall be constituted and marked as follows:

920405802B

Detail Specification Number _____

Type Variant (see Table 1(a)) _____

Testing Level (B or C, as applicable) _____

4.5.4 Traceability Information

Each component shall be marked in respect of traceability information in accordance with the requirements of ESA/SCC Basic Specification No. 21700.

4.6 ELECTRICAL MEASUREMENTS

4.6.1 Electrical Measurements at Room Temperature

The parameters to be measured in respect of electrical characteristics are scheduled in Table 2. Unless otherwise specified, the measurements shall be performed at $T_{amb} = +22 \pm 3$ °C.

4.6.2 Electrical Measurements at High and Low Temperatures

The parameters to be measured at high and low temperatures are scheduled in Table 3. The measurements shall be performed at $T_{amb} = +125(+0 - 5)$ °C and $-55(+5 - 0)$ °C respectively.

4.6.3 Circuits for Electrical Measurements

Circuits for use in performing electrical measurements listed in Tables 2 and 3 of this specification are shown in Figure 4.

4.7 BURN-IN TESTS

4.7.1 Parameter Drift Values

The parameter drift values applicable to burn-in are as specified in Table 4 of this specification. Unless otherwise stated, the measurements shall be performed at $T_{amb} = +22 \pm 3$ °C. The parameter drift values (Δ) applicable to the parameters scheduled, shall not be exceeded. In addition to these drift value requirements, the appropriate limit value specified for a given parameter in Table 2 shall not be exceeded.

4.7.2 Conditions for Power Burn-in

The requirements for power burn-in are specified in Section 7 of ESA/SCC Generic Specification No. 9000. The conditions for power burn-in shall be as specified in Table 5 of this specification.

4.7.3 Electrical Circuits for Power Burn-in

Circuits for use in performing the power burn-in tests are shown in Figure 5 of this specification.



		<p>ESA/SCC Detail Specification</p> <p>No. 9204/058</p>		<p>PAGE 18</p> <p>ISSUE 2</p>
--	--	---	--	-------------------------------

TABLE 2 - ELECTRICAL MEASUREMENTS AT ROOM TEMPERATURE - d.c. PARAMETERS

NO.	CHARACTERISTICS	SYMBOL	TEST METHOD MIL-STD 883	TEST FIG.	TEST CONDITIONS (PINS UNDER TEST D/F = DIP AND FP C = CCP)	LIMITS		UNIT
						MIN	MAX	
1	Functional Test	-	-	3(b)	Verify Truth Table with Load. Note 1	-	-	-
2 to 9	Input Current High Level	I_{IH1}	3010	4(a)	$V_{CC} = 5.5V$, $V_{IN} = 2.7V$ (Pins D/F 1-4-5-9-10-11-14-15) (Pins C 2-5-7-12-13-14-18-19)	-	20	μA
10 to 17	Input Current High Level (Max. Input Voltage)	I_{IH2}	3010	4(a)	$V_{CC} = 5.5V$, $V_{IN} = 7.0V$ (Pins D/F 1-4-5-9-10-11-14-15) (Pins C 2-5-7-12-13-14-18-19)	-	100	μA
18 to 25	Input Clamp Voltage	V_{IC}	3008	4(b)	$V_{CC} = 4.5V$, $I_{IN} = -18mA$ Note 2 (Pins D/F 1-4-5-9-10-11-14-15) (Pins C 2-5-7-12-13-14-18-19)	-	-1.5	V
26 to 31	Input Current Low Level at Data Inputs, Load and Clear	I_{IL1}	3009	4(c)	$V_{CC} = 5.5V$, $V_{IL} = 0.4V$ (Pins D/F 1-9-10-11-14-15) (Pins C 2-12-13-14-18-19)	-	-100	μA
32 to 33	Input Current Low Level at Up and Down	I_{IL2}	3009	4(c)	$V_{CC} = 5.5V$, $V_{IL} = 0.4V$ (Pins D/F 4-5) (Pins C 5-7)	-	-200	μA
34 to 39	Output Voltage Low Level	V_{OL}	3007	4(d)	$V_{CC} = 4.5V$ $V_{IL} = 0.7V$, $I_{OL} = 4.0mA$ (Pins D/F 2-3-6-7-12-13) (Pins C 3-4-8-9-15-17)	-	0.4	V
40 to 45	Output Voltage High Level 1	V_{OH1}	3006	4(e)	$V_{CC} = 4.5V$, $V_{IH} = 2.0V$ $V_{IL} = 0.7V$, $I_{OH} = -400\mu A$ (Pins D/F 2-3-6-7-12-13) (Pins C 3-4-8-9-15-17)	2.5	-	V

NOTES: See Page 21.



 	ESA/SCC Detail Specification No. 9204/058		PAGE 19 ISSUE 2
---	--	--	--------------------

TABLE 2 - ELECTRICAL MEASUREMENTS AT ROOM TEMPERATURE - d.c. PARAMETERS (CONT'D)

NO.	CHARACTERISTICS	SYMBOL	TEST METHOD MIL-STD 883	TEST FIG.	TEST CONDITIONS (PINS UNDER TEST D/F = DIP AND FP C = CCP)	LIMITS		UNIT
						MIN	MAX	
46 to 51	Output Voltage High Level 2	V_{OH2}	3006	4(e)	$V_{CC} = 5.5V$, $V_{IH} = 2.0V$ $V_{IL} = 0.7V$, $I_{OH} = -400\mu A$ (Pins D/F 2-3-6-7-12-13) (Pins C 3-4-8-9-15-17)	3.5	-	V
52 to 57	One Half of the True Output Short Circuit Current	$I_{OS/2}$	3011	4(f)	$V_{CC} = 5.5V$, $V_{OUT} = 2.25V$ Note 3 (Pins D/F 2-3-6-7-12-13) (Pins C 3-4-8-9-15-17)	- 30	- 112	mA
58	Supply Current	I_{CC}	3005	4(g)	$V_{CC} = 5.5V$ Note 4 (Pin D/F 16) (Pin C 20)	-	22	mA

NOTES: See Page 21.


	SCC	ESA/SCC Detail Specification No. 9204/058	PAGE 20 ISSUE 2
--	------------	--	--------------------

TABLE 2 - ELECTRICAL MEASUREMENTS AT ROOM TEMPERATURE - a.c. PARAMETERS

NO.	CHARACTERISTICS	SYMBOL	TEST METHOD MIL-STD 883	TEST FIG.	TEST CONDITIONS (PINS UNDER TEST D/F = DIP AND FP C = CCP) (NOTE 5)	LIMITS		UNIT
						MIN	MAX	
59 to 60	Propagation Delay Low to High Level Up to $\overline{C0}$	t_{PLH1}	3003	4(h)	$V_{CC} = 4.5$ and $5.5V$ $C_L = 50pF$, $R_L = 500\Omega$ <u>Pins D/F</u> <u>Pins C</u> 5 to 12 7 to 15	4.0	19	ns
61 to 62	Propagation Delay High to Low Level Up to $\overline{C0}$	t_{PHL1}	3003	4(h)	$V_{CC} = 4.5$ and $5.5V$ $C_L = 50pF$, $R_L = 500\Omega$ <u>Pins D/F</u> <u>Pins C</u> 5 to 12 7 to 15	5.0	21	ns
63 to 64	Propagation Delay Low to High Level Down to $\overline{B0}$	t_{PLH2}	3003	4(h)	$V_{CC} = 4.5$ and $5.5V$ $C_L = 50pF$, $R_L = 500\Omega$ <u>Pins D/F</u> <u>Pins C</u> 4 to 13 5 to 17	4.0	19	ns
65 to 66	Propagation Delay High to Low Level Down to $\overline{B0}$	t_{PHL2}	3003	4(h)	$V_{CC} = 4.5$ and $5.5V$ $C_L = 50pF$, $R_L = 500\Omega$ <u>Pins D/F</u> <u>Pins C</u> 4 to 13 5 to 17	5.0	21	ns
67 to 82	Propagation Delay Low to High Level Down or Up to Any Q	t_{PLH3}	3003	4(h)	$V_{CC} = 4.5$ and $5.5V$ $C_L = 50pF$, $R_L = 500\Omega$ <u>Pins D/F</u> <u>Pins C</u> 4 to 2 5 to 3 4 to 3 5 to 4 4 to 6 5 to 8 4 to 7 5 to 9 5 to 2 7 to 3 5 to 3 7 to 4 5 to 6 7 to 8 5 to 7 7 to 9	4.0	23	ns
83 to 98	Propagation Delay High to Low Level Down or Up to Any Q	t_{PHL3}	3003	4(h)	$V_{CC} = 4.5$ and $5.5V$ $C_L = 50pF$, $R_L = 500\Omega$ <u>Pins D/F</u> <u>Pins C</u> 4 to 2 5 to 3 4 to 3 5 to 4 4 to 6 5 to 8 4 to 7 5 to 9 5 to 2 7 to 3 5 to 3 7 to 4 5 to 6 7 to 8 5 to 7 7 to 9	4.0	20	ns

NOTES: See Page 21




 SCC	ESA/SCC Detail Specification No. 9204/058	PAGE 21 ISSUE 2
---	--	--------------------

TABLE 2 - ELECTRICAL MEASUREMENTS AT ROOM TEMPERATURE - a.c. PARAMETERS (CONT'D)

NO.	CHARACTERISTICS	SYMBOL	TEST METHOD MIL-STD 883	TEST FIG.	TEST CONDITIONS (PINS UNDER TEST D/F = DIP AND FP C = CCP) (NOTE 5)	LIMITS		UNIT																				
						MIN	MAX																					
99 to 106	Propagation Delay Low to High Level Load to Any Q	t _{PLH4}	3003	4(h)	V _{CC} = 4.5 and 5.5V C _L = 50pF R _L = 500Ω <table><tr><td colspan="2">Pins D/F</td><td colspan="2">Pins C</td></tr><tr><td>11 to 2</td><td>14 to 3</td><td>14 to 3</td><td>3</td></tr><tr><td>11 to 3</td><td>14 to 4</td><td>14 to 4</td><td>4</td></tr><tr><td>11 to 6</td><td>14 to 8</td><td>14 to 8</td><td>8</td></tr><tr><td>11 to 7</td><td>14 to 9</td><td>14 to 9</td><td>9</td></tr></table>	Pins D/F		Pins C		11 to 2	14 to 3	14 to 3	3	11 to 3	14 to 4	14 to 4	4	11 to 6	14 to 8	14 to 8	8	11 to 7	14 to 9	14 to 9	9	8.0	35	ns
Pins D/F		Pins C																										
11 to 2	14 to 3	14 to 3	3																									
11 to 3	14 to 4	14 to 4	4																									
11 to 6	14 to 8	14 to 8	8																									
11 to 7	14 to 9	14 to 9	9																									
107 to 114	Propagation Delay High to Low Level Load to Any Q	t _{PHL4}	3003	4(h)	V _{CC} = 4.5 and 5.5V C _L = 50pF R _L = 500Ω <table><tr><td colspan="2">Pins D/F</td><td colspan="2">Pins C</td></tr><tr><td>11 to 2</td><td>14 to 3</td><td>14 to 3</td><td>3</td></tr><tr><td>11 to 3</td><td>14 to 4</td><td>14 to 4</td><td>4</td></tr><tr><td>11 to 6</td><td>14 to 8</td><td>14 to 8</td><td>8</td></tr><tr><td>11 to 7</td><td>14 to 9</td><td>14 to 9</td><td>9</td></tr></table>	Pins D/F		Pins C		11 to 2	14 to 3	14 to 3	3	11 to 3	14 to 4	14 to 4	4	11 to 6	14 to 8	14 to 8	8	11 to 7	14 to 9	14 to 9	9	8.0	31	ns
Pins D/F		Pins C																										
11 to 2	14 to 3	14 to 3	3																									
11 to 3	14 to 4	14 to 4	4																									
11 to 6	14 to 8	14 to 8	8																									
11 to 7	14 to 9	14 to 9	9																									
115 to 122	Propagation Delay High to Low Level CLR to Any Q	t _{PHL5}	3003	4(h)	V _{CC} = 4.5 and 5.5V C _L = 50pF R _L = 500Ω <table><tr><td colspan="2">Pins D/F</td><td colspan="2">Pins C</td></tr><tr><td>14 to 2</td><td>18 to 3</td><td>18 to 3</td><td>3</td></tr><tr><td>14 to 3</td><td>18 to 4</td><td>18 to 4</td><td>4</td></tr><tr><td>14 to 6</td><td>18 to 8</td><td>18 to 8</td><td>8</td></tr><tr><td>14 to 7</td><td>18 to 9</td><td>18 to 9</td><td>9</td></tr></table>	Pins D/F		Pins C		14 to 2	18 to 3	18 to 3	3	14 to 3	18 to 4	18 to 4	4	14 to 6	18 to 8	18 to 8	8	14 to 7	18 to 9	18 to 9	9	5.0	20	ns
Pins D/F		Pins C																										
14 to 2	18 to 3	18 to 3	3																									
14 to 3	18 to 4	18 to 4	4																									
14 to 6	18 to 8	18 to 8	8																									
14 to 7	18 to 9	18 to 9	9																									
123 to 126	Maximum Clock Frequency	f _{max}	-	4(h)	V _{CC} = 4.5 and 5.5V C _L = 50pF R _L = 500Ω Note 6 (Pins D/F 4-5) (Pins C 5-7)	25	-	MHz																				

NOTES



- Go-no-go test with $V_{IL} = 0.3V$, $V_{IH} = 3.0V$, trip point $1.5V$.
- All inputs and outputs not under test shall be open.
- No more than 1 output should be tested at a time.
- I_{CC} is measured with the Clear and \overline{Load} Grounded and all other Inputs = $4.5V$.
- Propagation delay measurements shall be performed as a go-no-go test on a 100% basis. Read-and-record measurements shall be performed on an LTPD7 sample basis following the Chart III Burn-in Test.
- This parameter shall be tested as go-no-go on a 100% basis.

		ESA/SCC Detail Specification No. 9204/058	PAGE 22 ISSUE 2
--	--	--	--------------------

**TABLE 3 - ELECTRICAL MEASUREMENTS AT HIGH AND LOW TEMPERATURES,
+ 125(+ 0 – 5) °C AND – 55(+ 5 – 0) °C**

NO.	CHARACTERISTICS	SYMBOL	TEST METHOD MIL-STD 883	TEST FIG.	TEST CONDITIONS (PINS UNDER TEST D/F = DIP AND FP C = CCP)	LIMITS		UNIT
						MIN	MAX	
1	Functional Test	-	-	3(b)	Verify Truth Table with Load. Note 1	-	-	-
2 to 9	Input Current High Level	I _{IH1}	3010	4(a)	V _{CC} = 5.5V, V _{IN} = 2.7V (Pins D/F 1-4-5-9-10-11-14-15) (Pins C 2-5-7-12-13-14-18-19)	-	20	μA
10 to 17	Input Current High Level (Max. Input Voltage)	I _{IH2}	3010	4(a)	V _{CC} = 5.5V, V _{IN} = 7.0V (Pins D/F 1-4-5-9-10-11-14-15) (Pins C 2-5-7-12-13-14-18-19)	-	100	μA
18 to 25	Input Clamp Voltage	V _{IC}	3008	4(b)	V _{CC} = 4.5V, I _{IN} = – 18mA Note 2 (Pins D/F 1-4-5-9-10-11-14-15) (Pins C 2-5-7-12-13-14-18-19)	-	– 1.5	V
26 to 31	Input Current Low Level at Data Inputs, Load and Clear	I _{IL1}	3009	4(c)	V _{CC} = 5.5V, V _{IL} = 0.4V (Pins D/F 1-9-10-11-14-15) (Pins C 2-12-13-14-18-19)	-	– 100	μA
32 to 33	Input Current Low Level at Up and Down	I _{IL2}	3009	4(c)	V _{CC} = 5.5V, V _{IL} = 0.4V (Pins D/F 4-5) (Pins C 5-7)	-	– 200	μA
34 to 39	Output Voltage Low Level	V _{OL}	3007	4(d)	V _{CC} = 4.5V V _{IL} = 0.7V, I _{OL} = 4.0mA (Pins D/F 2-3-6-7-12-13) (Pins C 3-4-8-9-15-17)	-	0.4	V
40 to 45	Output Voltage High Level 1	V _{OH1}	3006	4(e)	V _{CC} = 4.5V, V _{IH} = 2.0V V _{IL} = 0.7V, I _{OH} = – 400μA (Pins D/F 2-3-6-7-12-13) (Pins C 3-4-8-9-15-17)	2.5	-	V

NOTES: See Page 21.

 	<p>ESA/SCC Detail Specification No. 9204/058</p>	<p>PAGE 23 ISSUE 2</p>
---	--	----------------------------


**TABLE 3 - ELECTRICAL MEASUREMENTS AT HIGH AND LOW TEMPERATURES,
+ 125(+ 0 – 5) °C AND – 55(+ 5 – 0) °C (CONT'D)**

NO.	CHARACTERISTICS	SYMBOL	TEST METHOD MIL-STD 883	TEST FIG.	TEST CONDITIONS (PINS UNDER TEST D/F = DIP AND FP C = CCP)	LIMITS		UNIT
						MIN	MAX	
46 to 51	Output Voltage High Level 2	V_{OH2}	3006	4(e)	$V_{CC} = 5.5V$, $V_{IH} = 2.0V$ $V_{IL} = 0.7V$, $I_{OH} = -400\mu A$ (Pins D/F 2-3-6-7-12-13) (Pins C 3-4-8-9-15-17)	3.5	-	V
52 to 57	One Half of the True Output Short Circuit Current	$I_{OS/2}$	3011	4(f)	$V_{CC} = 5.5V$, $V_{OUT} = 2.25V$ Note 3 (Pins D/F 2-3-6-7-12-13) (Pins C 3-4-8-9-15-17)	- 30	- 112	mA
58	Supply Current	I_{CC}	3005	4(g)	$V_{CC} = 5.5V$ Note 4 (Pin D/F 16) (Pin C 20)	-	22	mA

NOTES: See Page 21.


FIGURE 4 - CIRCUITS FOR ELECTRICAL MEASUREMENTS

FIGURE 4(a) - INPUT CURRENT HIGH LEVEL **FIGURE 4(b) - INPUT CLAMP VOLTAGE**



NOTES


1. Each input to be tested separately.



NOTES

1. Each input to be tested separately.


FIGURE 4(c) - LOW LEVEL INPUT CURRENT



NOTES

1. Each input to be tested separately.

FIGURE 4(d) - LOW LEVEL OUTPUT VOLTAGE




NOTES

1. Test per Figure 3(b)

FIGURE 4 - CIRCUITS FOR ELECTRICAL MEASUREMENTS (CONTINUED)


FIGURE 4(e) - HIGH LEVEL OUTPUT VOLTAGE



NOTES

1. Test per Figure 3(b).


FIGURE 4(f) - ONE HALF SHORT CIRCUIT OUTPUT CURRENT



NOTES



1. Test per Figure 3(b).
2. No more than 1 output should be tested at a time.



FIGURE 4(g) - SUPPLY CURRENT



NOTES

1. See Note 4 on Page 21.

**FIGURE 4 - CIRCUITS FOR ELECTRICAL MEASUREMENTS (CONTINUED)****FIGURE 4(h) - DYNAMIC TEST AND SWITCHING WAVEFORMS****VOLTAGE WAVEFORMS - SET-UP AND HOLD TIMES****VOLTAGE WAVEFORMS - PULSE WIDTHS**

**FIGURE 4 - CIRCUITS FOR ELECTRICAL MEASUREMENTS (CONTINUED)****FIGURE 4(h) - DYNAMIC TEST AND SWITCHING WAVEFORMS (CONTINUED)****VOLTAGE WAVEFORMS - PROPAGATION DELAY TIMES****NOTES**

1. The generator has the following characteristics: $t_r = t_f = 2\text{ns}$, $\text{PRR} = 1\text{MHz}$, $Z_{\text{out}} = 50\Omega$, Duty Cycle = 50%.
2. $C_L = 50\text{pF} \pm 5\%$ including scope probe, wiring and stray capacitance without package in test fixture.
3. Each counter tested separately.
4. $R_L = 500\Omega \pm 5\%$.

TABLE 4 - PARAMETER DRIFT VALUES

NO.	CHARACTERISTICS	SYMBOL	SPEC. AND/OR TEST METHOD	TEST CONDITIONS	CHANGE LIMITS (Δ)	UNIT
2 to 9	Input Current High Level	I_{IH1}	As per Table 2	As per Table 2	± 20 or (1) ± 0.5	% μA
26 to 31	Input Current Low Level at Data Inputs Load and Clear	I_{IL1}	As per Table 2	As per Table 2	± 10	μA
32 to 33	Input Current Low Level at Up and Down	I_{IL2}	As per Table 2	As per Table 2	± 20	μA
34 to 39	Output Voltage Low Level	V_{OL}	As per Table 2	As per Table 2	± 60	mV
40 to 45	Output Voltage High Level 1	V_{OH1}	As per Table 2	As per Table 2	± 200	mV
46 to 51	Output Voltage High Level 2	V_{OH2}	As per Table 2	As per Table 2	± 200	mV

NOTES

1. Whichever is greater referred to the initial value.


TABLE 5 - CONDITIONS FOR POWER BURN-IN AND OPERATING LIFE TEST

NO.	CHARACTERISTICS	SYMBOL	CONDITION	UNIT
1	Ambient Temperature	T_{amb}	+ 125(+ 0 – 5)	$^{\circ}C$
2	Power Supply Voltage	V_{CC}	+ 5(+ 0.5 – 0)	V
3	Pulse Voltage	V_{GEN}	0.5 max. to 3.0 min.	Vac
4	Frequency	f	100 (See Note 1)	Hz
5	Fan-out	-	10	-
6	Rise Time	t_r	50 max.	μs
7	Fall Time	t_f	50 max.	μs
8	Duty Cycle	-	20 min.	%

NOTES



1. Tolerance $\pm 10\%$.

FIGURE 5 - ELECTRICAL CIRCUIT FOR POWER BURN-IN AND OPERATING LIFE TEST



NOTES

1. Pin numbers in parenthesis are for the chip carrier package.
2. R = 1.2k Ω .

 	<p>ESA/SCC Detail Specification No. 9204/058</p>	<p>PAGE 30 ISSUE 2</p>
--	--	----------------------------

4.8 ENVIRONMENTAL AND ENDURANCE TESTS (CHARTS IV AND V OF ESA/SCC GENERIC SPECIFICATION NO. 9000)

4.8.1 Electrical Measurements on Completion of Environmental Tests

The parameters to be measured on completion of environmental tests are scheduled in Table 6. Unless otherwise stated, the measurements shall be performed at $T_{amb} = +22 \pm 3$ °C.

4.8.2 Electrical Measurements at Intermediate Points during Endurance Tests

The parameters to be measured at intermediate points during endurance tests are as scheduled in Table 6 of this specification. Unless otherwise stated, the measurements shall be performed at $T_{amb} = +22 \pm 3$ °C.

4.8.3 Electrical Measurements on Completion of Endurance Tests

The parameters to be measured on completion of endurance testing are as scheduled in Table 6 of this specification. Unless otherwise stated, the measurements shall be performed at $T_{amb} = +22 \pm 3$ °C.

4.8.4 Conditions for Operating Life Tests

The requirements for operating life testing are specified in Section 9 of ESA/SCC Generic Specification No. 9000. The conditions for operating life testing shall be as specified in Table 5 of this specification.

4.8.5 Electrical Circuits for Operating Life Tests



Circuits for use in performing the operating life tests are shown in Figure 5.

4.8.6 Conditions for High Temperature Storage Test

The requirements for the high temperature storage test are specified in ESA/SCC Generic Specification No. 9000. The conditions for high temperature storage shall be $T_{amb} = +150(+0-5)$ °C.

TABLE 6 - ELECTRICAL MEASUREMENTS ON COMPLETION OF ENVIRONMENTAL TESTS AND AT INTERMEDIATE POINTS AND ON COMPLETION OF ENDURANCE TESTS

NO.	CHARACTERISTICS	SYMBOL	SPEC. AND/OR TEST METHOD	TEST CONDITIONS	CHANGE LIMITS		UNIT
					(Δ)	ABSOLUTE	
2 to 9	Input Current High Level	I_{IH1}	As per Table 2	As per Table 2	± 1	-	μA
10 to 17	Input Current High Level 2 (Max. Input Voltage)	I_{IH2}	As per Table 2	As per Table 2	-	100	μA
26 to 31	Input Current Low Level at Data Inputs Load and Clear	I_{IL1}	As per Table 2	As per Table 2	± 10	-	μA
32 to 33	Input Current Low Level at Up and Down	I_{IL2}	As per Table 2	As per Table 2	± 20	-	μA
34 to 39	Output Voltage Low Level	V_{OL}	As per Table 2	As per Table 2	± 60	-	mV
40 to 45	Output Voltage High Level 1	V_{OH1}	As per Table 2	As per Table 2	± 200	-	mV
46 to 51	Output Voltage High Level 2	V_{OH2}	As per Table 2	As per Table 2	± 200	-	mV
58	Supply Current	I_{CC}	As per Table 2	As per Table 2	± 20	-	%

 	<p>ESA/SCC Detail Specification No. 9204/058</p>		<p>PAGE 32 ISSUE 2</p>
---	--	--	----------------------------

APPENDIX 'A'

Page 1 of 1

AGREED DEVIATIONS FOR TEXAS INSTRUMENTS (F)

ITEMS AFFECTED	DESCRIPTION OF DEVIATIONS
Para. 4.2.1	Scanning Electron Microscope (SEM) Inspection may be performed using TIF document TIF 3.61.610.001.
Para. 4.2.2	Prior to Die Shear Test TIF may perform a Radiographic Inspection on the randomly chosen samples to be subjected to this test, using TIF document TI 50.42-3002.
Para. 4.2.3	Radiographic Inspection may be performed using TIF document TI 50.42-3002.