



europaean space agency
agence spatiale européenne

Pages 1 to 6

EXTERNAL VISUAL INSPECTION

ESA/SCC Basic Specification No. 20500



**space components
coordination group**

Issue/Rev.	Date	Approved by	
		SCCG Chairman	ESA Director General or his Deputy
Issue 3	September 1994	<i>[Signature]</i>	<i>[Signature]</i>
Revision 'A'	February 1998	<i>[Signature]</i>	<i>[Signature]</i>

**SCC**ESA/SCC Basic Specification
No. 20500

Rev. 'A'

PAGE 2

ISSUE 3

DOCUMENTATION CHANGE NOTICE

Rev. Letter	Rev. Date	Reference	CHANGE Item	Approved DCR No.
		This Issue supersedes Issue 2 Revision 'A' and incorporates all modifications defined in Revision 'A' to Issue 2 and the following DCR's: Cover Page DCN Para. 5 : Reference to ESA/SCC No. 20530 changed to 2053000 : Reference to ESA/SCC Nos. 2053102, 2053400, 2053501, 2053502, 2053600, 2053701, 2054000, 2055000 and 2059000 added		None None 21057 21057
'A'	Feb. '98	P1. Cover Page P2. DCN P6. Para. 5	: No. 2054009 entry added	None None 23881

**SCC**ESA/SCC Basic Specification
No. 20500

PAGE 3

ISSUE 3

TABLE OF CONTENTS

	<u>Page</u>
1. <u>SCOPE</u>	4
1.1 General	4
1.2 Purpose	4
1.3 Alternative Standards	4
2. <u>APPLICABLE DOCUMENTS</u>	4
3. <u>TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS</u>	4
4. <u>REQUIREMENTS</u>	4
4.1 General	4
4.2 Equipment Required	5
4.3 Illumination	5
4.4 Material and External Construction	5
4.5 External Surfaces	5
4.6 Dimension Check	5
4.7 Marking	5
4.8 Solder Joints	6
5. <u>ANCILLARY SPECIFICATIONS</u>	6

**1. SCOPE****1.1 GENERAL**

This specification defines the minimum acceptable external visual inspection criteria for electrical, electronic and electro-mechanical components suitable for space application.

1.2 PURPOSE

The purpose of this specification is to describe the inspection procedures to be used to check the external aspects of materials, design, construction and workmanship of electrical, electronic and electro-mechanical components.

This specification covers the overall requirements for all components. Specific requirements, for individual families of components, are detailed in ancillary specifications numbered in the 20500 series (see Section 5).

Each of these must be read in conjunction with this specification.

1.3 ALTERNATIVE STANDARDS

Where the configuration of a particular component is not in accordance with the requirements shown in a 20500 series specification, or where current in-house inspection drawings or standards (accepted in the PID) are to be used, it shall be the manufacturer's responsibility to obtain the formal interpretation of the SCCG, or its designated representative, concerning any deviation.

2. APPLICABLE DOCUMENTS

The following document forms part of this specification. The relevant issue shall be that in effect on the date of placing the purchase order.

- IEC Publication No. 410, Sampling Plans and Procedures for Inspection by Attributes.

3. TERMS, DEFINITIONS, ABBREVIATIONS, SYMBOLS AND UNITS

The terms, definitions, abbreviations, symbols and units specified in ESA/SCC Basic Specification No. 21300 shall apply.

In addition, the following definitions apply in this specification:

- Lead Width: The major dimension.
- Lead Thickness: The minor dimension.
- Case or Package: The outer envelope of a component, excluding leads and seals, however fabricated, e.g. welded can, epoxy mould, etc.

Where necessary, other specific definitions will be contained within the relevant 20500 series specification.

4. REQUIREMENTS**4.1 GENERAL**

A lot or subplot being examined at any one time shall be drawn from the same production lot. Evidence that this is not so shall be cause for rejection of the total lot in question.



4.2 EQUIPMENT REQUIRED

Optical equipment, visual standards and any other equipment (subject to Paragraph 1.3), required for the performance of the inspections, will be detailed in the appropriate 20500 series specification. All equipment shall be subject to periodic calibration or certifications as appropriate.

4.3 ILLUMINATION

Components undergoing inspection with optical equipment shall be illuminated such that a particle or blemish which has a size of 0.0125mm in the major dimension can be detected at magnification of 20 power.

4.4 MATERIAL AND EXTERNAL CONSTRUCTION

The material and external construction shall be in accordance with the appropriate ESA/SCC Detail Specification.

4.5 EXTERNAL SURFACES

All external surfaces shall be free of foreign particles and contamination. There shall be no evidence of corrosion, peeling of finish or plating nor of any holes or cracks.

Surfaces shall not show any colour change unless explained by, and authorised in, the relevant P.I.D. except for the instances given below:-

- (a) Discoloration of tinned surfaces due to oxidisation after exposure to endurance and storage testing at elevated temperature.
- (b) Even discoloration of the body and/or metal surfaces after exposure to endurance testing or high temperature storage testing.

Where components have been subjected to robustness of terminations (terminal strength) testing, degradation of the leads or terminations due to the mechanical action of clamping or probing instruments shall not be cause for rejection.

4.6 DIMENSION CHECK

Dimension check shall apply only to final production test. Unless otherwise specified in the relevant ESA/SCC Detail Specification, inspection shall be to Inspection Level II and to an AQL of 1.0.

All dimensions specified for the component in the relevant ESA/SCC Detail Specification shall be checked to ensure that they comply with the detailed requirements. At final production test, the same sample may be used for marking (see Paragraph 4.7).

4.7 MARKING

Unless otherwise specified in the relevant ESA/SCC Detail Specification, inspection shall be to Inspection Level II and to an AQL of 1.0. The marking on the component shall be inspected to ensure that it complies with the detailed requirements specified in the relevant ESA/SCC Generic and Detail Specifications and that it is legible and shows no signs of damage or degradation.

**4.8 SOLDER JOINTS**

Any solder joint exhibiting one or more of the following defects shall be cause for rejection.

- (a) Surface of the solder not smooth or clean.
- (b) Evidence of cracks, voids or holes.
- (c) Structure of the soldered part not visible.
- (d) Incomplete solder flow or coverage.
- (e) Balling or spherical appearance of the solder.
- (f) Evidence of foreign materials encapsulated in the solder.

5. ANCILLARY SPECIFICATIONS

The following specifications in the 20500 series have been issued with this issue of ESA/SCC Basic Specification No. 20500:-

- No. 2053000 - External Visual Inspection of Capacitors.
- No. 2053102 - External Visual Inspection of Waveguide Devices.
- No. 2053400 - External Visual Inspection of Electrical Connectors.
- No. 2053501 - External Visual Inspection of Quartz Crystal Units.
- No. 2053502 - External Visual Inspection of Surface Acoustic Wave (SAW) Devices.
- No. 2053600 - External Visual Inspection of Electromagnetic Relays.
- No. 2053701 - External Visual Inspection of Electromechanical Switches.
- No. 2054000 - External Visual Inspection of Resistors.
- No. 2054009 - External Visual Inspection of Flexible Heaters.
- No. 2055000 - External Visual Inspection of Discrete Non-Microwave Semiconductor Devices (1).
- No. 2059000 - External Visual Inspection of Integrated Circuits.

NOTES

- 1. For Discrete Microwave Semiconductor Devices (ESA/SCC Generic Specification No. 5010), no individual ancillary specification for External Visual Inspection exists. ESA/SCC 2055000 should be used to the extent applicable.