

Types covered by similarity: Coil voltage 12 Vdc .			Remarks: Long term strategy favours 15A relays from STPI-REL. Planning to be confirmed.		
Procurement Specifications		Manufacturer	Nature of Approval	Supervising Authority	Date
Generic ESCC 3601 Detail ESCC 3601/007		STPI Paris France	Qualification	CNES	Apr 2007
			Extension	CNES	Oct 2010
			Extension	CNES	Jun 2012
Characteristics: Variants 01 to 06 are qualified Contact Rating 15 A at 28 Vdc Contact Configuration 2 PDT Size (mm. max.) 26x26x14 Package Type 1/2 can Coil Voltage 28 Vdc Operating Temperature Range (°C): -65 to +125					
	RELAY, NON-LATCHING, ELECTROMAGNETIC, TYPE 317		Current Validity of Qualification		Page
			Certificate 279 B	Valid Until April 2013	09-01 006

Types covered by similarity:				Remarks: Long term strategy favours 15A relays from STPI-REL. Planning to be confirmed.		
Coil Voltage 12 Vdc						
Procurement Specifications				Manufacturer		Date
Generic ESCC 3602				STPI Paris France		Apr 2007
Detail ESCC 3602/004						Oct 2010
3602/009						Jun 2012
Characteristics: 3602/004 Variants 04, 06 and 09 14, 16 and 19 are qualified Contact Rating 15 A at 28 Vdc Contact Configuration 4 PDT Size (mm. max.) 26x26x26 Package Type can Coil Voltage 28 Vdc Operating Temperature Range (°C): -65 to +125				3602/009 Variants 03, 04 and 06 and 13, 14 and 16 are qualified Contact Rating 15 A at 28 Vdc Contact Configuration 2 PDT Size (mm. max.) 26x26x13.34 Package Type 1/2 can Coil Voltage 28 Vdc Operating Temperature Range (°C): -65 to +125		
				RELAY, NON-LATCHING, ELECTROMAGNETIC, TYPE 3*7B		Page
				Current Validity of Qualification		09-02
				Certificate		Valid Until
				280 B		April 2013
						006