



## TOTAL DOSE RADIATION TEST REPORT

**Part Type : K6R4008V1C**

**Package : 36-Pin SOJ**

**4Mb Static RAM (512-kword x 8-bit)**

**Manufacturer: Samsung**

**Report Reference : ESA\_QCA0103T\_C**

**Issue : 01**

**Date : January 19th 2001**

**ESA Contract no. 13528/99/NL/MV CCN N°3 dated 24/11/00**

**ESTEC Technical Officer: R. Harboe Sorensen**

**European Space Agency Contract Report**

The work described in this report was done under ESA contract.  
Responsibility for the contents resides in the author or organization that prepared it

<b>Hirex reference :</b>	HRX/TID/0075	Issue : 01	Date :	January 19 <sup>th</sup> 2001
<b>Written by :</b>	O. PERROTIN	Study Engineer		
<b>Approved by :</b>	J.F. PASCAL	Technical Responsible		
<b>Authorized by:</b>	F.X. GUERRE	Study Manager		

**TOTAL DOSE RADIATION TEST REPORT**  
on  
**Samsung K6R4008V1C**  
**4Mb Static RAM (512-kword x 8-bit).**

**TABLE OF CONTENTS**

<b>1 ABSTRACT .....</b>	<b>3</b>
<b>2 INTRODUCTION .....</b>	<b>4</b>
<b>3 APPLICABLE AND REFERENCE DOCUMENTS.....</b>	<b>4</b>
3.1 APPLICABLE DOCUMENTS.....	4
3.2 REFERENCE DOCUMENTS.....	4
<b>4 TEST SAMPLES .....</b>	<b>4</b>
<b>5 EXPERIMENTAL CONDITIONS.....</b>	<b>5</b>
5.1 RADIATION SOURCE DOSE RATE AND ANNEALING .....	5
5.2 BIAS CONDITION DURING DOSE EXPOSURES AND ANNEALING .....	6
5.3 MEASUREMENTS CONDITIONS .....	7
5.4 ELECTRICAL PARAMETERS TEST CONDITIONS AND LIMITS.....	8
<b>6 CONCLUSION.....</b>	<b>9</b>

**List of tables:**

Table 1 : Experimental Conditions .....	5
Table 2 : Test Conditions .....	8

**List of Figures:**

Figure 1 : Bias Conditions during Irradiation Exposures and Annealing .....	6
Figure 2 : K6R4008V1C test program principle .....	7

**Appendix:**

APPENDIX 1 : TEST RESULTS.....	10
--------------------------------	----

<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>		
	Réf. : HRX/TID/0075 Issue : 01		
Part Type :	K6R4008V1C	Manufacturer :	Samsung

## 1 Abstract

Under ESA Contract no. 13528/99/NL/MV CCN N°3 dated 24/11/00, covering "Radiation Evaluation of COTS semiconductor Components", four different commercially available 4Mb Static RAM device types were radiation assessed. Results from these assessments, primarily focussing on the sensitivity of these devices to Total Ionizing Dose (TID) and Single Event Effects (SEE), are reported in individual TID and SEE reports. The below summary table lists manufacturer and evaluated types, and gives references to the various reports issued.

Manufacturer	Type	TID Report	SEE Report
Hitachi	HM6216255H	ESA_QCA0104T_C	ESA_QCA0104S_C
Samsung	K6R4008C1C	ESA_QCA0102T_C	ESA_QCA0102S_C
Samsung	K6R4008V1C	ESA_QCA0103T_C	ESA_QCA0103S_C
Samsung	KM684002AJ	-	ESA_QCA0101S_C

<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>			Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :		Samsung

## 2 Introduction

A total dose radiation evaluation test of the Samsung K6R4008V1C , high-speed, 3.3 V, Monolithic 4Mb Static RAM has been performed with an accumulated dose of about 47 Krad(Si), in response to European Space Agency contract reference : ESA Contract no. 13528/99/NL/MV CCN N°3 dated 24/11/00.

The purpose of this test was to evaluate total dose withstanding of this component, to investigate its suitability for being used in space applications. This test was conducted on commercial samples procured from Samsung and provided to HIREX by ESA.

A complete set of electrical measurements together with graphical representation of measured parameters with respect to total dose received, are provided for all samples.

SEE results for this device type can be found in SEE radiation test report: ESA\_QCA0103S\_C.

## 3 Applicable and Reference Documents

### 3.1 Applicable Documents

- ESA/SCC Basic specification N° 22900 issue 4.
- Samsung K6R4008V1C datasheet – Rev. 4.0 April 2000.
- ESA Contract no. 13528/99/NL/MV CCN N°3 dated 24/11/00.

### 3.2 Reference Documents

- MIL-STD-883: test methods and procedures for microcircuits.

## 4 Test Samples

5 samples of the K6R4008V1C device were tested (4 + 1 control sample). Each device was submitted to exposures at a dose rate of 200 Rad(Si)/hour.

Serial Number	Allocation
20	Control
21	Irradiated under bias
22	Irradiated under bias
23	Irradiated under bias
24	Irradiated under bias

Identification of the K6R4008V1C is given below:

<b>Part Number:</b>	K6R4008V1C-JC12	<b>Mask Set:</b>	NA
<b>Top Marking:</b>	SAMSUNG 037 K6R4008V1C- JC12 TZVE04DB KOREA	<b>Chip Marking:</b>	NA
<b>Diffusion Lot:</b>	NA	<b>Wafer #:</b>	NA
<b>Date Code:</b>	NA	<b>Project:</b>	Multi-Project

Further K6R4008V1C identification details can be found in ESA\_QCA0103S\_C.

<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>			Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :		Samsung

## 5 Experimental Conditions

### 5.1 Radiation Source Dose Rate and Annealing

The dose exposures were performed at ONERA-CERT. In this irradiation facility, a Cobalt 60 source is used with the possibility to vary the dose rate by simply adjusting the distance to the source.

The irradiation conditions used for this test are provided in the following tables:

Irradiation Steps krads	Dose rate krads/hour	Annealing steps hours	Temperature °C
0			25
4.6	0,2		25
10	0,2		25
14.8	0,2		25
19	0,2		25
31.8	0,2		25
47.2	0,2	0	25
		24	25
		192	100

**Table 1 : Experimental Conditions**

HIREX Engineering	Total Dose Test Report			Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung	

## 5.2 Bias condition during Dose Exposures and Annealing

During exposures a dedicated test board was used mounted on a special board-holder made for irradiation. The test board allowed to bias the devices in accordance with the electrical circuit provided in Figure 1.




Figure 1 : Bias Conditions during Irradiation Exposures and Annealing

HIREX Engineering	Total Dose Test Report		Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung

### 5.3 Measurements conditions

The electrical measurements were performed at HIREX ENGINEERING.  
 Electrical parameters test program principle for K6R4008V1C is provided in Figure 2.

The test Setup for this device includes an IMS ATS Test Station and a DC test system HP4142B.  
 The ATS generates and then acquires data. A dedicated sequencer program analyses the data and displays the results on a SUN workstation.




Figure 2 : K6R4008V1C test program principle

<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>			Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung	

#### 5.4 Electrical parameters test conditions and limits

Electrical parameters test conditions and limits used for performing this test are given in the following table.

<b>SYMBOL</b>	<b>CHARACTERISTICS</b>	<b>TESTS CONDITIONS</b>	<b>LIMIT</b>		<b>UNIT</b>
			<b>Min</b>	<b>Max</b>	
ILLI	Input Leakage Current Low Level	V <sub>in</sub> (under test) = V <sub>IL</sub> V <sub>in</sub> (remaining inputs) = V <sub>IH</sub> output unloaded	-2	2	µA
IHLI	Input Leakage Current High Level	V <sub>in</sub> (under test) = V <sub>IH</sub> V <sub>in</sub> (remaining inputs) = V <sub>IL</sub> output unloaded	-2	2	µA
ILLO	Output Leakage Current Low Level	V <sub>out</sub> (under test) = V <sub>IL</sub> V <sub>out</sub> (remaining outputs) = tristate CS* = OE* = V <sub>IH</sub> Remaining inputs V <sub>IL</sub> or V <sub>IH</sub>	-2	2	µA
IHLO	Output Leakage Current High Level	V <sub>out</sub> (under test) = V <sub>IH</sub> V <sub>out</sub> (remaining outputs) = tristate CE* = OE* = V <sub>IH</sub> Remaining inputs V <sub>IL</sub>	-2	2	µA
VOH	Output Voltage High Level	I <sub>OH</sub> = -4 mA	2.4		V
VOL	Output Voltage Low Level	I <sub>OL</sub> = 8 mA		0.4	V
ICC	Operating Power Supply Current	CS* = V <sub>IL</sub> OE* = V <sub>IH</sub> F = 80 Mhz outputs unloaded		145	mA
ISB	Standby Power Supply Current	CS* = OE* = V <sub>IH</sub> Outputs unloaded		10	mA
t <sub>AA L-&gt;H</sub>	Address Access Time	Output Load : 50 O		12	ns
t <sub>AA H-&gt;L</sub>	Address Access Time	Output Load : 50 O		12	ns
t <sub>AS</sub>	Address setup time	Output Load : 50 O	0		ns
Zero	Functional Test 1: , Test Pattern: All 0	Frequency=80MHz			
One	Functional Test 1: , Test Pattern: All 1	Frequency=80MHz			
Checkerboard	Functional Test 1: , Test Pattern: Checkerboard	Frequency=80MHz			
*Checkerboard	Functional Test 1: , Test Pattern: Complementary Checkerboard	Frequency=80MHz			

V<sub>cc</sub> = 3.3V

**Table 2 : Test Conditions**

<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>			Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :		Samsung

## 6 Conclusion

A Total Ionizing Dose assessment was carried out by Hirex Engineering under ESA contract on the Samsung K6R4008V1C 4Mb 3.3V high speed Static RAM (256kword x 16-bit).

4 samples plus one control sample were used during testing. Each device was exposed to Co-60 radiation using a dose rate of 200 Rad(Si)/hour at room temperature.

All samples were functional up to 47.2Krad(Si).

All parameters measured remained within specification limits throughout the testing.

As a general conclusion, this device type has shown a fairly good total dose withstanding without any failure recorded up to 47.2Krad(Si)..

Electrical measurement results can be found in Appendix 1.

<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>			Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :		Samsung

#### **APPENDIX 1 : TEST RESULTS**

<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>			Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :		Samsung

Test results including tables and graphics are provided in this section for each measured parameter.

**Notes on tables and graphics:**

For  $V_{OH}$ ,  $V_{OL}$ ,  $I_{I(L)}$ ,  $I_{O(L)}$ ,  $I_{OZ(L)}$ ,  $I_{OZ(H)}$  measurements were performed on all applicable pins respectively.

In some cases, they may be missing points in tables and graphs, this situation corresponds to a failure corresponding to an out of range measurement.

To allow logarithmic representation of some parameters, corresponding negative values have been reversed. This is identified for those parameters having a minus sign before their symbol.

HIREX Engineering	Total Dose Test Report					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

Parameter : Negative Input Current Low Level Pin A18: -IiL A18

Vin=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	2,000E -10	1,000E -10	1,000E -10	1,500E -10	2,000E -10	1,500E -10	1,000E -10
21	1,000E -10	3,000E -10	1,000E -10	1,000E -10	1,000E -10	1,500E -10	1,000E -10	1,500E -10
22	1,500E -10	1,000E -10						
23	2,000E -10	1,000E -10	2,000E -10	1,000E -10	1,500E -10	1,000E -10	1,500E -10	1,000E -10
24	1,000E -10	2,000E -10	3,000E -10	1,500E -10	3,000E -10	1,000E -10	3,000E -10	1,000E -10
Statistics								
Min	1,000E -10							
Max	2,000E -10	3,000E -10	3,000E -10	1,500E -10	3,000E -10	1,500E -10	3,000E -10	1,500E -10
Mean	1,375E -10	1,750E -10	1,750E -10	1,125E -10	1,625E -10	1,125E -10	1,625E -10	1,125E -10
Sigma	4,787E -11	9,574E -11	9,574E -11	2,500E -11	9,465E -11	2,500E -11	9,465E -11	2,500E -11

Test Step	192 hours
Serial #	
20 Ref.	3,000E -10
21	3,000E -10
22	2,000E -10
23	1,000E -10
24	1,000E -10
Statistics	
Min	1,000E -10
Max	3,000E -10
Mean	1,750E -10
Sigma	9,574E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :	Samsung			

**Parameter : Negative Input Current Low Level Pin A17: -IiL A17**

Vin=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	1,000E -10	2,000E -10	1,000E -10	2,000E -10	1,000E -10	1,500E -10	1,000E -10	1,000E -10
21	1,000E -10	1,000E -10	1,000E -10	2,000E -10	1,000E -10	1,000E -10	1,000E -10	1,000E -10
22	1,000E -10	1,000E -10	1,500E -10	1,000E -10				
23	1,500E -10	2,000E -10	1,000E -10	1,000E -10	1,500E -10	1,500E -10	2,000E -10	1,000E -10
24	1,000E -10	1,500E -10	2,000E -10	1,000E -10	2,000E -10	1,500E -10	2,000E -10	2,000E -10
Statistics								
Min	1,000E -10							
Max	1,500E -10	2,000E -10	2,000E -10	2,000E -10	2,000E -10	1,500E -10	2,000E -10	2,000E -10
Mean	1,125E -10	1,375E -10	1,375E -10	1,250E -10	1,375E -10	1,250E -10	1,500E -10	1,250E -10
Sigma	2,500E -11	4,787E -11	4,787E -11	5,000E -11	4,787E -11	2,887E -11	5,774E -11	5,000E -11

Test Step	192 hours
Serial #	
20 Ref.	2,000E -10
21	1,000E -10
22	2,000E -10
23	2,000E -10
24	2,000E -10
Statistics	
Min	1,000E -10
Max	2,000E -10
Mean	1,750E -10
Sigma	5,000E -11



HIREX Engineering	Total Dose Test Report					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

Parameter : Negative Input Current Low Level Pin A16: -IiL A16

Vin=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	1,000E -10	1,000E -10	1,000E -10	1,000E -10	1,500E -10	1,000E -10	1,000E -10	1,000E -10
21	1,000E -10	2,000E -10	1,000E -10	1,000E -10	1,500E -10	1,000E -10	2,000E -10	1,000E -10
22	1,500E -10	2,000E -10	2,000E -10	1,500E -10	2,000E -10	2,000E -10	1,500E -10	1,000E -10
23	1,000E -10	2,000E -10	2,000E -10					
24	2,000E -10	2,000E -10	1,000E -10	1,500E -10	1,000E -10	2,000E -10	2,000E -10	2,000E -10
Statistics								
Min	1,000E -10	1,500E -10	1,000E -10					
Max	2,000E -10	2,000E -10	2,000E -10	1,500E -10	2,000E -10	2,000E -10	2,000E -10	2,000E -10
Mean	1,375E -10	1,750E -10	1,250E -10	1,250E -10	1,375E -10	1,500E -10	1,875E -10	1,500E -10
Sigma	4,787E -11	5,000E -11	5,000E -11	2,887E -11	4,787E -11	5,774E -11	2,500E -11	5,774E -11

Test Step	192 hours
Serial #	
20 Ref.	1,000E -10
21	2,000E -10
22	1,000E -10
23	1,000E -10
24	1,000E -10
Statistics	
Min	1,000E -10
Max	2,000E -10
Mean	1,250E -10
Sigma	5,000E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Negative Input Current Low Level Pin A15: -IiL A15**

Vin=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	3,500E -10	3,000E -10	2,500E -10	2,000E -10	1,000E -10	2,500E -10	2,000E -10	3,000E -10
21	3,000E -10	3,000E -10	2,000E -10	2,000E -10	1,000E -10	2,000E -10	2,000E -10	2,500E -10
22	4,000E -10	1,000E -10	2,000E -10	1,000E -10	1,500E -10	2,000E -10	2,000E -10	1,500E -10
23	3,500E -10	1,000E -10	2,000E -10	1,500E -10	1,500E -10	2,000E -10	2,000E -10	1,500E -10
24	3,500E -10	1,000E -10	3,000E -10	1,000E -10	3,000E -10	2,000E -10	2,000E -10	1,000E -10
Statistics								
Min	3,000E -10	1,000E -10	2,000E -10	1,000E -10	1,000E -10	2,000E -10	2,000E -10	1,000E -10
Max	4,000E -10	3,000E -10	3,000E -10	2,000E -10	3,000E -10	2,000E -10	2,000E -10	2,500E -10
Mean	3,500E -10	1,500E -10	2,250E -10	1,375E -10	1,750E -10	2,000E -10	2,000E -10	1,625E -10
Sigma	4,082E -11	1,000E -10	5,000E -11	4,787E -11	8,660E -11	1,878E -19	1,878E -19	6,292E -11

Test Step	192 hours
Serial #	
20 Ref.	2,000E -10
21	2,000E -10
22	2,000E -10
23	2,000E -10
24	2,000E -10
Statistics	
Min	2,000E -10
Max	2,000E -10
Mean	2,000E -10
Sigma	1,878E -19



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Negative Input Current Low Level Pin A14: -IiL A14**

Vin=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	3,000E -10	3,000E -10	2,000E -10	2,500E -10	2,500E -10	1,500E -10	2,000E -10
21	3,000E -10	1,000E -10	2,500E -10	2,500E -10	3,000E -10	2,000E -10	2,000E -10	2,000E -10
22	3,000E -10	3,000E -10	2,000E -10	2,000E -10	2,000E -10	2,000E -10	2,500E -10	1,500E -10
23	3,500E -10	1,000E -10	3,000E -10	1,000E -10	2,000E -10	2,000E -10	1,500E -10	2,000E -10
24	2,500E -10	1,000E -10	2,000E -10	1,500E -10	2,000E -10	1,500E -10	2,500E -10	2,500E -10
Statistics								
Min	2,500E -10	1,000E -10	2,000E -10	1,000E -10	2,000E -10	1,500E -10	1,500E -10	1,500E -10
Max	3,500E -10	3,000E -10	3,000E -10	2,500E -10	3,000E -10	2,000E -10	2,500E -10	2,500E -10
Mean	3,000E -10	1,500E -10	2,375E -10	1,750E -10	2,250E -10	1,875E -10	2,125E -10	2,000E -10
Sigma	4,082E -11	1,000E -10	4,787E -11	6,455E -11	5,000E -11	2,500E -11	4,787E -11	4,082E -11

Test Step	192 hours
Serial #	
20 Ref.	2,000E -10
21	2,500E -10
22	1,500E -10
23	1,500E -10
24	1,000E -10
Statistics	
Min	1,000E -10
Max	2,500E -10
Mean	1,625E -10
Sigma	6,292E -11



HIREX Engineering	Total Dose Test Report					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

Parameter : Negative Input Current Low Level Pin A13: -IiL A13

Vin=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,500E -10	1,000E -10	2,500E -10	2,500E -10	1,500E -10	2,500E -10	1,000E -10	2,000E -10
21	2,500E -10	1,000E -10	2,500E -10	1,500E -10	2,000E -10	2,000E -10	2,000E -10	2,500E -10
22	2,000E -10	3,000E -10	2,000E -10	1,000E -10	1,000E -10	3,000E -10	1,500E -10	1,500E -10
23	2,000E -10	2,000E -10	2,500E -10	2,500E -10	2,500E -10	1,500E -10	1,500E -10	2,000E -10
24	2,500E -10	1,000E -10	2,000E -10	2,500E -10	2,000E -10	2,000E -10	1,000E -10	2,000E -10
Statistics								
Min	2,000E -10	1,000E -10	2,000E -10	1,000E -10	1,000E -10	1,500E -10	1,000E -10	1,500E -10
Max	2,500E -10	3,000E -10	2,500E -10	2,500E -10	2,500E -10	3,000E -10	2,000E -10	2,500E -10
Mean	2,250E -10	1,750E -10	2,250E -10	1,875E -10	1,875E -10	2,125E -10	1,500E -10	2,000E -10
Sigma	2,887E -11	9,574E -11	2,887E -11	7,500E -11	6,292E -11	6,292E -11	4,082E -11	4,082E -11

Test Step	192 hours
Serial #	
20 Ref.	2,000E -10
21	2,000E -10
22	2,000E -10
23	2,500E -10
24	2,500E -10
Statistics	
Min	2,000E -10
Max	2,500E -10
Mean	2,250E -10
Sigma	2,887E -11



HIREX Engineering	Total Dose Test Report					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

Parameter : Negative Input Current Low Level Pin A12: -IiL A12

Vin=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	3,000E -10	1,500E -10	2,500E -10	2,500E -10	1,000E -10	2,000E -10	2,000E -10
21	2,000E -10	3,000E -10	2,000E -10	2,000E -10	2,000E -10	3,000E -10	2,500E -10	2,500E -10
22	2,000E -10	1,000E -10	1,500E -10	2,000E -10	2,500E -10	2,000E -10	1,000E -10	1,500E -10
23	1,000E -10	3,000E -10	1,500E -10	1,500E -10	2,000E -10	2,000E -10	2,000E -10	1,500E -10
24	2,000E -10	3,000E -10	2,000E -10	1,000E -10	2,000E -10	2,500E -10	1,500E -10	1,000E -10
Statistics								
Min	1,000E -10	1,000E -10	1,500E -10	1,000E -10	2,000E -10	2,000E -10	1,000E -10	1,000E -10
Max	2,000E -10	3,000E -10	2,000E -10	2,000E -10	2,500E -10	3,000E -10	2,500E -10	2,500E -10
Mean	1,750E -10	2,500E -10	1,750E -10	1,625E -10	2,125E -10	2,375E -10	1,750E -10	1,625E -10
Sigma	5,000E -11	1,000E -10	2,887E -11	4,787E -11	2,500E -11	4,787E -11	6,455E -11	6,292E -11

Test Step	192 hours
Serial #	
20 Ref.	2,000E -10
21	1,000E -10
22	2,500E -10
23	2,000E -10
24	2,000E -10
Statistics	
Min	1,000E -10
Max	2,500E -10
Mean	1,875E -10
Sigma	6,292E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Negative Input Current Low Level Pin A11: -IiL A11**

Vin=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	3,000E -10	2,000E -10	2,500E -10	2,000E -10	2,000E -10	2,000E -10	2,500E -10
21	2,500E -10	2,500E -10	2,500E -10	3,000E -10	1,000E -10	2,500E -10	2,000E -10	1,500E -10
22	3,000E -10	3,000E -10	2,500E -10	1,500E -10	2,000E -10	2,000E -10	1,500E -10	1,500E -10
23	3,000E -10	2,500E -10	2,500E -10	1,500E -10	1,500E -10	2,000E -10	1,500E -10	2,000E -10
24	2,000E -10	2,000E -10	2,500E -10	2,000E -10	1,500E -10	2,000E -10	1,500E -10	2,500E -10
Statistics								
Min	2,000E -10	2,000E -10	2,500E -10	1,500E -10	1,000E -10	2,000E -10	1,500E -10	1,500E -10
Max	3,000E -10	3,000E -10	2,500E -10	3,000E -10	2,000E -10	2,500E -10	2,000E -10	2,500E -10
Mean	2,625E -10	2,500E -10	2,500E -10	2,000E -10	1,500E -10	2,125E -10	1,625E -10	1,875E -10
Sigma	4,787E -11	4,082E -11	2,342E -19	7,071E -11	4,082E -11	2,500E -11	2,500E -11	4,787E -11

Test Step	192 hours
Serial #	
20 Ref.	2,000E -10
21	2,000E -10
22	1,500E -10
23	1,500E -10
24	2,000E -10
Statistics	
Min	1,500E -10
Max	2,000E -10
Mean	1,750E -10
Sigma	2,887E -11



HIREX Engineering	Total Dose Test Report						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung				

Parameter : Negative Input Current Low Level Pin A10: -IiL A10

Vin=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	2,500E -10	2,500E -10	2,000E -10	1,500E -10	1,500E -10	1,500E -10	1,500E -10
21	2,000E -10	2,500E -10	2,500E -10	2,000E -10	1,000E -10	1,000E -10	2,000E -10	1,500E -10
22	2,000E -10	3,000E -10	2,500E -10	1,500E -10	1,500E -10	1,000E -10	1,000E -10	1,500E -10
23	2,000E -10	2,500E -10	2,000E -10	2,000E -10	1,000E -10	1,000E -10	1,000E -10	1,500E -10
24	2,000E -10	2,000E -10	2,500E -10	1,000E -10	1,500E -10	2,500E -10	1,500E -10	1,500E -10
Statistics								
Min	2,000E -10	2,000E -10	2,000E -10	1,000E -10	1,000E -10	1,000E -10	1,000E -10	1,500E -10
Max	2,000E -10	3,000E -10	2,500E -10	2,000E -10	1,500E -10	2,500E -10	2,000E -10	1,500E -10
Mean	2,000E -10	2,500E -10	2,375E -10	1,625E -10	1,250E -10	1,375E -10	1,375E -10	1,500E -10
Sigma	1,878E -19	4,082E -11	2,500E -11	4,787E -11	2,887E -11	7,500E -11	4,787E -11	2,028E -19

Test Step	192 hours
Serial #	
20 Ref.	2,500E -10
21	1,500E -10
22	2,500E -10
23	1,000E -10
24	1,500E -10
Statistics	
Min	1,000E -10
Max	2,500E -10
Mean	1,625E -10
Sigma	6,292E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Negative Input Current Low Level Pin A9: -I<sub>IL</sub> A9**

V<sub>in</sub>=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,500E -10	3,000E -10	2,500E -10	1,500E -10	2,000E -10	1,500E -10	2,000E -10	2,000E -10
21	2,000E -10	2,000E -10	2,500E -10	2,000E -10	2,000E -10	1,500E -10	2,000E -10	1,500E -10
22	2,500E -10	2,500E -10	2,000E -10	2,000E -10	2,000E -10	2,000E -10	3,000E -10	1,000E -10
23	2,000E -10	3,500E -10	2,500E -10	2,500E -10	1,000E -10	2,500E -10	2,500E -10	1,000E -10
24	2,000E -10	3,000E -10	2,500E -10	2,000E -10	2,500E -10	2,500E -10	1,500E -10	1,500E -10
Statistics								
Min	2,000E -10	2,000E -10	2,000E -10	2,000E -10	1,000E -10	1,500E -10	1,500E -10	1,000E -10
Max	2,500E -10	3,500E -10	2,500E -10	2,500E -10	2,500E -10	2,500E -10	3,000E -10	1,500E -10
Mean	2,125E -10	2,750E -10	2,375E -10	2,125E -10	1,875E -10	2,125E -10	2,250E -10	1,250E -10
Sigma	2,500E -11	6,455E -11	2,500E -11	2,500E -11	6,292E -11	4,787E -11	6,455E -11	2,887E -11

Test Step	192 hours
Serial #	
20 Ref.	1,500E -10
21	2,000E -10
22	2,000E -10
23	1,500E -10
24	2,500E -10
Statistics	
Min	1,500E -10
Max	2,500E -10
Mean	2,000E -10
Sigma	4,082E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Negative Input Current Low Level Pin A8: -I<sub>IL</sub> A8**

V<sub>in</sub>=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,500E -10	2,500E -10	2,500E -10	1,000E -10	2,500E -10	2,500E -10	2,000E -10	2,000E -10
21	2,000E -10	2,000E -10	2,000E -10	1,500E -10	2,500E -10	2,000E -10	1,000E -10	1,500E -10
22	2,000E -10	1,500E -10	2,500E -10	3,000E -10	1,000E -10	2,000E -10	1,500E -10	1,500E -10
23	2,500E -10	2,500E -10	2,500E -10	1,000E -10	1,500E -10	2,500E -10	2,500E -10	2,500E -10
24	2,000E -10	2,000E -10	2,000E -10	1,000E -10	1,000E -10	1,000E -10	1,000E -10	2,000E -10
Statistics								
Min	2,000E -10	1,500E -10	2,000E -10	1,000E -10	1,000E -10	1,000E -10	1,000E -10	1,500E -10
Max	2,500E -10	2,500E -10	2,500E -10	3,000E -10	2,500E -10	2,500E -10	2,500E -10	2,500E -10
Mean	2,125E -10	2,000E -10	2,250E -10	1,625E -10	1,500E -10	1,875E -10	1,500E -10	1,875E -10
Sigma	2,500E -11	4,082E -11	2,887E -11	9,465E -11	7,071E -11	6,292E -11	7,071E -11	4,787E -11

Test Step	192 hours
Serial #	
20 Ref.	1,500E -10
21	1,500E -10
22	1,500E -10
23	2,500E -10
24	1,000E -10
Statistics	
Min	1,000E -10
Max	2,500E -10
Mean	1,625E -10
Sigma	6,292E -11



HIREX Engineering	Total Dose Test Report						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung				

Parameter : Negative Input Current Low Level Pin A7: -IIL A7

Vin=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	4,500E -10	6,000E -10	4,500E -10	1,500E -10	3,500E -10	2,500E -10	2,000E -10	2,500E -10
21	5,500E -10	5,000E -10	5,500E -10	2,000E -10	2,000E -10	3,000E -10	1,500E -10	3,000E -10
22	4,000E -10	4,500E -10	6,000E -10	2,500E -10	2,500E -10	2,500E -10	2,000E -10	1,000E -10
23	4,000E -10	5,000E -10	4,000E -10	2,000E -10	3,500E -10	3,000E -10	2,500E -10	1,500E -10
24	4,000E -10	7,500E -10	5,500E -10	2,000E -10	2,500E -10	2,500E -10	2,000E -10	2,000E -10
Statistics								
Min	4,000E -10	4,500E -10	4,000E -10	2,000E -10	2,000E -10	2,500E -10	1,500E -10	1,000E -10
Max	5,500E -10	7,500E -10	6,000E -10	2,500E -10	3,500E -10	3,000E -10	2,500E -10	3,000E -10
Mean	4,375E -10	5,500E -10	5,250E -10	2,125E -10	2,625E -10	2,750E -10	2,000E -10	1,875E -10
Sigma	7,500E -11	1,354E -10	8,660E -11	2,500E -11	6,292E -11	2,887E -11	4,082E -11	8,539E -11

Test Step	192 hours
Serial #	
20 Ref.	3,000E -10
21	3,500E -10
22	4,500E -10
23	3,000E -10
24	4,500E -10
Statistics	
Min	3,000E -10
Max	4,500E -10
Mean	3,875E -10
Sigma	7,500E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Negative Input Current Low Level Pin A6: -I<sub>IL</sub> A6**

V<sub>in</sub>=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	3,000E -10	3,000E -10	4,000E -10	1,500E -10	2,500E -10	2,000E -10	2,000E -10	2,000E -10
21	5,000E -10	3,500E -10	4,000E -10	2,500E -10	2,500E -10	2,500E -10	3,000E -10	2,000E -10
22	3,500E -10	3,500E -10	3,500E -10	2,500E -10	2,000E -10	2,000E -10	1,500E -10	2,500E -10
23	3,500E -10	3,000E -10	3,500E -10	2,500E -10	3,000E -10	3,000E -10	2,000E -10	2,000E -10
24	3,000E -10	2,500E -10	3,500E -10	2,000E -10	2,500E -10	2,500E -10	2,000E -10	2,500E -10
Statistics								
Min	3,000E -10	2,500E -10	3,500E -10	2,000E -10	2,000E -10	2,000E -10	1,500E -10	2,000E -10
Max	5,000E -10	3,500E -10	4,000E -10	2,500E -10	3,000E -10	3,000E -10	3,000E -10	2,500E -10
Mean	3,750E -10	3,125E -10	3,625E -10	2,375E -10	2,500E -10	2,500E -10	2,125E -10	2,250E -10
Sigma	8,660E -11	4,787E -11	2,500E -11	2,500E -11	4,082E -11	4,082E -11	6,292E -11	2,887E -11

Test Step	192 hours
Serial #	
20 Ref.	2,500E -10
21	3,000E -10
22	2,000E -10
23	3,000E -10
24	3,000E -10
Statistics	
Min	2,000E -10
Max	3,000E -10
Mean	2,750E -10
Sigma	5,000E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Negative Input Current Low Level Pin A5: -I<sub>IL</sub> A5**

V<sub>in</sub>=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	3,500E -10	2,500E -10	2,000E -10	2,000E -10	2,500E -10	2,000E -10	2,000E -10
21	3,000E -10	3,000E -10	3,000E -10	3,000E -10	2,000E -10	2,500E -10	2,500E -10	2,000E -10
22	1,500E -10	3,000E -10	3,000E -10	2,000E -10	2,500E -10	2,000E -10	2,500E -10	1,500E -10
23	4,000E -10	4,000E -10	3,000E -10	2,000E -10	2,500E -10	2,500E -10	1,000E -10	2,000E -10
24	3,500E -10	3,000E -10	3,000E -10	2,000E -10	1,000E -10	2,500E -10	2,000E -10	2,000E -10
Statistics								
Min	1,500E -10	3,000E -10	3,000E -10	2,000E -10	1,000E -10	2,000E -10	1,000E -10	1,500E -10
Max	4,000E -10	4,000E -10	3,000E -10	3,000E -10	2,500E -10	2,500E -10	2,500E -10	2,000E -10
Mean	3,000E -10	3,250E -10	3,000E -10	2,250E -10	2,000E -10	2,375E -10	2,000E -10	1,875E -10
Sigma	1,080E -10	5,000E -11	3,650E -19	5,000E -11	7,071E -11	2,500E -11	7,071E -11	2,500E -11

Test Step	192 hours
Serial #	
20 Ref.	2,500E -10
21	3,500E -10
22	3,500E -10
23	1,500E -10
24	2,500E -10
Statistics	
Min	1,500E -10
Max	3,500E -10
Mean	2,750E -10
Sigma	9,574E -11



HIREX Engineering	Total Dose Test Report					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

Parameter : Negative Input Current Low Level Pin A4: -I<sub>IL</sub> A4

V<sub>in</sub>=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,500E -10	3,500E -10	2,000E -10	1,500E -10	1,500E -10	2,500E -10	2,500E -10	2,500E -10
21	2,500E -10	2,000E -10	3,500E -10	2,500E -10				
22	2,500E -10	2,000E -10	2,500E -10	2,000E -10	3,000E -10	2,000E -10	1,000E -10	2,000E -10
23	2,000E -10	2,000E -10	3,000E -10	1,500E -10	3,000E -10	2,000E -10	2,000E -10	2,000E -10
24	3,000E -10	2,500E -10	3,000E -10	2,000E -10	2,000E -10	2,500E -10	2,000E -10	2,500E -10
Statistics								
Min	2,000E -10	2,000E -10	2,500E -10	1,500E -10	2,000E -10	2,000E -10	1,000E -10	2,000E -10
Max	3,000E -10	2,500E -10	3,500E -10	2,500E -10	3,000E -10	2,500E -10	2,500E -10	2,500E -10
Mean	2,500E -10	2,125E -10	3,000E -10	2,000E -10	2,625E -10	2,250E -10	1,875E -10	2,250E -10
Sigma	4,082E -11	2,500E -11	4,082E -11	4,082E -11	4,787E -11	2,887E -11	6,292E -11	2,887E -11

Test Step	192 hours
Serial #	
20 Ref.	2,000E -10
21	2,500E -10
22	2,500E -10
23	2,000E -10
24	3,500E -10
Statistics	
Min	2,000E -10
Max	3,500E -10
Mean	2,625E -10
Sigma	6,292E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Negative Input Current Low Level Pin A3: -I<sub>IL</sub> A3**

V<sub>in</sub>=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,500E -10	2,500E -10	3,500E -10	3,000E -10	2,000E -10	2,000E -10	1,500E -10	2,500E -10
21	2,500E -10	3,000E -10	2,500E -10	1,500E -10	2,500E -10	2,500E -10	1,000E -10	3,000E -10
22	2,500E -10	2,000E -10	1,500E -10	2,500E -10	2,000E -10	2,500E -10	1,500E -10	2,500E -10
23	2,500E -10	3,000E -10	2,500E -10	2,000E -10	1,500E -10	2,000E -10	2,500E -10	2,500E -10
24	3,000E -10	3,000E -10	2,500E -10	2,500E -10	2,000E -10	2,000E -10	2,500E -10	2,000E -10
Statistics								
Min	2,500E -10	2,000E -10	1,500E -10	1,500E -10	1,500E -10	2,000E -10	1,000E -10	2,000E -10
Max	3,000E -10	3,000E -10	2,500E -10	3,000E -10				
Mean	2,625E -10	2,750E -10	2,250E -10	2,125E -10	2,000E -10	2,250E -10	1,875E -10	2,500E -10
Sigma	2,500E -11	5,000E -11	5,000E -11	4,787E -11	4,082E -11	2,887E -11	7,500E -11	4,082E -11

Test Step	192 hours
Serial #	
20 Ref.	2,500E -10
21	2,500E -10
22	2,500E -10
23	2,000E -10
24	2,000E -10
Statistics	
Min	2,000E -10
Max	2,500E -10
Mean	2,250E -10
Sigma	2,887E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Negative Input Current Low Level Pin A2: -IIL A2**

Vin=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	3,000E -10	2,500E -10	2,000E -10	2,000E -10	2,000E -10	2,000E -10	2,500E -10
21	3,000E -10	2,500E -10	2,500E -10	2,000E -10	2,500E -10	2,500E -10	1,500E -10	2,000E -10
22	2,000E -10	3,000E -10	2,000E -10	2,000E -10	2,500E -10	2,500E -10	2,000E -10	3,000E -10
23	2,000E -10	3,500E -10	2,500E -10	2,500E -10	2,500E -10	1,500E -10	2,500E -10	2,000E -10
24	2,000E -10	3,500E -10	2,000E -10	1,500E -10	2,000E -10	2,000E -10	2,500E -10	2,000E -10
Statistics								
Min	2,000E -10	2,500E -10	2,000E -10	1,500E -10	2,000E -10	1,500E -10	1,500E -10	2,000E -10
Max	3,000E -10	3,500E -10	2,500E -10	3,000E -10				
Mean	2,250E -10	3,125E -10	2,250E -10	2,000E -10	2,375E -10	2,125E -10	2,125E -10	2,250E -10
Sigma	5,000E -11	4,787E -11	2,887E -11	4,082E -11	2,500E -11	4,787E -11	4,787E -11	5,000E -11

Test Step	192 hours
Serial #	
20 Ref.	2,500E -10
21	1,000E -10
22	2,000E -10
23	1,500E -10
24	2,000E -10
Statistics	
Min	1,000E -10
Max	2,000E -10
Mean	1,625E -10
Sigma	4,787E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Negative Input Current Low Level Pin A1: -I<sub>IL</sub> A1**

V<sub>in</sub>=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,500E -10	2,500E -10	1,500E -10	2,500E -10	1,500E -10	2,000E -10	2,000E -10	2,500E -10
21	2,500E -10	2,000E -10	2,000E -10	2,000E -10	2,000E -10	2,500E -10	2,000E -10	2,000E -10
22	2,000E -10	2,500E -10	2,000E -10	2,000E -10	2,000E -10	1,000E -10	2,000E -10	2,000E -10
23	2,000E -10	2,000E -10	2,000E -10	2,500E -10	1,500E -10	2,000E -10	2,000E -10	2,000E -10
24	3,000E -10	2,500E -10	1,500E -10	1,000E -10	2,000E -10	1,000E -10	2,500E -10	1,500E -10
Statistics								
Min	2,000E -10	2,000E -10	1,500E -10	1,000E -10	1,500E -10	1,000E -10	2,000E -10	1,500E -10
Max	3,000E -10	2,500E -10	2,000E -10	2,500E -10	2,000E -10	2,500E -10	2,500E -10	2,000E -10
Mean	2,375E -10	2,250E -10	1,875E -10	1,875E -10	1,875E -10	1,625E -10	2,125E -10	1,875E -10
Sigma	4,787E -11	2,887E -11	2,500E -11	6,292E -11	2,500E -11	7,500E -11	2,500E -11	2,500E -11

Test Step	192 hours
Serial #	
20 Ref.	2,500E -10
21	1,500E -10
22	2,000E -10
23	1,500E -10
24	1,000E -10
Statistics	
Min	1,000E -10
Max	2,000E -10
Mean	1,500E -10
Sigma	4,082E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :	Samsung			

**Parameter : Negative Input Current Low Level Pin A0: -IIL A0**

Vin=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,500E -10	2,500E -10	2,500E -10	3,000E -10	1,500E -10	2,500E -10	2,000E -10	1,500E -10
21	2,500E -10	2,000E -10	2,000E -10	1,000E -10	2,500E -10	1,500E -10	1,500E -10	2,500E -10
22	2,000E -10	2,000E -10	2,500E -10	2,000E -10	2,500E -10	2,500E -10	1,000E -10	2,000E -10
23	2,000E -10	2,500E -10	2,000E -10	1,000E -10	3,000E -10	2,000E -10	2,000E -10	2,500E -10
24	2,500E -10	2,500E -10	2,500E -10	2,500E -10	1,500E -10	2,500E -10	2,000E -10	2,500E -10
Statistics								
Min	2,000E -10	2,000E -10	2,000E -10	1,000E -10	1,500E -10	1,500E -10	1,000E -10	2,000E -10
Max	2,500E -10	2,500E -10	2,500E -10	2,500E -10	3,000E -10	2,500E -10	2,000E -10	2,500E -10
Mean	2,250E -10	2,250E -10	2,250E -10	1,625E -10	2,375E -10	2,125E -10	1,625E -10	2,375E -10
Sigma	2,887E -11	2,887E -11	2,887E -11	7,500E -11	6,292E -11	4,787E -11	4,787E -11	2,500E -11

Test Step	192 hours
Serial #	
20 Ref.	2,500E -10
21	1,500E -10
22	2,500E -10
23	2,000E -10
24	2,000E -10
Statistics	
Min	1,500E -10
Max	2,500E -10
Mean	2,000E -10
Sigma	4,082E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : High Input Current Pin A18: iiH A18**

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	1,000E -10	1,500E -10	1,500E -10	2,000E -10	1,000E -10	1,000E -10	1,500E -10	2,000E -10
21	1,000E -10	1,000E -10	1,500E -10	2,000E -10	1,000E -10	1,500E -10	1,000E -10	1,000E -10
22	1,500E -10	2,000E -10	2,000E -10	1,000E -10	2,000E -10	2,000E -10	2,000E -10	1,000E -10
23	1,000E -10	1,500E -10	1,500E -10	1,000E -10	1,000E -10	1,500E -10	1,000E -10	1,500E -10
24	1,500E -10	1,500E -10	1,000E -10	1,500E -10	1,000E -10	2,000E -10	2,000E -10	1,500E -10
Statistics								
Min	1,000E -10	1,500E -10	1,000E -10	1,000E -10				
Max	1,500E -10	2,000E -10	1,500E -10					
Mean	1,250E -10	1,500E -10	1,500E -10	1,375E -10	1,250E -10	1,750E -10	1,500E -10	1,250E -10
Sigma	2,887E -11	4,082E -11	4,082E -11	4,787E -11	5,000E -11	2,887E -11	5,774E -11	2,887E -11

Test Step	192 hours
Serial #	
20 Ref.	1,000E -10
21	1,000E -10
22	1,000E -10
23	1,500E -10
24	1,000E -10
Statistics	
Min	1,000E -10
Max	1,500E -10
Mean	1,125E -10
Sigma	2,500E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : High Input Current Pin A17: iiH A17**

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	1,000E -10	2,000E -10	2,000E -10	1,000E -10	1,000E -10	1,000E -10	2,000E -10	1,000E -10
21	1,000E -10	1,500E -10	1,500E -10	2,000E -10	1,000E -10	1,000E -10	1,000E -10	1,000E -10
22	1,000E -10	2,000E -10	2,000E -10	1,000E -10				
23	1,000E -10	2,000E -10	1,000E -10	1,500E -10	1,000E -10	1,000E -10	1,500E -10	2,000E -10
24	1,500E -10	2,000E -10	1,000E -10	1,000E -10	1,000E -10	1,000E -10	2,000E -10	2,000E -10
Statistics								
Min	1,000E -10	1,500E -10	1,000E -10					
Max	1,500E -10	2,000E -10	2,000E -10	2,000E -10	1,000E -10	1,000E -10	2,000E -10	2,000E -10
Mean	1,125E -10	1,875E -10	1,375E -10	1,375E -10	1,000E -10	1,000E -10	1,375E -10	1,500E -10
Sigma	2,500E -11	2,500E -11	4,787E -11	4,787E -11	9,389E -20	9,389E -20	4,787E -11	5,774E -11

Test Step	192 hours
Serial #	
20 Ref.	1,000E -10
21	1,000E -10
22	2,000E -10
23	1,000E -10
24	2,000E -10
Statistics	
Min	1,000E -10
Max	2,000E -10
Mean	1,500E -10
Sigma	5,774E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : High Input Current Pin A16: iiH A16**

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	2,500E -10	2,000E -10	2,000E -10	1,000E -10	2,000E -10	2,000E -10	2,000E -10
21	1,000E -10	1,500E -10	1,000E -10	1,000E -10	2,000E -10	2,000E -10	1,000E -10	1,000E -10
22	2,500E -10	1,000E -10	2,000E -10	2,000E -10	1,000E -10	1,500E -10	2,000E -10	1,000E -10
23	2,000E -10	1,500E -10	2,000E -10	1,000E -10	2,000E -10	1,000E -10	1,000E -10	1,500E -10
24	2,000E -10	1,000E -10	2,000E -10	2,000E -10	2,000E -10	1,000E -10	1,500E -10	2,000E -10
Statistics								
Min	1,000E -10							
Max	2,500E -10	1,500E -10	2,000E -10					
Mean	1,875E -10	1,250E -10	1,750E -10	1,500E -10	1,750E -10	1,375E -10	1,375E -10	1,375E -10
Sigma	6,292E -11	2,887E -11	5,000E -11	5,774E -11	5,000E -11	4,787E -11	4,787E -11	4,787E -11

Test Step	192 hours
Serial #	
20 Ref.	1,000E -10
21	1,000E -10
22	2,000E -10
23	1,000E -10
24	1,000E -10
Statistics	
Min	1,000E -10
Max	2,000E -10
Mean	1,250E -10
Sigma	5,000E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : High Input Current Pin A15: IiH A15**

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	1,000E -10	1,000E -10	1,000E -10	2,000E -10	2,000E -10	3,000E -10	3,000E -10	2,000E -10
21	1,000E -10	1,000E -10	2,000E -10	2,000E -10	1,500E -10	2,500E -10	1,500E -10	1,500E -10
22	1,000E -10	2,000E -10	1,000E -10	1,500E -10	3,000E -10	2,000E -10	2,000E -10	1,000E -10
23	2,000E -10	2,000E -10	2,000E -10	2,500E -10	1,500E -10	1,000E -10	1,500E -10	2,500E -10
24	1,000E -10	2,000E -10	2,000E -10	1,500E -10	1,500E -10	2,000E -10	1,500E -10	2,500E -10
Statistics								
Min	1,000E -10	1,000E -10	1,000E -10	1,500E -10	1,500E -10	1,000E -10	1,500E -10	1,000E -10
Max	2,000E -10	2,000E -10	2,000E -10	2,500E -10	3,000E -10	2,500E -10	2,000E -10	2,500E -10
Mean	1,250E -10	1,750E -10	1,750E -10	1,875E -10	1,875E -10	1,875E -10	1,625E -10	1,875E -10
Sigma	5,000E -11	5,000E -11	5,000E -11	4,787E -11	7,500E -11	6,292E -11	2,500E -11	7,500E -11

Test Step	192 hours
Serial #	
20 Ref.	2,000E -10
21	1,000E -10
22	1,000E -10
23	2,000E -10
24	3,000E -10
Statistics	
Min	1,000E -10
Max	3,000E -10
Mean	1,750E -10
Sigma	9,574E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :	Samsung			

**Parameter : High Input Current Pin A14: iiH A14**

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	1,000E -10	1,000E -10	1,000E -10	1,500E -10	1,500E -10	2,000E -10	1,000E -10
21	2,000E -10	1,000E -10	1,000E -10	1,500E -10	2,000E -10	2,000E -10	1,500E -10	1,500E -10
22	2,000E -10	1,000E -10	2,000E -10	1,500E -10	1,500E -10	2,000E -10	2,500E -10	2,000E -10
23	3,000E -10	2,000E -10	1,000E -10	2,000E -10	1,500E -10	1,500E -10	1,500E -10	1,500E -10
24	1,000E -10	2,000E -10	1,000E -10	1,000E -10	2,500E -10	1,500E -10	1,000E -10	2,000E -10
Statistics								
Min	1,000E -10	1,000E -10	1,000E -10	1,000E -10	1,500E -10	1,500E -10	1,000E -10	1,500E -10
Max	3,000E -10	2,000E -10	2,000E -10	2,000E -10	2,500E -10	2,000E -10	2,500E -10	2,000E -10
Mean	2,000E -10	1,500E -10	1,250E -10	1,500E -10	1,875E -10	1,750E -10	1,625E -10	1,750E -10
Sigma	8,165E -11	5,774E -11	5,000E -11	4,082E -11	4,787E -11	2,887E -11	6,292E -11	2,887E -11

Test Step	192 hours
Serial #	
20 Ref.	3,000E -10
21	2,500E -10
22	2,000E -10
23	1,500E -10
24	3,000E -10
Statistics	
Min	1,500E -10
Max	3,000E -10
Mean	2,250E -10
Sigma	6,455E -11



HIKEX Engineering	Total Dose Test Report					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

Parameter : High Input Current Pin A13: iiH A13

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	1,000E -10	1,000E -10	2,000E -10	1,000E -10	1,000E -10	2,000E -10	2,000E -10	2,000E -10
21	1,000E -10	2,000E -10	3,000E -10	2,500E -10	1,000E -10	2,500E -10	1,500E -10	2,000E -10
22	2,000E -10	1,000E -10	3,000E -10	1,000E -10	3,000E -10	2,000E -10	2,500E -10	1,000E -10
23	2,000E -10	2,000E -10	2,000E -10	1,000E -10	1,000E -10	1,500E -10	1,500E -10	2,000E -10
24	1,000E -10	2,000E -10	1,000E -10	2,000E -10	1,500E -10	1,500E -10	1,500E -10	2,000E -10
Statistics								
Min	1,000E -10	1,500E -10	1,500E -10	1,000E -10				
Max	2,000E -10	2,000E -10	3,000E -10	2,500E -10	3,000E -10	2,500E -10	2,500E -10	2,000E -10
Mean	1,500E -10	1,750E -10	2,250E -10	1,625E -10	1,625E -10	1,875E -10	1,750E -10	1,750E -10
Sigma	5,774E -11	5,000E -11	9,574E -11	7,500E -11	9,465E -11	4,787E -11	5,000E -11	5,000E -11

Test Step	192 hours
Serial #	
20 Ref.	2,000E -10
21	1,500E -10
22	3,000E -10
23	2,000E -10
24	2,500E -10
Statistics	
Min	1,500E -10
Max	3,000E -10
Mean	2,250E -10
Sigma	6,455E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : High Input Current Pin A12: iiH A12**

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	1,000E -10	2,000E -10	2,000E -10	1,000E -10	2,000E -10	1,000E -10	1,500E -10
21	2,000E -10	2,000E -10	3,000E -10	1,000E -10	2,000E -10	2,000E -10	1,000E -10	1,500E -10
22	2,000E -10	2,000E -10	1,000E -10	1,000E -10	1,000E -10	2,000E -10	2,000E -10	2,000E -10
23	3,000E -10	1,000E -10	1,000E -10	2,000E -10	1,000E -10	2,000E -10	2,000E -10	1,500E -10
24	2,000E -10	1,000E -10	1,000E -10	2,000E -10	1,500E -10	2,000E -10	1,000E -10	2,000E -10
Statistics								
Min	2,000E -10	1,000E -10	1,000E -10	1,000E -10	1,000E -10	2,000E -10	1,000E -10	1,500E -10
Max	3,000E -10	2,000E -10	3,000E -10	2,000E -10				
Mean	2,250E -10	1,500E -10	1,500E -10	1,500E -10	1,375E -10	2,000E -10	1,500E -10	1,750E -10
Sigma	5,000E -11	5,774E -11	1,000E -10	5,774E -11	4,787E -11	1,878E -19	5,774E -11	2,887E -11

Test Step	192 hours
Serial #	
20 Ref.	2,500E -10
21	2,500E -10
22	2,000E -10
23	2,500E -10
24	2,000E -10
Statistics	
Min	2,000E -10
Max	2,500E -10
Mean	2,250E -10
Sigma	2,887E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : High Input Current Pin A11: iiH A11**

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	1,000E -10	2,000E -10	2,000E -10	1,000E -10	3,000E -10	1,000E -10	1,000E -10
21	2,000E -10	1,000E -10	2,000E -10	2,000E -10	1,500E -10	1,000E -10	2,000E -10	2,000E -10
22	2,000E -10	2,000E -10	2,000E -10	1,500E -10	2,000E -10	1,500E -10	1,000E -10	2,500E -10
23	1,000E -10	2,000E -10	2,000E -10	1,500E -10	2,000E -10	1,500E -10	2,000E -10	1,000E -10
24	2,500E -10	1,000E -10	2,000E -10	1,500E -10	3,000E -10	2,000E -10	2,000E -10	1,500E -10
Statistics								
Min	1,000E -10	1,000E -10	2,000E -10	1,500E -10	1,500E -10	1,000E -10	1,000E -10	1,000E -10
Max	2,500E -10	2,000E -10	2,000E -10	2,000E -10	3,000E -10	2,000E -10	2,000E -10	2,500E -10
Mean	1,875E -10	1,500E -10	2,000E -10	1,625E -10	2,125E -10	1,500E -10	1,750E -10	1,750E -10
Sigma	6,292E -11	5,774E -11	1,878E -19	2,500E -11	6,292E -11	4,082E -11	5,000E -11	6,455E -11

Test Step	192 hours
Serial #	
20 Ref.	3,000E -10
21	2,000E -10
22	2,000E -10
23	1,000E -10
24	2,000E -10
Statistics	
Min	1,000E -10
Max	2,000E -10
Mean	1,750E -10
Sigma	5,000E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : High Input Current Pin A10: IiH A10**

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	1,000E -10	1,000E -10	3,000E -10	1,000E -10				
21	2,000E -10	2,000E -10	2,500E -10	1,500E -10	1,000E -10	2,000E -10	1,500E -10	1,000E -10
22	2,000E -10	1,000E -10	2,000E -10	1,500E -10	1,500E -10	2,000E -10	1,000E -10	1,500E -10
23	1,000E -10	2,000E -10	1,000E -10	2,000E -10	2,000E -10	1,500E -10	2,000E -10	1,500E -10
24	1,000E -10	2,000E -10	2,500E -10	2,000E -10	1,000E -10	1,500E -10	1,500E -10	1,000E -10
Statistics								
Min	1,000E -10	1,000E -10	1,000E -10	1,500E -10	1,000E -10	1,500E -10	1,000E -10	1,000E -10
Max	2,000E -10	2,000E -10	2,500E -10	2,000E -10	2,000E -10	2,000E -10	2,000E -10	1,500E -10
Mean	1,500E -10	1,750E -10	2,000E -10	1,750E -10	1,375E -10	1,750E -10	1,500E -10	1,250E -10
Sigma	5,774E -11	5,000E -11	7,071E -11	2,887E -11	4,787E -11	2,887E -11	4,082E -11	2,887E -11

Test Step	192 hours
Serial #	
20 Ref.	1,000E -10
21	1,500E -10
22	2,000E -10
23	1,500E -10
24	2,000E -10
Statistics	
Min	1,500E -10
Max	2,000E -10
Mean	1,750E -10
Sigma	2,887E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : High Input Current Pin A9: IiH A9**

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	2,000E -10	3,000E -10	2,500E -10	2,500E -10	2,000E -10	1,000E -10	1,500E -10
21	3,000E -10	2,000E -10	3,000E -10	1,000E -10	1,500E -10	2,000E -10	1,500E -10	2,000E -10
22	1,000E -10	1,000E -10	1,000E -10	2,000E -10	1,000E -10	2,500E -10	2,000E -10	1,500E -10
23	3,000E -10	2,000E -10	1,000E -10	1,000E -10	1,500E -10	2,000E -10	2,000E -10	2,500E -10
24	3,000E -10	2,000E -10	1,000E -10	2,500E -10	2,000E -10	2,000E -10	1,000E -10	2,000E -10
Statistics								
Min	1,000E -10	2,000E -10	1,000E -10	1,500E -10				
Max	3,000E -10	2,000E -10	3,000E -10	2,500E -10	2,000E -10	2,500E -10	2,000E -10	2,500E -10
Mean	2,500E -10	1,750E -10	1,500E -10	1,625E -10	1,500E -10	2,125E -10	1,625E -10	2,000E -10
Sigma	1,000E -10	5,000E -11	1,000E -10	7,500E -11	4,082E -11	2,500E -11	4,787E -11	4,082E -11

Test Step	192 hours
Serial #	
20 Ref.	2,000E -10
21	2,000E -10
22	2,500E -10
23	2,500E -10
24	2,000E -10
Statistics	
Min	2,000E -10
Max	2,500E -10
Mean	2,250E -10
Sigma	2,887E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : High Input Current Pin A8: IiH A8**

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	3,000E -10	2,000E -10	3,000E -10	1,000E -10	1,000E -10	2,000E -10	1,500E -10	2,000E -10
21	1,500E -10	1,000E -10	2,000E -10	1,500E -10	2,000E -10	2,000E -10	1,000E -10	1,500E -10
22	3,000E -10	1,000E -10	3,000E -10	2,000E -10	1,000E -10	1,000E -10	1,000E -10	2,000E -10
23	3,000E -10	2,000E -10	2,500E -10	2,000E -10	2,000E -10	1,500E -10	1,000E -10	1,000E -10
24	3,000E -10	1,000E -10	3,000E -10	1,000E -10	2,000E -10	2,000E -10	2,000E -10	1,000E -10
Statistics								
Min	1,500E -10	1,000E -10	2,000E -10	1,000E -10				
Max	3,000E -10	2,000E -10	3,000E -10	2,000E -10				
Mean	2,625E -10	1,250E -10	2,625E -10	1,625E -10	1,750E -10	1,625E -10	1,250E -10	1,375E -10
Sigma	7,500E -11	5,000E -11	4,787E -11	4,787E -11	5,000E -11	4,787E -11	5,000E -11	4,787E -11

Test Step	192 hours
Serial #	
20 Ref.	2,500E -10
21	1,500E -10
22	1,500E -10
23	3,000E -10
24	2,000E -10
Statistics	
Min	1,500E -10
Max	3,000E -10
Mean	2,000E -10
Sigma	7,071E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :	Samsung			

**Parameter : High Input Current Pin A7: IiH A7**

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	2,000E -10	1,000E -10	3,500E -10	4,000E -10	4,000E -10	2,000E -10	2,500E -10
21	2,000E -10	1,000E -10	1,000E -10	2,000E -10	4,000E -10	4,000E -10	1,000E -10	4,000E -10
22	1,000E -10	1,000E -10	2,000E -10	3,000E -10	3,000E -10	1,000E -10	2,500E -10	2,500E -10
23	1,000E -10	2,000E -10	2,000E -10	1,500E -10	4,000E -10	4,000E -10	1,000E -10	2,000E -10
24	1,000E -10	2,000E -10	2,000E -10	2,500E -10	2,000E -10	4,000E -10	1,500E -10	2,000E -10
Statistics								
Min	1,000E -10	1,000E -10	1,000E -10	1,500E -10	2,000E -10	1,000E -10	1,000E -10	2,000E -10
Max	2,000E -10	2,000E -10	2,000E -10	3,000E -10	4,000E -10	4,000E -10	2,500E -10	4,000E -10
Mean	1,250E -10	1,500E -10	1,750E -10	2,250E -10	3,250E -10	3,250E -10	1,500E -10	2,625E -10
Sigma	5,000E -11	5,774E -11	5,000E -11	6,455E -11	9,574E -11	1,500E -10	7,071E -11	9,465E -11

Test Step	192 hours
Serial #	
20 Ref.	1,000E -10
21	2,000E -10
22	4,000E -10
23	2,000E -10
24	2,000E -10
Statistics	
Min	2,000E -10
Max	4,000E -10
Mean	2,500E -10
Sigma	1,000E -10



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :	Samsung			

**Parameter : High Input Current Pin A6: IiH A6**

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	3,000E -10	6,000E -10	5,000E -10	1,500E -10	4,000E -10	3,000E -10	2,500E -10	4,000E -10
21	5,500E -10	6,000E -10	5,500E -10	2,000E -10	3,000E -10	4,500E -10	1,500E -10	2,500E -10
22	4,000E -10	4,000E -10	5,000E -10	1,500E -10	3,000E -10	4,500E -10	3,000E -10	2,500E -10
23	6,000E -10	5,500E -10	4,000E -10	2,500E -10	2,000E -10	4,500E -10	2,000E -10	2,000E -10
24	4,000E -10	4,000E -10	6,000E -10	2,500E -10	3,500E -10	4,000E -10	2,000E -10	4,000E -10
Statistics								
Min	4,000E -10	4,000E -10	4,000E -10	1,500E -10	2,000E -10	4,000E -10	1,500E -10	2,000E -10
Max	6,000E -10	6,000E -10	6,000E -10	2,500E -10	3,500E -10	4,500E -10	3,000E -10	4,000E -10
Mean	4,875E -10	4,875E -10	5,125E -10	2,125E -10	2,875E -10	4,375E -10	2,125E -10	2,750E -10
Sigma	1,031E -10	1,031E -10	8,539E -11	4,787E -11	6,292E -11	2,500E -11	6,292E -11	8,660E -11

Test Step	192 hours
Serial #	
20 Ref.	3,000E -10
21	4,000E -10
22	4,000E -10
23	4,500E -10
24	3,000E -10
Statistics	
Min	3,000E -10
Max	4,500E -10
Mean	3,875E -10
Sigma	6,292E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : High Input Current Pin A5: IiH A5**

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	4,000E -10	4,000E -10	5,000E -10	3,000E -10	3,000E -10	4,000E -10	3,000E -10	3,000E -10
21	4,500E -10	5,500E -10	4,500E -10	3,500E -10	4,000E -10	3,000E -10	1,500E -10	1,500E -10
22	5,000E -10	5,000E -10	4,000E -10	1,500E -10	3,500E -10	2,000E -10	3,000E -10	2,000E -10
23	6,000E -10	6,000E -10	5,000E -10	4,000E -10	2,000E -10	2,000E -10	2,000E -10	2,000E -10
24	5,500E -10	6,000E -10	5,000E -10	3,000E -10	3,000E -10	2,500E -10	2,000E -10	4,000E -10
Statistics								
Min	4,500E -10	5,000E -10	4,000E -10	1,500E -10	2,000E -10	2,000E -10	1,500E -10	1,500E -10
Max	6,000E -10	6,000E -10	5,000E -10	4,000E -10	4,000E -10	3,000E -10	3,000E -10	4,000E -10
Mean	5,250E -10	5,625E -10	4,625E -10	3,000E -10	3,125E -10	2,375E -10	2,125E -10	2,375E -10
Sigma	6,455E -11	4,787E -11	4,787E -11	1,080E -10	8,539E -11	4,787E -11	6,292E -11	1,109E -10

Test Step	192 hours
Serial #	
20 Ref.	4,500E -10
21	3,000E -10
22	4,000E -10
23	3,500E -10
24	3,500E -10
Statistics	
Min	3,000E -10
Max	4,000E -10
Mean	3,500E -10
Sigma	4,082E -11



HIREX Engineering	Total Dose Test Report						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung				

Parameter : High Input Current Pin A4: IiH A4

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	3,500E -10	4,000E -10	4,500E -10	1,500E -10	3,000E -10	3,500E -10	1,500E -10	2,000E -10
21	4,500E -10	3,500E -10	4,000E -10	2,000E -10	2,500E -10	3,000E -10	1,500E -10	2,000E -10
22	6,000E -10	5,500E -10	6,000E -10	2,500E -10	4,000E -10	2,500E -10	2,000E -10	4,000E -10
23	5,000E -10	5,500E -10	5,000E -10	2,500E -10	1,500E -10	2,000E -10	2,500E -10	2,500E -10
24	5,000E -10	4,500E -10	5,000E -10	4,000E -10	2,000E -10	2,500E -10	2,000E -10	4,000E -10
Statistics								
Min	4,500E -10	3,500E -10	4,000E -10	2,000E -10	1,500E -10	2,000E -10	1,500E -10	2,000E -10
Max	6,000E -10	5,500E -10	6,000E -10	4,000E -10	4,000E -10	3,000E -10	2,500E -10	4,000E -10
Mean	5,125E -10	4,750E -10	5,000E -10	2,750E -10	2,500E -10	2,500E -10	2,000E -10	3,125E -10
Sigma	6,292E -11	9,574E -11	8,165E -11	8,660E -11	1,080E -10	4,082E -11	4,082E -11	1,031E -10

Test Step	192 hours
Serial #	
20 Ref.	3,000E -10
21	3,500E -10
22	2,500E -10
23	3,000E -10
24	2,000E -10
Statistics	
Min	2,000E -10
Max	3,500E -10
Mean	2,750E -10
Sigma	6,455E -11



HIREX Engineering	Total Dose Test Report					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

Parameter : High Input Current Pin A3: IiH A3

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	5,500E -10	3,000E -10	6,000E -10	2,000E -10	3,000E -10	2,500E -10	1,500E -10	2,000E -10
21	4,500E -10	3,000E -10	4,500E -10	2,000E -10	2,000E -10	3,000E -10	2,000E -10	2,000E -10
22	6,000E -10	4,000E -10	4,500E -10	2,000E -10	2,000E -10	4,000E -10	2,500E -10	1,500E -10
23	3,500E -10	4,000E -10	5,000E -10	3,000E -10	3,000E -10	4,000E -10	2,000E -10	1,500E -10
24	6,000E -10	6,000E -10	6,000E -10	1,500E -10	3,000E -10	1,500E -10	3,000E -10	2,500E -10
Statistics								
Min	3,500E -10	3,000E -10	4,500E -10	1,500E -10	2,000E -10	1,500E -10	2,000E -10	1,500E -10
Max	6,000E -10	6,000E -10	6,000E -10	3,000E -10	3,000E -10	4,000E -10	3,000E -10	2,500E -10
Mean	5,000E -10	4,250E -10	5,000E -10	2,125E -10	2,500E -10	3,125E -10	2,375E -10	1,875E -10
Sigma	1,225E -10	1,258E -10	7,071E -11	6,292E -11	5,774E -11	1,181E -10	4,787E -11	4,787E -11

Test Step	192 hours
Serial #	
20 Ref.	2,500E -10
21	4,000E -10
22	2,500E -10
23	4,000E -10
24	2,500E -10
Statistics	
Min	2,500E -10
Max	4,000E -10
Mean	3,250E -10
Sigma	8,660E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : High Input Current Pin A2: IiH A2**

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	4,000E -10	3,000E -10	4,000E -10	1,500E -10	2,000E -10	4,000E -10	2,500E -10	3,000E -10
21	4,000E -10	4,000E -10	4,500E -10	2,000E -10	2,500E -10	4,000E -10	2,000E -10	3,000E -10
22	5,500E -10	6,000E -10	2,500E -10	4,000E -10	4,000E -10	3,000E -10	1,000E -10	2,000E -10
23	4,500E -10	3,000E -10	4,500E -10	2,000E -10	2,000E -10	2,000E -10	2,000E -10	1,500E -10
24	5,000E -10	5,500E -10	4,000E -10	3,500E -10	3,000E -10	2,000E -10	1,500E -10	1,500E -10
Statistics								
Min	4,000E -10	3,000E -10	2,500E -10	2,000E -10	2,000E -10	2,000E -10	1,000E -10	1,500E -10
Max	5,500E -10	6,000E -10	4,500E -10	4,000E -10	4,000E -10	4,000E -10	2,000E -10	3,000E -10
Mean	4,750E -10	4,625E -10	3,875E -10	2,875E -10	2,875E -10	2,750E -10	1,625E -10	2,000E -10
Sigma	6,455E -11	1,377E -10	9,465E -11	1,031E -10	8,539E -11	9,574E -11	4,787E -11	7,071E -11

Test Step	192 hours
Serial #	
20 Ref.	4,000E -10
21	4,000E -10
22	2,000E -10
23	4,000E -10
24	2,500E -10
Statistics	
Min	2,000E -10
Max	4,000E -10
Mean	3,125E -10
Sigma	1,031E -10



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : High Input Current Pin A1: IiH A1**

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	4,000E -10	4,500E -10	4,500E -10	1,500E -10	2,000E -10	2,000E -10	1,500E -10	3,000E -10
21	4,000E -10	5,000E -10	4,000E -10	2,000E -10	1,000E -10	3,000E -10	2,000E -10	2,000E -10
22	3,500E -10	4,000E -10	5,000E -10	3,000E -10	2,000E -10	2,000E -10	1,500E -10	1,500E -10
23	3,500E -10	5,500E -10	4,000E -10	2,000E -10	2,500E -10	2,000E -10	2,000E -10	1,500E -10
24	3,500E -10	4,000E -10	5,500E -10	2,500E -10	4,000E -10	2,500E -10	2,000E -10	2,000E -10
Statistics								
Min	3,500E -10	4,000E -10	4,000E -10	2,000E -10	1,000E -10	2,000E -10	1,500E -10	1,500E -10
Max	4,000E -10	5,500E -10	5,500E -10	3,000E -10	4,000E -10	3,000E -10	2,000E -10	2,000E -10
Mean	3,625E -10	4,625E -10	4,625E -10	2,375E -10	2,375E -10	2,375E -10	1,875E -10	1,750E -10
Sigma	2,500E -11	7,500E -11	7,500E -11	4,787E -11	1,250E -10	4,787E -11	2,500E -11	2,887E -11

Test Step	192 hours
Serial #	
20 Ref.	4,000E -10
21	3,000E -10
22	3,000E -10
23	3,500E -10
24	3,500E -10
Statistics	
Min	3,000E -10
Max	3,500E -10
Mean	3,250E -10
Sigma	2,887E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :	Samsung			

**Parameter : High Input Current Pin A0: IiH A0**

Vin=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	5,000E -10	4,000E -10	4,500E -10	2,500E -10	2,000E -10	4,000E -10	2,000E -10	1,500E -10
21	3,500E -10	5,500E -10	3,500E -10	2,500E -10	2,500E -10	2,500E -10	2,500E -10	1,500E -10
22	6,000E -10	6,000E -10	3,000E -10	1,500E -10	2,000E -10	2,000E -10	1,500E -10	3,000E -10
23	4,500E -10	3,000E -10	4,000E -10	3,000E -10	3,500E -10	3,000E -10	1,500E -10	2,500E -10
24	4,500E -10	5,000E -10	4,500E -10	2,000E -10	2,000E -10	4,000E -10	2,000E -10	2,000E -10
Statistics								
Min	3,500E -10	3,000E -10	3,000E -10	1,500E -10	2,000E -10	2,000E -10	1,500E -10	1,500E -10
Max	6,000E -10	6,000E -10	4,500E -10	3,000E -10	3,500E -10	4,000E -10	2,500E -10	3,000E -10
Mean	4,625E -10	4,875E -10	3,750E -10	2,250E -10	2,500E -10	2,875E -10	1,875E -10	2,250E -10
Sigma	1,031E -10	1,315E -10	6,455E -11	6,455E -11	7,071E -11	8,539E -11	4,787E -11	6,455E -11

Test Step	192 hours
Serial #	
20 Ref.	2,500E -10
21	4,500E -10
22	2,000E -10
23	3,000E -10
24	3,000E -10
Statistics	
Min	2,000E -10
Max	4,500E -10
Mean	3,125E -10
Sigma	1,031E -10



HIREX Engineering	Total Dose Test Report					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Output Current Low Level Pin I/O7: IoZL I/O7**

**Vout=0V**


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	-5,000E -11	-2,500E -10	-2,000E -10	-1,000E -10	0,000E +00	-1,000E -10	-1,000E -10	-1,000E -10
21	-1,500E -10	-1,500E -10	-1,000E -10	-1,500E -10	-1,000E -10	-1,500E -10	-5,000E -11	0,000E +00
22	1,000E -10	-3,000E -10	-1,500E -10	0,000E +00	0,000E +00	-1,500E -10	-1,000E -10	-1,000E -10
23	-1,000E -10	-2,000E -10	-5,000E -11	-5,000E -11	0,000E +00	-1,500E -10	0,000E +00	-5,000E -11
24	-1,000E -10	-2,000E -10	-1,500E -10	-1,000E -10	-1,000E -10	-5,000E -11	0,000E +00	0,000E +00
Statistics								
Min	-1,500E -10	-3,000E -10	-1,500E -10	-1,500E -10	-1,000E -10	-1,500E -10	-1,000E -10	-1,000E -10
Max	1,000E -10	-1,500E -10	-5,000E -11	0,000E +00	0,000E +00	-5,000E -11	0,000E +00	0,000E +00
Mean	-6,250E -11	-2,125E -10	-1,125E -10	-7,500E -11	-5,000E -11	-1,250E -10	-3,750E -11	-3,750E -11
Sigma	1,109E -10	6,292E -11	4,787E -11	6,455E -11	5,774E -11	5,000E -11	4,787E -11	4,787E -11

Test Step	192 hours
Serial #	
20 Ref.	0,000E +00
21	0,000E +00
22	-1,000E -10
23	0,000E +00
24	-5,000E -11
Statistics	
Min	-1,000E -10
Max	0,000E +00
Mean	-3,750E -11
Sigma	4,787E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :	Samsung		

**Parameter : Output Current Low Level Pin I/O6: IozL I/O6**

**Vout=0V**


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	-1,000E -10	-1,500E -10	-1,500E -10	-2,000E -10	-1,500E -10	-5,000E -11	0,000E +00	-1,500E -10
21	-1,000E -10	-1,500E -10	-2,000E -10	-1,000E -10	-1,500E -10	-1,500E -10	-1,000E -10	0,000E +00
22	5,000E -11	-1,500E -10	-2,000E -10	-1,000E -10	0,000E +00	-2,000E -10	-1,500E -10	-1,000E -10
23	-2,000E -10	-1,000E -10	0,000E +00	-1,000E -10	-1,000E -10	-5,000E -11	0,000E +00	-1,000E -10
24	-1,000E -10	-1,500E -10	-1,500E -10	-1,000E -10	0,000E +00	-1,500E -10	-1,500E -10	-5,000E -11
Statistics								
Min	-2,000E -10	-1,500E -10	-2,000E -10	-1,000E -10	-1,500E -10	-2,000E -10	-1,500E -10	-1,000E -10
Max	5,000E -11	-1,000E -10	0,000E +00	-1,000E -10	0,000E +00	-5,000E -11	0,000E +00	0,000E +00
Mean	-8,750E -11	-1,375E -10	-1,375E -10	-1,000E -10	-6,250E -11	-1,375E -10	-1,000E -10	-6,250E -11
Sigma	1,031E -10	2,500E -11	9,465E -11	9,389E -20	7,500E -11	6,292E -11	7,071E -11	4,787E -11

Test Step	192 hours
Serial #	
20 Ref.	0,000E +00
21	-1,000E -10
22	-1,000E -10
23	-1,000E -10
24	-1,500E -10
Statistics	
Min	-1,500E -10
Max	-1,000E -10
Mean	-1,125E -10
Sigma	2,500E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :	Samsung		

**Parameter : Output Current Low Level Pin I/O5: IoZL I/O5**

**Vout=0V**


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	-1,500E -10	-1,500E -10	-5,000E -11	-1,000E -10	5,000E -11	-1,000E -10	-5,000E -11	-1,500E -10
21	-1,000E -10	0,000E +00	-1,000E -10	-1,000E -10	0,000E +00	0,000E +00	-1,000E -10	-1,500E -10
22	0,000E +00	-1,000E -10	-1,000E -10	0,000E +00	-1,000E -10	0,000E +00	-5,000E -11	0,000E +00
23	0,000E +00	-1,000E -10	-5,000E -11	0,000E +00	-5,000E -11	-1,500E -10	0,000E +00	-1,000E -10
24	-5,000E -11	-1,000E -10	-1,500E -10	-5,000E -11	0,000E +00	-1,000E -10	0,000E +00	-1,000E -10
Statistics								
Min	-1,000E -10	-1,000E -10	-1,500E -10	-1,000E -10	-1,000E -10	-1,500E -10	-1,000E -10	-1,500E -10
Max	0,000E +00	0,000E +00	-5,000E -11	0,000E +00				
Mean	-3,750E -11	-7,500E -11	-1,000E -10	-3,750E -11	-3,750E -11	-6,250E -11	-3,750E -11	-8,750E -11
Sigma	4,787E -11	5,000E -11	4,082E -11	4,787E -11	4,787E -11	7,500E -11	4,787E -11	6,292E -11

Test Step	192 hours
Serial #	
20 Ref.	0,000E +00
21	-1,000E -10
22	0,000E +00
23	-1,000E -10
24	-5,000E -11
Statistics	
Min	-1,000E -10
Max	0,000E +00
Mean	-6,250E -11
Sigma	4,787E -11



HIREX Engineering	Total Dose Test Report						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung				

Parameter : Output Current Low Level Pin I/O4: IozL I/O4

Vout=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	-1,000E -10	-4,000E -10	-2,000E -10	-2,000E -10	-1,500E -10	-1,000E -10	0,000E +00	-1,500E -10
21	-5,000E -11	-2,500E -10	-5,000E -11	-1,000E -10	-1,000E -10	-1,000E -10	-1,000E -10	-1,500E -10
22	-1,000E -10	-3,000E -10	-1,000E -10	-1,000E -10	-1,000E -10	-5,000E -11	-1,000E -10	-1,000E -10
23	-1,500E -10	-3,000E -10	0,000E +00	0,000E +00	0,000E +00	-1,000E -10	-1,000E -10	-1,000E -10
24	-1,000E -10	-2,500E -10	-2,000E -10	-1,500E -10	5,000E -11	-1,500E -10	0,000E +00	-1,500E -10
Statistics								
Min	-1,500E -10	-3,000E -10	-2,000E -10	-1,500E -10	-1,000E -10	-1,500E -10	-1,000E -10	-1,500E -10
Max	-5,000E -11	-2,500E -10	0,000E +00	0,000E +00	5,000E -11	-5,000E -11	0,000E +00	-1,000E -10
Mean	-1,000E -10	-2,750E -10	-8,750E -11	-8,750E -11	-3,750E -11	-1,000E -10	-7,500E -11	-1,250E -10
Sigma	4,082E -11	2,887E -11	8,539E -11	6,292E -11	7,500E -11	4,082E -11	5,000E -11	2,887E -11

Test Step	192 hours
Serial #	
20 Ref.	-5,000E -11
21	0,000E +00
22	0,000E +00
23	-1,500E -10
24	-5,000E -11
Statistics	
Min	-1,500E -10
Max	0,000E +00
Mean	-5,000E -11
Sigma	7,071E -11



HIREX Engineering	Total Dose Test Report						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung				

Parameter : Output Current Low Level Pin I/O3: IoZL I/O3

Vout=0V


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	-1,000E -10	-5,000E -11	-1,500E -10	0,000E +00	-1,000E -10	-5,000E -11	-5,000E -11	-5,000E -11
21	-1,000E -10	-5,000E -11	-1,000E -10	0,000E +00	-1,000E -10	0,000E +00	0,000E +00	-5,000E -11
22	0,000E +00	-5,000E -11	-1,000E -10	-1,000E -10	-1,000E -10	-1,500E -10	-5,000E -11	0,000E +00
23	-1,500E -10	-1,000E -10	-5,000E -11	-1,000E -10	-5,000E -11	-1,500E -10	-1,000E -10	-1,000E -10
24	0,000E +00	5,000E -11	-1,000E -10	0,000E +00	5,000E -11	-5,000E -11	-5,000E -11	-1,500E -10
Statistics								
Min	-1,500E -10	-1,000E -10	-1,000E -10	-1,000E -10	-1,000E -10	-1,500E -10	-1,000E -10	-1,500E -10
Max	0,000E +00	5,000E -11	-5,000E -11	0,000E +00	5,000E -11	0,000E +00	0,000E +00	0,000E +00
Mean	-6,250E -11	-3,750E -11	-8,750E -11	-5,000E -11	-5,000E -11	-8,750E -11	-5,000E -11	-7,500E -11
Sigma	7,500E -11	6,292E -11	2,500E -11	5,774E -11	7,071E -11	7,500E -11	4,082E -11	6,455E -11

Test Step	192 hours
Serial #	
20 Ref.	-1,000E -10
21	-1,500E -10
22	-5,000E -11
23	-1,000E -10
24	-1,500E -10
Statistics	
Min	-1,500E -10
Max	-5,000E -11
Mean	-1,125E -10
Sigma	4,787E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Output Current Low Level Pin I/O2: IoZL I/O2**

**Vout=0V**


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	-5,000E -11	-1,000E -10	-1,000E -10	-1,000E -10	-5,000E -11	0,000E +00	-1,000E -10	-1,000E -10
21	-1,500E -10	-1,000E -10	-5,000E -11	-1,000E -10	-1,000E -10	-5,000E -11	-1,000E -10	-1,500E -10
22	-1,500E -10	0,000E +00	-1,000E -10	-1,000E -10	-5,000E -11	0,000E +00	-1,500E -10	-1,500E -10
23	-5,000E -11	-5,000E -11	-1,500E -10	0,000E +00	-5,000E -11	-1,000E -10	-5,000E -11	0,000E +00
24	-1,000E -10	0,000E +00	-5,000E -11	0,000E +00	0,000E +00	-1,000E -10	0,000E +00	-1,000E -10
Statistics								
Min	-1,500E -10	-1,000E -10	-1,500E -10	-1,000E -10	-1,000E -10	-1,000E -10	-1,500E -10	-1,500E -10
Max	-5,000E -11	0,000E +00	-5,000E -11	0,000E +00				
Mean	-1,125E -10	-3,750E -11	-8,750E -11	-5,000E -11	-5,000E -11	-6,250E -11	-7,500E -11	-1,000E -10
Sigma	4,787E -11	4,787E -11	4,787E -11	5,774E -11	4,082E -11	4,787E -11	6,455E -11	7,071E -11

Test Step	192 hours
Serial #	
20 Ref.	-1,500E -10
21	0,000E +00
22	0,000E +00
23	0,000E +00
24	5,000E -11
Statistics	
Min	0,000E +00
Max	5,000E -11
Mean	1,250E -11
Sigma	2,500E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :	Samsung		

**Parameter : Output Current Low Level Pin I/O1: IoZL I/O1**

**Vout=0V**


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	-1,000E -10	-1,500E -10	-1,000E -10	-1,000E -10	-1,000E -10	-1,500E -10	0,000E +00	-1,000E -10
21	0,000E +00	-5,000E -11	-5,000E -11	-1,000E -10	-1,000E -10	-5,000E -11	0,000E +00	-5,000E -11
22	-1,500E -10	-1,000E -10	-1,000E -10	5,000E -11	0,000E +00	0,000E +00	0,000E +00	-1,000E -10
23	-1,500E -10	-5,000E -11	-5,000E -11	-1,000E -10	0,000E +00	0,000E +00	0,000E +00	-1,500E -10
24	-5,000E -11	5,000E -11	-1,000E -10	-1,000E -10	0,000E +00	-1,000E -10	-5,000E -11	-5,000E -11
Statistics								
Min	-1,500E -10	-1,000E -10	-5,000E -11	-1,500E -10				
Max	0,000E +00	5,000E -11	-5,000E -11	5,000E -11	0,000E +00	0,000E +00	0,000E +00	-5,000E -11
Mean	-8,750E -11	-3,750E -11	-7,500E -11	-6,250E -11	-2,500E -11	-3,750E -11	-1,250E -11	-8,750E -11
Sigma	7,500E -11	6,292E -11	2,887E -11	7,500E -11	5,000E -11	4,787E -11	2,500E -11	4,787E -11

Test Step	192 hours
Serial #	
20 Ref.	-1,000E -10
21	0,000E +00
22	-1,000E -10
23	0,000E +00
24	-1,000E -10
Statistics	
Min	-1,000E -10
Max	0,000E +00
Mean	-5,000E -11
Sigma	5,774E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Output Current Low Level Pin I/O0: IozL I/O0**

**Vout=0V**


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	-1,500E -10	-1,000E -10	-1,500E -10	0,000E +00	-1,000E -10	-1,000E -10	0,000E +00	-1,000E -10
21	-5,000E -11	-5,000E -11	-1,000E -10	-1,000E -10	-5,000E -11	-1,000E -10	-1,000E -10	-5,000E -11
22	0,000E +00	0,000E +00	0,000E +00	-1,000E -10	-1,500E -10	0,000E +00	0,000E +00	0,000E +00
23	-5,000E -11	0,000E +00	-1,500E -10	-5,000E -11	0,000E +00	-5,000E -11	-1,500E -10	-5,000E -11
24	-1,000E -10	0,000E +00	0,000E +00	-1,000E -10	-1,000E -10	-1,500E -10	-5,000E -11	-1,000E -10
Statistics								
Min	-1,000E -10	-5,000E -11	-1,500E -10	-1,000E -10	-1,500E -10	-1,500E -10	-1,500E -10	-1,000E -10
Max	0,000E +00	0,000E +00	0,000E +00	-5,000E -11	0,000E +00	0,000E +00	0,000E +00	0,000E +00
Mean	-5,000E -11	-1,250E -11	-6,250E -11	-8,750E -11	-7,500E -11	-7,500E -11	-7,500E -11	-5,000E -11
Sigma	4,082E -11	2,500E -11	7,500E -11	2,500E -11	6,455E -11	6,455E -11	6,455E -11	4,082E -11

Test Step	192 hours
Serial #	
20 Ref.	0,000E +00
21	5,000E -11
22	0,000E +00
23	-1,000E -10
24	-5,000E -11
Statistics	
Min	-1,000E -10
Max	5,000E -11
Mean	-2,500E -11
Sigma	6,455E -11



HIREX Engineering	Total Dose Test Report					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

Parameter : Output Current High Level Pin I/O7: IoZH I/O7

Vout=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	3,500E -10	2,000E -10	4,000E -10	1,500E -10	1,000E -10	1,000E -10	1,000E -10	1,500E -10
21	2,000E -10	2,000E -10	3,000E -10	2,000E -10	1,500E -10	2,000E -10	1,500E -10	2,000E -10
22	2,000E -10	2,000E -10	3,000E -10	1,500E -10	2,000E -10	1,500E -10	1,000E -10	1,000E -10
23	2,000E -10	2,000E -10	4,000E -10	1,500E -10	1,500E -10	1,500E -10	1,000E -10	1,500E -10
24	3,000E -10	2,000E -10	2,500E -10	2,000E -10	2,000E -10	2,000E -10	2,000E -10	1,000E -10
Statistics								
Min	2,000E -10	2,000E -10	2,500E -10	1,500E -10	1,500E -10	1,500E -10	1,000E -10	1,000E -10
Max	3,000E -10	2,000E -10	4,000E -10	2,000E -10				
Mean	2,250E -10	2,000E -10	3,125E -10	1,750E -10	1,750E -10	1,750E -10	1,375E -10	1,375E -10
Sigma	5,000E -11	1,878E -19	6,292E -11	2,887E -11	2,887E -11	2,887E -11	4,787E -11	4,787E -11

Test Step	192 hours
Serial #	
20 Ref.	2,500E -10
21	2,000E -10
22	1,500E -10
23	2,000E -10
24	1,500E -10
Statistics	
Min	1,500E -10
Max	2,000E -10
Mean	1,750E -10
Sigma	2,887E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Output Current High Level Pin I/O6: IoZH I/O6**

**Vout=Vcc**


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	2,000E -10	3,000E -10	1,000E -10	2,500E -10	2,000E -10	1,500E -10	1,000E -10
21	4,000E -10	2,000E -10	3,000E -10	2,000E -10	1,000E -10	1,000E -10	1,000E -10	1,000E -10
22	2,500E -10	2,000E -10	2,500E -10	2,000E -10	1,000E -10	2,000E -10	2,000E -10	1,500E -10
23	2,000E -10	2,000E -10	2,500E -10	2,000E -10	1,500E -10	1,500E -10	1,500E -10	1,000E -10
24	2,500E -10	2,000E -10	3,000E -10	1,000E -10	2,000E -10	1,500E -10	1,500E -10	1,500E -10
Statistics								
Min	2,000E -10	2,000E -10	2,500E -10	1,000E -10				
Max	4,000E -10	2,000E -10	3,000E -10	2,000E -10	2,000E -10	2,000E -10	2,000E -10	1,500E -10
Mean	2,750E -10	2,000E -10	2,750E -10	1,750E -10	1,375E -10	1,500E -10	1,500E -10	1,250E -10
Sigma	8,660E -11	1,878E -19	2,887E -11	5,000E -11	4,787E -11	4,082E -11	4,082E -11	2,887E -11

Test Step	192 hours
Serial #	
20 Ref.	1,500E -10
21	1,500E -10
22	1,500E -10
23	1,500E -10
24	1,500E -10
Statistics	
Min	1,500E -10
Max	1,500E -10
Mean	1,500E -10
Sigma	2,028E -19



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Output Current High Level Pin I/O5: IoZH I/O5**

**Vout=Vcc**


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	5,500E -10	2,000E -10	1,500E -10	1,500E -10	1,500E -10	1,000E -10	1,000E -10
21	1,000E -10	2,000E -10	3,000E -10	2,000E -10	1,500E -10	2,000E -10	1,000E -10	1,500E -10
22	1,500E -10	6,000E -10	2,000E -10	1,500E -10	1,000E -10	2,000E -10	1,500E -10	2,000E -10
23	1,000E -10	6,000E -10	2,000E -10	1,500E -10	2,000E -10	1,000E -10	1,000E -10	2,000E -10
24	2,000E -10	2,000E -10	3,000E -10	1,000E -10	1,000E -10	1,500E -10	2,000E -10	2,000E -10
Statistics								
Min	1,000E -10	2,000E -10	2,000E -10	1,000E -10	1,000E -10	1,000E -10	1,000E -10	1,500E -10
Max	2,000E -10	6,000E -10	3,000E -10	2,000E -10				
Mean	1,375E -10	4,000E -10	2,500E -10	1,500E -10	1,375E -10	1,625E -10	1,375E -10	1,875E -10
Sigma	4,787E -11	2,309E -10	5,774E -11	4,082E -11	4,787E -11	4,787E -11	4,787E -11	2,500E -11

Test Step	192 hours
Serial #	
20 Ref.	2,000E -10
21	2,000E -10
22	2,000E -10
23	2,000E -10
24	1,500E -10
Statistics	
Min	1,500E -10
Max	2,000E -10
Mean	1,875E -10
Sigma	2,500E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Output Current High Level Pin I/O4: IoZH I/O4**

**Vout=Vcc**


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,500E -10	2,000E -10	2,500E -10	2,000E -10	2,000E -10	1,500E -10	1,000E -10	2,000E -10
21	4,000E -10	2,000E -10	2,500E -10	2,000E -10	1,000E -10	1,000E -10	1,000E -10	2,000E -10
22	2,000E -10	2,000E -10	2,000E -10	2,000E -10	1,000E -10	2,000E -10	2,000E -10	1,000E -10
23	2,500E -10	2,000E -10	3,500E -10	2,000E -10	2,000E -10	2,000E -10	1,000E -10	1,500E -10
24	2,000E -10	2,000E -10	3,000E -10	1,500E -10	1,000E -10	1,500E -10	2,000E -10	1,000E -10
Statistics								
Min	2,000E -10	2,000E -10	2,000E -10	1,500E -10	1,000E -10	1,000E -10	1,000E -10	1,000E -10
Max	4,000E -10	2,000E -10	3,500E -10	2,000E -10				
Mean	2,625E -10	2,000E -10	2,750E -10	1,875E -10	1,250E -10	1,625E -10	1,500E -10	1,375E -10
Sigma	9,465E -11	1,878E -19	6,455E -11	2,500E -11	5,000E -11	4,787E -11	5,774E -11	4,787E -11

Test Step	192 hours
Serial #	
20 Ref.	1,500E -10
21	2,000E -10
22	1,500E -10
23	2,000E -10
24	1,000E -10
Statistics	
Min	1,000E -10
Max	2,000E -10
Mean	1,625E -10
Sigma	4,787E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :	Samsung			

**Parameter : Output Current High Level Pin I/O3: IoZH I/O3**

**Vout=Vcc**


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	6,000E -10	2,000E -10	1,500E -10	1,000E -10	1,500E -10	1,000E -10	1,000E -10
21	2,500E -10	5,500E -10	2,000E -10	2,000E -10	2,000E -10	2,000E -10	1,000E -10	2,000E -10
22	1,500E -10	2,000E -10	2,000E -10	2,000E -10	1,000E -10	1,500E -10	2,000E -10	1,000E -10
23	1,500E -10	6,000E -10	2,500E -10	1,000E -10	2,000E -10	1,000E -10	1,000E -10	2,000E -10
24	2,000E -10	5,500E -10	1,500E -10	2,000E -10	2,000E -10	2,000E -10	1,000E -10	5,000E -11
Statistics								
Min	1,500E -10	2,000E -10	1,500E -10	1,000E -10	1,000E -10	1,000E -10	1,000E -10	5,000E -11
Max	2,500E -10	6,000E -10	2,500E -10	2,000E -10				
Mean	1,875E -10	4,750E -10	2,000E -10	1,750E -10	1,750E -10	1,625E -10	1,250E -10	1,375E -10
Sigma	4,787E -11	1,848E -10	4,082E -11	5,000E -11	5,000E -11	4,787E -11	5,000E -11	7,500E -11

Test Step	192 hours
Serial #	
20 Ref.	1,500E -10
21	2,000E -10
22	1,500E -10
23	1,500E -10
24	2,000E -10
Statistics	
Min	1,500E -10
Max	2,000E -10
Mean	1,750E -10
Sigma	2,887E -11



HIREX Engineering	Total Dose Test Report					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

Parameter : Output Current High Level Pin I/O2: IoZH I/O2

Vout=Vcc


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	5,500E -10	4,000E -10	1,000E -10	2,000E -10	2,000E -10	2,000E -10	1,500E -10
21	2,500E -10	2,000E -10	1,500E -10	2,000E -10	1,000E -10	2,000E -10	1,000E -10	2,000E -10
22	2,000E -10	2,000E -10	1,500E -10	2,000E -10				
23	2,000E -10	5,500E -10	2,500E -10	2,000E -10	2,000E -10	1,000E -10	1,000E -10	5,000E -11
24	2,000E -10	2,000E -10	2,500E -10	5,000E -11	1,000E -10	1,000E -10	1,000E -10	1,000E -10
Statistics								
Min	2,000E -10	2,000E -10	1,500E -10	5,000E -11	1,000E -10	1,000E -10	1,000E -10	5,000E -11
Max	2,500E -10	5,500E -10	2,500E -10	2,000E -10				
Mean	2,125E -10	2,875E -10	2,000E -10	1,625E -10	1,500E -10	1,500E -10	1,250E -10	1,375E -10
Sigma	2,500E -11	1,750E -10	5,774E -11	7,500E -11	5,774E -11	5,774E -11	5,000E -11	7,500E -11

Test Step	192 hours
Serial #	
20 Ref.	1,500E -10
21	2,000E -10
22	2,000E -10
23	2,000E -10
24	2,000E -10
Statistics	
Min	2,000E -10
Max	2,000E -10
Mean	2,000E -10
Sigma	1,878E -19



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Output Current High Level Pin I/O1: IoZH I/O1**

**Vout=Vcc**


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	1,500E -10	6,000E -10	1,500E -10	1,500E -10	1,000E -10	2,000E -10	1,000E -10	2,000E -10
21	2,500E -10	5,000E -10	2,000E -10	1,500E -10	2,000E -10	1,500E -10	2,000E -10	1,000E -10
22	1,500E -10	5,500E -10	2,000E -10	1,000E -10	2,000E -10	1,500E -10	1,000E -10	2,000E -10
23	1,500E -10	4,500E -10	2,500E -10	2,000E -10	2,000E -10	2,000E -10	1,000E -10	2,000E -10
24	1,500E -10	5,500E -10	3,000E -10	2,000E -10	1,000E -10	2,000E -10	2,500E -10	2,000E -10
Statistics								
Min	1,500E -10	4,500E -10	2,000E -10	1,000E -10	1,000E -10	1,500E -10	1,000E -10	1,000E -10
Max	2,500E -10	5,500E -10	3,000E -10	2,000E -10	2,000E -10	2,000E -10	2,500E -10	2,000E -10
Mean	1,750E -10	5,125E -10	2,375E -10	1,625E -10	1,750E -10	1,750E -10	1,625E -10	1,750E -10
Sigma	5,000E -11	4,787E -11	4,787E -11	4,787E -11	5,000E -11	2,887E -11	7,500E -11	5,000E -11

Test Step	192 hours
Serial #	
20 Ref.	1,500E -10
21	1,500E -10
22	1,000E -10
23	1,000E -10
24	2,000E -10
Statistics	
Min	1,000E -10
Max	2,000E -10
Mean	1,375E -10
Sigma	4,787E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Output Current High Level Pin I/O0: IoZH I/O0**

**Vout=Vcc**


Unit= A

Spec limit max: 20,0E-7

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,000E -10	5,500E -10	2,000E -10	1,000E -10	1,000E -10	1,500E -10	2,000E -10	2,000E -10
21	1,500E -10	6,000E -10	3,000E -10	2,000E -10	1,500E -10	1,500E -10	1,000E -10	1,500E -10
22	2,000E -10	5,000E -10	1,500E -10	1,500E -10	2,000E -10	1,000E -10	1,000E -10	1,000E -10
23	1,500E -10	5,500E -10	2,000E -10	1,500E -10	1,000E -10	2,000E -10	1,500E -10	2,000E -10
24	2,500E -10	5,500E -10	3,000E -10	1,500E -10	1,500E -10	2,000E -10	1,500E -10	2,000E -10
Statistics								
Min	1,500E -10	5,000E -10	1,500E -10	1,500E -10	1,000E -10	1,000E -10	1,000E -10	1,000E -10
Max	2,500E -10	6,000E -10	3,000E -10	2,000E -10	2,000E -10	2,000E -10	1,500E -10	2,000E -10
Mean	1,875E -10	5,500E -10	2,375E -10	1,625E -10	1,500E -10	1,625E -10	1,250E -10	1,625E -10
Sigma	4,787E -11	4,082E -11	7,500E -11	2,500E -11	4,082E -11	4,787E -11	2,887E -11	4,787E -11

Test Step	192 hours
Serial #	
20 Ref.	1,000E -10
21	2,000E -10
22	1,000E -10
23	2,000E -10
24	2,000E -10
Statistics	
Min	1,000E -10
Max	2,000E -10
Mean	1,750E -10
Sigma	5,000E -11



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

**Parameter : Output Voltage Low Level Pin I/O7: VoL I/O7**

**IOL=8mA**


Unit= V

Spec limit max: 40,0E-2

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	9,500E -02	9,400E -02	9,600E -02	9,400E -02	9,500E -02	9,600E -02	9,600E -02	9,400E -02
21	9,500E -02	9,500E -02	9,600E -02	9,400E -02	9,600E -02	9,600E -02	9,600E -02	9,500E -02
22	9,500E -02	9,400E -02	9,600E -02	9,500E -02	9,400E -02	9,500E -02	9,400E -02	9,500E -02
23	9,300E -02	9,200E -02	9,400E -02	9,300E -02	9,200E -02	9,300E -02	9,400E -02	9,300E -02
24	9,300E -02	9,200E -02	9,400E -02	9,300E -02	9,300E -02	9,500E -02	9,500E -02	9,300E -02
Statistics								
Min	9,300E -02	9,200E -02	9,400E -02	9,300E -02	9,200E -02	9,300E -02	9,400E -02	9,300E -02
Max	9,500E -02	9,500E -02	9,600E -02	9,500E -02	9,600E -02	9,600E -02	9,600E -02	9,500E -02
Mean	9,400E -02	9,325E -02	9,500E -02	9,375E -02	9,375E -02	9,475E -02	9,475E -02	9,400E -02
Sigma	1,155E -03	1,500E -03	1,155E -03	9,574E -04	1,708E -03	1,258E -03	9,574E -04	1,155E -03

Test Step	192 hours
Serial #	
20 Ref.	9,400E -02
21	9,500E -02
22	9,500E -02
23	9,300E -02
24	9,200E -02
Statistics	
Min	9,200E -02
Max	9,500E -02
Mean	9,375E -02
Sigma	1,500E -03



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :	Samsung			

Parameter : Output Voltage Low Level Pin I/O6: VoL I/O6  
**IOL=8mA**


Unit= V

Spec limit max: 40,0E-2

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	9,500E -02	9,500E -02	9,700E -02	9,500E -02	9,500E -02	9,500E -02	9,600E -02	9,400E -02
21	9,600E -02	9,500E -02	9,600E -02	9,500E -02	9,600E -02	9,600E -02	9,600E -02	9,600E -02
22	9,500E -02	9,500E -02	9,600E -02	9,500E -02	9,400E -02	9,500E -02	9,400E -02	9,500E -02
23	9,200E -02	9,200E -02	9,500E -02	9,300E -02	9,300E -02	9,400E -02	9,300E -02	9,300E -02
24	9,200E -02	9,200E -02	9,500E -02	9,300E -02	9,400E -02	9,500E -02	9,400E -02	9,300E -02
Statistics								
Min	9,200E -02	9,200E -02	9,500E -02	9,300E -02	9,300E -02	9,400E -02	9,300E -02	9,300E -02
Max	9,600E -02	9,500E -02	9,600E -02	9,500E -02	9,600E -02	9,600E -02	9,600E -02	9,600E -02
Mean	9,375E -02	9,350E -02	9,550E -02	9,400E -02	9,425E -02	9,500E -02	9,425E -02	9,425E -02
Sigma	2,062E -03	1,732E -03	5,774E -04	1,155E -03	1,258E -03	8,165E -04	1,258E -03	1,500E -03

Test Step	192 hours
Serial #	
20 Ref.	9,500E -02
21	9,500E -02
22	9,500E -02
23	9,400E -02
24	9,300E -02
Statistics	
Min	9,300E -02
Max	9,500E -02
Mean	9,425E -02
Sigma	9,574E -04



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :	Samsung		

**Parameter : Output Voltage Low Level Pin I/O5: VoL I/O5**

**IOL=8mA**


Unit= V

Spec limit max: 40,0E-2

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	1,150E -01	1,150E -01	1,170E -01	1,140E -01	1,150E -01	1,160E -01	1,160E -01	1,150E -01
21	1,160E -01	1,150E -01	1,160E -01	1,150E -01	1,170E -01	1,160E -01	1,160E -01	1,150E -01
22	1,150E -01	1,150E -01	1,160E -01	1,150E -01	1,150E -01	1,160E -01	1,140E -01	1,140E -01
23	1,120E -01	1,110E -01	1,140E -01	1,130E -01	1,120E -01	1,130E -01	1,140E -01	1,120E -01
24	1,120E -01	1,120E -01	1,150E -01	1,140E -01				
Statistics								
Min	1,120E -01	1,110E -01	1,140E -01	1,130E -01	1,120E -01	1,130E -01	1,140E -01	1,120E -01
Max	1,160E -01	1,150E -01	1,160E -01	1,150E -01	1,170E -01	1,160E -01	1,160E -01	1,150E -01
Mean	1,138E -01	1,133E -01	1,152E -01	1,143E -01	1,145E -01	1,147E -01	1,145E -01	1,138E -01
Sigma	2,062E -03	2,062E -03	9,574E -04	9,574E -04	2,082E -03	1,500E -03	1,000E -03	1,258E -03

Test Step	192 hours
Serial #	
20 Ref.	1,150E -01
21	1,150E -01
22	1,140E -01
23	1,130E -01
24	1,120E -01
Statistics	
Min	1,120E -01
Max	1,150E -01
Mean	1,135E -01
Sigma	1,291E -03



HIREX Engineering	Total Dose Test Report						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :		Samsung		

Parameter : Output Voltage Low Level Pin I/O4: VoL I/O4

IOL=8mA


Unit= V

Spec limit max: 40,0E-2

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	1,160E -01	1,160E -01	1,190E -01	1,150E -01	1,160E -01	1,170E -01	1,170E -01	1,160E -01
21	1,180E -01	1,170E -01	1,180E -01	1,160E -01	1,170E -01	1,180E -01	1,180E -01	1,160E -01
22	1,170E -01	1,160E -01	1,180E -01	1,160E -01	1,160E -01	1,170E -01	1,160E -01	1,170E -01
23	1,130E -01	1,140E -01	1,150E -01	1,150E -01	1,140E -01	1,150E -01	1,150E -01	1,140E -01
24	1,140E -01	1,130E -01	1,160E -01	1,150E -01				
Statistics								
Min	1,130E -01	1,130E -01	1,150E -01	1,150E -01	1,140E -01	1,150E -01	1,150E -01	1,140E -01
Max	1,180E -01	1,170E -01	1,180E -01	1,160E -01	1,170E -01	1,180E -01	1,180E -01	1,170E -01
Mean	1,155E -01	1,150E -01	1,168E -01	1,155E -01	1,155E -01	1,163E -01	1,160E -01	1,155E -01
Sigma	2,380E -03	1,826E -03	1,500E -03	5,773E -04	1,291E -03	1,500E -03	1,414E -03	1,291E -03

Test Step	192 hours
Serial #	
20 Ref.	1,170E -01
21	1,170E -01
22	1,160E -01
23	1,140E -01
24	1,130E -01
Statistics	
Min	1,130E -01
Max	1,170E -01
Mean	1,150E -01
Sigma	1,826E -03



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :	Samsung			

**Parameter : Output Voltage Low Level Pin I/O3: VoL I/O3**

**IOL=8mA**


Unit= V

Spec limit max: 40,0E-2

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	9,500E -02	9,400E -02	9,600E -02	9,300E -02	9,400E -02	9,600E -02	9,500E -02	9,500E -02
21	9,600E -02	9,500E -02	9,600E -02	9,400E -02	9,500E -02	9,600E -02	9,500E -02	9,500E -02
22	9,400E -02	9,300E -02	9,500E -02	9,400E -02	9,300E -02	9,400E -02	9,300E -02	9,300E -02
23	9,200E -02	9,100E -02	9,400E -02	9,300E -02	9,200E -02	9,300E -02	9,300E -02	9,300E -02
24	9,300E -02	9,200E -02	9,500E -02	9,400E -02				
Statistics								
Min	9,200E -02	9,100E -02	9,400E -02	9,300E -02	9,200E -02	9,300E -02	9,300E -02	9,300E -02
Max	9,600E -02	9,500E -02	9,600E -02	9,400E -02	9,500E -02	9,600E -02	9,500E -02	9,500E -02
Mean	9,375E -02	9,275E -02	9,500E -02	9,375E -02	9,350E -02	9,425E -02	9,375E -02	9,375E -02
Sigma	1,708E -03	1,708E -03	8,165E -04	5,000E -04	1,291E -03	1,258E -03	9,574E -04	9,574E -04

Test Step	192 hours
Serial #	
20 Ref.	9,400E -02
21	9,500E -02
22	9,400E -02
23	9,300E -02
24	9,200E -02
Statistics	
Min	9,200E -02
Max	9,500E -02
Mean	9,350E -02
Sigma	1,291E -03



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :	Samsung			

**Parameter : Output Voltage Low Level Pin I/O2: VoL I/O2**

**IOL=8mA**


Unit= V

Spec limit max: 40,0E-2

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	9,500E -02	9,500E -02	9,700E -02	9,400E -02	9,500E -02	9,600E -02	9,600E -02	9,500E -02
21	9,600E -02	9,500E -02	9,600E -02	9,500E -02	9,500E -02	9,600E -02	9,600E -02	9,500E -02
22	9,400E -02	9,300E -02	9,600E -02	9,400E -02	9,300E -02	9,500E -02	9,300E -02	9,400E -02
23	9,200E -02	9,100E -02	9,500E -02	9,300E -02	9,200E -02	9,400E -02	9,400E -02	9,300E -02
24	9,300E -02	9,200E -02	9,500E -02	9,300E -02	9,400E -02	9,400E -02	9,400E -02	9,300E -02
Statistics								
Min	9,200E -02	9,100E -02	9,500E -02	9,300E -02	9,200E -02	9,400E -02	9,300E -02	9,300E -02
Max	9,600E -02	9,500E -02	9,600E -02	9,500E -02	9,500E -02	9,600E -02	9,600E -02	9,500E -02
Mean	9,375E -02	9,275E -02	9,550E -02	9,375E -02	9,350E -02	9,475E -02	9,425E -02	9,375E -02
Sigma	1,708E -03	1,708E -03	5,774E -04	9,574E -04	1,291E -03	9,574E -04	1,258E -03	9,574E -04

Test Step	192 hours
Serial #	
20 Ref.	9,500E -02
21	9,600E -02
22	9,400E -02
23	9,300E -02
24	9,300E -02
Statistics	
Min	9,300E -02
Max	9,600E -02
Mean	9,400E -02
Sigma	1,414E -03



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :	Samsung		

**Parameter : Output Voltage Low Level Pin I/O1: VoL I/O1**

**IOL=8mA**


Unit= V

Spec limit max: 40,0E-2

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	1,160E -01	1,160E -01	1,170E -01	1,160E -01	1,160E -01	1,170E -01	1,170E -01	1,160E -01
21	1,170E -01	1,160E -01	1,170E -01	1,150E -01	1,160E -01	1,170E -01	1,180E -01	1,160E -01
22	1,140E -01	1,150E -01	1,140E -01	1,130E -01				
23	1,130E -01	1,120E -01	1,140E -01	1,130E -01	1,130E -01	1,140E -01	1,140E -01	1,140E -01
24	1,130E -01	1,120E -01	1,140E -01	1,130E -01	1,140E -01	1,140E -01	1,140E -01	1,130E -01
Statistics								
Min	1,130E -01	1,120E -01	1,140E -01	1,130E -01	1,130E -01	1,140E -01	1,140E -01	1,130E -01
Max	1,170E -01	1,160E -01	1,170E -01	1,150E -01	1,160E -01	1,170E -01	1,180E -01	1,160E -01
Mean	1,142E -01	1,135E -01	1,147E -01	1,137E -01	1,142E -01	1,150E -01	1,150E -01	1,140E -01
Sigma	1,893E -03	1,915E -03	1,500E -03	9,574E -04	1,258E -03	1,414E -03	2,000E -03	1,414E -03

Test Step	192 hours
Serial #	
20 Ref.	1,160E -01
21	1,160E -01
22	1,140E -01
23	1,130E -01
24	1,120E -01
Statistics	
Min	1,120E -01
Max	1,160E -01
Mean	1,137E -01
Sigma	1,708E -03



HIREX Engineering	Total Dose Test Report					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

Parameter : Output Voltage Low Level Pin I/O0: VoL I/O0

IOL=8mA


Unit= V

Spec limit max: 40,0E-2

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	1,160E -01	1,150E -01	1,170E -01	1,150E -01	1,160E -01	1,160E -01	1,170E -01	1,160E -01
21	1,160E -01	1,150E -01	1,160E -01	1,150E -01	1,160E -01	1,160E -01	1,160E -01	1,160E -01
22	1,140E -01	1,130E -01	1,150E -01	1,140E -01	1,130E -01	1,150E -01	1,130E -01	1,140E -01
23	1,120E -01	1,120E -01	1,140E -01	1,120E -01	1,120E -01	1,140E -01	1,140E -01	1,120E -01
24	1,120E -01	1,120E -01	1,140E -01	1,130E -01	1,130E -01	1,140E -01	1,130E -01	1,130E -01
Statistics								
Min	1,120E -01	1,120E -01	1,140E -01	1,120E -01	1,120E -01	1,140E -01	1,130E -01	1,120E -01
Max	1,160E -01	1,150E -01	1,160E -01	1,150E -01	1,160E -01	1,160E -01	1,160E -01	1,160E -01
Mean	1,135E -01	1,130E -01	1,147E -01	1,135E -01	1,135E -01	1,147E -01	1,140E -01	1,137E -01
Sigma	1,915E -03	1,414E -03	9,574E -04	1,291E -03	1,732E -03	9,574E -04	1,414E -03	1,708E -03

Test Step	192 hours
Serial #	
20 Ref.	1,160E -01
21	1,150E -01
22	1,140E -01
23	1,120E -01
24	1,120E -01
Statistics	
Min	1,120E -01
Max	1,150E -01
Mean	1,133E -01
Sigma	1,500E -03



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung				

**Parameter : Output Voltage High Level Pin I/O7: VoH I/O7**

**IOH=4mA**


Unit= V

Spec limit min: 240,0E-2

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	3,100E +00	3,100E +00	3,090E +00	3,110E +00	3,100E +00	3,100E +00	3,100E +00	3,110E +00
21	3,070E +00	3,080E +00	3,070E +00	3,080E +00	3,080E +00	3,080E +00	3,080E +00	3,090E +00
22	3,060E +00	3,060E +00	3,060E +00	3,070E +00	3,050E +00	3,060E +00	3,040E +00	3,070E +00
23	3,070E +00	3,070E +00	3,070E +00	3,090E +00	3,070E +00	3,070E +00	3,070E +00	3,080E +00
24	3,070E +00	3,080E +00	3,070E +00	3,090E +00	3,080E +00	3,080E +00	3,080E +00	3,090E +00
Statistics								
Min	3,060E +00	3,060E +00	3,060E +00	3,070E +00	3,050E +00	3,060E +00	3,040E +00	3,070E +00
Max	3,070E +00	3,080E +00	3,070E +00	3,090E +00	3,080E +00	3,080E +00	3,080E +00	3,090E +00
Mean	3,067E +00	3,072E +00	3,067E +00	3,082E +00	3,070E +00	3,072E +00	3,067E +00	3,082E +00
Sigma	5,000E -03	9,574E -03	5,000E -03	9,574E -03	1,414E -02	9,574E -03	1,893E -02	9,574E -03

Test Step	192 hours
Serial #	
20 Ref.	3,100E +00
21	3,080E +00
22	3,060E +00
23	3,090E +00
24	3,060E +00
Statistics	
Min	3,060E +00
Max	3,090E +00
Mean	3,072E +00
Sigma	1,500E -02



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung				

**Parameter : Output Voltage High Level Pin I/O6: VoH I/O6**

**IOH=4mA**


Unit= V

Spec limit min: 240,0E-2

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	3,080E +00	3,100E +00	3,090E +00	3,100E +00	3,080E +00	3,090E +00	3,090E +00	3,110E +00
21	3,070E +00	3,070E +00	3,070E +00	3,080E +00	3,060E +00	3,060E +00	3,070E +00	3,090E +00
22	3,050E +00	3,060E +00	3,040E +00	3,060E +00	3,060E +00	3,050E +00	3,050E +00	3,070E +00
23	3,070E +00	3,080E +00	3,070E +00	3,090E +00	3,070E +00	3,080E +00	3,070E +00	3,090E +00
24	3,070E +00	3,080E +00	3,070E +00	3,080E +00	3,070E +00	3,070E +00	3,080E +00	3,090E +00
Statistics								
Min	3,050E +00	3,060E +00	3,040E +00	3,060E +00	3,060E +00	3,050E +00	3,050E +00	3,070E +00
Max	3,070E +00	3,080E +00	3,070E +00	3,090E +00	3,070E +00	3,080E +00	3,080E +00	3,090E +00
Mean	3,065E +00	3,072E +00	3,062E +00	3,077E +00	3,065E +00	3,065E +00	3,067E +00	3,085E +00
Sigma	1,000E -02	9,574E -03	1,500E -02	1,258E -02	5,773E -03	1,291E -02	1,258E -02	1,000E -02

Test Step	192 hours
Serial #	
20 Ref.	3,090E +00
21	3,070E +00
22	3,060E +00
23	3,080E +00
24	3,070E +00
Statistics	
Min	3,060E +00
Max	3,080E +00
Mean	3,070E +00
Sigma	8,165E -03



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung				

**Parameter : Output Voltage High Level Pin I/O5: VoH I/O5**

**IOH=4mA**


Unit= V

Spec limit min: 240,0E-2

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	3,100E +00	3,100E +00	3,090E +00	3,110E +00	3,100E +00	3,100E +00	3,100E +00	3,120E +00
21	3,080E +00	3,090E +00	3,080E +00	3,090E +00	3,080E +00	3,080E +00	3,070E +00	3,100E +00
22	3,050E +00	3,060E +00	3,050E +00	3,060E +00	3,050E +00	3,050E +00	3,060E +00	3,060E +00
23	3,090E +00	3,090E +00	3,080E +00	3,100E +00	3,090E +00	3,080E +00	3,090E +00	3,110E +00
24	3,060E +00	3,070E +00	3,060E +00	3,070E +00	3,060E +00	3,060E +00	3,050E +00	3,080E +00
Statistics								
Min	3,050E +00	3,060E +00	3,050E +00	3,060E +00	3,050E +00	3,050E +00	3,050E +00	3,060E +00
Max	3,090E +00	3,090E +00	3,080E +00	3,100E +00	3,090E +00	3,080E +00	3,090E +00	3,110E +00
Mean	3,070E +00	3,077E +00	3,067E +00	3,080E +00	3,070E +00	3,067E +00	3,067E +00	3,087E +00
Sigma	1,826E -02	1,500E -02	1,500E -02	1,826E -02	1,826E -02	1,500E -02	1,708E -02	2,217E -02

Test Step	192 hours
Serial #	
20 Ref.	3,100E +00
21	3,080E +00
22	3,050E +00
23	3,080E +00
24	3,060E +00
Statistics	
Min	3,050E +00
Max	3,080E +00
Mean	3,067E +00
Sigma	1,500E -02



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung				

**Parameter : Output Voltage High Level Pin I/O4: VoH I/O4**

**IOH=4mA**


Unit= V

Spec limit min: 240,0E-2

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	3,090E +00	3,100E +00	3,090E +00	3,110E +00	3,100E +00	3,090E +00	3,090E +00	3,120E +00
21	3,080E +00	3,080E +00	3,080E +00	3,090E +00	3,080E +00	3,080E +00	3,080E +00	3,100E +00
22	3,040E +00	3,050E +00	3,040E +00	3,060E +00	3,050E +00	3,040E +00	3,050E +00	3,070E +00
23	3,080E +00	3,090E +00	3,080E +00	3,090E +00	3,070E +00	3,080E +00	3,080E +00	3,100E +00
24	3,060E +00	3,060E +00	3,050E +00	3,070E +00	3,050E +00	3,050E +00	3,050E +00	3,080E +00
Statistics								
Min	3,040E +00	3,050E +00	3,040E +00	3,060E +00	3,050E +00	3,040E +00	3,050E +00	3,070E +00
Max	3,080E +00	3,090E +00	3,080E +00	3,090E +00	3,080E +00	3,080E +00	3,080E +00	3,100E +00
Mean	3,065E +00	3,070E +00	3,062E +00	3,077E +00	3,062E +00	3,062E +00	3,065E +00	3,087E +00
Sigma	1,915E -02	1,826E -02	2,062E -02	1,500E -02	1,500E -02	2,062E -02	1,732E -02	1,500E -02

Test Step	192 hours
Serial #	
20 Ref.	3,100E +00
21	3,080E +00
22	3,050E +00
23	3,080E +00
24	3,060E +00
Statistics	
Min	3,050E +00
Max	3,080E +00
Mean	3,067E +00
Sigma	1,500E -02



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :	Samsung			

**Parameter : Output Voltage High Level Pin I/O3: VoH I/O3**

**IOH=4mA**


Unit= V

Spec limit min: 240,0E-2

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	3,080E +00	3,100E +00	3,090E +00	3,100E +00	3,090E +00	3,090E +00	3,090E +00	3,110E +00
21	3,070E +00	3,060E +00	3,070E +00	3,090E +00				
22	3,050E +00	3,070E +00	3,050E +00	3,060E +00	3,050E +00	3,050E +00	3,050E +00	3,080E +00
23	3,060E +00	3,080E +00	3,070E +00	3,080E +00	3,060E +00	3,070E +00	3,070E +00	3,100E +00
24	3,030E +00	3,040E +00	3,030E +00	3,040E +00	3,040E +00	3,030E +00	3,030E +00	3,050E +00
Statistics								
Min	3,030E +00	3,040E +00	3,030E +00	3,040E +00	3,040E +00	3,030E +00	3,030E +00	3,050E +00
Max	3,070E +00	3,080E +00	3,070E +00	3,080E +00	3,070E +00	3,070E +00	3,070E +00	3,100E +00
Mean	3,052E +00	3,065E +00	3,055E +00	3,062E +00	3,055E +00	3,052E +00	3,055E +00	3,080E +00
Sigma	1,708E -02	1,732E -02	1,915E -02	1,708E -02	1,291E -02	1,708E -02	1,915E -02	2,160E -02

Test Step	192 hours
Serial #	
20 Ref.	3,090E +00
21	3,070E +00
22	3,060E +00
23	3,070E +00
24	3,040E +00
Statistics	
Min	3,040E +00
Max	3,070E +00
Mean	3,060E +00
Sigma	1,414E -02



HIREX Engineering	Total Dose Test Report						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung				

Parameter : Output Voltage High Level Pin I/O2: VoH I/O2

IOH=4mA


Unit= V

Spec limit min: 240,0E-2

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	3,080E +00	3,100E +00	3,090E +00	3,110E +00	3,090E +00	3,090E +00	3,090E +00	3,110E +00
21	3,070E +00	3,080E +00	3,070E +00	3,070E +00	3,080E +00	3,070E +00	3,070E +00	3,090E +00
22	3,050E +00	3,060E +00	3,060E +00	3,070E +00	3,060E +00	3,060E +00	3,060E +00	3,080E +00
23	3,070E +00	3,080E +00	3,070E +00	3,080E +00	3,070E +00	3,070E +00	3,070E +00	3,100E +00
24	3,030E +00	3,060E +00	3,040E +00	3,050E +00	3,040E +00	3,050E +00	3,040E +00	3,070E +00
Statistics								
Min	3,030E +00	3,060E +00	3,040E +00	3,050E +00	3,040E +00	3,050E +00	3,040E +00	3,070E +00
Max	3,070E +00	3,080E +00	3,070E +00	3,080E +00	3,080E +00	3,070E +00	3,070E +00	3,100E +00
Mean	3,055E +00	3,070E +00	3,060E +00	3,067E +00	3,062E +00	3,062E +00	3,060E +00	3,085E +00
Sigma	1,915E -02	1,155E -02	1,414E -02	1,258E -02	1,708E -02	9,574E -03	1,414E -02	1,291E -02

Test Step	192 hours
Serial #	
20 Ref.	3,100E +00
21	3,070E +00
22	3,060E +00
23	3,070E +00
24	3,050E +00
Statistics	
Min	3,050E +00
Max	3,070E +00
Mean	3,062E +00
Sigma	9,574E -03



HIREX Engineering	Total Dose Test Report						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung				

Parameter : Output Voltage High Level Pin I/O1: VoH I/O1

IOH=4mA


Unit= V

Spec limit min: 240,0E-2

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	3,100E +00	3,120E +00	3,100E +00	3,120E +00	3,110E +00	3,110E +00	3,100E +00	3,130E +00
21	3,070E +00	3,080E +00	3,060E +00	3,080E +00	3,070E +00	3,060E +00	3,070E +00	3,090E +00
22	3,070E +00	3,080E +00	3,070E +00	3,090E +00	3,080E +00	3,070E +00	3,080E +00	3,100E +00
23	3,070E +00	3,080E +00	3,070E +00	3,080E +00	3,070E +00	3,070E +00	3,080E +00	3,100E +00
24	3,080E +00	3,080E +00	3,080E +00	3,090E +00	3,080E +00	3,070E +00	3,070E +00	3,090E +00
Statistics								
Min	3,070E +00	3,080E +00	3,060E +00	3,080E +00	3,070E +00	3,060E +00	3,070E +00	3,090E +00
Max	3,080E +00	3,080E +00	3,080E +00	3,090E +00	3,080E +00	3,070E +00	3,080E +00	3,100E +00
Mean	3,072E +00	3,080E +00	3,070E +00	3,085E +00	3,075E +00	3,067E +00	3,075E +00	3,095E +00
Sigma	5,000E -03	1,075E -09	8,165E -03	5,773E -03	5,773E -03	5,000E -03	5,773E -03	5,773E -03

Test Step	192 hours
Serial #	
20 Ref.	3,110E +00
21	3,080E +00
22	3,080E +00
23	3,080E +00
24	3,080E +00
Statistics	
Min	3,080E +00
Max	3,080E +00
Mean	3,080E +00
Sigma	1,075E -09



HIREX Engineering	Total Dose Test Report						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung				

Parameter : Output Voltage High Level Pin I/O0: VoH I/O0

IOH=4mA


Unit= V

Spec limit min: 240,0E-2

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	3,110E +00	3,110E +00	3,100E +00	3,110E +00	3,110E +00	3,100E +00	3,100E +00	3,120E +00
21	3,070E +00	3,080E +00	3,070E +00	3,080E +00	3,060E +00	3,060E +00	3,060E +00	3,090E +00
22	3,070E +00	3,080E +00	3,070E +00	3,080E +00	3,070E +00	3,070E +00	3,070E +00	3,090E +00
23	3,070E +00	3,080E +00	3,080E +00	3,080E +00	3,080E +00	3,070E +00	3,070E +00	3,090E +00
24	3,070E +00	3,080E +00	3,080E +00	3,080E +00	3,070E +00	3,070E +00	3,070E +00	3,100E +00
Statistics								
Min	3,070E +00	3,080E +00	3,070E +00	3,080E +00	3,060E +00	3,060E +00	3,060E +00	3,090E +00
Max	3,070E +00	3,080E +00	3,080E +00	3,080E +00	3,080E +00	3,070E +00	3,070E +00	3,100E +00
Mean	3,070E +00	3,080E +00	3,075E +00	3,080E +00	3,070E +00	3,067E +00	3,067E +00	3,092E +00
Sigma	1,075E -09	1,075E -09	5,773E -03	1,075E -09	8,165E -03	5,000E -03	5,000E -03	5,000E -03

Test Step	192 hours
Serial #	
20 Ref.	3,100E +00
21	3,070E +00
22	3,070E +00
23	3,070E +00
24	3,080E +00
Statistics	
Min	3,070E +00
Max	3,080E +00
Mean	3,072E +00
Sigma	5,000E -03



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :	Samsung		

**Parameter : Standby Power Supply Current: ISB\_CMOS**

**CMOS Input Level**


Unit= A

Spec limit max: 10,0E-3

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	2,903E -03	2,940E -03	2,900E -03	2,930E -03	2,892E -03	2,913E -03	2,953E -03	2,901E -03
21	2,861E -03	2,921E -03	2,912E -03	2,953E -03	2,928E -03	3,013E -03	3,068E -03	3,125E -03
22	3,044E -03	3,156E -03	3,081E -03	3,133E -03	3,124E -03	3,178E -03	3,254E -03	3,274E -03
23	2,973E -03	3,057E -03	3,035E -03	3,095E -03	3,156E -03	3,160E -03	3,250E -03	3,326E -03
24	2,946E -03	3,001E -03	2,992E -03	3,099E -03	3,146E -03	3,150E -03	3,302E -03	3,379E -03
Statistics								
Min	2,861E -03	2,921E -03	2,912E -03	2,953E -03	2,928E -03	3,013E -03	3,068E -03	3,125E -03
Max	3,044E -03	3,156E -03	3,081E -03	3,133E -03	3,156E -03	3,178E -03	3,302E -03	3,379E -03
Mean	2,956E -03	3,034E -03	3,005E -03	3,070E -03	3,089E -03	3,125E -03	3,219E -03	3,276E -03
Sigma	7,563E -05	9,878E -05	7,187E -05	7,984E -05	1,078E -04	7,572E -05	1,031E -04	1,094E -04

Test Step	192 hours
Serial #	
20 Ref.	2,882E -03
21	3,012E -03
22	3,187E -03
23	3,034E -03
24	3,069E -03
Statistics	
Min	3,012E -03
Max	3,187E -03
Mean	3,076E -03
Sigma	7,795E -05



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

Parameter : Operating Power Supply Current: ICC  
CS=VIL, VIN=VIH or VIL, IOUT=0mA ; F=80MHz


Unit= A

Spec limit max: 14,5E-2

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	7,960E -02	7,980E -02	7,930E -02	7,980E -02	7,960E -02	7,950E -02	7,930E -02	7,970E -02
21	7,500E -02	7,570E -02	7,570E -02	7,610E -02	7,620E -02	7,670E -02	7,700E -02	7,720E -02
22	8,270E -02	8,350E -02	8,340E -02	8,380E -02	8,390E -02	8,450E -02	8,470E -02	8,490E -02
23	7,720E -02	7,780E -02	7,760E -02	7,850E -02	7,860E -02	7,930E -02	7,940E -02	7,990E -02
24	7,750E -02	7,800E -02	7,770E -02	7,870E -02	7,870E -02	7,920E -02	7,970E -02	8,000E -02
Statistics								
Min	7,500E -02	7,570E -02	7,570E -02	7,610E -02	7,620E -02	7,670E -02	7,700E -02	7,720E -02
Max	8,270E -02	8,350E -02	8,340E -02	8,380E -02	8,390E -02	8,450E -02	8,470E -02	8,490E -02
Mean	7,810E -02	7,875E -02	7,860E -02	7,928E -02	7,935E -02	7,993E -02	8,020E -02	8,050E -02
Sigma	3,263E -03	3,333E -03	3,330E -03	3,240E -03	3,246E -03	3,279E -03	3,234E -03	3,207E -03

Test Step	192 hours
Serial #	
20 Ref.	7,970E -02
21	7,670E -02
22	8,430E -02
23	7,870E -02
24	7,930E -02
Statistics	
Min	7,670E -02
Max	8,430E -02
Mean	7,975E -02
Sigma	3,231E -03



HIREX Engineering	Total Dose Test Report						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung				

Parameter : Address Access Time Low to High Level: taaL->H

F=80Mhz


Unit= s

Spec limit max: 12,0E-9

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	9,700E -09	9,700E -09	9,900E -09	9,700E -09	9,700E -09	9,700E -09	9,800E -09	9,800E -09
21	1,000E -08	1,000E -08	1,000E -08	9,900E -09				
22	1,040E -08	1,050E -08	1,050E -08	1,030E -08	1,050E -08	1,060E -08	1,060E -08	1,050E -08
23	9,900E -09	9,900E -09	9,900E -09	9,800E -09	9,800E -09	9,900E -09	9,800E -09	9,800E -09
24	1,010E -08	1,010E -08	1,020E -08	1,000E -08	1,010E -08	1,010E -08	1,010E -08	1,010E -08
Statistics								
Min	9,900E -09	9,900E -09	9,900E -09	9,800E -09	9,800E -09	9,900E -09	9,800E -09	9,800E -09
Max	1,040E -08	1,050E -08	1,050E -08	1,030E -08	1,050E -08	1,060E -08	1,060E -08	1,050E -08
Mean	1,010E -08	1,012E -08	1,015E -08	1,000E -08	1,007E -08	1,012E -08	1,010E -08	1,007E -08
Sigma	2,160E -10	2,630E -10	2,646E -10	2,160E -10	3,096E -10	3,304E -10	3,559E -10	3,096E -10

Test Step	192 hours
Serial #	
20 Ref.	9,700E -09
21	9,900E -09
22	1,050E -08
23	9,700E -09
24	1,000E -08
Statistics	
Min	9,700E -09
Max	1,050E -08
Mean	1,002E -08
Sigma	3,403E -10



HIKEX Engineering	Total Dose Test Report						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung				

Parameter : Address Access Time High to Low Level: taaH->L  
F=80Mhz


Unit= s

Spec limit max: 12,0E-9

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	1,040E -08	1,040E -08	1,050E -08	1,040E -08				
21	1,040E -08	1,010E -08	9,900E -09	1,060E -08	1,020E -08	1,040E -08	1,000E -08	1,010E -08
22	1,050E -08	1,040E -08	1,030E -08					
23	1,030E -08	1,040E -08	1,040E -08	1,030E -08	1,040E -08	1,020E -08	1,030E -08	1,030E -08
24	1,070E -08	1,080E -08	1,090E -08	1,070E -08	1,050E -08	1,070E -08	1,050E -08	1,050E -08
Statistics								
Min	1,030E -08	1,010E -08	9,900E -09	1,030E -08	1,020E -08	1,020E -08	1,000E -08	1,010E -08
Max	1,070E -08	1,080E -08	1,090E -08	1,070E -08	1,050E -08	1,070E -08	1,050E -08	1,050E -08
Mean	1,047E -08	1,042E -08	1,037E -08	1,047E -08	1,035E -08	1,040E -08	1,027E -08	1,030E -08
Sigma	1,708E -10	2,872E -10	4,113E -10	2,062E -10	1,291E -10	2,160E -10	2,062E -10	1,633E -10

Test Step	192 hours
Serial #	
20 Ref.	1,040E -08
21	9,900E -09
22	1,030E -08
23	1,030E -08
24	1,070E -08
Statistics	
Min	9,900E -09
Max	1,070E -08
Mean	1,030E -08
Sigma	3,266E -10



<b>HIREX Engineering</b>	<b>Total Dose Test Report</b>					Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C	Manufacturer :	Samsung			

Parameter : Address Set-up time: tas

F=80Mhz


Unit= s

Spec limit min: 000,0E+0

Spec limits are represented in bold lines on the graphic.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	-4,300E -09							
21	-4,600E -09	-4,600E -09	-4,400E -09	-4,300E -09	-4,300E -09	-4,100E -09	-4,400E -09	-4,300E -09
22	-4,100E -09	-4,000E -09	-3,900E -09	-4,100E -09	-4,200E -09	-4,100E -09	-4,300E -09	-4,100E -09
23	-4,400E -09	-4,100E -09	-4,200E -09	-4,300E -09	-4,100E -09	-4,300E -09	-4,100E -09	-4,100E -09
24	-4,000E -09	-4,000E -09	-4,400E -09	-4,100E -09	-4,100E -09	-4,000E -09	-4,100E -09	-4,100E -09
Statistics								
Min	-4,600E -09	-4,600E -09	-4,400E -09	-4,300E -09	-4,300E -09	-4,300E -09	-4,400E -09	-4,300E -09
Max	-4,000E -09	-4,000E -09	-3,900E -09	-4,100E -09	-4,100E -09	-4,000E -09	-4,100E -09	-4,100E -09
Mean	-4,275E -09	-4,175E -09	-4,225E -09	-4,200E -09	-4,175E -09	-4,125E -09	-4,225E -09	-4,150E -09
Sigma	2,754E -10	2,872E -10	2,363E -10	1,155E -10	9,574E -11	1,258E -10	1,500E -10	1,000E -10

Test Step	192 hours
Serial #	
20 Ref.	-4,300E -09
21	-4,900E -09
22	-4,200E -09
23	-4,100E -09
24	-4,200E -09
Statistics	
Min	-4,900E -09
Max	-4,100E -09
Mean	-4,350E -09
Sigma	3,697E -10



HIREX Engineering	Total Dose Test Report						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :		Samsung		


Parameter : Functional Test : Zero Pattern: Zero

F=80Mhz

No spec limit specified.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	P	P	P	P	P	P	P	P
21	P	P	P	P	P	P	P	P
22	P	P	P	P	P	P	P	P
23	P	P	P	P	P	P	P	P
24	P	P	P	P	P	P	P	P

Test Step	192 hours
Serial #	
20 Ref.	P
21	P
22	P
23	P
24	P



HIREX Engineering	Total Dose Test Report						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :		Samsung		


Parameter : Functional Test : One Pattern: One

F=80Mhz

No spec limit specified.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	P	P	P	P	P	P	P	P
21	P	P	P	P	P	P	P	P
22	P	P	P	P	P	P	P	P
23	P	P	P	P	P	P	P	P
24	P	P	P	P	P	P	P	P

Test Step	192 hours
Serial #	
20 Ref.	P
21	P
22	P
23	P
24	P



HIREX Engineering	Total Dose Test Report						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :		Samsung		

Parameter : Functional Test : CheckBoard Pattern: Checkerboard


F=80Mhz

No spec limit specified.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	P	P	P	P	P	P	P	P
21	P	P	P	P	P	P	P	P
22	P	P	P	P	P	P	P	P
23	P	P	P	P	P	P	P	P
24	P	P	P	P	P	P	P	P

Test Step	192 hours
Serial #	
20 Ref.	P
21	P
22	P
23	P
24	P

### Checkerboard



HIREX Engineering	Total Dose Test Report						Réf. : HRX/TID/0075 Issue : 01
Part Type :	K6R4008V1C		Manufacturer :		Samsung		

Parameter : Functional Test : Complementary CheckBoard Pattern: \*Checkerboard  
F=80Mhz

No spec limit specified.

Test Step	Initial	5 krads	10 krads	14,8 krads	19 krads	31,8 krads	47,2 krads	24 hours
Serial #								
20 Ref.	P	P	P	P	P	P	P	P
21	P	P	P	P	P	P	P	P
22	P	P	P	P	P	P	P	P
23	P	P	P	P	P	P	P	P
24	P	P	P	P	P	P	P	P

Test Step	192 hours
Serial #	
20 Ref.	P
21	P
22	P
23	P
24	P

### \*Checkerboard

