



ESCC QUALIFIED PARTS LIST



REP005


Updated 15 June 2013






Document Custodian: European Space Agency - see <https://spacecomponents.org>

| | General Information | |
|-------------------------|---|----------|
| As affected | | |
| Section/Page No. | Description | |
| Section 01 | Index of Capacitors | Amended |
| 01-01-006 | Ceramic, Fixed, Type II, High Voltage from AVX (N.I.) | Amended |
| 01-02-001-1 | Ceramic, Fixed, Chip Type I from AVX/TPC | Extended |
| 01-02-002-1 | Ceramic, Fixed, Chip Type II from AVX/TPC | Extended |
| 01-02-004-1 | Ceramic, Fixed Chip, Type II, high Voltage from AVX (N.I.) | Amended |
| Section 03 | Index of Crystals | Amended |
| 03-01-001-3 | TO-5 Can from KVG (D) | Extended |
| 03-01-002-3 | TO-8 Can from KVG (D) | Extended |
| Section 04 | Index of Diodes | |
| 04-01-003-2 | Types 1N6640U and 1N6642U from ST Microelectronics | Amended |
| Section 08 | Index of Microcircuits | |
| 08-09-001 | PLL Frequency Synthesizer from Peregrine Semiconductor Europe | Amended |
| Section 12 | Index of Transistors | |
| 12-05-003-1 | Type STRH100N10FSYS3 | Amended |
| Section 13 | Index of Wires and Cables | Amended |
| 13-01-004-1 | Polyimide, Types SPC from W.L. Gore | Extended |

| | |
|--|--|
|   | Qualified Parts List DOCUMENT CHANGES |
| | Change Date: 15 Jun 2013 |


| | General Information | |
|---|--|--------------------|
| As affected | | |
| Section/Page No. | Description | |
| Section 01 01-02-001-1 01-02-002-1 | Index of Capacitors Ceramic, Fixed, Chip Type I from AVX/TPC Ceramic, Fixed, Chip Type II from AVX/TPC | Amended Amended |
| Section 03 03-01-001-3 03-01-002-3 | Index of Crystals TO-5 Can from KVG (D) TO-8 Can from KVG (D) | Amended Amended |
| Section 14 14-16-99-003 | Index of Miscellaneous Thermostatic, Bimetallic from COMEPA | Amended |
|  | Qualified Parts List DOCUMENT CHANGES | |
| | Change Date: 15 May 2013 | |


| | General Information | |
|--|---|---------------------------------|
| As affected | | |
| Section/Page No. | Description | |
| Section 01 01-01-007 01-11-001 | Index of Capacitors Type II, Types CNC53 to CNC56 from Eurofarad Type 101M, 201M, 400M 401M from Cobham Microwave | Amended Extended Extended |
| Section 09 09-02-003 09-02-004-3 | Index of Relays Type EL415 from REL STPI Type M302 from LEACH Sarralbe | Amended Extended Extended |
| Section 10 10-09-002 A-D | Index of Resistors Type PHR; PFRR; PRAHR/CNWHR from Vishay S.A. Sfernice | Amended Amended |
|   | Qualified Parts List DOCUMENT CHANGES | |
| | Change Date: 15 April 2013 | |


| | General Information | |
|---|---|-----------------------------|
| As affected | | |
| Section/Page No. | Description | |
| Section 01 01-02-002-2 | Index of Capacitors Type II, Types CNC2S to CNC14S from Eurofarad | Amended |
| Section 04 04-13-003-1A-B | Index of Diodes PIN and Varactors from RF2M Microwave | Amended Extended |
| Section 08 08-09-001 | Index of Microcircuits PLL Frequency Synthesizer from Peregrine | Amended |
| Section 10 10-11-002 | Index of Resistors Single & Double Layer from Minco | Amended Added |
| Section 12 12-05-003-01 12-06-003-01 | Index of Transistors Type STRH100N10FSY3 from STMicroelectronics Type STRH40P10 from STMicroelectronics | Amended Amended Added |
|  | | |
| Qualified Parts List | | |
| DOCUMENT CHANGES | | |
| Change Date: 15 March 2013 | | |



QPL


| | General Information | |
|---|--|---|
| As affected | | |
| Section/Page No. | Description | |
| Section 02 02-05-004-1 | Index of Connectors 8MCG, Rectangular from SOURIAU | Amended |
| Section 10 10-07-001 | Index of Resistors Types SM*-PW and SM*-PT from Isabellenhütte | Amended Extended |
| Section 12 12-02-002-3A-B | Index of Transistors Types PNP from STMicroelectronics | Amended |
| Section 13 13-01-003 13-01-011-1 13-02-001 | Index of Wires and Cables PTFE, Types MTV-BTV from Nexans Crosslinked, Modified ETFE, Type Silver-Plated Copper, Lightweight from Tyco Electronics PTFE/Polyimide, Type 50 CIS from Nexans | Amended Extended Extended Extended |
|  | | |
| Qualified Parts List DOCUMENT CHANGES | | |
| Change Date: 15 February 2013 | | |


| | General Information | |
|---|---|--|
| As affected | | |
| Section/Page No. | Description | |
| Section 04 04-02-002-1 04-02-003-1 | Index of Diodes Type STPS20100 from STMicroelectronics Types BYW-81, BYV52, BYV54 from STMicroelectronics | Amended Amended |
| Section 08 08-80-001-2 08-80-002-2 | Index of Microcircuits 4000 B Series from ST Microelectronics 54HCMOS Series from ST Microelectronics | Amended Amended |
| Section 09 09-01-004 | Index of Relays Type E 215 from REL STPI | Amended Extended |
| Section 12 12-02-002-3A-B | Index of Transistors Types PNP from STMicroelectronics | Amended |
| Section 13 13-01-012-2 | Index of Wires and Cables Fluoropolymer, Lightweight, Based on Type CSWL from W.L. Gore | Amended Extended |
|  | | |
| | | Qualified Parts List DOCUMENT CHANGES |
| | | Change Date: 15 January 2013 |

| | General Information | |
|---|---|---------------------------------|
| As affected | | |
| Section/Page No. | Description | |
| Section 01 01-01-005 01-02-001-1 | Index of Capacitors Type II, High Capacitance from AVX (N.I.) Type I from AVX/TPC | Amended Extended Amended |
| Section 02 02-05-004-1 | Index of Connectors 8MCG, Rectangular from SOURIAU | Amended Extended |
| Section 04 04-02-002-1 04-02-003-1 | Index of Diodes Type STPS20100 from STMicroelectronics Types BYW-81, BYV52, BYV54 from STMicroelectronics | Amended Extended Extended |
| Section 09 09-02-004 | Index of Relays Type EL215 from REL STPI | Amended Extended |
| Section 12 12-05-003-01 | Index of Transistors Type STRH100N10FSY3 from STMicroelectronics | Amended Extended |
| Section 13 13-02-003-2 | Index of Wires and Cables Symmetric, Quad, Spacewire from W.L. Gore | Amended Extended |
|  | | |
| Qualified Parts List | | |
| DOCUMENT CHANGES | | |
| Change Date: 15 December 2012 | | |




QPL

| | General Information | |
|---|---|---------------------|
| As affected | | |
| Section/Page No. | Description | |
| Section 01 01-01-005 | Index of Capacitors Type II, High Capacitance from AVX (N.I.) | Amended |
| Section 02 02-02-009 | Index of Connectors Series ACB1 from Axon' Cables | Amended Extended |
| Section 04 04-02-002-1 04-02-003-1 | Index of Diodes Type STPS20100 from STMicroelectronics Types BYW-81, BYV52, BYV54 from STMicroelectronics | Amended Amended |
| Section 09 09-02-004 | Index of Relays Type EL215 from REL STPI | Amended |
| Section 13 13-01-004-2 | Index of Wires and Cables Polyimide, Types SPL from W.L. Gore | Amended Extended |
|  | Qualified Parts List | |
| | DOCUMENT CHANGES | |
| | Change Date: 15 November 2012 | |

| | General Information | |
|---|--|-------------------------------|
| As affected | | |
| Section/Page No. | Description | |
| Section 01 01-02-001-2 01-02-002-2 | Index of Capacitors Type I, Types CEC2S to CEC14S from Eurofarad Type II, Types CNC2S to CNC14S from Eurofarad | Amended Added Added |
| Section 07 07-01-001 | Index of Inductors Types MSCI 10K, 12K 20K and H01 from Microspire | Amended Extended |
| Section 12 12-10-003 12-10-004 12-10-005 | Index of Transistors Type BFY640 from Infineon Types BFY640B and BFY650B from Infineon Type BFY740B from Infineon | Amended Amended Amended |
|  | Qualified Parts List | |
| | DOCUMENT CHANGES | |
| | Change Date: 15 October 2012 | |

| | General Information | |
|---|---|---|
| As affected | | |
| Section/Page No. | Description | |
| Section 02 02-01-001-1 02-02-001-1 | Index of Connectors D*M Series, Rectangular from C&K Components D*MA Series, Rectangular from C&K Components | Amended Amended |
| Section 04 04-02-001-4 | Index of Diodes Types 1N5819U and 1N5822U from STMicroelectronics | Amended Extended |
| Section 06 06-01-001 | Index of Fuses Type MGA-S from Schurter | Amended Extended |
| Section 09 09-01-005 | Index of Relays Type E from LEACH | Amended |
| Section 11 11-01-001 | Index of Thermistors Types G15K4D489 and *K3A35* from MEAS Ireland (Betatherm) | Amended |
| Section 12 12-05-003-01 12-10-003 12-10-004 12-10-005 | Index of Transistors Type STRH100N10FSY3 from STMicroelectronics Type BFY640 from Infineon Types BFY640B and BFY650B from Infineon Type BFY740B from Infineon | Amended Amended Added Added Added |
| Section 13 13-01-004-2 13-01-008 | Index of Wires and Cables Polyimide, Types SPL from WL Gore PTFE, Polyimide/PFA Insulated, Type SPP from WL Gore | Amended Amended Extended |
| Qualified Parts List | | |
| DOCUMENT CHANGES | | |
| Change Date: 15 September 2012 | | |



| | General Information | |
|---|--|--|
| As affected | | |
| Section/Page No. | Description | |
| Section 01 01-05-001-1 | Index of Capacitors Type HT86PS, High Voltage from Eurofarad | Amended Extended |
| Section 03 03-01-001-1 03-01-002 | Index of Crystals TO-5 Can from RAKON (F) TO-8 Can from RAKON (F) | Amended Extended Extended |
| Section 05 05-01-001-A-B | Index of Filters Types SFC, SFL, SFP from Eurofarad | Amended Extended |
| Section 10 10-02-001 | Index of Resistors Type RNC 90 from Vishay SA Sfernice | Amended Extended |
| Section 12 12-01-002-3A-B 12-02-002-3A-B 12-05-003-2 | Index of Transistors Types NPN from STMicroelectronics Types PNP from STMicroelectronics Type BUY**CS** from Infineon | Amended Extended Extended Added |
|  | Qualified Parts List | |
| | DOCUMENT CHANGES | |
| | Change Date: 15 August 2012 | |


| | General Information | |
|---|---|---------------------------------|
| As affected | | |
| Section/Page No. | Description | |
| Section 01 01-01-005 | Index of Capacitors Type II, High Capacitance from AVX (N.I.) | Amended Extended |
| Section 02 02-01-001-2 02-02-001-2 | Index of Connectors D*M Series, Rectangular from SOURIAU D*MA Series, Rectangular from SOURIAU | Amended Extended Extended |
|  | <p align="center">Qualified Parts List</p> <p align="center">DOCUMENT CHANGES</p> <p align="center">Change Date: 15 July 2012</p> | |

TABLE OF CONTENTS

| <u>SECTION</u> | <u>PAGE</u> |
|--------------------------------------|-------------|
| Document Changes | - |
| Table of Contents | 1 |
| 1 Foreword | 2 |
| 2 Procurors' Responsibility | 2 |
| 3 Use of Tables | 2 |
| 4 Revision Procedure | 2 |
| 5 Table of Qualified Component Types | 3 |
| Appendices | |
| 'A' Qualified Components List | 4 |

1. FOREWORD

This document contains a list of components that have been qualified to the rules of the ESCC System and are intended for use in ESA and other spacecraft and associated equipment in accordance with the requirements of the ECSS Standard ESCC-Q-ST-60.

It is permitted to advertise the ESCC qualification status of a product provided such publicity or advertisement does not state or imply that the product is the only qualified or capability approved one of that particular type, range or family.

2. PROCURORS' RESPONSIBILITY

When procuring ESCC qualified or capability approved components, the procurer is responsible for ensuring that the qualification or capability approval status is valid and that delivered components fulfill the specified requirements of the applicable ESCC specifications. The procurer is advised to utilise the ESCC non-conformance system in the event that a qualified or capability approved manufacturer delivers non-conforming components.

3. USE OF TABLES

3.1 Publication

The individual entries are published in sections within this document and are presented by manufacturer on the web. Please refer to our escies.org website.

3.2 Type Designation

The referenced type (style) designations are derived from industrial standards (i.e., JEDEC PRO-ELECTRON, MIL, IEC and CECC). The purpose is to identify the similarity of a listed qualified component to a standard type designation.

3.3 Components Characteristics

The electrical characteristics are listed for guidance only and, unless otherwise stated, are specified at +25°C. The precise characteristics of the qualified component are defined in the referenced ESCC specification.

3.4 Manufacturer

Plant locations are indicated in the individual listing; contact information is given in full on the appropriate web pages. Please refer to our escies.org website.

4. REVISION PROCEDURE

Amendments to earlier issues of the QPL implemented herein are indicated by the date on the front page and by the content of the "Document Changes" pages. The latter provides the changes over a one year period. The same issue date appears on the table at the start of each Section on the Appendix irrespective of whether changes have been made in a particular section. This indicates the information has been reviewed and is current. Finally, it should be noted that the ESA/SCC System is superseded by the ESCC (European Space Components Coordination) System.



5. **TABLE OF QUALIFIED COMPONENTS**

Components qualified to the ESCC System are grouped by component type designations. Individual components are listed within the relevant sections as indicated in Table 5.1

TABLE 5.1


| Section | Component Types |
|---------|------------------|
| 01 | Capacitors |
| 02 | Connectors |
| 03 | Crystals |
| 04 | Diodes |
| 05 | Filters |
| 06 | Fuses |
| 07 | Inductors |
| 08 | Microcircuits |
| 09 | Relays |
| 10 | Resistors |
| 11 | Thermistors |
| 12 | Transistors |
| 13 | Wires and Cables |
| 14 | Miscellaneous |
| 18 | Optoelectronics |


APPENDIX A


Qualified Components List


Section 01**Component Type: Capacitors**


| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|--------------|-------------|-------|---|------------------|
| 01-01 | | | Ceramic, Fixed | |
| | 01-01-005 | 231 H | Type II, High Capacitance | AVX (N.I.) |
| | 01-01-005-1 | 315 | Type II, Types CNC 31 to CNC 34 | Eurofarad |
| | 01-01-006 | 262 D | Type II, High Voltage | AVX (N.I.) |
| | 01-01-007 | 306 A | Type II, Types CNC 53 to CNC 56 | Eurofarad |
| 01-02 | | | Ceramic, Fixed, Chip | |
| | 01-02-001-1 | 109 L | Type I | AVX/TPC |
| | 01-02-001-2 | 323 | Type I, Types CEC2S to CEC14S | Eurofarad |
| | 01-02-002-1 | 110 L | Type II | AVX/TPC |
| | 01-02-002-2 | 324 | Type II, Types CNC2S to CNC14S | Eurofarad |
| | 01-02-004-1 | 264 D | Type II, High Voltage | AVX (N.I.) |
| 01-03 | | | Tantalum, (Solid), Fixed, Electrolytic | |
| | 01-03-004 | 196 E | Type TAJ | AXV (CZ) |
| 01-05 | | | Fixed, Film | |
| | 01-05-001-1 | 251 F | Type HT86PS, High Voltage | Eurofarad |
| | 01-05-003-1 | 270 D | Type PM94S | Eurofarad |
| 01-11 | | | Semiconductor | |
| | 01-11-001 | 286 B | Type 101M, 201M, 400M and 401M | Cobham Microwave |


| | | | | |
|---|--|---|-----------------------|----------|
| Types covered by similarity: ±20% tolerance | | Remarks: Capacitors no longer use a varnish finish. | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3001 Detail ESCC 3001/030 | AVX Limited Coleraine Northern Ireland | Qualification | DRA | Jul 1996 |
| | | Extension | DERA | Jul 1999 |
| | | Extension | DERA | Jul 2001 |
| | | Extension | QinetiQ | Oct 2003 |
| | | Extension | QinetiQ | Mar 2006 |
| | | Extension | BNSC | Jun 2008 |
| Characteristics: E12 series | | Extension | UK Space Agency | Sep 2010 |
| Qualified Range: | | Extension | UK Space Agency | Jun 2012 |
| Variants 01 to 74 capacitance range for 50V, 100V and 200V, as per Detail Specification | | Extension | UK Space Agency | Dec 2012 |
| Variants 01 to 52, and 59 to 60, for 500V are qualified | | | | |
| ±10% tolerance | | | | |
| Operating Temperature Range (°C): -55 to +125 | | | | |
|  | <p>CAPACITORS, CERAMIC, TYPE II, HIGH CAPACITANCE, BASED ON CASE STYLES BR, CV, AND CH</p> | Current Validity of Qualification | | Page |
| | | Certificate | Valid Until | 01-01 |
| | | 231 H | December 2014 | 005 |

| | | | | |
|---|--|-----------------------------------|-----------------------|----------|
| Types covered by similarity: E6 ±20% tolerance | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3001 Detail ESCC 3001/037 | EUROFARAD Chanteloup en Brie France | Qualification | CNES | Nov 2011 |
| Characteristics: E12 ±10% tolerance Qualified Range: Variants 01 to 16. 16V : 2.2 to 68 µF 25V: 1.2 to 39 µF DIL format with equal number of leads per side Lead material : type A with type 10 finish (electro-deposited 98% Ag min.) Operating Temperature Range (°C): -55 to +125 | | | | |
|  | CAPACITORS, CERAMIC, TYPE II, MULTIPLE LAYERS, BASED ON TYPES CNC 31 to 34, NE, PE AND PLE | Current Validity of Qualification | | Page |
| | | Certificate | Valid Until | 01-01 |
| | | 315 | November 2013 | 005-1 |

| | | | | |
|---|--|--|-----------------------|----------|
| Types covered by similarity: ±20% tolerance | | Remarks: Extension of qualification testing has been completed. | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3001 | AVX Limited Coleraine Northern Ireland | Qualification | DERA | Sep 2000 |
| Detail ESCC 3001/034 | | Extension | QinetiQ | Aug 2002 |
| | | Extension | QinetiQ | Mar 2006 |
| | | Extension | BNSC | Jan 2009 |
| | | Extension | UK Space Agency | Apr 2011 |
| Characteristics: E12 series Qualified Range: Variants 01 to 22 are qualified ±10% tolerance Operating Temperature Range (°C): -55 to +125 | | | | |
|  | CAPACITORS, CERAMIC, TYPE II, HIGH VOLTAGE, 1.0 TO 5.0 KV, BASED ON CASE STYLES VR, CV, AND CH | Current Validity of Qualification | | Page |
| | | Certificate | Valid Until | 01-01 |
| | | 262 D | January 2013 | 006 |

| | | | | |
|---|---|-----------------------------------|-------------------------------|--------------------------|
| Types covered by similarity: E6: ±20% tolerance | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3001 Detail ESCC 3001/038 | EUROFARAD Chanteloup en Brie France | Qualification Extension | CNES CNES | Mar 2011 Apr 2013 |
| <p>Characteristics:</p> <p>Qualified Range:</p> <p>Variants 01 to 04, 08 to 11, 15 to 18 and 22 to 25 are qualified All values 50V to 500V E12: ±10% tolerance</p> <p>Operating Temperature Range (°C): -55 to +125</p> | | | | |
|  | <p>CAPACITORS, CERAMIC, TYPE II, 50V TO 500V, BASED ON TYPES CNC53 TO CNC56</p> | Current Validity of Qualification | | Page |
| | | Certificate 306 A | Valid Until March 2015 | 01-01 007 |

| Types covered by similarity: Tolerance (\pm): 0.5pF; 2, 5, 20% | | | | | | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|------|----------|--|--|--|--|--|-----------------------------------|-----------------------|--------------|------------|--------------------------------|--------------------|----------------------|------------------------|------|-------|----------|------------|---------------------------|--------------------|----------------------|----------|------|-------|----------|------------|-------------|---------|-------------|----------|------|-------|----------|------------|--------------------------------|---------------|-------------|----------|------|-------|----------|------------|---------------|---------|-------------|----------|------|-------|----------|------------|---------------|---------|-------------|----------|-----------|------|----------|
| Procurement Specifications | | | | Manufacturer | | | | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 3009 Detail ESCC 3009/003 3009/004 3009/005 3009/006 3009/022 | | | | AVX/TPC St Apollinaire France | | | | Qualification | CNES | Feb 1983 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics: Operating Temp. Range ($^{\circ}$ C), -55 to +125 Variants 01, 03 and 06 are qualified Values covered by ESCC Specifications defined below. | | | | <table border="1"> <thead> <tr> <th>Style</th> <th>Model</th> <th>Detail Spec.</th> <th>Variants</th> <th>Capacitance Range (pF)</th> <th>Rated Volt. (V)</th> <th>Tolerance (\pm%)</th> <th>TC (ppm/$^{\circ}$C)</th> </tr> </thead> <tbody> <tr> <td>0805</td> <td>A_12C</td> <td>3009/003</td> <td>01, 03, 06</td> <td>4.7 to 9.1 10 to 1 500</td> <td>50, 100 50, 100</td> <td>0.5pF 1, 2, 5, 10</td> <td>\pm30</td> </tr> <tr> <td>1206</td> <td>A_20C</td> <td>3009/022</td> <td>01, 03, 06</td> <td>10 to 3 900</td> <td>50, 100</td> <td>1, 2, 5, 10</td> <td>\pm30</td> </tr> <tr> <td>1210</td> <td>A_13C</td> <td>3009/004</td> <td>01, 03, 06</td> <td>22 to 6 800 8 200 to 10 000</td> <td>50, 100 50</td> <td>1, 2, 5, 10</td> <td>\pm30</td> </tr> <tr> <td>1812</td> <td>A_14C</td> <td>3009/005</td> <td>01, 03, 06</td> <td>100 to 15 000</td> <td>50, 100</td> <td>1, 2, 5, 10</td> <td>\pm30</td> </tr> <tr> <td>2220</td> <td>A_15C</td> <td>3009/006</td> <td>01, 03, 06</td> <td>470 to 33 000</td> <td>50, 100</td> <td>1, 2, 5, 10</td> <td>\pm30</td> </tr> </tbody> </table> | | | | Style | Model | Detail Spec. | Variants | Capacitance Range (pF) | Rated Volt. (V) | Tolerance (\pm %) | TC (ppm/ $^{\circ}$ C) | 0805 | A_12C | 3009/003 | 01, 03, 06 | 4.7 to 9.1 10 to 1 500 | 50, 100 50, 100 | 0.5pF 1, 2, 5, 10 | \pm 30 | 1206 | A_20C | 3009/022 | 01, 03, 06 | 10 to 3 900 | 50, 100 | 1, 2, 5, 10 | \pm 30 | 1210 | A_13C | 3009/004 | 01, 03, 06 | 22 to 6 800 8 200 to 10 000 | 50, 100 50 | 1, 2, 5, 10 | \pm 30 | 1812 | A_14C | 3009/005 | 01, 03, 06 | 100 to 15 000 | 50, 100 | 1, 2, 5, 10 | \pm 30 | 2220 | A_15C | 3009/006 | 01, 03, 06 | 470 to 33 000 | 50, 100 | 1, 2, 5, 10 | \pm 30 | Extension | CNES | Sep 1986 |
| | | | | | | | | Style | Model | Detail Spec. | Variants | Capacitance Range (pF) | Rated Volt. (V) | Tolerance (\pm %) | TC (ppm/ $^{\circ}$ C) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | 0805 | A_12C | 3009/003 | 01, 03, 06 | 4.7 to 9.1 10 to 1 500 | 50, 100 50, 100 | 0.5pF 1, 2, 5, 10 | \pm 30 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | 1206 | A_20C | 3009/022 | 01, 03, 06 | 10 to 3 900 | 50, 100 | 1, 2, 5, 10 | \pm 30 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | 1210 | A_13C | 3009/004 | 01, 03, 06 | 22 to 6 800 8 200 to 10 000 | 50, 100 50 | 1, 2, 5, 10 | \pm 30 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | 1812 | A_14C | 3009/005 | 01, 03, 06 | 100 to 15 000 | 50, 100 | 1, 2, 5, 10 | \pm 30 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | 2220 | A_15C | 3009/006 | 01, 03, 06 | 470 to 33 000 | 50, 100 | 1, 2, 5, 10 | \pm 30 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | Requalification | CNES | Apr 1992 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | Extension | CNES | Jan 1995 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | Extension | CNES | Jun 1998 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | CNES | Nov 2000 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | CNES | Jun 2003 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Requalification | CNES | Feb 2005 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | CNES | May 2007 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | CNES | Jun 2009 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | CNES | Jun 2011 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | CNES | Jun 2013 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | | | CAPACITORS, CERAMIC, FIXED, CHIP, TYPE I | | | | Current Validity of Qualification | | Page | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | Certificate | Valid Until | 01-02 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | 109 L | June 2015 | 001-1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | | |
|---|--|-----------------------------------|-----------------------|----------|
| Types covered by similarity: Tolerance (\pm): <10pF; 0.25– 0.5-1pF; \geq 10pF; 1, 2, 5, 10% | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3009 Detail ESCC 3009/003 3009/004 3009/005 3009/006 3009/022 3009/037 | EUROFARAD Chanteloup en Brie France | Qualification | CNES | Oct 2012 |
| Characteristics: Variant 06 is qualified See Table on next page Operating Temp. Range ($^{\circ}$ C), -55 to +125 | | | | |
|  | CAPACITORS, CERAMIC, FIXED, CHIP, TYPE I | Current Validity of Qualification | | Page |
| | | Certificate | Valid Until | 01-02 |
| | | 323 | October 2014 | 001-2A |

Characteristics:

| Style | Model | Detail Spec. | Variants | Capacitance Range (pF) | | | Rated Volt. (V) | Tol. (±%) |
|-------|--------|--------------|----------|------------------------|----|--------|-----------------|---|
| 0805 | CEC2S | 3009/003 | 06 | 10 | to | 2 700 | 16 | <10pF 0.25—0.5 -1 (pF) ≥10pF 1, 2, 5, 10 |
| | | | | 10 | to | 2 200 | 25 | |
| | | | | 1 | to | 1 800 | 50 | |
| | | | | 1 | to | 1 200 | 100 | |
| 1210 | CEC4S | 3009/004 | 06 | 10 | to | 15 000 | 16 | |
| | | | | 10 | to | 13 000 | 25 | |
| | | | | 10 | to | 12 000 | 50 | |
| | | | | 10 | To | 6 800 | 100 | |
| 1812 | CEC6S | 3009/005 | 06 | 100 | to | 33 000 | 16 | |
| | | | | 100 | to | 30 000 | 25 | |
| | | | | 100 | to | 22 000 | 50 | |
| | | | | 100 | to | 12 000 | 100 | |
| 2220 | CEC7S | 3009/006 | 06 | 470 | to | 68 000 | 16 | |
| | | | | 470 | to | 56 000 | 25 | |
| | | | | 470 | to | 47 000 | 50 | |
| | | | | 470 | to | 27 000 | 100 | |
| 1206 | CEC12S | 3009/022 | 06 | 10 | to | 6 800 | 16 | |
| | | | | 10 | to | 6 200 | 25 | |
| | | | | 1 | to | 5 600 | 50 | |
| | | | | 1 | to | 3 900 | 100 | |
| 0603 | CEC14S | 3009/037 | 06 | 10 | to | 1 000 | 16 | |
| | | | | 10 | to | 680 | 25 | |
| | | | | 1 | to | 560 | 50 | |
| | | | | 1 | to | 330 | 100 | |



CAPACITORS,
CERAMIC, FIXED,
CHIP, TYPE I

Current Validity of Qualification

Certificate

323


Valid Until

October 2014

Page

01-02

002-2B

| | | | | |
|---|---|--|--|--|
| Types covered by similarity: Tolerance ($\pm\%$): 10, 20% | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3009 Detail ESCC 3009/008 3009/009 3009/010 3009/011 3009/023 | AVX/TPC St Apollinaire France | Qualification Extension Requalification Extension Extension Extension Extension Requalification Extension Extension Extension Extension | CNES CNES CNES CNES CNES CNES CNES CNES CNES CNES CNES CNES | Feb 1983 Sep 1986 Oct 1992 Mar 1995 Jun 1998 Nov 2000 Jun 2003 Feb 2005 May 2007 Jun 2009 Jun 2011 Jun 2013 |
| Characteristics: See Table on next page Operating Temperature Range ($^{\circ}\text{C}$), -55 to +125 | | | | |
|  | CAPACITORS, CERAMIC, FIXED, CHIP, TYPE II | Current Validity of Qualification | | Page |
| | | Certificate 110 L | Valid Until June 2015 | 01-02 002-1A |

| Characteristics: | Style | Model | Detail Spec. | Variants | Capacitance Range (pF) | | | Rated Volt. (V) | Tol. (±%) |
|------------------|-------|----------|--------------|------------|------------------------|-----------|---------|-----------------|-----------|
| | 0805 | A_12G | 3009/008 | 01, 03, 06 | 10 000 | to | 47 000 | 25 | 5, 10, 20 |
| | | | | | 3 900 | to | 27 000 | 50 | 5, 10, 20 |
| | | | | | 820 | to | 10 000 | 100 | 5, 10, 20 |
| | 0805 | A612Z | 3009/008 | 07 | 27 000 | to | 100 000 | 25 | 5, 10, 20 |
| | | | | | 27 000 | to | 68 000 | 50 | |
| | | | | | 10 000 | to | 47 000 | 100 | |
| | 1210 | A_13G | 3009/009 | 01, 03, 06 | 47 000 | to | 220 000 | 25 | 5, 10, 20 |
| | | | | | 33 000 | to | 120 000 | 50 | 5, 10, 20 |
| | | | | | 3 900 | to | 47 000 | 100 | 5, 10, 20 |
| 1210 | A613Z | 3009/009 | 07 | 100 000 | to | 470 000 | 25 | 5, 10, 20 | |
| | | | | 100 000 | to | 330 000 | 50 | | |
| | | | | 47 000 | to | 220 000 | 100 | | |
| 1812 | A_14G | 3009/010 | 01, 03, 06 | 82 000 | to | 470 000 | 25 | 5, 10, 20 | |
| | | | | 56 000 | to | 270 000 | 50 | 5, 10, 20 | |
| | | | | 6 800 | to | 82 000 | 100 | 5, 10, 20 | |
| 1812 | A614Z | 3009/010 | 07 | 220 000 | to | 1 000 000 | 25 | 5, 10, 20 | |
| | | | | 220 000 | to | 680 000 | 50 | | |
| | | | | 82 000 | to | 470 000 | 100 | | |
| 2220 | A_15G | 3009/011 | 01, 03, 06 | 180 000 | to | 1 000 000 | 25 | 5, 10, 20 | |
| | | | | 100 000 | to | 680 000 | 50 | 5, 10, 20 | |
| | | | | 18 000 | to | 180 000 | 100 | 5, 10, 20 | |
| 2220 | A615Z | 3009/011 | 07 | 470 000 | to | 2 200 000 | 25 | 5, 10, 20 | |
| | | | | 470 000 | to | 1 500 000 | 50 | | |
| | | | | 180 000 | to | 1 000 000 | 100 | | |
| 1206 | A_20G | 3009/023 | 01, 03, 06 | 27 000 | to | 100 000 | 25 | 5, 10, 20 | |
| | | | | 12 000 | to | 68 000 | 50 | 5, 10, 20 | |
| | | | | 2 200 | to | 22 000 | 100 | 5, 10, 20 | |
| 1206 | A620Z | 3009/023 | 07 | 47 000 | to | 220 000 | 25 | 5, 10, 20 | |
| | | | | 47 000 | to | 150 000 | 50 | | |
| | | | | 27000 | to | 100 000 | 100 | | |



CAPACITORS,
 CERAMIC, FIXED,
 CHIP, TYPE II

Current Validity of Qualification

Certificate

110 L


Valid Until

June 2015

Page

01-02

002-1B

| | | | | | | | | | |
|---|-------|---|--------------|---|------------------------|-----------------------------------|-----------------|-----------------------|-----------------|
| Types covered by similarity: Tolerance ($\pm\%$): 10, 20% | | | | | | Remarks: | | | |
| Procurement Specifications | | | | Manufacturer | | Nature of Approval | | Supervising Authority | Date |
| Generic ESCC 3009 Detail ESCC 3009/008 3009/009 3009/010 3009/011 3009/023 3009/038 3009/039 | | | | EUROFARAD Chanteloup en Brie France | | Qualification | | CNES | Oct 2012 |
| Characteristics: | Style | Model | Detail Spec. | Variants | Capacitance Range (pF) | | Rated Volt. (V) | Tol. ($\pm\%$) | |
| | 0805 | CNC2S | 3009/008 | 06 | 6 800 | to | 150 000 | 16 | 5, 10, 20 |
| | | | | | 6 800 | to | 100 000 | 25 | |
| | | | | 100 | to | 47 000 | 50 | | |
| | | | | 68 | to | 10 000 | 100 | | |
| Table continues on next page | | | | 07 | 6 800 | to | 220 000 | 16 | 5, 10, 20 |
| | | | | | 6 800 | to | 150 000 | 25 | |
| | | | | | 100 | to | 100 000 | 50 | |
| | | | | | 68 | to | 47 000 | 100 | |
| Operating Temperature Range ($^{\circ}\text{C}$), -55 to +125 | | | | | | | | | |
|  ESCC <small>European Space Components Coordination</small> QPL | | CAPACITORS, CERAMIC, FIXED, CHIP, TYPE II | | | | Current Validity of Qualification | | | Page |
| | | | | | | Certificate | Valid Until | | Page |
| | | | | | | 324 | October 2014 | | 01-02 002-2A |

| Characteristics: | Style | Model | Detail Spec. | Variants | Capacitance Range (pF) | | | Rated Volt. (V) | Tol. (±%) |
|------------------|-------|----------|--------------|----------|--------------------------------|-----------------------------|--|--|-----------------------|
| | 0805 | | CNC2 04S | 3009/039 | 02 | 6 800 6 800 100 68 | to to to to | 150 000 100 000 47 000 10 000 | 16 25 50 100 |
| | | | | 14 | 6 800 6 800 100 68 | to to to to | 390 000 150 000 100 000 47 000 | 16 25 50 100 | 5, 10, 20 |
| 1210 | | CNC4S | 3009/009 | 06 | 33 000 33 000 | to to | 560 000 330 000 | 16 25 | 5, 10, 20 |
| | | CNC4 04S | 3009/039 | 04 | 2 200 2 200 | to to | 220 000 56 000 | 50 100 | |
| | | CNC4S | 3009/009 | 07 | 33 000 33 000 | to to | 820 000 560 000 | 16 25 | 5, 10, 20 |
| | | CNC4 04S | 3009/039 | 16 | 2 200 2 200 | to to | 390 000 220 000 | 50 100 | |
| 1812 | | CNC6S | 3009/010 | 06 | 100 000 100 000 | to to | 1 200 000 680 000 | 16 25 | 5, 10, 20 |
| | | CNC6 04S | 3009/039 | 05 | 3 900 3 900 | to to | 470 000 120 000 | 50 100 | |
| | | CNC6S | 3009/010 | 07 | 100 000 100 000 | to to | 1 800 000 1 200 000 | 16 25 | 5, 10, 20 |
| | | CNC6 04S | 3009/039 | 17 | 3 900 3 900 | to to | 820 000 470 000 | 50 100 | |
| 2220 | | CNC7S | 3009/011 | 06 | 150 000 150 22 000 | to to to | 2 700 000 1 500 000 1 000 000 | 16 25 50 | 5, 10, 20 |
| | | CNC7 04S | 3009/039 | 06 | 22 000 22 000 | to to | 1 000 000 270 000 | 50 100 | |
| | | CNC7S | 3009/011 | 07 | 150 000 150 000 | to to | 3 900 000 2 200 000 | 16 25 | 5, 10, 20 |
| | | CNC7 04S | 3009/039 | 18 | 22 000 22 000 | to to | 1 800 000 1 000 000 | 50 100 | |
| 1206 | | CNC12S | 3009/023 | 06 | 10 000 10 000 470 470 | to to to to | 270 000 180 000 82 000 27 000 | 16 25 50 100 | 5, 10, 20 |
| | | | | 07 | 10 000 10 000 470 470 | to to to to | 390 000 270 000 180 000 120 000 | 16 25 50 100 | 5, 10, 20 |



CAPACITORS,
CERAMIC, FIXED,
CHIP, TYPE II

Current Validity of Qualification

Certificate

324

Valid Until

October 2014

Page

01-02

002-1B

Characteristics:

| Style | Model | Detail Spec. | Variants | Capacitance Range (pF) | | | Rated Volt. (V) | Tol. (±%) |
|-------|-----------|--------------|----------|------------------------|----|-----------|-----------------|-----------|
| 1206 | CNC12 04S | 3009/039 | 03 | 10 000 | to | 270 000 | 16 | 5, 10, 20 |
| | | | | 10 000 | to | 180 000 | 25 | |
| | | | | 470 | to | 82 000 | 50 | |
| | | | | 470 | to | 27 000 | 100 | |
| | | | 15 | 10 000 | to | 1 000 000 | 16 | 5, 10, 20 |
| | | | | 10 000 | to | 270 000 | 25 | |
| | | | | 470 | to | 180 000 | 50 | |
| | | | | 470 | to | 120 000 | 100 | |
| 0603 | CNC14S | 3009/038 | 06 | 390 | to | 33 000 | 16 | 5, 10, 20 |
| | | | | 390 | to | 22 000 | 25 | |
| | | | | 10 | to | 10 000 | 50 | |
| | | | | 10 | to | 2 700 | 100 | |
| | | | 07 | 390 | to | 39 000 | 16 | 5, 10, 20 |
| | | | | 390 | to | 33 000 | 25 | |
| | | | | 10 | to | 22 000 | 50 | |
| | | | | 10 | to | 12 000 | 100 | |
| 0603 | CNC14 04S | 3009/039 | 01 | 390 | to | 33 000 | 16 | 5, 10, 20 |
| | | | | 390 | to | 22 000 | 25 | |
| | | | | 10 | to | 10 000 | 50 | |
| | | | | 10 | to | 2 700 | 100 | |
| | | | 13 | 390 | to | 100 000 | 16 | 5, 10, 20 |
| | | | | 390 | to | 33 000 | 25 | |
| | | | | 10 | to | 22 000 | 50 | |
| | | | | 10 | to | 12 000 | 100 | |



CAPACITORS,
 CERAMIC, FIXED,
 CHIP, TYPE II

Current Validity of Qualification

Certificate

324


Valid Until


October 2014


Page


01-02


002-1B

| Types covered by similarity: ±20% tolerance | | | | Remarks: Extension of qualification testing has been completed. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--------------------|---|-----------|--|-----------------------|----------|--------------------|------------------------|--|-----------|------|-----|-------|-----------|----|-----|-------|----------|----|-----|-----|----------|----|------|-----|--------|-----------|----|-----|-------|----------|----|-----|-----|----------|----|
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 3009 | | AVX Limited Coleraine Northern Ireland | | Qualification | DERA | Feb 2001 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Detail ESCC 3009/034 | | | | Extension | QinetiQ | Apr 2003 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | Extension | QinetiQ | May 2006 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | Extension | BNSC | Jan 2009 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | Extension | UK Space Agency | Mar 2011 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Characteristics: E12 series</p> <p>Qualified Range: Variants 01 to 12 are qualified</p> <p>Terminations: Variants 01 to 12: metallised pads</p> <p>Operating Temperature Range (°C):-55 to +125</p> | | <table border="1"> <thead> <tr> <th>Style</th> <th>Rated Voltage (kV)</th> <th colspan="2">Capacitance Range (pF)</th> <th>Tol. (±%)</th> </tr> </thead> <tbody> <tr> <td rowspan="3">1812</td> <td>1.0</td> <td>3 900</td> <td>to 22 000</td> <td>10</td> </tr> <tr> <td>2.0</td> <td>1 500</td> <td>to 1 800</td> <td>10</td> </tr> <tr> <td>3.0</td> <td>820</td> <td>to 1 000</td> <td>10</td> </tr> <tr> <td rowspan="3">1825</td> <td>1.0</td> <td>27 000</td> <td>to 56 000</td> <td>10</td> </tr> <tr> <td>2.0</td> <td>2 200</td> <td>to 6 800</td> <td>10</td> </tr> <tr> <td>3.0</td> <td>820</td> <td>to 2 700</td> <td>10</td> </tr> </tbody> </table> | | | | Style | Rated Voltage (kV) | Capacitance Range (pF) | | Tol. (±%) | 1812 | 1.0 | 3 900 | to 22 000 | 10 | 2.0 | 1 500 | to 1 800 | 10 | 3.0 | 820 | to 1 000 | 10 | 1825 | 1.0 | 27 000 | to 56 000 | 10 | 2.0 | 2 200 | to 6 800 | 10 | 3.0 | 820 | to 2 700 | 10 |
| Style | Rated Voltage (kV) | Capacitance Range (pF) | | Tol. (±%) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1812 | 1.0 | 3 900 | to 22 000 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 2.0 | 1 500 | to 1 800 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 3.0 | 820 | to 1 000 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1825 | 1.0 | 27 000 | to 56 000 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 2.0 | 2 200 | to 6 800 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 3.0 | 820 | to 2 700 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | <p>CAPACITORS, FIXED, CHIP, CERAMIC, TYPE II, HIGH VOLTAGE, BASED ON 1812 and 1825</p> | | <p>Current Validity of Qualification</p> | | Page | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | Certificate | Valid Until | 01-02 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | 264 D | January 2013 | 004-1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | | |
|--|---|-----------------------------------|---------------------------|--------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3012 | AVX Czech Republic sro Tantalum Division Lanskroun Czech Republic | Qualification | DRA | Jun 1993 |
| Detail ESCC 3012/001 | | Extension | DERA | Apr 2001 |
| | | Extension | QinetiQ | Apr 2003 |
| | | Extension | BNSC | Mar 2008 |
| | | Re-qualification | ESTEC | Mar 2010 |
| | Extension | ESTEC | Mar 2012 | |
| Characteristics: Variants 01 to 07 and 11 to 17 are qualified Termination finish: <ul style="list-style-type: none"> A and B case sizes are available in NILO only, e.g., <ul style="list-style-type: none"> Variant 01 (A case), Variant 02 (B case) C, D, E case sizes are available as Copper only, e.g., <ul style="list-style-type: none"> Variant 13 (C case), Variant 14 (D case), Variant 17 (E case) | | | | |
|  | CAPACITORS, LEADLESS SURFACE MOUNTED, TANTALUM, SOLID ELECTROLYTE, TYPE TAJ | Current Validity of Qualification | | Page |
| | | Certificate 196 E | Valid Until March 2014 | 01-03 004 |

| Types covered by similarity: 20% tolerance by variant where applicable | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|----|---|---|--|--|-----------|---------------------|----|----|-------|----|-----|----|----|-------|----|-----|----|----|-------|----|-----|-----|----|-----|----|-----|-----|----|-----|----|-----|-----|----|-----|----|------|-----|----|----|----|------|-----|----|----|----|------|------|----|----|----|------|--|--|--|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 3006 Detail ESCC 3006/022 | | EUROFARAD Chanteloup en Brie France | Qualification Extension Extension Extension Extension Extension Extension | CNES CNES CNES CNES CNES CNES CNES | Aug 1998 Jan 2001 Aug 2003 Dec 2005 Apr 2008 Oct 2010 Aug 2012 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics: Operating Temperature Range, (°C): -55 to +125 All values defined by the ESCC Detail Specification <table border="1"> <thead> <tr> <th colspan="3">Capacitance Range (nF)</th> <th>Tol. (±%)</th> <th>U_R(kV)</th> </tr> </thead> <tbody> <tr> <td>33</td> <td>to</td> <td>2 200</td> <td>10</td> <td>1.5</td> </tr> <tr> <td>15</td> <td>to</td> <td>1 500</td> <td>10</td> <td>2.5</td> </tr> <tr> <td>15</td> <td>to</td> <td>1 000</td> <td>10</td> <td>3.5</td> </tr> <tr> <td>6.8</td> <td>to</td> <td>470</td> <td>10</td> <td>5.0</td> </tr> <tr> <td>2.2</td> <td>to</td> <td>220</td> <td>10</td> <td>7.5</td> </tr> <tr> <td>1.0</td> <td>to</td> <td>100</td> <td>10</td> <td>10.0</td> </tr> <tr> <td>3.3</td> <td>to</td> <td>68</td> <td>10</td> <td>12.5</td> </tr> <tr> <td>1.5</td> <td>to</td> <td>33</td> <td>10</td> <td>15.0</td> </tr> <tr> <td>0.68</td> <td>to</td> <td>15</td> <td>10</td> <td>20.0</td> </tr> </tbody> </table> | | | Capacitance Range (nF) | | | Tol. (±%) | U _R (kV) | 33 | to | 2 200 | 10 | 1.5 | 15 | to | 1 500 | 10 | 2.5 | 15 | to | 1 000 | 10 | 3.5 | 6.8 | to | 470 | 10 | 5.0 | 2.2 | to | 220 | 10 | 7.5 | 1.0 | to | 100 | 10 | 10.0 | 3.3 | to | 68 | 10 | 12.5 | 1.5 | to | 33 | 10 | 15.0 | 0.68 | to | 15 | 10 | 20.0 | | | |
| Capacitance Range (nF) | | | Tol. (±%) | U _R (kV) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 33 | to | 2 200 | 10 | 1.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 15 | to | 1 500 | 10 | 2.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 15 | to | 1 000 | 10 | 3.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.8 | to | 470 | 10 | 5.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.2 | to | 220 | 10 | 7.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.0 | to | 100 | 10 | 10.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3.3 | to | 68 | 10 | 12.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5 | to | 33 | 10 | 15.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.68 | to | 15 | 10 | 20.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  ESCC European Space Components Coordination QPL | | CAPACITORS, FIXED, RECONSTITUTED MICA, HIGH VOLTAGE, BASED ON TYPE HT86PS | | Current Validity of Qualification | | Page | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | Certificate | Valid Until | 01-05 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | 251 F | April 2014 | 001-1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |


| Types covered by similarity: All values defined by the ESCC Detail Specification ±20% (E6 Series) tolerance by variant where applicable | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|-----------------------------------|-----------|-----------------------------------|-----------------------|--------------------|-----|----|----|----|----|-----|----|----|----|----|------|----|----|----|-----|------|----|-----|----|-----|------|----|-----|----|-----|------|----|-----|----|-----|--|--|-----------|------|----------|
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 3006 Detail ESCC 3006/024 | | EUROFARAD Marmoutier France | | Qualification | CNES | Aug 2002 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | Extension | CNES | Apr 2005 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | Extension | CNES | Aug 2007 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics: E12 Series All values defined by the ESCC Detail Specification | | | | Extension | CNES | Jun 2010 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Sizes Available 01, 02, 03, 04</p> <table border="1"> <thead> <tr> <th colspan="3">Capacitance Range (µF)</th> <th>Tol. (±%)</th> <th>U_R(V)</th> </tr> </thead> <tbody> <tr> <td>2.2</td> <td>to</td> <td>47</td> <td>10</td> <td>50</td> </tr> <tr> <td>1.5</td> <td>to</td> <td>22</td> <td>10</td> <td>63</td> </tr> <tr> <td>0.56</td> <td>to</td> <td>12</td> <td>10</td> <td>100</td> </tr> <tr> <td>0.33</td> <td>to</td> <td>5.6</td> <td>10</td> <td>200</td> </tr> <tr> <td>0.22</td> <td>to</td> <td>4.7</td> <td>10</td> <td>250</td> </tr> <tr> <td>0.10</td> <td>to</td> <td>1.8</td> <td>10</td> <td>400</td> </tr> </tbody> </table> <p>Maximum dimensions (mm): 01: 10.7 x 10.7 x B 02: 15.5 x 15.5 x B 03: 16.5 x 15.5 x B 04: 18.5 x 17.0 x B</p> <p>Where B= 6, 8, 10, 12, 14, 15 depending on capacitance value Operating Temperature Range, (°C): -55 to +125</p> | | Capacitance Range (µF) | | | Tol. (±%) | U _R (V) | 2.2 | to | 47 | 10 | 50 | 1.5 | to | 22 | 10 | 63 | 0.56 | to | 12 | 10 | 100 | 0.33 | to | 5.6 | 10 | 200 | 0.22 | to | 4.7 | 10 | 250 | 0.10 | to | 1.8 | 10 | 400 | | | Extension | CNES | Aug 2011 |
| Capacitance Range (µF) | | | Tol. (±%) | U _R (V) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.2 | to | 47 | 10 | 50 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5 | to | 22 | 10 | 63 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.56 | to | 12 | 10 | 100 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.33 | to | 5.6 | 10 | 200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.22 | to | 4.7 | 10 | 250 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.10 | to | 1.8 | 10 | 400 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | CAPACITORS, FIXED, SURFACE MOUNT, D.C. SELF-HEALING, NON-INDUCTIVE, POLYTEREPHTHALATE DIELECTRIC, BASED ON TYPE PM94S | | | Current Validity of Qualification | | Page | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | Certificate | Valid Until | 01-05 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | 270 D | August 2013 | 003-1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |



| Types covered by similarity: Unless otherwise stated in Table 1(a) of the Detail Specification, 10% and 20% tolerance are available. | | Remarks: | | | | | | | | | | | | | | | | | | |
|--|--|--|---|-----------------------------------|--|-------|------------------------|--------------------|--|--|----|---|--|-----|--|--|-----|----------------------|--------------|-----|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | |
| Generic ESCC 5010 Detail ESCC 5711/002 | | COBHAM MICROWAVE Les Ulis France | Qualification Extension Extension | CNES CNES CNES | Dec 2008 May 2011 Apr 2013 | | | | | | | | | | | | | | | |
| Characteristics: Operating Temperature Range, (°C): -55 to +150 All variants defined by the ESCC Detail Specification. <table border="1" data-bbox="143 746 1317 1209"> <thead> <tr> <th>Type</th> <th>Capacitance Range (pF)</th> <th>U_R(V)</th> </tr> </thead> <tbody> <tr> <td>400M106A & C 400M10xA & 107C 400M108A & C 400M110A & C 400M113J & 114J</td> <td>8.2, 10, 12, 15 18, 22, 27, 33, 39 47, 56, 68 81, 100 10</td> <td>40</td> </tr> <tr> <td>101M106A & C 101M10xA & 107C 101M108A & C</td> <td>3.9, 4.7, 5.6, 6.8 10, 12, 15 22, 27, 33, 39</td> <td>100</td> </tr> <tr> <td>201M106C 201M106A 201M10xA & 107C 201M108A & C 201M111J & 112J</td> <td>2.2, 2.7, 3.3 0.1X (201M106C, -107C, -108C) + 210M106C 3.9, 4.7, 5.6, 6.8, 8.2 10, 12, 15, 18 0.25 & 0.4</td> <td>200</td> </tr> <tr> <td>401M111J 401M112J</td> <td>0.125 0.2</td> <td>400</td> </tr> </tbody> </table> | | | | | | Type | Capacitance Range (pF) | U _R (V) | 400M106A & C 400M10xA & 107C 400M108A & C 400M110A & C 400M113J & 114J | 8.2, 10, 12, 15 18, 22, 27, 33, 39 47, 56, 68 81, 100 10 | 40 | 101M106A & C 101M10xA & 107C 101M108A & C | 3.9, 4.7, 5.6, 6.8 10, 12, 15 22, 27, 33, 39 | 100 | 201M106C 201M106A 201M10xA & 107C 201M108A & C 201M111J & 112J | 2.2, 2.7, 3.3 0.1X (201M106C, -107C, -108C) + 210M106C 3.9, 4.7, 5.6, 6.8, 8.2 10, 12, 15, 18 0.25 & 0.4 | 200 | 401M111J 401M112J | 0.125 0.2 | 400 |
| Type | Capacitance Range (pF) | U _R (V) | | | | | | | | | | | | | | | | | | |
| 400M106A & C 400M10xA & 107C 400M108A & C 400M110A & C 400M113J & 114J | 8.2, 10, 12, 15 18, 22, 27, 33, 39 47, 56, 68 81, 100 10 | 40 | | | | | | | | | | | | | | | | | | |
| 101M106A & C 101M10xA & 107C 101M108A & C | 3.9, 4.7, 5.6, 6.8 10, 12, 15 22, 27, 33, 39 | 100 | | | | | | | | | | | | | | | | | | |
| 201M106C 201M106A 201M10xA & 107C 201M108A & C 201M111J & 112J | 2.2, 2.7, 3.3 0.1X (201M106C, -107C, -108C) + 210M106C 3.9, 4.7, 5.6, 6.8, 8.2 10, 12, 15, 18 0.25 & 0.4 | 200 | | | | | | | | | | | | | | | | | | |
| 401M111J 401M112J | 0.125 0.2 | 400 | | | | | | | | | | | | | | | | | | |
|  | | CAPACITORS, MICROWAVE, SILICON, NAKED DIE, MOS, BASED ON TYPES 101M, 201M, 400M AND 401M | | Current Validity of Qualification | | Page | | | | | | | | | | | | | | |
| | | | | Certificate | Valid Until | 01-11 | | | | | | | | | | | | | | |
| | | | | 286 B | December 2014 | 001 | | | | | | | | | | | | | | |


Section 02


Component Type: Connectors


| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|--------------|-------------|-------|--|----------------|
| 02-01 | | | Multipin, Solder Contacts | |
| | 02-01-001-1 | 71 N | D*M Series, Rectangular | C&K COMPONENTS |
| | 02-01-001-2 | 155 K | D*M Series, Rectangular | SOURIAU |
| 02-02 | | | Multipin, Crimp Contacts | |
| | 02-02-001-1 | 72 N | D*MA Series, Rectangular | C&K COMPONENTS |
| | 02-02-001-2 | 156 J | D*MA Series, Rectangular | SOURIAU |
| | 02-02-003 | 25 M | DBAS Series, Circular | Deutsch |
| | 02-02-005 | 220 F | Series I, Circular, Crimp | SOURIAU |
| | 02-02-006 | 221 F | Series II, Circular, Crimp | SOURIAU |
| | 02-02-007-1 | 222 F | Series III, Circular, Miniature | SOURIAU |
| | 02-02-008 | 223 E | Series III, Hermetic | SOURIAU |
| | 02-02-009 | 288 A | Series ACB1 | Axon' Cables |
| 02-03 | | | Printed Circuit Board | |
| | 02-03-001-1 | 99 L | HE 801 Series | HYPERTAC |
| | 02-03-001-2 | 217 F | HE 801 Series | HYPERTAC UK |
| | 02-03-002-1 | 149 J | KMC Series | HYPERTAC |
| | 02-03-003-1 | 250 E | MHD Series | HYPERTAC |
| | 02-03-004-1 | 281 B | IHD INTERPOSER | HYPERTAC |
| 02-04 | | | R.F. Coaxial | |
| | 02-04-001 | 68 L | SMA Series | Radiall |
| | 02-04-002 | 283 B | SMA 2.9 | Radiall |
| 02-05 | | | Micro-miniature, Crimp Contacts | |
| | 02-05-001-1 | 140 L | MDM Series, Rectangular | C&K COMPONENTS |
| | 02-05-002-1 | 141 L | MTB Series, Rectangular | C&K COMPONENTS |
| | 02-05-003-1 | 290 A | MDMA, Rectangular | C&K COMPONENTS |
| | 02-05-004-1 | 301 A | 8MCG, Rectangular | SOURIAU |


| | | | | | | |
|---|--|--|--------------------|-----------------------------------|----------------|-------|
| Types covered by similarity: | | Remarks: | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | |
| Generic ESCC 3401 Detail ESCC 3401/001 3401/004 3401/022 3401/040 3401/080 | | C&K COMPONENTS Dole France | Qualification | CNES | Feb 1981 | |
| | | | Extension | CNES | Jun 1983 | |
| | | | Extension | CNES | Sep 1986 | |
| | | | Extension | CNES | Oct 1988 | |
| | | | Extension | CNES | Jun 1989 | |
| | | | Extension | CNES | Sep 1991 | |
| | | | Extension | CNES | Apr 1994 | |
| Characteristics: Complete range as defined in the corresponding Detail Specifications are qualified Shell Size: E, A, B, C, D, F Range of Contacts: 9, 15, 25, 37 and 50 size 20 contacts for standard density layout 3W3 to 8W8, 5W1 to 47W1 combined contact arrangements 15, 26, 44, 62, 78 and 104 size 22 contacts for high density layout Mounting Type: Blank: standard mounting holes Y: floating mount E: captive nuts Termination contacts: solder bucket, straight PCB, 90° PCB Gold-plated non-magnetic coating Coaxial contact arrangements: 3401/004 variants 01 to 25 Power contact arrangements: 3401/040 variants 01 to 17 Operating Temperature Range (°C): -55 to +125 | | | Extension | CNES | Jan 1997 | |
| | | | Extension | CNES | Jan 2000 | |
| | | | Extension | CNES | Apr 2003 | |
| | | | Extension | CNES | Aug 2005 | |
| | | | Extension | CNES | Aug 2007 | |
| | | | Extension | CNES | Sep 2009 | |
| | | | Extension | CNES | Aug 2011 | |
|  | | CONNECTORS, ELECTRICAL, SOLDER AND WIRE WRAP CONTACTS, RECTANGULAR RECEPTACLE AND PLUG, BASED ON TYPE D*M | | Current Validity of Qualification | | |
| | | | | Certificate | Valid Until | Page |
| | | | | 71 N | September 2013 | 02-01 |
| | | | | | | 001-1 |



| | | | | | |
|--|--|---|-------------------------|-----------------------|----------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| <p>Generic ESCC 3401</p> <p>Detail ESCC 3401/001 3401/022 3401/072</p> | | <p>SOURIAU Connection Technology Marolles en Brie France</p> | Qualification | CNES | Sep 1988 |
| | | | Extension | CNES | Apr 1991 |
| | | | Extension | CNES | Jan 1994 |
| | | | Extension | CNES | Jul 1996 |
| | | | Extension | CNES | Oct 1997 |
| <p>Characteristics: Complete range as defined in the Detail Specifications are qualified except for</p> <ul style="list-style-type: none"> high density 104 contacts arrangement coaxial and power contacts and arrangement | | | Extension | CNES | Mar 2000 |
| <p>Range of Connectors: 3401/001: variants 01 to 02</p> | | | Extension | CNES | Apr 2003 |
| <p>Range of Contacts: Size 20 : 9, 15, 25, 37 and 50 contacts, Size 22: 15, 26, 44, 62, 78 contacts</p> | | | Extension | CNES | Mar 2006 |
| <p>3401/022: variants 01 to 16 & 44 to 57 & 65 to 80 3401/072: variants 01 to 65</p> | | | Extension | CNES | May 2008 |
| <p>Mounting Type= blank: standard mounting holes; Y: floating mount; E: captive nuts</p> | | | Extension | CNES | May 2010 |
| <p>Gold-plated non-magnetic coating</p> | | Extension | CNES | May 2012 | |
| <p>Operating Temperature Range (°C): -55 to +125</p> | | Current Validity of Qualification | | Page | |
|   | | CONNECTORS, ELECTRICAL, SOLDER AND WIRE WRAP CONTACTS, NON-REMOVABLE, RECTANGULAR RECEPTACLE AND PLUG, BASED ON TYPE D*M | | 02-01 | |
| | | Certificate 155 K | Valid Until May 2014 | 001-2 | |


| | | | | | |
|---|--|---|--------------------|-----------------------|----------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| <p>Generic ESCC 3401</p> <p>Detail ESCC 3401/002 3401/005 3401/020 3401/021</p> | | <p>C&K COMPONENTS Dole France</p> | Qualification | CNES | Feb 1981 |
| | | | Extension | CNES | Jun 1983 |
| | | | Extension | CNES | Sep 1986 |
| | | | Extension | CNES | Oct 1988 |
| | | | Extension | CNES | Jun 1989 |
| | | | Extension | CNES | Sep 1991 |
| <p>Characteristics: Complete range defined in the corresponding Detail Specifications are qualified Shell Size: E, A, B, C, D, F</p> | | | Extension | CNES | Apr 1994 |
| <p>Range of Contacts: 9, 15, 25, 37 and 50 size 20* contacts for standard density layout *Accepts wire sizes AWG # 20 to 24 (standard bucket: variants 01 and 02) per 3401/005 *Accepts wire sizes AWG # 26 and 28 (reduced bucket: variants 03 and 04) per 3401/005 *Accepts wire size AWG # 18 and 20 (large bucket: variants 05 to 06) per 3401/005 ** Accepts wire sizes AWG # 22 to 26 (standard bucket: variants 07 to 08) per 3401/005 15, 26, 44, 62, 78 and 104 size 22** contacts for high density layout</p> | | | Extension | CNES | Jan 1997 |
| <p>Mounting Type: Blank: standard mounting holes; Y: floating mount; E: captive nuts Gold-plated non-magnetic coating Connector Savers: For usage with above connector range Operating Temperature Range (°C): -55 to +125</p> | | | Extension | CNES | Jan 2000 |
| | | | Extension | CNES | Apr 2003 |
| | | Extension | CNES | Aug 2005 | |
| | | Extension | CNES | Aug 2007 | |
| | | Extension | CNES | Sep 2009 | |
| | | Extension | CNES | Aug 2011 | |
|  | <p>CONNECTORS, ELECTRICAL, CRIMP CONTACTS, RECTANGULAR RECEPTACLE AND PLUG, BASED ON TYPE D*MA</p> | Current Validity of Qualification | | Page | |
| | | Certificate | Valid Until | 02-02 | |
| | | 72 N | September 2013 | 001-1 | |


| | | | | | |
|--|--|--|--------------------|-----------------------|----------|
| Types covered by similarity: | | Remarks: . | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3401 Detail ESCC 3401/002 3401/005 3401/020 3401/021 3401/022 3401/072 | | SOURIAU Connection Technology Marolles en Brie France | Qualification | CNES | Sep 1988 |
| | | | Extension | CNES | Apr 1991 |
| | | | Extension | CNES | Jan 1994 |
| | | | Extension | CNES | Jul 1996 |
| | | Extension | CNES | Mar 2000 | |
| | | Extension | CNES | Apr 2003 | |
| | | Extension | CNES | Mar 2006 | |
| Characteristics: Complete range as defined in the Detail Specifications except high density 104 contacts arrangement are qualified Accessories variants qualified : 3401/022: variants 01 to 16, 44 to 57, 65 to 80 3401/072: variants 01 to 65 Range of Connectors:- 3401/002: variants 1 & 2 *Accepts wire sizes AWG # 20 to 24 (standard bucket: variants 01 and 02) 3401/005: variants 1 to 8 *Accepts wire sizes AWG # 26 and 28 (reduced bucket: variants 03 and 04) 3401/021 & 22: variants 1 & 2 *Accepts wire size AWG# 18 and 20 (large bucket: variants 05 and 06) *Accepts wire size AWG # 22, 24 and 26 (contact AWG # 22 for high density, contact arrangements, variants 07 and 08) Range of Contacts: 9, 15, 25, 37 and 50 contacts size 20 for standard contact arrangements 15, 26, 44, 62, 78 contacts size 22 for high density contact arrangements Gold-plated non-magnetic coating Connector Savers- For usage with connector range defined above Operating Temperature Range (°C): -55 to +125 | | Extension | CNES | May 2008 | |
| | | Extension | CNES | Jun 2010 | |
| | | Extension | CNES | May 2012 | |
|  | CONNECTORS AND CONNECTOR SAVER, ELECTRICAL, CRIMP CONTACTS, REMOVABLE RECTANGULAR RECEPTACLE AND PLUG, BASED ON TYPE D*MA | Current Validity of Qualification | | Page | |
| | | Certificate | Valid Until | 02-02 | |
| | | 156 J | May 2014 | 001-2 | |


| Types covered by similarity: | | | Remarks: | | | | | | | | | | | | | | | | |
|--|-------------|---|---|--|--|------|---|------|----|------|----|------|----|-----|----|-----|---|--|--|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | |
| Generic ESCC 3401 Detail ESCC 3401/052 3401/058 3401/062 | | SOURIAU Connection Technology Marolles en Brie France | Qualification Extension Extension Extension Extension Extension Extension | CNES CNES CNES CNES CNES CNES CNES | May 1995 Mar 1998 Jul 2001 Jun 2005 Mar 2008 Mar 2010 Mar 2012 | | | | | | | | | | | | | | |
| Characteristics: All connector variants are qualified For 3401/058, variants 01 to 14 are qualified For 3401/062, variants 01 to 27 are qualified | | <table border="1"> <thead> <tr> <th>Contact Size</th> <th>Ratings (A)</th> </tr> </thead> <tbody> <tr><td>4</td><td>80</td></tr> <tr><td>8</td><td>46.0</td></tr> <tr><td>12</td><td>23.0</td></tr> <tr><td>16</td><td>13.0</td></tr> <tr><td>20</td><td>7.5</td></tr> <tr><td>22</td><td>5.0</td></tr> </tbody> </table> | Contact Size | Ratings (A) | 4 | 80 | 8 | 46.0 | 12 | 23.0 | 16 | 13.0 | 20 | 7.5 | 22 | 5.0 | Extension Extension Extension Extension Extension Extension Extension | CNES CNES CNES CNES CNES CNES CNES | Mar 2012 Mar 2012 Mar 2012 Mar 2012 Mar 2012 Mar 2012 Mar 2012 |
| Contact Size | Ratings (A) | | | | | | | | | | | | | | | | | | |
| 4 | 80 | | | | | | | | | | | | | | | | | | |
| 8 | 46.0 | | | | | | | | | | | | | | | | | | |
| 12 | 23.0 | | | | | | | | | | | | | | | | | | |
| 16 | 13.0 | | | | | | | | | | | | | | | | | | |
| 20 | 7.5 | | | | | | | | | | | | | | | | | | |
| 22 | 5.0 | | | | | | | | | | | | | | | | | | |
| Range: # 20 with standard contact arrangements 3, 6, 10, 19, 26, 32, 41, 53, 61 # 22 with high density arrangements 6, 13, 22, 37, 55, 66, 79, 100, 128 Other arrangements with contact sizes: 20, 16, 12, 8 Receptacle and Plug Shell Sizes: 09, 11, 13, 15, 17, 19, 21, 23, 25 Operating Temperature Range (°C): -65 to +200 | | | | | | | | | | | | | | | | | | | |
|  | | CONNECTORS, ELECTRICAL, CIRCULAR, BAYONET COUPLING, SCOOP-PROOF, REMOVABLE CRIMP CONTACTS, BASED ON TYPE MIL-C-38999, SERIES I | | Current Validity of Qualification | | Page | | | | | | | | | | | | | |
| | | Certificate | Valid Until | 02-02 | 005 | | | | | | | | | | | | | | |
| | | 220 F | March 2014 | | | | | | | | | | | | | | | | |


| Types covered by similarity: | | Remarks: | | | | | | | | | | | | | |
|---|-------------|---|-----------------------------------|-----------------------|----------|----------|----|------|----|-----|----|-----|-----------|------|----------|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | | | | | | | | | | |
| Generic ESCC 3401 Detail ESCC 3401/044 3401/045 3401/062 | | SOURIAU Connection Technology Marolles en Brie France | Qualification | CNES | May 1995 | | | | | | | | | | |
| Characteristics: For 3401/044, all variants are qualified For 3401/045, variants 01 to 08 are qualified For 3401/062, variants 01 to 27 are qualified | | | Extension | CNES | Mar 1998 | | | | | | | | | | |
| Range: # 20 with standard contact arrangements 3, 6, 10, 18, 26, 32, 41, 55, 61 # 22 with high density arrangements 6, 13, 22, 37, 55, 66, 79, 100, 128 | | <table border="1"> <thead> <tr> <th>Contact Size</th> <th>Ratings (A)</th> </tr> </thead> <tbody> <tr> <td>12</td> <td>23.0</td> </tr> <tr> <td>16</td> <td>13.0</td> </tr> <tr> <td>20</td> <td>7.5</td> </tr> <tr> <td>22</td> <td>5.0</td> </tr> </tbody> </table> | Contact Size | Ratings (A) | 12 | 23.0 | 16 | 13.0 | 20 | 7.5 | 22 | 5.0 | Extension | CNES | Jul 2001 |
| Contact Size | Ratings (A) | | | | | | | | | | | | | | |
| 12 | 23.0 | | | | | | | | | | | | | | |
| 16 | 13.0 | | | | | | | | | | | | | | |
| 20 | 7.5 | | | | | | | | | | | | | | |
| 22 | 5.0 | | | | | | | | | | | | | | |
| Other arrangements with contact sizes: 20, 16, 12 Receptacle and Plug Shell Sizes: 08, 10, 12, 14, 16, 18, 20, 22, 24 Operating Temperature Range (°C): -65 to +200 | | | Extension | CNES | Jun 2005 | | | | | | | | | | |
|  | | CONNECTORS, ELECTRICAL, CIRCULAR, BAYONET COUPLING, REMOVABLE CRIMP CONTACTS, BASED ON TYPE MIL-C-38999, SERIES II | Extension | CNES | Mar 2008 | | | | | | | | | | |
| | | | | Extension | CNES | Mar 2010 | | | | | | | | | |
| | | | Extension | CNES | Mar 2012 | | | | | | | | | | |
| | | | Current Validity of Qualification | | Page | | | | | | | | | | |
| | | | Certificate | Valid Until | 02-02 | | | | | | | | | | |
| | | | 221 F | March 2014 | 006 | | | | | | | | | | |


| Types covered by similarity: | | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|-------------|--|--|----------|---|--|--|-------------|---|------|----|------|---|------|----|-----|----|------|----|-----|----|------|--|--|----|-----|--|--|----|-----|--|--|-------------------------------|--|--|
| Procurement Specifications | | | Manufacturer | | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 3401 Detail ESCC 3401/056 3401/058 3401/062 3401/066 3401/070 | | | SOURIAU Connection Technology Marolles en Brie France | | Qualification Extension Extension Extension Extension Extension Extension | CNES CNES CNES CNES CNES CNES CNES | May 1995 Mar 1998 Jul 2001 Jun 2005 Mar 2008 Mar 2010 Mar 2012 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Charac- 3401/056 all variants are qualified teristics: 3401/058 variants 01 to 14 are qualified 3401/062 variants 28 to 54 are qualified 3401/066 variants 01 and 02 are qualified 3401/058 crimp contacts and 3401/066 triax contacts to be mounted on 3401/056 connectors 3401/070 connector receptacles with PCB contacts | | | <table border="1"> <thead> <tr> <th>Crimp Contact Size</th> <th>Ratings (A)</th> <th>PCB Contact Size</th> <th>Ratings (A)</th> </tr> </thead> <tbody> <tr> <td>4</td> <td>80.0</td> <td>16</td> <td>10.0</td> </tr> <tr> <td>8</td> <td>46.0</td> <td>20</td> <td>5.0</td> </tr> <tr> <td>12</td> <td>23.0</td> <td>22</td> <td>3.0</td> </tr> <tr> <td>16</td> <td>13.0</td> <td></td> <td></td> </tr> <tr> <td>20</td> <td>7.5</td> <td></td> <td></td> </tr> <tr> <td>22</td> <td>5.0</td> <td></td> <td></td> </tr> </tbody> </table> | | Crimp Contact Size | Ratings (A) | PCB Contact Size | Ratings (A) | 4 | 80.0 | 16 | 10.0 | 8 | 46.0 | 20 | 5.0 | 12 | 23.0 | 22 | 3.0 | 16 | 13.0 | | | 20 | 7.5 | | | 22 | 5.0 | | | Extension CNES Mar 2012 | | |
| Crimp Contact Size | Ratings (A) | PCB Contact Size | Ratings (A) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | 80.0 | 16 | 10.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 8 | 46.0 | 20 | 5.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 12 | 23.0 | 22 | 3.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16 | 13.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 20 | 7.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 22 | 5.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Range: # 20 with standard contact arrangements (3, 4, 5, 6, 7, 8, 10, 18, 19, 26, 32, 41, 53, 55, 61 contacts) # 22 with high density arrangements (6, 13, 22, 37, 55, 66, 79, 100, 128 contacts) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Other arrangements with contact sizes:# 20, 16, 12, 8,4 Receptacle and Plug Shell Sizes: 09, 11, 13, 15, 17, 19, 21, 23, 25. Triax contacts Operating Temperature Range (°C): -65 to +200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|   | | CONNECTORS, MINIATURE, ELECTRICAL, CIRCULAR, TRIPLE-START SELF- LOCKING COUPLING, SCOOP-PROOF, REMOVABLE AND NON-REMOVABLE CRIMP CONTACTS BASED ON TYPE MIL-C-38999, SERIES III | | | Current Validity of Qualification | | Page | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | Certificate 222 F | Valid Until March 2014 | 02-02 007-1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |


| Types covered by similarity: | | Remarks: | | | | | | |
|--|--|--|-----------------------------------|-----------------------|------------------------|--|--|--|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | | | |
| Generic ESCC 3401 Detail ESCC 3401/057 | | SOURIAU Connection Technology Marolles en Brie France | Qualification | CNES | May 1995 | | | |
| | | | Requalification | CNES | Jul 2001 | | | |
| | | | Extension | CNES | Jun 2005 | | | |
| | | | Extension | CNES | Mar 2008 | | | |
| | | | Extension | CNES | Mar 2010 | | | |
| | | | Extension | CNES | Mar 2012 | | | |
| Characteristics: All variants are qualified <table border="1"> <thead> <tr> <th>Contact Size</th> <th>Ratings (A)</th> </tr> </thead> <tbody> <tr> <td>8, 12, 16 20, 22D</td> <td>33, 17, 10 5.0, 3.0</td> </tr> </tbody> </table> Range: # 20 with standard contact arrangements (3, 6, 10, 19, 26, 32, 41, 53, 61 contacts) # 22 with high density arrangements (6, 13, 22, 37, 55, 66, 79, 100, 128 contacts) Receptacle Shell Sizes: 09, 11, 13, 15, 17, 19, 21, 23, 25 Receptacle (contacts # 8, 12, 16, 20, 22D) and Feedthrough (contacts # 8, 12, 16, 20, 22D) Operating Temperature Range (°C): -65 to +200 | | Contact Size | Ratings (A) | 8, 12, 16 20, 22D | 33, 17, 10 5.0, 3.0 | | | |
| Contact Size | Ratings (A) | | | | | | | |
| 8, 12, 16 20, 22D | 33, 17, 10 5.0, 3.0 | | | | | | | |
|  ESCC European Space Components Coordination QPL | CONNECTORS, MINIATURE, ELECTRICAL, CIRCULAR, TRIPLE-START SELF-LOCKING COUPLING, SCOOP-PROOF, HERMETIC RECEPTACLE AND FEEDTHROUGH, BASED ON TYPE MIL-C-38999, SERIES III | | Current Validity of Qualification | | Page | | | |
| | | | Certificate | Valid Until | 02-02 | | | |
| | | 223 E | March 2014 | 008 | | | | |


| | | | | |
|--|---|-----------------------------------|-----------------------------|--------------------------|
| Types covered by similarity: Variants 02 to 04, 06 to 08, 10 to 12, 14 to 16 and 18 | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3401 Detail ESCC 3401/079 | AXON' CABLE S.A. Montmirail France | Qualification Extension | CNES CNES | May 2009 Nov 2012 |
| <p>Characteristics:</p> <p>Variants 01 to 18 are qualified</p> <p>Variants 01 to 08: Plug 3 and 4 Lugs, Straight and Right Angle with pin contact Variants 09 to 18: Bulkhead Jacks, 3 and 4 Lugs, Straight and Right Angle with solder contact</p> <p>All cables are 77Ω MIL-STD- 1553B Data Bus twisted shielded pairs</p> <p>Working Voltage: 200 Vrms Rated Current (contact): 1A</p> <p>Operating Temperature Range (°C): -55 to +150</p> | | | | |
|  | <p>CONNECTORS, ELECTRICAL, TRIAXIAL, BAYONET COUPLING, NON-REMOVABLE CRIMP CON- TACTS, MIL-STD-1553B DATABUS, BASED ON TYPE ACB1 SERIES</p> | Current Validity of Qualification | | Page |
| | | Certificate 288 A | Valid Until May 2013 | 02-02 009 |


| | | | | | |
|--|------|--|--------------------|-----------------------------------|----------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3401 Detail ESCC 3401/016 3401/017 | | HYPERTAC SA Saint-Aubin-Lès-Elbeuf France | Qualification | CNES | Nov 1982 |
| Characteristics: All variants are qualified Shell specifications and sizes: 3401/016 Contact: 3401/017 Crimp wire-wrap solder and savers, 1 to 22 and 64 to 70 2 rows: 17, 29, 41, 53, 65, 72, 84, 96, 120 contacts 3 rows: 62, 80, 98, 160 contacts Contact Ratings: 5 A (1 contact AWG 22) 1.5 A (>31 contacts, AWG 22) Operating Temperature Range (°C): -55 to +125 | | | Extension | CNES | May 1985 |
| | | | Extension | CNES | May 1988 |
| | | | Extension | CNES | Apr 1991 |
| | | | Extension | CNES | Jan 1994 |
| | | | Extension | CNES | Mar 1996 |
| | | | Extension | CNES | Mar 1998 |
| | | | Extension | CNES | Jan 2002 |
| | | | Extension | CNES | Jun 2004 |
| | | | Extension | CNES | Mar 2007 |
| | | Extension | CNES | Oct 2009 | |
| Extension | CNES | Nov 2011 | | | |
|  | | CONNECTORS, ELECTRICAL, REMOVABLE CONTACTS, CRIMP WIRE-WRAP SOLDER AND SAVER, PRINTED CIRCUIT BOARD, BASED ON TYPE HE 801 | | Current Validity of Qualification | |
| | | Certificate | Valid Until | Page | |
| | | 99 L | October 2013 | 02-03 001-1 | |


| | | | | | | |
|---|--|--|---|---|--|-------|
| Types covered by similarity: | | Remarks: | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | |
| Generic ESCC 3401 Detail ESCC 3401/016 3401/017 | | HYPERTAC LTD London England | Qualification Extension Extension Extension Extension Extension Extension | DRA DRA DERA QinetiQ QinetiQ BNSC UK Space Agency | Jul 1994 Nov 1996 Nov 1998 Apr 2002 Mar 2005 Jan 2009 Dec 2011 | |
| Characteristics: All variants are qualified Shell specifications and sizes: 3401/016 Range of components: 17 to 160 way connectors PCB, 90°, crimp, wire-wrap and saver contacts Guiding/locking device numbers: 26, 27, 28, 29, 33, 34, 35, 36, 40, 41, 43, 46, 54, 55, 71, 72, 73, 76, 77, 78 Contact Ratings: 5 A (1 contact AWG 22) 1.5 A (>31 contacts, AWG 22) Operating Temperature Range (°C): -55 to +125 | | | | | | |
|  | | CONNECTORS, ELECTRICAL, REMOVABLE CONTACTS, CRIMP WIRE-WRAP SOLDER AND SAVER, PRINTED CIRCUIT BOARD, BASED ON TYPE HE 801 | | Current Validity of Qualification | | Page |
| | | | | Certificate | Valid Until | 02-03 |
| | | | | 217 F | January 2013 | 001-2 |


| | | | | | |
|--|-------------|---|---|-----------------------|-----------------------------------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3401 Detail ESCC 3401/039 | | HYPERTAC SA Saint-Aubin-Lès-Elbeuf France | Qualification | CNES | Mar 1987 |
| Characteristics: 3 rows 26, 44, 62, 80, 98, 144 contacts Contact Ratings: 2 A (1 contact) Operating Temperature Range (°C): -55 to +125 | | | Extension | CNES | May 1990 |
| | | | Extension | CNES | Jan 1993 |
| | | | Extension | CNES | Oct 1995 |
| | | | Extension | CNES | Mar 1998 |
| | | | Extension | CNES | Jan 2002 |
| | | | Extension | CNES | Jun 2004 |
| | | | Extension | CNES | Mar 2007 |
| | | | Extension | CNES | Sep 2009 |
| | | | Extension | CNES | Nov 2011 |
| | |  | CONNECTORS, ELECTRICAL, NON-REMOVABLE SOLDER AND WIRE-WRAP CONTACTS AND SAVERS, PRINTED CIRCUIT BOARD, BASED ON TYPE KMC | | Current Validity of Qualification |
| Certificate | Valid Until | | | | 02-03 |
| | | 149 J | September 2013 | 002-1 | |


| | | | | | |
|--|--|---|-----------------------------------|-----------------------|----------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3401 Detail ESCC 3401/065 | | HYPERTAC SA Saint-Aubin-Les-Elbeuf France | Qualification | CNES | Aug 1998 |
| Characteristics: Contact: 52, 100, 152, 200, 252, 300, 352 and 400 Contact Codes: 10, 11, 12, 30, 31, 43, 45, 47 and 91 Guiding and Locking Devices Codes: 110, 111, 121, 124, 134 and 201 Operating Temperature Range (°C): -55 to +125 | | | Extension | CNES | Jan 2002 |
| | | | Extension | CNES | Jun 2004 |
| | | | Extension | CNES | Mar 2007 |
| | | | Extension | CNES | Sep 2009 |
| | | | Extension | CNES | Nov 2011 |
|  | CONNECTORS AND SAVERS, ELECTRICAL, RECTANGULAR, NON-REMOVABLE, PRINTED CIRCUIT BOARD, BASED ON TYPE MHD | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 02-03 |
| | | | 250 E | September 2013 | 003-1 |


| | | | | | |
|---|---|---|--|------------------------------|--------------------------------------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3401 Detail ESCC 3401/076 | | HYPERTAC SA Saint-Aubin-Les-Elbeuf France | Qualification | CNES | Aug 2007 |
| | | | Extension Extension | CNES CNES | Oct 2009 Apr 2012 |
| Characteristics: All design envelops specified in Table 1(a) of ESCC Detail Specification are qualified Max. number of rows 11 Max. number of contacts: 660 Locking and Guiding Devices: -Through holes only -M2 studs with locking nuts and washers -Locating pins not available Rated current: 1A each contact Total contact compression range: 0.1 to 0.65 mm per contact Compression force: 1.6N per contact Torque for locking devices: 10 Ncm Operating Temperature Range (°C): -55 to +125 | | | | | |
|  | CONNECTORS, ELECTRICAL, CRIMP CONTACTS, Z-AXIS INTERPOSER, PRINTED CIRCUIT BOARD, BASED ON TYPE RX | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 02-03 |
| | | 281 B | October 2013 | 004-1 | |


| | | | | | |
|---|--|--|----------------------|--------------------------|----------|
| Types covered by similarity: - Hermetically sealed receptacle | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| <p>Generic ESCC 3402</p> <p>Detail ESCC 3402/001 3402/002 3402/003</p> | | RADIALL Saint-Quentin-Fallavier France | Qualification | CNES | Feb 1981 |
| | | | Extension | CNES | Apr 1983 |
| | | | Extension | CNES | Apr 1986 |
| | | | Extension | CNES | Nov 1989 |
| | | | Extension | CNES | Jul 1992 |
| | | | Extension | CNES | Nov 1994 |
| | | | Extension | CNES | May 1998 |
| | | | Extension | CNES | Aug 2002 |
| | | | Extension | CNES | Jan 2005 |
| | | | Extension | CNES | Dec 2007 |
| | | | Extension | CNES | May 2010 |
| | | Extension | CNES | Jan 2012 | |
| <p>Characteristics:</p> <p>Frequency Range 0-18 GHz 3402/001 Pin contact (Plug). Variants 01 to 47 3402/002 socket contact (Receptacle). Variants 01 to 85 3402/003 Adapters. Variants 01 to 14 Crimp— or solder-type contact for flexible and semi-rigid cables, contacts for micro strip Shell material and finish: Beryllium copper gold plated, copper or nickel underplate; stainless steel, electro-passivated or gold plated.</p> <p>Operating Temperature Range (°C): See Detail Specifications</p> | | | | | |
|  | <p align="center">CONNECTORS, RF, COAXIAL, SOLDER AND CRIMP CONTACTS, MALE, FEMALE ADAPTORS AND CONNECTING PIECES, BASED ON TYPE SMA</p> | Current Validity of Qualification | | Page | |
| | | Certificate | Valid Until | 02-04 | |
| | | 68 L | December 2013 | 001 | |

| | | | | | |
|--|--|---|---|-----------------------------------|----------------------------------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3402 Detail ESCC 3402/021 3402/022 3402/023 | | RADIALL Saint-Quentin-Fallavier France | Qualification Extension Extension | CNES CNES CNES | Dec 2007 May 2010 Jan 2012 |
| Characteristics: Frequency Range 0-40 GHz 50 Ohms 3402/021 Pin contact (Plug). Variants 01 to 05 and 07 3402/022 Socket contact (Receptacle). Variants 01 to 05 3402/023 Adapters. Variants 01 to 06 Crimp- or solder-type contact for flexible and semi-rigid cables, contacts for micro strip Shell material and finish: passivated amagnetic stainless steel. Operating Temperature Range (°C): -65 to +165 | | | | | |
|  | | CONNECTORS, RF, COAXIAL, SOLDER AND CRIMP CONTACTS, MALE, FEMALE ADAPTORS AND CONNECTING PIECES, BASED ON TYPE SMA 2.9 | | Current Validity of Qualification | |
| | | Certificate 283 B | | Valid Until December 2013 | |
| | | | | Page 02-04 002 | |

| Types covered by similarity: | | Remarks: | | | | | | | | | | | | | | |
|--|--|---|-----------------------------------|-----------------------|----------------|----|---|-----|----|----------------------------|-----|----|----------------------------|-----|--|--|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | |
| Generic ESCC 3401 Detail ESCC 3401/029 3401/041 3401/032 | | C&K COMPONENTS Dole France | Qualification | CNES | Oct 1986 | | | | | | | | | | | |
| | | | Extension | CNES | Oct 1988 | | | | | | | | | | | |
| | | | Extension | CNES | Jun 1989 | | | | | | | | | | | |
| | | | Extension | CNES | Sep 1991 | | | | | | | | | | | |
| | | | Extension | CNES | Apr 1994 | | | | | | | | | | | |
| | | | Extension | CNES | Jan 1997 | | | | | | | | | | | |
| | | | Extension | CNES | Oct 1999 | | | | | | | | | | | |
| | | | Extension | CNES | Apr 2003 | | | | | | | | | | | |
| | | | Extension | CNES | Nov 2005 | | | | | | | | | | | |
| | | | Extension | CNES | Aug 2007 | | | | | | | | | | | |
| | | Extension | CNES | Sep 2009 | | | | | | | | | | | | |
| | | Extension | CNES | Aug 2011 | | | | | | | | | | | | |
| Characteristics: Layout: 9 - 15 - 21- 25 - 31 - 37 - 51 Contacts Non removable crimp contacts Termination types: Nickel or Gold Plated Shells Operating Temperature Range (°C): -55 to +125 | | <table border="1"> <thead> <tr> <th>AWG #</th> <th>ESCC No.</th> <th>Max. Rated (A)</th> </tr> </thead> <tbody> <tr> <td>25</td> <td>Uninsulated rigid wire Bent and straight PCB</td> <td>2.5</td> </tr> <tr> <td>26</td> <td>3901 013 02 3901 002 56</td> <td>2.5</td> </tr> <tr> <td>28</td> <td>3901 013 01 3901 002 61</td> <td>1.5</td> </tr> </tbody> </table> | AWG # | ESCC No. | Max. Rated (A) | 25 | Uninsulated rigid wire Bent and straight PCB | 2.5 | 26 | 3901 013 02 3901 002 56 | 2.5 | 28 | 3901 013 01 3901 002 61 | 1.5 | | |
| AWG # | ESCC No. | Max. Rated (A) | | | | | | | | | | | | | | |
| 25 | Uninsulated rigid wire Bent and straight PCB | 2.5 | | | | | | | | | | | | | | |
| 26 | 3901 013 02 3901 002 56 | 2.5 | | | | | | | | | | | | | | |
| 28 | 3901 013 01 3901 002 61 | 1.5 | | | | | | | | | | | | | | |
|  | CONNECTORS, ELECTRICAL, RECTANGULAR, MICROMINIATURE, CRIMP CONTACT, BASED ON TYPE MDM | | Current Validity of Qualification | | Page | | | | | | | | | | | |
| | | | Certificate | Valid Until | 02-05 | | | | | | | | | | | |
| | | 140 L | September 2013 | 001-1 | | | | | | | | | | | | |

| Types covered by similarity: | | Remarks: | | | | | | | | | | | | | | |
|--|------------------------------------|---|--------------------|---|----------|------------------------------------|-----|------|-------------|-------------|----|-------------|----------------|----------------|--|--|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | |
| Generic ESCC 3401 Detail ESCC 3401/031 | | C&K COMPONENTS Dole France | Qualification | CNES | Oct 1986 | | | | | | | | | | | |
| Characteristics: Shell sizes: 5 through 81 contacts Non removable crimp contacts Termination Types: Operating Temperature Range (°C): -55 to +125 | | | Extension | CNES | Oct 1988 | | | | | | | | | | | |
| | | | Extension | CNES | Jun 1989 | | | | | | | | | | | |
| | | | Extension | CNES | Sep 1991 | | | | | | | | | | | |
| | | | Extension | CNES | Apr 1994 | | | | | | | | | | | |
| | | | Extension | CNES | Jan 1997 | | | | | | | | | | | |
| | | | Extension | CNES | Oct 1999 | | | | | | | | | | | |
| | | | Extension | CNES | Apr 2003 | | | | | | | | | | | |
| | | | Extension | CNES | Nov 2005 | | | | | | | | | | | |
| | | | Extension | CNES | Aug 2007 | | | | | | | | | | | |
| | | Extension | CNES | Sep 2009 | | | | | | | | | | | | |
| Extension | CNES | Aug 2011 | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>AWG #</th> <th>ESCC No.</th> <th>Max. Rated (A)</th> </tr> </thead> <tbody> <tr> <td>25</td> <td>Uninsulated rigid wire Bent PCB</td> <td>2.5</td> </tr> <tr> <td>26</td> <td>3901 013 02</td> <td>2.5</td> </tr> <tr> <td>28</td> <td>3901 013 01</td> <td>1.5</td> </tr> </tbody> </table> | | AWG # | ESCC No. | Max. Rated (A) | 25 | Uninsulated rigid wire Bent PCB | 2.5 | 26 | 3901 013 02 | 2.5 | 28 | 3901 013 01 | 1.5 | | | |
| AWG # | ESCC No. | Max. Rated (A) | | | | | | | | | | | | | | |
| 25 | Uninsulated rigid wire Bent PCB | 2.5 | | | | | | | | | | | | | | |
| 26 | 3901 013 02 | 2.5 | | | | | | | | | | | | | | |
| 28 | 3901 013 01 | 1.5 | | | | | | | | | | | | | | |
|  | | CONNECTORS, ELECTRICAL, MICROMINIATURE, CRIMP CONTACT, SINGLE-IN-LINE, BASED ON TYPE MTB | | <table border="1"> <thead> <tr> <th colspan="2">Current Validity of Qualification</th> <th>Page</th> </tr> <tr> <th>Certificate</th> <th>Valid Until</th> <th></th> </tr> </thead> <tbody> <tr> <td>141 L</td> <td>September 2013</td> <td>02-05 002-1</td> </tr> </tbody> </table> | | Current Validity of Qualification | | Page | Certificate | Valid Until | | 141 L | September 2013 | 02-05 002-1 | | |
| Current Validity of Qualification | | Page | | | | | | | | | | | | | | |
| Certificate | Valid Until | | | | | | | | | | | | | | | |
| 141 L | September 2013 | 02-05 002-1 | | | | | | | | | | | | | | |


| | | | | | | |
|--|--|---|----------------------------|-----------------------------------|----------------------|-------|
| Types covered by similarity: Contact sizes 21, 31 | | Remarks: | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | |
| Generic ESCC 3401 Detail ESCC 3401/077 3401/078 | | C&K COMPONENTS Dole France | Qualification Extension | CNES CNES | Jun 2009 Aug 2011 | |
| Characteristics: All variants are qualified Range of contacts: 9 - 15 - 21- 25 - 31 - 37 Accepts wires AWG 26 and 28 Max. rating for 1 isolated contact:- uninsulated AWG 25 solid wire: 2.5 A AWG 26 wire: 2.5 A AWG 28 wire: 1.5 A Nickel or Gold Plated Shells Working Voltage (Max.) 150Vrms Operating Temperature Range (°C): -55 to +125 | | | | | | |
|  | | CONNECTORS, ELECTRICAL, RECTANGULAR, MICROMINIATURE, REMOVABLE CRIMP CONTACT, BASED ON TYPE MDMA | | Current Validity of Qualification | | Page |
| | | | | Certificate | Valid Until | 02-05 |
| | | | | 290 A | June 2013 | 003-1 |


| | | | | | | |
|--|--|--|--|--------------------------------------|--|-------|
| Types covered by similarity: | | Remarks: | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | |
| <p>Generic ESCC 3401</p> <p>Detail ESCC 3401/081 3401/082 3401/083 3401/084</p> | | <p>SOURIAU Connection Technology Marolles en Brie France</p> | <p>Qualification Extension</p> | <p>CNES CNES</p> | <p>Jun 2010 Dec 2012</p> | |
| <p>Characteristics:</p> <p>3401/081: Shell variant 01 (glass-fibre reinforced thermoplastic), variant 02 (aluminium alloy). Contacts arrangements 7, 13, 25, 51, 104 contacts. Contacts termination OL3 (straight PCB), 1A7N (90° PCB 2.54mm spacing), 1B7N (90° PCB 2.54mm spacing). Gold-plated shells.</p> <p>3401/082: Shell variant 01 (glass-fibre reinforced thermoplastic), variant 02 (aluminium alloy). Contacts arrangements 7, 13, 25, 51, 104 contacts.</p> <p>3401/083: Contacts variant 01 (male crimp barrel 26), 02 (female crimp barrel 26), 03 (male crimp barrel 24), 04 (female crimp barrel 24). Accepts wires AWG 24, 26, 28</p> <p>3401/084: Accessories variants 01 to 62.</p> <p>Operating Temperature Range (°C): -55 to +125</p> | | | | | | |
|  | | <p>CONNECTORS, ELECTRICAL, RECTANGULAR, MICROMINIATURE, REMOVABLE AND NON-REMOVABLE, GAUGE 26, PCB PIN CONTACT, BASED ON TYPE 8MCG</p> | | Current Validity of Qualification | | Page |
| | | | | Certificate | Valid Until | 02-05 |
| | | | | 301 A | June 2014 | 004-1 |


Section 03**Component Type: Crystals**


| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|-------------|-------|------------------|--------------|
| 03-01 | | | Crystals | |
| | 03-01-001-1 | 33 L | TO-5 Can | RAKON (F) |
| | 03-01-001-3 | 308 A | TO-5 Can | KVG (D) |
| | 03-01-002 | 34 L | TO-8 Can | RAKON (F) |
| | 03-01-002-3 | 309 A | TO-8 Can | KVG (D) |

**SECTION 03-**: INDEX OF CRYSTALS****REP005 Updated on 15 Jun 2013**

| | | | | | |
|---|-----------------------|--------------------------------------|-----------------------------------|-----------------------|--------------------------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3501 Detail ESCC 3501/001 3501/008 3501/011 3501/012 3501/018 | | RAKON France Argenteuil France | Qualification | CNES | Oct 1979 |
| | | | Extension | CNES | Jun 1983 |
| | | | Extension | CNES | Oct 1986 |
| | | | Extension | CNES | Jul 1989 |
| | | | Extension | CNES | Jan 1995 |
| | | | Extension | CNES | Nov 1996 |
| | | | Extension | CNES | Apr 2000 |
| | | | Extension | CNES | Nov 2002 |
| | | | Extension | CNES | Jun 2005 |
| | | | Extension | CNES | Mar 2008 |
| Characteristics: All variants are qualified. TO-5 Can (T 807) Frequency Range: 15 - 140 MHz | | | Extension | CNES | Jul 2010 |
| | | | Extension | CNES | Aug 2012 |
|  ESCC <small>European Space Components Coordination</small> QPL | CRYSTALS, TO-5 CAN | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 03-01 |
| | | 33 L | March 2014 | 001-1 | |

| | | | | | |
|---|-----------------------|--|--|--------------------------------|--|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3501 Detail ESCC 3501/001 3501/008 3501/011 3501/012 3501/018 | | KVG Quartz Crystal Technology GmbH Neckarbischofsheim Germany | Qualification Extension | DLR DLR | Apr 2011 Jun 2013 |
| Characteristics: All variants are qualified. TO-5 Can (T 807) Frequency Range: 8 - 140 MHz | | | | | |
|  | CRYSTALS, TO-5 CAN | Current Validity of Qualification | | Page | |
| | | Certificate | Valid Until | 03-01 | |
| | | 308 A | April 2015 | 001-3 | |

| | | | | | |
|---|-----------------------|--------------------------------------|-----------------------------------|-----------------------|----------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3501 Detail ESCC 3501/002 3501/009 3501/019 | | RAKON France Argenteuil France | Qualification | CNES | Oct 1979 |
| | | | Extension | CNES | Jun 1983 |
| | | | Extension | CNES | Oct 1986 |
| | | | Extension | CNES | Jul 1989 |
| | | | Extension | CNES | Jan 1995 |
| | | | Extension | CNES | Apr 1997 |
| | | | Extension | CNES | Apr 2000 |
| | | | Extension | CNES | Nov 2002 |
| | | | Extension | CNES | Jun 2005 |
| | | | Extension | CNES | Mar 2008 |
| Characteristics: All variants are qualified. TO-8 Can (T 1507) Frequency Range: 2.5 - 20 MHz | | | Extension | CNES | Jul 2010 |
| | | | Extension | CNES | Aug 2012 |
|  | CRYSTALS, TO-8 CAN | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 03-01 |
| | | 34 L | March 2014 | 002 | |

| | | | | | |
|---|-----------------------|--|-----------------------------------|-----------------------|--------------------------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3501 Detail ESCC 3501/002 3501/009 3501/019 | | KVG Quartz Crystal Technology GmbH Neckarbischofsheim Germany | Qualification Extension | DLR DLR | Apr 2011 Jun 2013 |
| Characteristics: All variants are qualified. TO-8 Can (T 1507) Frequency Range: 2.5 - 26 MHz | | | | | |
|  | CRYSTALS, TO-8 CAN | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 03-01 |
| | | 309 A | April 2015 | 002-3 | |

Section 04

Component Type: Diodes

| | | | | |
|-------|----------------|-------|---|--------------------|
| 04-01 | | | Switching | |
| | 04-01-003-2 | 311 | Types 1N6640U and 1N6642U | STMicroelectronics |
| | 04-01-003-3 | 316 | Types BAY6642 | Infineon |
| 04-02 | | | Power Rectifier | |
| | 04-02-001-3 | 297 A | Types 1N5806U and 1N5811U | STMicroelectronics |
| | 04-02-001-4 | 302 A | Types 1N5819U and 1N5822U | STMicroelectronics |
| | 04-02-002-1 | 272 E | Type STPS20100 | STMicroelectronics |
| | 04-02-003-1 | 274 D | Types BYW-81, BYV52, BYV54 | STMicroelectronics |
| 04-05 | | | RF/Microwave, Silicon Schottky | |
| | 04-05-001-3 | 227 D | Schottky, BAS 70 | Infineon |
| 04-13 | | | RF/Microwave, Varactors | |
| | 04-13-003 1A-B | 200 F | PIN and Varactors | RF2M Microwave |
| | 04-13-003-2A-B | 225 E | Multiplier and PIN, DH 2xx and DH 50xxx | Cobham Microwave |
| | 04-13-003-3 | 273 C | Varactor, Tuning, DH 76xxx | Cobham Microwave |
| 04-16 | | | RF/Microwave, PIN | |
| | 04-16-002-2 | 224 E | PIN, BXY 42 | Infineon |
| | 04-16-003 | 236 E | PIN, BXY 43 and 44 | Infineon |



| | |
|------------------------------|--|
| Types covered by similarity: | Remarks: Extension of qualification testing has been completed. |
|------------------------------|--|


| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
|--|---|--------------------|-----------------------|----------|
| Generic ESCC 5000 Detail ESCC 5101/026 5101/027 | ST Microelectronics Rennes France | Qualification | CNES | May 2011 |


Characteristics:


| Type | Variants | V _{BR} (V) | V _{RWM} (V) | I _{FSM} (A) | Case |
|---------|----------|---------------------|----------------------|----------------------|--------|
| 1N6640U | 07, 08 | 75 | 75 | 2 | LCC2-D |
| 1N6642U | 07, 08 | 100 | 100 | 2 | LCC2-D |


Operating Temperature Range (°C): -65 to +175

| | | | | |
|--|---|-----------------------------------|-------------------------|------------------|
|   | DIODES, SWITCHING, BASED ON TYPES 1N6640U AND 1N6642U | Current Validity of Qualification | | Page |
| | | Certificate 311 | Valid Until May 2013 | 04-01 001-3-2 |

| Types covered by similarity: | | | | Remarks: | | | | | | | | | | | | | | | | | | | | |
|--|---------|---|----------------------|-------------------------------------|---------------------------------------|-------------------------------------|------------------|-----------|---------------------|----------------------|-------------------------------------|---------------------------------------|-------------------------------------|--------|------|--------------|----|-----|---|----|-----|-----|-----|-----------|
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5000 Detail ESCC 5101/029 | | INFINEON Technologies AG Neubiberg Germany | | Qualification | DLR | Dec 2011 | | | | | | | | | | | | | | | | | | |
| Characteristics: <table border="1" data-bbox="85 890 1400 1053"> <thead> <tr> <th>Type</th> <th>Variant</th> <th>V_{BR} (V)</th> <th>t_{rr} (ns)</th> <th>V_{RWM} (V_{pk})</th> <th>I_R (μA)@ V_{RWM}</th> <th>I_{FSM} (A_{pk})</th> <th>C (pF)</th> <th>Case</th> </tr> </thead> <tbody> <tr> <td>BAY6642 (ES)</td> <td>01</td> <td>100</td> <td>4</td> <td>75</td> <td>100</td> <td>2.5</td> <td>2.5</td> <td>HSL2-1808</td> </tr> </tbody> </table> | | | | | | | Type | Variant | V _{BR} (V) | t _{rr} (ns) | V _{RWM} (V _{pk}) | I _R (μA)@ V _{RWM} | I _{FSM} (A _{pk}) | C (pF) | Case | BAY6642 (ES) | 01 | 100 | 4 | 75 | 100 | 2.5 | 2.5 | HSL2-1808 |
| Type | Variant | V _{BR} (V) | t _{rr} (ns) | V _{RWM} (V _{pk}) | I _R (μA)@ V _{RWM} | I _{FSM} (A _{pk}) | C (pF) | Case | | | | | | | | | | | | | | | | |
| BAY6642 (ES) | 01 | 100 | 4 | 75 | 100 | 2.5 | 2.5 | HSL2-1808 | | | | | | | | | | | | | | | | |
| Operating Temperature Range (°C): -65 to +175 | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | DIODES, SWITCHING, BASED ON TYPES BAY6642(ES) | | | Current Validity of Qualification | | Page | | | | | | | | | | | | | | | | | |
| | | | | | Certificate 316 | Valid Until December 2013 | 04-01 001-3-3 | | | | | | | | | | | | | | | | | |

| Types covered by similarity: | | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | |
|--|---------|---|---------------------|--------------------------------|-----------------------------------|--------------------------|-------|------|----------|---------------------|----------------------|----------------------|------|----------|---------|--------|-----|-----|----|--------|----------|---------|--------|-----|-----|-----|--------|
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5000 Detail ESCC 5101/013 5101/014 | | ST Microelectronics Rennes France | | Qualification Extension | CNES CNES | Nov 2009 Jan 2012 | | | | | | | | | | | | | | | | | | | | | |
| Characteristics: <table border="1" data-bbox="107 885 1384 1050"> <thead> <tr> <th>ESCC</th> <th>Type</th> <th>Variants</th> <th>V_{BR} (V)</th> <th>V_{RWM} (V)</th> <th>I_{FSM} (A)</th> <th>Case</th> </tr> </thead> <tbody> <tr> <td>5101/014</td> <td>1N5806U</td> <td>13, 14</td> <td>160</td> <td>150</td> <td>33</td> <td>LCC2-A</td> </tr> <tr> <td>5101/013</td> <td>1N5811U</td> <td>11, 12</td> <td>160</td> <td>150</td> <td>100</td> <td>LCC2-B</td> </tr> </tbody> </table> | | | | | | | ESCC | Type | Variants | V _{BR} (V) | V _{RWM} (V) | I _{FSM} (A) | Case | 5101/014 | 1N5806U | 13, 14 | 160 | 150 | 33 | LCC2-A | 5101/013 | 1N5811U | 11, 12 | 160 | 150 | 100 | LCC2-B |
| ESCC | Type | Variants | V _{BR} (V) | V _{RWM} (V) | I _{FSM} (A) | Case | | | | | | | | | | | | | | | | | | | | | |
| 5101/014 | 1N5806U | 13, 14 | 160 | 150 | 33 | LCC2-A | | | | | | | | | | | | | | | | | | | | | |
| 5101/013 | 1N5811U | 11, 12 | 160 | 150 | 100 | LCC2-B | | | | | | | | | | | | | | | | | | | | | |
| Operating Temperature Range (°C): -65 to +175 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  <p>ESCC European Space Components Coordination QPL</p> | | DIODES, POWER RECTIFIER, BASED ON TYPES 1N5806U AND 1N5811U | | | Current Validity of Qualification | | Page | | | | | | | | | | | | | | | | | | | | |
| | | | | | Certificate | Valid Until | 04-02 | | | | | | | | | | | | | | | | | | | | |
| | | | | | 297 A | November 2013 | 001-3 | | | | | | | | | | | | | | | | | | | | |

| Types covered by similarity: | | Remarks: | | | | | | | | | | | | | | | | | | | | | |
|---|----------------------|---|--|-----------------------------------|---------------------------|------|----------------------|--------------|--|----------------------|---------------------------|---------|----|--------|---------|----|---|---------|----|--------|------------|----|---|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5000 Detail ESCC 5106/020 5106/021 | | ST Microelectronics Rennes France | Qualification Extension | CNES CNES | Sep 2010 Sep 2012 | | | | | | | | | | | | | | | | | | |
| Characteristics: Variants 01 and 02 of 5106/020 and Variants 02 and 03 of 5106/021 are qualified | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>Type</th> <th>V_{RWM} (V)</th> <th>dV/dt (V/μs)</th> <th>I_R (μA) @ V_R= 40</th> <th>I_{FSM} (A)</th> <th>I_O (A) @ Tamb</th> </tr> </thead> <tbody> <tr> <td>1N5819U</td> <td>40</td> <td>10 000</td> <td>15 (DC)</td> <td>25</td> <td>1</td> </tr> <tr> <td>1N5822U</td> <td>40</td> <td>10 000</td> <td>80 (pulse)</td> <td>80</td> <td>3</td> </tr> </tbody> </table> | | | | | | Type | V _{RWM} (V) | dV/dt (V/μs) | I _R (μA) @ V _R = 40 | I _{FSM} (A) | I _O (A) @ Tamb | 1N5819U | 40 | 10 000 | 15 (DC) | 25 | 1 | 1N5822U | 40 | 10 000 | 80 (pulse) | 80 | 3 |
| Type | V _{RWM} (V) | dV/dt (V/μs) | I _R (μA) @ V _R = 40 | I _{FSM} (A) | I _O (A) @ Tamb | | | | | | | | | | | | | | | | | | |
| 1N5819U | 40 | 10 000 | 15 (DC) | 25 | 1 | | | | | | | | | | | | | | | | | | |
| 1N5822U | 40 | 10 000 | 80 (pulse) | 80 | 3 | | | | | | | | | | | | | | | | | | |
| Operating Temperature Range (°C): -65 to +150 Package Type: LCC2-B | | | | | | | | | | | | | | | | | | | | | | | |
|  | | DIODES, POWER SCHOTTKY, BASED ON TYPES 1N5819U AND 1N5822U | | Current Validity of Qualification | Page | | | | | | | | | | | | | | | | | | |
| | | Certificate 302 A | Valid Until September 2014 | 04-02 001-4 | | | | | | | | | | | | | | | | | | | |

| | | | | | | |
|--|--|---|--|--|--|--------|
| Types covered by similarity | | Remarks: | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | |
| Generic ESCC 5000 Detail ESCC 5106/016 5106/017 5106/018 5106/019 | | ST Microelectronics Rennes France | Qualification Extension Extension Extension Extension Extension | CNES CNES CNES CNES CNES CNES | Nov 2002 Mar 2006 Jul 2008 Feb 2009 Nov 2010 Dec 2012 | |
| Characteristics: Maximum Ratings for 5106/016: V_{RRM} : 100 V I_o : 2 x 20 A dV/dt 10 000 V/ μ s T_j : + 175°C Package Types TO254, SMD.5 and SMD1 Operating Temperature Range (°C): -65 to +175 | | | | | | |
|  | | DIODES, POWER, SCHOTTKY BARRIER, BASED ON TYPE STPS20100 | | Current Validity of Qualification | | Page |
| | | | | Certificate | Valid Until | 04-02 |
| | | | | 272 E | November 2014 | 002-1A |

Types covered by similarity:

| ESCC COMP. NO. | VARANTS | RANGE OF COMPONENTS | BASED ON |
|-------------------|---------|------------------------|----------------|
| 5106/016 | 01 | TO254 | STPS20100FSY |
| | 02 | TO254 | STPS20100AFSY |
| | 03 | TO254 | STPS20100CFSY |
| | 04 | TO254 | STPS20100SFSY |
| | 05 | SMD.5 | STPS20100S |
| | 06 | SMD1 | STPS20100SA |
| | 07 | SMD1 | STPS20100CSA |
| 5106/017 | 01 | SMD.5 | STPS1045S |
| | 02 | SMD.5 | STPS1045CS |
| 5106/018 | 01 | TO254 | STPS6045CFSY |
| | 02 | SMD1 | STPS6045CSA |
| 5106/019 | 01 | TO254 | STPS40100C2FSY |
| | 02 | TO254 | STPS40100C1FSY |
| | 03 | SMD1 | STPS40100CSA |



DIODES, POWER, SCHOTTKY BARRIER,
BASED ON TYPE STPS20H100

Current Validity of Qualification

Certificate

272 E


Valid Until


November 2014


Page

04-02

002-1B

| | | | | | |
|---|--|---|---|--------------------------------------|--|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 5000 Detail ESCC 5103/029 5103/030 5103/031 | | ST Microelectronics Rennes France | Qualification Extension Extension Extension Extension | CNES CNES CNES CNES CNES | Aug 2003 Mar 2006 Jul 2008 Nov 2010 Dec 2012 |
| Characteristics: 5103/029 variants 01 to 05 are qualified (types BYW81-200) 5103/030 variant 01 is qualified (types BYV52-200) 5103/031 variant 01 to 05 are qualified (types BYV54-200) Maximum Ratings: V_{RRM} : 200 V I_O : 40 A for BYV 54-200, 30 A for BYV52-200, 15 and 30 A for BYW-81-200 T_j : + 150°C Package Types TO254, TO254AA and SMD.5 Operating Temperature Range (°C): -55 to +150 | | | | | |
|  | | DIODES, SILICON, POWER RECTIFIER, HIGH EFFICIENCY, FAST RECOVERY, BASED ON TYPES BYW81, BYV52 AND BYV54 | | Current Validity of Qualification | |
| | | Certificate 274 D | | Valid Until November 2014 | |
| | | | | Page 04-02 003-1 | |

| Types covered by similarity: Variant 03 (~ 40 V) | | Remarks: | | | |
|---|--|--|--|---|---|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| <p>Generic ESCC 5010</p> <p>Detail ESCC 5512/020</p> | | <p>INFINEON Technologies AG Neubiberg Germany</p> | <p>Qualification</p> <p>Extension</p> <p>Requalification</p> <p>Requalification</p> <p>Extension</p> | <p>DARA</p> <p>DLR</p> <p>DLR</p> <p>DLR</p> <p>DLR</p> | <p>Sep 1995</p> <p>Jan 2000</p> <p>Mar 2008</p> <p>Nov 2010</p> <p>Mar 2012</p> |
| <p>Characteristics: Variants 01 and 03 are qualified</p> <p>Maximum Ratings: BAS 70</p> <p>V_{RR}: 70 V</p> <p>I_F: 70 mA</p> <p>I_{FSM}: 85 mA_{pk} @ t<10ms, duty cycle=10%</p> <p>D.C Parameters: $I_R = 100$ nA max @ $V_R = 56$ V $V_{F1} = 0.44$ V max. @ $I_F = 1.0$ mA At room temp. $V_{BR} = 70$V min @ $I_R = 10$μA $V_{F2} = 0.78$ V max. @ $I_F = 10$ mA $V_{F3} = 1.00$ V max. @ $I_F = 15$ mA</p> <p>Package Type T1 P_{tot}=0.25W @ T_{case}= +125 °C</p> <p>Operating Temperature Range (°C): -55 to +150</p> | | | | | |
|  | | <p>DIODES,</p> <p>MICROWAVE, SILICON, SCHOTTKY, GENERAL PURPOSE,</p> <p>BASED ON TYPE BAS 70</p> | | <p>Current Validity of Qualification</p> | |
| | | | Certificate | Valid Until | Page |
| | | | 227 D | March 2014 | 04-05 |
| | | | | | 001-3 |

| | | | | | |
|---|--|--|-----------------------------------|---------------------------------|--------------------------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 5010 Detail ESCC See types covered by similarity | | RF2M Microwave Milton Keynes England | Qualification | DRA | Dec 1993 |
| | | | Extension | DERA | Oct 1997 |
| | | | Extension | QinetiQ | Mar 2002 |
| | | | Extension | QinetiQ | Feb 2006 |
| | | | Extension | BNSC | Nov 2008 |
| | | | Extension | UK Space Agency | Jan 2011 |
| | | | Extension | UK Space Agency | Mar 2013 |
| Characteristics: Operating Temperature Range (°C): -65 to +125 and 150 | | | | | |
|  | DIODES, MICROWAVE, SILICON, PIN AND VARACTORS | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 04-13 |
| | | 200 F | November 2014 | 003-1A | |

Types covered by similarity:

| ESCC Spec. No. | Component Type |
|----------------|---|
| 5513/007 | ML4207 to ML 4209, variants 01-03, 06, 08-13, 17, 19, 21-27, 30, 32-37, 41, 43, 45-51, 54, 56-61, 65, 67, 69-72 |
| 5513/009 | ML4610, ML4617 to ML4619, variants 01-03, 06, 08-13, 17, 19, 21-23, 25-28, 31, 33-38, 42, 44, 46-48, 50-53, 56, 58-63, 67, 69, 71-73, 75-78, 81, 83-88, 92, 94, 96-99 |
| 5513/010 | ML4611, ML4612, ML4614, ML4615, variants 01-03, 06, 08-13, 17, 19, 21-23, 25-28, 31, 33-38, 42, 44, 46-48, 50-53, 56, 58-63, 67, 69, 71-73, 75-78, 81, 83-88, 92, 94, 96-99 |
| 5513/014 | ML4622 to ML4624, variants 01-03, 06, 08-13, 17, 19, 21-23, 25-28, 31, 33-38, 42, 45-47, 49-52, 55, 57-58, 61, 63 |
| 5513/015 | ML4627 to ML4629, variants 01-03, 06, 08-13, 17, 19, 21-23, 25-28, 31, 33-38, 42, 45-47, 49-52, 55, 57-58, 61, 63 |
| 5512/001 | ML4402, ML4404 to ML4409 and ML40721, variants 01-03,05, 07-12, 14-18, 20, 22-27, 29-33, 35, 37-42, 44-48, 50, 52-57, 59-63, 65, 67-72, 74-78, 80, 82-84, 86, 88, 90-92 |
| 5512/003 | ML4310 to ML4319, variants 01-02, 05-06, 09-13, 16-17, 20-24, 27-28, 31-35, 38-39, 42-46, 49-50, 53-57, 60-61, 64-68, 71-72, 75-79, 83-85, 89-91, 95 |
| 5512/004 | ML4331 to ML4335, variants 01-02, 05-06, 09-13, 16-17, 20-24, 27-28, 31-35, 38-39, 42-46, 49-50, 53-55 |
| 5512/005 | ML4336 to ML4343, variants 01-02, 06-08, 12-14, 18-20, 24-26, 30-32, 36-38, 42-44, 48 |
| 5512/006 | ML4351 to ML4354, variants 01-02, 05-06, 09-13, 16-17, 20-24, 27-28, 31-35, 38-39, 42-44 |
| 5512/007 | ML4355 to ML4365, variants 01-02, 06-08, 12-14, 18-20, 24-26, 30-32, 36-38, 42-44, 47-48, 51-52, 55-56 |



DIODES,
MICROWAVE, SILICON, PIN AND VARACTORS

Current Validity of Qualification

Certificate

200 F


Valid Until

November 2014

Page

04-13

003-1B

| | | | | | |
|---|--|---|-----------------------------------|-----------------------|----------|
| Types covered by similarity: | | Remarks: Certificate 259C has been merged with this certificate beginning February 2012. | | | |
| Procurement Specifications Issues in effect on certification date | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 5010 Detail ESCC Please refer to the next page | | COBHAM MICROWAVE Les Ulis France | Qualification | CNES | Jun 1995 |
| | | | Extension | CNES | Aug 1998 |
| | | | Extension | CNES | Jun 2003 |
| | | | Extension | CNES | Mar 2007 |
| | | | Extension | CNES | Mar 2010 |
| | | | Extension | CNES | Feb 2012 |
| Characteristics: Refer to the Detail Specifications | | | | | |
| Operating Temperature Range (°C): -55 to +125 | | | | | |
|  ESCC <small>European Space Components Coordination</small> QPL | DIODES, MICROWAVE, SILICON, MULTIPLIER AND PIN, BASED ON TYPES DH 2XX AND DH 50XXX | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 04-13 |
| | | 225 E | February 2014 | 003-2A | |

Types covered by similarity:

| ESCC Spec. No. | Component Type |
|----------------|---|
| 5513/031 | DH 50151 to DH 50157, Variants 01 to 56 |
| 5513/032 | DH 50033 to DH 50037, Variants 01 to 40 |
| 5513/033 | DH 50201 to DH 50209, Variants 01 to 70 |
| 5513/034 | DH 50251 to DH 50256, Variants 01 to 41 |
| 5513/036 | DH 50052 to DH 50057, Variants 01 to 48 |
| 5513/037 | DH 50071 to DH 50077, Variants 01 to 56 |
| 5513/038 | DH 50101 to DH 50107, Variants 01 to 56 |
| 5512/016 | DH 267, Variants 10 to 15 and 16 |
| 5512/016 | DH 292, Variants 20 to 25 and 26 |
| 5512/016 | DH 256, Variants 30 to 35 and 36 |
| 5512/016 | DH 252, Variants 40 to 45 and 46 |
| 5512/016 | DH 294, Variants 50 to 55 and 56 |




DIODES,
 MICROWAVE, SILICON, MULTIPLIER AND PIN,
 BASED ON TYPES DH 2XX AND DH 50XXX


Current Validity of Qualification


Certificate
 225 E

Valid Until
 February 2014

Page
 04-13
 003-2B


| Types covered by similarity: . | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---------------------|---|--------------------|-----------------------|-----------------------------------|-------------|---------------------|---------------|----------|--------|----------|----------|---------|----------|----------|---------|----------|----------|---------|----------|----------|---------|----------|----------|---------|----------|----------|----------|----------|----------|----------|----------|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5010 | | COBHAM MICROWAVE Les Ulis France | Qualification | CNES | Jun 2003 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Detail ESCC 5512/023 | | | Extension | CNES | Mar 2007 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | Extension | CNES | Jun 2009 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | Extension | CNES | Feb 2012 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Characteristics: All variants are qualified.</p> <p>Maximum Ratings: $V_R = 20$ at $I_R = 10 \mu A$ and $T_{amb} = +25 \text{ }^\circ C$</p> <p>Operating Temperature Range ($^\circ C$): -55 to +155</p> <table border="1"> <thead> <tr> <th>Variants</th> <th>C_j(typ.) (-4 V)</th> <th>Based on Type</th> </tr> </thead> <tbody> <tr><td>01 to 09</td><td>1.0 pF</td><td>DH 76010</td></tr> <tr><td>10 to 18</td><td>1.50 pF</td><td>DH 76015</td></tr> <tr><td>19 to 27</td><td>2.20 pF</td><td>DH 76022</td></tr> <tr><td>28 to 36</td><td>2.30 pF</td><td>DH 76033</td></tr> <tr><td>37 to 45</td><td>4.70 pF</td><td>DH 76047</td></tr> <tr><td>46 to 54</td><td>6.80 pF</td><td>DH 76068</td></tr> <tr><td>55 to 63</td><td>10.00 pF</td><td>DH 76100</td></tr> <tr><td>64 to 72</td><td>15.00 pF</td><td>DH 76150</td></tr> </tbody> </table> | | | | | | Variants | C_j (typ.) (-4 V) | Based on Type | 01 to 09 | 1.0 pF | DH 76010 | 10 to 18 | 1.50 pF | DH 76015 | 19 to 27 | 2.20 pF | DH 76022 | 28 to 36 | 2.30 pF | DH 76033 | 37 to 45 | 4.70 pF | DH 76047 | 46 to 54 | 6.80 pF | DH 76068 | 55 to 63 | 10.00 pF | DH 76100 | 64 to 72 | 15.00 pF | DH 76150 |
| Variants | C_j (typ.) (-4 V) | Based on Type | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 01 to 09 | 1.0 pF | DH 76010 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10 to 18 | 1.50 pF | DH 76015 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 19 to 27 | 2.20 pF | DH 76022 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 28 to 36 | 2.30 pF | DH 76033 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 37 to 45 | 4.70 pF | DH 76047 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 46 to 54 | 6.80 pF | DH 76068 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 55 to 63 | 10.00 pF | DH 76100 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 64 to 72 | 15.00 pF | DH 76150 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | DIODES, MICROWAVE, SILICON, HYPER-ABRUPT JUNCTION TUNING VARACTOR BASED ON TYPES DH 76xxx | | | Current Validity of Qualification | Page | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | Certificate | Valid Until | 04-13 | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | 273 C | June 2013 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | 003-3 | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | | | | |
|---|-------|---|--|---|--|-------|
| Types covered by similarity: Variant 02 | | Remarks: | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | |
| Generic ESCC 5010 Detail ESCC 5513/017 | | INFINEON Technologies AG Neubiberg Germany | Qualification Extension Extension Requalification Requalification Extension | DARA DLR DLR DLR DLR DLR | Jun 1995 Jan 2000 Jan 2004 Mar 2008 Nov 2010 Mar 2012 | |
| Characteristics: Variants 01 and 02 are qualified Maximum Ratings: V_R : 50 V I_{FM} : 5.0 A @ $t_p=1.0 \mu s$, duty cycle = 0.001% D.C Parameters: $I_{R1} = 10 \mu A$ max @ $V_R = 50 V$ $I_{R2} = 5 nA$ max @ $V_R = 40 V$ $V_F = 1.1 V$ max. @ $I_F = 100 mA$ Package Types T1 ($P_D= 350mW$) and T Operating Temperature Range ($^{\circ}C$): -55 to $+175$ | | | | | | |
|  | | DIODES, MICROWAVE, SILICON, PIN, BASED ON TYPE BXY 42- MESA | | Current Validity of Qualification | | Page |
| | | | | Certificate | Valid Until | 04-16 |
| | 224 E | March 2014 | 002-2 | | | |

| | | | | | | |
|--|--|--|--------------------|-----------------------------------|-------------|-------|
| Types covered by similarity: | | Remarks: | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | |
| Generic ESCC 5010 Detail ESCC 5513/030 | | INFINEON Technologies AG Neubiberg Germany | Qualification | DARA | Oct 1996 | |
| | | | Extension | DLR | Jan 2000 | |
| | | | Extension | DLR | Jan 2004 | |
| | | | Requalification | DLR | Mar 2008 | |
| | | | Requalification | DLR | Nov 2010 | |
| | | | Extension | DLR | Mar 2012 | |
| Characteristics: Variants 01, 02, 05 and 06 are qualified. BXY 43 (variants 01-02) BXY 44 (variants 05-06) Maximum Ratings: $V_R = \overset{-}{\sim} 150 \text{ V}$ $\overset{-}{\sim} 200 \text{ V}$ $I_F = 400 \text{ mA}$ $P_D = 500 \text{ mW}$ D.C Parameters: $I_R = 100 \text{ nA max @ } V_R = \overset{-}{\sim} 150 \text{ V}$ $5 \text{ nA @ } V_R = \overset{-}{\sim} 100 \text{ V}$ $V_F = 1.0 \text{ V max.}$ $1.05 \text{ V max. @ } I_F = 100 \text{ mA}$ Package Type T, T1 Operating Temperature Range (°C): $\overset{-}{\sim} 55 \text{ to } \overset{+}{\sim} 150$ | | | | | | |
|  | | DIODES, MICROWAVE, SILICON, PIN, PLANAR BASED ON TYPES BXY 43 AND 44 | | Current Validity of Qualification | | Page |
| | | | | Certificate | Valid Until | 04-16 |
| | | | | 236 E | March 2014 | 003 |

Section 05**Component Type: Filters**

| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|---------------|-------|---------------------|--------------|
| 05 | | | Feedthrough | |
| | 05-01-001-A-B | 252 F | Types SFC, SFL, SFP | Eurofarad |

| | | | | | |
|---|---|---|--------------------|-----------------------|----------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3008 Detail ESCC Please refer to the next page | | EUROFARAD Chanteloup en Brie France | Qualification | CNES | Aug 1998 |
| | | | Extension | CNES | Apr 2001 |
| | | | Extension | CNES | Nov 2003 |
| | | | Extension | CNES | Mar 2006 |
| | | | Extension | CNES | Jun 2008 |
| | | | Extension | CNES | Apr 2011 |
| Characteristics: All variants specified in the Detail Specifications are qualified. Operating Temperature Range (°C): -55 to +125 | | | Extension | CNES | Aug 2012 |
|  | CAPACITOR FILTERS, PI-, C-, AND L- TYPES, FEEDTHROUGH, ELECTROMAGNETIC INTERFERENCE SUPPRESSION, HERMETICALLY AND NON-HERMETICALLY SEALED, BASED ON TYPES SFC, SFL AND SFP | Current Validity of Qualification | | Page | |
| | | Certificate | Valid Until | 05-01 | |
| | | 252 F | June 2014 | 001A | |

Types covered by certificate:

| Domain | Style | Detail Specification | Variants | Capacitance Range (nF) | Rated Current (A) | Rated Voltage (V) |
|--------------------------------|----------|----------------------|----------|------------------------|-------------------|-------------------|
| SFC, Hermetic, Glass Fill | SFC 060 | 3008/026 | 01 to 06 | 0.68 to 220 | 10 | 25 to 200 |
| | SFC 100 | 3008/027 | 01 to 06 | 1.0 to 1000 | 10 | 25 to 200 |
| SFP, Hermetic, Glass Fill | SFP 060 | 3008/021 | 01 to 14 | 2.4 to 89.6 | 10 | 35 to 500 |
| | SFP 100 | 3008/028 | 01 to 06 | 0.16 to 1 312.0 | 10 | 50 to 300 |
| SFL, Hermetic, Glass Fill | SFL 100 | 3008/029 | 01 to 48 | 17.6 to 1 600 | 5, 10, 15 | 40 to 300 |
| Capacitance Range (pF) | | | | | | |
| SFC, Non-Hermetic, Resin Fill | SFC 035 | 3008/031 | 01 to 06 | 470 to 22 000 | 10 | 25 to 200 |
| | SFC 040 | 3008/032 | 01 to 12 | 470 to 22 000 | 10 | 25 to 200 |
| | SFC 060 | 3008/033 | 01 to 12 | 680 to 220 000 | 10 | 25 to 200 |
| SFP, Non-Hermetic, Resin Fill | SFP 035 | 3008/025 | 01 to 20 | 2 400 to 35 200 | 10 | 35 to 200 |
| | SFP 040 | 3008/014 | 01 to 40 | 750 to 4 800 | 10 (DC 7 LF) | 70 to 250 |
| | SFP 060 | 3008/030 | 01 to 28 | 2 400 to 89 600 | 10 | 35 to 500 |
| Capacitance Range (pF) | | | | | | |
| SFC, Mixed fill, for soldering | SFC 030V | 3008/020 | 01 to 12 | 470 to 22 000 | 1.0 to 5.0 | 25 to 200 |



CAPACITOR FILTERS, PI-, C-, AND L- TYPES, FEEDTHROUGH,
ELECTROMAGNETIC INTERFERENCE SUPPRESSION,
HERMETICALLY AND NON-HERMETICALLY SEALED,

Current Validity of Qualification

Certificate

252 F

Valid Until

June 2014

Page


05-01

001B

Section 06**Component Type: Fuses**

| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|-----------|-------|------------------|--------------|
| 06-01 | | | Thin film | |
| | 06-01-001 | 284 B | Type MGA-S | Schurter |


**SECTION 06-**: INDEX OF FUSES****REP005 Updated on 15 Jun 2013**


| | | | | |
|---|---|---|---|--|
| Types covered by similarity: Variants 02 to 09 | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 4008 Detail ESCC 4008/001 | Schurter Lucerne Switzerland | Qualification Extension Extension | ESTEC ESTEC ESTEC | Jun 2008 Oct 2010 Sep 2012 |
| <p>Characteristics: Variants 01 to 12 are qualified.</p> <p>Rated Voltage (VAC or VDC): 125/125, 63/125 and 32/125 by variant</p> <p>Rated Current (VAC and VDC): 0.14 to 3.5 A by variant</p> <p>AC Interrupt Current (A): 50 at maximum rated voltage, power factor > 0.95</p> <p>DC Interrupt Current (A): at maximum rated voltage, time constant ≤ 1 ms</p> <p>Variants 01 to 10: 300, Variants 11 and 12: 50</p> <p>Operating Temperature Range, (°C): -50 to +125 (90% I_R to 107% I_R)</p> | | | | |
|  | <p>FUSES, SURFACE MOUNT, THIN FILM, 0.14 TO 3.5 AMPS, BASED ON TYPE MGA-S</p> | Current Validity of Qualification | | Page |
| | | Certificate 284 B | Valid Until June 2014 | 06-01 001 |

Section 07**Component Type: Inductors**

| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|-----------|-------|----------------------------------|--------------|
| 07-01 | | | Fixed, RF | |
| | 07-01-001 | 241 F | Types MSC1 10K, 12K, 20K and H01 | Microspire |
| 07-02 | | | Power | |
| | 07-02-002 | 276 C | Types SESI and CMC | Microspire |


**SECTION 07-**: INDEX OF INDUCTORS****REP005 Updated on 15 Jun 2013**

| | | | | | | | | | | |
|---|--------------|----------------|---|---------------------------------|-------------------------------|---------------------------------------|-----------------------------------|-----------------------|-------------|-------|
| Types covered by similarity: | | | | | | Remarks: | | | | |
| Procurement Specifications | | | | Manufacturer | | Nature of Approval | | Supervising Authority | Date | |
| Generic ESCC 3201 | | | | MICROSPIRE Illange France | | Qualification | | CNES | Apr 1997 | |
| Detail ESCC 3201/008 | | | | | | Extension | | CNES | Nov 2000 | |
| | | | | | | Extension | | CNES | Mar 2003 | |
| | | | | | | Extension | | CNES | Dec 2005 | |
| | | | | | | Extension | | CNES | Jun 2008 | |
| | | | | | | Extension | | CNES | Jan 2011 | |
| Characteristics: Variants 01 to 05 are qualified | | | | | | Extension | | CNES | Oct 2012 | |
| Series No. | Range (μH) | Tolerance (±%) | Q min. | Min. SRF f _r (MHz) | Max. DCR, R _{dc} (Ω) | Rated DC Current, I _R (mA) | | | | |
| 10k | 0.010-10 | 2.0, 5.0, 10 | 60 - 42 | 1000 - 33 | 0.025 - 3.3 | 750 - 87 | | | | |
| 12k | 12 - 1000 | 2.0, 5.0, 10 | 56 - 12 | 26 - 1.5 | 2.0 - 120 | 110 - 15 | | | | |
| 20k | 0.010 - 1000 | 10 | 75 - 30 | 1000 - 1.7 | 0.04 - 80 | 1000 - 25 | | | | |
| H01 | 0.380 - 100 | 15 | 30 | 8 | 0.029 - 3.8 | 1500 - 100 | | | | |
| Dielectric Withstanding Voltage (DWV): 200 Vrms | | | | | | | | | | |
| Operating Temperature Range (°C): -55 to +125 | | | | | | | | | | |
|  | | | INDUCTORS, FIXED, RF, MINIATURE, MOULDED, SURFACE MOUNT, BASED ON SERIES MSC1 10k, 12k, 20k and H01 | | | | Current Validity of Qualification | | | Page |
| | | | | | | | Certificate | | Valid Until | 07-01 |
| 241 F | | June 2014 | 001 | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|----|--|-----|--|-----------------------------------|--|-------|------|----|-----|----|-----|----|------|------|---------|----|----|----|----|----|----|----|----|-----|----|----|----|---------|----|----|----|
| Types covered by similarity: | | | | Remarks: Termination finish shall be Sn90Pb10. | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 3201 Detail ESCC 3201/009 3201/010 | | MICROSPIRE Illange France | | Qualification Extension Extension Extension | CNES CNES CNES CNES | Apr 2004 May 2007 Dec 2010 Feb 2012 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics: 3201/009 Variants 01 to 08 are qualified 3201/010 Variants 01, 03 and 05 are qualified 3201/009 <table border="0"> <tr> <td>SESI</td> <td>14</td> <td>15</td> <td>15W</td> <td>18</td> <td>9.1</td> <td>22</td> <td>32WR</td> <td>32PR</td> </tr> <tr> <td>Variant</td> <td>01</td> <td>02</td> <td>03</td> <td>04</td> <td>05</td> <td>06</td> <td>07</td> <td>08</td> </tr> </table> 3201/010 <table border="0"> <tr> <td>CMC</td> <td>15</td> <td>18</td> <td>22</td> </tr> <tr> <td>Variant</td> <td>01</td> <td>02</td> <td>03</td> </tr> </table> Operating Temperature Range (°C): -55 to +125 | | | | | | | SESI | 14 | 15 | 15W | 18 | 9.1 | 22 | 32WR | 32PR | Variant | 01 | 02 | 03 | 04 | 05 | 06 | 07 | 08 | CMC | 15 | 18 | 22 | Variant | 01 | 02 | 03 |
| SESI | 14 | 15 | 15W | 18 | 9.1 | 22 | 32WR | 32PR | | | | | | | | | | | | | | | | | | | | | | | | |
| Variant | 01 | 02 | 03 | 04 | 05 | 06 | 07 | 08 | | | | | | | | | | | | | | | | | | | | | | | | |
| CMC | 15 | 18 | 22 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Variant | 01 | 02 | 03 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  QPL | | INDUCTORS, POWER, MOULDED, SURFACE MOUNT, BASED ON SERIES SESI AND CMC | | | Current Validity of Qualification | | Page | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | Certificate | Valid Until | 07-02 | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | 276 C | May 2013 | 002 | | | | | | | | | | | | | | | | | | | | | | | | | |

Section 08**Component Type: Microcircuits**

| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|-----------------------|-------|---------------------------|--------------------------------|
| 08-80 | | | Digital C-MOS | |
| | 08-80-001-2 A to E | 73 N | 4000 B Series | ST Microelectronics |
| | 08-80-002-2 A to F | 190 J | 54HCMOS Series | ST Microelectronics |
| 08-90 | | | Other Functions | |
| | 08-90-001 | 307 | PLL Frequency Synthesizer | Peregrine Semiconductor Europe |

| Types covered by similarity: See next pages | | Remarks: ST has announced a customer last time buy ending 15 June 2013 affecting devices listed herein marked with an (*). | | | |
|---|--|--|--------------------|-----------------------|----------|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 9000 Detail ESCC See types covered by similarity | | ST Microelectronics Rennes France | Qualification | CNES | Apr 1981 |
| | | | Extension | CNES | Jan 1981 |
| | | | Extension | CNES | Dec 1984 |
| | | | Extension | CNES | May 1987 |
| | | | Extension | CNES | Apr 1990 |
| | | | Extension | CNES | Oct 1992 |
| | | | Extension | CNES | Apr 1995 |
| | | | Extension | CNES | Apr 1997 |
| | | | Extension | CNES | Apr 1999 |
| | | | Extension | CNES | May 2001 |
| | | Extension | CNES | Nov 2002 | |
| | | Extension | CNES | Nov 2005 | |
| | | Extension | CNES | Feb 2008 | |
| | | Extension | CNES | May 2010 | |
| | | Extension | CNES | Feb 2012 | |
| Characteristics: Package Types: Ceramic Dual-in-Line Ceramic Flat Pack | | | | | |
|  | MICROCIRCUITS, DIGITAL, C-MOS-B, 4000B SERIES | Current Validity of Qualification | | Page | |
| | | Certificate | Valid Until | 08-80 | |
| | | 73 N | February 2014 | 001-2A | |

Types covered by similarity:

| ESCC Spec. No. | Component Type | Component Type |
|----------------|---|----------------|
| 9201/041 | Quad 2-input NOR gate | 4001B |
| 9201/042 | Dual 4-input NOR gate | 4002B |
| 9202/039 | 4-bit full adder | 4008B |
| 9201/043 | Quad 2-input NAND gate | 4011B |
| 9201/044 | Dual 4-input NAND gate | 4012B |
| 9203/023 | Dual D-type flip-flop | 4013B |
| 9306/014 | 8-stage synchronous static shift register | 4014B |
| 9306/015 | Dual 4-stage static shift register with serial input/parallel input | 4015B |
| 9202/050 | Quad bilateral switch | 4016B (*) |
| 9204/020 | Decade counter/divider | 4017B |
| 9204/021 | Presettable divide-by-N counter | 4018B |
| 9202/051 | Quad AND/OR select gate | 4019B |
| 9204/022 | 14-stage ripple carry binary counter/divider | 4020B |
| 9306/016 | 8-stage static shift register | 4021B |
| 9204/023 | Octal counter/divider | 4022B |
| 9201/045 | Triple 3-input NAND gates | 4023B |
| 9204/024 | 7-stage ripple carry binary counter/divider | 4024B |
| 9201/046 | Triple 3-input NOR gate | 4025B |
| 9406/001 | Ripple carry decade counter/divider | 4026B (*) |
| 9203/022 | Dual J-K master slave flip-flop | 4027B |



MICROCIRCUITS, DIGITAL,
C-MOS-B, 4000B SERIES

Current Validity of Qualification

Certificate

73 N

Valid Until

February 2014

Page

08-80

001-2B

Types covered by similarity:

| ESCC Spec. No. | Component Type | Component Type |
|----------------|--|----------------|
| 9205/010 | BCD-to-decimal or binary-to-octal decoder | 4028B |
| 9204/025 | Presetable up/down counter binary or BCD decade | 4029B |
| 9201/047 | Quad 2-input exclusive OR gates | 4030B |
| 9306/017 | 64-stage static shift register | 4031B (*) |
| 9306/025 | 8-stage static bidirectional parallel/serial input/output bus register with 3 state output | 4034B |
| 9306/018 | 4-bit universal shift register | 4035B (*) |
| 9204/026 | 12-stage ripple carry binary counter/divider | 4040B |
| 9202/040 | Quad true/complement buffer with unbuffered outputs | 4041UB |
| 9202/041 | Quad clocked D latch | 4042B |
| 9202/042 | Quad NOR 3-state R/S latches | 4043B |
| 9202/043 | Quad NAND 3-state R/S latch | 4044B |
| 9202/044 | Micropower phase-locked loop | 4046B |
| 9207/003 | Low power monostable/astable multivibrator | 4047B |
| 9202/045 | Hex buffer/converter (inverting type) | 4049UB |
| 9202/046 | Hex buffer/converter (non-inverting type) | 4050B |
| 9202/047 | Analogue multiplexer/demultiplexer | 4051B |
| 9202/048 | Analogue multiplexer/demultiplexer | 4052B |
| 9202/049 | Triple 2-channel analogue multiplexer/demultiplexer | 4053B |
| 9209/001 | 4-bit magnitude comparator | 4063B |
| 9204/052 | 14-stage ripple-carry binary counter/divider and oscillator | 4060B |



MICROCIRCUITS, DIGITAL,
C-MOS-B, 4000B SERIES

Current Validity of Qualification

Certificate

73 N

Valid Until

February 2014

Page

08-80

001-2C

| Types covered by similarity: | | |
|------------------------------|--|----------------|
| ESCC Spec. No. | Component Type | Component Type |
| 9408/005 | Quad bilateral switch | 4066B |
| 9408/009 | Analogue multiplexer/demultiplexer | 4067B |
| 9201/061 | 8-input NAND gate | 4068B |
| 9401/010 | Hex inverter | 4069UB |
| 9201/048 | Quad exclusive OR gate | 4070B |
| 9201/063 | Quad 2-input OR gate | 4071B |
| 9201/082 | Dual 4-input OR gate | 4072B |
| 9201/064 | Triple 3-input AND gate | 4073B |
| 9201/065 | Triple 3-input OR gate | 4075B |
| 9306/022 | 4-bit D-type register with 3-state output | 4076B |
| 9201/055 | Quad exclusive NOR gate | 4077B |
| 9201/062 | 8-input OR/NOR gate | 4078B |
| 9201/052 | Quad 2-input AND gate | 4081B |
| 9201/066 | Dual 4-input AND gate | 4082B |
| 9201/067 | Dual 2-wide 2-input AND/OR inverter gate | 4085B (*) |
| 9409/002 | Quad 2-input NAND gate with Schmitt trigger input | 4093B |
| 9306/026 | 8-stage shift and store bus register with synchronous serial outputs and 3-state parallel output | 4094B |
| 9206/003 | Dual monostable multivibrator | 4098B |
| 9202/058 | 8-bit addressable latch | 4099B (*) |
| 9401/006 | Strobed hex inverter/buffer | 4502B (*) |



MICROCIRCUITS, DIGITAL,
C-MOS-B, 4000B SERIES

Current Validity of Qualification

Certificate

73 N

Valid Until

February 2014

Page

08-80

001-2D

Types covered by similarity:

| ESCC Spec. No. | Component Type | Component Type |
|----------------|--|----------------|
| 9401/030 | Hex non-inverting buffers with 3-state output | 4503B |
| 9202/063 | Dual 4-bit latch with 3-state output | 4508B (*) |
| 9408/006 | 8-channel multiplexer with 3-state output | 4512B |
| 9408/012 | 4-bit latch/4-to-16 decoder | 4514B |
| 9205/011 | 4-bit latch/4-to-16 line decoder | 4515B |
| 9204/045 | Synchronous quad presettable up/down binary counter | 4516B |
| 9204/028 | Dual binary up counter | 4520B |
| 9202/065 | 8-bit priority encoder | 4532B |
| 9207/007 | Dual monostable multivibrator with reset | 4538B |
| 9408/011 | Dual 1-of-4 decoder/demultiplexer | 4555B |
| 9408/025 | Dual 1-of-4 decoder/demultiplexer (output low on select) | 4556B |
| 9204/036 | Presettable 8-bit synchronous down-counter | 40103B |
| 9306/033 | FIFO register with 3-state output | 40105B (*) |
| 9409/005 | Hex Schmitt-trigger | 40106B |
| 9401/013 | Dual 2-input NAND buffer/driffer | 40107B |
| 9407/003 | Quad low-to-high 3-state voltage level shifter | 40109B |
| 9204/054 | Programmable 4-bit binary counter with asynchronous clear | 40161B |
| 9204/046 | Programmable 4-bit binary counter with synchronous clear | 40163B (*) |
| 9203/038 | Hex D-type flip-flop | 40174B |
| 9204/041 | Presettable binary up/down counter (dual clock with reset) | 40193B |
| 9408/017 | Quad 2-lin-to-1-line data selector/multiplexer with 3-state output | 40257B (*) |



MICROCIRCUITS, DIGITAL,
C-MOS-B, 4000B SERIES

Current Validity of Qualification

Certificate

73 N


Valid Until


February 2014

Page

08-80

001-2E

| Types covered by similarity: See next pages | | Remarks: ST has announced a customer last time buy ending 15 June 2013 affecting devices listed herein marked with an (*). | | | |
|--|---|--|--------------------|-----------------------|----------|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 9000 Detail ESCC See types covered by similarity | | ST Microelectronics Rennes France | Qualification | CNES | Nov 1992 |
| | | | Extension | CNES | Apr 1995 |
| | | | Extension | CNES | Apr 1997 |
| | | | Extension | CNES | Apr 1999 |
| | | | Extension | CNES | May 2001 |
| | | | Extension | CNES | Nov 2002 |
| | | | Extension | CNES | Nov 2005 |
| | | | Extension | CNES | Feb 2008 |
| | | | Extension | CNES | May 2010 |
| | | | Extension | CNES | Feb 2012 |
| Characteristics: Qualified Packages: <ul style="list-style-type: none"> Ceramic Dual-in-Line Ceramic Flat Pack NOTES 1. These parts have successfully passed radiation testing to 50 kRads. | | | | | |
|  | MICROCIRCUITS, DIGITAL, MONOLITHIC, HIGH SPEED CMOS, 54HC AND 54HCT SERIES | Current Validity of Qualification | | Page | |
| | | Certificate | Valid Until | 08-80 | |
| | | 190 J | February 2014 | 002-2A | |

| Types covered by similarity: | | | | |
|---|---|-----------------------------------|----------------------------------|---------------------|
| ESCC Spec. No. | Component Type | Component Type | Note | |
| 9201/105 | Quad 2-input NAND gate | 54HC 00 | 1 | |
| 9201/113 | Quad 2-input NOR gate | 02 | 1 | |
| 9201/114 | Quad 2-input NAND gate with open drain output | 03 | 1 | |
| 9401/033 | Hex inverter | 04 | 1 | |
| 9201/106 | Quad 2-input positive AND gate | 08 | 1 | |
| 9201/107 | Triple 3-input NAND gate | 10 | 1 | |
| 9201/117 | Triple 3-input AND gate | 11 | 1 | |
| 9409/007 | Hex Schmitt trigger inverter | 14 | 1 | |
| 9201/118 | Dual 4-input NAND gate | 20 | 1 | |
| 9201/108 | Dual 4-input AND gate | 21 | 1 | |
| 9201/109 | Triple 3-input NOR gate | 27 | 1 | |
| 9201/110 | 8-input NAND gate | 30 | 1 | |
| 9201/111 | Quad 2-input OR gate | 32 | 1 | |
| 9203/071 | Dual negative-edge triggered J-K flip-flops with clear | 73 (*) | 1 | |
| 9203/050 | Dual D-type flip-flop with preset and clear | 74 | 1 | |
| 9203/065 | Quad 4-bit bistable D-type latch | 75 (*) | 1 | |
| 9209/004 | 4-bit magnitude comparator | 85 | 1 | |
| 9201/119 | Quad 2-input exclusive OR gate | 86 | 1 | |
| 9203/072 | Dual J-K negative-edge triggered flip-flop with direct clear | 107 (*) | 1 | |
| | | | | |
|  | <p style="text-align: center;">MICROCIRCUITS, DIGITAL, MONOLITHIC, HIGH SPEED CMOS, 54HC AND 54HCT SERIES</p> | Current Validity of Qualification | | Page |
| | | Certificate 190 J | Valid Until February 2014 | 08-80 002-2B |

Types covered by similarity:

| ESCC Spec. No. | Component Type | Component Type | Note |
|----------------|--|----------------|------|
| 9306/048 | Dual J-K positive edge triggered flip-flop with preset and clear | 54HC 109 | 1 |
| 9203/051 | Dual J-K negative edge triggered flip-flop with preset and clear | 112 (*) | 1 |
| 9207/006 | Dual positive or negative edge Schmitt-retriggerable monostable multivibrator with clear | 123 | 1 |
| 9401/039 | Quad bus buffer with 3 state output | 125 | 1 |
| 9401/046 | Quad bus buffer with 3 state output | 126 (*) | 1 |
| 9201/120 | Quad 2-input NAND gate with Schmitt-trigger input | 132 | 1 |
| 9205/013 | 3-to-8 line decoder/demultiplexer with address latch and inverted output | 137 | 1 |
| 9408/046 | 3-to-8 line decoder/demultiplexer with inverted output | 138 | 1 |
| 9205/017 | Dual 2-to-4 line decoder/demultiplexer with inverted output | 139 | 1 |
| 9410/017 | 8-line to 3-line priority encoder | 148 | 1 |
| 9408/054 | 8-line to 1-line data selector/multiplexer | 151 | 1 |
| 9408/038 | Dual 4-line to 1-line data selectors/multiplexer | 153 | 1 |
| 9205/023 | 4-to-16 line decoder/demultiplexer with inverted output | 154 | 1 |
| 9408/057 | Quad 2-line to 1-line data selector/multiplexer | 157 | 1 |
| 9408/059 | Quad 2-line to 1-line data selector/multiplexer with inverted output | 158 | 1 |
| 9204/062 | Synchronous presettable 4-bit decade counter with direct clear | 160 | 1 |
| 9204/059 | Asynchronous 4-bit binary counter | 161 | 1 |
| 9204/073 | Synchronous 4-bit binary counter | 163 (*) | 1 |
| 9306/041 | 8-bit SIPO shift register | 164 | 1 |
| 9306/042 | 8-bit PISO shift register | 165 | 1 |



MICROCIRCUITS, DIGITAL, MONOLITHIC,
HIGH SPEED CMOS, 54HC AND 54HCT SERIES

Current Validity of Qualification

Certificate

190 J

Valid Until

February 2014

Page

08-80

002-2C

Types covered by similarity:

| ESCC Spec. No. | Component Type | Component Type | Note |
|----------------|---|----------------|------|
| 9306/043 | 8-bit PISO shift register | 54HC 166 | 1 |
| 9306/052 | Hex D-type edge-triggered flip-flop with clear | 174 | 1 |
| 9203/052 | Quad D-type edge-triggered flip-flop with clear | 175 | 1 |
| 9204/066 | Synchronous 4-bit up/down binary counter | 191 | 1 |
| 9204/065 | Synchronous 4-bit up/down binary counter (dual clock with clear) | 193 | 1 |
| 9306/047 | 4-bit PIPO shift register | 194 | 1 |
| 9306/053 | 4-bit PIPO shift register with overriding clear | 195 (*) | 1 |
| 9205/021 | 3-line to 8-line decoder/demultiplexer with address latch | 237 | 1 |
| 9401/034 | Octal bus buffer with inverted 3-state output | 240 | 1 |
| 9401/035 | Octal bus buffer with 3-state output | 241 (*) | 1 |
| 9405/011 | Quad bus transceiver with inverted 3-state output | 242 (*) | 1 |
| 9405/012 | Quad bus transceiver with 3-state output | 243 (*) | 1 |
| 9401/048 | Octal bus buffer with 3-state output | 244 | 1 |
| 9405/013 | Octal bus transceiver with 3-state output | 245 | 1 |
| 9408/048 | 1-to-8 data selector/multiplexer with 3-state output | 251 | 1 |
| 9408/058 | Dual 4-line to 1-line data selector/multiplexer with 3-state output | 253 (*) | 1 |
| 9408/047 | Quad 2-line to 1-line data selector/multiplexer with 3-state output | 257 | 1 |
| 9203/073 | 8-bit addressable latch | 259 | 1 |
| 9203/053 | Octal D-type edge-triggered flip-flop with clear | 273 | 1 |
| 9208/003 | 9-bit odd/even parity generator/checker | 280 | 1 |



MICROCIRCUITS, DIGITAL, MONOLITHIC,
HIGH SPEED CMOS, 54HC AND 54HCT SERIES

Current Validity of Qualification

Certificate

190 J

Valid Until

February 2014

Page

08-80

002-2D

Types covered by similarity:

| ESCC Spec. No. | Component Type | Component Type | Note |
|----------------|--|----------------|------|
| 9202/075 | 4-bit binary full adder with fast carry | 54HC 283 | 1 |
| 9401/052 | Hex bus buffer with 3-state output | 365 (*) | 1 |
| 9401/044 | Hex bus buffer with 3-state output | 367 | 1 |
| 9203/059 | Octal D-type transparent latch with 3-state output | 373 | 1 |
| 9203/060 | Octal D-type edge-triggered flip-flop with 3-state output | 374 | 1 |
| 9201/121 | Quad 2-input exclusive OR gate | 386 (*) | 1 |
| 9204/074 | Dual 4-bit negative edge-triggered binary counter | 393 | 1 |
| 9401/049 | Octal bus buffer with inverted 3-state output | 540 | 1 |
| 9401/047 | Octal bus buffer with 3-state output | 541 | 1 |
| 9202/072 | Octal D-type transparent latch with 3-state output | 573 | 1 |
| 9203/054 | Octal D-type edge-triggered flip-flop with 3-state output | 574 | 1 |
| 9204/071 | 8-bit binary counter with 3-state output register | 590 | 1 |
| 9306/051 | 8-bit shift register with 3-state output register | 595 | 1 |
| 9306/054 | 8-bit PISO shift register | 597 | 1 |
| 9209/005 | 8-bit identify comparator | 688 | 1 |
| 9201/130 | Dual 4-input NOR gate | 4002 (*) | 1 |
| 9204/070 | Asynchronous negative-edge-triggered 14-bit binary counter | 4020 | 1 |
| 9204/069 | Asynchronous negative edge-triggered 12-bit binary counter | 4040 | 1 |
| 9401/037 | Hex buffer/converter with inverted output | 4049 | 1 |
| 9401/038 | Hex buffer/converter | 4050 | 1 |



MICROCIRCUITS, DIGITAL, MONOLITHIC,
HIGH SPEED CMOS, 54HC AND 54HCT SERIES

Current Validity of Qualification

Certificate

190 J

Valid Until

February 2014

Page

08-80

002-2E

Types covered by similarity:

| ESCC Spec. No. | Component Type | Component Type | Note |
|----------------|---|----------------|------|
| 9408/064 | Analogue multiplexer/demultiplexer | 54HC 4051 | 1 |
| 9408/065 | Analogue multiplexer/demultiplexer (triple 2-channel) | 4053 | 1 |
| 9204/076 | Asynchronous negative-edge-triggered 14-bit binary counter and oscillator | 4060 | 1 |
| 9408/052 | Quad bilateral switch | 4066 | 1 |
| 9201/124 | Dual 4-input OR gate | 4072 (*) | 1 |
| 9201/129 | Triple 3-input OR gate | 4075 (*) | 1 |
| 9201/123 | 8-input OR/NOR gate | 4078 | 1 |
| 9306/050 | 8-bit SIPO shift latch register with 3-state output | 4094 | 1 |
| 9205/019 | 4-to-16 line decoder/latch | 4514 | 1 |
| 9203/070 | Dual D-type flip-flop with preset and clear | 54HCT 74 | 1 |
| 9401/045 | Octal buffer with inverted 3-state output | 240 (*) | 1 |
| 9402/009 | Octal bus buffer with 3-state output | 244 | 1 |
| 9405/014 | Octal bus transceiver with 3-state output | 245 | 1 |
| 9203/064 | Octal D-type transparent latch with 3-state output | 373 | 1 |
| 9203/066 | Octal D-type edge-triggered flip-flop with 3-state output | 374 (*) | 1 |
| | | | |



MICROCIRCUITS, DIGITAL, MONOLITHIC,
HIGH SPEED CMOS, 54HC AND 54HCT SERIES

Current Validity of Qualification

Certificate

190 J


Valid Until

February 2014

Page

08-80

002-2F

| | | | | | | | |
|--|--|--|--|--------------------|-----------------------------------|-------------|-------|
| Types covered by similarity: . | | Remarks: Extension of qualification testing is underway. | | | | | |
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Date | |
| Generic ESCC 9000 Detail ESCC 9202/077 | | Peregrine Semiconductor Berkshire England | | Qualification | ESTEC | Mar 2011 | |
| Characteristics: Variant 01 is qualified V_{DD} (V)= 2.85 to 3.45 RF input up to 3.5 GHz, 3 wire serial interface 18-bit delta-sigma modulator, divide by 10/11 dual mode prescaler, programmable counters, phase detectors and control logic Power Dissipation (maximum): PD (max) = 275mW Package Type: CQFPJ-68 Operating Temperature Range (°C): -40 to +80 | | | | | | | |
|  ESCC European Space Components Coordination QPL | | MICROCIRCUITS, CMOS SOS, 3.5 GHz DELTA-SIGMA MODULATED FRACTIONAL-N PLL FREQUENCY SYNTHESIZER, | | | Current Validity of Qualification | | Page |
| | | | | | Certificate | Valid Until | 08-90 |
| | | | | | 307 | March 2013 | 001 |

Section 09



Component Type: Relays


| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|-------------|-------|------------------------------------|----------------|
| 09-01 | | | Non-Latching, 28Vdc Contact Rating | |
| | 09-01-001 | 102 F | Type T** | REL STPI |
| | 09-01-002 | 02 L | Type GP5 | LEACH |
| | 09-01-004 | 205 D | Type E 215 | REL STPI |
| | 09-01-004-3 | 318 | Type M300 | LEACH Sarralbe |
| | 09-01-005 | 239 D | Type E | LEACH |
| | 09-01-006 | 279 B | Type 317 | STPI |
| 09-02 | | | Latching, 28Vdc Contact Rating | |
| | 09-02-001 | 88 G | Type TL | REL STPI |
| | 09-02-002 | 13 L | Type GP2 | LEACH |
| | 09-02-003 | 98 F | Type EL415 | REL STPI |
| | 09-02-003-3 | 317 | Type M402 | LEACH Sarralbe |
| | 09-02-004 | 167 E | Type EL215 | REL STPI |
| | 09-02-004-3 | 310 A | Type M302 | LEACH Sarralbe |
| | 09-02-006 | 240 E | Type D | LEACH |
| | 09-02-007 | 280 B | Type 3*7B | STPI |
| 09-03 | | | Latching, 50Vdc Contact Rating | |
| | 09-03-001 | 93 K | Type GP250 | LEACH |






SECTION 09-**: INDEX OF RELAYS



REP005 Updated on 15 Jun 2013


| | | | | | |
|--|---|--|-----------------------------------|-----------------------|----------|
| Types covered by similarity: Rated Coil Voltages 5, 6, 9, 12 and 18 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3601 | 3601/002 | REL-STPI St Jean de la Ruelle France | Qualification | CNES | Feb 1983 |
| Detail ESCC | | | Extension | CNES | Dec 1985 |
| | | | Extension | CNES | Dec 1988 |
| | | | Extension | CNES | Jan 1993 |
| | | | Extension | CNES | Nov 1997 |
| | | | Re-qualification | CNES | Oct 2009 |
| Characteristics: Variants 01 to 06 are qualified | | | Extension | CNES | Nov 2011 |
| Contact Rating | 1A at 28Vdc | | | | |
| Contact Configuration | 2PDT | | | | |
| Package Type | TO-5 Can | | | | |
| Coil Voltage | 5 - 26.5 Vdc | | | | |
| Operating Temperature Range (°C): -65 to +125 | | | | | |
|   | RELAY, NON-LATCHING, ELECTROMAGNETIC, TYPE T ** | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 09-01 |
| | 102 F | October 2013 | 001 | | |



| | | | | | |
|---|---|---|-----------------------------------|-----------------------|----------|
| Types covered by similarity: Coil Voltages 6 and 12 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC | 3601 | LEACH International Europe Niort France | Qualification | CNES | Apr 1978 |
| | | | Extension | CNES | Oct 1980 |
| Detail ESCC | 3601/003 | | Extension | CNES | Jan 1984 |
| | | | Extension | CNES | Oct 1986 |
| | | | Extension | CNES | Jul 1992 |
| | | | Extension | CNES | Jun 1995 |
| | | | Extension | CNES | Dec 1998 |
| | | | Extension | CNES | Nov 2001 |
| | | | Extension | CNES | Jun 2005 |
| | | | Extension | CNES | Feb 2008 |
| Characteristics: Variants 01 to 08 are qualified | | | Extension | CNES | Apr 2010 |
| Contact Rating | 2 A at 28 Vdc | | Extension | CNES | Mar 2012 |
| Contact Configuration | 2 PDT | | Extension | CNES | |
| Package Type | Half-crystal can | | Extension | CNES | |
| Coil Voltage | 26.5 Vdc | | Extension | CNES | |
| Operating Temperature Range (°C): -65 to +125 | | | Extension | CNES | |
|  | RELAY, NON-LATCHING, ELECTROMAGNETIC, TYPE GP 5 | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 09-01 |
| | | | 02 L | April 2014 | 002 |


| | | | | | |
|--|--|--|-----------------------------------|-----------------------|----------|
| Types covered by similarity: Coil Voltage 12 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC | 3601 | REL STPI St Jean de la Ruelle France | Qualification | CNES | Jan 1994 |
| Detail ESCC | 3601/007 | | Extension | CNES | Dec 1998 |
| | | | Merge | CNES | Nov 1999 |
| | | | Re-qualification | CNES | Dec 2010 |
| | | | Extension | CNES | Jan 2013 |
| Characteristics: Variants 03, 04 and 06 are qualified | | | | | |
| Contact Rating | 15 A at 28 Vdc | | | | |
| Contact Configuration | 2 PDT | | | | |
| Package Type | Half cubic inch can | | | | |
| Coil Voltage | 12 and 28 Vdc | | | | |
| Operating Temperature Range (°C): -65 to +125 | | | | | |
|   | RELAY, NON-LATCHING, ELECTROMAGNETIC, TYPE E 215 | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 09-01 |
| | | 205 D | December 2014 | 004 | |



| | | | | | |
|--|---|-----------------------------|-----------------------------------|-----------------------|----------|
| Types covered by similarity: Coil Voltage 12 Vdc . | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC | 3601 | LEACH Sarralbe France | Qualification | CNES | Feb 2012 |
| Detail ESCC | 3601/007 | | | | |
| Characteristics: Variants 03, 04 and 06 are qualified Contact Rating 15 A at 28 Vdc Contact Configuration 2 PDT Package Type Half cubic inch can Coil Voltage 12 and 28 Vdc Operating Temperature Range (°C): -65 to +125 | | | | | |
|  | RELAY, NON-LATCHING, ELECTROMAGNETIC, TYPE M300 | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 09-01 |
| | | | 318 | February 2014 | 004-3 |


| | | | | | |
|--|--|--|-----------------------------------|-----------------------|----------|
| Types covered by similarity: Coil Voltages 6 and 12 Vdc | | Remarks: Maintenance of qualification testing is underway. | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC | 3601 | LEACH International Europe Niort France | Qualification | CNES | Apr 1997 |
| | | | Extension | CNES | Sep 2000 |
| Detail ESCC | 3601/012 | | Extension | CNES | Jan 2004 |
| | | | Extension | CNES | Feb 2008 |
| | | | Extension | CNES | Apr 2010 |
| Characteristics: Variants 01 to 11 are qualified | | | | | |
| Contact Rating | 1 A at 28 Vdc | | | | |
| Contact Configuration | 2 PDT | | | | |
| Package Type | 1/6 crystal can | | | | |
| Coil Voltage | 26.5 Vdc | | | | |
| Operating Temperature Range (°C): -65 to +125 | | | | | |
|   | RELAY, NON-LATCHING, ELECTROMAGNETIC, TYPE E | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 09-01 |
| | | 239 D | April 2012 | 005 | |


| | | | | | |
|---|--|---|-----------------------------------|-----------------------|----------|
| Types covered by similarity: Coil voltage 12 Vdc | | Remarks: Long term strategy favours 15A relays from STPI-REL. Planning to be confirmed. | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC | 3601 | STPI Paris France | Qualification | CNES | Apr 2007 |
| Detail ESCC | 3601/007 | | Extension | CNES | Oct 2010 |
| | | | Extension | CNES | Jun 2012 |
| Characteristics: Variants 01 to 06 are qualified | | | | | |
| Contact Rating | 15 A at 28 Vdc | | | | |
| Contact Configuration | 2 PDT | | | | |
| Size (mm. max.) | 26x26x14 | | | | |
| Package Type | 1/2 can | | | | |
| Coil Voltage | 28 Vdc | | | | |
| Operating Temperature Range (°C): -65 to +125 | | | | | |
|  | RELAY, NON-LATCHING, ELECTROMAGNETIC, TYPE 317 | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 09-01 |
| | | | 279 B | April 2013 | 006 |


| | | | | | |
|--|---|---|-----------------------------------|-----------------------|----------|
| Types covered by similarity: Rated Coil Voltages 5, 6, 9, 12 and 18 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC | 3602 | REL-STPI Saint Jean de la Ruelle France | Qualification | CNES | Jan 1982 |
| Detail ESCC | 3602/002 | | Extension | CNES | Oct 1983 |
| | | | Extension | CNES | Oct 1986 |
| | | | Extension | CNES | Nov 1989 |
| | | | Extension | CNES | Jan 1993 |
| | | | Requalification | CNES | Nov 1997 |
| | | | Requalification | CNES | Jan 2010 |
| Characteristics: Variants 01 to 06 are qualified | | | Extension | CNES | Mar 2012 |
| Contact Rating | 1 A at 28 Vdc | | | | |
| Contact Configuration | 2 PDT | | | | |
| Package Type | TO-5 Can | | | | |
| Coil Voltage | 26.5 Vdc | | | | |
| Operating Temperature Range (°C): -65 to +125 | | | | | |
|   | RELAY, LATCHING, ELECTROMAGNETIC, TYPE TL | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 09-02 |
| | | 88 G | January 2014 | 001 | |


| | | | | | |
|---|---|---|-----------------------------------|-----------------------|----------|
| Types covered by similarity: Coil Voltages 6 and 12 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC | 3602 | LEACH International Europe Niort France | Qualification | CNES | Jan 1979 |
| | | | Extension | CNES | Feb 1981 |
| Detail ESCC | 3602/003 | | Extension | CNES | Jan 1984 |
| | | | Extension | CNES | Oct 1986 |
| | | | Extension | CNES | Jul 1992 |
| | | | Extension | CNES | Jun 1995 |
| | | | Extension | CNES | Dec 1998 |
| | | | Extension | CNES | Nov 2001 |
| | | | Extension | CNES | Jun 2005 |
| | | | Extension | CNES | Feb 2008 |
| Characteristics: | Variants 01 to 08 are qualified | | Extension | CNES | Apr 2010 |
| Contact Rating | 2 A at 28 Vdc | | Extension | CNES | Mar 2012 |
| Contact Configuration | 2 PDT | | Extension | CNES | |
| Package Type | Half-size crystal can | | Extension | CNES | |
| Coil Voltage | 26.5 Vdc | | Extension | CNES | |
| Operating Temperature Range (°C): | -65 to +125 | | Extension | CNES | |
|  | RELAY, LATCHING, ELECTROMAGNETIC, TYPE GP 2 | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 09-02 |
| | | | 13 L | April 2014 | 002 |


| | | | | | |
|--|---|--|-----------------------------------|-----------------------|----------|
| Types covered by similarity: Coil voltage : 12 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC | 3602 | REL STPI St Jean de la Ruelle France | Qualification | CNES | Nov 1982 |
| | | | Extension | CNES | Dec 1985 |
| Detail ESCC | 3602/004 | | Extension | CNES | Nov 1989 |
| | | | Extension | CNES | Jan 1994 |
| | | | Re-qualification | CNES | Apr 2011 |
| | | | Extension | CNES | Apr 2013 |
| Characteristics: Variants 04, 06 and 09 and 14, 16 and 19 are qualified | | | | | |
| Contact Rating | 15 A at 28 Vdc | | | | |
| Contact Configuration | 4PDT | | | | |
| Package Type | Cubic inch can | | | | |
| Coil Voltage | 28 Vdc | | | | |
| Operating Temperature Range (°C): -65 to +125 | | | | | |
|   | RELAY, LATCHING, ELECTROMAGNETIC, TYPE EL 415 | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 09-02 |
| | | 98 F | April 2015 | 003 | |


| | | | | | |
|---|---|-----------------------------|-----------------------------------|-----------------------|----------|
| Types covered by similarity: Coil voltage : 12 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3602 | | LEACH Sarralbe France | Qualification | CNES | Feb 2012 |
| Detail ESCC 3602/004 | | | | | |
| Characteristics: Variants 04, 06 and 09 and 14, 16 and 19 are qualified Contact Rating 15 A at 28 Vdc Contact Configuration 4PDT Package Type Cubic inch can Coil Voltage 28 Vdc Operating Temperature Range (°C): -65 to +125 | | | | | |
|  | RELAY, LATCHING, ELECTROMAGNETIC, TYPE M402 | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 09-02 |
| | | | 317 | February 2014 | 003-3 |

| | | | | | | |
|--|----------|---|--------------------|-----------------------------------|--------------|-------|
| Types covered by similarity: Coil voltage : 12 Vdc | | Remarks: | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | |
| Generic ESCC | 3602 | REL STPI St Jean de la Ruelle France | Qualification | CNES | Feb 1990 | |
| Detail ESCC | 3602/009 | | Extension | CNES | Nov 1993 | |
| | | | Extension | CNES | Dec 1998 | |
| | | | Merged | CNES | Nov 1999 | |
| | | | Re-qualification | CNES | Oct 2010 | |
| | | | Extension | CNES | Dec 2012 | |
| Characteristics: Variants 03, 04 and 06 and 13, 14 and 16 are qualified Contact Rating 15 A at 28 Vdc Contact Configuration 2PDT Package Type Half-cubic inch can Coil Voltage 28 Vdc Operating Temperature Range (°C): -65 to +125 | | | | | | |
|  QPL | | RELAY, LATCHING, ELECTROMAGNETIC, TYPE EL 215 | | Current Validity of Qualification | | Page |
| | | | | Certificate | Valid Until | 09-02 |
| | | | | 167 E | October 2014 | 004 |

| | | | | | |
|--|--|-----------------------------|-----------------------------------|-----------------------|--------------------------|
| Types covered by similarity: Coil voltage : 12 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3602 | | LEACH Sarralbe France | Qualification Extension | CNES CNES | Apr 2011 Apr 2013 |
| Detail ESCC 3602/009 | | | | | |
| Characteristics: Variants 03, 04 and 06 and 13, 14 and 16 are qualified Contact Rating 15 A at 28 Vdc Contact Configuration 2PDT Package Type Half-cubic inch can Coil Voltage 28 Vdc Operating Temperature Range (°C): -65 to +125 | | | | | |
|  | RELAY, LATCHING, ELECTROMAGNETIC, BASED ON TYPE M302 | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 09-02 |
| | | | 310 A | April 2015 | 004-2 |

| | | | | | |
|---|--|---|-----------------------------------|-----------------------|----------|
| Types covered by similarity: Coil Voltages 6 and 12 Vdc . | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC | 3602 | LEACH International Europe Niort France | Qualification | CNES | Apr 1997 |
| | | | Extension | CNES | Sep 2000 |
| Detail ESCC | 3602/019 | | Extension | CNES | Jan 2004 |
| | | | Extension | CNES | Feb 2008 |
| | | | Extension | CNES | Apr 2010 |
| | | | Extension | CNES | Mar 2012 |
| Characteristics: Variants 01 to 11 are qualified | | | | | |
| Contact Rating | 1 A at 28 Vdc | | | | |
| Contact Configuration | 2 PDT | | | | |
| Package Type | 1/6 crystal can | | | | |
| Coil Voltage | 26.5 Vdc | | | | |
| Operating Temperature Range (°C): -65 to +125 | | | | | |
|  | RELAY, LATCHING, ELECTROMAGNETIC, TYPE D | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 09-02 |
| | | 240 E | April 2014 | 006 | |


| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|--|-------|----------|---|----------|---|----------------|----------------|----------------|----------------|-----------------------|-------|-----------------------|-------|-----------------|----------|-----------------|-------------|--------------|-----|--------------|---------|--------------|--------|--------------|--------|---|--|---|--|
| Types covered by similarity: Coil Voltage 12 Vdc | | | | Remarks: Long term strategy favours 15A relays from STPI-REL. Planning to be confirmed. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC | 3602 | STPI Paris France | Qualification Extension Extension | CNES CNES CNES | Apr 2007 Oct 2010 Jun 2012 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Detail ESCC | 3602/004 3602/009 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Characteristics:</p> <table border="0"> <tr> <td>3602/004</td> <td>Variants 04, 06 and 09 14, 16 and 19 are qualified</td> <td>3602/009</td> <td>Variants 03, 04 and 06 and 13, 14 and 16 are qualified</td> </tr> <tr> <td>Contact Rating</td> <td>15 A at 28 Vdc</td> <td>Contact Rating</td> <td>15 A at 28 Vdc</td> </tr> <tr> <td>Contact Configuration</td> <td>4 PDT</td> <td>Contact Configuration</td> <td>2 PDT</td> </tr> <tr> <td>Size (mm. max.)</td> <td>26x26x26</td> <td>Size (mm. max.)</td> <td>26x26x13.34</td> </tr> <tr> <td>Package Type</td> <td>can</td> <td>Package Type</td> <td>1/2 can</td> </tr> <tr> <td>Coil Voltage</td> <td>28 Vdc</td> <td>Coil Voltage</td> <td>28 Vdc</td> </tr> <tr> <td colspan="2">Operating Temperature Range (°C): -65 to +125</td> <td colspan="2">Operating Temperature Range (°C): -65 to +125</td> </tr> </table> | | | | | | | 3602/004 | Variants 04, 06 and 09 14, 16 and 19 are qualified | 3602/009 | Variants 03, 04 and 06 and 13, 14 and 16 are qualified | Contact Rating | 15 A at 28 Vdc | Contact Rating | 15 A at 28 Vdc | Contact Configuration | 4 PDT | Contact Configuration | 2 PDT | Size (mm. max.) | 26x26x26 | Size (mm. max.) | 26x26x13.34 | Package Type | can | Package Type | 1/2 can | Coil Voltage | 28 Vdc | Coil Voltage | 28 Vdc | Operating Temperature Range (°C): -65 to +125 | | Operating Temperature Range (°C): -65 to +125 | |
| 3602/004 | Variants 04, 06 and 09 14, 16 and 19 are qualified | 3602/009 | Variants 03, 04 and 06 and 13, 14 and 16 are qualified | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Contact Rating | 15 A at 28 Vdc | Contact Rating | 15 A at 28 Vdc | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Contact Configuration | 4 PDT | Contact Configuration | 2 PDT | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Size (mm. max.) | 26x26x26 | Size (mm. max.) | 26x26x13.34 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Package Type | can | Package Type | 1/2 can | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Coil Voltage | 28 Vdc | Coil Voltage | 28 Vdc | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Operating Temperature Range (°C): -65 to +125 | | Operating Temperature Range (°C): -65 to +125 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | RELAY, NON-LATCHING, ELECTROMAGNETIC, TYPE 3*7B | | Current Validity of Qualification | | Page | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | Certificate | Valid Until | 09-02 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | 280 B | April 2013 | 006 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |


| | | | | | |
|--|---|---|-----------------------------------|-----------------------|----------|
| Types covered by similarity: Coil Voltage 6 Vdc and 12 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3602 | Variants 01 to 08 are qualified | LEACH International Europe Niort France | Qualification | ESTEC | Feb 1982 |
| Detail ESCC 3602/010 | | | Extension | CNES | Jul 1984 |
| | | | Extension | CNES | Sep 1987 |
| | | | Extension | CNES | Jul 1992 |
| | | | Extension | CNES | Jun 1995 |
| | | | Extension | CNES | Dec 1998 |
| | | | Extension | CNES | Nov 2001 |
| | | | Extension | CNES | Jun 2005 |
| | | | Extension | CNES | Feb 2008 |
| | | | Extension | CNES | Apr 2010 |
| Extension | CNES | Mar 2012 | | | |
| Characteristics: Variants 01 to 08 are qualified Contact Rating 2 A at 50 Vdc (100000 ops) Contact Configuration 2 PDT Package Type Half-size crystal can Coil Voltage 26.5 Vdc Operating Temperature Range (°C): -65 to +125 | | | | | |
|  ESCC European Space Components Coordination QPL | RELAY, LATCHING, ELECTROMAGNETIC, TYPE GP 250 | | Current Validity of Qualification | | Page |
| | | | Certificate | Valid Until | 09-03 |
| | | 93 K | April 2014 | 001 | |

Section 10

Component Type: Resistors

| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|---------------------|-------|-----------------------------|--------------------------|
| 10-02 | | | Fixed, Film, High Precision | |
| | 10-02-001 | 116 M | Type RNC 90 | Vishay S.A. Sfernice |
| 10-07 | | | Shunts | |
| | 10-07-001 | 285 B | Types SM*-PW and SM*-PT | Isabellenhütte |
| 10-08 | | | Fixed, Film | |
| | 10-08-006 | 256 F | Surface Mount, Type MS1 | Vishay Electronic (Selb) |
| | 10-08-007 | 289 A | Surface Mount, Type TNPS | Vishay Electronic (Selb) |
| 10-09 | | | Chip | |
| | 10-09-002 A to D | 287 C | Type PHR; PFRR; PRAHR/CNWHR | Vishay S.A. Sfernice |
| | 10-09-003 | 314 | Type CHP | Vishay S.A. Sfernice |
| 10-11 | | | Flexible, Foil, Heaters | |
| | 10-11-001-1 | 184 J | Single & Double Layer | IRCA |
| | 10-11-002 | 325 | Single & Double Layer | Minco |

| Types covered by similarity: | | | | | | | Remarks: New package fabrication is now located in Nice. | | | | | | | | | | | | | | | |
|---|----------|-----------|----------------------------|---|---|--------------------|--|-------------------------------|------------------|------------------|----------------|----------|-----------|----------------------------|---|---|-----|-----------------|--|--|------|----------|
| Tolerance ($\pm\%$) = 0.02, 0.05, 0.1, 0.2, 0.5, 1% | | | | | | | | | | | | | | | | | | | | | | |
| Procurement Specifications | | | | Manufacturer | | | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | |
| Generic ESCC 4001 | | | | VISHAY S.A. Division Sfernice Nice France | | | Qualification | CNES | Dec 1983 | | | | | | | | | | | | | |
| Detail ESCC 4001/011 | | | | | | | Extension | | | CNES | Oct 1986 | | | | | | | | | | | |
| Characteristics: Variants 03, 04, 07 and 08 are qualified | | | | | | | Extension | CNES | Nov 1989 | | | | | | | | | | | | | |
| | | | | | | | Extension | | | CNES | Jul 1992 | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>Style</th> <th>Detail Spec.</th> <th>Range (Ω)</th> <th>Tol. ($\pm\%$)</th> <th>TC (\pmppm/$^{\circ}$C)</th> <th>Power Rating (W)</th> <th>Max. Voltage (V)</th> </tr> </thead> <tbody> <tr> <td>RNC 90 (RS92N)</td> <td>4001/011</td> <td>50 - 100k</td> <td>0.02 0.05 0.5 1.0</td> <td>$\pm 5, \leq 125^{\circ}$C $\pm 10, \leq 125^{\circ}$C $\pm 10, > 125^{\circ}$C and $\leq 175^{\circ}$C</td> <td>0.5 @ 70 $^{\circ}$C 0.3 @ 125 $^{\circ}$C</td> <td>300</td> </tr> </tbody> </table> | | | | Style | Detail Spec. | Range (Ω) | Tol. ($\pm\%$) | TC (\pm ppm/ $^{\circ}$ C) | Power Rating (W) | Max. Voltage (V) | RNC 90 (RS92N) | 4001/011 | 50 - 100k | 0.02 0.05 0.5 1.0 | $\pm 5, \leq 125^{\circ}$ C $\pm 10, \leq 125^{\circ}$ C $\pm 10, > 125^{\circ}$ C and $\leq 175^{\circ}$ C | 0.5 @ 70 $^{\circ}$ C 0.3 @ 125 $^{\circ}$ C | 300 | Requalification | | | CNES | Apr 1994 |
| | | | | Style | Detail Spec. | Range (Ω) | Tol. ($\pm\%$) | TC (\pm ppm/ $^{\circ}$ C) | Power Rating (W) | Max. Voltage (V) | | | | | | | | | | | | |
| RNC 90 (RS92N) | 4001/011 | 50 - 100k | 0.02 0.05 0.5 1.0 | $\pm 5, \leq 125^{\circ}$ C $\pm 10, \leq 125^{\circ}$ C $\pm 10, > 125^{\circ}$ C and $\leq 175^{\circ}$ C | 0.5 @ 70 $^{\circ}$ C 0.3 @ 125 $^{\circ}$ C | 300 | | | | | | | | | | | | | | | | |
| Operating Temperature Range, ($^{\circ}$ C): -55 to +175 | | | | | | | Extension | CNES | Sep 1996 | | | | | | | | | | | | | |
| | | | | | | | Extension | | | CNES | Jan 1999 | | | | | | | | | | | |
| | | | | | | | Extension | CNES | Jul 2001 | | | | | | | | | | | | | |
| | | | | | | | Extension | | | CNES | Nov 2003 | | | | | | | | | | | |
| | | | | | | | Extension | CNES | Apr 2006 | | | | | | | | | | | | | |
| | | | | | | | Extension | | | CNES | Sep 2008 | | | | | | | | | | | |
| | | | | | | | Extension | CNES | Nov 2010 | | | | | | | | | | | | | |
| | | | | | | | Extension | | | CNES | Aug 2012 | | | | | | | | | | | |
|  | | | | RESISTORS, FILM, FIXED, NON-HERMETICALLY SEALED, BASED ON TYPE RNC 90 | | | Current Validity of Qualification | | Page | | | | | | | | | | | | | |
| | | | | | | | Certificate | Valid Until | 10-02 | | | | | | | | | | | | | |
| | | | | | | | 116 M | September 2014 | 001 | | | | | | | | | | | | | |

| Types covered by similarity: Tolerance (%) = ±1 | | | | Remarks: | | | |
|---|----------------------|--|-----------|---|-----------------------------------|--|------------------|
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Date | |
| Generic ESCC 4001 Detail ESCC 4001/027 4001/028 | | ISABELLENHÜTTE HEUSLER GmbH & Co. KG Dillenburg Germany | | Qualification Extension Extension | DLR DLR DLR | Nov 2008 Jul 2010 Feb 2013 | |
| Characteristics: Variants 01, 02 and 03 are qualified | | | | | | | |
| Style | Detail Spec. Variant | Range (Ω) | Tol. (±%) | TC (± 10 ⁻⁶ /°C) Applicable to All Variants | Power Rating (W) | | |
| SMP- 2010 | 001 | 0.005-1.000 | 0.5 | Refer to ESCC Detail Specifications | 1 | | |
| SMR-4723 | 001 | 0.010– 4.7 | 0.5 | | 3 | | |
| SMS- 2512 | 002 | 0.003-1.000 | 0.5 | | 2 | | |
| SMT- 2817 | 003 | 0.004-2.000 | 0.5 | | 3 | | |
| SMV-4723 | 002 | 0.0022 - 1.0 | 0.5 | | 3 | | |
| Operating Temperature Range, (°C): -55 to +170 | | | | | | | |
|  | | RESISTORS, FIXED, CHIP, METAL FOIL, BASED ON TYPES SM*-PW AND SM*-PT | | | Current Validity of Qualification | | Page |
| | | | | | Certificate 285 B | Valid Until July 2014 | 10-07 001 |

Types covered by similarity:
Tolerance ($\pm\%$) = 0.1, 0.5, 1.0

Remarks:

| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
|----------------------------|--------------|--------------------|-----------------------|------|
|----------------------------|--------------|--------------------|-----------------------|------|

Generic
ESCC 4001

Detail
ESCC 4001/022

VISHAY Electronic GmbH
Division Draloric
Selb
Germany

| | | |
|---------------|-----|----------|
| Qualification | DLR | Oct 1999 |
| Extension | DLR | Oct 2001 |
| Extension | DLR | Oct 2003 |
| Extension | DLR | Nov 2005 |
| Extension | DLR | Oct 2007 |
| Extension | DLR | Oct 2009 |
| Extension | DLR | Oct 2011 |

Characteristics: Critical R = 160 k Ω


| Range (Ω) | Tol. ($\pm\%$) | TC (\pm ppm/ $^{\circ}$ C) | Value Series |
|--------------------|------------------|-------------------------------|--------------|
| 43.2 - 1.004 M | 0.1 | 50 | E96 |
| 10.0 - 1.004 M | 0.5 | | |
| 2.20 - 5.114 M | 1.0 | | |
| 43.2 - 1.004 M | 0.1 | 25 | E96 |
| 10.0 - 1.004 M | 0.5 | | |
| 10.0 - 1.004 M | 1.0 | | |
| 43.2 - 0.2213 M | 0.1 | 15 | E96 |
| 10.0 - 0.5113 M | 0.5 | | |


Operating Temperature Range, ($^{\circ}$ C): -55 to +125



RESISTORS,
FILM, FIXED, SURFACE MOUNT, NON-HERMETICALLY SEALED, BASED ON TYPE
MS1

| Current Validity of Qualification | | Page |
|-----------------------------------|--------------|-------|
| Certificate | Valid Until | 10-08 |
| 256 F | October 2013 | 006 |

| Types covered by similarity: Temperature Coefficient (\pm ppm/ $^{\circ}$ C): 25, 50 Tolerance (\pm %) = 0.5, 1.0 | | | | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|-------|--------------------|--|---|-----------------|--------------------------------|-----------------------------------|-----------------------------|------------------|-------|--------------------|--|--|-----------------|-------------------------------|-------------------------|--|----|------|----|---|---------|-----|----|-------|--|----|------|----|---|---------|-----|----|-----|--|----|------|----|---|-----|-----|----|-----|--|
| Procurement Specifications | | | | Manufacturer | | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 4001 Detail ESCC 4001/029 | | | | VISHAY Electronic Division Draloric Selb Germany | | Qualification Extension | DLR DLR | May 2009 Jun 2011 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Characteristics: Variants 01 to 03 inclusive are qualified E96 Series</p> <table border="1"> <thead> <tr> <th>Variants</th> <th>Style</th> <th colspan="3">Range (Ω)</th> <th>Tol. (\pm%)</th> <th>TC (\pmppm/$^{\circ}$C)</th> <th colspan="2">Critical R (Ω)</th> </tr> </thead> <tbody> <tr> <td>01</td> <td>0603</td> <td>10</td> <td>-</td> <td>0.221 M</td> <td>0.1</td> <td>15</td> <td colspan="2">56.25</td> </tr> <tr> <td>02</td> <td>0805</td> <td>10</td> <td>-</td> <td>0.422 M</td> <td>0.1</td> <td>15</td> <td colspan="2">180</td> </tr> <tr> <td>03</td> <td>1206</td> <td>10</td> <td>-</td> <td>1 M</td> <td>0.1</td> <td>15</td> <td colspan="2">160</td> </tr> </tbody> </table> <p>Operating Temperature Range, ($^{\circ}$C): -55 to +125</p> | | | | | | | | | Variants | Style | Range (Ω) | | | Tol. (\pm %) | TC (\pm ppm/ $^{\circ}$ C) | Critical R (Ω) | | 01 | 0603 | 10 | - | 0.221 M | 0.1 | 15 | 56.25 | | 02 | 0805 | 10 | - | 0.422 M | 0.1 | 15 | 180 | | 03 | 1206 | 10 | - | 1 M | 0.1 | 15 | 160 | |
| Variants | Style | Range (Ω) | | | Tol. (\pm %) | TC (\pm ppm/ $^{\circ}$ C) | Critical R (Ω) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 01 | 0603 | 10 | - | 0.221 M | 0.1 | 15 | 56.25 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 02 | 0805 | 10 | - | 0.422 M | 0.1 | 15 | 180 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 03 | 1206 | 10 | - | 1 M | 0.1 | 15 | 160 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | | RESISTORS, FILM, FIXED, SURFACE MOUNT, NON-HERMETICALLY SEALED, BASED ON TYPE TNPS | | | | Current Validity of Qualification | | Page | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | Certificate 289 A | Valid Until May 2013 | 10-08 007 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | | |
|--|--|---|--------------------------------------|--|
| Types covered by similarity: | | Remarks: Components under ESCC QML qualification. Refer to Technology Flow description in REF006. This certificate replaces certificate 265C. | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 4001 Detail ESCC 4001/023 ESCC 4001/025 | VISHAY S.A. Division Sfernice Nice France | Qualification Extension Extension | CNES CNES CNES | Feb 2009 Feb 2011 Feb 2013 |
| <p>Characteristics: Refer to tables on the next page</p> <p>4001/023 PHR High Stability and Precision Chip</p> <p>4001/023 PFRR High Stability and Precision Chip with Established Reliability Level R</p> <p>4001/025 PRA/CNWHR High Stability and Precision Surface Mount Array</p> <p>Operating Temperature Range, (°C): -55 to +155 Lead material is E with either Type 2 or Type 4 finish</p> | | | | |
|  | RESISTORS, FILM, FIXED, CHIP AND ARRAY, THIN FILM, BASED ON TYPES PHR; PFRR; PRAHR/CNWHR | Current Validity of Qualification | | Page |
| | | Certificate 287 C | Valid Until Feb 2015 | 10-09 002-A |

Characteristics: Type PHR, Variants 01 to 08 are qualified

| Detail Specification | Style | Critical R (kΩ) | Rated Dissipation (W) | Limiting Element Voltage (V) | Type Variant |
|----------------------|-------|-----------------|-----------------------|------------------------------|--------------|
| 4001/023 | 0603 | 12.25 | 0.100 | 35 | 01; 05 |
| | 0805 | 45 | 0.125 | 75 | 02; 06 |
| | 1206 | 40 | 0.250 | 100 | 03; 07 |
| | 2010 | 45 | 0.500 | 150 | 04; 08 |

| Style | Range (Ω) | Tolerance (±%) | Temperature Coefficient (±ppm/°C) |
|------------------------|--------------------|-----------------------|-----------------------------------|
| 0603; 0805; 1206; 2010 | From 10 to <20 | 0.1 | 25 |
| 0603; 0805; 1206; 2010 | From 20 to <50 | 0.1 | 10; 25 |
| 0603; 0805; 1206; 2010 | From 50 to <100 | 0.05; 0.1 | 5; 10; 25 |
| 0603; 0805; 1206; 2010 | From 100 to <250 | 0.02; 0.05; 0.1 | 5; 10; 25 |
| 0603; 0805; 1206; 2010 | From 250 to <200K | 0.01; 0.02; 0.05; 0.1 | 5; 10; 25 |
| 0805; 1206; 2010 | From 200K to <250K | 0.01; 0.02; 0.05; 0.1 | 5; 10; 25 |
| 1206; 2010 | From 250K to <1M | 0.01; 0.02; 0.05; 0.1 | 5; 10; 25 |
| 2010 | From 1M to 3M | 0.01; 0.02; 0.05; 0.1 | 5; 10; 25 |



RESISTORS,
FILM, FIXED, CHIP AND ARRAY, THIN FILM,
BASED ON TYPES PHR; PFRR; PRAHR/CNWHR

Current Validity of Qualification

Certificate

287 C

Valid Until

Feb 2015

Page

10-09


002-B

Characteristics: Type PFRR, Variants 09 to 12 and 15 are qualified

| Detail Specification | Style | Critical R (kΩ) | Rated Dissipation (W) | Limiting Element Voltage (V) | Type Variant |
|----------------------|-------|-----------------|-----------------------|------------------------------|--------------|
| 4001/023 | 0402 | 32 | 0.050 | 40 | 15 |
| | 0603 | 25 | 0.100 | 50 | 09 |
| | 0805 | 80 | 0.125 | 100 | 10 |
| | 1206 | 90 | 0.250 | 150 | 11 |
| | 2010 | 80 | 0.500 | 200 | 12 |

| Style | Resistance Range (Ω) | Tolerance (±%) | Temperature Coefficient TC(±10 ⁻⁶ /°C) |
|------------------------------|----------------------|----------------|---|
| 0402; 0603; 0805; 1206; 2010 | From 100 to ≤ 100K | 0.05; 0.1 | 10; 25 |
| 0603; 0805; 1206; 2010 | From 100 to ≤ 261K | 0.05; 0.1 | 10; 25 |
| 0805; 1206; 2010 | From 261K to ≤ 301K | 0.05; 0.1 | 10; 25 |
| 1206; 2010 | From 301K to ≤ 1M | 0.05; 0.1 | 10; 25 |
| 2010 | From 1M to 3M01 | 0.05; 0.1 | 10; 25 |

The Established Reliability Level R is evaluated according to the ESCC Basic Specification 26000.

| | | | | |
|---|---|-----------------------------------|-------------|-------|
|  ESCC <small>European Space Components Coordination</small> QPL | RESISTORS, FILM, FIXED, CHIP AND ARRAY, THIN FILM, BASED ON TYPES PHR; PFRR; PRAHR/CNWHR | Current Validity of Qualification | | Page |
| | | Certificate | Valid Until | |
| | | 287 C | Feb 2015 | 002-C |

Characteristics: Type PRAHR/CNWHR,, Variants 01 to 42 are qualified

| Detail Specification | Style | Critical R (K Ω) | Rated Dissipation (W/resistor) | Limiting Element Voltage (V/resistor) | Type Variant | |
|----------------------|--------|-----------------------------|-----------------------------------|---|-------------------------|------------------------------|
| | | | | | Same Ohmic Values | Different Ohmic Values |
| 4001/025 | PRA100 | 12.25 | 0.100 | 35 | 01 to 07 | 22 to 28 |
| | PRA135 | 56.25 | 0.100 | 75 | 08 to 14 | 29 to 35 |
| | PRA182 | 100 | 0.100 | 100 | 15 to 21 | 36 to 42 |

| Style | Resistance Range (Ω) | Tolerance ($\pm\%$) | | Temperature Coefficient TC($\pm 10^{-6}$ / $^{\circ}$ C) | |
|------------------------|----------------------------------|--------------------------|-----------|--|----------|
| | | Absolute | Relative | Absolute | Relative |
| PRA100; PRA135; PRA182 | From 100 to 200K | 0.1; 0.5; 1 | 0.05; 0.1 | 10 | 3; 5 |
| PRA135; PRA182 | From 200K to 250K | 0.1; 0.5; 1 | 0.05; 0.1 | 10 | 3; 5 |
| PRA182 | From 250K to 1M | 0.1; 0.5; 1 | 0.05; 0.1 | 10 | 3; 5 |

Number of Resistors per Array: 2 to 8



RESISTORS,
FILM, FIXED, CHIP AND ARRAY, THIN FILM,
BASED ON TYPES PHR; PFRR; PRAHR/CNWHR

Current Validity of Qualification

Certificate

287 C


Valid Until



Feb 2015



Page

10-09

002-D



| Types covered by similarity: | | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--------------------------|--|------------------------------|--------------------|-----------------------------------|--------------|-------|--------------------------|-------------------|------------------------------|--------------------------|----------------|------|-------|--------------------------|-----------------|---------|---------|--------------------------|-----------------------|-------|------|-----|-------|-----|-------|------|-----|-------|-----|-------|------|-------|-------|-----|-------|
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 4001 Detail ESCC 4001/026 | | VISHAY S.A. Division Sfernice Nice France | | Qualification | CNES | Oct 2011 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics: Type CHPHR, Variants 01 to 10 are qualified | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>Style</th> <th>Critical R (KΩ)</th> <th>Rated Dissipation</th> <th>Limited Element Voltage (V)</th> <th>Type Variant</th> </tr> </thead> <tbody> <tr> <td>0603</td> <td>25</td> <td>0.100</td> <td>50</td> <td>01;06</td> </tr> <tr> <td>0805</td> <td>50</td> <td>0.200</td> <td>100</td> <td>02;07</td> </tr> <tr> <td>1206</td> <td>160</td> <td>0.250</td> <td>200</td> <td>03;08</td> </tr> <tr> <td>2010</td> <td>180</td> <td>0.500</td> <td>300</td> <td>04;09</td> </tr> <tr> <td>2512</td> <td>112.5</td> <td>0.800</td> <td>300</td> <td>05;10</td> </tr> </tbody> </table> | | | | | | | Style | Critical R (K Ω) | Rated Dissipation | Limited Element Voltage (V) | Type Variant | 0603 | 25 | 0.100 | 50 | 01;06 | 0805 | 50 | 0.200 | 100 | 02;07 | 1206 | 160 | 0.250 | 200 | 03;08 | 2010 | 180 | 0.500 | 300 | 04;09 | 2512 | 112.5 | 0.800 | 300 | 05;10 |
| Style | Critical R (K Ω) | Rated Dissipation | Limited Element Voltage (V) | Type Variant | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0603 | 25 | 0.100 | 50 | 01;06 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0805 | 50 | 0.200 | 100 | 02;07 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1206 | 160 | 0.250 | 200 | 03;08 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2010 | 180 | 0.500 | 300 | 04;09 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2512 | 112.5 | 0.800 | 300 | 05;10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>Style</th> <th>Range(Ω)</th> <th>Tol. (\pm%)</th> <th>TC(\pmppm/$^{\circ}$C)</th> </tr> </thead> <tbody> <tr> <td>0603;0805;1206;2010;2512</td> <td>From 1 to < 10</td> <td>2; 5</td> <td>200</td> </tr> <tr> <td>0603;0805;1206;2010;2512</td> <td>From 10 to < 1M</td> <td>1; 2; 5</td> <td>100;200</td> </tr> <tr> <td>0603;0805;1206;2010;2512</td> <td>From 1M to \leq 10M</td> <td>2; 5</td> <td>200</td> </tr> </tbody> </table> | | | | | | | Style | Range(Ω) | Tol. (\pm %) | TC(\pm ppm/ $^{\circ}$ C) | 0603;0805;1206;2010;2512 | From 1 to < 10 | 2; 5 | 200 | 0603;0805;1206;2010;2512 | From 10 to < 1M | 1; 2; 5 | 100;200 | 0603;0805;1206;2010;2512 | From 1M to \leq 10M | 2; 5 | 200 | | | | | | | | | | | | | | |
| Style | Range(Ω) | Tol. (\pm %) | TC(\pm ppm/ $^{\circ}$ C) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0603;0805;1206;2010;2512 | From 1 to < 10 | 2; 5 | 200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0603;0805;1206;2010;2512 | From 10 to < 1M | 1; 2; 5 | 100;200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0603;0805;1206;2010;2512 | From 1M to \leq 10M | 2; 5 | 200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Operating Temperature Range, ($^{\circ}$ C): -55 to +155 Lead material is E with either Type 2 or Type 4 finish | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | RESISTORS, FIXED, CHIP, THICK FILM, BASED ON TYPE CHP | | | Current Validity of Qualification | | Page | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | Certificate | Valid Until | 10-09 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | 314 | October 2013 | 003 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | | | |
|--|--|--|--------------------|-----------------------|----------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 4009 Detail ESCC 4009/002 | | IRCA RICA Division Vitorio Veneto Italy | Qualification | ESTEC | Apr 1992 |
| Characteristics: Single, double layer and magnetically compensated heaters Maximum Ohmic density 200 Ω/cm ² Tolerances ±2, 3, 5, 10 % Resistance 1 to 5000 Ω Heating Area 1.6 to 1300 cm ² Terminal Lead 20, 22, 24, 26, 28, 30 AWG Temperature coefficient (10 ⁻⁶ /°C): 175 Operating Temperature Range, (°C): -65 to +200 | | | Extension | ESTEC | May 1994 |
| | | | Extension | ESTEC | Mar 1996 |
| | | | Extension | ESTEC | Feb 1998 |
| | | | Extension | ESTEC | Apr 2000 |
| | | | Extension | ESTEC | Aug 2002 |
| | | | Extension | ESTEC | Dec 2004 |
| | | | Extension | ESTEC | Aug 2007 |
| | | Extension | ESTEC | Oct 2009 | |
| | | | Extension | ESTEC | Oct 2011 |
|   | RESISTORS, HEATERS, FLEXIBLE SINGLE AND DOUBLE LAYER | Current Validity of Qualification | | Page | |
| | | Certificate | Valid Until | 10-11 | |
| | | | 184 J | October 2013 | 001-1 |

| | | | | |
|---|--|-----------------------------------|-----------------------|----------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 4009 Detail ESCC 4009/003 | Minco SAS Aston France | Qualification | ESTEC | Mar 2013 |
| <p>Characteristics: Variants 01, 02 and 03 are qualified</p> <p>Single, double layer heaters</p> <p>Maximum Ohmic density 70 Ω/cm²</p> <p>Rated power density 0.38 (variants 01, 03), 0.54 (variant 02) W/cm²</p> <p>Resistance 1 to 5000 Ω</p> <p>Heating Area 0.26 to 1000 cm²</p> <p>Terminal Lead 20 to 30 AWG</p> <p>Resistance Tolerance (%): ±1 to ±10</p> <p>Operating Temperature Range, (°C): -65 to +150 for variants 01 and 03; 65 to +200 for variant 02</p> | | | | |
|   | RESISTORS, HEATERS, FLEXIBLE SINGLE AND DOUBLE LAYER | Current Validity of Qualification | | Page |
| | | Certificate | Valid Until | 10-11 |
| | | 325 | March 2015 | 002 |

Section 11**Component Type: Thermistors**


| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|-----------|-------|-----------------------------|----------------------------------|
| 11-01 | | | NTC | |
| | 11-01-001 | 266 F | Types G15K4D489 and *K3A35* | MEAS Ireland (Betatherm) Ltd. |

| | | | | | | |
|--|--|--|--|-----------------------------------|-----------------------|----------|
| Types covered by similarity: | | Remarks: Refer to variants table 1(a) in the Detail Specifications for resistance to temperature characteristics | | | | |
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 4006 Detail ESCC 4006/013 4006/014 | | MEAS Ireland (Betatherm) Galway Ireland | | Qualification | ESTEC | Jul 2001 |
| Characteristics: 4006/013: Variants 01 to 05 and 06 to 07 are qualified. 4006/014: Variants 08, 09, 12 and 13 are qualified. Operating Temperature Range, (°C): 4006/013 : -55 to +115 4006/014 : -60 to +160 Please refer to the relevant Detail Specification for complete information on the qualified variants. | | | | Extension | ESTEC | Jan 2002 |
| | | | | Extension | ESTEC | Sep 2004 |
| | | | | Extension | ESTEC | Nov 2006 |
| | | | | Extension | Enterprise Ireland | Nov 2008 |
| | | | | Extension | Enterprise Ireland | Nov 2009 |
| | | | | Extension | Enterprise Ireland | Dec 2011 |
|   | | THERMISTORS, (THERMALLY SENSITIVE RESISTORS), NTC, BASED ON TYPES G15K4D489 AND *K3A35* | | Current Validity of Qualification | | Page |
| | | | | Certificate | Valid Until | 11-01 |
| | | | | 266 F | November 2013 | 001 |


Section 12


Component Type: Transistors


| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|----------------|-------|--|--------------------|
| 12-01 | | | Low Power, NPN | |
| | 12-01-002-3A-B | 233 J | Types NPN | STMicroelectronics |
| 12-02 | | | Low Power, PNP | |
| | 12-02-002-3A-B | 234 J | Types PNP | STMicroelectronics |
| 12-05 | | | MOSFET, Power, N-Channel | |
| | 12-05-003-01 | 303 A | Type STRH100N10FSY3 | STMicroelectronics |
| | 12-05-003-02 | 319 | Type BUY**CS*** | Infineon |
| 12-06 | | | MOSFET, Power, P-Channel | |
| | 12-06-003-01 | 326 | Type STRH40P10 | STMicroelectronics |
| 12-10 | | | RF/Microwave, NPN, Low Power, Low Noise | |
| | 12-10-001 | 230 E | Types BFY193 | Infineon |
| | 12-10-002 | 245 E | Types BFY405, -420 and -450 | Infineon |
| | 12-10-003 | 320 | Type BFY640 | Infineon |
| | 12-10-004 | 321 | Types BFY640B and BFY650B | Infineon |
| | 12-10-005 | 322 | Type BFY740B | Infineon |
| 12-16 | | | Microwave, Gallium Arsenide | |
| | 12-16-001 | 213 E | Types CFY67, High Electron Mobility, Low Noise | Infineon |

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|------|--|---|--|-------------|-----------------------|--------|--------|--------|--------|---------|-----------------------|----|----|-----------------------|-----|-----|-----|-----|----|-----------------------|----|----|-----------------------|-----|----|----|----|----|-----------|--|--|--|--|--|--|--|--|---|--|--|--|--|--|--|--|--|-----------|------|----------|
| Types covered by similarity: | | Remarks: As a result of NCCS 2CSTM201 currently under investigation, the qualification of products in TO39 package is suspended. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5000 Detail ESCC Please refer to the next page | | ST Microelectronics Rennes France | Qualification | CNES | Sep 1996 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics: Maximum Rating: <table border="1" data-bbox="71 901 1160 1193"> <tr> <td></td> <td>2N2222A</td> <td>2N2484</td> <td></td> <td>2N5551</td> <td>2N3700</td> <td>2N5154</td> <td>BUX 77</td> <td>2N2920A</td> </tr> <tr> <td>V_{CB0}(V):</td> <td>75</td> <td>60</td> <td>BV_{CB0}(V)</td> <td>180</td> <td>140</td> <td>100</td> <td>100</td> <td>60</td> </tr> <tr> <td>V_{CE0}(V):</td> <td>40</td> <td>60</td> <td>BV_{CE0}(V)</td> <td>160</td> <td>80</td> <td>80</td> <td>80</td> <td>60</td> </tr> <tr> <td>Packages:</td> <td colspan="8">TO-18, TO-66, TO-77, TO-257, LCCC3, LCCC6 and SMD0.5</td> </tr> <tr> <td colspan="9">Operating Temperature Range (°C), -65 to +200</td> </tr> </table> | | | | 2N2222A | 2N2484 | | 2N5551 | 2N3700 | 2N5154 | BUX 77 | 2N2920A | V _{CB0} (V): | 75 | 60 | BV _{CB0} (V) | 180 | 140 | 100 | 100 | 60 | V _{CE0} (V): | 40 | 60 | BV _{CE0} (V) | 160 | 80 | 80 | 80 | 60 | Packages: | TO-18, TO-66, TO-77, TO-257, LCCC3, LCCC6 and SMD0.5 | | | | | | | | Operating Temperature Range (°C), -65 to +200 | | | | | | | | | Extension | CNES | Sep 1997 |
| | | | | 2N2222A | 2N2484 | | 2N5551 | 2N3700 | 2N5154 | BUX 77 | 2N2920A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | V _{CB0} (V): | 75 | 60 | BV _{CB0} (V) | 180 | 140 | 100 | 100 | 60 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | V _{CE0} (V): | 40 | 60 | BV _{CE0} (V) | 160 | 80 | 80 | 80 | 60 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | Packages: | TO-18, TO-66, TO-77, TO-257, LCCC3, LCCC6 and SMD0.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | Operating Temperature Range (°C), -65 to +200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | Extension | CNES | Aug 1998 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | Extension | CNES | Nov 1999 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | Extension | CNES | Nov 2001 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | Extension | CNES | Dec 2003 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | CNES | Mar 2006 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | CNES | Jul 2008 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | CNES | Jul 2010 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | CNES | Aug 2012 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | TRANSISTORS, LOW AND HIGH POWER, NPN | | Current Validity of Qualification | | Page | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | Certificate | Valid Until | 12-01 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | 233 J | July 2014 | 002-3A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| ESCC Specification No. | Component Type | Package | Qualified Variants |
|------------------------|-----------------|------------------------|------------------------|
| 5201/001 | 2N 2484 | TO-18, LCCC3, LCCC3 +1 | 01, 02, 04, 05, 06, 07 |
| 5201/002 | 2N 2222A | TO-18, LCCC3, LCCC3 +1 | 01, 02, 04, 05, 11, 12 |
| 5201/019 | 2N 5551 | TO-18, LCCC3, LCCC3 +1 | 01, 02, 04, 05, 08, 09 |
| | | | |
| 5201/004 | 2N 3700 | TO-18, LCCC3, LCCC3 +1 | 01, 02, 04, 05, 06, 07 |
| 5203/010 | 2N 5154, BFX 34 | TO-257, SMD.5 | 04, 05, 06, 07 |
| 5203/016 | BUX 77ESY | TO-257 | 06, 07 |
| 5207/002 | 2N 2920A | TO-77 and LCCC6 | 03, 06, 12, 15 |
| | | | |





| | | | | |
|---|---|-----------------------------------|--------------------------|-------------------------|
|  ESCC <small>European Space Components Coordination</small> QPL | <p style="text-align: center;">TRANSISTORS, LOW AND HIGH POWER, NPN</p> | Current Validity of Qualification | | Page 12-01 002-3B |
| | | Certificate 233 J | Valid Until July 2014 | |


| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|------|----------|--|--|---|--|--------------------|-----------------------|-----------------------------------|-------------|-----------------------|--------|----|-----|-----|-----|-----------------------|----|----|----|----|-----|-----------|--|--|--|--|--|---|--|--|--|--|--|-----------|--|------|----------|
| Types covered by similarity: | | | | | | Remarks: As a result of NCCS 2CSTM201 currently under investigation, the qualification of products in TO39 package is suspended. Devices 2N3350 and 2N4033 are not extended. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Procurement Specifications | | | | | | Manufacturer | | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5000 Detail ESCC Please refer to the next page | | | | | | ST Microelectronics Rennes France | | Qualification | CNES | Sep 1996 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics: <table border="1"> <tr> <td></td> <td>2N2907A</td> <td>2N3810</td> <td>2N5153</td> <td>BUX 78</td> <td>2N5401</td> </tr> <tr> <td>BV_{CBO}(V)</td> <td>60</td> <td>60</td> <td>100</td> <td>100</td> <td>160</td> </tr> <tr> <td>BV_{CEO}(V)</td> <td>60</td> <td>60</td> <td>80</td> <td>80</td> <td>150</td> </tr> <tr> <td>Packages:</td> <td colspan="5">TO-18, TO-77, TO-78, TO-257, LCCC3, LCCC6 and SMD0.5</td> </tr> <tr> <td colspan="6">Operating Temperature Range (°C), -65 to +200</td> </tr> </table> | | | | | | | 2N2907A | 2N3810 | 2N5153 | BUX 78 | 2N5401 | BV _{CBO} (V) | 60 | 60 | 100 | 100 | 160 | BV _{CEO} (V) | 60 | 60 | 80 | 80 | 150 | Packages: | TO-18, TO-77, TO-78, TO-257, LCCC3, LCCC6 and SMD0.5 | | | | | Operating Temperature Range (°C), -65 to +200 | | | | | | Extension | | CNES | Sep 1997 |
| | | | | | | | 2N2907A | 2N3810 | 2N5153 | BUX 78 | 2N5401 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | BV _{CBO} (V) | 60 | 60 | 100 | 100 | 160 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | BV _{CEO} (V) | 60 | 60 | 80 | 80 | 150 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | Packages: | TO-18, TO-77, TO-78, TO-257, LCCC3, LCCC6 and SMD0.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | Operating Temperature Range (°C), -65 to +200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | Extension | | CNES | Aug 1998 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | | CNES | Nov 1999 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | | CNES | Nov 2001 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | | CNES | Jan 2004 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | | CNES | Mar 2006 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | | CNES | Jul 2008 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | | CNES | Jul 2010 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | | CNES | Aug 2012 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  ESCC European Space Components Coordination QPL | | | | | | TRANSISTORS, LOW AND HIGH POWER, PNP | | | | Current Validity of Qualification | | Page | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | Certificate | Valid Until | | 12-02 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | 234 J | July 2014 | | 002-3A | | | | | | | | | | | | | | | | | | | | | | | | | | |


| ESCC Specification No. | Component Type | Package | Qualified Variants |
|---------------------------|----------------|------------------------|------------------------|
| 5202/001 | 2N 2907A | TO-18, LCCC3, LCCC3 +1 | 01, 02, 04, 05,06, 07 |
| 5202/014 | 2N 5401 | TO-18, LCCC3, LCCC3 +1 | 01, 02, 04, 05, 06, 07 |
| 5204/002 | 2N 5153 | TO-257, SMD.5 | 04, 05, 06 |
| 5204/006 | BUX 78ESY | TO-257 | 06, 07 |
| 5207/005 | 2N 3810 | TO-78, LCCC6 | 01, 02, 07, 09 |
| | | | |





| | | | | |
|---|---|-----------------------------------|-------------|--------|
|  | <p>TRANSISTORS, LOW AND HIGH POWER, PNP</p> | Current Validity of Qualification | | Page |
| | | Certificate | Valid Until | |
| | | 234 J | July 2014 | 002-3B |


| | | | | | |
|---|--|---|-----------------------------------|-----------------------|--------------------------|
| Types covered by similarity: | | Remarks: These devices have a TID tested capability of 70kRADs (Si). | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 5000 Detail ESCC 5205/021 ESCC 5205/024 | | STMicroelectronics Rennes France | Qualification Extension | CNES CNES | Oct 2010 Dec 2012 |
| Characteristics: Maximum Ratings for: 5202/021 Package Type: Operating Temperature Range (°C): - 55 to +150 | 5202/021 5202/024 $V_{GS(th)}$ $r_{DS(on)}$ (m Ω): I_{DS} (A) V_{DS} (V_{dc}): V_{GS} (V_{dc}): P_{TOT} : TO-254AA | Variants 01 and 02 are qualified Variant 01 is qualified 2 -4.5 min/max, $I_D=1$ mA 35, $V_{GS}=12V$, $I_D=24A$ 48, T_{case} (°C)= +25 100 over T_{op} , $V_{GS}=0$ V ± 20 170 W at $T_{case} \leq +25$ C | | | |
|  | TRANSISTORS, MOSFET, N-CHANNEL, POWER, TYPES STRH100N10FSY3 AND STRH40N6SG | | Current validity of Qualification | | Page |
| | | | Certificate | Valid Until | 12-05 |
| | | | 303 A | October 2014 | 003-1 |


| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|----------|---|----------|--|-----------------------------------|--------------------------------|---------------------------|----------|----------|----------|--|--|--|----------------------------------|-----|----|-----|--|--|--|------------------|--|--|--|--|--|--|---------------------|------|----|------|--|--|--|--------------------------|-----|-----|-----|--|--|--|--------------------------|------|------|------|--|--|--|----------------------|----|-----|----|--|--|--|-----------------------------|------|-----|------|--|--|--|----------|--------|------|--------|--|--|--|--|--|--|--|--|--|--|
| Types covered by similarity: Variant 01 in each Detail Specification is qualified. | | | | Remarks: These devices have a TID tested capability of 100 kRad (Si) SEE tested : LET (MeV-cm ² /mg) 56 @ V _{GS} = -10V, V _{DS} = 250V SOA and SE SOA derating graphs are incorporated in the Detail Specifications. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5000 Detail ESCC 5205/026 5205/027 5205/028 | | Infineon Technologies AG Neubiberg Germany | | Qualification | DLR | Aug 2012 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="0"> <tr> <td>Characteristics: ESCC No.</td> <td>5205/026</td> <td>5205/027</td> <td>5205/028</td> <td colspan="3"></td> </tr> <tr> <td>r_{DS(ON)} (mΩ) @ 25 °C</td> <td>130</td> <td>30</td> <td>130</td> <td colspan="3"></td> </tr> <tr> <td colspan="7">Maximum Ratings:</td> </tr> <tr> <td>I_{DS} (A)</td> <td>12.4</td> <td>54</td> <td>12.4</td> <td colspan="3"></td> </tr> <tr> <td>V_{DS} (V) max.</td> <td>250</td> <td>250</td> <td>100</td> <td colspan="3"></td> </tr> <tr> <td>V_{GS} (V) max.</td> <td>± 20</td> <td>± 20</td> <td>± 20</td> <td colspan="3"></td> </tr> <tr> <td>P_{tot} (W)</td> <td>75</td> <td>250</td> <td>75</td> <td colspan="3"></td> </tr> <tr> <td>R_{th(j-c)} (°C/W)</td> <td>1.66</td> <td>0.5</td> <td>1.66</td> <td colspan="3"></td> </tr> <tr> <td>Package:</td> <td>SMD0.5</td> <td>SMD2</td> <td>SMD0.5</td> <td colspan="3"></td> </tr> <tr> <td colspan="7">Operating Temperature Range (°C): T_{op} = - 55 to +150</td> </tr> </table> | | | | | | | Characteristics: ESCC No. | 5205/026 | 5205/027 | 5205/028 | | | | r _{DS(ON)} (mΩ) @ 25 °C | 130 | 30 | 130 | | | | Maximum Ratings: | | | | | | | I _{DS} (A) | 12.4 | 54 | 12.4 | | | | V _{DS} (V) max. | 250 | 250 | 100 | | | | V _{GS} (V) max. | ± 20 | ± 20 | ± 20 | | | | P _{tot} (W) | 75 | 250 | 75 | | | | R _{th(j-c)} (°C/W) | 1.66 | 0.5 | 1.66 | | | | Package: | SMD0.5 | SMD2 | SMD0.5 | | | | Operating Temperature Range (°C): T _{op} = - 55 to +150 | | | | | | |
| Characteristics: ESCC No. | 5205/026 | 5205/027 | 5205/028 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| r _{DS(ON)} (mΩ) @ 25 °C | 130 | 30 | 130 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Maximum Ratings: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| I _{DS} (A) | 12.4 | 54 | 12.4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| V _{DS} (V) max. | 250 | 250 | 100 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| V _{GS} (V) max. | ± 20 | ± 20 | ± 20 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| P _{tot} (W) | 75 | 250 | 75 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| R _{th(j-c)} (°C/W) | 1.66 | 0.5 | 1.66 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Package: | SMD0.5 | SMD2 | SMD0.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Operating Temperature Range (°C): T _{op} = - 55 to +150 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | <p style="text-align: center;">TRANSISTORS, POWER, MOSFET, N-CHANNEL, BASED ON TYPE BUY **CS***</p> | | | Current validity of Qualification | | Page | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | Certificate 319 | Valid Until August 2014 | 12-05 003-2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |


| | | | | | |
|---|--|--|-----------------------------------|-----------------------|----------|
| Types covered by similarity: | | Remarks: These devices have a TID tested capability of 100kRAD(Si). | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 5000 Detail ESCC 5205/025 | | ST Microelectronics Rennes France | Qualification | CNES | Mar 2013 |
| <p>Characteristics: Variants 01 and 02 are qualified</p> <p>$V_{GS(th)}$ -2 to -4.5V min/max, $V_{DS} \geq V_{GS}$, $I_D = -1mA$</p> <p>$r_{DS(on)}$ 75 mΩ, $V_{GS} = -12V$, $I_D = -17A$ pulsed</p> <p>Maximum Ratings: $I_{DS} (A)$ -34, $T_{case} (^\circ C) = \leq +25$</p> <p>$V_{DS} (V_{dc})$: -100 over T_{op}, $V_{GS} = 0V$</p> <p>$V_{GS} (V_{dc})$: ± 20</p> <p>$R_{th(j-s)}$ 0.71 $^\circ C/W$</p> <p>P_{tot} 176 W at $T_{case} (^\circ C) = \leq +25 C$</p> <p>Package Type: TO-254AA</p> <p>Operating Temperature Range ($^\circ C$): -55 to +150</p> | | | | | |
|  | <p>TRANSISTORS, MOSFET, P-CHANNEL, POWER, TYPE STRH40P10</p> | | Current validity of Qualification | | Page |
| | | | Certificate | Valid Until | 12-06 |
| | | | 326 | March 2015 | 003-1 |

| | | | | | |
|---|--|--|---|-----------------------|--------------------------|
| Types covered by similarity: Variants 01, 02 and 03 are qualified. | | | Remarks: | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 5010 | | Infineon Technologies AG Neubiberg Germany | Qualification | DARA | Jun 1997 |
| Detail ESCC 5611/008 | | | Extension | DLR | Jan 2000 |
| Characteristics for BFY 450 V_{CE0} (V) max. 4.5 V_{CBO} (V) max. 15 I_C (mA) max. 100 I_B (mA) max. 10 h_{FE} min/max. 50/150 @ $V_{CE} = 1.0$ V, $I_C = 20$ mA NF (dB) max. @ 1.8 GHz 2.0 @ $V_{CE} = 2.0$ V, $I_C = 10$ mA f_T (GHz) min. @ 1.0 GHz 18 @ $V_{CE} = 3.0$ V, $I_C = 90$ mA Package: "Micro-X" Total Power Dissipation (P_{tot}) = 450 mW Operating Temperature Range (°C): $T_{op} = -65$ to +175 | | | Extension | DLR | Dec 2003 |
| | | | Requalification | DLR | Mar 2008 |
| | | | Requalification | DLR | Nov 2010 |
| | | | Extension | DLR | Mar 2012 |
| | | |  | | |
| | | | | | Page 12-10 002 |

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|--|-----------------------------------|-----------------------|---------------------------|--|----|--------------------------|--|------|--------------------------|--|-----|-------------------------|--|--|------------------|----------|--|--|-----------|--|------------------------|-----------|---|------------------------|-----------|---|--|--|--|--|
| Types covered by similarity: Variants 01, 02 and 03 are qualified. | | Remarks: - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5010 Detail ESCC 5611/009 | | Infineon Technologies AG Neubiberg Germany | Qualification | DLR | Sep 2012 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics for BFY 640 Variant 03 <table border="0"> <tr> <td>V_{CE0} (V) max.</td> <td></td> <td>4.0</td> </tr> <tr> <td>V_{CB0} (V) max.</td> <td></td> <td>13</td> </tr> <tr> <td>I_C (mA) max.</td> <td></td> <td>50.0</td> </tr> <tr> <td>I_B (mA) max.</td> <td></td> <td>3.0</td> </tr> <tr> <td>h_{FE} min/max</td> <td></td> <td>135/250 @ V_{ce}=3V & I_C=30mA</td> </tr> <tr> <td>MSG/MAG min (dB)</td> <td>@ 1.8GHz</td> <td>23 @ V_{ce}=3V & I_C= 30mA</td> </tr> <tr> <td></td> <td>@ 6.0 GHz</td> <td>12 V_{ce}=3V & I_C= 30mA</td> </tr> <tr> <td>NF_{max} (dB)</td> <td>@ 1.8 GHz</td> <td>< 0.8 @ V_{ce}=3V & I_C=5mA</td> </tr> <tr> <td>NF_{max} (dB)</td> <td>@ 6.0 GHz</td> <td>< 1.4 @ V_{ce}=3V & I_C=5mA</td> </tr> </table> Package: "Micro-X" Total Power Dissipation (P _{tot}) max. = 200 mW Operating Temperature Range (°C): T _{op} = - 65 to +175 | | V _{CE0} (V) max. | | 4.0 | V _{CB0} (V) max. | | 13 | I _C (mA) max. | | 50.0 | I _B (mA) max. | | 3.0 | h _{FE} min/max | | 135/250 @ V _{ce} =3V & I _C =30mA | MSG/MAG min (dB) | @ 1.8GHz | 23 @ V _{ce} =3V & I _C = 30mA | | @ 6.0 GHz | 12 V _{ce} =3V & I _C = 30mA | NF _{max} (dB) | @ 1.8 GHz | < 0.8 @ V _{ce} =3V & I _C =5mA | NF _{max} (dB) | @ 6.0 GHz | < 1.4 @ V _{ce} =3V & I _C =5mA | | | | |
| V _{CE0} (V) max. | | 4.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| V _{CB0} (V) max. | | 13 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| I _C (mA) max. | | 50.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| I _B (mA) max. | | 3.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| h _{FE} min/max | | 135/250 @ V _{ce} =3V & I _C =30mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MSG/MAG min (dB) | @ 1.8GHz | 23 @ V _{ce} =3V & I _C = 30mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | @ 6.0 GHz | 12 V _{ce} =3V & I _C = 30mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| NF _{max} (dB) | @ 1.8 GHz | < 0.8 @ V _{ce} =3V & I _C =5mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| NF _{max} (dB) | @ 6.0 GHz | < 1.4 @ V _{ce} =3V & I _C =5mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | TRANSISTORS, MICROWAVE, SMALL SIGNAL, BIPOLAR, BASED ON TYPE BFY 640 | | Current validity of Qualification | | Page | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | Certificate | Valid Until | 12-10 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | 320 | September 2014 | 003 | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|-----------|---|--------------------|-----------------------------------|----------------|---------------------------|--|-----|---------------------------|--|----|--------------------------|--|-----|--------------------------|--|----|-------------------------|--|--|------------------|----------|---|------------------------|-----------|----|
| Types covered by similarity: Variants 01, 02, 03 and 04 are qualified. | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5010 Detail ESCC 5611/010 | | Infineon Technologies AG Neubiberg Germany | Qualification | DLR | Sep 2012 | | | | | | | | | | | | | | | | | | | | | |
| <p>Characteristics for BFY 650B Variant 04</p> <table border="0"> <tr> <td>V_{CEO} (V) max.</td> <td></td> <td>4.0</td> </tr> <tr> <td>V_{CBO} (V) max.</td> <td></td> <td>13</td> </tr> <tr> <td>I_C (mA) max.</td> <td></td> <td>150</td> </tr> <tr> <td>I_B (mA) max.</td> <td></td> <td>10</td> </tr> <tr> <td>h_{FE} min/max</td> <td></td> <td>100/250 @ V_{CE}=3V & I_C=80mA</td> </tr> <tr> <td>MSG/MAG min (dB)</td> <td>@1.8 GHz</td> <td>18 @ V_{CE}=3V & I_C=80mA</td> </tr> <tr> <td>P_{out} (dBm)</td> <td>@ 1.8 GHz</td> <td>16</td> </tr> </table> <p>Package: "Micro-X"</p> <p>Total Power Dissipation (P_{tot}) max. = 600 mW</p> <p>Operating Temperature Range (°C): T_{op} = - 65 to +175</p> | | | | | | V _{CEO} (V) max. | | 4.0 | V _{CBO} (V) max. | | 13 | I _C (mA) max. | | 150 | I _B (mA) max. | | 10 | h _{FE} min/max | | 100/250 @ V _{CE} =3V & I _C =80mA | MSG/MAG min (dB) | @1.8 GHz | 18 @ V _{CE} =3V & I _C =80mA | P _{out} (dBm) | @ 1.8 GHz | 16 |
| V _{CEO} (V) max. | | 4.0 | | | | | | | | | | | | | | | | | | | | | | | | |
| V _{CBO} (V) max. | | 13 | | | | | | | | | | | | | | | | | | | | | | | | |
| I _C (mA) max. | | 150 | | | | | | | | | | | | | | | | | | | | | | | | |
| I _B (mA) max. | | 10 | | | | | | | | | | | | | | | | | | | | | | | | |
| h _{FE} min/max | | 100/250 @ V _{CE} =3V & I _C =80mA | | | | | | | | | | | | | | | | | | | | | | | | |
| MSG/MAG min (dB) | @1.8 GHz | 18 @ V _{CE} =3V & I _C =80mA | | | | | | | | | | | | | | | | | | | | | | | | |
| P _{out} (dBm) | @ 1.8 GHz | 16 | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | <p>TRANSISTORS, MICROWAVE, SMALL SIGNAL, BIPOLAR, BASED ON TYPES BFY 640B and BFY650B</p> | | Current validity of Qualification | | Page | | | | | | | | | | | | | | | | | | | | |
| | | | | Certificate | Valid Until | 12-10 | | | | | | | | | | | | | | | | | | | | |
| | | | | 321 | September 2014 | 004 | | | | | | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---|---|-----------------------------------|-----------------------|---------------------------|--|----|--------------------------|--|------|--------------------------|--|-----|-------------------------|--|---|------------------|-----------|--|------------------|-----------|--|------------------------|-----------|---|------------------------|-----------|---|--|--|--|--|
| Types covered by similarity: | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5010 Detail ESCC 5611/011 | | Infineon Technologies AG Neubiberg Germany | Qualification | DLR | Sep 2012 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics for BFY 740B Variant 01 <table border="0"> <tr> <td>V_{CEO} (V) max.</td> <td></td> <td>4.0</td> </tr> <tr> <td>V_{CBO} (V) max.</td> <td></td> <td>13</td> </tr> <tr> <td>I_C (mA) max.</td> <td></td> <td>30.0</td> </tr> <tr> <td>I_B (mA) max.</td> <td></td> <td>3.0</td> </tr> <tr> <td>h_{FE} min/max</td> <td></td> <td>185/380 @V_{CE}=3V & I_C=20mA</td> </tr> <tr> <td>MSG/MAG min (dB)</td> <td>@ 1.8 GHz</td> <td>24 @V_{CE}=3V & I_C=20mA</td> </tr> <tr> <td>MSG/MAG min (dB)</td> <td>@ 6.0 GHz</td> <td>17 @V_{CE}=3V & I_C=20mA</td> </tr> <tr> <td>NF_{max} (dB)</td> <td>@ 1.8 GHz</td> <td>≤ 0.75 @V_{CE}=3V & I_C=8mA</td> </tr> <tr> <td>NF_{max} (dB)</td> <td>@ 6.0 GHz</td> <td>≤ 1.15 @V_{CE}=3V & I_C=8mA</td> </tr> </table> Package: "Micro-X" Total Power Dissipation (P _{tot}) max. = 120 mW Operating Temperature Range (°C): T _{op} = - 65 to +175 | | V _{CEO} (V) max. | | 4.0 | V _{CBO} (V) max. | | 13 | I _C (mA) max. | | 30.0 | I _B (mA) max. | | 3.0 | h _{FE} min/max | | 185/380 @V _{CE} =3V & I _C =20mA | MSG/MAG min (dB) | @ 1.8 GHz | 24 @V _{CE} =3V & I _C =20mA | MSG/MAG min (dB) | @ 6.0 GHz | 17 @V _{CE} =3V & I _C =20mA | NF _{max} (dB) | @ 1.8 GHz | ≤ 0.75 @V _{CE} =3V & I _C =8mA | NF _{max} (dB) | @ 6.0 GHz | ≤ 1.15 @V _{CE} =3V & I _C =8mA | | | | |
| V _{CEO} (V) max. | | 4.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| V _{CBO} (V) max. | | 13 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| I _C (mA) max. | | 30.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| I _B (mA) max. | | 3.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| h _{FE} min/max | | 185/380 @V _{CE} =3V & I _C =20mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MSG/MAG min (dB) | @ 1.8 GHz | 24 @V _{CE} =3V & I _C =20mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MSG/MAG min (dB) | @ 6.0 GHz | 17 @V _{CE} =3V & I _C =20mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| NF _{max} (dB) | @ 1.8 GHz | ≤ 0.75 @V _{CE} =3V & I _C =8mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| NF _{max} (dB) | @ 6.0 GHz | ≤ 1.15 @V _{CE} =3V & I _C =8mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | TRANSISTORS, MICROWAVE, SMALL SIGNAL, BIPOLAR, BASED ON TYPE BFY 740B | | Current validity of Qualification | | Page | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | Certificate | Valid Until | 12-10 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | 322 | September 2014 | 005 | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| Types covered by similarity: | | | | Remarks: | | | | | | | | | | | |
|---|-------------|--|--|--------------------|-----------------------------------|-------------|----------|-----|----|----------------|-----|------|-----------------|-----|----------|
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Date | | | | | | | | | |
| Generic ESCC 5010 | | Infineon Technologies AG Neubiberg Germany | | Qualification | DARA | Apr 1994 | | | | | | | | | |
| Detail ESCC 5613/004 | | | | Extension | DLR | Jan 2000 | | | | | | | | | |
| Characteristics (@ 12 GHz): All variants are qualified | | | | Extension | DLR | Dec 2003 | | | | | | | | | |
| | | | | Requalification | DLR | Mar 2008 | | | | | | | | | |
| | | <table border="1"> <thead> <tr> <th></th> <th>NFmin. (dB)</th> <th>Ga (dB)</th> </tr> </thead> <tbody> <tr> <td>5613/004</td> <td>0.8</td> <td>11</td> </tr> <tr> <td>pseudo-morphic</td> <td>1.0</td> <td>10.5</td> </tr> </tbody> </table> | | | NFmin. (dB) | Ga (dB) | 5613/004 | 0.8 | 11 | pseudo-morphic | 1.0 | 10.5 | Requalification | DLR | Nov 2010 |
| | NFmin. (dB) | Ga (dB) | | | | | | | | | | | | | |
| 5613/004 | 0.8 | 11 | | | | | | | | | | | | | |
| pseudo-morphic | 1.0 | 10.5 | | | | | | | | | | | | | |
| | | | | Extension | DLR | Mar 2012 | | | | | | | | | |
| Package: Micro-X Total Power Dissipation (P_{tot}) = 200 mW derated from $+31\text{ }^{\circ}\text{C } T_{amb}$ Operating Temperature Range ($^{\circ}\text{C}$): $T_{stg} = -65$ to $+150$ | | | | | | | | | | | | | | | |
|  | | TRANSISTORS, HIGH ELECTRON MOBILITY, GALLIUM ARSENIDE, MICROWAVE, LOW NOISE, SMALL SIGNAL, BASED ON TYPE CFY 67 | | | Current validity of Qualification | | Page | | | | | | | | |
| | | | | | Certificate | Valid Until | 12-16 | | | | | | | | |
| | | | | 213 E | March 2014 | 001 | | | | | | | | | |

Section 13

Component Type: Wires and Cables

INDEX PAGE 1 of 2

| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|-------------|-------|--|------------------|
| 13-01 | | | Low Frequency | |
| | 13-01-001-1 | 07 P | Polyimide, Types FA-3901-1, FA 3901-2 | Draka Fileca |
| | 13-01-001-2 | 09 N | Polyimide, Types 1871-1872 | Nexans |
| | 13-01-001-3 | 132 L | Polyimide, Types 3901002**B | Axon' Cable |
| | 13-01-003 | 08 P | PTFE, Types MTV-BTV | Nexans |
| | 13-01-003-2 | 292 A | PTFE/Polyimide, Types 3901013**B | Axon' Cable |
| | 13-01-004-1 | 138 K | Polyimide, Type SPC | Gore |
| | 13-01-004-2 | 219 J | Polyimide, Types SPL | Gore |
| | 13-01-004-3 | 268 D | Polyimide, Types 3901019**B | Axon' Cable |
| | 13-01-004-4 | 295 A | Polyimide, Types 3901019 | Leoni |
| | 13-01-005-1 | 159 K | Crosslinked PTFE, Type Silver-Plated Copper | Tyco Electronics |
| | 13-01-005-2 | 267 E | Crosslinked PTFE, Type Silver-Plated Copper | Axon' Cable |
| | 13-01-008 | 215 J | PTFE, Polyimide / PFA Insulated, Type SPP | Gore |
| | 13-01-009 | 216 H | PTFE, Polyimide / PFA Insulated, Shielded, Type SPM | Gore |
| | 13-01-009-2 | 294 A | PTFE, Polyimide/PFA Insulated, Shielded, Type 3901018 | Leoni |
| | 13-01-009-3 | 300 A | PTFE, Polyimide / PFA Insulated, Shielded, Type SPM | Axon' Cable |
| | 13-01-010-1 | 229 H | Polyimide, Insulated, Shielded, Type SPLD, Drain Wire | Gore |
| | 13-01-010-2 | 293 A | Polyimide, Insulated, Shielded, Drain Wire, Types 3901021**B | Axon' Cable |
| | 13-01-010-3 | 296 A | Polyimide, Insultated, Shielded, Drain Wire, Type 3901021 | Leoni |
| | 13-01-011-1 | 257 F | Crosslinked, Modified ETFE, Type Silver-Plated Copper, Lightweight | Tyco Electronics |
| | 13-01-012-1 | 299 A | Fluoropolymer, Lightweight, Based on Type CSWL | Axon' Cable |
| | 13-01-012-2 | 305 A | Fluoropolymer, Lightweight, Based on Type CSWL | Gore |




SECTION 13-**: INDEX OF WIRES AND CABLES


REP005 Updated on 15 Jun 2013



Section 13**Component Type: Wires and Cables
INDEX PAGE 2 of 2**


| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|-------------|-------|---|--------------|
| 13-02 | | | Coaxial, RF, Flexible | |
| | 13-02-001 | 24 Q | PTFE/Polyimide, Type 50 CIS | Nexans |
| | 13-02-002-1 | 255 G | Coaxial, Triaxial, Balanced Shielded Line | Gore |
| | 13-02-002-2 | 298 A | Coaxial, Triaxial, Balanced Shielded Line | Axon' Cable |
| | 13-02-003-1 | 291 A | Symmetric, Quad, Spacewire | Axon' Cable |
| | 13-02-003-2 | 304 A | Symmetric, Quad, Spacewire | Gore |


**SECTION 13-**: INDEX OF WIRES AND CABLES****REP005 Updated on 15 Jun 2013**



| | | | | | |
|---|--|-----------------------------|-----------------------------------|-----------------------|----------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3901 Detail ESCC 3901/001 3901/002 | | Nexans Draveil France | Qualification | CNES | Jan 1979 |
| Characteristics: Medium weight 1871 - n/1871 - 871 (3901/001) Variants 24 to 47 are qualified Light weight 1872 - n/1872 - 872 (3901/002) Variants 31 to 73 are qualified Voltage Rating, maximum (Vrms):600 Temperature Range (°C): -100 to +200 | | | Extension | CNES | Sep 1981 |
| | | | Extension | CNES | Dec 1983 |
| | | | Extension | CNES | Mar 1987 |
| | | | Extension | CNES | Jul 1989 |
| | | | Extension | CNES | Sep 1991 |
| | | | Extension | CNES | Aug 1993 |
| | | | Extension | CNES | Sep 1995 |
| | | | Extension | CNES | Aug 1997 |
| | | | Extension | CNES | Aug 1999 |
| | | Extension | CNES | Aug 2001 | |
| Extension | CNES | Aug 2003 | | | |
| Extension | CNES | Nov 2005 | | | |
| Extension | CNES | May 2008 | | | |
| Extension | CNES | Oct 2011 | | | |
|  | WIRES AND CABLES, LOW FREQUENCY, POLYIMIDE INSULATION BASED ON TYPES 1871 - 1872 | | Current validity of Qualification | | Page |
| | | | Certificate | Valid Until | 13-01 |
| | | 09 N | May 2013 | 001-2 | |



| | | | | | |
|---|---|-------------------------------------|-----------------------------------|-----------------------|----------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3901 Detail ESCC 3901/001 3901/002 | | AXON' CABLE Montmirail France | Qualification | ESTEC | Dec 1985 |
| Characteristics: All variants are qualified. 3009/001: variants 24 to 47 3009/002: variants 31 to 73 Voltage Rating, maximum (Vrms):600 Temperature Range (°C): -100 to +200 | | | Extension | ESTEC | Jul 1988 |
| | | | Extension | ESTEC | Jul 1990 |
| | | | Extension | ESTEC | Nov 1993 |
| | | | Extension | ESTEC | Jan 1996 |
| | | | Extension | ESTEC | May 1999 |
| | | | Extension | CNES | Jun 2002 |
| | | | Extension | CNES | Sep 2004 |
| | | | Extension | CNES | Oct 2004 |
| | | | Extension | CNES | Mar 2007 |
| | | Extension | CNES | Jun 2009 | |
| | Extension | CNES | Jun 2011 | | |
|  | WIRES AND CABLES, LOW FREQUENCY, POLYIMIDE INSULATION, BASED ON TYPES 3901001**B and 3901002**B | | Current validity of Qualification | | Page |
| | | | Certificate | Valid Until | 13-01 |
| | | | 132 L | June 2013 | 001-3 |


| Types covered by similarity: -MTV - BTV -MTV/G - BTV/G -MTV/BF/G - BTV/BF/G | | Remarks: | | |
|---|--|-----------------------------|-----------------------------------|----------|
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3901 Detail ESCC 3901/013 | Nexans Draveil France | Qualification | CNES | Jan 1979 |
| | | Extension | CNES | Sep 1981 |
| Characteristics: Variants 01 to 77 are qualified Voltage Rating, maximum (Vrms):600 Temperature Range (°C): -100 to +200 | | Extension | CNES | Dec 1983 |
| | | Extension | CNES | Mar 1987 |
| | | Extension | CNES | Jul 1989 |
| | | Extension | CNES | Sep 1991 |
| | | Extension | CNES | Aug 1993 |
| | | Extension | CNES | Sep 1995 |
| | | Extension | CNES | Aug 1997 |
| | | Extension | CNES | Aug 1999 |
| | | Extension | CNES | Aug 2001 |
| | | Extension | CNES | Aug 2003 |
| | | Extension | CNES | Nov 2005 |
| | | Extension | CNES | May 2008 |
| | | Extension | CNES | Jan 2011 |
| | | Extension | CNES | Feb 2013 |
|  ESCC European Space Components Coordination  QPL | WIRES AND CABLES, LOW FREQUENCY, PTFE/POLYIMIDE INSULATION, BASED ON TYPES MTV-BTV | | Current validity of Qualification | |
| | Certificate 08 P | Valid Until May 2014 | Page 13-01 003 | |


| | | | | |
|---|--|-----------------------------------|------------------------------|--------------------------|
| Types covered by similarity: | | Remarks: : | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3901 Detail ESCC 3901/013 | AXON' CABLE Montmirail France | Qualification Extension | CNES CNES | Jun 2009 Jun 2011 |
| <p>Characteristics:</p> <p>Variants 01 to 77 are qualified</p> <p>Voltage Rating, maximum (Vrms):600 Temperature Range (°C): -100 to +200</p> | | | | |
|  | <p>WIRES AND CABLES, LOW FREQUENCY, PTFE/POLYIMIDE INSULATION, BASED ON TYPES 3901013**B</p> | Current validity of Qualification | | Page |
| | | Certificate 292 A | Valid Until June 2013 | 13-01 003-02 |


| | | | | |
|--|--|-----------------------------------|-----------------------|----------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3901 | W.L. Gore & Co Pleinfeld Germany | Qualification | DLR | Aug 1986 |
| Detail ESCC 3901/009 | | Extension | ESTEC | Dec 1988 |
| | | Extension | DARA | Jul 1991 |
| | | Extension | DARA | Aug 1993 |
| | | Extension | DARA | Feb 1996 |
| | | Extension | DLR | Feb 1998 |
| | | Requalification | DLR | Nov 2004 |
| | | Extension | DLR | Apr 2007 |
| | | Extension | DLR | May 2009 |
| Extension | | DLR | May 2011 | |
| Extension | DLR | June 2013 | | |
| Characteristics: Variants 01-66 are qualified Voltage Rating, maximum (Vrms):600 Temperature Range (°C): -200 to +200 | | | | |
|  | WIRES AND CABLES, LOW FREQUENCY, POLYIMIDE INSULATION, BASED ON TYPES SPC 2110 | Current validity of Qualification | | Page |
| | | Certificate | Valid Until | 13-01 |
| | | 138 K | May 2015 | 004-1 |



| | | | | | |
|--|---|--------------------|-----------------------------------|-------------|-------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date | |
| Generic ESCC 3901 | W.L. Gore & Co Pleinfeld Germany | Qualification | DARA | Nov 1994 | |
| Detail ESCC 3901/019 | | Extension | DARA | Nov 1996 | |
| | | Extension | DLR | Oct 1998 | |
| | | Extension | DLR | Oct 2000 | |
| | | Extension | DLR | Nov 2002 | |
| | | Extension | DLR | Nov 2004 | |
| | | Extension | DLR | Oct 2006 | |
| | | Extension | DLR | Nov 2008 | |
| | | Extension | DLR | Dec 2010 | |
| | | Extension | DLR | Nov 2012 | |
| Characteristics: Variants 01-94 are qualified Voltage Rating, maximum (Vrms):600 Temperature Range (°C): -200 to +200 | | | | | |
|   | WIRES AND CABLES, LOW FREQUENCY, POLYIMIDE INSULATION, BASED ON TYPES SPL | | Current validity of Qualification | | Page |
| | | | Certificate | Valid Until | 13-01 |
| | | 219 J | November 2014 | 004-2 | |


| | | | | |
|---|---|---|--|--|
| Types covered by similarity: | | Remarks: : | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3901 Detail ESCC 3901/019 | AXON' CABLE Montmirail France | Qualification Extension Extension Extension Extension | CNES CNES CNES CNES CNES | Jun 2002 Sep 2004 Mar 2007 Jun 2009 Jun 2011 |
| <p>Characteristics:</p> <p>All variants are qualified with the exception of variants 01, 09, 17, 24, 25, 32, 48, 56, 64, 72, and 79</p> <p>AWG 12 to 28 inclusive are qualified</p> <p>Voltage Rating, maximum (Vrms):600</p> <p>Temperature Range (°C): -200 to +200</p> | | | | |
|   | <p>WIRES AND CABLES, LOW FREQUENCY, POLYIMIDE INSULATION, BASED ON TYPES 3901019**B</p> | Current validity of Qualification | | Page |
| | | Certificate | Valid Until | 13-01 |
| | | 268 D | June 2013 | 004-3 |


| | | | | |
|---|--|-----------------------------------|---------------------------------|--------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3901 Detail ESCC 3901/019 | LEONI Special Cables GmbH Friesoythe Germany | Qualification Extension | DLR DLR | Oct 2009 Apr 2012 |
| Characteristics: All variants are qualified with the exception of variants 01, 09, 17, 24, 25, 32, 48, 56, 64, 72, and 79 Conductor according to ISO 2635 (except AWG 28) AWG 12 to 28 inclusive are qualified For silver coated strands the silver thickness shall be 2.0µm minimum Voltage Rating, maximum (V_{rms}):600 Temperature Range (°C): -200 to +200 | | | | |
|  | WIRES AND CABLES, LOW FREQUENCY, POLYIMIDE INSULATION, BASED ON TYPE 3901019 | Current validity of Qualification | | Page |
| | | Certificate 295 A | Valid Until October 2013 | 13-01 004-4 |


| | | | | |
|---|---|--|--|--|
| Types covered by similarity: | | Remarks: : This product is not intended for human space flight applications. | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3901 Detail ESCC 3901/012 | AXON' CABLE Montmirail France | Qualification Extension Extension Extension Extension Extension | CNES CNES CNES CNES CNES CNES | Mar 2002 Feb 2003 Sep 2004 Mar 2007 Jun 2009 Jun 2011 |
| <p>Characteristics:</p> <p>All variants are qualified except those variants based on AWG 30</p> <p>Wire code ISO 2635</p> <p>Voltage Rating, maximum (Vrms) : 600</p> <p>Temperature Range (°C): -100 to +200</p> | | | | |
|  | <p>WIRES AND CABLES, LOW FREQUENCY, 600V, SILVER-PLATED COPPER, EXTRUDED CROSSLINKED FLUOROPOLYMER INSULATION, BASED ON TYPE 3901012**B</p> | Current validity of Qualification | | Page |
| | | Certificate 267 E | Valid Until June 2013 | 13-01 005-2 |


| | | | | |
|---|---|-----------------------------------|-----------------------|----------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3901 | W.L. Gore & Co. Pleinfeld Germany | Qualification | DARA | Jul 1994 |
| Detail ESCC 3901/018 | | Extension | DARA | Sep 1997 |
| | | Extension | DLR | Aug 1999 |
| | | Extension | DLR | Aug 2001 |
| | | Extension | DLR | Aug 2003 |
| | | Extension | DLR | Nov 2005 |
| | | Extension | DLR | Feb 2008 |
| Characteristics: Variants 01 to 88 are qualified. Voltage Rating, maximum (V^{rms}) : 600 Temperature Range (°C): -200 to +200 Expanded PTFE, extruded polyimide/ FEP, sintered PTFE insulated wires. Expanded PTFE, extruded polyimide/fluorothermoplast insulated cables, shielded and jacketed. | | Extension | DLR | Mar 2010 |
| | Extension | DLR | Mar 2012 | |
|  | WIRES AND CABLES, LOW FREQUENCY, INSULATED, POLYIMIDE/FLUOROTHERMOPLAST, BASED ON TYPE SPM | Current validity of Qualification | | Page |
| | | Certificate | Valid Until | 13-01 |
| | | 216 H | March 2014 | 009 |


| | | | | |
|--|---|-----------------------------------|---------------------------------|--------------------------|
| Types covered by similarity: . | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3901 Detail ESCC 3901/018 | LEONI Special Cables GmbH Friesoythe Germany | Qualification Extension | DLR DLR | Oct 2009 Apr 2012 |
| Characteristics: Variants 01 to 88 are qualified. Voltage Rating, maximum (V_{rms}) : 600 Temperature Range (°C): -200 to +200 Expanded PTFE, extruded polyimide/ FEP, sintered PTFE insulated wires. Expanded PTFE, extruded polyimide/fluorothermoplast insulated cables, shielded and jacketed. Conductor silver thickness shall be 2.0µm minimum | | | | |
|   | WIRES AND CABLES, LOW FREQUENCY, INSULATED, POLYIMIDE/FLUOROTHERMOPLAST, BASED ON TYPE 3901018 | Current validity of Qualification | | Page |
| | | Certificate 294 A | Valid Until October 2013 | 13-01 009-2 |


| | | | | |
|---|---|-----------------------------------|-----------------------|--------------------------|
| Types covered by similarity: | | Remarks: : | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3901 Detail ESCC 3901/018 | AXON' CABLE Montmirail France | Qualification Extension | CNES CNES | Dec 2009 Jun 2011 |
| <p>Characteristics:</p> <p>All variants are qualified except those based on AWG 30 and 32 are not qualified.</p> <p>Voltage Rating, maximum (V_{rms}) : 600</p> <p>Temperature Range (°C): -200 to +200</p> <p>Expanded PTFE, extruded polyimide/ FEP, sintered PTFE insulated wires. Expanded PTFE, extruded polyimide/fluorothermoplast insulated cables, shielded and jacketed.</p> | | | | |
|  | <p>WIRES AND CABLES, LOW FREQUENCY, INSULATED, POLYIMIDE/FLUOROTHERMOPLAST, BASED ON TYPE SPM</p> | Current validity of Qualification | | Page |
| | | Certificate | Valid Until | 13-01 |
| | | 300 A | December 2013 | 009-03 |


| | | | | |
|---|--|--|---|---|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3901 Detail ESCC 3901/021 | W.L. Gore & Co. Pleinfeld Germany | Qualification Extension Extension Extension Extension Extension Extension Extension Extension Extension Extension Extension | DARA DLR DLR DLR DLR DLR DLR DLR DLR DLR DLR DLR | Feb1996 Feb 1998 Feb 2000 Feb 2002 Feb 2004 Feb 2006 Mar 2008 Apr 2010 Apr 2012 |
| <p>Characteristics:</p> <p>All variants (01 to 41) are qualified</p> <p>Voltage Rating, maximum (Vrms) : 600</p> <p>Temperature Range (°C): -200 to +200</p> <p>.</p> | | | | |
|  | <p>POLYIMIDE INSULATED SHIELDED CABLES WITH DRAIN WIRE,</p> <p>LOW FREQUENCY, BASED ON TYPE SPLD</p> | Current validity of Qualification | | Page |
| | | Certificate 229 H | Valid Until April 2014 | 13-01 010-1 |


| | | | | |
|---|---|-----------------------------------|------------------------------|--------------------------|
| Types covered by similarity: | | Remarks: : | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3901 Detail ESCC 3901/021 | AXON' CABLE Montmirail France | Qualification Extension | CNES CNES | Jun 2009 Jun 2011 |
| <p>Characteristics:</p> <p>All variants are qualified except those based on AWG 30.</p> <p>Voltage Rating, maximum (Vrms) : 600 Temperature Range (°C): -200 to +200</p> <p>.</p> | | | | |
|  | <p>POLYIMIDE INSULATED SHIELDED CABLES WITH DRAIN WIRE, LOW FREQUENCY, BASED ON TYPES 3901021**B</p> | Current validity of Qualification | | Page |
| | | Certificate 293 A | Valid Until June 2013 | 13-01 010-2 |


| | | | | |
|---|---|-----------------------------------|---------------------------------|--------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3901 Detail ESCC 3901/021 | LEONI Special Cables GmbH Friesoythe Germany | Qualification Extension | DLR DLR | Oct 2009 Apr 2012 |
| <p>Characteristics:</p> <p>All variants 01 to 41 are qualified</p> <p>Voltage Rating, maximum (Vrms) : 600 Temperature Range (°C): -200 to +200</p> | | | | |
|  | <p>POLYIMIDE INSULATED SHIELDED CABLES WITH DRAIN WIRE, LOW FREQUENCY, BASED ON TYPE 3901021</p> | Current validity of Qualification | | Page |
| | | Certificate 296 A | Valid Until October 2013 | 13-01 010-3 |


| | | | | |
|--|---|--|--|--|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3901 Detail ESCC 3901/020 ESCC 3901/022 | Tyco Electronics Dorcan, Swindon England | Qualification Extension Extension Extension Extension Extension | DERA QinetiQ QinetiQ BNSC BNSC UK Space Agency UK Space Agency | Oct 1999 Jan 2002 Jan 2005 Feb 2007 Feb 2009 Jan 2011 Feb 2013 |
| <p>Characteristics: 3901/020: All variants (01 - 80) are qualified 3901/022: All variants (01 - 72) are qualified.</p> <p>Wires and Cables variants consist of 1, 2, 3 and 4 cores with and without jackets and shields</p> <p>ESCC Detail Specification No. 3901/020 cables are silver-plated copper braided, and ESCC Detail Specification No. 3901/022 cables are silver-plated copper spiral shielded, Wire sizes are in accordance with ISO 2635.</p> <p>Maximum voltage: 600 Vrms Operating temperature range (°C): -100 to +200</p> | | Extension | UK Space Agency | Feb 2013 |
|  | <p>WIRES AND CABLES, LOW FREQUENCY, 600V, SILVER-PLATED COPPER, EXTRUDED CROSSLINKED MODIFIED ETFE, LIGHTWEIGHT</p> | Current validity of Qualification | | Page |
| | | Certificate 257 F | Valid Until February 2015 | 13-01 011-1 |


| | | | | |
|--|---|--|----------------------------------|--|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3901 Detail ESCC 3901/024 | AXON' CABLE Montmirail France | Qualification Extension | CNES CNES | Dec 2009 Jun 2011 |
| <p>Characteristics:</p> <p>All variants are qualified except for those variants based on AWG 30</p> <p>Wires and Cables variants consist of 1, 2, 3 and 4 cores with and without jackets and shields</p> <p>Maximum voltage: 600 Vrms Operating temperature range (°C): -200 to +200</p> | | | | |
|  | <p>WIRES AND CABLES, LOW FREQUENCY, FLUROPOLYMER INSULATION, 600V, BASED ON TYPE CSWL</p> | Current validity of Qualification | | Page |
| | | Certificate 299 A | Valid Until December 2013 | 13-01 012-1 |

| | | | | |
|---|---|--|---------------------------------|--|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3901 Detail ESCC 3901/024 | W.L. Gore Pleinfeld Germany | Qualification Extension | DLR DLR | Jan 2011 Jan 2013 |
| <p>Characteristics:</p> <p>Variants 01 to 64 inclusive are qualified The specification contains 64 variants with several wire sizes, single wires and cables with several cores, either shielded or unshielded.</p> <p>Cable construction: 1, 2, 3 and 4 twisted wires are in one core with or without shield</p> <p>Maximum voltage: 600 Vrms Operating temperature range (°C): -200 to +200</p> | | | | |
|  | <p>WIRES AND CABLES, LOW FREQUENCY, FLUROPOLYMER INSULATION, 600V, BASED ON TYPE CSWL</p> | Current validity of Qualification | | Page |
| | | Certificate 305 A | Valid Until January 2015 | 13-01 012-2 |

| | | | | |
|--|---|-----------------------------------|-----------------------|-----------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3902 | Nexans Draveil France | Qualification | CNES | July 1979 |
| Detail ESCC 3902/001 | | Extension | CNES | Feb 1982 |
| | | Extension | CNES | July 1984 |
| | | Extension | CNES | Mar 1987 |
| | | Extension | CNES | July 1989 |
| | | Extension | CNES | Sept 1991 |
| | | Extension | CNES | Aug 1993 |
| | | Extension | CNES | Sep 1995 |
| | | Extension | CNES | Aug 1997 |
| | | Extension | CNES | Jan 1998 |
| | | Extension | CNES | Aug 1999 |
| | | Extension | CNES | Aug 2001 |
| | | Extension | CNES | Aug 2003 |
| | | Extension | CNES | Nov 2005 |
| Extension | CNES | May 2008 | | |
| Extension | CNES | Jan 2011 | | |
| Extension | CNES | Feb 2013 | | |
| Characteristics: Variants 01, 02, and 03 are qualified Miniature flexible 50 ohm coaxial cable PTFE Dielectric Polyimide Jacketed, Double Shield and Shielded / Jacketed Maximum voltage: 900 Vrms Operating temperature range (°C): -80 to +200 (-100 for variant 01) | | | | |
|  | WIRES AND CABLES, RF COAXIAL, PTFE/POLYIMIDE INSULATION, BASED ON TYPE 50 CIS | Current validity of Qualification | | Page |
| | | Certificate | Valid Until | 13-02 |
| | | 24 Q | May 2014 | 001 |


| | | | | | | | | | | | | |
|---|---|--|--|--|-----|-----------------|-----|--------------------|-----|--|--|--|
| Types covered by similarity: | | Remarks: | | | | | | | | | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date | | | | | | | | |
| Generic ESCC 3902 Detail ESCC 3902/002 | W.L. Gore Pleinfeld Germany | Qualification Extension Extension Extension Extension Extension Extension Extension | DLR DLR DLR DLR DLR DLR DLR DLR | Jan 1999 Feb 2001 Feb 2003 Mar 2005 Mar 2007 May 2009 May 2010 Jun 2012 | | | | | | | | |
| <p>Characteristics:</p> <p>Variants 03 to 06, 10 to 13 and 20 to 30 are qualified</p> <p>Variants encompass coaxial, triaxial, and balanced shielded line</p> <p>Operating Voltage (Continuous), maximum ratings, (Vrms):</p> <table> <tr> <td>Variants 03</td> <td>180</td> </tr> <tr> <td>Variants 04, 10, 21, 22, 23, 24</td> <td>200</td> </tr> <tr> <td>Variants 06, 25</td> <td>250</td> </tr> <tr> <td>All Other Variants</td> <td>300</td> </tr> </table> <p>AWG Range: 20, 22, 24, 26, 28, 30 dependent on variant</p> <p>Temperature range (°C): -200 to +180</p> | | Variants 03 | 180 | Variants 04, 10, 21, 22, 23, 24 | 200 | Variants 06, 25 | 250 | All Other Variants | 300 | | | |
| Variants 03 | 180 | | | | | | | | | | | |
| Variants 04, 10, 21, 22, 23, 24 | 200 | | | | | | | | | | | |
| Variants 06, 25 | 250 | | | | | | | | | | | |
| All Other Variants | 300 | | | | | | | | | | | |
|  | <p>WIRES AND CABLES, RADIO FREQUENCY, FLEXIBLE, COAXIAL, TRIAxIAL AND SYMMETRIC, BASED ON TYPES GCX, GTX, GSC AND GBL</p> | Current validity of Qualification | | Page | | | | | | | | |
| | | Certificate 255 G | Valid Until May 2014 | 13-02 002-1 | | | | | | | | |


| | | | | | | | | | | | | |
|---|---|-----------------------------------|----------------------------------|-----------------------------|-----|-----------------|-----|--------------------|-----|--|--|--|
| Types covered by similarity: | | Remarks: | | | | | | | | | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date | | | | | | | | |
| Generic ESCC 3902 Detail ESCC 3902/002 | AXON' CABLE Montmirail France | Qualification Extension | CNES CNES | Dec 2009 Jun 2011 | | | | | | | | |
| <p>Characteristics:</p> <p>All variants are qualified except variants 13 and 22 are not qualified</p> <p>Variants encompass coaxial, triaxial, and balanced shielded line</p> <p>Operating Voltage (Continuous), maximum ratings, (Vrms):</p> <table> <tr> <td>Variants 03</td> <td>180</td> </tr> <tr> <td>Variants 04, 10, 21, 23, 24</td> <td>200</td> </tr> <tr> <td>Variants 06, 25</td> <td>250</td> </tr> <tr> <td>All Other Variants</td> <td>300</td> </tr> </table> <p>AWG Range: 20, 22, 24, 26, 28 dependent on variant</p> <p>Temperature range (°C): -200 to +180</p> | | Variants 03 | 180 | Variants 04, 10, 21, 23, 24 | 200 | Variants 06, 25 | 250 | All Other Variants | 300 | | | |
| Variants 03 | 180 | | | | | | | | | | | |
| Variants 04, 10, 21, 23, 24 | 200 | | | | | | | | | | | |
| Variants 06, 25 | 250 | | | | | | | | | | | |
| All Other Variants | 300 | | | | | | | | | | | |
|  | <p>WIRES AND CABLES, RADIO FREQUENCY, FLEXIBLE, COAXIAL, TRIAxIAL AND SYMMETRIC, BASED ON TYPE 3902/002</p> | Current validity of Qualification | | Page | | | | | | | | |
| | | Certificate 298 A | Valid Until December 2013 | 13-02 002-2 | | | | | | | | |


| | | | | |
|--|---|-----------------------------------|-----------------------|--------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3902 Detail ESCC 3902/003 | W.L. Gore Pleinfeld Germany | Qualification Extension | DLR DLR | Jan 2011 Dec 2012 |
| Characteristics: Variant 01 AWG 28/07 (white) and Variant 02 AWG 26/07 (blue) are qualified, 100 Ω Data Rate, Operating Voltage (Continuous), Current Variant 01 100Mb/s—400 MHz 200V—1.5A Variant 02 200Mb/s—400 MHz 200V— 2.5A Temperature range (°C): -200 to +180 | | | | |
|  | WIRES AND CABLES, SPACEWIRE, ROUND, QUAD SYMMETRIC, FLEXIBLE, BASED ON TYPE SPACEWIRE | Current validity of Qualification | | Page |
| | | Certificate | Valid Until | 13-02 |
| | | 304 A | January 2015 | 003-2 |

Section 14**Component Type: Miscellaneous**

| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|----------------|-------|----------------------------|--------------|
| 14-16-99 | | | Switches | |
| | 14-16-99-003 | 275 C | Thermostatic, Bimetallic | COMEPA |
| 14-30-10 | | | Passive Devices, RF | |
| | 14-30-10-002-2 | 185 F | Coaxial Loads, 0 to 22 GHz | Radiall |
| | 14-30-10-004 | 178 G | Attenuators, Type R413 | Radiall |

| | | | | | |
|---|---|--|-----------------------------------|--------------------------|----------------------|
| Types covered by similarity: | | Remarks: Extension of qualification is pending the resolution of a nonconformance. | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3702 Detail 3702/001 | | COMEPA BAGNOLET France | Qualification | CNES | Mar 2004 |
| | | | Requalification | CNES | Aug 2005 |
| | | | Extension | CNES | Jun 2008 |
| | | | Extension | CNES | Jul 2010 |
| Characteristics: Variants 01 to 03 are qualified Range of Components: Grade 1 and Grade Y Maximum Ratings: Rated Current (I _R): 4 A (30 Vdc resistive) Operating Temperature Range (°C), -50 to +150 | | | | | |
|  | SWITCHES, THERMOSTATIC, BIMETALLIC, SPST, OPENING CONTACT, BASED ON TYPE TH 47 | | Current Validity of Qualification | | Page 14-16-99-003 |
| | | | Certificate 275 C | Valid Until June 2012 | |

| Types covered by similarity: | | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|------|--|------|--------------------|-----------------------------------|-------------------------------|--------------------------------|------------------------------|----------|----------|------|---|----|------|----------|--|--|--|----------------------------|-------------------------------|--------------------------------|------------------------------|---|------|------|------|------|---|------|------|------|------|-----------|------|----------|
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 3403 Detail 3403/006 | | RADIALL Saint-Quentin-Fallavier France | | Qualification | CNES | Jul 1992 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics: All variants are qualified. 50 ohms DC to 22 GHz <table border="1"> <thead> <tr> <th>Type</th> <th>Detail Spec.</th> <th>Frequency Range (GHz)</th> <th>Rated Pin (W)</th> <th>Impedance (Ω)</th> </tr> </thead> <tbody> <tr> <td>3403/006</td> <td>3403/006</td> <td>0-22</td> <td>1</td> <td>50</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th rowspan="2">Type</th> <th colspan="4">VSWR max</th> </tr> <tr> <th>$0 < f(\text{GHz}) \leq 4$</th> <th>$4 < f(\text{GHz}) \leq 12.4$</th> <th>$12.4 < f(\text{GHz}) \leq 18$</th> <th>$18 < f(\text{GHz}) \leq 22$</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>1.05</td> <td>1.15</td> <td>1.20</td> <td>1.30</td> </tr> <tr> <td>2</td> <td>1.05</td> <td>1.15</td> <td>1.20</td> <td>1.25</td> </tr> </tbody> </table> Operating Temperature Range ($^{\circ}\text{C}$), -55 to +125 | | | | Type | Detail Spec. | Frequency Range (GHz) | Rated Pin (W) | Impedance (Ω) | 3403/006 | 3403/006 | 0-22 | 1 | 50 | Type | VSWR max | | | | $0 < f(\text{GHz}) \leq 4$ | $4 < f(\text{GHz}) \leq 12.4$ | $12.4 < f(\text{GHz}) \leq 18$ | $18 < f(\text{GHz}) \leq 22$ | 1 | 1.05 | 1.15 | 1.20 | 1.30 | 2 | 1.05 | 1.15 | 1.20 | 1.25 | Extension | CNES | Jun 1997 |
| | | | | Type | Detail Spec. | Frequency Range (GHz) | Rated Pin (W) | Impedance (Ω) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | 3403/006 | 3403/006 | 0-22 | 1 | 50 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | Type | VSWR max | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | $0 < f(\text{GHz}) \leq 4$ | $4 < f(\text{GHz}) \leq 12.4$ | $12.4 < f(\text{GHz}) \leq 18$ | $18 < f(\text{GHz}) \leq 22$ | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | 1 | 1.05 | 1.15 | 1.20 | 1.30 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | 1.05 | 1.15 | 1.20 | 1.25 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | CNES | Jan 2002 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | CNES | Apr 2005 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | CNES | Mar 2008 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | CNES | Sep 2010 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Extension | CNES | Jun 2012 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | PASSIVE DEVICES, R.F. COAXIAL LOADS, 0-22 GHz BASED ON TYPE R404 | | | Current Validity of Qualification | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | Certificate | Valid Until | Page | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | 185 F | March 2014 | 14-30-10 002-2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | | |
|---|--|--|--|--|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Date |
| Generic ESCC 3403 Detail 3403/005 | RADIALL Saint-Quentin-Fallavier France | Qualification Extension Extension Extension Extension Extension Extension Extension | CNES CNES CNES CNES CNES CNES CNES CNES | Jan 1991 Jan 1994 Jun 1997 Mar 2002 Apr 2005 Mar 2008 Sep 2010 Jun 2012 |
| Characteristics: Variants 01 to 31 Frequency range (GHz): 0 - 22 Attenuation (dB): 0 - 20 Operating Temperature Range (°C), -55 to +125 | | | | |
|  | R.F. ATTENUATORS FIXED, COAXIAL BASED ON TYPE R413 | Current Validity of Qualification | | Page |
| | | Certificate | Valid Until | 14-30-10 |
| | | 178 G | March 2014 | 004 |

Section 18**Component Type: Optoelectronics**

| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|----------|-------|---|--------------|
| | | | Currently there are no qualified sources of Optoelectronics | |



SECTION 18-: INDEX OF OPTOELECTRONICS**

REP005 Updated on 15 Jun 2013