

# European Preferred Parts List

01 CAPACITORS | 01 CERAMIC

| EPPL Part      | Part Type    | Description   | Detail Specification      | Package    | Manufacturer(s) | Remarks                 |            |          |           |                           |             |            |          |                           |            |            |            |                           |               |          |               |              |                |          |             |          |            |                   |                     |             |  |
|----------------|--------------|---|---------------------------|------------|-----------------|-------------------------|------------|----------|-----------|---------------------------|-------------|------------|----------|---------------------------|------------|------------|------------|---------------------------|---------------|----------|---------------|--------------|----------------|----------|-------------|----------|------------|-------------------|---------------------|-------------|--|
| 1              | CH (Type II) | <p>Ceramic dielectric, Fixed, high capacitance.</p> <table border="1"> <thead> <tr> <th>Cap.Range (uF)</th> <th>Tol. (%)</th> <th>Rated Volt. (V)</th> <th>Temp.Characteristic (%)</th> </tr> </thead> <tbody> <tr> <td>0.33 to 39</td> <td>10/20</td> <td>200</td> <td>±20(Vt=0V), -50+30(Vt=Ur)</td> </tr> <tr> <td>1.2 to 150</td> <td>10/20</td> <td>100</td> <td>±20(Vt=0V), -50+30(Vt=Ur)</td> </tr> <tr> <td>1.8 to 180</td> <td>10/20</td> <td>50</td> <td>±20(Vt=0V), -50+30(Vt=Ur)</td> </tr> </tbody> </table> <p>Size (max. mm.): 40.6 x 24 x 14.8 (Style L case)<br/>                     Operating temperature range (°C.): -55 to +125</p>   | Cap.Range (uF)            | Tol. (%)   | Rated Volt. (V) | Temp.Characteristic (%) | 0.33 to 39 | 10/20    | 200       | ±20(Vt=0V), -50+30(Vt=Ur) | 1.2 to 150  | 10/20      | 100      | ±20(Vt=0V), -50+30(Vt=Ur) | 1.8 to 180 | 10/20      | 50         | ±20(Vt=0V), -50+30(Vt=Ur) | ESCC 3001/030 | SMD      | • AVX Limited |              |                |          |             |          |            |                   |                     |             |  |
| Cap.Range (uF) | Tol. (%)     | Rated Volt. (V)   | Temp.Characteristic (%)   |            |                 |                         |            |          |           |                           |             |            |          |                           |            |            |            |                           |               |          |               |              |                |          |             |          |            |                   |                     |             |  |
| 0.33 to 39     | 10/20        | 200   | ±20(Vt=0V), -50+30(Vt=Ur) |            |                 |                         |            |          |           |                           |             |            |          |                           |            |            |            |                           |               |          |               |              |                |          |             |          |            |                   |                     |             |  |
| 1.2 to 150     | 10/20        | 100   | ±20(Vt=0V), -50+30(Vt=Ur) |            |                 |                         |            |          |           |                           |             |            |          |                           |            |            |            |                           |               |          |               |              |                |          |             |          |            |                   |                     |             |  |
| 1.8 to 180     | 10/20        | 50  | ±20(Vt=0V), -50+30(Vt=Ur) |            |                 |                         |            |          |           |                           |             |            |          |                           |            |            |            |                           |               |          |               |              |                |          |             |          |            |                   |                     |             |  |
| 2              | CNC 3*       | <p>Ceramic dielectric, Fixed, high capacitance.</p> <p>Tolerance: 10, 20%</p> <p>Capacitance ranges (uf):</p> <table border="1"> <thead> <tr> <th></th> <th>16V</th> <th>25V</th> <th></th> </tr> </thead> <tbody> <tr> <td>CNC31PE</td> <td>2.2 - 12</td> <td>1.2 - 6.8</td> <td>1 to 3 chips</td> </tr> <tr> <td>CNC32PE</td> <td>2.7 - 15</td> <td>1.8 - 10</td> <td>1 to 3 chips</td> </tr> <tr> <td>CNC33PE</td> <td>4.7 - 33</td> <td>3.3 - 22</td> <td>1 to 4 chips</td> </tr> <tr> <td>CNC34PE</td> <td>8.2 - 68</td> <td>5.6 - 39</td> <td>1 to 4 chips</td> </tr> </tbody> </table> <p>Size (max. mm.): 12 x 12.5 x H;<br/>                     H = 2.5mm (case A), 4.8mm (case B), 7mm (case C), 9.5mm (case D)</p> <p>Operating temperature range (°C.): -55 to +125</p>  |                           | 16V        | 25V             |                         | CNC31PE    | 2.2 - 12 | 1.2 - 6.8 | 1 to 3 chips              | CNC32PE     | 2.7 - 15   | 1.8 - 10 | 1 to 3 chips              | CNC33PE    | 4.7 - 33   | 3.3 - 22   | 1 to 4 chips              | CNC34PE       | 8.2 - 68 | 5.6 - 39      | 1 to 4 chips | EFD 635.03.390 | DIL, SMD | • EUROFARAD |          |            |                   |                     |             |  |
|                | 16V          | 25V   |                           |            |                 |                         |            |          |           |                           |             |            |          |                           |            |            |            |                           |               |          |               |              |                |          |             |          |            |                   |                     |             |  |
| CNC31PE        | 2.2 - 12     | 1.2 - 6.8   | 1 to 3 chips              |            |                 |                         |            |          |           |                           |             |            |          |                           |            |            |            |                           |               |          |               |              |                |          |             |          |            |                   |                     |             |  |
| CNC32PE        | 2.7 - 15     | 1.8 - 10  | 1 to 3 chips              |            |                 |                         |            |          |           |                           |             |            |          |                           |            |            |            |                           |               |          |               |              |                |          |             |          |            |                   |                     |             |  |
| CNC33PE        | 4.7 - 33     | 3.3 - 22  | 1 to 4 chips              |            |                 |                         |            |          |           |                           |             |            |          |                           |            |            |            |                           |               |          |               |              |                |          |             |          |            |                   |                     |             |  |
| CNC34PE        | 8.2 - 68     | 5.6 - 39  | 1 to 4 chips              |            |                 |                         |            |          |           |                           |             |            |          |                           |            |            |            |                           |               |          |               |              |                |          |             |          |            |                   |                     |             |  |
| 2              | CNC 5*       | <p>Ceramic dielectric, Fixed, high capacitance.</p> <p>Tolerance: 10, 20%</p> <p>Capacitance ranges (uf):</p> <table border="1"> <thead> <tr> <th></th> <th>50V</th> <th>100V</th> <th>200V</th> <th>500V</th> </tr> </thead> <tbody> <tr> <td>CNC53PE</td> <td>1.8 - 12</td> <td>1.0 - 10</td> <td>0.27 - 2.70</td> <td>0.10 - 1.0</td> </tr> <tr> <td>CNC54PE</td> <td>3.3 - 22</td> <td>1.8 - 15</td> <td>0.47 - 3.9</td> <td>0.22 - 1.5</td> </tr> <tr> <td>CNC55PE</td> <td>6.8 - 39</td> <td>2.7 - 33</td> <td>1.0 - 10</td> <td>0.33 - 3.3</td> </tr> <tr> <td>CNC56PE</td> <td>10 - 68</td> <td>4.7 - 47</td> <td>1.8 - 12</td> <td>0.47 - 5.6</td> </tr> </tbody> </table> <p>Size (max. mm.): 21.6 x 16.6 x H; H = 4mm (case A), 8mm (case B), 12mm (case C), 16mm (case D)</p> <p>Operating temperature range (°C.): -55 to +125</p> |                           | 50V        | 100V            | 200V                    | 500V       | CNC53PE  | 1.8 - 12  | 1.0 - 10                  | 0.27 - 2.70 | 0.10 - 1.0 | CNC54PE  | 3.3 - 22                  | 1.8 - 15   | 0.47 - 3.9 | 0.22 - 1.5 | CNC55PE                   | 6.8 - 39      | 2.7 - 33 | 1.0 - 10      | 0.33 - 3.3   | CNC56PE        | 10 - 68  | 4.7 - 47    | 1.8 - 12 | 0.47 - 5.6 | 567.99.390 Ind. D | SMD<br>(variant PE) | • EUROFARAD |  |
|                | 50V          | 100V  | 200V                      | 500V       |                 |                         |            |          |           |                           |             |            |          |                           |            |            |            |                           |               |          |               |              |                |          |             |          |            |                   |                     |             |  |
| CNC53PE        | 1.8 - 12     | 1.0 - 10  | 0.27 - 2.70               | 0.10 - 1.0 |                 |                         |            |          |           |                           |             |            |          |                           |            |            |            |                           |               |          |               |              |                |          |             |          |            |                   |                     |             |  |
| CNC54PE        | 3.3 - 22     | 1.8 - 15  | 0.47 - 3.9                | 0.22 - 1.5 |                 |                         |            |          |           |                           |             |            |          |                           |            |            |            |                           |               |          |               |              |                |          |             |          |            |                   |                     |             |  |
| CNC55PE        | 6.8 - 39     | 2.7 - 33  | 1.0 - 10                  | 0.33 - 3.3 |                 |                         |            |          |           |                           |             |            |          |                           |            |            |            |                           |               |          |               |              |                |          |             |          |            |                   |                     |             |  |
| CNC56PE        | 10 - 68      | 4.7 - 47  | 1.8 - 12                  | 0.47 - 5.6 |                 |                         |            |          |           |                           |             |            |          |                           |            |            |            |                           |               |          |               |              |                |          |             |          |            |                   |                     |             |  |

01 CAPACITORS | 02 CERAMIC CHIP

| EPPL Part | Part Type                                    | Description   | Detail Specification   | Package | Manufacturer(s)      | Remarks                                |
|-----------|--|---|--|---------|----------------------|--|
| 2         | 0603, 0805, 1206, 1210, 1812, 2220 (TYPE I)  | Ceramic chips, type I, low voltages<br>Type (size); Capacitance ranges (pF); Voltage (16, 25, 50, 100V)<br>CEC14S (0603); 10-1000; 10-680; 1-560; 1-330<br>CEC2S (0805); 10-2700; 10-2200; 1-1800; 1-1200<br>CEC12S (1206); 10-6800; 10-6200; 1-5600; 1-3900<br>CEC4S (1210); 10-15000; 10-13000; 10-12000; 10-6800<br>CEC6S (1812); 100-33000; 100-30000; 100-22000; 100-12000<br>CEC7S (2220); 470-68000; 470-56000; 470-47000; 470-27000<br>Operating temperature range (°C.): -55 to +125   | EFD 761.10.390,<br>ESCC 3009/003,<br>/022, /004, /005,<br>/006 | CHIP    | • EUROFARAD          | PartType<br>Standardization            |
| 2         | 0603, 0805, 1206, 1210, 1812, 2220 (TYPE II) | Ceramic chips, type II, low voltages<br>Type (size); Capacitance ranges (pF); Voltage (16, 25, 50, 100V)<br>CNC14S (0603); 0,39-39; 0,39-33; 0,01-22; 0,01-12<br>CNC2S (0805); 6,8-220; 6,8-150; 0,1-100; 0,68-33<br>CNC12S (1206); 10-390; 10-270; 0,47-180; 0,47-120<br>CNC4S (1210); 33-820; 33-560; 2,2-390; 2,2-220<br>CNC6S (1812); 100-1800; 100-1200; 3,9-820; 3,9-470<br>CNC7S (2220); 150-3900; 150-2200; 22-1800; 22-1000<br>Operating temperature range (°C.): -55 to +125  | EFD 711.07.390,<br>ESCC 3009/008,<br>/023, /009, /010,<br>/011 | CHIP    | • EUROFARAD          | PartType<br>Standardization            |
| 1         | 0805, 1206, 1210, 1812, 2220 (TYPE I)        | Ceramic Dielectric, Multilayer, Fixed, Type I<br>Case; Capacitance Range(pF); Rated Volt(V); Case Size (max mm); Tolerances (%)<br>0805; 4.7 - 1500; 50-100; 2.3 x 1.45 x 1.3; 0.5, 1, 2, 5, 10<br>1206; 10 - 3900; 50-100; 3.6 x 1.9 x 1.8; 1, 2, 5, 10<br>1210; 22 - 6800; 50-100; 3.6 x 2.8 x 1.8; 1, 2, 5, 10<br>1812; 100 - 15000; 50-100; 5 x 3.6 x 1.8; 1, 2, 5, 10<br>2220; 470 - 33000; 50-100; 6.2 x 5.5 x 1.8; 1, 2, 5, 10<br>(For applicable Exx Series and maximum capacitance value within each rated voltage and for each case size refer to Tables 1a of Detailed Specifications)<br>Variants 03 (AgPdPt Pads) and 06 (SnPb)<br>Temperature Coefficient (10-6/°C.): ± 30<br>Operating Temperature Range (°C.): -55 to +125        | ESCC 3009/003,<br>/022, /004, /005,<br>/006                    | CHIP    | • AVX - DIVISION TPC | Harmonization for Ceramic Cap. entries |
| 1         | 0805, 1206, 1210, 1812, 2220 (TYPE II)       | Ceramic Dielectric, Multilayer, Fixed, Type II<br>Case; Capacitance Range; Rated Volt(V); Case Size (max mm); Tolerances (%)<br>0805; 820pF - 100nF; 25-50-100; 2.3 x 1.45 x 1.3; 5, 10, 20<br>1206; 2.2nF - 220nF; 25-50-100; 3.6 x 1.9 x 1.8; 5, 10, 20<br>1210; 3.9nF - 470nF; 25-50-100; 3.6 x 2.8 x 1.8; 5, 10, 20<br>1812; 6.8nF - 1uF; 25-50-100; 5 x 3.6 x 1.8; 5, 10, 20<br>2220; 18nF - 2.2uF; 25-50-100; 6.2 x 5.5 x 1.8; 5, 10, 20<br>(For applicable Exx Series and maximum capacitance value within each rated voltage and for each case size refer to Tables 1a of Detailed Specifications)<br>Variants 03 (AgPdPt) and 06/07 (SnPb)<br>Temperature Coefficient (10-6/°C.): ± 30<br>Operating Temperature Range (°C.): -55 to +125 | 3009/008, /023,<br>/009, /010, /011                            | CHIP    | • AVX - DIVISION TPC | Harmonization for Ceramic Cap. entries |

01 CAPACITORS | 02 CERAMIC CHIP

| EPPL Part | Part Type           | Description   | Detail Specification | Package | Manufacturer(s)            | Remarks |
|-----------|---------------------|---|----------------------|---------|----------------------------|---------|
| 2         | 32101801<br>Type I  | Ceramic Dielectric, Multilayer, Fixed, Type I<br>Case Size Capacitance Range. Rated Volt. Case Size Tolerance<br>(pF) (V) (max mm) (%)<br>0805 10.0 - 1000 (E12 series) 50-100-200 2.3x1.55x1.3 1<br>1206 10.0 - 3300 (E12 series) 50-100-200 3.5x1.9x1.6 1<br>1210 10.0 - 6800 (E12 series) 50-100-200 3.5x2.8x1.8 1<br>1812 220 - 18000 (E12 series) 50-100-200 4.8x3.5x1.8 1<br>(For the maximum capacitance value within each rated voltage and for each case<br>size refer to Table 2A of Detail Specification)<br>Temperature Coefficient (10-6/°C.): ± 30<br>Operating Temperature Range (°C.): -55 to +125  | S02A 0100            | Chip    | • SYFER TECHNOLOGY<br>Ltd. |         |
| 2         | 32101801<br>Type II | Ceramic Dielectric, Multilayer, Fixed, Type II<br>Case Size Capacitance Range. Rated Volt. Case Size Tolerance<br>(pF) (V) (max mm) (%)<br>0805 100 - 47000 (E6 series) 50-100-200 2.3x1.55x1.3 10<br>1206 680 - 100000 (E6 series) 50-100-200 3.5x1.9x1.6 10<br>1210 1000 - 220000 (E6 series) 50-100-200 3.5x2.8x1.8 10<br>1812 3900 - 470000 (E6 series) 50-100-200 4.8x3.5x1.8 10<br>(For the maximum capacitance value within each rated voltage and for each case<br>size refer to Table 2A of Detail Specification)<br>Temperature Coefficient (%): ± 20 (Vt= 0V), +20/-30 (Vt= nominal voltage)<br>Operating Temperature Range (°C.): -55 to +125 | S02A 0100            | Chip    | • SYFER TECHNOLOGY<br>Ltd. |         |

01 CAPACITORS | 03 TANTALUM SOLID

| EPPL Part | Part Type | Description  | Detail Specification | Package | Manufacturer(s)           | Remarks |
|-----------|-----------|--|----------------------|---------|---------------------------|---------|
| 1         | CSR09     | Tantalum Solid Electrolyte   | MIL-C-39003/2        | Axial   | • KEMET ELECTRONICS Corp. |         |
|           |           | Capacitance Range    Tol.    Rated Volt.    Dimensions (max mm)<br>(μF)           (±%)           (V)           (max mm)                |                      |         |                           |         |
|           |           | 0.047 to 0.18    5/10    75    Size A1 7.14 x Dia 2.51   |                      |         |                           |         |
|           |           | 0.22 to 1.2    5/10    75    Size B1 10.3 x Dia 3.76   |                      |         |                           |         |
|           |           | 0.22, 0.27    5/10    50    Size A1 7.14 x Dia 2.51  |                      |         |                           |         |
|           |           | 1.5,1.8    5/10    50    Size B1 10.3 x Dia 3.76   |                      |         |                           |         |
|           |           | 0.33,0.39,0.47    5/10    35    Size A1 7.14 x Dia 2.51  |                      |         |                           |         |
|           |           | 2.2,2.7    5/10    35    Size B1 10.3 x Dia 3.76   |                      |         |                           |         |
|           |           | 0.56 to 1.00    5/10    20    Size A1 7.14 x Dia 2.51  |                      |         |                           |         |
|           |           | 3.3 to 6.8    5/10    20    Size B1 10.3 x Dia 3.76  |                      |         |                           |         |
|           |           | 1.8, 2.0    5/10    10    Size A1 7.14 x Dia 2.51  |                      |         |                           |         |
|           |           | 10.0 to 15.0    5/10    10    Size B1 10.3 x Dia 3.76  |                      |         |                           |         |
|           |           | Operating temperature range (°C) : -55 to +125   |                      |         |                           |         |
| 1         | CSR13     | Tantalum Solid Electrolyte   | MIL-PRF-39003/1      | Axial   | • KEMET ELECTRONICS Corp. |         |
|           |           | Capacitance Range    Tol.    Rated Volt.    Case Size<br>(μF)           (±%)           (V)   |                      |         |                           |         |
|           |           | 0.0047 to 6.8    5,10    100    Case A, B, C   |                      |         |                           |         |
|           |           | 0.1 to 15    5,10    75    Case A, B, C, D   |                      |         |                           |         |
|           |           | 0.0047 to 22    5,10    50    Case A, B, C, D  |                      |         |                           |         |
|           |           | 5.6 to 47    5,10    35    Case B, C, D  |                      |         |                           |         |
|           |           | 3.9 to 220    5,10    10    case A, B, C, D  |                      |         |                           |         |
|           |           | Dimensions (max mm) : Case A : 10.72 x 3.84 DIA<br>Case B : 15.49 x 5.11 DIA<br>Case C : 20.88 x 7.75 DIA<br>Case D : 23.42 x 9.33 DIA |                      |         |                           |         |
|           |           | Operating temperature range (°C) : -55 to +125   |                      |         |                           |         |
| 1         | CSR23     | Tantalum Solid Electrolyte   | MIL-PRF-39003/3      | Axial   | • KEMET ELECTRONICS Corp. |         |
|           |           | Capacitance Range    Tol.    Rated Volt.    Case Size<br>(μF)           (±%)           (V)   |                      |         |                           |         |
|           |           | 1.2 to 39    10/20    50    Case A, B, C, D  |                      |         |                           |         |
|           |           | 1.8 to 68    10/20    35    Case A, B, C, D  |                      |         |                           |         |
|           |           | 2.7 to 180    10/20    20    Case A, B, C, D   |                      |         |                           |         |
|           |           | 6.8 to 560    10/20    10    Case A, B, C, D   |                      |         |                           |         |
|           |           | Dimensions (max mm) : Case A : 10.72 x 3.84 DIA<br>Case B : 15.49 x 5.11 DIA<br>Case C : 20.88 x 7.75 DIA<br>Case D : 23.42 x 9.33 DIA |                      |         |                           |         |
|           |           | Operating temperature range (°C) : -55 to +125   |                      |         |                           |         |

01 CAPACITORS | 03 TANTALUM SOLID

| EPPL Part                    | Part Type       | Description  | Detail Specification         | Package         | Manufacturer(s)           | Remarks                           |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
|------------------------------|-----------------|--|------------------------------|-----------------|---------------------------|-----------------------------------|------------|------------|-----|----------------|-----------|----|----|-----------------|-----------|----|----|----------------|------------|----|----|-----------------|------------|----|----|-----------------|----|----|----|----------------|----|----|----|---------------|----|----|----|----------------|-----|----|----|---------------|----|----|----|----------------|-----|----|----|---------------|-----|----|----|----------------|-----|----|----|---------------|-----|----|-----|----------------|-----|----|-----|---------------|--|--|--|
| 1                            | CSS33           | Tantalum Solid Electrolyte   | MIL-PRF-39003/10             | Axial           | • KEMET ELECTRONICS Corp. | SEE QPL FOR FAILURE RATE C VALUES |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
|                              |                 | <table border="0"> <tr> <td>Capacitance Range</td> <td>Tol.</td> <td>Rated Volt.</td> <td>Case Size</td> </tr> <tr> <td>(<math>\mu</math>F)</td> <td>(<math>\pm</math>%)</td> <td>(V)</td> <td></td> </tr> <tr> <td>1.2 to 39</td> <td>10</td> <td>50</td> <td>Case A, B, C, D</td> </tr> <tr> <td>1.8 to 68</td> <td>10</td> <td>35</td> <td>Case B, C, D</td> </tr> <tr> <td>2.7 to 180</td> <td>10</td> <td>20</td> <td>Case A, B, C, D</td> </tr> <tr> <td>6.8 to 560</td> <td>10</td> <td>10</td> <td>Case A, B, C, D</td> </tr> </table>   | Capacitance Range            | Tol.            | Rated Volt.               | Case Size                         | ( $\mu$ F) | ( $\pm$ %) | (V) |                | 1.2 to 39 | 10 | 50 | Case A, B, C, D | 1.8 to 68 | 10 | 35 | Case B, C, D   | 2.7 to 180 | 10 | 20 | Case A, B, C, D | 6.8 to 560 | 10 | 10 | Case A, B, C, D |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| Capacitance Range            | Tol.            | Rated Volt.  | Case Size                    |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| ( $\mu$ F)                   | ( $\pm$ %)      | (V)  |                              |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 1.2 to 39                    | 10              | 50   | Case A, B, C, D              |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 1.8 to 68                    | 10              | 35   | Case B, C, D                 |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 2.7 to 180                   | 10              | 20   | Case A, B, C, D              |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 6.8 to 560                   | 10              | 10   | Case A, B, C, D              |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
|                              |                 | Dimensions (max mm) : Case A : 10.72 x 3.84 DIA<br>Case B : 15.49 x 5.11 DIA<br>Case C : 20.88 x 7.75 DIA<br>Case D : 23.42 x 9.33 DIA   |                              |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
|                              |                 | Operating temperature range ( $^{\circ}$ C) : -55 to +125.   |                              |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 1                            | CTC21           | Tantalum Solid Electrolyte   | ESCC 3012/002                | SMD             | • FIRADEC                 |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
|                              |                 | <table border="0"> <tr> <td>Capacitance range (<math>\mu</math>F)</td> <td>Tol. (<math>\pm</math> %)</td> <td>Rated Volt. (V)</td> <td>Dimensions (max mm)</td> </tr> <tr> <td>10</td> <td>10</td> <td>63</td> <td>11.5 x 9.5 x 5</td> </tr> <tr> <td>22</td> <td>10</td> <td>63</td> <td>11.5 x 13 x 6</td> </tr> <tr> <td>15</td> <td>10</td> <td>50</td> <td>11.5 x 9.5 x 5</td> </tr> <tr> <td>22</td> <td>10</td> <td>40</td> <td>11.5 x 9.5 x 5</td> </tr> <tr> <td>47</td> <td>10</td> <td>40</td> <td>11.5 x 13 x 6</td> </tr> <tr> <td>33</td> <td>10</td> <td>25</td> <td>11.5 x 9.5 x 5</td> </tr> <tr> <td>68</td> <td>10</td> <td>25</td> <td>11.5 x 13 x 6</td> </tr> <tr> <td>47</td> <td>10</td> <td>20</td> <td>11.5 x 9.5 x 5</td> </tr> <tr> <td>100</td> <td>10</td> <td>20</td> <td>11.5 x 13 x 6</td> </tr> <tr> <td>68</td> <td>10</td> <td>16</td> <td>11.5 x 9.5 x 5</td> </tr> <tr> <td>150</td> <td>10</td> <td>16</td> <td>11.5 x 13 x 6</td> </tr> <tr> <td>100</td> <td>10</td> <td>10</td> <td>11.5 x 9.5 x 5</td> </tr> <tr> <td>220</td> <td>10</td> <td>10</td> <td>11.5 x 13 x 6</td> </tr> <tr> <td>150</td> <td>10</td> <td>6.3</td> <td>11.5 x 9.5 x 5</td> </tr> <tr> <td>330</td> <td>10</td> <td>6.3</td> <td>11.5 x 13 x 6</td> </tr> </table> | Capacitance range ( $\mu$ F) | Tol. ( $\pm$ %) | Rated Volt. (V)           | Dimensions (max mm)               | 10         | 10         | 63  | 11.5 x 9.5 x 5 | 22        | 10 | 63 | 11.5 x 13 x 6   | 15        | 10 | 50 | 11.5 x 9.5 x 5 | 22         | 10 | 40 | 11.5 x 9.5 x 5  | 47         | 10 | 40 | 11.5 x 13 x 6   | 33 | 10 | 25 | 11.5 x 9.5 x 5 | 68 | 10 | 25 | 11.5 x 13 x 6 | 47 | 10 | 20 | 11.5 x 9.5 x 5 | 100 | 10 | 20 | 11.5 x 13 x 6 | 68 | 10 | 16 | 11.5 x 9.5 x 5 | 150 | 10 | 16 | 11.5 x 13 x 6 | 100 | 10 | 10 | 11.5 x 9.5 x 5 | 220 | 10 | 10 | 11.5 x 13 x 6 | 150 | 10 | 6.3 | 11.5 x 9.5 x 5 | 330 | 10 | 6.3 | 11.5 x 13 x 6 |  |  |  |
| Capacitance range ( $\mu$ F) | Tol. ( $\pm$ %) | Rated Volt. (V)  | Dimensions (max mm)          |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 10                           | 10              | 63   | 11.5 x 9.5 x 5               |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 22                           | 10              | 63   | 11.5 x 13 x 6                |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 15                           | 10              | 50   | 11.5 x 9.5 x 5               |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 22                           | 10              | 40   | 11.5 x 9.5 x 5               |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 47                           | 10              | 40   | 11.5 x 13 x 6                |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 33                           | 10              | 25   | 11.5 x 9.5 x 5               |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 68                           | 10              | 25   | 11.5 x 13 x 6                |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 47                           | 10              | 20   | 11.5 x 9.5 x 5               |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 100                          | 10              | 20   | 11.5 x 13 x 6                |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 68                           | 10              | 16   | 11.5 x 9.5 x 5               |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 150                          | 10              | 16   | 11.5 x 13 x 6                |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 100                          | 10              | 10   | 11.5 x 9.5 x 5               |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 220                          | 10              | 10   | 11.5 x 13 x 6                |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 150                          | 10              | 6.3  | 11.5 x 9.5 x 5               |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
| 330                          | 10              | 6.3  | 11.5 x 13 x 6                |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |
|                              |                 | Operating temperature range ( $^{\circ}$ C) : -55 to +125  |                              |                 |                           |                                   |            |            |     |                |           |    |    |                 |           |    |    |                |            |    |    |                 |            |    |    |                 |    |    |    |                |    |    |    |               |    |    |    |                |     |    |    |               |    |    |    |                |     |    |    |               |     |    |    |                |     |    |    |               |     |    |     |                |     |    |     |               |  |  |  |

01 CAPACITORS | 03 TANTALUM SOLID

| EPPL Part | Part Type   | Description   | Detail Specification              | Package | Manufacturer(s)      | Remarks   |  |
|-----------|-------------|---|-----------------------------------|---------|----------------------|---|--|
| 2         | CTC21E      | Tantalum Solid Electrolyte<br>Capacitance range (µF) Tol. (± %) Rated Volt. (V) Dimensions (max mm) | ESCC 3012/003                     | SMD     | • FIRADEC            | Bigger anodes require further attention during parts mounting |  |
|           |             | 22 10 50 11.5 x 9.5 x 5   |                                   |         |                      |   |  |
|           |             | 47 10 50 11.5 x 13 x 6  |                                   |         |                      |   |  |
|           |             | 33 10 40 11.5 x 9.5 x 5   |                                   |         |                      |   |  |
|           |             | 68 10 40 11.5 x 13 x 6  |                                   |         |                      |   |  |
|           |             | 47 10 25 11.5 x 9.5 x 5   |                                   |         |                      |   |  |
|           |             | 100 10 25 11.5 x 13 x 6   |                                   |         |                      |   |  |
|           |             | 100 10 20 11.5 x 9.5 x 5  |                                   |         |                      |   |  |
|           |             | 220 10 20 11.5 x 13 x 6   |                                   |         |                      |   |  |
|           |             | 150 10 16 11.5 x 9.5 x 5  |                                   |         |                      |   |  |
|           |             | 330 10 16 11.5 x 13 x 6   |                                   |         |                      |   |  |
|           |             | 220 10 10 11.5 x 9.5 x 5  |                                   |         |                      |   |  |
|           |             | 470 10 10 11.5 x 13 x 6   |                                   |         |                      |   |  |
|           |             | 330 10 6.3 11.5 x 9.5 x 5   |                                   |         |                      |   |  |
|           |             | 680 10 6.3 11.5 x 13 x 6  |                                   |         |                      |   |  |
|           |             | Operating temperature range (°C) : -55 to +125  |                                   |         |                      |   |  |
| 1         | TAJ         | Tantalum Solid Electrolyte<br>Capacitance value Tol. Rated Volt. Case size                          | ESCC 3012/001                     | SMD     | • AVX LTD            |   |  |
|           |             | (µF) (±%) (V)   |                                   |         |                      |   |  |
|           |             | 1.0 10 50 C   |                                   |         |                      |   |  |
|           |             | 1.0 10 35 B   |                                   |         |                      |   |  |
|           |             | 2.2 10 35 C   |                                   |         |                      |   |  |
|           |             | 10 10 35 D  |                                   |         |                      |   |  |
|           |             | 22 10 35 E  |                                   |         |                      |   |  |
|           |             | 1.5 10 16 A   |                                   |         |                      |   |  |
|           |             | 4.7 10 16 B   |                                   |         |                      |   |  |
|           |             | 10 10 16 C  |                                   |         |                      |   |  |
|           |             | 100 10 16 E   |                                   |         |                      |   |  |
|           |             | 220 10 10 E   |                                   |         |                      |   |  |
|           |             | Size A (max mm) : 3.4 x 1.8 x 1.8   | Size B (max mm) : 3.7 x 3.0 x 2.1 |         |                      |   |  |
|           |             | Size C (max mm) : 6.2 x 3.4 x 2.8   | Size D (max mm) : 7.5 x 4.5 x 3.1 |         |                      |   |  |
|           |             | Size E (max mm) : 7.5 x 4.5 x 4.3   |                                   |         |                      |   |  |
|           |             | Gold plated termination.  |                                   |         |                      |   |  |
|           |             | Operating temperature range (°C) : -55 to +125  |                                   |         |                      |   |  |
| 2         | TES low ESR | Tantalum Solid Electrolyte, Low ESR<br>Capacitance value Tol. Rated Volt. (Case size)               | Mfr DataSheet                     | SMD     | • AVX Czech Republic | New component   |  |
|           |             | (µF) (±%) (V) 1.0 10 25(A) 4.7 10 16(B)4.7 10 50(D)10 10 10(A),                                     | (6.0) + LAT and                   |         | SRO                  |   |  |
|           |             | 20(C), 35(C,D)22 10 6.3(A), 16(C), 35(D)33 10 16(C), 20(D), 25(D),                                  | screening iaw                     |         |                      |   |  |
|           |             | 35(E)47 10 10(C), 25(D)100 10 6.3(C), 16(D)150 10 10(E), 16(E)220                                   | ESCC 3012                         |         |                      |   |  |
|           |             | 10 10(D,E)330 10 6.3(D), 10(E)Size A (max mm) : 3.2 x 1.6 x 1.6 Size B (max                         |                                   |         |                      |   |  |
|           |             | mm) : 3.5 x 2.8 x 1.9 Size C (max mm) : 6.0 x 3.2 x 2.6 Size D (max mm) : 7.3 x                     |                                   |         |                      |   |  |
|           |             | 4.3 x 2.9 Size E (max mm) : 7.3 x 4.3 x 4.1 Gold plated termination. Operating                      |                                   |         |                      |   |  |
|           |             | temperature range (°C) : -55 to +125  |                                   |         |                      |   |  |

01 CAPACITORS | 04 TANTALUM NON-SOLID

| EPPL Part | Part Type   | Description   | Detail Specification | Package                            | Manufacturer(s) | Remarks  |
|-----------|-------------|---|----------------------|------------------------------------|-----------------|--|
| 2         | CT79        | Tubular, Porous, Tantalum Cathode and Anode, Gelled Electrolyte<br>Rated Voltage: 16 to 125 V<br>Capacitance range: as per Table 1(a) of Detail specification<br>Case sizes A, B, C and D<br>Operating temperature range: -55 to +125 °C  | ESCC 3003/005        | Size A,<br>B, C, D                 | • FIRADEC       |  |
| 2         | CT79, CT79E | Non-Solid Tantalum, gel<br>Rated Voltage 6.0 to 125 V<br>Capacitance range 2.7 to 2200 uF<br>Operating Temperature range: -55 to +125 °C  | ESCC 3003/005        | A, B, C<br>& D<br>package<br>style | • FIRADEC       | Also available<br>i.a.w. CCC<br>specification<br>30202-801 |
| 2         | ST79        | Capacitors Fixed, Tubular, Porous Tantalum Cathode and Anode, gelled Electrolyte<br><br>Voltage (V)    Capacitance (uF)<br><br>60                560<br>60                700<br>63                500<br>75                330<br>75                470<br>100               150<br>100               220<br><br>Tolerance: 10%<br>Case size: C (variant 04), D (variant 05)<br>Dimensions max. (mm): 34 (length), 10 (diam.)<br>Operating temperature range: -55 to +125 °C | ESCC 3003/006        | Axial                              | • FIRADEC       | 125 V high<br>capacitance values<br>shall be avoided       |



01 CAPACITORS | 05 PLASTIC METALLIZED

| EPPL Part | Part Type | Description  | Detail Specification | Package | Manufacturer(s) | Remarks |
|-----------|-----------|--|----------------------|---------|-----------------|---------|
| 1         | HT86PS    | Plastic Film Dielectric, High Voltage.<br>Cap. Range(nF)    Tol.(±%)    Rated Volt.(V)<br>0.68 to 15            10            20000<br>1.5 to 33             10            15000<br>3.3 to 68             10            12500<br>1.0 to 100            10            10000<br>2.2 to 220            10            7500<br>6.8 to 470            10            5000<br>15 to 1000            10            3500<br>15 to 1500            10            2500<br>33 to 2200            10            1500<br>Temperature Coefficient:<br>Temperature (°C.)    Capacitance change (%)<br>+22 to -55            -3.0 min<br>+22 to +125            +10 max<br>Size (max mm):36x11x5 to 106x51x15 depending on Voltage/Capacitance Value<br>Operating Temperature Range (°C) : -55 to +125 | ESCC 3006/022        | Axial   | • EUROFARAD     |         |
| 1         | PM94S     | Self-healing metalised film dielectric<br>Capacitance Value (uF)    Rated Voltage (V)    Tolerance    Available sizes<br>0.56 - 12                    100                    10 %        01, 02, 03, 04<br>0.22 - 4.7                    250                    10 %        01, 02, 03, 04<br>0.1 - 1.8                     400                    10 %        01, 02, 03, 04<br>Size 01 (max mm) : 10.7 x 10.7 x B (6, 8, 10, 12, 14, 15 mm depending on cap. value)<br>Size 02 (max mm) : 15.5 x 11.5 x B (6, 8, 10, 12, 14, 15 mm depending on cap. value)<br>Size 03 (max mm) : 16.5 x 15.5 x B (6, 8, 10, 12, 14, 15 mm depending on cap. value)<br>Size 04 (max mm) : 18.5 x 17.0 x B (6, 8, 10, 12, 14, 15 mm depending on cap. value)  | ESCC 3006/024        | SMD     | • EUROFARAD     |         |

02 CONNECTORS | 01 CIRCULAR

| EPPL Part     | Part Type                                    | Description   | Detail Specification | Package    | Manufacturer(s) | Remarks    |    |      |    |      |               |                 |           |      |               |                 |           |     |               |                 |           |  |
|---------------|--|---|----------------------|------------|-----------------|------------|----|------|----|------|---------------|-----------------|-----------|------|---------------|-----------------|-----------|-----|---------------|-----------------|-----------|--|
| 1             | 38999<br>Series I                            | <p>Circular, Bayonet Coupling, Removable Crimp Contacts, scoop-proof, based on MIL-C-38999 Series I.</p> <p>Range: 6, 13, 22, 37, 55, 66, 79, 100, 128 contacts size #22.<br/>3, 6, 10, 19, 26, 32, 41, 53, 61 contacts size #20.</p> <p>Other arrangements with contact sizes: 16, 12, 8.</p> <p>For contact sizes refer to ESCC 3401/058.</p> <p>Receptacle and plug shell sizes:09,11,13,15,17,19,21,23,25.</p> <table border="0"> <tr> <td>Contact sizes</td> <td>Rating (A)</td> <td>Contact sizes</td> <td>Rating (A)</td> </tr> <tr> <td>08</td> <td>46.0</td> <td>12</td> <td>23.0</td> </tr> <tr> <td>16</td> <td>13.0</td> <td>20</td> <td>7.5</td> </tr> <tr> <td>22</td> <td>5.0</td> <td></td> <td></td> </tr> </table> <p>Operating Temperature Range (°C): -65 to +200</p> | Contact sizes        | Rating (A) | Contact sizes   | Rating (A) | 08 | 46.0 | 12 | 23.0 | 16            | 13.0            | 20        | 7.5  | 22            | 5.0             |           |     | ESCC 3401/052 | AS PER<br>SPEC. | • SOURIAU |  |
| Contact sizes | Rating (A)                                   | Contact sizes   | Rating (A)           |            |                 |            |    |      |    |      |               |                 |           |      |               |                 |           |     |               |                 |           |  |
| 08            | 46.0   | 12  | 23.0                 |            |                 |            |    |      |    |      |               |                 |           |      |               |                 |           |     |               |                 |           |  |
| 16            | 13.0   | 20  | 7.5                  |            |                 |            |    |      |    |      |               |                 |           |      |               |                 |           |     |               |                 |           |  |
| 22            | 5.0  |   |                      |            |                 |            |    |      |    |      |               |                 |           |      |               |                 |           |     |               |                 |           |  |
| 1             | 38999<br>Series II                           | <p>Circular, Bayonet Coupling, Low Profile, Removable Crimp Contacts, Based on MIL-C-38999 Series II.</p> <p>Range: 6, 13, 22, 37, 55, 66, 79, 100, 128 contacts size #22.<br/>3, 6, 10, 18, 26, 32, 41, 55, 61 contacts size #20.</p> <p>Other arrangements with contact sizes: 20, 16, 12.</p> <p>For contact sizes refer to ESCC 3401/045.</p> <p>Receptacle and plug shell sizes:08,10,12,14,16,18,20,22,24.</p> <table border="0"> <tr> <td>Contact sizes</td> <td>Rating (A)</td> <td>Contact sizes</td> <td>Rating (A)</td> </tr> <tr> <td>12</td> <td>23.0</td> <td>16</td> <td>13.0</td> </tr> <tr> <td>20</td> <td>7.5</td> <td>22</td> <td>5.0</td> </tr> </table> <p>Operating Temperature Range (°C): -65 to +200</p>  | Contact sizes        | Rating (A) | Contact sizes   | Rating (A) | 12 | 23.0 | 16 | 13.0 | 20            | 7.5             | 22        | 5.0  | ESCC 3401/044 | AS PER<br>SPEC. | • SOURIAU |     |               |                 |           |  |
| Contact sizes | Rating (A)                                   | Contact sizes   | Rating (A)           |            |                 |            |    |      |    |      |               |                 |           |      |               |                 |           |     |               |                 |           |  |
| 12            | 23.0   | 16  | 13.0                 |            |                 |            |    |      |    |      |               |                 |           |      |               |                 |           |     |               |                 |           |  |
| 20            | 7.5  | 22  | 5.0                  |            |                 |            |    |      |    |      |               |                 |           |      |               |                 |           |     |               |                 |           |  |
| 1             | 38999<br>Series III                          | <p>Circular, Triple-start, Self Locking Coupling, Scoop-proof, Removable Crimp Contacts, based on MIL-C-38999 Series III</p> <p>Range: 6, 13, 22, 37, 55, 66, 79, 100, 128 contacts #22<br/>3, 6, 10, 19, 26, 32, 41, 53, 61 contacts #20</p> <p>Other arrangements with contact sizes: 20, 16, 12, 8, 4.</p> <p>For contact sizes refer to ESCC 3401/058, /066, /070.</p> <table border="0"> <tr> <td>Contact sizes</td> <td>Rating (A)</td> <td>Contact sizes</td> <td>Rating (A)</td> </tr> <tr> <td>4</td> <td>80.0</td> <td>8</td> <td>46.0</td> </tr> <tr> <td>12</td> <td>23.0</td> <td>16</td> <td>13.0</td> </tr> <tr> <td>20</td> <td>7.5</td> <td>22</td> <td>5.0</td> </tr> </table> <p>Operating Temperature Range (°C): -65 to +200</p>                                     | Contact sizes        | Rating (A) | Contact sizes   | Rating (A) | 4  | 80.0 | 8  | 46.0 | 12            | 23.0            | 16        | 13.0 | 20            | 7.5             | 22        | 5.0 | ESCC 3401/056 | AS PER<br>SPEC. | • SOURIAU |  |
| Contact sizes | Rating (A)                                   | Contact sizes   | Rating (A)           |            |                 |            |    |      |    |      |               |                 |           |      |               |                 |           |     |               |                 |           |  |
| 4             | 80.0   | 8   | 46.0                 |            |                 |            |    |      |    |      |               |                 |           |      |               |                 |           |     |               |                 |           |  |
| 12            | 23.0   | 16  | 13.0                 |            |                 |            |    |      |    |      |               |                 |           |      |               |                 |           |     |               |                 |           |  |
| 20            | 7.5  | 22  | 5.0                  |            |                 |            |    |      |    |      |               |                 |           |      |               |                 |           |     |               |                 |           |  |
| 1             | 38999<br>SeriesIII<br>Hermetic<br>receptacle | <p>Circular, Hermetic Receptacle, Scoop-proof, non-removable solder contacts, based on MIL-C-38999 Series III.</p> <p>Range: 6, 13, 22, 37, 55, 66, 79, 100, 128 contacts size#22<br/>3, 6, 10, 19, 26, 32, 41, 53, 61 contacts size#20</p> <table border="0"> <tr> <td>Contact size</td> <td>Rating (A)</td> <td>Contact size</td> <td>Rating (A)</td> </tr> <tr> <td>20</td> <td>7.5</td> <td>22</td> <td>5.0</td> </tr> </table> <p>Operating Temperature Range (°C): -65 to +200</p>  | Contact size         | Rating (A) | Contact size    | Rating (A) | 20 | 7.5  | 22 | 5.0  | ESCC 3401/057 | AS PER<br>SPEC. | • SOURIAU |      |               |                 |           |     |               |                 |           |  |
| Contact size  | Rating (A)                                   | Contact size  | Rating (A)           |            |                 |            |    |      |    |      |               |                 |           |      |               |                 |           |     |               |                 |           |  |
| 20            | 7.5  | 22  | 5.0                  |            |                 |            |    |      |    |      |               |                 |           |      |               |                 |           |     |               |                 |           |  |

02 CONNECTORS | 02 RECTANGULAR

| EPPL Part | Part Type                                | Description  | Detail Specification | Package         | Manufacturer(s)               | Remarks  |
|-----------|--|--|----------------------|-----------------|-------------------------------|--|
| 1         | D*M<br>(Solder,<br>PCB and<br>Wire Wrap) | Rectangular, non removable solder bucket, PCB and wire-wrap contacts and removable coaxial and power contacts.<br>Range: 9, 15, 25, 37 and 50 contacts size# 20<br>15, 26, 44, 62 and 78 contacts size# 22<br>Coaxial Contact Arrangements: contact variants 01 to 20 (ITT Cannon).<br>Power Contact Arrangements: contact variants 01 to 12 (ITT Cannon).<br>Gold-plated non-magnetic shells<br>Contact size      Rating (A)      Contact size      Rating (A)<br>20                    7.5                    22                    3.0<br>Operating Temperature Range (°C): -55 to +125               | ESCC 3401/001        | AS PER<br>SPEC. | • C&K Components<br>• SOURIAU | Souriau is not qualified for Coaxial and Power Contacts  |
| 1         | D*MA<br>(Crimp)                          | Rectangular, removable crimp contact.<br>Range: 9, 15, 25, 37, 50 contacts size# 20<br>15, 26, 44, 62, 78 contacts size# 22<br>For contact sizes refer to ESCC 3401/005; for the corresponding saver and for its own contacts refer to ESCC 3401/021 and ESCC 3401/020 respectively.<br>Gold-plated non-magnetic shells<br>Contact size      Rating (A)      Contact size      Rating (A)<br>20                    7.5(AWG 20to24)      20                    3.0(AWG 26and28)<br>20                    7.5(AWG 18and20)      22                    5.0<br>Operating Temperature Range (°C): -55 to +125 | ESCC 3401/002        | AS PER<br>SPEC. | • C&K Components<br>• SOURIAU |  |
| 1         | MTB                                      | Single in line, microminiature.<br>Shell size: 5 through 81 contacts single in line<br>Terminations: Wire sizes AWG 26 and 28 and<br>AWG 25 uninsulated solid gold-plated wire<br>Rating (A): 2.5 with AWG 26 and uninsulated wire<br>1.5 with AWG 28<br>Operating Temperature Range (°C): -55 to +125   | ESCC 3401/031        | AS PER<br>SPEC. | • C&K Components              | Supplied with uninsulated or already fitted wires; length of wires shall be specified by the orderer |

02 CONNECTORS | 03 PRINTED CIRCUIT BOARD

| EPPL Part | Part Type         | Description  | Detail Specification | Package         | Manufacturer(s)   | Remarks |
|-----------|-------------------|--|----------------------|-----------------|---|---------|
| 1         | HE801/HPD         | <p>For PCB, removable contacts, crimp, wire-wrap, solder type, saver type.</p> <p>Range: 2 rows: 17, 29, 41, 53, 65, 72, 84, 96, 120 contacts<br/>                     3 rows: 62, 80, 98, 160 contacts</p> <p>Contact Type: 3401/017 Crimp-type.<br/>                     3401/018 Wire-wrap type.<br/>                     3401/019 Solder/Saver type(wire sizes 22 to 26).</p> <p>Rating (A): 5.0 (1 contact,AWG 22)<br/>                     1.5 (&gt;31 contacts,AWG 22)</p> <p>Operating Temperature Range (°C): -55 to +125</p> | ESCC 3401/016        | AS PER<br>SPEC. | <ul style="list-style-type: none"> <li>HYPERTAC S.A.</li> <li>HYPERTAC LTD</li> </ul> |         |
| 1         | IHD<br>INTERPOSER | <p>PCB/PCB and PCB/MCM connections</p> <p>Pad Size (min.) : 0,8 mm</p> <p>Standard Pitch : 1.905 mm between contacts and 1.524 mm between rows</p> <p>Standard Height : 7.8 mm</p> <p>RFF contacts</p> <p>Contact Resistance: &lt;25 mohm</p> <p>Nominal current: 1 A</p> <p>Operating temperature range: -55 to +125 °C</p>   | ESCC 3401/076        | N/A             | <ul style="list-style-type: none"> <li>HYPERTAC</li> </ul>                            |         |
| 1         | KMC               | <p>For PCB, non removable solder and wire wrap contacts and connector saver.</p> <p>Range: 3 rows 26, 44, 62, 80, 98, 144 contacts</p> <p>Contact Type: Solder and Wire-wrap for AWG 28 wires and PCB</p> <p>Rating (A): 2.0 (1 to 3 used contacts),<br/>                     0.9 (4 to 26 used contacts)<br/>                     and 0.5 (over 27 used contacts)</p> <p>Operating Temperature Range (°C): -55 to +125</p>  | ESCC 3401/039        | AS PER<br>SPEC. | <ul style="list-style-type: none"> <li>HYPERTAC S.A.</li> </ul>                       |         |
| 1         | MHD               | <p>For PCB, non removable solder through board and surface mount contacts and connector saver.</p> <p>Range: 4 rows 52, 100, 152, 200, 252, 300, 352 and 400 contacts</p> <p>Contact Type: Solder through board and surface mount for PCB</p> <p>Rating (A): 2.0 (1 to 3 used contacts),<br/>                     0.9 (4 to 26 used contacts)<br/>                     and 0.5 (over 27 used contacts)</p> <p>Operating Temperature Range (°C): -55 to +125</p>  | ESCC 3401/065        | AS PER<br>SPEC. | <ul style="list-style-type: none"> <li>HYPERTAC S.A.</li> </ul>                       |         |

02 CONNECTORS | 05 RF COAXIAL

| EPPL Part | Part Type | Description   | Detail Specification                            | Package              | Manufacturer(s) | Remarks |
|-----------|-----------|---|---|----------------------|-----------------|---------|
| 1         | ACB1      | Triaxial databus connector for MIL-STD-1553 harnesses.<br>Bayonet & Thread coupling.<br>Plug and Bulkhead connector types.<br>Straight and Rightangle versions.<br>Frequency range: up to 1 MHz<br>Working Voltage: 200 Vrms<br>Rated Current (contact): 1A<br>Operating temperature range: -55 to +150 °C  | ESCC 3401/079                                   | Coaxial              | • AXON' CABLE   |         |
| 1         | SMA       | RF coaxial, 50 ohms.<br>3402/001 male contacts (plug), 3402/002 female contacts (receptacle), 3402/003 adapters.<br>Crimp or solder contacts for flexible and semi-rigid cables, contacts for micro-strip.<br>Types covered by similarity :<br>hermetically sealed receptacle;<br>Amagnetic stainless steel;<br>Operating temperature range as per det. Spec.   | ESCC 3402/001<br>ESCC 3402/002<br>ESCC 3402/003 | AS PER<br>SPEC.      | • RADIALL       |         |
| 1         | SMA 2.9   | RF coaxial, 50 ohms, DC to 40 GHz<br>3402/021 male contacts (plug)<br>3402/022 female contacts (receptacle)<br>3402/023 adapters and connecting pieces<br><br>Type variants as per Table 1(a) of Detail Specifications<br>Operating temperature range: -65 / +165 °c  | ESCC 3402/021<br>ESCC 3402/022<br>ESCC 3402/023 | AS PER<br>SPEC.      | • RADIALL       |         |
| 2         | SMP       | RF Coaxial Connectors, 50 ohms, adaptor and connecting pieces<br>Frequency limit up to 20 GHz<br>Variant 01: limited detent receptacle for PCB CMS (pin contact)<br>Variant 02: straight female-female adapter (10.3 mm)<br>Variant 03: straight female-female adapter (5.69 mm)<br>Variant 04: right angle receptacle for PCB, limited detent, solder type (pin contact)<br><br>Operating temperature range: -65 / +165 °C | RAD-DET-CONN-019                                | AS PER<br>SPEC.      | • RADIALL       |         |
| 2         | TNC       | RF coaxial type TNC connectors male or female contact and adptators 50W<br>Max working voltage : 500Vrms, power : 75-120W, frequency :<br>0-18GHz<br>Operating temperature range: -55 to +105 °C  | ESCC 3402/008-<br>009-010                       | TNC<br>connecto<br>r | • RADIALL       |         |

02 CONNECTORS | 07 MICROMINIATURE

| EPPL Part | Part Type  | Description   | Detail Specification                  | Package            | Manufacturer(s)  | Remarks  |
|-----------|------------|---|---------------------------------------|--------------------|------------------|--|
| 1         | MDM        | Rectangular, non removable wired contacts<br>Range: 9, 15, 21, 25, 31, 37, 51 contacts size.<br>Terminations: Wire sizes AWG 26 and 28 and<br>AWG 25 uninsulated solid gold-plated wire<br>Rating (A): 2.5 with AWG 26 and uninsulated wire<br>1.5 with AWG 28<br>Nickel Plated Shells<br>For the corresponding saver refer to ESCC 3401/041.<br>Operating Temperature Range (°C): -55 to +125  | ESCC 3401/029                         | AS PER<br>SPEC.    | • C&K Components | Supplied with<br>uninsulated or<br>already fitted<br>wires; length of<br>wires shall be<br>specified by the<br>orderer |
| 2         | MDSA       | Rectangular, non removable wired contacts<br>Range: 9, 15, 21, 25, 31, 37, 51 contacts size.<br>Terminations: Single wire ESCC/3901/013 variant 01 (AWG28)<br>Single wire ESCC/3901/013 variant 02 (AWG26)<br>Single wire ESCC/3901/002 variant 61 (AWG28)<br>Single wire ESCC/3901/002 variant 56 (AWG26)<br>AWG 25 uninsulated solid gold-plated wire<br>Single wire M22759/33-26 as per MIL-DTL-83513<br>Rating (A): 2.5 with AWG 26 and uninsulated wire<br>1.5 with AWG 28<br>Nickel or Gold Plated Shells<br>For the corresponding saver refer to ESCC 3401/041.<br>Operating Temperature Range (°C): -55 to +125 | Axon 05039-ST-01<br>Issue A           | AS PER<br>SPEC.    | • AXON' CABLE    |  |
| 2         | Micro Comp | Electrical, rectangular, composite microminiature<br>Operating temperature Range: 0 to +175 °C  | 8MC/001, 8MC/002,<br>8MC/003, 8MC/004 | MICROMIN<br>IATURE | • SOURIAU        |  |

02 CONNECTORS | 08 RF FILTER

| EPPL Part | Part Type | Description  | Detail Specification | Package      | Manufacturer(s)  | Remarks       |
|-----------|-----------|--|----------------------|--------------|------------------|---------------|
| 2         | D*J       | Filtered, rectangular, non-removable solder bucket contacts, filtering.<br>Range: 9, 15, 25, 37, 50 contacts<br>Filter type M (medium frequency) only<br>Solder buckets terminations<br>Rated Current: 5 Adc<br>Operating Temperature Range (C): -55 to +125 | CSFR 165             | AS PER SPEC. | • C&K Components | New component |

03 PIEZO-ELECTRIC DEVICES | 01 CRYSTAL RESONATOR

| EPPL Part | Part Type | Description   | Detail Specification | Package | Manufacturer(s)                    | Remarks |
|-----------|-----------|---|----------------------|---------|------------------------------------|---------|
| 2         | T1507     | Crystal units in metal holder<br>Frequency Range: 2,5 - 20 MHz<br>Operating temperature range depending on type variant | ESCC 3501/019        | T08 CAN | • KVG Quartz Crystal<br>Technology |         |
| 1         | T1507     | Crystal units in metal holder<br>Frequency Range: 3 - 20 MHz<br>Operating temperature range depending on type variant   | ESCC 3501/019        | T08 CAN | • Rakon France                     |         |
| 2         | T807      | Crystal units in metal holder<br>Frequency Range: 4 - 140 MHz<br>Operating temperature range depending on type variant  | ESCC 3501 /018       | T05 CAN | • KVG Quartz Crystal<br>Technology |         |
| 1         | T807      | Crystal units in metal holder<br>Frequency Range: 14 - 140 MHz<br>Operating temperature range depending on type variant | ESCC 3501/018        | T05 CAN | • Rakon France                     |         |



04 DIODES | 02 RECTIFIER

| EPPL Part | Part Type                                      | Description   | Detail Specification | Package | Manufacturer(s)                   | Remarks  |
|-----------|--|---|----------------------|---------|-----------------------------------|--|
| 2         | 1N5416 thru<br>1N5418,<br>1N5420               | Silicon, Power Rectifier, Fast Recovery.<br>DC forward voltage (max V): 1.5 @ DC forward current (pk A): 9.0<br>DC reverse current (max $\mu$ A): 1.0 @ DC reverse voltage (V):100,200,400,600.<br>Switching time (ns): 150 (400 for 1N5420);<br>IFSM=80 A (pk); Io=3.0 A (t=55°C.)<br>Operating Temperature range (°C.): -65 to +175.                        | MIL-S-19500/411      | AXIAL   | • Sensitron<br>Semiconductor Inc. | Sensitron spec.<br>7700-4091 for JANS-<br>equivalent<br>screening flow   |
| 1         | 1N5416,<br>1N5417,<br>1N5418,<br>1N5420        | Silicon, Power Rectifier, Fast Recovery.<br>DC forward voltage (max V): 1.5 @ DC forward current (pk A): 9.0<br>DC reverse current (max $\mu$ A): 1.0 @ DC reverse voltage (V):100,200,400,600.<br>Switching time (ns): 150 (400 for 1N5420); IFSM=80 A (pk); Io=2.0 A (t=55°C.)<br>Operating Temperature range (°C.): -65 to +175.                           | MIL-PRF-19500/411    | A248    | • MICROSEMI<br>SCOTTSDALE         | Manufacturer<br>Standardization  |
| 2         | 1N5416US<br>thru<br>1N5418US,<br>1N5420US      | Silicon, Power Rectifier, Fast Recovery. DC forward voltage (max V): 1.5 @ DC<br>forward current (pk A): 9.0 DC reverse current (max $\mu$ A): 1.0 @ DC reverse voltage<br>(V):100,200,400,600. Switching time (ns): 150 (400 for 1N5420US); IFSM=80 A<br>(pk); Io=3.0 A (t=55°C.) Operating Temperature range (°C.): -65 to +175.                            | MIL-PRF-19500/411    | MELF    | • Sensitron<br>Semiconductor Inc. |  |
| 2         | 1N5550,<br>1N5552,<br>1N5554                   | Silicon, Power Rectifier, General Purpose.<br>DC forward voltage(max V):1.2(1.3 for 1N5554) @DC forward current(pk A):9.0<br>DC reverse current(max $\mu$ A):1.0 @ DC reverse voltage (V): 200, 600, 1000<br>Switching time (ns): 2000; IFSM= 100 A (pk); Io= 3.0 A (t=55°C.)<br>Operating Temperature range (°C.): -65 to +175.                              | MIL-PRF-19500/420    | A1      | • MICROSEMI<br>SCOTTSDALE         | Manufacturer<br>Standardization  |
| 1         | 1N5614,<br>1N5616,<br>1N5618                   | Silicon, Power Rectifier<br>DC forward voltage (max V): 1.3 @ DC forward current (pk A): 3.0*<br>DC reverse current (max $\mu$ A): 0.5 @ DC reverse voltage (V): 200, 400, 600<br>Switching time (ns): 2000; IFSM= 30 A (pk); Io= 1 A (t=55°C.)<br>Operating Temperature range (°C.): -65 to +175. * pulsed   | MIL-PRF-19500/427    | A248    | • MICROSEMI<br>SCOTTSDALE         | manufacturer<br>Standardization  |
| 2         | 1N5615,<br>1N5617(A/UN<br>) ,1N5619,<br>1N5623 | Silicon, Power Rectifier, Fast Recovery.<br>DC forward voltage (max V): 1.6 @ DC forward current (pk A): 3.0*<br>DC reverse current (max $\mu$ A): 1.0 @ DC reverse voltage (V): 200, 600, 1000<br>Switching time (ns): 150, 250, 500 respectively<br>IFSM= 25 A (pk); Io= 1 A (t=55°C.)<br>Operating Temperature Range (°C.): -65 to +175. * pulsed          | MIL-PRF-19500/429    | A248    | • MICROSEMI<br>SCOTTSDALE         | Manufacturer<br>Standardization  |
| 1         | 1N5806U  | Silicon, Power Rectifier, Switching.<br>DC forward voltage (max V): 0.875 @ DC forward current (pk A): 1.0<br>DC reverse current (max $\mu$ A): 1.0 @ DC reverse voltage (V):150.<br>Switching time (ns): 25; IFSM=35 A (pk); Io=1.0 A (t=55°C.)<br>Operating Temperature range (°C.): -55 to +125.   | ESCC 5101/014        | LCC2-A  | • STMicroelectronics              |  |
| 1         | 1N5806US                                       | Silicon, Fast Recovery, Power Rectifier.<br>DC forward voltage (max V):0.975,0.925 @DC forward current (pk A):2.5,6.0*<br>DC reverse current (max $\mu$ A): 1.0, 5.0 @DC reverse voltage (V): 150<br>Switching time (ns): 25, 30 respectively<br>IFSM= 35, 125 A (pk); Io= 1.0, 3.0 respectively.<br>Operating Temperature Range (°C.): -65 to +175. * pulsed | MIL-PRF-19500/477    | D-5A    | • MICROSEMI<br>SCOTTSDALE         | GIDEP Problem<br>Advisory N. WV9-P-<br>06-01 for LDC 0415<br>to 00614 - check<br>LDC for flight<br>application |

## 04 DIODES | 02 RECTIFIER

| EPPL Part | Part Type  | Description  | Detail Specification | Package  | Manufacturer(s)                   | Remarks  |
|-----------|------------|--|----------------------|----------|-----------------------------------|--|
| 2         | 1N5806US   | Silicon, Fast Recovery, Power Rectifier.<br>DC forward voltage (max V):0.975,0.925 @DC forward current (pk A):2.5,6.0*<br>DC reverse current (max $\mu$ A): 1.0, 5.0 @DC reverse voltage (V): 150<br>Switching time (ns): 25, 30 respectively<br>IFSM= 35, 125 A (pk); Io= 1.0, 3.0 respectively.<br>Operating Temperature Range ( $^{\circ}$ C.): -65 to +175. * pulsed | MIL-PRF-19500/477    | D-5A     | • Sensitron<br>Semiconductor Inc. | Manufacturer<br>Standardization.<br>Moved to EPPL part<br>II   |
| 1         | 1N5811U    | Silicon, Power Rectifier, Switching.<br>DC forward voltage (max V): 0.875 @ DC forward current (pk A): 4.0<br>DC reverse current (max $\mu$ A): 5.0 @ DC reverse voltage (V):150.<br>Switching time (ns): 30; IFSM=125 A (pk); Io=6.0 A (t=55 $^{\circ}$ C.)<br>Operating Temperature range ( $^{\circ}$ C.): -55 to +125.   | ESCC 5101/013        | LCC2-B   | • STMicroelectronics              |  |
| 2         | 1N5811US   | Silicon, Fast Recovery, Power Rectifier.<br>DC forward voltage (max V):0.975,0.925 @DC forward current (pk A):2.5,6.0*<br>DC reverse current (max $\mu$ A): 1.0, 5.0 @DC reverse voltage (V): 150<br>Switching time (ns): 25, 30 respectively<br>IFSM= 35, 125 A (pk); Io= 1.0, 3.0 respectively.<br>Operating Temperature Range ( $^{\circ}$ C.): -65 to +175. * pulsed | MIL-PRF-19500/477    | D-5B     | • MICROSEMI<br>SCOTTSDALE         | GIDEP Problem<br>Advisory N. WV9-P-<br>06-01 for LDC 0415<br>to 00614 - check<br>LDC for flight<br>application |
| 2         | 1N5811US   | Silicon, Fast Recovery, Power Rectifier.<br>DC forward voltage (max V):0.975,0.925 @DC forward current (pk A):2.5,6.0*<br>DC reverse current (max $\mu$ A): 1.0, 5.0 @DC reverse voltage (V): 150<br>Switching time (ns): 25, 30 respectively<br>IFSM= 35, 125 A (pk); Io= 1.0, 3.0 respectively.<br>Operating Temperature Range ( $^{\circ}$ C.): -65 to +175. * pulsed | MIL-PRF-19500/477    | D-5B     | • Sensitron<br>Semiconductor Inc. | Manufacturer<br>Specification  |
| 1         | 1N5819U    | Silicon, Power Rectifier, Schottky.<br>DC forward voltage (max V): 0.55 @ DC forward current (pk A): 1.0<br>DC reverse current (max $\mu$ A): 25.0 @ DC reverse voltage (V):40.<br>IFSM=50 A (pk); Io=1.0 A (t=55 $^{\circ}$ C.)<br>Operating Temperature range ( $^{\circ}$ C.): -55 to +125 $^{\circ}$ C   | ESCC 5106/021        | LCC2-B   | • STMicroelectronics              | Change to EPPL part<br>I   |
| 2         | 1N5819UR-1 | Silicon, Hermetic, Schottky barrier.<br>DC forward voltage (max V): 0.8 @max. forward current 3.1 A (pulsed)<br>IFSM= 24 A(pk); Io= 1.0 A at Tec= +55 $^{\circ}$ C.<br>Operating Temperature Range ( $^{\circ}$ C.): -65 to +125   | MIL-PRF-19500/586    | DO-213AB | • MICROSEMI LAWRENCE              | Manufacturer<br>Specification.<br>Moved to EPPL II   |
| 1         | 1N5822U    | Silicon, Rectifier, Schottky barrier.<br>DC forward voltage (max V): 0.7 @max. forward current 9.4 A* (pk)<br>IFSM= 80 A(pk); Io= 3.0 A at Tec=+55 $^{\circ}$ C.<br>Operating Temperature Range ( $^{\circ}$ C.): -55 to +125 *pulsed  | ESCC 5106/020        | LCC2-B   | • STMicroelectronics              | Change to EPPL part<br>I   |
| 2         | 1N5822US   | Silicon, Rectifier, Schottky barrier.<br>DC forward voltage (max V): 0.7 @max. forward current 9.4 A* (pk)<br>IFSM= 80 A(pk); Io= 3.0 A at Tec=+55 $^{\circ}$ C.<br>Operating Temperature Range ( $^{\circ}$ C.): -65 to +150 *pulsed  | MIL-PRF-19500/620    | D-5B     | • MICROSEMI LAWRENCE              | Manufacturer<br>Standardization.<br>Moved to EPPL II   |

04 DIODES | 02 RECTIFIER

| EPPL Part | Part Type  | Description  | Detail Specification | Package  | Manufacturer(s)      | Remarks |
|-----------|------------|--|----------------------|----------|----------------------|---------|
| 1         | BYV52-200  | Single, Ultra Fast Power Rectifier, 200 V, 30 A<br>Operating Temperature range : -55 to +150 °C<br>Storage Temperature Range : -55 to +150 °C<br>Dimensions (mm, max.) : 20.07 x 13.59 x 6.3   | ESCC 5103/030        | TO254    | • STMicroelectronics |         |
| 1         | BYV54-200  | Single, Ultra Fast Power Rectifier, 200 V, 60 A<br>Operating Temperature range : -55 to +150 °C<br>Storage Temperature Range : -55 to +150 °C<br>Dimensions (mm, max.) : 20.07 x 13.59 x 6.3   | ESCC 5103/031        | TO254-AA | • STMicroelectronics |         |
| 1         | BYW81-200  | Dual, Ultra Fast Power Rectifier 200 V, 2x15 A<br>Operating Temperature range : -55 to +150 °C<br>Storage Temperature Range : -55 to +150 °C<br>Available in Common Anode, Common Cathode and Doubler configuration<br>Dimensions (mm, max.) : 20.07 x 13.59 x 6.3 | ESCC 5103/029        | SMD .5   | • STMicroelectronics |         |
| 1         | STPS20H100 | Dual, Power Schottky, 100 V, 2x20 A<br>Operating Temperature Range : -55 to +175 °C<br>Storage Temperature Range : -55 to +175 °C<br>Available in Common Anode, Common Cathode and Doubler configuration<br>Dimensions (mm, max.) : 20.07 x 13.59 x 6.3            | ESCC 5106/016        | SMD .5   | • STMicroelectronics |         |

04 DIODES | 03 VOLTAGE REGULATOR

| EPPL Part | Part Type                        | Description   | Detail Specification | Package  | Manufacturer(s)        | Remarks                      |
|-----------|----------------------------------|---|----------------------|----------|------------------------|------------------------------|
| 1         | 1N4099UR-1<br>thru<br>1N4135UR-1 | Silicon, Voltage regulator, Low noise.<br>DC forward voltage (max V): 1.1 @max. forward current : 200 mA<br>Regulator voltage (nom V): 6.8 to 100 @Iz=250 uA dc<br>Voltage tolerance: ± 5% Power (W): 0.5 at Tec= 125°C.<br>Operating Temperature Range (°C.): -65 to +175  | MIL-PRF-19500/435    | DO-213AA | • MICROSEMI LAWRENCE   | Manufacturer Standardization |
| 1         | 1N4464 thru<br>1N4496            | Silicon, Voltage Regulator.<br>DC forward voltage (max V): 1.5 @max. forward current : 1 A<br>Nominal Zener volt. (V): 9.1 - 200 @ Nom. Iz (mA): 28.0 - 1.2<br>Zener tolerance (V): 0.35 - 10.0 Power (W): 1.5<br>Operating Temperature Range (°C.): -55 to +175  | MIL-PRF-19500/406    | Al       | • MICROSEMI SCOTTSDALE | Manufacturer Standardization |
| 1         | 1N4954 thru<br>1N4992            | Silicon, Voltage Regulator.<br>DC forward voltage (max V): 1.5 @max. forward current : 1 A<br>Nominal Zener volt. (V): 6.8 - 270 @ Nom. Iz (mA): 175.0 - 5.0<br>Voltage Regulation (V): 0.7 - 25.0 Power (W): 5.0 at Tl= +65°C.<br>Operating Temperature Range (°C.): -55 to +175                                     | MIL-PRF-19500/356    | A248     | • MICROSEMI SCOTTSDALE | Manufacturer Standardization |
| 1         | 1N6309 thru<br>1N6319            | Silicon, Zener, Voltage regulator, Solid glass noncavity constr.<br>DC forward voltage(max V):1.4 @max If = 1 A* dc<br>Nom. Vz (V): 2.4 to 6.2 @ Nom. Iz (mA): 20<br>Zener tolerance: ± 5% Power (W): 0.5 at Tl=+75°C.<br>Operating Temperature Range (°C.): -65 to +175 *pulsed                                      | MIL-PRF-19500/533    | DO-35    | • MICROSEMI LAWRENCE   | Manufacturer Standardization |
| 1         | 1N6309US<br>thru<br>1N6319US     | Silicon, Zener, Voltage regulator, Solid glass noncavity constr.<br>DC forward voltage(max V):1.4 @max If = 1 A* dc<br>Nom. Vz (V): 2.4 to 6.2 @ Nom. Iz (mA): 20<br>Zener tolerance: ± 5% Power (W): 0.5 at Tec=+125°C.<br>Operating Temperature Range (°C.): -65 to +175 *pulsed                                    | MIL-PRF-19500/533    | SMD      | • MICROSEMI LAWRENCE   | Manufacturer Standardization |
| 1         | 1N6320 thru<br>1N6336            | Silicon, Zener, Voltage Regulator, Solid glass noncavity constr.<br>DC forward voltage (max V): 1.4 @max. forward current : 1 A* dc<br>Nominal Zener volt. (V): 6.8 - 33.0 @ Nom. Iz (mA): 20.0 - 3.8<br>Zener tolerance: ± 5% Power (W): 0.5 at Tl= +75°C.<br>Operating Temperature Range (°C.): -65 to +175 *pulsed | MIL-PRF-19500/533    | DO-204   | • MICROSEMI SCOTTSDALE | Manufacturer Standardization |
| 1         | 1N6320US<br>thru<br>1N6336US     | Silicon, Zener, Voltage Regulator, Solid glass noncavity constr.<br>DC forward voltage (max V): 1.4 @max. forward current : 1 A* dc<br>Nominal Zener volt. (V): 6.8 - 33.0 @ Nom. Iz (mA): 20.0 - 3.8<br>Zener tolerance: ± 5% Power (W): 0.5 at Tl= +75°C.<br>Operating Temperature Range (°C.): -65 to +175 *pulsed | MIL-PRF-19500/533    | MELF     | • MICROSEMI SANTA ANA  | Manufacturer Standardization |

04 DIODES | 04 VOLTAGE REFERENCE/ZENER

| EPPL Part | Part Type                        | Description  | Detail Specification | Package  | Manufacturer(s)      | Remarks                         |
|-----------|----------------------------------|--|----------------------|----------|----------------------|---------------------------------|
| 1         | 1N4568AUR-1                      | Silicon, Low level, Voltage-reference.<br>Nominal Zener Voltage (V): 6.4 @max. forward current (mA): 0.5±0.01 to 4.0±0.01<br>Zener tolerance: ±5%                      Power (W): 0.475 at Ta=+25°C.<br>Operating Temperature Range (°C.): -65 to +175                                       | MIL-PRF-19500/452    | DO-213AA | • MICROSEMI LAWRENCE | Manufacturer<br>Standardization |
| 1         | 1N4614UR-1<br>thru<br>1N4627UR-1 | Silicon, Low-noise Voltage regulator.<br>DC forward voltage (max V): 1.1 @max. forward current 200 mA dc<br>Regulator voltage (max V): 1.8 to 6.2 @Iz= 250 uA<br>Voltage tolerance: ±5%                      Power (W): 0.5 at Tec=+125°C.<br>Operating Temperature Range (°C.): -65 to +175 | MIL-S-19500/435      | DO-213AA | • MICROSEMI LAWRENCE | Manufacturer<br>Standardization |

04 DIODES | 05 RF/MICROWAVE SCHOTTKY (Si)

| EPPL Part | Part Type | Description  | Detail Specification | Package           | Manufacturer(s)                 | Remarks |
|-----------|-----------|--|----------------------|-------------------|---------------------------------|---------|
| 1         | BAS 70    | Microwave, Silicon, Schottky, General purpose.<br>DC reverse volt. (min V): -70 @Ir= 10 uA<br>Reverse current (max nA): 100 @Vr= -56 V<br>Forward voltage (max V): 1.0 @If= 15 mA IFSM= 85 mA (pk)<br>Total Capacitance CT (pF): 1.2 / 2.0 (BAS 70-094 single diode)<br>0.08 (BAS 70-B bridge)<br>Package (max mm): BAS 70-094 DIA 1.45 x 1.35 x 1.95 (T1 package)<br>BAS 70-B 3.60 x 3.60 x 1.60 (HPAC-140 package)<br>Operating Temperature Range (°C.): -55 to +150 | ESCC 5512/020        | HPAC-140<br>or T1 | • INFINEON<br>TECHNOLOGIES A.G. |         |

04 DIODES | 08 TRANSIENT SUPPRESSION

| EPPL Part | Part Type                  | Description  | Detail Specification | Package              | Manufacturer(s)           | Remarks                         |
|-----------|----------------------------|--|----------------------|----------------------|---------------------------|---------------------------------|
| 2         | 1N5629A<br>thru<br>1N5665A | Silicon, transient voltage suppressor.<br>DC reverse current (max uA):1000 to 5 @Vr =5.8 to 171<br>Vbr (min/max V): 6.45/7.14 to 190/210 @Ibr=10 to 1<br>Power (W): 1.0<br>Operating Temperature Range (°C.): -55 to +175                                  | MIL-PRF-19500/500    | DO-13                | • MICROSEMI<br>SCOTTSDALE | Manufacturer<br>Standardization |
| 2         | 1N6124A                    | Silicon, bipolar transient voltage suppressor.<br>Reverse current leakage (max uA): 1 @Vr=27.4 to 152<br>Breakdown voltage (min V):53 @Ibr(mA)=30 to 5<br>Power (W): 2.0<br>Peak Power (W): 500 for 1 ms<br>Operating Temperature Range (°C.): -55 to +175 | MIL-PRF-19500/516    | E (MSCUA<br>Outline) | • MICROSEMI<br>SCOTTSDALE | Manufacturer<br>Standardization |

04 DIODES | 13 RF/MICROWAVE VARACTOR (Si)

| EPPL Part | Part Type                             | Description   | Detail Specification | Package         | Manufacturer(s)               | Remarks |
|-----------|---------------------------------------|---|----------------------|-----------------|-------------------------------|---------|
| 1         | DH 252, DH 256, DH 267, DH 292, DH294 | Microwave, Silicon, Multiplier varactor.<br>Min. Breakdown voltage (V):-45,-40,-30,-20,-15 @ Ir= 10 uA max.<br>Reverse Current (nA): 20 @ Vr= -10V<br>Max. Forward Voltage (V): 0.9 @ If= 10 mA<br>Max. Total Capacitance (pF): 0.5 to 7.2<br>Min. Carrier Lifetime (ns): 6 to 125 @ If= 10 mA and Ir=6.0 mA<br>Max. Snap-off Time (ps): 60 to 400 @ If= 10 mA and Vf= 10 V<br>Max. R.F. Power Dissipation (W): 0.5 to 1.25<br>Operating Temperature Range (°C.): -55 to +150 | ESCC 5512/016        | AS PER SPEC.    | • CHELTON TELECOM & MICROWAVE |         |
| 1         | DH76010 thru DH760150                 | Microwave, Silicon, Tuning varactor, Hyper Abrupt<br>Max. Reverse current (µA) : 10 @ Vr = -20 V.<br>Max Forward voltage (V) : 1 @ If = 10 mA<br>Max Total Capacitance (pF) : 0,9 - 18,30 @ Vr = -4 V, 1 MHz<br>Min. Quality Factor : 100 - 4 @ Vr = -4 V, 1 GHz<br>Operating Temperature Range (°C) : -55 to +150  | ESCC 5512/023        | M208, F27D, F30 | • CHELTON TELECOM & MICROWAVE |         |
| 1         | ML4310 to ML4319                      | Microwave, Silicon, Tuning varactor<br>Reverse current (max uA): 10 @Vr=-25V<br>Forward voltage (max V): 1.0 @If= 100 mA<br>Total Capacitance (max pF): 0.55 - 5.4<br>Quality Factor (min Q): 2750 - 1500<br>Operating Temperature Range (°C.): -65 to +150   | ESCC 5512/003        | AS PER SPEC.    | • Cobham Mal Ltd.             |         |
| 1         | ML4331 to ML4335                      | Microwave, Silicon, Tuning varactor<br>Reverse current (max uA): 10 @Vr=-40V<br>Forward voltage (max V): 1.0 @If= 100 mA<br>Total Capacitance (max pF): 0.79 - 2.60<br>Quality Factor (min Q): 2000 - 1350<br>Operating Temperature Range (°C.): -65 to +150  | ESCC 5512/004        | AS PER SPEC.    | • Cobham Mal Ltd.             |         |
| 1         | ML4336 to ML4343                      | Microwave, Silicon, Tuning varactor<br>Reverse current (max uA): 10 @Vr=-40V<br>Forward voltage (max V): 1.0 @If= 100 mA<br>Total Capacitance (max pF): 3.05 - 11.40<br>Quality Factor (min Q): 1350 - 800<br>Operating Temperature Range (°C.): -65 to +150  | ESCC 5512/005        | AS PER SPEC.    | • Cobham Mal Ltd.             |         |
| 1         | ML4355 to ML4365                      | Microwave, Silicon, Tuning varactor<br>Reverse current (max uA): 10 @Vr=-60V<br>Forward voltage (max V): 1.0 @If= 100 mA<br>Total Capacitance (max pF): 2.45 - 17.10<br>Quality Factor (min Q): 850 - 500<br>Operating Temperature Range (°C.): -65 to +150   | ESCC 5512/007        | AS PER SPEC.    | • Cobham Mal Ltd.             |         |



04 DIODES | 16 RF/MICROWAVE PIN

| EPPL Part | Part Type                      | Description  | Detail Specification | Package                                | Manufacturer(s)                  | Remarks |
|-----------|--------------------------------|--|----------------------|--|----------------------------------|---------|
| 1         | BXY42-MESA                     | Microwave, Silicon, PIN.<br>Reverse current (max uA): 10 @Vr=-50V<br>Forward voltage (max V): 1.1 @If= 100 mA<br>Total Capacitance (max pF): 0.24<br>RF power (W): 0.35 (Var.-01), 0.60 (Var.-02).<br>Minor. carrier life time (min ns): 35 @If= 10 mA<br>Package (max mm): DIA 1.45 x 1.95 x 1.35 variant 01<br>DIA 1.45 x 1.35 variant 02<br>Operating Temperature Range (°C.): -55 to +175                                  | ESCC 5513/017        | T, T1                                  | • INFINEON<br>TECHNOLOGIES A.G.  |         |
| 1         | BXY43/44                       | Microwave, Silicon, PIN.<br>Reverse current (max nA): 100 @Vr=-150V (Var.-01 to -04)<br>@Vr=-200V (Var.-05 to -08)<br>Forward voltage (max V): 1.0 (Var.-01 to -04) @If= 100mA<br>1.05 (Var.-05 to -08) @If= 100mA<br>Total Capacitance Range (pF): 0/0.35 - 0.40/0.85<br>Power Dissipation (W): 0.5<br>Operating Temperature Range (°C.): -55 to +150   | ESCC 5513/030        | T, T1,<br>Teller,<br>Pill,<br>FlatPack | • INFINEON<br>TECHNOLOGIES A.G.  |         |
| 1         | DH50151<br>thru<br>DH50157     | RF/MW PIN, Ultra Fast Switching, VR=-150 V.<br>Variants 01 to 49 of detail spec.   | ESCC 5513/031        | M208,<br>F27D                          | • CHELTON TELECOM &<br>MICROWAVE |         |
| 1         | DH50201<br>thru<br>DH50209     | RF/MW PIN, Ultra Fast Switching, VR=-200 V.<br>Variants 01 to 63 of detail spec.   | ESCC 5513/033        | M208,<br>F27D                          | • CHELTON TELECOM &<br>MICROWAVE |         |
| 1         | DH50251<br>thru<br>DH50256     | RF/MW PIN, Ultra Fast Switching, VR=-250 V.<br>Variants 01 to 36 of detail spec.   | ESCC 5513/034        | M208,<br>F27D                          | • CHELTON TELECOM &<br>MICROWAVE |         |
| 1         | ML4610,<br>4617, 4618,<br>4619 | Microwave, Silicon, PIN, Fast switching.<br>Reverse current (max uA): 10 @Vr=-15V (Var.-01 to -25)<br>@Vr=-100V (Var.-26 to -99)<br>Forward voltage (max V): 1.0 @If= 100mA<br>Total Capacitance Range (max pF): 0.2 - 1.20<br>Minority Carrier Lifetime (max ns): 35 @If= 10mA (Var.-01 to -25)<br>400 @If= 10mA (Var.-26 to -99)<br>R.F. Power Dissipation (W): 0.2 to 3.1<br>Operating Temperature Range (°C.): -65 to +150 | ESCC 5513/009        | AS PER<br>SPEC.                        | • Cobham Mal Ltd.                |         |
| 1         | ML4622 to<br>ML4624            | Microwave, Silicon, PIN, Fast switching.<br>Reverse current (max uA): 10 @Vr=-150V<br>Forward voltage (max V): 1.3 @If= 100mA<br>Total Capacitance Range (max pF): 0.3 - 1.20<br>Minority Carrier Lifetime (max ns): 700 @If= 4.5 mA<br>R.F. Power Dissipation (W): 0.2 to 3.5<br>Operating Temperature Range (°C.): -65 to +125 (Variant -24, -48 and -62)<br>-65 to +150   | ESCC 5513/014        | AS PER<br>SPEC.                        | • Cobham Mal Ltd.                |         |

04 DIODES | 16 RF/MICROWAVE PIN

| EPPL Part | Part Type           | Description   | Detail Specification | Package         | Manufacturer(s)   | Remarks |
|-----------|---------------------|---|----------------------|-----------------|-------------------|---------|
| 1         | ML4627 to<br>ML4629 | Microwave, Silicon, PIN, Fast switching.<br>Reverse current (max uA): 10 @Vr=-200V<br>Forward voltage (max V): 1.3 @If= 100mA<br>Total Capacitance Range (max pF): 0.2 - 1.20<br>Minority Carrier Lifetime (max ns): 1200 @If= 4.5 mA<br>R.F. Power Dissipation (W): 0.2 to 4.1<br>Operating Temperature Range (°C.): -65 to +125 (Variant -24, -48 and -62)<br>-65 to +150 | ESCC 5513/015        | AS PER<br>SPEC. | • Cobham Mal Ltd. |         |

05 FILTERS | 01 FEEDTHROUGH

| EPPL Part | Part Type | Description   | Detail Specification           | Package | Manufacturer(s) | Remarks |
|-----------|-----------|---|--------------------------------|---------|-----------------|---------|
| 1         | SFC 030   | C Filter - Electromagnetic interference suppression, hermetically sealed.<br>Capacitance      Rated      Rated DC      Insertion Loss<br>Range (pF)      Voltage (V)      Current (A)      (dB) @ 1GHz<br>470 to 22000      25 to 250      1.0 to 5.0      34 to 68<br>Size (max mm): DIA 4.10 x 16.90<br>Operating Temperature Range (°C): -55 to + 125  | ESCC 3008/020                  | Axial   | • EUROFARAD     |         |
| 1         | SFC 60    | C Filter - Electromagnetic interference suppression, hermetically (SCC 3008/026) and non-hermetically (SCC 3008/033) sealed.<br>Capacitance      Rated      Rated DC      Insertion Loss<br>Range (pF)      Voltage (V)      Current (A)      (dB) @ 1GHz<br>680 to 220000      25 to 200      10      37 to 70<br>Size (max mm): DIA 6 x 20 (hermetically sealed)<br>Size (max mm): DIA 6 x 32 (non-hermetically sealed)<br>Operating Temperature Range (°C): -55 to + 125 | ESCC 3008/026 -<br>3008/033    | Axial   | • EUROFARAD     |         |
| 1         | SFL 100   | L Filter - Electromagnetic interference suppression, hermetically sealed<br>Capacitance      Rated      Rated DC      Insertion Loss<br>Range (uF)      Voltage (V)      Current (A)      (dB) @ 1GHz<br>0.0176 to 1.6      40 to 300      5, 10, 15      57 to 70<br>Size (max mm) : DIA 9.90 x 27.30<br>Operating Temperature Range (°C): -55 to + 125  | ESCC 3008/029                  | Axial   | • EUROFARAD     |         |
| 1         | SFP 035   | Pi Filter - Electromagnetic interference suppression, non hermetically sealed.<br>Capacitance      Rated      Rated DC      Insertion loss<br>Range (pF)      Voltage (V)      Current (A)      (dB) @ 1GHz<br>3520 to 35200      35 to 200      10      50/55 to 70/70 (*)<br>(*) With no current applied / With current applied<br>Size (max mm): DIA 4.1 x 25<br>Operating Temperature Range (°C): -55 to + 125  | ESCC 3008/025                  | Axial   | • EUROFARAD     |         |
| 1         | SFP 040   | Pi Filter - Electromagnetic interference suppression, non hermetically sealed.<br>Capacitance      Rated      Rated DC      Insertion loss<br>Range(pF)      Voltage (V)      Current (A)      (dB) @ 1GHz<br>750 to 44800      100,200,250      10 (DC/LF)      40/35 to 75/75 (*)<br>(*) With no current applied / With current applied<br>Size (max mm): DIA 5 x 31<br>Operating Temperature Range (°C): -55 to + 125  | ESCC 3008/014                  | Axial   | • EUROFARAD     |         |
| 1         | SFP 060   | Pi Filter - Electromagnetic interference suppression, hermetically sealed.<br>Capacitance      Rated      Rated DC      Insertion loss<br>Range (pF)      Voltage (V)      Current (A)      (dB) @ 1GHz<br>2400 to 89600      35 to 500      10      65 to 75<br>Size (max mm): DIA 7.1 x 26.5<br>Operating Temperature Range (°C): -55 to + 125  | ESCC 3008/021<br>ESCC 3008/030 | Axial   | • EUROFARAD     |         |

06 FUSES | 01 ALL

| EPPL Part | Part Type | Description   | Detail Specification | Package | Manufacturer(s) | Remarks |
|-----------|-----------|---|----------------------|---------|-----------------|---------|
| 1         | MGA-S     | Surface mount, Thin Film<br>Rated Voltage (VAC or VDC): 125/125, 63/125 and 32/125 by variant<br>AC Interrupt Current (A): 50 at maximum rated voltage, power factor > 0.95<br>DC Interrupt Current (A): at maximum rated voltage, time constant &#8804; 1 ms:<br>Variants 01 to 10: 300<br>Variants 11 and 12: 50<br>Rated Current (VAC and VDC): 0.14 to 3.5 A by variant<br>Operating Temperature Range, (°C): -50 to +125 (90% IR to 107% IR) | ESCC 4008/001        | SMD     | • Schurter AG   |         |

07 INDUCTORS | 03 CHIP

| EPPL Part | Part Type  | Description  | Detail Specification | Package | Manufacturer(s) | Remarks |
|-----------|------------|--|----------------------|---------|-----------------|---------|
| 1         | MSCI 10000 | RF, Moulded, Surface mount.<br>Inductance Range (uH)    Tol. (%)    Rated DC Current (mA)    Q min<br>0.010 to 10                    10                    750 to 87                    60 to 42<br>Dielectric withstanding voltage (Vrms): 200<br>Size (max mm): 2.67 x 2.80 x 2.16<br>Operating Temperature Range (°C.): -55 to +125.    | ESCC 3201/008        | SMD     | • MICROSPIRE    |         |
| 1         | MSCI 12000 | RF, Moulded, Surface mount.<br>Inductance Range (uH)    Tol. (%)    Rated DC Current (mA)    Q min<br>12 to 1000                    10                    110 to 15                    37 to 12<br>Dielectric withstanding voltage (Vrms): 200<br>Size (max mm): 2.67 x 2.80 x 2.54<br>Operating Temperature Range (°C.): -55 to +125.     | ESCC 3201/008        | SMD     | • MICROSPIRE    |         |
| 1         | MSCI 20000 | RF, Moulded, Surface mount.<br>Inductance Range (uH)    Tol. (%)    Rated DC Current (mA)    Q min<br>0.010 to 1000                    10                    1000 to 25                    75 to 30<br>Dielectric withstanding voltage (Vrms): 200<br>Size (max mm): 3.38 x 4.14 x 3.30<br>Operating Temperature Range (°C.): -55 to +125. | ESCC 3201/008        | SMD     | • MICROSPIRE    |         |

07 INDUCTORS | 99 MISCELLANEOUS

| EPPL Part | Part Type | Description  | Detail Specification | Package | Manufacturer(s) | Remarks |
|-----------|-----------|--|----------------------|---------|-----------------|---------|
| 1         | SESI 15   | Power, Moulded, Surface mount.<br>Inductance Range (uH) Tol. (%) Rated DC Current (mA)<br>1.5 to 330 10 14 to 0.74<br>Dielectric withstanding voltage (Vrms): 500<br>Size (max mm): 16.0 x 16.5 x 7.5<br>Operating Temperature Range (°C.): -55 to +125. | ESCC 3201/009        | SMD     | • MICROSPIRE    |         |
| 1         | SESI 9.1  | Power, Moulded, Surface mount.<br>Inductance Range (uH) Tol. (%) Rated DC Current (mA)<br>1 to 1000 10 6.0 to 0.2<br>Dielectric withstanding voltage (Vrms): 500<br>Size (max mm): 10.7 x 10.6 x 5.8<br>Operating Temperature Range (°C.): -55 to +125.  | ESCC 3201/009        | SMD     | • MICROSPIRE    |         |

08 MICROCIRCUITS | 10 MICROPROCESS/ MICROCONTROL /PERIPHER

| EPPL Part | Part Type | Description   | Detail Specification | Package  | Manufacturer(s) | Remarks                            |
|-----------|-----------|---|----------------------|----------|-----------------|------------------------------------|
| 2         | AT697E    | SPARC V8 Processor based on ESA LEON2 FT model, produced on the AT58KRHA process using ATC18 standard cell library.<br>100 MHz, 85 Mips, 60kRad, Latch-up immune, SET hardned<br><br>Operating temperature range: -55 / +125 °C | PS-AT697E            | 349 MCGA | • ATMEL         | QXB variant obsolete               |
| 1         | AT7908E   | CAN Controller<br>Programmable MCU 8-bit general-purpose interface<br>Operating temperature range -55 to +125 °C  | SMD/5962-03A06       | MLCC 44  | • ATMEL         | ESCC specification under issueing  |
| 1         | TSC695F   | Single chip, 32 bit, SPARC Microprocessor<br>Process SCMOS3/2RTP<br>Operating temperature range : -55 / +125 °C   | ESCC 9512/003        | QFP 256  | • ATMEL         | Also available with SMD/5962-00540 |
| 1         | TSC695FL  | Single chip, 32 bit, SPARC Microprocessor<br>Specified at 3.3 V with 12 MIPs<br>Process SCMOS3/2RTP<br>Operating temperature range : -55 / +125 °C  | SMD/5962-03246       | MQFP256  | • ATMEL         |                                    |

## 08 MICROCIRCUITS | 20 MEMORY SRAM

| EPPL Part | Part Type       | Description  | Detail Specification | Package | Manufacturer(s) | Remarks  |
|-----------|-----------------|--|----------------------|---------|-----------------|--|
| 1         | AT60142H        | 3.3 V 512Kx8 SRAM<br>High speed, rad-hard version<br>Operating temperature range : -55 / +125 °C       | SMD 5962-05208       | FP36    | • ATMEL         | SEE behaviour should be verified where necessary |
| 1         | AT60142HT       | 5V tolerant 512Kx8 SRAM<br>High speed, rad-hard version<br>Operating temperature range : -55 / +125 °C | SMD 5962-05208       | FP36    | • ATMEL         |  |
| 1         | SMDJ-65608EV-30 | 128Kx8 SRAM<br>Variant 06 of ESCC 9301/047   | ESCC 9301/047        | FP-32   | • ATMEL         | Also available with SMD/5962-89598               |
| 1         | SMDJ-65609E     | 3.3 V 128Kx8 SRAM<br>Operating temperature range : -55 / +125 °C                                       | ESCC 9301/053        | FP 32   | • ATMEL         | Also available with SMD/5962-02501               |



## 08 MICROCIRCUITS | 21 MEMORY DRAM

| EPPL Part | Part Type           | Description                         | Detail Specification                               | Package         | Manufacturer(s) | Remarks |
|-----------|---------------------|-------------------------------------|--|-----------------|-----------------|---------|
| 2         | MMSD3203260<br>2S-J | 1 Gb (32M x 32) SDRAM memory module | 3DPA-1600-4<br>(Detail), 3DPF-<br>0141-4 (Generic) | SOP 70-<br>0635 | • 3D-Plus       |         |

## 08 MICROCIRCUITS | 30 PROGRAMMABLE LOGIC

---

| EPPL Part | Part Type  | Description   | Detail Specification | Package  | Manufacturer(s) | Remarks                               |
|-----------|------------|---|----------------------|----------|-----------------|---------------------------------------|
| 1         | AT40KEL040 | 40k Gates SEU hardened reprogrammable FPGA<br>DSP Optimized Core Cell and Distributed FreeRam, Enhanced Performance Improvement<br>and Bi-directional I/Os (3.3 V)<br>Operating temperature range: -55 to +125 °C | ESCC 9304/008        | MQFP 160 | • ATMEL         | Also available with<br>SMD/5962-03250 |

---

08 MICROCIRCUITS | 40 ASIC TECHNOLOGIES DIGITAL

| EPPL Part | Part Type | Description   | Detail Specification | Package | Manufacturer(s) | Remarks   |
|-----------|-----------|---|----------------------|---------|-----------------|---|
| 1         | ATC18RHA  | <p>0.18u CMOS ASIC standard cell library with predefined matrix sizes:</p> <p>ATC18RHA95_216 allowing to integrate typically 1Mgates<br/>                     ATC18RHA95_324 allowing to integrate typically 2.2Mgates<br/>                     ATC18RHA95_404 allowing to integrate typically 3.5Mgates<br/>                     ATC18RHA95_504 allowing to integrate typically 5.5Mgates</p> <p>Predefined combinations of matrix and package:<br/>                     196 to 352 MQFP<br/>                     Operating temperature range : -55 / +125 C</p> | SMD/5962-06B02       | MQFP    | • ATMEL         |   |
| 1         | MH1RT     | <p>Sea of gates with up to 1600K available gates with embedded blocks option</p> <p>Available matrices :</p> <p>MH1099E (520K used gates)<br/>                     MH1156E (760K used gates)<br/>                     MH1242E (1190K used gates)<br/>                     MH1332E (1640K used gates)</p> <p>Operating temperature range : -55 / +125 °C<br/>                     Storage temperature range : -65 / +150 °C</p>  | ESCC 9202/076        | MQFP    | • ATMEL         | ESCC Specification issued, preferred to SMD-5962-01B01. ESCC QML qualified. |

## 08 MICROCIRCUITS | 50 LINEAR OPERATIONAL AMPLIFIER

| EPPL Part | Part Type   | Description  | Detail Specification | Package             | Manufacturer(s)             | Remarks   |
|-----------|-------------|--|----------------------|---------------------|-----------------------------|---|
| 1         | LM124AW     | Low Power Quad Bipolar Operational Amplifier<br>Operating temperature range: -55 / +125 °C                 | SMD/5962-99504       | FP-14               | • NATIONAL<br>SEMICONDUCTOR | Part is R level<br>(100 kRad(Si)) TID<br>tolerant, Var. 02<br>is "not sensitive<br>to low dose rate";<br>it is recommended<br>to procure P/N<br>5962R9950402VDA (no<br>lower TID levels). |
| 1         | OP27A       | Single, Ultra-Low Noise and Offset, Internally Compensated Operational Amplifier                           | SMD/5962-94680       | DIL<br>Metal<br>Can | • ANALOG DEVICES            |   |
| 1         | OP470AY     | Operational Amplifier, Quad, Very Low Noise  | SMD/5962-88565       | DIL                 | • ANALOG DEVICES            |   |
| 1         | OP77        | Ultra low offset Voltage Operational Amplifier (replacement of OP-07 and OP-108A).                         | SMD/5962-87738       | LCC20<br>FP10       | • ANALOG DEVICES            |   |
| 1         | RHF310K-01V | Operational Amplifier Single, High Speed, Current Feedback<br>Operating temperature range: -55 / +125 °C   | SMD/5962-07233       | FP-8                | • STMicroelectronics        |   |
| 1         | RHF330K-01V | Operational Amplifier, Single, High Speed, Current Feedback<br>Operating Temperature Range: -55 to +125 °C | SMD/5962-07231       | FP-8                | • STMicroelectronics        | New component   |
| 1         | RHF43B      | Operational Amplifier, Single<br>Operating Temperature Range: -55 to +125 °C                               | SMD/5962-06237       | FP-8                | • STMicroelectronics        |   |

## 08 MICROCIRCUITS | 52 LINEAR VOLTAGE REGULATOR

| EPPL Part | Part Type       | Description   | Detail Specification | Package        | Manufacturer(s)             | Remarks |
|-----------|-----------------|---|----------------------|----------------|-----------------------------|---------|
| 1         | LM117H          | 3-Terminal Adjustable Positive Regulator, 0.5A                                      | SMD/5962-99517       | TO-39          | • NATIONAL<br>SEMICONDUCTOR |         |
| 1         | LM117K          | 3-Terminal Adjustable Positive Regulator, 1.5A                                      | SMD/5962-99517       | TO-3           | • NATIONAL<br>SEMICONDUCTOR |         |
| 1         | LM137H          | 3 Terminal Adjustable Negative Regulator, 0.5A                                      | SMD/5962-99517       | TO-39          | • NATIONAL<br>SEMICONDUCTOR |         |
| 1         | RH-L4913        | Fixed, Positive, 2.5 V, 2A<br>Operating temperature range: -55 / +125 °C            | SMD/5962-02534       | FP16,<br>SMD.5 | • STMicroelectronics        |         |
| 1         | RH-L4913        | Fixed, Positive, 3.3 V, 2A<br>Operating temperature range: -55 / +125 °C            | SMD/5962-02535       | FP16,<br>SMD.5 | • STMicroelectronics        |         |
| 1         | RH-L4913 5      | Fixed, Positive, 5 V, 2A<br>Operating temperature range: -55 / +125 °C              | SMD/5962-02536       | FP16,<br>SMD.5 | • STMicroelectronics        |         |
| 1         | RH-L4913<br>ADJ | Adjustable, Positive, Low Dropout, 2A<br>Operating temperature range: -55 / +125 °C | SMD/5962-02524       | FP16           | • STMicroelectronics        |         |
| 1         | RH-L7913<br>ADJ | Adjustable, Negative, Low Dropout, 2A<br>Operating temperature range: -55 / +125 C  | SMD/5962-02532       | FP-16          | • STMicroelectronics        |         |

## 08 MICROCIRCUITS | 53 LINEAR VOLTAGE COMPARATOR

| EPPL Part | Part Type | Description   | Detail Specification | Package               | Manufacturer(s)             | Remarks                |
|-----------|-----------|---|----------------------|-----------------------|-----------------------------|------------------------|
| 1         | AD584SH   | Voltage Reference, Precision Pin Programmable<br>Variant 01 od SMD/5962-38128 (S precision type)<br><br>Operating Temperature range: -55 to +125 °C | SMD/5962-38128       | 8-Pin<br>Metal<br>Can | • ANALOG DEVICES            |                        |
| 1         | LM111W    | Voltage Comparator/Buffer, Precision  | SMD/5962-00524       | FP                    | • NATIONAL<br>SEMICONDUCTOR |                        |
| 1         | LM119     | Dual, High Speed Voltage Comparator   | SMD/5962-96798       | FP                    | • NATIONAL<br>SEMICONDUCTOR | Part is not ELDRS-free |
| 1         | LM139AWR  | Quad, Single Supply, Low Power Voltage Comparator   | SMD/5962-96738       | FP14                  | • NATIONAL<br>SEMICONDUCTOR |                        |
| 1         | LM193AH   | Dual, Low Power, Low Offset Voltage Comparator  | SMD/5962-94526       | Metal<br>Can          | • NATIONAL<br>SEMICONDUCTOR | Part is not ELDRS-free |

08 MICROCIRCUITS | 61 LINEAR ANALOG TO DIGITAL CONVERTER

| EPPL Part | Part Type      | Description  | Detail Specification | Package | Manufacturer(s)      | Remarks |
|-----------|----------------|--|----------------------|---------|----------------------|---------|
| 1         | AD574AT        | A/D Converter, 12-Bit, High Speed, with Microprocessor Interface   | SMD 5962-85127       | FP      | • ANALOG DEVICES     |         |
| 1         | RHF1201KSO-01V | Rad-Hard, 12 bit, 0.5 to 50 MHz sampling frequency Analog-to-Digital Converter<br>CMOS, 0.25 um technology<br>Operating temperature range: -55 / +125 °C | SMD/5962-05217       | FP-48   | • STMicroelectronics |         |
| 1         | RHF1401        | Rad-Hard 14-bit 20Msps 85mW A/D Converter<br>Operating Temperature Range: -55 to +125 °C   | SMD/5962-0626        | SO-48   | • STMicroelectronics |         |

08 MICROCIRCUITS | 62 LINEAR DIGITAL TO ANALOG CONVERTER

---

| EPPL Part | Part Type | Description                           | Detail Specification | Package | Manufacturer(s)  | Remarks |
|-----------|-----------|---------------------------------------|----------------------|---------|------------------|---------|
| 1         | DAC08     | 8-Bit D/A Converters, 0.19% Linearity | SMD/5962-89932       | DIL     | • ANALOG DEVICES |         |

---



08 MICROCIRCUITS | 69 LINEAR OTHER FUNCTIONS

| EPPL Part | Part Type | Description   | Detail Specification | Package        | Manufacturer(s)     | Remarks               |
|-----------|-----------|---|----------------------|----------------|---------------------|-----------------------|
| 1         | AD590M    | Temperature Transducer, Two Terminals<br>Forward voltage (E+ to E-)(Vdc): +44<br>Forward voltage (E- to E+)(Vdc): -20<br>Breakdown voltage (Case to E+ or E-)(Vdc): ± 200<br>Rated performance temperature range (°C.): -55 to +150 | SMD/5962-87571       | FP             | • ANALOG DEVICES    |                       |
| 1         | UC1707    | High Speed Schottky, Dual Channel Power Driver.   | SMD/5962-87619       | DIL16<br>LCC20 | • TEXAS INSTRUMENTS | Part is not ELDR-free |

## 08 MICROCIRCUITS | 80 LOGIC FAMILIES

| EPPL Part | Part Type | Description                                    | Detail Specification | Package | Manufacturer(s)      | Remarks  |
|-----------|-----------|--|----------------------|---------|----------------------|--|
| 1         | 4001B     | QUAD 2-INPUT NOR GATE                          | ESCC 9201/041        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 40103B    | PRESETTABLE 8-BIT SYNCHRONOUS DOWN-COUNTER     | ESCC 9204/036        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 40105B    | FIFO REGISTER WITH 3-STATE OUTPUT              | ESCC 9306/033        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 40106B    | HEX SCHMITT TRIGGER                            | ESCC 9409/005        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 40107B    | DUAL 2-INPUT NAND BUFFER / DRIVER              | ESCC 9401/013        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 40109B    | QUAD LOW-TO-HIGH 3-STATE VOLTAGE LEVEL SHIFTER | ESCC 9407/003        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4011B     | QUAD 2 INPUT NAND GATE                         | ESCC 9201/043        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4013B     | DUAL D-TYPE FLIP-FLOP                          | ESCC 9203/023        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |

## 08 MICROCIRCUITS | 80 LOGIC FAMILIES

| EPPL Part | Part Type | Description  | Detail Specification | Package | Manufacturer(s)      | Remarks  |
|-----------|-----------|--|----------------------|---------|----------------------|--|
| 1         | 4014B     | 8-STAGE SYNCHRONOUS STATIC SHIFT REGISTER                              | ESCC 9306/014        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4015B     | DUAL 4-STAGE STATIC SHIFT REGISTER WITH SERIAL INPUT / PARALLEL OUTPUT | ESCC 9306/015        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 40161B    | PROGRAMMABLE 4-BIT BINARY COUNTER WITH ASYNCHRONOUS CLEAR              | ESCC 9204/054        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 40174B    | HEX D-TYPE FLIP-FLOP   | ESCC 9203/038        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4017B     | DECADE COUNTER / DIVIDER   | ESCC 9204/020        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4019B     | QUAD AND/OR SELECT GATE  | ESCC 9202/051        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4020B     | 14-STAGE RIPPLE CARRY BINARY COUNTER / DIVIDER                         | ESCC 9204/022        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4021B     | 8-STAGE STATIC SHIFT REGISTER  | ESCC 9306/016        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |

## 08 MICROCIRCUITS | 80 LOGIC FAMILIES

| EPPL Part | Part Type | Description                                      | Detail Specification | Package | Manufacturer(s)      | Remarks  |
|-----------|-----------|--|----------------------|---------|----------------------|--|
| 1         | 4023B     | TRIPLE 3-INPUT NAND GATE                         | ESCC 9201/045        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4024B     | 7-STAGE RIPPLE CARRY BINARY COUNTER / DIVIDER    | ESCC 9204/024        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4027B     | DUAL J-K MASTER-SLAVE FLIP-FLOP                  | ESCC 9203/022        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4028B     | BCD-TO-DECIMAL OR BINARY-TO-OCTAL DECODER        | ESCC 9205/010        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4029B     | PRESETTABLE UP/DOWN COUNTER BINARY OR BCD DECADE | ESCC 9204/025        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4030B     | QUAD 2-INPUT EXCLUSIVE OR GATE                   | ESCC 9201/047        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4035B     | 4-BIT UNIVERSAL SHIFT REGISTER                   | ESCC 9306/018        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4040B     | 12-STAGE RIPPLE CARRY BINARY COUNTER / DIVIDER   | ESCC 9204/026        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |

## 08 MICROCIRCUITS | 80 LOGIC FAMILIES

| EPPL Part | Part Type | Description                                  | Detail Specification | Package | Manufacturer(s)      | Remarks  |
|-----------|-----------|--|----------------------|---------|----------------------|--|
| 1         | 4047B     | LOW POWER MONOSTABLE / ASTABLE MULTIVIBRATOR | ESCC 9207/003        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4049UB    | HEX BUFFER-CONVERTER (INVERTING TYPE)        | ESCC 9202/045        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4050B     | HEX BUFFER-CONVERTER (NON-INVERTING TYPE)    | ESCC 9202/046        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4051B     | ANALOGUE MULTIPLEXER / DEMULTIPLEXER         | ESCC 9202/047        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4063B     | 4-BIT MAGNITUDE COMPARATOR                   | ESCC 9209/001        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4066B     | QUAD BILATERAL SWITCH                        | ESCC 9408/005        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4069UB    | HEX INVERTER                                 | ESCC 9401/010        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4071B     | QUAD 2-INPUT OR GATE                         | ESCC 9201/063        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |

## 08 MICROCIRCUITS | 80 LOGIC FAMILIES

| EPPL Part | Part Type | Description  | Detail Specification | Package | Manufacturer(s)      | Remarks  |
|-----------|-----------|--|----------------------|---------|----------------------|--|
| 1         | 4073B     | TRIPLE 3-INPUT AND GATE  | ESCC 9201/064        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4076B     | 4-BIT D TYPE REGISTER WITH 3-STATE OUTPUT  | ESCC 9306/022        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4081B     | 8 INPUT OR-NOR GATE  | ESCC 9201/052        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4093B     | QUAD 2 INPUT NAND GATE WITH SCHMITT TRIGGER INPUT  | ESCC 9409/002        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4094B     | 8-STAGE SHIFT AND STORE BUS REGISTER WITH SYNCHRONOUS SERIAL OUTPUTS AND 3-STATE PARALLEL OUTPUT | ESCC 9306/026        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4098B     | DUAL MONOSTABLE MULTIVIBRATOR  | ESCC 9206/003        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4099B     | 8-BIT ADDRESSABLE LATCH  | ESCC 9202/058        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4502B     | STROBED HEX INVERTER / BUFFER  | ESCC 9401/006        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |

## 08 MICROCIRCUITS | 80 LOGIC FAMILIES

| EPPL Part | Part Type | Description   | Detail Specification | Package | Manufacturer(s)      | Remarks  |
|-----------|-----------|---|----------------------|---------|----------------------|--|
| 1         | 4503B     | HEX NON-INVERTING BUFFER WITH 3-STATE OUTPUT                  | ESCC 9401/030        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4508B     | DUAL 4-BIT LATCH WITH 3-STATE OUTPUT                          | ESCC 9202/063        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4512B     | 8-CHANNEL MULTIPLEXER WITH 3-STATE OUTPUT                     | ESCC 9408/006        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 4555B     | DUAL 1-OF-4 DECODER / DEMULTIPLEXER                           | ESCC 9408/011        | FP      | • STMicroelectronics | 100 kRad(Si) TID test performed on each wafer lot i.a.w. ST internal procedure |
| 1         | 54AC00    | Quad 2-Input NAND Gate  | SMD/5962-87549       | FP      | • STMicroelectronics |  |
| 1         | 54AC02    | Quad 2-Input NOR Gate   | SMD/5962-87612       | FP      | • STMicroelectronics |  |
| 1         | 54AC04    | Hex Inverter  | SMD/5962-87609       | FP      | • STMicroelectronics |  |
| 1         | 54AC08    | Quad 2-Input AND Gate   | SMD/5962-87615       | FP      | • STMicroelectronics |  |
| 1         | 54AC10    | Triple 3-Input NAND Gate                                      | SMD/5962-87610       | FP      | • STMicroelectronics |  |
| 1         | 54AC11    | Triple 3-Input AND Gate                                       | SMD/5962-87611       | FP      | • STMicroelectronics |  |
| 1         | 54AC138   | Decoder/Demultiplexer, 3-to-8 line                            | SMD/5962-87622       | FP      | • STMicroelectronics |  |
| 1         | 54AC139   | Dual 2 To 4 Line Decoder/Demultiplexer, with Inverted Outputs | SMD/5962-87623       | FP      | • STMicroelectronics |  |
| 1         | 54AC14    | Hex Schmitt Trigger Inverter                                  | SMD/5962-87624       | FP      | • STMicroelectronics |  |
| 1         | 54AC157   | Quad 2-Input Multiplexer                                      | SMD/5962-89539       | FP      | • STMicroelectronics |  |

## 08 MICROCIRCUITS | 80 LOGIC FAMILIES

| EPPL Part | Part Type | Description   | Detail Specification | Package | Manufacturer(s)      | Remarks |
|-----------|-----------|---|----------------------|---------|----------------------|---------|
| 1         | 54AC161   | Synchronous 4-Bit Binary Counter  | SMD/5962-89561       | FP      | • STMicroelectronics |         |
| 1         | 54AC16244 | 16 bit Buffer/Driver with three-state outputs                               | SMD/5962-04210       | FP      | • STMicroelectronics |         |
| 1         | 54AC240   | Octal Bus Buffer with Inverted 3-State Outputs                              | SMD/5962-87550       | FP      | • STMicroelectronics |         |
| 1         | 54AC244   | Octal Buffer/Line Driver with 3-State Outputs                               | SMD/5962-87552       | FP      | • STMicroelectronics |         |
| 1         | 54AC245   | Bus Transceiver, 8-Bit, Bidirectional, with 3-State Inputs/Outputs          | SMD/5962-87758       | FP      | • STMicroelectronics |         |
| 1         | 54AC273   | Octal D-Type Flip-Flop with Clear   | SMD/5962-87756       | FP      | • STMicroelectronics |         |
| 1         | 54AC32    | Quad 2-Input OR Gate  | SMD/5962-87614       | FP      | • STMicroelectronics |         |
| 1         | 54AC373   | Octal D-Type Transparent Latches with 3-State Outputs                       | SMD/5962-87555       | FP      | • STMicroelectronics |         |
| 1         | 54AC374   | Octal D-Type Flip-Flop with 3-State Outputs                                 | SMD/5962-87694       | FP      | • STMicroelectronics |         |
| 1         | 54AC541   | Octal Bus Buffer with 3-State Outputs                                       | SMD/5962-88706       | FP      | • STMicroelectronics |         |
| 1         | 54AC74    | Octal D-Type Flip-Flop with 3-State Outputs                                 | SMD/5962-88520       | FP      | • STMicroelectronics |         |
| 1         | 54AC86    | Quad 2-Input Exclusive OR Gate  | SMD/5962-89550       | FP      | • STMicroelectronics |         |
| 1         | 54ACT00   | Quad 2-Input NAND Gate, with TTL Compatible Inputs                          | SMD/5962-87699       | FP      | • STMicroelectronics |         |
| 1         | 54ACT240  | Octal Bus Buffer with Inverted 3-State Outputs, TTL Compatible Inputs       | SMD/5962-87759       | FP      | • STMicroelectronics |         |
| 1         | 54ACT244  | Octal Buffer/Line Driver with 3-State Outputs, TTL Compatible Inputs        | SMD/5962-87760       | FP      | • STMicroelectronics |         |
| 1         | 54ACT245  | Octal Bidirectional Transceiver with 3-State Outputs, TTL Compatible Inputs | SMD/5962-87663       | FP      | • STMicroelectronics |         |
| 1         | 54ACT574  | Octal D-Type Flip-Flop with 3-State Outputs, TTL Compatible Inputs          | SMD/5962-89601       | FP      | • STMicroelectronics |         |
| 1         | 54ACT86   | Quad 2-Input Exclusive OR Gate, TTL Compatible Inputs                       | SMD/5962-90687       | FP      | • STMicroelectronics |         |
| 1         | 54HC00    | Quad 2-Input NAND Gate  | ESCC 9201/105        | FP      | • STMicroelectronics |         |



## 08 MICROCIRCUITS | 80 LOGIC FAMILIES

| EPPL Part | Part Type | Description  | Detail Specification | Package | Manufacturer(s)      | Remarks |
|-----------|-----------|--|----------------------|---------|----------------------|---------|
| 1         | 54HC02    | Quad 2-Input NOR Gate  | ESCC 9201/113        | FP      | • STMicroelectronics |         |
| 1         | 54HC03    | Quad 2-Input Nand Gate with Open Drain Output                      | ESCC 9201/114        | FP      | • STMicroelectronics |         |
| 1         | 54HC04    | Hex Inverter   | ESCC 9401/033        | FP      | • STMicroelectronics |         |
| 1         | 54HC08    | Quad 2-Input Positive AND Gate                                     | ESCC 9201/106        | FP      | • STMicroelectronics |         |
| 1         | 54HC10    | Triple 3-Input NAND Gate   | ESCC 9201/107        | FP      | • STMicroelectronics |         |
| 1         | 54HC109   | Dual J-K Positive Edge Triggered Flip-Flop with Preset and Clear   | ESCC 9306/048        | FP      | • STMicroelectronics |         |
| 1         | 54HC11    | Triple 3-Input AND Gate  | ESCC 9201/117        | FP      | • STMicroelectronics |         |
| 1         | 54HC125   | Quad Bus Buffers with 3 State Outputs                              | ESCC 9401/039        | FP      | • STMicroelectronics |         |
| 1         | 54HC132   | Quad 2-Input NAND Gate with Schmitt-trigger Inputs                 | ESCC 9201/120        | FP      | • STMicroelectronics |         |
| 1         | 54HC138   | 3-to-8 Line Decoders/Demultiplexers with Inverted Outputs          | ESCC 9408/046        | FP      | • STMicroelectronics |         |
| 1         | 54HC139   | Dual 2-to-4-line Decoders/Demultiplexers with Inverted Outputs     | ESCC 9205/017        | FP      | • STMicroelectronics |         |
| 1         | 54HC14    | Hex Schmitt Trigger Inverter                                       | ESCC 9409/007        | FP      | • STMicroelectronics |         |
| 1         | 54HC151   | 8-line to 1-line Data Selectors/Multiplexer                        | ESCC 9408/054        | FP      | • STMicroelectronics |         |
| 1         | 54HC154   | 4-to-6 Line Decoder/Demultiplexer with Inverted Output             | ESCC 9205/023        | FP      | • STMicroelectronics |         |
| 1         | 54HC157   | Quad 2-line to 1-line Data Selectors/Multiplexers                  | ESCC 9408/057        | FP      | • STMicroelectronics |         |
| 1         | 54HC158   | Quad 2-to-1-Line Data Selectors/Multiplexers with Inverted Outputs | ESCC 9408/059        | FP      | • STMicroelectronics |         |
| 1         | 54HC161   | Asynchronous 4-Bit Binary Counter                                  | ESCC 9204/059        | FP      | • STMicroelectronics |         |
| 1         | 54HC163   | Synchronous 4-Bit Binary Counter                                   | ESCC 9204/073        | FP      | • STMicroelectronics |         |
| 1         | 54HC164   | 8-bit Sipo Shift Register  | ESCC 9306/041        | FP      | • STMicroelectronics |         |

## 08 MICROCIRCUITS | 80 LOGIC FAMILIES

| EPPL Part | Part Type | Description  | Detail Specification | Package | Manufacturer(s)      | Remarks |
|-----------|-----------|--|----------------------|---------|----------------------|---------|
| 1         | 54HC165   | 8-bit Sipo Shift Register  | ESCC 9306/042        | FP      | • STMicroelectronics |         |
| 1         | 54HC166   | 8-bit Piso Shift Register  | ESCC 9306/043        | FP      | • STMicroelectronics |         |
| 1         | 54HC174   | Hex D-Type Edge-triggered Flip-Flop with Clear                   | ESCC 9306/052        | FP      | • STMicroelectronics |         |
| 1         | 54HC175   | Quad D-Type Edge-triggered Flip-Flop with Clear                  | ESCC 9203/052        | FP      | • STMicroelectronics |         |
| 1         | 54HC191   | Synchronous 4-Bit Up/Down Binary Counter                         | ESCC 9204/066        | FP      | • STMicroelectronics |         |
| 1         | 54HC193   | Synchronous 4-Bit Up/Down Binary Counter (Dual Clock with Clear) | ESCC 9204/065        | FP      | • STMicroelectronics |         |
| 1         | 54HC20    | Dual 4-Input NAND Gate   | ESCC 9201/118        | FP      | • STMicroelectronics |         |
| 1         | 54HC21    | Dual 4-Input AND Gate  | ESCC 9201/108        | FP      | • STMicroelectronics |         |
| 1         | 54HC237   | 3-to-8-Line Decoder/Demultiplexer with Address Latch             | ESCC 9205/021        | FP      | • STMicroelectronics |         |
| 1         | 54HC240   | Octal Bus Buffer with Inverted 3-State Outputs                   | ESCC 9401/034        | FP      | • STMicroelectronics |         |
| 1         | 54HC244   | Octal Bus Buffer with 3-State Outputs                            | ESCC 9401/048        | FP      | • STMicroelectronics |         |
| 1         | 54HC245   | Octal Bus Transceiver with 3-State Outputs                       | ESCC 9405/013        | FP      | • STMicroelectronics |         |
| 1         | 54HC257   | Quad 2-to-1-Line Data Selector/Multiplexer with 3-State Outputs  | ESCC 9408/047        | FP      | • STMicroelectronics |         |
| 1         | 54HC27    | Triple 3-Input NOR Gate  | ESCC 9201/109        | FP      | • STMicroelectronics |         |
| 1         | 54HC273   | Octal D-Type Edge-triggered Flip-Flop with Clear                 | ESCC 9203/053        | FP      | • STMicroelectronics |         |
| 1         | 54HC283   | 4-Bit Binary Full Adders with Fast Carry                         | ESCC 9202/075        | FP      | • STMicroelectronics |         |
| 1         | 54HC32    | Quad 2-Input OR Gate   | ESCC 9201/111        | FP      | • STMicroelectronics |         |
| 1         | 54HC373   | Octal D-Type Transparent Latches with 3-State Outputs            | ESCC 9203/059        | FP      | • STMicroelectronics |         |
| 1         | 54HC374   | Octal D-Type Edge-triggered Flip-Flop with 3-State Outputs       | ESCC 9203/060        | FP      | • STMicroelectronics |         |

## 08 MICROCIRCUITS | 80 LOGIC FAMILIES

| EPPL Part | Part Type | Description   | Detail Specification | Package | Manufacturer(s)      | Remarks |
|-----------|-----------|---|----------------------|---------|----------------------|---------|
| 1         | 54HC4040  | Asynchronous Negative Edge-triggered 12-Bit Binary Counters | ESCC 9204/069        | FP      | • STMicroelectronics |         |
| 1         | 54HC4049  | Hex Buffer Converter with Inverted Outputs                  | ESCC 9401/037        | FP      | • STMicroelectronics |         |
| 1         | 54HC4050  | Hex Buffer Converter  | ESCC 9401/038        | FP      | • STMicroelectronics |         |
| 1         | 54HC540   | Octal Bus Buffer with Inverted 3-State Outputs              | ESCC 9401/049        | FP      | • STMicroelectronics |         |
| 1         | 54HC541   | Octal bus buffer with 3-state output                        | ESCC 9401/047        | FP      | • STMicroelectronics |         |
| 1         | 54HC573   | Octal D-type transparent latch with 3-state output          | ESCC 9202/072        | FP      | • STMicroelectronics |         |
| 1         | 54HC574   | Octal D-type edge-triggered flip-flop with 3-state output   | ESCC 9203/054        | FP      | • STMicroelectronics |         |
| 1         | 54HC590   | 8-Bit Binary Counter with 3-State Output Registers          | ESCC 9204/071        | FP      | • STMicroelectronics |         |
| 1         | 54HC595   | 8-Bit Shift Registers with 3-State Output Registers         | ESCC 9306/051        | FP      | • STMicroelectronics |         |
| 1         | 54HC597   | 8-Bit PISO Shift Register                                   | ESCC 9306/054        | FP      | • STMicroelectronics |         |
| 1         | 54HC688   | 8-bit identify comparator                                   | ESCC 9209/005        | FP      | • STMicroelectronics |         |
| 1         | 54HC74    | Dual Negative Edge Triggered D-Type Flip-Flop with Clear    | ESCC 9203/050        | FP      | • STMicroelectronics |         |
| 1         | 54HC85    | 4-Bit Magnitude Comparator                                  | ESCC 9209/004        | FP      | • STMicroelectronics |         |
| 1         | 54HC86    | Quad 2-Input Exclusive OR Gate                              | ESCC 9201/119        | FP      | • STMicroelectronics |         |
| 1         | 54HCT240  | Octal Bus Buffer with Inverted 3-State Outputs              | ESCC 9401/045        | FP      | • STMicroelectronics |         |
| 1         | 54HCT244  | Octal Bus Buffer with 3-State Outputs                       | ESCC 9402/009        | FP      | • STMicroelectronics |         |
| 1         | 54HCT245  | Octal Bus Transceiver with 3-State Outputs                  | ESCC 9405/014        | FP      | • STMicroelectronics |         |
| 1         | 54HCT373  | Octal D-Type Transparent Latch with 3-State Outputs         | ESCC 9203/064        | FP      | • STMicroelectronics |         |
| 1         | 54HCT374  | Octal D-Type Edge-triggered Flip-Flop with 3-State Outputs  | ESCC 9203/066        | FP      | • STMicroelectronics |         |

## 08 MICROCIRCUITS | 80 LOGIC FAMILIES

| EPPL Part | Part Type         | Description   | Detail Specification | Package | Manufacturer(s)      | Remarks |
|-----------|-------------------|---|----------------------|---------|----------------------|---------|
| 1         | 54HCT74           | Dual D-Type Flip-Flop with Preset and Clear   | ESCC 9203/070        | FP      | • STMicroelectronics |         |
| 1         | 54VCXH16224<br>4  | Low Voltage CMOS 16-bit Bus Buffer with Bus hold, series Output Resistors and three-state Outputs<br>Operating temperature range: -55 / +125 °C   | SMD/5962-05210       | FP-48   | • STMicroelectronics |         |
| 1         | 54VCXH16237<br>3  | Low Voltage CMOS 16-bit D-type Latch with Bus hold, series Output Resistors and three-state Outputs<br>Operating temperature range: -55 / +125 °C   | SMD/5962-05211       | FP-48   | • STMicroelectronics |         |
| 1         | 54VCXH16237<br>4  | Low Voltage CMOS 16-bit D-type Flip-Flop with Bus hold, series Output Resistors and three-state Outputs   | SMD/5962-05212       | FP-48   | • STMicroelectronics |         |
| 1         | 54VCXHR1622<br>45 | Rad-Hard low voltage CMOS, 16-bit bus transceiver with bus hold, Series Output Resistors, and Three-State Outputs<br>Supply voltage range from +1.8 V dc to +3.6 V dc<br>Operating temperature range: -55 / +125 °C | SMD 5962/05213       | FP-48   | • STMicroelectronics |         |

08 MICROCIRCUITS | 90 OTHER FUNCTIONS

| EPPL Part | Part Type | Description   | Detail Specification | Package  | Manufacturer(s)                     | Remarks |
|-----------|-----------|---|----------------------|----------|-------------------------------------|---------|
| 2         | PE33362   | Silicon on Sapphire, 3.5 GHz Integer-N Phase Locked Loop (PLL) Frequency Synthesizer, 10/11 Dual Mode Prescaler, Programmable Counters, Phase Detector and Control Logic, Hermetically Sealed<br><br>Operating Temperature Range: -55 to +85 °C | 14-0054              | CQFPJ-44 | • Peregrine<br>Semiconductor Europe |         |
| 2         | PE33382   | Silicon on Sapphire, 3.5 GHz Integer-N Phase Locked Loop (PLL) Frequency Synthesizer, 10/11 Dual Mode Prescaler, Programmable Counters, Phase Detector and Control Logic, Hermetically Sealed<br><br>Operating Temperature Range: -55 to +85 °C | 14-0055              | CQFPJ-44 | • Peregrine<br>Semiconductor Europe |         |

08 MICROCIRCUITS | 95 MICROWAVE MONOLITIC INTEGRATED CIRCUITS (MMIC)

| EPPL Part | Part Type | Description   | Detail Specification | Package | Manufacturer(s) | Remarks   |
|-----------|-----------|---|----------------------|---------|-----------------|---|
| 2         | BES       | 1µm Schottky diode process  | ESCC 9010            | N/A     | • UMS           | It is the responsibility of the users to check that the process design can withstand the radiation requirements for its application   |
| 2         | D01PH     | 0.13 µm 100 GHz ft 12V VBGD Pseudomorphic Power MMIC Process  | Standard D01PH       | DIE     | • OMMIC         | D01PH Process is sensitive to Hydrogen poisoning. A Hydrogen getter is mandatory in case of hermetic encapsulation. No radiation tests were performed on this process. Therefore it is the responsibility of the users to check that its design can withstand the radiation requirements for its application (especially for SEE) |
| 2         | ED02AH    | 0.18 µm Mixed Analog/Digital 60 GHz Ft Pseudomorphic Low Noise MMIC Process   | Standard ED02AH      | DIE     | • OMMIC         | ED02AH Process is sensitive to Hydrogen poisoning. A Hydrogen getter is mandatory in case of hermetic encapsulation.  |
| 2         | HB20M     | Mixed digital/analog MMIC HBT process<br>InGaP HBT (2 µm emitter width)<br>Application in mixed digital/analog circuits up to Ku band | ESCC 9010            | N/A     | • UMS           | Single Events Effects have to be considered due to the digital elements   |
| 2         | HB20P     | HBT GaInP/GaAs Foundry Process, 0.7 µm GateApplications in Power Amplifiers up to Ku Band   | ESCC 9010            | N/A     | • UMS           |   |

08 MICROCIRCUITS | 95 MICROWAVE MONOLITIC INTEGRATED CIRCUITS (MMIC)

| EPPL Part | Part Type | Description  | Detail Specification | Package | Manufacturer(s) | Remarks  |
|-----------|-----------|--|----------------------|---------|-----------------|--|
| 2         | HB20PX    | HBT InGaP (2 $\mu$ m emitter width)<br>Applications in Power Amplifiers up to Ku Band  | ESCC 9010            | N/A     | • UMS           | It is the responsibility of the users to check that the process design can withstand the radiation requirements for its application. Max ratings should be in conformance with the application   |
| 2         | HB20S     | Power HBT process<br>Application in Power Transistors for L to C band Amplifiers   | ESCC 9010            | N/A     | • UMS           | No radiation tests was performed on this process. Therefore it is the responsibility of the users to check that its design can withstand the radiation requirements for its application.   |
| 2         | HP07      | MMIC, GaAs Foundry Process, MESFET 0.7 $\mu$ m for power applications up to Ku Band  | ESCC 9010            | N/A     | • UMS           |  |
| 2         | PH15      | MMIC GaAs Foundry Process, 0.15 $\mu$ m Pseudomorphic High Electron Mobility Transistor (P-HEMT) for low noise, low level applications up to W Band  | NONE                 | N/A     | • UMS           | Passive elements are similar to PH25 Process. No radiation tests were performed on this process. Therefore it is the responsibility of the users to check that its design can withstand the radiation requirements for its application (especially for SEE). |
| 2         | PH25      | MMIC GaAs Foundry Process, 0.25 $\mu$ m Pseudomorphic High Electron Mobility Transistor (P-HEMT) for low noise, low level applications up to 100 GHz | ESCC 9010            | N/A     | • UMS           |  |

08 MICROCIRCUITS | 95 MICROWAVE MONOLITIC INTEGRATED CIRCUITS (MMIC)

| EPPL Part | Part Type | Description  | Detail Specification | Package | Manufacturer(s) | Remarks  |
|-----------|-----------|--|----------------------|---------|-----------------|--|
| 2         | PPH25X    | 0.25 $\mu$ m Power P-HEMT process<br>Application in Power Amplifiers C to K band | ESCC 9010            | N/A     | • UMS           | No radiation tests was performed on this process. Therefore it is the responsibility of the users to check that its design can withstand the radiation requirements for its application. Max ratings should be in conformance with the application |



08 MICROCIRCUITS | 99 MISCELLANEOUS

| EPPL Part | Part Type    | Description   | Detail Specification | Package                           | Manufacturer(s) | Remarks                             |
|-----------|--------------|---|----------------------|-----------------------------------|-----------------|-------------------------------------|
| 1         | AT7906E      | SMCS Lite<br>(belonging to standard ASIC library MG1RT)<br>ASIC Matrix : MG1090E<br>Operating temperature range : -55 / +125 °C | SMD/5962-02A02       | CQFP100                           | • ATMEL         |                                     |
| 1         | AT7911E      | Triple SpaceWire links high speed controller  | SMD/5962-08A01       | MQFP196                           | • ATMEL         |                                     |
| 1         | SMFR-29C516E | 16 bit flow through EDAC  | SMD/5962-01A18       | QUAD<br>FLAT-<br>PACK 100<br>pins | • ATMEL         | Last Time Buy:<br>March 31st , 2011 |

## 09 RELAYS | 01 NON LATCHING

| EPPL Part | Part Type | Description  | Detail Specification                         | Package                    | Manufacturer(s)                 | Remarks |
|-----------|-----------|--|--|----------------------------|---------------------------------|---------|
| 2         | 317       | Contact Rating: 15A at 28 Vdc<br>Coil Voltage: 6, 12 and 28Vdc<br>Mounting Variants 01 to 06<br>Size (max mm.): 26 x 26 x 14.<br>Operating Temperature Range (°C): -65 to +125                 | Contact Configuration: 2PDT<br>ESCC 3601/007 | 1/2 CAN                    | • STPI                          |         |
| 1         | E         | Contact Rating: 1A at 28 Vdc<br>Coil Voltage: 6, 12 and 26.5Vdc<br>Mounting Variants 01 and 11<br>Size (max mm.): 13.00 x 10.40 x 6.10.<br>Operating Temperature Range (°C): -65 to +125       | Contact Configuration: 2PDT<br>ESCC 3601/012 | 1/6<br>Crystal<br>CAN      | • LEACH INTERNATIONAL<br>Europe |         |
| 2         | E215      | Contact Rating: 15 A at 28 Vdc<br>Coil Voltage: 6, 12 and 28 Vdc<br>Mounting Variants 03,04 and 06<br>Size (max mm.): 13.00 x 25.70 x 25.80.<br>Operating Temperature Range (°C): -65 to +125  | Contact Configuration: 2PDT<br>ESCC 3601/007 | Half-<br>cubic<br>inch can | • REL STPI                      |         |
| 1         | GP5       | Contact Rating: 2A at 28 Vdc<br>Coil Voltage: 6, 12 and 26.5 Vdc<br>Mounting Variants 02, 03 and 06<br>Size (max mm.): 20.57 x 10.41 x 10.41.<br>Operating Temperature Range (°C): -65 to +125 | Contact Configuration: 2PDT<br>ESCC 3601/003 | Half<br>crystal<br>can     | • LEACH INTERNATIONAL<br>Europe |         |
| 1         | T         | Contact Rating: 1A at 28 Vdc<br>Coil Voltage: 6.0, 12 V<br>Size (max mm):DIA 9.40 x 7.00<br>Operating Temperature Range (°C.): -65 to +125   | Contact Configuration: 2PDT<br>ESCC 3601/002 | TO-5                       | • REL STPI                      |         |

## 09 RELAYS | 02 LATCHING

| EPPL Part | Part Type | Description   | Detail Specification                         | Package                | Manufacturer(s)                 | Remarks |
|-----------|-----------|---|--|------------------------|---------------------------------|---------|
| 1         | 317B      | Contact Rating: 15A at 28 Vdc<br>Coil Voltage: 6, 12 and 28Vdc<br>Mounting Variants 03, 04, 06, 14 and 16<br>Size (max mm.): 26 x 26 x 13.34<br>Operating Temperature Range (°C): -65 to +125                           | Contact Configuration: 2PDT<br>ESCC 3602/009 | 1/2 CAN                | • STPI                          |         |
| 1         | 327B      | Contact Rating: 15A at 28 Vdc<br>Coil Voltage: 6, 12 and 28Vdc<br>Mounting Variants 04, 06, 09, 14, 16 and 19<br>Size (max mm.): 26 x 26 x 26<br>Operating Temperature Range (°C): -65 to +125                          | Contact Configuration: 4PDT<br>ESCC 3602/004 | CAN                    | • STPI                          |         |
| 1         | D         | Contact Rating: 1A at 28 Vdc<br>Coil Voltage: 6, 12 and 26.5 Vdc<br>Mounting Variants 01 and 11<br>Size (max mm.): 13.00 x 10.40 x 6.10.<br>Operating Temperature Range (°C): -65 to +125                               | Contact Configuration: 2PDT<br>ESCC 3602/019 | 1/6<br>Crystal<br>CAN  | • LEACH INTERNATIONAL<br>Europe |         |
| 1         | GP2       | Contact Rating: 2A at 28 Vdc<br>Coil Voltage: 6, 12 and 26.5 Vdc<br>Mounting Variants 02, 03 and 06<br>Size (max mm.): 20.57 x 10.41 x 11.00.<br>Operating Temperature Range (°C): -65 to +125                          | Contact Configuration: 2PDT<br>ESCC 3602/003 | Half<br>crystal<br>can | • LEACH INTERNATIONAL<br>Europe |         |
| 1         | GP250     | Contact Rating: 2A at 50 Vdc (4A pp. at 56 Vrms, 20 kHz)<br>Coil Voltage: 12 and 26.5 Vdc<br>Mounting Variants 02, 03 and 06<br>Size (max mm.): 20.57 x 10.41 x 11.00.<br>Operating Temperature Range (°C): -65 to +125 | Contact Configuration: 2PDT<br>ESCC 3602/010 | Half<br>crystal<br>can | • LEACH INTERNATIONAL<br>Europe |         |
| 2         | PHL50     | Contact Rating: 50A at 50 Vdc<br>Coil Voltage : 48, 28, 12 Vdc<br>Size (max mm): 47.8 x 34.6 x 26.2<br>Operating Temperature Range (°C): -65 to +125  | Contact Configuration: 1PDT<br>ESCC 3602/014 | AS PER<br>SPEC.        | • REL STPI                      |         |
| 1         | TL        | Contact Rating: 1A at 28 Vdc<br>Coil Voltage: 6.0, 12 V<br>Size (max mm): DIA 9.40 x 7.00<br>Operating Temperature Range (°C.): -65 to +125   | Contact Configuration: 2PDT<br>ESCC 3602/002 | TO-5                   | • REL STPI                      |         |

# 10 RESISTORS | 07 SHUNT

| EPPL Part | Part Type   | Description                                 | Detail Specification | Package       | Manufacturer(s)                           | Remarks |
|-----------|-------------|---|----------------------|---------------|---|---------|
| 1         | SMP/SMS/SMT | SMD tape and reel shunt resistors           | ESCC 4001/027        | TAPE AND REEL | • ISABELLENHUETTE<br>HEUSLER GmbH & Co.KG |         |
|           |             | Variant                                     | Res. range (mohm)    | Tolerance (%) | Temp. coefficient (ppm/°C)                |         |
|           |             | 01  | 5 - 1000             | 0.5 - 1.0     | 50  |         |
|           |             | 02  | 3 - 1000             | 0.5 - 1.0     | 50  |         |
|           |             | 03  | 4 - 2000             | 0.5 - 1.0     | 50  |         |
|           |             | Dimensions max. (mm): 7.3 x 4.3 x 1.0       |                      |               |   |         |
|           |             | Operating temperature range: -55 to +170 °C |                      |               |   |         |

10 RESISTORS | 08 METAL FILM

| EPPL Part | Part Type | Description   | Detail Specification   | Package          | Manufacturer(s) | Remarks  |
|-----------|-----------|---|--|------------------|-----------------|--|
| 2         | MG680     | High Voltage<br>Range (Ohm): 600 - 20M<br>TC (10E-6/±C): 140<br>Max. Voltage (V): 2000<br>Operating temperature range (°C): -55 to +125                                     | Tol. ( ±%) : 0.5<br>Power Rating (W): 0.800<br>Size (max mm): DIA 1.80 x 4.30  | GSFC S-311-P-683 | Axial           | • CADDOCK ELECTRONICS                              |
| 2         | MG710     | High Voltage<br>Range (Ohm): 800 - 50M<br>TC (10E-6/°C): 140<br>Max. Voltage (V): 4000<br>Operating temperature range (°C): -55 to +125                                     | Tol. ( ± %) : 0.5<br>Power Rating (W): 1<br>Size (max mm): DIA 1.80 x 4.30     | GSFC S-311-P-683 | Axial           | • CADDOCK ELECTRONICS                              |
| 2         | MG716     | High Voltage<br>Range (Ohm): 600 - 75M<br>TC (10E-6/°C): 140<br>Max. Voltage (V): 4000<br>Operating temperature range (°C): -55 to +125                                     | Tol. ( ± %) : 0.5<br>Power Rating (W): 1.5<br>Size (max mm): DIA 1.80 x 4.30   | GSFC S-311-P-683 | Axial           | • CADDOCK ELECTRONICS                              |
| 2         | MG721     | High Voltage<br>Range (Ohm): 200 - 100M<br>TC (10E-6/°C): 140<br>Max. Voltage (V): 4000<br>Operating temperature range (°C): -55 to +125                                    | Tol. ( ± %) : 0.5<br>Power Rating (W): 2<br>Size (max mm): DIA 1.80 x 4.30     | GSFC S-311-P-683 | Axial           | • CADDOCK ELECTRONICS                              |
| 1         | RNC90     | Film Non-Hermetically Sealed<br>Range (Ohm): 50 - 100K<br>TC (10E-6/°C): 5<br>Max. Voltage (V): 300<br>Operating temperature range (°C): -55 to +175                        | Tol. ( ± %) : 0.02, 1<br>Power Rating (W): 0.5<br>Size (max mm): 7.5 x 8 x 2.5 | ESCC 4001/011    | AXIAL           | • VISHAY S.A. div.<br>SFERNICE                     |
| 1         | TNPS      | Resistors, Fixed, Surface Mount, Thin Film, Non-Hermetic, Based on Type TNPS<br><br>E96 series, Style 0603, 0805 and 1206, 10 to 1.0 MOhm, 0.1 % tolerance, 15 ppm/°C<br>TC |  | ESCC 4001/029    | Chip            | • VISHAY ELECTRONIC<br>GmbH - DIVISION<br>DRALORIC |

10 RESISTORS | 09 CHIP (ALL)

| EPPL Part | Part Type       | Description   | Detail Specification | Package | Manufacturer(s)                | Remarks                     |
|-----------|-----------------|---|----------------------|---------|--------------------------------|-----------------------------|
| 2         | CHP             | Thick Film Chip Resistors with wraparound terminations<br>Temperature coefficient: 100, 200 ppm/°C<br>Tolerance: 1%, 2%, 5%   | ESCC 4001/026        | CHIP    | • VISHAY S.A. div.<br>SFERNICE |                             |
|           |                 | Res. range (ohm) Power (mW) Max. Rated Voltage (V)  |                      |         |                                |                             |
|           |                 | Size 0603: 1 to 1M 100 49   |                      |         |                                |                             |
|           |                 | Size 0805: 1 to 1M 200 49   |                      |         |                                |                             |
|           |                 | Size 1206: 1 to 1M 250 49   |                      |         |                                |                             |
|           |                 | Size 2010: 1 to 1M 500 49   |                      |         |                                |                             |
|           |                 | Size 2512: 1 to 1M 800 49   |                      |         |                                |                             |
| 1         | P HR            | Thin Film, 1206/0805/2010/0603 Series, High Precision and Stability<br>Case Size Resistance Range (ohm) Tolerance Power Rating (mW) Dimensions<br>(max. mm)   | ESCC 4001/023        | CHIP    | • VISHAY S.A. div.<br>SFERNICE |                             |
|           |                 | 0603(Var. 01-05) 250 to 200 k 0.01, 0.02 % 100 2.16 x 1.01 x 1.02   |                      |         |                                |                             |
|           |                 | 0805(Var. 02-06) 250 to 250 k 0.01, 0.02 % 125 2.55 x 1.53 x 1.02   |                      |         |                                |                             |
|           |                 | 1206(Var. 03-07) 250 to 1 M 0.01, 0.02 % 250 3.64 x 1.86 x 1.02   |                      |         |                                |                             |
|           |                 | TC (10E-6/°C) : 10<br>Operating Temperature Range -55 to +125 °C  |                      |         |                                |                             |
| 1         | PFRR            | Thin Film, 0603/0805/1206/2010 Series, High Precision and Stability with Establish Reliability Level R<br>Case Size Resistance Range (ohm); Tolerance (%); Power Rating (mW); Dimen.(max. mm)   | ESCC 4001/023        | CHIP    | • VISHAY S.A. div.<br>SFERNICE | Modification in Description |
|           |                 | 0603(Var. 09): 100 to 261K; 0.05, 0.1; 100; 2.16 x 1.01 x 1.02  |                      |         |                                |                             |
|           |                 | 0805(Var. 10): 100 to 301K; 0.05, 0.1; 125; 2.55 x 1.53 x 1.02  |                      |         |                                |                             |
|           |                 | 1206(Var. 11): 100 to 1M; 0.05, 0.1; 250; 3.64 x 1.86 x 1.02  |                      |         |                                |                             |
|           |                 | 2010(Var. 12): 100 to 3M01; 0.05, 0.1; 500; 5.72 x 2.8 x 1.02   |                      |         |                                |                             |
|           |                 | TC (10E-6/°C) : 10<br>Operating Temperature Range -55 to +125°C   |                      |         |                                |                             |
| 1         | PRA HR & CNW HR | Surface mounting, high precision thin film array<br>2 to 8 resistors by Array. PRA HR (same ohmic value) CNW HR (diff. ohmic value)<br>Range (Ohm): 100 - 1.0M; Tol. (± %): 0.05, 1<br>Power Rating (mW): 100/resistor; Temp. Coeff. (±10E-6/°C): 10<br>Terminations : Nickel, hot-solder dip finish<br>Variant(Type); Limit. Elem. Voltage (V); Size for Array with 8 resistors (max mm) | ESCC 4001/025        | SMD     | • VISHAY S.A. div.<br>SFERNICE |                             |
|           |                 | 01 to 07 & 22 to 28 (PRA100); 35 ; 1.8 x 8.4 x 0.58   |                      |         |                                |                             |
|           |                 | 08 to 14 & 29 to 35 (PRA135); 75 ; 2.05 x 11.2 x 0.58   |                      |         |                                |                             |
|           |                 | 15 to 21 & 36 to 42 (PRA135); 3.2 ; 14.96 x 0.58  |                      |         |                                |                             |
|           |                 | Operating Temperature Range (°C) : -55 to +155  |                      |         |                                |                             |

10 RESISTORS | 09 CHIP (ALL)

| EPPL Part | Part Type | Description   | Detail Specification                | Package | Manufacturer(s)                           | Remarks |
|-----------|-----------|---|-------------------------------------|---------|---|---------|
| 1         | RM2010    | Film<br>Range (Ohm): 5.6 - 15M Tol. (± %): 1, 2<br>Power Rating (mW): 800 Voltage Rating (V): 150<br>Temp. Coeff. (±10E-6/°C) : 100(K), 300(M)<br>Size (max mm) : 5.60 x 2.65 x 0.85<br>Operating temperature range (°C) : -55 to +70 (+150 at 0 watt)  | MIL-PRF-55342/8                     | CHIP    | • STATE OF THE ART                        |         |
| 1         | SMV/SMR   | SMD metal foil chip resistors<br><br>Variant Res. range (ohm) Tolerance (%) Temp. coefficient (ppm/°C)<br>01 (SMR-PW) 0.010 - 4.7 0.5 see Para. 1.4.2 of detail spec.<br>02 (SMV-PW) 0.0022 - 1.0 0.5 see Para. 1.4.2 of detail spec.<br><br>Dimensions max. (mm):<br>Variant 01 (2 terminals): 12.3 x 6.6 x 3.6<br>Variant 02 (4 terminals): 12.3 x 6.6 x 3.6<br>Operating temperature range: -55 to +140 °C | ESCC 4001/028                       | SMD     | • ISABELLENHUETTE<br>HEUSLER GmbH & Co.KG |         |
| 2         | VCS1625   | Z-foil Wraparound Chip Resistors<br>Temperature coefficient: 2 ppm/°C typical<br>resistance range: 0.01 to 2 ohm<br>Tolerance: 0.5%, 1%<br>Power rating: 1 W  | Data sheet 303119<br>+ EEE-INST-002 | CHIP    | • VISHAY ISRAEL                           | Update  |

## 10 RESISTORS | 11 HEATERS, FLEXIBLE

| EPPL Part | Part Type           | Description  | Detail Specification             | Package         | Manufacturer(s)      | Remarks |
|-----------|---------------------|--|----------------------------------|-----------------|----------------------|---------|
| 1         | Heater              | Resistor, Heater, Flexible, Single and double layer.<br>Maximum ohmic density: 200 ohm/cm2<br>Tolerances: ±2, 5 %<br>Resistance range: 1 to 5000 ohm<br>Heating area: 1.6 to 1300 cm2<br>Maximum heating side dimension: 60 cm<br>Terminal lead: 20, 22, 24, 26, 28, 30 AWG<br>Temperature range (10-6°C.): 175<br>Operating Temperature Range (°C.): -65 to +200. | ESCC 4009/002                    | AS PER<br>SPEC. | • IRCA-DIVISION RICA |         |
| 2         | HEATERS<br>FLEXIBLE | Single sided flexible heated, polyimide coated<br>Operating temperature range: -200 to +200 °C   | MINCO P.Q.02 Rev.<br>01 18/09/01 | N/A             | • MINCO - SA         |         |



# 11 THERMISTORS | 02 TEMPERATURE MEASURING

| EPPL Part | Part Type       | Description  | Detail Specification | Package         | Manufacturer(s)                                       | Remarks                            |
|-----------|-----------------|--|----------------------|-----------------|---|------------------------------------|
| 1         | 4006013***      | NTC, range 1000 to 100000 ohms @ +25 °C<br>temperature range -55 / +115 °C<br>nominal values and tolerances at +25 °C :<br>Var. 01 : 1000 ohm 0.88 %<br>Var. 02 : 2000 ohm 0.88 %<br>Var. 03 : 3000 ohm 0.88 %<br>Var. 04 : 4000 ohm 0.88 %<br>Var. 05 : 5000 ohm 0.88 %<br>Var. 07 : 100000 ohm 0.93 %              | ESCC 4006/013        | AS PER<br>SPEC. | • MEAS Ireland<br>(Betatherm) Ltd.                    | New Variant 07<br>included         |
| 1         | 4006014***      | NTC, range 2000 to 100000 ohms @ +25 °C<br>temperature range -40 / +160 °C<br>nominal values and tolerances at +25 °C :<br>Var. 08 : G15K4D489 15000 ohm 1.01 %<br>Var. 09 : G10K4D453 10000 ohm 2.00 %<br>Var. 12 : G100K6D487 100000 ohm 1.75 %<br>Var. 13 : G15K4D589 15000 ohm 1.01 %                            | ESCC 4006/014        | AS PER<br>SPEC. | • MEAS Ireland<br>(Betatherm) Ltd.                    | New Variants 12 and<br>13 included |
| 2         | 44900<br>Series | Leaded, Epoxy Encapsulated, Negative Temperature Coefficient<br>Pd (mW): 1            Tolerance (± %): 0.4 to 10<br>Range (Ohm @ 25°C): 2.2k, 3k, 5k, 10k, 30k<br>Package (max mm): S Variant DIA 2.40, T Variant DIA 2.80<br>Various Wires Definitions (Type & AWG)<br>Operating Temperature Range (°C): -55 to +90 | GSFC S-311-P-18      | AS PER<br>SPEC. | • MEASUREMENT<br>SPECIALTIES Ltd (YSI<br>TEMPERATURE) |                                    |

## 11 THERMISTORS | 03 TEMPERATURE SENSOR

| EPPL Part | Part Type | Description   | Detail Specification | Package         | Manufacturer(s)                       | Remarks       |
|-----------|-----------|---|----------------------|-----------------|---------------------------------------|---------------|
| 1         | N1043/301 | Platinum probe sheath type thermal sensor<br>Nominal resistance: 1000±2ohm (at 0°C)<br>Source current: 5mA Max.<br>Operating temperature range: -260 to +135°C  | JAXA-QTS-2180/103    | Probe<br>Sheath | • Mitsubishi Heavy<br>Industries, Ltd | New component |
| 1         | N1043/501 | Platinum surface type thermal sensor<br>Type; Operating Temp. Range; Nominal resistance<br>N1043/501-90-300; -260 to +400°C; 2000±4ohm (at 0°C)<br>N1043/501-91-600; -196 to +400°C; 500±1ohm (at 0°C)<br>Source current: 5mA Max.<br>Operating temperature range: -260 to +135°C | JAXA-QTS-2180/105    | SMD             | • Mitsubishi Heavy<br>Industries, Ltd | New component |

11 THERMISTORS | 99 MISCELLANEOUS

| EPPL Part | Part Type | Description  | Detail Specification | Package | Manufacturer(s)                    | Remarks       |
|-----------|-----------|--|----------------------|---------|------------------------------------|---------------|
| 1         | N1043/401 | Platinum Extension Wire Sheath Type thermal sensor<br>Type; Length; Measured Temp Range; Operating Temp Range; Nominal Resistance (@0°C)<br>N1043/401-70-902-1; 43±1mm±; -18 to +930°C; -60 to +980°C; 100±0.5ohm<br>N1043/401-70-902-2; 84±1mm; -18 to +930°C; -60 to +980°C; 100±0.5ohm<br>N1043/401-70-902-3; 66±1mm; -18 to +930°C; -60 to +980°C; 100±0.5ohm<br>N1043/401-71-702-1; 84±1mm; -80 to +430°C; -120 to +430°C; 500±2.5ohm<br>Source current: 5mA Max. | JAXA-QTS-2180/104    | N/A     | • Mitsubishi Heavy Industries, Ltd | New component |

12 TRANSISTORS | 01 LOW POWER, NPN (< 2WATTS)

| EPPL Part | Part Type         | Description   | Detail Specification | Package | Manufacturer(s)      | Remarks                      |
|-----------|-------------------|---|----------------------|---------|----------------------|------------------------------|
| 1         | 2N2219A           | hFE min/max: 100/300 @ IC = 150 mA PD (mW): 800<br>BV CBO (V): 75 BV CEO (V): 40 IC (mA): 800<br>Operating Temperature Range (°C.): -65 to +200   | ESCC 5201/003        | T039    | • STMicroelectronics |                              |
| 1         | 2N2222A           | hFE min/max: 100/300 @ IC = 150 mA PD (mW): 500<br>BV CBO (V): 75 BV CEO (V): 40 IC (mA): 800 @10 us pulse<br>Operating Temperature Range (°C.): -65 to +200  | ESCC 5201/002        | LCCC3   | • STMicroelectronics |                              |
| 1         | 2N2484            | hFE min/max: 250/650 @ IC = 1 mA PD (mW): 360<br>BV CBO (V): 60 BV CEO (V): 60 IC (mA): 50<br>Operating Temperature Range (°C.): -65 to +200  | ESCC 5201/001        | LCCC3   | • STMicroelectronics |                              |
| 1         | 2N3019            | hFE min/max: 100/300 @ IC = 150 mA PD (mW): 800<br>BV CBO (V): 140 BV CEO (V): 80 IC (A): 1<br>Operating Temperature Range (°C.): -55 to +175   | ESCC 5201/011        | T039    | • STMicroelectronics |                              |
| 1         | 2N3501L           | hFE min/max: 100/300 @ IC = 150 mA PD (W): 1<br>BV CBO (V): 150 BV CEO (V): 150 IC (A): 0.3<br>Operating Temperature Range (°C.): -65 to +200   | MIL-PRF-19500/366    | T0205   | • MICROSEMI LAWRENCE | Manufacturer Standardization |
| 1         | 2N3700            | hFE min/max: 100/300 @ IC = 150 mA PD (mW): 500<br>BV CBO (V): 140 BV CEO (V): 80 IC (A): 1<br>Operating Temperature Range (°C.): -65 to +200   | ESCC 5201/004        | LCCC3   | • STMicroelectronics |                              |
| 1         | 2N5551            | hFE min/max: 80/250 @ IC = 10 mA PD (mW): 360<br>BV CBO (V): 180 BV CEO (V): 160 IC (mA): 500<br>Operating Temperature Range (C.): -65 to +200  | ESCC 5201/019        | LCCC3   | • STMicroelectronics |                              |
| 1         | 2N5666,<br>2N5667 | hFE min/max: 40/120 @ IC = 1 A (2N5666) PD (W): 1.2<br>hFE min/max: 25/75 @ IC = 1 A (2N5667) PD (W): 1.2<br>BV CBO (V): 250 BV CEO (V): 200 IC (A): 5 (2N5666)<br>BV CBO (V): 400 BV CEO (v): 300 IC (A): 5 (2N5667)<br>Operating Temperature Range (°C.): -65 to +200 | MIL-PRF-19500/455    | T0205   | • MICROSEMI LAWRENCE | Manufacturer Standardization |

12 TRANSISTORS | 02 LOW POWER, PNP (< 2WATTS)

| EPPL Part | Part Type           | Description  | Detail Specification | Package | Manufacturer(s)      | Remarks                      |
|-----------|---------------------|--|----------------------|---------|----------------------|------------------------------|
| 1         | 2N2905A             | hFE min/max: 100/300 @ IC = -150 mA PD (mW): 600<br>BV CBO (V): -60 BV CEO (V): -60 IC (mA): -600<br>Operating Temperature Range (°C.): -65 to +200  | ESCC 5202/002        | T039    | • STMicroelectronics |                              |
| 1         | 2N2907A             | hFE min/max: 100/300 @ IC = -150 mA PD (mW): 400<br>BV CBO (V): -60 BV CEO (V): -60 IC (mA): -600 (-500 for LCC3)<br>Operating Temperature Range (°C.): -65 to +200  | ESCC 5202/001        | LCCC3   | • STMicroelectronics |                              |
| 1         | 2N3637              | hFE min/max: 100/300 @ IC = -50 mA pulsed PD (W): 1<br>BV CBO (V): -175 BV CEO (V): -175 IC (A): -1<br>Operating Temperature Range (°C.): -65 to +200  | MIL-PRF-19500/357    | TO-205  | • MICROSEMI LAWRENCE | Manufacturer Standardization |
| 1         | 2N3867S,<br>2N3868S | hFE min/max: 40/120 @ IC = -1.5 A (2N3867S) PD (W): 1<br>hFE min/max: 30/150 @ IC = -1.5 A (2N3868S) PD (W): 1<br>BV CBO (V): -40 BV CEO (V): -40 IC (A): -3 (2N3867S)<br>BV CBO (V): -60 BV CEO (V): -60 IC (A): -3 (2N3868S)<br>Operating Temperature Range (°C.): -65 to +200 | MIL-PRF-19500/350    | TO205   | • MICROSEMI LAWRENCE | Manufacturer Standardization |
| 1         | 2N5401              | hFE min/max: 60/240 @ IC = -10 mA PD (mW): 360<br>BV CBO (V): -160 BV CEO (V): -150 IC (mA): -500<br>Operating Temperature Range (C.): -65 to +200   | ESCC 5202/014        | LCCC3   | • STMicroelectronics |                              |
| 1         | 2N5415              | hfe = 30/120 @ Ic=50mA Pdmax. = 0,75 W @Tamb. = +25°C.<br>BV CBO = 200 V BV CEO = 200 V Ic = 1 A<br>Operating Temperature Range (°C.): -65 to +200   | MIL-PRF-19500/485    | TO39    | • MICROSEMI LAWRENCE | Manufacturer Standardization |

12 TRANSISTORS | 03 HIGH POWER, NPN (> 2WATTS)

| EPPL Part | Part Type | Description  | Detail Specification                                 | Package       | Manufacturer(s) | Remarks              |
|-----------|-----------|--|--|---------------|-----------------|----------------------|
| 1         | 2N5154    | hFE min/max: 70/200 @ IC = 2.5 mA<br>BV CBO (V): 100      BV CEO (V): 80<br>Operating Temperature Range (°C.): -65 to +200 | PD (W): 8.75<br>IC (A): 5                            | ESCC 5203/010 | SMD .5          | • STMicroelectronics |
| 1         | BUX77     | hFE min/max: 50/200 @ IC = 2 A<br>BV CBO (V): 100      BV CEO (V): 80<br>Operating Temperature Range (°C.): -65 to +200    | PD (W): 40 (Var. 01-05), 35 (Var.06-07)<br>IC (A): 5 | ESCC 5203/016 | T0257           | • STMicroelectronics |

12 TRANSISTORS | 04 HIGH POWER, PNP (> 2WATTS)

| EPPL Part | Part Type | Description   | Detail Specification | Package | Manufacturer(s)      | Remarks |
|-----------|-----------|---|----------------------|---------|----------------------|---------|
| 1         | 2N5153    | hFE min/max: 70/200 @ IC = -2.5 mA      PD (W): 10<br>BV CBO (V): -100      BV CEO (V): -80      IC (A): -2<br>Operating Temperature Range (°C.): -65 to +200                           | ESCC 5204/002        | SMD .5  | • STMicroelectronics |         |
| 1         | BUX78     | hFE min/max: 50/200 @ IC = -2 A      PD (W): 40 (Var. 01-05), 35 (Var.06-07)<br>BV CBO (V): -100      BV CEO (V): -80      IC (A): -5<br>Operating Temperature Range (°C.): -65 to +200 | ESCC 5204/006        | T0257   | • STMicroelectronics |         |

12 TRANSISTORS | 05 FET N CHANNEL

| EPPL Part | Part Type         | Description  | Detail Specification | Package | Manufacturer(s)                                   | Remarks                      |
|-----------|-------------------|--|----------------------|---------|---|------------------------------|
| 1         | JAXA R<br>2SK4048 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=100 V<br>ID=42 A, Rds(on)=18 mohm @ VGS=12 V<br>Rth(ch-c)=0.5 °C/W<br>Tch=150 °C  | JAXA-QTS-2030/101    | TO-254  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4049 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=200 V<br>ID=14 A, Rds(on)=155 mohm @ VGS=12 V<br>Rth(ch-c)=2.0 °C/W<br>Tch=150 °C | JAXA-QTS-2030/101    | TO-254  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4050 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=100 V<br>ID=15 A, Rds(on)=69 mohm @ VGS=12 V<br>Rth(ch-c)=2.0 °C/W<br>Tch=150 °C  | JAXA-QTS-2030/101    | TO-254  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4051 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=200 V<br>ID=42 A, Rds(on)=33 mohm @ VGS=12 V<br>Rth(ch-c)=0.5 °C/W<br>Tch=150 °C  | JAXA-QTS-2030/101    | TO-254  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4052 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=200 V<br>ID=33 A, Rds(on)=69 mohm @ VGS=12 V<br>Rth(ch-c)=1.0 °C/W<br>Tch=150 °C  | JAXA-QTS-2030/101    | TO-254  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4053 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=200 V<br>ID=14 A, Rds(on)=155 mohm @ VGS=12 V<br>Rth(ch-c)=2.0 °C/W<br>Tch=150 °C | JAXA-QTS-2030/101    | TO-254  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4054 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=250 V<br>ID=42 A, Rds(on)=45 mohm @ VGS=12 V<br>Rth(ch-c)=0.5 °C/W<br>Tch=150 °C  | JAXA-QTS-2030/101    | TO-254  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4055 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=250 V<br>ID=27 A, Rds(on)=98 mohm @ VGS=12 V<br>Rth(ch-c)=1.0 °C/W<br>Tch=150 °C  | JAXA-QTS-2030/101    | TO-254  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |



## 12 TRANSISTORS | 05 FET N CHANNEL

| EPPL Part | Part Type         | Description   | Detail Specification | Package | Manufacturer(s)                                   | Remarks                      |
|-----------|-------------------|---|----------------------|---------|---|------------------------------|
| 1         | JAXA R<br>2SK4056 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=250 V<br>ID=12 A, Rds(on)=230 mohm @ VGS=12 V<br>Rth(ch-c)=2.0 °C/W<br>Tch=150 °C  | JAXA-QTS-2030/101    | TO-254  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4152 |   | JAXA-QTS-2030/102    | SMD2    | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4153 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=130 V<br>ID=39 A, Rds(on)=39 mohm @ VGS=12 V<br>Rth(ch-c)=0.83 °C/W<br>Tch=150 °C  | JAXA-QTS-2030/102    | SMD1    | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4154 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=130 V<br>ID=15 A, Rds(on)=89 mohm @ VGS=12 V<br>Rth(ch-c)=1.67 °C/W<br>Tch=150 °C  | JAXA-QTS-2030/102    | SMD0.5  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4155 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=200 V<br>ID=42 A, Rds(on)=16 mohm @ VGS=12 V<br>Rth(ch-c)=0.5 °C/W<br>Tch=150 °C   | JAXA-QTS-2030/102    | SMD2    | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4156 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=200 V<br>ID=32 A, Rds(on)=62 mohm @ VGS=12 V<br>Rth(ch-c)=8.83 °C/W<br>Tch=150 °C  | JAXA-QTS-2030/102    | SMD1    | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4157 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=200 V<br>ID=14 A, Rds(on)=148 mohm @ VGS=12 V<br>Rth(ch-c)=1.67 °C/W<br>Tch=150 °C | JAXA-QTS-2030/102    | SMD0.5  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4158 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=250 V<br>ID=42 A, Rds(on)=38 mohm @ VGS=12 V<br>Rth(ch-c)=0.5 °C/W<br>Tch=150 °C   | JAXA-QTS-2030/102    | SMD2    | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4159 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=250 V<br>ID=26 A, Rds(on)=91 mohm @ VGS=12 V<br>Rth(ch-c)=0.83 °C/W<br>Tch=150 °C  | JAXA-QTS-2030/102    | SMD1    | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |

12 TRANSISTORS | 05 FET N CHANNEL

| EPPL Part | Part Type         | Description   | Detail Specification | Package | Manufacturer(s)                                   | Remarks                      |
|-----------|-------------------|---|----------------------|---------|---|------------------------------|
| 1         | JAXA R<br>2SK4160 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=250 V<br>ID=12 A, Rds(on)=223 mohm @ VGS=12 V<br>Rth(ch-c)=1.67 °C/W<br>Tch=150 °C   | JAXA-QTS-2030/102    | SMD0.5  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4185 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=500 V<br>ID=10 A, Rds(on)=0.48 mohm @ VGS=12 V<br>Rth(ch-c)=1.0 °C/W<br>Tch=150 °C   | JAXA-QTS-2030/103    | TO-254  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4186 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=500 V<br>ID=10 A, Rds(on)=0.48 mohm @ VGS=12 V<br>Rth(ch-c)=1.0 °C/W<br>Tch=150 °C   | JAXA-QTS-2030/103    | TO-254  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4187 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=500 V<br>ID=4.5 A, Rds(on)=1.15 mohm @ VGS=12 V<br>Rth(ch-c)=2.0 °C/W<br>Tch=150 °C  | JAXA-QTS-2030/103    | TO-254  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4188 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=500 V<br>ID=23 A, Rds(on)=0.18 mohm @ VGS=12 V<br>Rth(ch-c)=0.5 °C/W<br>Tch=150 °C   | JAXA-QTS-2030/103    | SMD2    | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4189 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=500 V<br>ID=10 A, Rds(on)=0.48 mohm @ VGS=12 V<br>Rth(ch-c)=0.83 °C/W<br>Tch=150 °C  | JAXA-QTS-2030/103    | SMD1    | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4190 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=500 V<br>ID=4.5 A, Rds(on)=1.15 mohm @ VGS=12 V<br>Rth(ch-c)=1.67 °C/W<br>Tch=150 °C | JAXA-QTS-2030/103    | SMD0.5  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4214 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=130 V<br>ID=42 A, Rds(on)=24 mohm @ VGS=12 V<br>Rth(ch-c)=0.5 °C/W<br>Tch=150 °C     | JAXA-QTS-2030/101    | TO-254  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |
| 1         | JAXA R<br>2SK4215 | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=130 V<br>ID=35 A, Rds(on)=46 mohm @ VGS=12 V<br>Rth(ch-c)=1.0 °C/W<br>Tch=150 °C     | JAXA-QTS-2030/101    | TO-254  | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required |

12 TRANSISTORS | 05 FET N CHANNEL

| EPPL Part | Part Type             | Description  | Detail Specification | Package  | Manufacturer(s)                                   | Remarks                                    |
|-----------|-----------------------|--|----------------------|----------|---|--|
| 1         | JAXA R<br>2SK4216     | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=130 V<br>ID=15 A, Rds(on)=96 mohm @ VGS=12 V<br>Rth(ch-c)=2.0 °C/W<br>Tch=150 °C  | JAXA-QTS-2030/101    | TO-254   | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required               |
| 1         | JAXA R<br>2SK4217     | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=100 V<br>ID=42 A, Rds(on)=13 mohm @ VGS=12 V<br>Rth(ch-c)=0.5 °C/W<br>Tch=150 °C  |                      |          | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required               |
| 1         | JAXA R<br>2SK4218     | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=100 V<br>ID=42 A, Rds(on)=28 mohm @ VGS=12 V<br>Rth(ch-c)=0.83 °C/W<br>Tch=150 °C | JAXA-QTS-2030/102    | SMD1     | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required               |
| 1         | JAXA R<br>2SK4219     | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=100 V<br>ID=15 A, Rds(on)=64 mohm @ VGS=12 V<br>Rth(ch-c)=1.67 °C/W<br>Tch=150 °C | JAXA-QTS-2030/102    | SMD0.5   | • Fuji Electric<br>Device Technology<br>Co., Ltd. | Export documents<br>required               |
| 1         | STRH100N10F<br>SY3HRB | MOSFET, N-channel<br>VGS=+-20 V, V(BR)DS(min.)=100 V<br>IDS=48 A, Rds(on)=35 mohm @ VGS=12 V<br>Rth(j-s)=0.73 °C/W<br>Tj=150 °C  | ESCC 5205/021        | T0-254AA | • STMicroelectronics                              | TID tested<br>capability of<br>70kRADS(Si) |

## 12 TRANSISTORS | 06 FET P CHANNEL

| EPPL Part | Part Type | Description  | Detail Specification | Package         | Manufacturer(s)              | Remarks |
|-----------|-----------|--|----------------------|-----------------|------------------------------|---------|
| 1         | 2N7389    | VGS = ± 20V, Breakdown Voltage DS min. = -100 V, ID = -6.5 A<br>max. thermal resistance = 5 °C/W, max. rds = 0.3 ohms @ Vgs = 12 V<br>Operating Temperature Range (°C.): -55 to +150 | MIL-PRF-19500/630    | TO-205AF<br>LCC | • INTERNATIONAL<br>RECTIFIER |         |

## 12 TRANSISTORS | 08 MULTIPLE

| EPPL Part | Part Type        | Description  | Detail Specification  | Package       | Manufacturer(s) | Remarks              |
|-----------|------------------|--|---|---------------|-----------------|----------------------|
| 1         | 2N2920A<br>(NPN) | hFE min/max: 150/600 @ IC = 10 uA<br>BV CBO (V): 60<br>Operating Temperature Range (°C.): -65 to +200  | PD (mW): 500 (both section)<br>BV CEO (V): 60<br>IC (mA): 30  | ESCC 5207/002 | LCC6            | • STMicroelectronics |
| 1         | 2N3810<br>(PNP)  | hFE min/max: 150/450 @ IC = -1 mA<br>BV CBO (V): -60<br>Operating Temperature Range (°C.): -65 to +200 | PD (mW): 600 (both section)<br>BV CEO (V): -60<br>IC (mA): 50 | ESCC 5207/005 | LCC6            | • STMicroelectronics |

12 TRANSISTORS | 10 RF/MICROWAVE NPN LOW POWER / LOW NOISE

| EPPL Part | Part Type | Description   | Detail Specification  | Package       | Manufacturer(s) | Remarks                         |
|-----------|-----------|---|---|---------------|-----------------|---------------------------------|
| 1         | BFY180    | BV CBO (V): 15<br>hFE min/max: 30/175 @ IC max = 0.25 mA<br>Nf max: 3.2 dB @ 2 GHz<br>fT min: 7.0 GHz<br>Variant 01 of ESCC spec.<br>Operating Temperature Range (°C.): -65 to +200 | BV CEO (V): 8<br>Ic (mA): 4.0<br>Pout (mW): 30<br>MAG/MSG min: 12 dB @ 2 GHz    | ESCC 5611/006 | MICRO X         | • INFINEON<br>TECHNOLOGIES A.G. |
| 1         | BFY181    | BV CBO (V): 20<br>hFE min/max: 55/175 @ IC max = 5.0 mA<br>Nf max: 2,9 dB @ 2 GHz<br>fT min: 7.0 GHz<br>Variant 03 of ESCC spec.<br>Operating Temperature Range (°C.): -65 to +200  | BV CEO (V): 12<br>Ic (mA): 20<br>Pout (mW): 175<br>MAG/MSG min: 13.5 dB @ 2 GHz | ESCC 5611/006 | MICRO X         | • INFINEON<br>TECHNOLOGIES A.G. |
| 1         | BFY183    | BV CBO (V): 20<br>hFE min/max: 55/160 @ IC max = 5.0 mA<br>Nf max: 2,9 dB @ 2 GHz<br>fT min: 7.0 GHz<br>Variant 05 of ESCC spec.<br>Operating Temperature Range (°C.): -65 to +200  | BV CEO (V): 12<br>Ic (mA): 65<br>Pout (mW): 450<br>MAG/MSG min: 12.5 dB @ 2 GHz | ESCC 5611/006 | MICRO X         | • INFINEON<br>TECHNOLOGIES A.G. |
| 1         | BFY193    | BV CBO (V): 20<br>hFE min/max: 50/175 @ IC max = 30 mA<br>Nf max: 2,9 dB @ 2 GHz<br>fT min: 7.0 GHz<br>Variant 06 of ESCC spec.<br>Operating Temperature Range (°C.): -65 to +200   | BV CEO (V): 12<br>Ic (mA): 80<br>Pout (mW): 580<br>MAG/MSG min: 12.5 dB @ 2 GHz | ESCC 5611/006 | MICRO X         | • INFINEON<br>TECHNOLOGIES A.G. |
| 1         | BFY280    | BV CBO (V): 8<br>hFE min/max: 30/175 @ IC max = 0.25 mA<br>Nf max: 2.9 dB @ 2 GHz<br>fT min: 7.0 GHz<br>Variant 02 of ESCC spec.<br>Operating Temperature Range (°C.): -65 to +200  | BV CEO (V): 15<br>Ic (mA): 10<br>Pout (mW): 80<br>MAG/MSG min: 13 dB @ 2 GHz    | ESCC 5611/006 | MICRO X         | • INFINEON<br>TECHNOLOGIES A.G. |
| 1         | BFY405    | BV CBO (V): 15<br>hFE min/max: 50/150 @ IC max = 2.0 mA<br>Nf max: 1.8 dB @ 1.8 GHz<br>fT min: 20 GHz<br>Variant 01 of ESCC spec.<br>Operating Temperature Range (°C.): -65 to +175 | BV CEO (V): 4.5<br>Ic (mA): 12<br>Pout (mW): 55<br>Ic (mA): 2.0                 | ESCC 5611/008 | MICRO X         | • INFINEON<br>TECHNOLOGIES A.G. |
| 1         | BFY420    | BV CBO (V): 15<br>hFE min/max: 50/150 @ IC max = 20 mA<br>Nf max: 1.7 dB @ 1.8 GHz<br>fT min: 20 GHz<br>Variant 02 of ESCC spec.<br>Operating Temperature Range (°C.): -65 to +175  | BV CEO (V): 4.5<br>Ic (mA): 35<br>Pout (mW): 160<br>Ic (mA): 5.0                | ESCC 5611/008 | MICRO X         | • INFINEON<br>TECHNOLOGIES A.G. |

12 TRANSISTORS | 10 RF/MICROWAVE NPN LOW POWER / LOW NOISE

| EPPL Part | Part Type | Description  | Detail Specification | Package | Manufacturer(s)                 | Remarks |
|-----------|-----------|--|----------------------|---------|---------------------------------|---------|
| 1         | BFY450    | BV CBO (V): 15      BV CEO (V): 4.5      Ic (mA): 100<br>hFE min/max: 50/150 @ IC max = 20 mA      Pout (mW): 450<br>Nf max: 2.0 dB @ 1.8 GHz      Ic (mA): 10<br>fT min: 18 GHz<br>Variant 03 of ESCC spec.<br>Operating Temperature Range (°C.): -65 to +175 | ESCC 5611/008        | MICRO X | • INFINEON<br>TECHNOLOGIES A.G. |         |

12 TRANSISTORS | 16 MICROWAVE LOW NOISE (GaAs)

| EPPL Part | Part Type           | Description   | Detail Specification | Package | Manufacturer(s)                 | Remarks   |
|-----------|---------------------|---|----------------------|---------|---------------------------------|---|
| 1         | CFY 67 CFY<br>67_08 | Pseudomorphic HEMT<br>Vds (V): 3.5      Vdg (V): 4.5      Id (mA): 60<br>NF <= 0.8 dB Ga >= 11 dB @ 12 GHz (Variant 01 and 03)<br>NF <= 1.0 dB Ga >= 10.5 dB @ 12 GHz (Variant 02 and 04)<br>Ptot (mW): 200<br>Operating Temperature Range (°C.): -65 to +150 | ESCC 5613/004        | MICRO X | • INFINEON<br>TECHNOLOGIES A.G. | Rrecommended for<br>applications in X<br>and Ku bands |



## 13 WIRES AND CABLES | 01 LOW FREQUENCY

| EPPL Part | Part Type                    | Description   | Detail Specification | Package | Manufacturer(s)                | Remarks |
|-----------|------------------------------|---|----------------------|---------|--------------------------------|---------|
| 1         | 3901001**B                   | Low Frequency, Polyimide Insulation<br>Voltage Rating, maximum (Vrms): 600<br>Insulation Type: Polyimide/Kapton, Light weight<br>Wire size AWG 26 to 12, shielded and jacketed wires only, up to 3 cores<br>Operating Temperature Range (°C): -100 to +200C                     | ESCC 3901/001        | N/A     | • AXON' CABLE                  |         |
| 1         | 3901002**B                   | Low Frequency, Polyimide Insulation<br>Voltage Rating, maximum (Vrms): 600<br>Insulation Type: Polyimide/Kapton, medium weight<br>Wire size AWG 28 to 18, single finished wires unjacketed and unshielded<br>Operating Temperature Range (°C): -100 to +200C                    | ESCC 3901/002        | N/A     | • AXON' CABLE                  |         |
| 1         | L45493-<br>R3901-A18*-<br>** | Wire size AWG 12 to 26, shielded and unshielded up to 7 cores   | ESCC 3901/018        | N/A     | • LEONI SPECIAL<br>CABLES GmbH |         |
| 1         | L45493-<br>R3901-A21*-<br>** | Wire size AWG 12 to 26, shielded and unshielded up to 7 cores   | ESCC 3901/021        | N/A     | • LEONI SPECIAL<br>CABLES GmbH |         |
| 1         | MTV-BTV                      | Low Frequency, PTFE/Polyimide Insulation<br>Voltage Rating, maximum (Vrms): 600<br>Insulation Type: Extruded PTFE for flexibility<br>Wire size AWG 30 to 18, shielded and unshielded, up to 5 cores<br>Operating Temperature Range (°C): -100 to +200C                          | ESCC 3901/013        | N/A     | • NEXANS                       |         |
| 1         | Series 55                    | Low Frequency, 600V, Silver-plated Copper, Extruded Crosslinked Fluoropolymer Insulation.<br>Voltage Rating (max Vrms): 600<br>Wire size ISO 001, 002, 004, 006, 010, 012, 020, 030, shielded and unshielded , up to 4 cores<br>Operating Temperature Range (°C): -100 to +200C | ESCC 3901/012        | N/A     | • TYCO ELECTRONICS UK<br>Ltd.  |         |
| 1         | SPL                          | Low Frequency, Polyimide Insulation.<br>Voltage Rating, maximum (Vrms): 600<br>Insulation Type: Polyimide/Expanded PTFE<br>Wire size AWG 28 to 12, shielded and unshielded, up to 7 cores<br>Operating Temperature Range (°C): -200 to +200C                                    | ESCC 3901/019        | N/A     | • W.L.GORE                     |         |
| 1         | SPM                          | Low Frequency, Polyimide/Fluorothermoplast.<br>Voltage Rating, maximum (Vrms): 600<br>Wire size AWG 30 to 12, shielded and unshielded, up to 7 cores<br>Operating Temperature Range (°C): -200 to +200C   | ESCC 3901/018        | N/A     | • W.L.GORE                     |         |
| 1         | SPP                          | Power Wires for Crimping, Low Frequency<br>Voltage Rating, maximum (Vrms): 600<br>Insulation Type: Expanded PTFE Tape<br>Wire size AWG 4 and 8<br>Operating Temperature Range (°C): -200 to +200C   | ESCC 3901/017        | N/A     | • W.L.GORE                     |         |

## 13 WIRES AND CABLES | 02 COAXIAL

| EPPL Part | Part Type             | Description  | Detail Specification | Package | Manufacturer(s) | Remarks    |
|-----------|-----------------------|--|----------------------|---------|-----------------|------------|
| 1         | 50CIS                 | Coaxial, double shield coaxial, shielded and jacketed coaxial.<br>Miniature, 50 Ohms, PTFE Dielectric, Polyimide Jacket<br>Maximum Voltage: 900 Vrms<br>Operating Temperature Range (°C): -100 to + 200  | ESCC 3902/001        | N/A     | • NEXANS        |            |
| 1         | GCX, GTX,<br>GSC, GBL | Flexible, Coaxial, Triaxial and Symmetric Cables, -200 to +180°C<br>Variants 03 to 06 (Coaxial), 10 to 13 (Triaxial) and 20 to 30 (shielded line)<br>Operating Voltage (Continuous), maximum ratings, (Vrms):<br>Variants 03 180<br>Variants 04,10,21,22,23,24,26 to 30 200<br>Variants 06,25 250<br>Variants 05,11 to 13,20 300<br>AWG Range: 20, 22, 24, 26, 28, 30 dependent on variant<br>Temperature range (°C): -200 to +180 | ESCC 3902/002        | N/A     | • W.L.GORE      | Max AWG 28 |

## 14 TRANSFORMER | 02 SIGNAL

| EPPL Part | Part Type | Description   | Detail Specification | Package      | Manufacturer(s) | Remarks |
|-----------|-----------|---|----------------------|--------------|-----------------|---------|
| 2         | DBIT      | DBIT Transformers 1553, moulded<br>Min. Impedance: 3Kohm    Max Leakage Inductance: 6uH<br>Size max (mm): 16 X 16 X H<br>DBIT-X-7P10. H(max): 17mm. Through Hole<br>DBIT-X-3S. H(max): 3,81mm. SMD<br>DBIT-X-5S. H(max): 5mm. SMD<br>DBIT-X-7S. H(max): 7mm. SMD<br>DBIT-X-7P. H(max): 11mm. Through Hole<br>Operating temperature range (°C.): -55 to +125 | MSP-003              | AS PER SPEC. | • MICROSPIRE    |         |

## 16 SWITCHES | 04 MICROSWITCH

| EPPL Part | Part Type | Description  | Detail Specification | Package         | Manufacturer(s) | Remarks |
|-----------|-----------|--|----------------------|-----------------|-----------------|---------|
| 2         | T3        | Microswitches, Sensitive, 1PDT<br>Contact Rating: 4A, 28 Vdc, Contact Configuration SPDT<br>Operating Temperature Range (°C): -55 to + 125 | ESCC 3701/003        | AS PER<br>SPEC. | • ABB ENTRELEC  |         |

20 THERMOSTAT | 01 ALL

| EPPL Part | Part Type | Description  | Detail Specification | Package         | Manufacturer(s) | Remarks |
|-----------|-----------|--|----------------------|-----------------|-----------------|---------|
| 1         | 47        | Contact Configuration SPST, Contact Rating: 4A, 30 Vdc<br>Difference between contact opening temp. and closing temp. (°C max):<br>For switching temp < -31°C                                10<br>For -30 < switching temp > +79°C                                5 or 10<br>For switching temp > +80°C                                15<br>Variant 02<br>Dimensions (max., mm.) : 16.2 DIA, 11.5 height<br>Minimum temperature gradient: 0.11 deg.C/minute<br>Operating Temperature Range (°C): -50 to + 150 | ESCC 3702/001        | AS PER<br>SPEC. | • COMEPA        |         |

### 30 RF PASSIVE COMPONENTS | 10 COAXIAL ATTENUATORS/LOADS

| EPPL Part | Part Type           | Description  | Detail Specification | Package       | Manufacturer(s) | Remarks |
|-----------|---------------------|--|----------------------|---------------|-----------------|---------|
| 1         | Coaxial Attenuators | R.F. Attenuators, Fixed, Coaxial.<br>Frequency Range (GHz): 0 - 22<br>Attenuation value range (dB): 0 - 20<br>Operating Temperature Range (°C): -55 + 125  | ESCC 3403/005        | AS PER SPEC.  | • RADIALL       |         |
| 2         | R4042106            | RF coaxial load<br>50W, DC to 18GHz, 1W<br>SMA male connector<br>Operating temperature range: -55 to +125 °C   | ESCC 3403/004        | SMA connector | • RADIALL       |         |
| 2         | R4043706            | RF coaxial load<br>50W, DC to 18GHz, 2W<br>TNC male connector<br>Operating temperature range: -55 to +125 °C   | ESCC 3403/010        | TNC connector | • RADIALL       |         |
| 1         | RF Coaxial Loads    | Passive Devices, RF, Coaxial, Loads<br>Frequency Range (GHz): 0 - 22<br>Rated P (in) (W): 1                  Impedance (Ohm): 50<br>VSWR (Max.):<br>Type 0<f(GHz)<= 4; 4<f(GHz)<= 12.4; 12.4<f(GHz)<= 18; 18<f(GHz)<= 22<br>1      1.05                  1.10                  1.15                  1.20<br>2      1.05                  1.15                  1.20                  1.25<br>Operating Temperature Range (°C): -55 to + 125 | ESCC 3403/006        | AS PER SPEC.  | • RADIALL       |         |

40 HYBRIDS | 01 THICK FILM

| EPPL Part | Part Type                            | Description   | Detail Specification   | Package                     | Manufacturer(s)                 | Remarks   |
|-----------|--------------------------------------|---|--|-----------------------------|---------------------------------|---|
| 1         | 8090.0832.G<br>03                    | Pulse Width Modulator Controller for DC/DC Converters for flyback, forward, push-pull and half bridge topologies, primary supply voltage range: 18 to 110V, Iout=1 mA for Vref @ 2.5 and 5.0V, Max. oscillator frequency: 250 kHz, Under-voltage lockout with hysteresis, Over-voltage protection, Ccurrent comparator, Voltage loop, Soft-start, Adjustable, Surface Mount, Hermetically Sealed, | 8090.0832-1,<br>Issue 2.5,<br>23/03/2009                               | CQFP-84                     | • Thales Alenia Space<br>- ETCA | According to PID<br>9100.0683, Issue<br>4.5 dated<br>10/09/2010 and HTIF<br>HYB-GEN-ES-0017-01-<br>02-HTIF-<br>80900832G03, Issue<br>1.2 dated<br>20/08/2010                    |
| 2         | A0000055<br>(H757)                   | Thick Film Hermetic Hybrid - MIL-STD-1553B Dual Transceiver<br>(Integrated MIL-STD-1553B Dual Complete Transmitter + MIL-STD-1553B Dual Complete Receiver)<br>Operational Rated Temperature -30 to +85 °C   | DPN-A5-ST-0426<br>Ed.02 Rev.00   | Metallic<br>FP-46           | • Astrium Velizy                | PID<br>GM.HYBR.NT.220.V.MM<br>S Ed.13 Rev.00  |
| 2         | A0005367                             | Thick Film Hermetic Hybrid - MIL-STD-1553B Remote Terminal Coupler<br>(Integrated MIL-STD-1553B Single Transceiver + MIL-STD-1553B Remote Terminal ASIC)<br>Operational Rated Temperature -30 to +85 °C   | A5-PS-CA5-491-MMV<br>Ed.00 Rev.0+DPN-<br>A5-ST-0376 Ed<br>01(ASP20-RT) | Metallic<br>FP-64           | • Astrium Velizy                | PID<br>GM.HYBR.NT.220.V.MM<br>S Ed.13 Rev.00  |
| 2         | MCM 21020<br>DSP BR334<br>(A0008778) | Multi-chip Module Digital Signal Processor 21020 (TSC21020E floating-point DPS + DPC co-prcessor + 128 kwords on-module SRAM + cascadable timers, full duplex UARTs, 1355 serial links, watchdog timers and PWM channels).<br>Operational Rated Temperature -30 to +85 °C   | MCM-DSP-SPEC-<br>DA0018353-V-ASTR<br>Ed.00 Rev.06                      | CQFP-334                    | • Astrium Velizy                | PID<br>GM.HYBR.NT.879.V.AS<br>TR Ed.03 Rev 00.<br>Det. Spec. is MCM<br>DSP21020<br>Procurement<br>specification.<br>Replaces the old<br>version MCM2102-<br>A0005305 (obsolete) |
| 2         | MCM ERC32<br>(A0008608)              | Multi Chip Module Software processing module (20 Mips at 25 MHz) based on a CPU core embedding the ERC32SC, VASI ASIC chip and memories<br>Operational Rated Temperature -30 to +85 °C  | MCM-ERC32-SP-<br>00306-V-ASTR<br>Ed.00 Rev.01                          | Dual-<br>cavity<br>co-fired | • Astrium Velizy                | PID<br>GM.HYBR.NT.879.V.AS<br>TR Ed.03 Rev 00.<br>Det. Spec. is MCM<br>ERC32 procurement<br>specification.  |

## 40 HYBRIDS | 02 THIN FILM

---

| EPPL Part | Part Type | Description   | Detail Specification | Package | Manufacturer(s)                  | Remarks |
|-----------|-----------|---|----------------------|---------|----------------------------------|---------|
| 2         | AGT-01    | Cascadable Amplifier (5-250 MHz)<br>High Gain two stage 31 dB<br>Medium output level +8.5 dBm<br>Low VSWR < 1.3:1<br>Supply power range +8V to +15V | TD200368-178         | TO-8    | • CHELTON TELECOM &<br>MICROWAVE |         |

---



40 HYBRIDS | 99 MISCELLANEOUS

| EPPL Part | Part Type | Description  | Detail Specification    | Package | Manufacturer(s)               | Remarks |
|-----------|-----------|--|-------------------------|---------|-------------------------------|---------|
| 2         | MRF-01    | Image Reject Mixer, variant V1=RF>LO, variant V2=RF<LO, LO to RF@1500 to 1650MHz=28 dB min., LO to IF@90 to 1510MHz= 35 dB min., Image Reject Ratio = 20 dB min., Hermetically Sealed, Ceramic Flatpack Package.<br><br>Operating temperature range: -55 to +125 °C  | TD200450-178D           | FP      | • CHELTON TELECOM & MICROWAVE |         |
| 2         | MXF-01    | Double Balanced Mixer (0.5 to 500 MHz), Conversion Loss: 7 dB max., Isolation: LO to RF, LO to IF @ midband: 35 dB min., RF to IF @ midband: 25 dB min., Hermetically Sealed.<br><br>Operating Temperature Range: -55 to +125 °C   | TD200369-178<br>Issue a | FP      | • CHELTON TELECOM & MICROWAVE |         |
| 2         | MXF-02    | Double balanced Mixer<br>10 to 1500 MHz<br><br>Operating temperature range: -55 to +125 °C   | TD200370-178<br>Issue a | FP      | • CHELTON TELECOM & MICROWAVE |         |
| 2         | MXF-03    | Termination Insensitive Mixer (1 to 3500 MHz), Isolation:LO to RF and LO to IF: 20 dB min. and RF to IF : 18 dB min., SSB Conversion Loss (RF to IF [60MHz] port): from 7.8 to 9.8 dB max., 3rd order intermodulation ratio degradation @ IF VSWR 3: 1: 3 dB typ., Hermetically Sealed, Metal Flatpack package.<br><br>Operating Temperature Range: -55 to +125 °C | TD200542-178<br>Issue B | FP      | • CHELTON TELECOM & MICROWAVE |         |