



Types covered by similarity: Coil voltage 12 Vdc .		Remarks: Will not be maintained. The qualification entry will be removed from the QPL by January 2014				
Procurement Specifications		Manufacturer	Nature of Approval	Supervising Authority	Date	
Generic ESCC 3601 Detail ESCC 3601/007		STPI Paris France	Qualification Extension Extension	CNES CNES CNES	Apr 2007 Oct 2010 Jun 2012	
Characteristics: Variants 01 to 06 are qualified Contact Rating 15 A at 28 Vdc Contact Configuration 2 PDT Size (mm. max.) 26x26x14 Package Type 1/2 can Coil Voltage 28 Vdc Operating Temperature Range (°C): -65 to +125						
		RELAY, NON-LATCHING, ELECTROMAGNETIC, TYPE 317		Current Validity of Qualification		Page
				Certificate	Valid Until	09-01
				279 B	April 2013	006

Types covered by similarity:				Remarks: Will not be maintained. The qualification entry will be removed from the QPL by January 2014		
Coil Voltage 12 Vdc						
.						
Procurement Specifications		Manufacturer		Nature of Approval	Supervising Authority	Date
Generic ESCC 3602		STPI Paris France		Qualification	CNES	Apr 2007
				Extension	CNES	Oct 2010
Detail ESCC 3602/004 3602/009				Extension	CNES	Jun 2012
Characteristics:						
3602/004		Variants 04, 06 and 09 14, 16 and 19 are qualified		3602/009		Variants 03, 04 and 06 and 13, 14 and 16 are qualified
Contact Rating	15 A at 28 Vdc		Contact Rating	15 A at 28 Vdc		
Contact Configuration	4 PDT		Contact Configuration	2 PDT		
Size (mm. max.)	26x26x26		Size (mm. max.)	26x26x13.34		
Package Type	can		Package Type	1/2 can		
Coil Voltage	28 Vdc		Coil Voltage	28 Vdc		
Operating Temperature Range (°C): -65 to +125		Operating Temperature Range (°C): -65 to +125				
		RELAY, NON-LATCHING, ELECTROMAGNETIC, TYPE 3*7B		Current Validity of Qualification		Page
				Certificate	Valid Until	09-02 006
				280 B	April 2013	