	A.	~
5		
	A.	
E	ES	ESC

Component Title:

Relays, latching, M302

Page 1

				-,		V. =>	Ballistation with the total and the total and the	Appl.	No.
1888 - 47 100 W. E.	5 96 MAG 98		Executive Member: CNES Date: 27/02/2015				310	310B	
Components (includ	ing series and familie	s) submitted for Ext	tension of Qua	alification App	proval:				
ESCC COMPONENT NO.	VARIANTS	RANGE (	OF COMPONE	ENTS	BASED ON	D TEST VEHICLE / S		COMPONE SIMILAR	
3602 009	03,04,06,13,14 and	Coil voltage 1	2 and 28 Volt	s	A 302	3602	009 06 B 12V	All other varia ESCC 360200	
Component M	CONTRACTOR	2 Location	of Manufactu	uring Plant(s)	3				4
Esterline Leach i Europe	nternational	2 Rue Goe 57430 Sarr	200	1000 0000		Date of origin Date: Certificate Re	nal qualification ap 01/04/2011 of No. 310	proval:	
ESCC Specifications Maintenance of quali Generic: 3602 Detail(s): 3602 00	used for ification testing: Issue: 3	Deviation from	Yes 🗆	(supply detai	ls in Box	Qualification reference and RT_1150776 February 201			7
Summary of procure	ment or equivalent tes	t results during cur	rent validity pe	eriod in suppo	rt of this ap	olication (those	to ESCC listed firs	st)	8
Project Name CFCD-ROM Annex 11- Summary of manufactured batche pdf	Testing Leve	i LA	T	Date	code		Quantity [	Delivered	
							(100 title) - 1 (100 title) - 1	talan saketan	
PID changes since st  None □  Minor* ☑  Major* □	art of qualification  *Provide details in bo	x:	9 Curre Ref N		ed by: M302_1156		CNES xcutive Represent Date:	ative 26/02/2015	10
Current Manufacturing facilities surveyed by:			Rev DESA	and CNES	2/2015 entative)	on 03/2014			11
Satisfactory:	Yes ⊠	No 🗆	Explain						
Report Reference:	Audit report LEA ESA-TECQES-R	NIO-AUD-2014, RP-0355, 03/2014	£8						

	APPLICATI	OIL I OIL EXT	ENSION OF ESCO	QUALIFICATION A	PPROVAL	Page 2
ESCC	Component title:	Relays, lato	hing, M302			Appl. No.
	Executive Member:	CNES		Date: 27/0	2/2015	310B
		(A)(1)(E)(A)				3108
ailure Analysis, DPA, NCCS	available: Yes	□ No		data)		<u>a</u>
f. No's and purposes:						
e undersigned hereby certifies on be t the appropriate documentation has	s been evaluated; - that full	Il compliance to	all ESCC requirer	ments is evidence		
cept as stated in box 15;) - that the r NES as the responsible Executive M	reports and data are availa Nember for ESCC qualifica	able at the ESC ition status to b	CC Executive and to be extended to the	herefore applies on be component(s) listed h	ehalf of erein.	mount
					`	
te: 27/02/2015				(Signatu	JP. BUSSENO re of the Executive (	
				(Signatu	TE OF THE EXECUTIVE O	Coordinator)
ntinuation of Boxes above:	20 20 20 20 22	55 SE				
Changes to comply with 3602 issu	ue 3, creation of a new PID	reference.				

		56	7	7
Non	 iones	to ES	C	

Relays, latching, M302

Component title:

Page 3 Appl. No.

2, 2,300 CA. No.		Executive Memb	per: CNES	Date:	27/02/2015	310B
Non compliance	e to ESCC_requirements	5:				15
No.:	Specification		Paragraph		Non compliance	700
7,44.	o positioning.		. a. agi apii		Tion compliance	
				4		
				1		
				1		
	0.02					
Additional tasks noncompliance	s required to achieve full	compliance for ESCC	qualification or rationale for acce	eptability of		16
noncompilario c	<b>*</b>					
Executive Man	ager Disposition				No.	47
		100 N-0				17
Application App		No 🗆				
Action / Remar	KS:					
				r	1	
				\	110	1
				\ \	$\sim 1 AO$	6
27						- 1
Date:						
				Signa	ature, ESA Representative	



Component Title: Relays, latching, M302

Page 4

Appl. No.

Executive Member: CNES

Date: 27/02/2015

310B

ANNEX 1: LIST OF TESTS DONE TO SUPPORT EXTENSION OF QUALIFICATION

Tests conducted in compliance with:

ESCC 3602 generic specification; Chart F4 (for ESCC/QPL parts);
 Or PID-TFD (for ESCC/QML parts)

Tests vehicle identification/description:

Detail Specification reference:

3602 009

Chart F4	Test	Tick when done	Conditions	Date Code	Tested Qty	No. of Rejects	Comments if not performed. Comments on Rejection
Thermal Shock		⋈	MIL-STD-202, Test Method 107	14-36	6	o	
Mechanical Subgroup olumn 1)	Low Level Sine Vibration	⊠	MIL-STD-202, Test Method 204	14-36	6	0	
iical Si	Random Vibration	×	MIL-STD-202, Test Method 214	14-36	6	0	
/ Mechani (Column 1)	Low Level Mechanical Shock	⊠	MIL-STD-202, Test Method 213	14-36	6	0	
	Resistance to Soldering Heat	⊠	MIL-STD-202, Test Method 210	14-36	6	0	
Environmental / (C	Seal (Fine and Gross Leak)	⊠	MIL-STD-202, Test Method 112	14-36	6	0	
	External Visual Inspection	Ø	ESCC Basic Specification No. 20500	14-36	6	0	
dno	High Level Sine Vibration	⊠	MIL-STD-202, Test Method 204	14-36	6	0	
nvironmental anical Subgroup (Column 2)	High Level Mechanical Shock	×	MIL-STD-202, Test Method 213	14-36	6	0	
Environmental Mechanical Subo (Column 2)	Seal (Fine and Gross Leak)	⊠	MIL-STD-202, Test Method 112	14-36	6	0	
/ Mec	External Visual Inspection	×	ESCC Basic Specification No. 20500	14-36	6	0	
p 1	Low Level Life	.0	ESCC 3602 Para. 8.11.1				
Subgrou In 1)	Inductive Life	Ø	ESCC 3602 Para. 8.11.2	14-36	3	0	
Endurance Subgroup 1 (Column 1)	Seal (Fine and Gross Leak)	⊠	MIL-STD-202, Test Method 112	14-36	3	0	
Endu	External Visual Inspection	⊠	ESCC Basic Specification No. 20500	14-36	3	0	



Relays, latching, M302

a minute thoras was appropriately the same

Component title:

Executive Member: CNES Date: 27/02/2015

Page 5

Appl. No.

310B

Chart F4	Test	Tick when done	Conditions	Date Code	Tested Qty	No. of Rejects	Comments if not performed. Comments on Rejection
0.50	Coil Life		ESCC 3602 Para. 8.12		V/12/4 May 17 - 17 -		
Endurance Subgroup 1 (Column 2)	Seal (Fine and Gross Leak)		MIL-STD-202, Test Method 112				
External Visual Inspection		ESCC Basic Specification No. 20500					
dno	Intermediate Current	Ø	ESCC 3602 Para. 8.13	14-36	6	0	
Endurance Subgroup 1 (Column 3)	Mechanical Life	×	ESCC 3602 Para. 8.14	14-36	6	0	
(Colun	Seal (Fine and Gross Leak)	×	MIL-STD-202, Test Method 112	14-36	6	0	
Endur 1	External Visual Inspection	⊠	ESCC Basic Specification No. 20500	14-36	6	0	
Resistive Life  Seal (Fine and Gross Leak)  External Visual	⊠	ESCC 3602 Para. 8.11.3	14-36	6	0		
		⊠	MIL-STD-202, Test Method 112	14-36	6	0	
End	External Visual Inspection	Ø	ESCC Basic Specification No. 20500	14-36	6	0	
	Solderability	⊠	MIL-STD-202, Test Method 208	14-36	3	0	
ability	Overload	×	ESCC 3602 Para. 8.16	14-36	3	0	
Assembly Capability Subgroup	Permanence of Marking	⊠	ESCC Basic Specification No. 24800	14-36	3	0	
Assen	Terminal Strength	×	MIL-STD-202, Test Method 211	14-36	3	0	
	Seal (Fine and Gross Leak)	×	MIL-STD-202, Test Method 112	14-36	3	0	
onal			127				
Additional		9/26					
<							



Component title: Relays, latching, M302

Page 7 Appl. No.

Executive Member: CNES Date: 27/02/2015

310B

#### NOTES ON THE COMPLETION OF THE APPLICATION FORM FOR ESCC QUALIFICATION EXTENSION APPROVAL

	NOTES OF THE COMPLETION OF THE AFFECATION FOR ESSE GOALS TO A TOTAL EXTENSION AFFECATE
ENTRIES Form heading	shall indicate: - the title of the component as given in its detail specification or the name of the series, family; - the Executive Member; - the entering date; - the certificate number and its sequential suffix.
Box 1	shall provide details given in the table; in particular there shall be listed: - the variants or range of variants; - the range of components (the ESCC code is recommended to indicate the values or values range, the tolerance, the voltage, etc); the designation given in the detail specification as 'base on'; - under Test Vehicle enter either an ESCC code or the specific characteristic capable of identifying the component tested (e.g., voltage of coil for a relay); - under component similar enter a cross if relevant.
Box 2; 3 and 4	As per QPL entry; otherwise, an explanation of the changes must be supplied.
Box 5	Will show the ESCC Generic and Detail specifications, including issue number and revision letter, current at the time the tests reported were performed. If the specifications are different from those current on the date of the application, see Box 6.
Box 6	Will show the deviations from the Generic and Detail Specifications listed in Box 5, in particular deviations from testing. In case of deviations this must be listed in Box 15. In case the referenced specification in Box 5 have currently a different issue and/or revision indicate also whether the test data deviates or not from such current documents.
Box 7	Must reference the report(s) supplied in support of the application.
Box 8	Should provide the details of procurement to the full ESCC System, documentation of all of which should already have been delivered to the ESCC Executive under the terms of the relevant Generic Specification. An appropriate table has been drawn in this box.
Box 9	If the PID evolved after the Original Qualification or after the last Extension of Qualification, adequate details of such evolution shall be provided together with the reasons for the changes. Major changes shall be clearly marked.
Box 10	Identify the current PID issue status, date and actual date of verification. The date of verification of the current PID should be arranged as close as possible to the required date of extension.
Box 11	This box can be completed only after a physical visit to the plant to confirm that no unexplained changes occurred and that the practices, procedures, material, etc. used in manufacturing the components are as described in the PID. This survey shall be carried out in accordance with the requirements of ESCC Basic Specification No. 20200 and its findings shall be recorded.
Box 12	Provide details of, or reference to, any Destructive Physical Analysis (DPA) and Failure Analysis reports as well as any Nonconformance(s) (NCCS) occurred during the qualification validity period, stating if established corrective action have produced satisfactory results.
Box 13	Enter only the name of the Executive Member (i.e., CNES, DLR, ESTEC, etc.) and the signature of the responsible Executive Coordinator.
Box 14	To be used when there is a need to expand any of the boxes from 1 through 12. Identify box affected and reference the Box 14 in the relevant Box. Box 14 can be broken into 14a, 14b, etc. if several boxes have to be expanded.
Box 15	Fill in Table as requested.
Box 16	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
Box 17	All Executive Manager recommendations on the application itself, special conditions or restrictions, modifications of the QPL or QML entry, letters to the manufacturer, etc. shall be entered clearly in Box 19, signed by the representative for ESA, and dated.
Box 18	Fill in Table as requested.
Box 19	Confidential Details of PID changes including those of a confidential nature, shall be provided.

State noncompliance with reference to specification(s) and paragraph(s). To simplify reference in Box 16 each nonconformance shall be sequentially numbered. If relevant state 'None'.

Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance. Box 21

Box 22 Additional Comments,

Box 20