Types covered by similarity: All values defined by the ESCC Detail Specification ±20% (E6 Series) tolerance by variant where applicable					Remarks:		
Generic ESCC 3006 Detail ESCC 3006/024			Exxelia Technologies Marmoutier France		Qualification	CNES	Aug 2002
Characteristics: E12 Series							
Sizes Available 01, 02, 03, 04	zes Available 01, 02, 03, 04 Capacitance Range (μ		Tol. (±%)	U _R (V)			
Maximum dimensions (mm): 01: 10.7 x 10.7 x B 02: 15.5 x 15.5 x B 03: 16.5 x 15.5 x B 04: 18.5 x 17.0 x B Where B= 6, 8, 10, 12, 14, 15 depen	2.2 to 1.5 to 0.56 to 0.33 to 0.22 to 0.10 to	47 22 12 5.6 4.7 1.8	10 10 10 10 10 10	50 63 100 200 250 400			
capacitance value Operating Temperature Range, (°C): -55 to +125							
European Space Components Coordination	CAPACITORS, FIXED, SURFACE MOUNT, D.C. SELF-HEALING, NON-INDUCTIVE, POLYTEREPH- THALATE DIELECTRIC, BASED ON TYPE PM94S				Certificate 270 E		Page 01-05 003-1