		700	~
of the state of	ES		
	-		

APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component Title:

Extruded, Cross-Linked Fluoropolymer Insulated Wires And Cables On Silver-Plated Copper Conductor, Low Frequency, 600V, -100 to +200°C

Page 1 Appl. No.

		Executive Member:	CNES		Date:	04/05/2015	26	7G
Components (includi	ing series and families) s	submitted for Extension	n of Qualification	Approval:				_1
ESCC COMP. NO.	VARIANTS	RANGE OF COMPONENTS		BASEC		TEST VEHICLE / S	COMPONENT SIMILAR	
3901 012	1 to 80	Voltage Rating, maximum (Vrms): Click here to text.		000000000000000000000000000000000000000	01 012 10; single re AWG12	10: single 3901 021		
Click here to enter text.	Click here to enter text.	Temperature Range (°C): -100 to Click here to e text.			ick here to enter			
	Click here to enter text.	All variants including	g AWG 30 are				İ	
	Click here to enter text.	Wire code ISO 263	5					
Component M Axon	anufacturer 2	Location of M Axon'Cable SA Route de Chalons e 51210 Montmirail	Manufacturing Pla	ant 3	Date of or Date:	riginal qualification a 01/03/2002 a Ref No. 267	pproval:	4
ESCC Specifications Maintenance of qual Generic: 3901 Detail(s): 3901 01	ification testing:	Deviations to LVT to used: No	☐ (supply of 15)	details in Box	reference TEST RE	ion Extension Repor and date: PORT N°3622 Issue IZT 3626 1013 - 78 VSION OF J	A, 7 th April 2015	7 5 8746 4-WG3
	ment or equivalent test r		alidity period in s	upport of this ap	plication (th	ose to ESCC listed f	first)	[8
Project Name See appendix	Testing Level	LAT		Date code		Qı	uantity Delivered	11-01-01-01-01-01-01-01-01-01-01-01-01-0
PID changes since	tart of qualification *Provide detail	9	50	Verified by: ESA-PID-01-AX 13		CNES of Excutive Represe		10
Current Manufacturin	ng facilities to be surveye		CNES & E		on	09	9/06/2015	11
Satisfactory: \[\sqrt{=} C n \]	Yes of es ca N	No □ Ex	e of Executive Re	epresentative)			(Date)	

Executive Member:			r Insulated Wires And Cables On Frequency, 600V, -100 to +200°C Date: 04/05/2015	
	CNES		Date: 04/05/2015	267G
Failure Analysis. DPA. NCCS available: Yes				AND THE REST
Ref. No's and purposes: Click here to enter text.	□ No I	⊠ (Supply data)	Click here to enter text.	
The undersigned hereby certifies on behalf of the ESCC Executive that the appropriate documentation has been evaluated; - that full c except as stated in box 15; - that the reports and data are available CNES as the responsible Executive Member for ESCC qualification	compliance to all at the ESCC Ex	ESCC requirements i recutive and therefore	s evidence applies on behalf of	- Words
Date: 21/05/2015			JP. BUSSENOT	
			((Signature of the Executiv	e Coordinator)
Continuation of Boxes above:				

		-	30
No. of Con.		51	
100	-	_	

APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component title:

Extruded, Cross-Linked Fluoropolymer Insulated Wires And Cables On Silver-Plated Copper Conductor, Low Frequency, 600V, -100 to +200°C

Appl. No.

Page 3

Executive Member: CNES

Date: 04/05/2015

267G

No.:		Noncompliance to ESCC requirements:			
	Specification	Paragraph	Non co	mpliance	
Additional tasks re	equired to achieve full compliance for Es	SCC qualification or rationale for acceptab	ility of		14
noncompliance:					8,40
				Tes	
Executive Manage	er Disposition				15
Application Appro	val: Yes 🗆 No 🗆			100	15
Application Appro	val: Yes 🗆 No 🗆				15
Application Appro	val: Yes 🗆 No 🗆				15
Application Appro	val: Yes 🗆 No 🗆				15
Application Appro	val: Yes 🗆 No 🗆				15
Application Appro	val: Yes 🗆 No 🗆				15
Application Appro	val: Yes 🗆 No 🗆				15
Application Appro	val: Yes 🗆 No 🗆				15
Application Appro	val: Yes 🗆 No 🗆				15
Executive Manage Application Appro Action / Remarks:	val: Yes 🗆 No 🗆				15
Application Appro	val: Yes 🗆 No 🗆				15
Application Appro	val: Yes 🗆 No 🗆			101.	15
Application Appro	val: Yes 🗆 No 🗆			<i>iOh</i>	15



Box 17

APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Extruded, Cross-Linked Fluoropolymer Insulated Wires And Cables On Silver-Plated Copper Conductor, Low Frequency, 600V, -100 to Component title:

Executive Member: CNES Date: 04/05/2015

Page 4 Appl. No.

267G

N	OTES ON THE COMPLETION OF THE APPLICATION FORM FOR ESCC QUALIFICATION EXTENSION APPROVAL
ENTRIES	
Form heading	shall indicate: - the title of the component as given in its detail specification or the name of the series, family; - the Executive Member; - the entering date; - the certificate number and its sequential suffix.
Box 1	shall provide details given in the table; in particular there shall be listed: - the variants or range of variants; - the range of components (the ESCC code is recommended to indicate the values or values range, the tolerance, the voltage, etc); the designation given in the detail specification as 'base on'; - under Test Vehicle enter either an ESCC code or the specific characteristic capable of identifying the component tested (e.g., voltage of coil for a relay); - under component similar enter a cross if relevant.
Box 2; 3 and 4	As per QPL entry; otherwise, an explanation of the changes must be supplied.
Box 5	Will show the ESCC Generic and Detail specifications, including issue number and revision letter, current at the time the tests reported were performed. If the specifications are different from those current on the date of the application, see Box 6.
Box 6	Will show the deviations from the Generic and Detail Specifications listed in Box 5, in particular deviations from testing. In case of deviations this must be listed in Box 15. In case the referenced specification in Box 5 have currently a different issue and/or revision indicate also whether the test data deviates or not from such current documents.
Box 7	Must reference the report(s) supplied in support of the application.
Вох 8	Should provide details of procurement to the full ESCC System, documentation of all of which should already have been delivered to the ESCC Executive under the terms of the relevant Generic Specification. An appropriate table has been drawn in this box.
Вох 9	If the PID evolved after the Original Qualification or after the last Extension of Qualification, adequate details of such evolution shall be provided together with the reasons for the changes. Major changes shall be clearly marked.
Box 10	Identify the current PID issue status, date and actual date of verification. The date of verification of the current PID should be arranged as close as possible to the required date of extension.
Box 11	This box can be completed only after a physical visit to the plant to confirm that no unexplained changes occurred and that the practices, procedures, material, etc. used in manufacturing the components are as described in the PID. This survey shall be carried out in accordance with the requirements of ESCC Basic Specification No. 20200 and its findings shall be recorded.
Box 12	Provide details of, or reference to, any Destructive Physical Analysis (DPA) and Failure Analysis reports as well as any Nonconformance(s) (NCCS) occurred during the qualification validity period, stating if established corrective action have produced satisfactory results.
Box 13	Enter only the name of the Executive Member (i.e., CNES, DLR, ESTEC, etc.) and the signature of the responsible Executive Coordinator.
Box 14	To be used when there is a need to expand any of the boxes from 1 through 12. Identify box affected and reference the Box 14 in the relevant Box. Box 14 can be broken into 14a, 14b, etc. if several boxes have to be expanded.
Box 15	State noncompliance with reference to specification(s) and paragraph(s). To simplify reference in Box 16 each nonconformance shall be sequentially numbered. If relevant state 'None'.
Box 16	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.

All Executive Manager recommendations on the application itself, special conditions or restrictions, modifications of the QPL entry, letters to the manufacturer, etc. shall be entered clearly in Box 17, signed by the representative for ESA, and dated.