

		<b>APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL</b>			Page 1
Component Title: Polyimide Insulated Shielded Cables With Drain Wire, Low Frequency, 600V, -200 To +200°C Based On Type SPLD		Executive Member: CNES			Date: 04/05/2015
Appl. No.		293C			1
Components (including series and families) submitted for Extension of Qualification Approval:					
ESCC COMP. NO.	VARIANTS	RANGE OF COMPONENTS	BASED ON	TEST VEHICLE / S	COMPONENT SIMILAR
3901 021	01 to 41	Voltage Rating, maximum (Vrms): 600	SPLD	3901 021 19:	3901 009
		Temperature Range (°C): -200 to +200		shielded and jacketed multicore cable, built with three wires and a drain wire of AWG28 twisted together	3901 019
		All variants including AWG 30 are qualified			
Component Manufacturer Axon		Location of Manufacturing Plant Axon Cable SA Route de Chalons en Champagne 51210 Montmirail		Date of original qualification approval: Date: 15/06/2009 Certificate Ref No. 293	
ESCC Specifications used for Maintenance of qualification testing: Generic: 3901 Detail(s): 3901 021		Deviations to LVT testing and Detail Specification used: No <input checked="" type="checkbox"/> Yes <input type="checkbox"/> (supply details in Box 15) Deviation from current Specifications: No <input checked="" type="checkbox"/> Yes <input type="checkbox"/> (Supply details)		Qualification Extension Report reference and date: TEST REPORT N°3637 Issue A, 15 <sup>th</sup> April 2015 [ADDING AWG-30 TO SCOPE OF QUALIFICATION IS SUPPORTED BY TEST REPORT 3626]	
Summary of procurement or equivalent test results during current validity period in support of this application (those to ESCC listed first)					
Project Name	Testing Level	LAT	Date code	Quantity Delivered	
See appendix					
PID changes since start of qualification None <input type="checkbox"/> Minor* <input checked="" type="checkbox"/> Major* <input type="checkbox"/> *Provide detail		Current PID Verified by: CNES Name of Executive Representative Ref No: ESA-PID-01-AXON Issue: 13 Rev Date: 19/11/2014		Date: 04/05/2015	
Current Manufacturing facilities to be surveyed by: CNES & ESA on 09/06/2015 (Name of Executive Representative) (Date)					
Satisfactory: Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Explain					
<i>wf = CNES 'CR No 999274</i>					



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component title: Polyimide Insulated Shielded Cables With Drain Wire, Low Frequency, 600V, -200 To +200°C Based On Type SPLD

Executive Member: CNES

Date: 04/05/2015

Page 2

Appl. No.

293C

Failure Analysis, DPA, NCCS available: Yes  No  (Supply data) [Click here to enter text.](#)

Ref. No's and purposes:

The undersigned hereby certifies on behalf of the ESCC Executive - that the above information is correct; - that the appropriate documentation has been evaluated; - that full compliance to all ESCC requirements is evidence except as stated in box 15; - that the reports and data are available at the ESCC Executive and therefore applies on behalf of CNES as the responsible Executive Member for ESCC qualification status to be extended to the component(s) listed herein.

Date: 21/05/2015

JP. BUSSENOT

((Signature of the Executive Coordinator)

Continuation of Boxes above:



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component title: Polyimide Insulated Shielded Cables With Drain Wire, Low Frequency, 600V, -200 To +200°C Based On Type SPLD  
Executive Member: CNES Date: 04/05/2015

Page 3  
Appl. No. 293C

Noncompliance to ESCC requirements:

13

No.:	Specification	Paragraph	Non compliance

Additional tasks required to achieve full compliance for ESCC qualification or rationale for acceptability of noncompliance:

14

Executive Manager Disposition

15

Application Approval: Yes  No

Action / Remarks:

Date: [Click here to enter a date.](#)

Signature, ESA Representative



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component title: Polyimide Insulated Shielded Cables With Drain Wire, Low Frequency, 600V, -200 To +200°C Based On Type SPLD

Executive Member: CNES

Date: 04/05/2015

Page 4

Appl. No.

293C

NOTES ON THE COMPLETION OF THE APPLICATION FORM FOR ESCC QUALIFICATION EXTENSION APPROVAL

ENTRIES

Form heading

shall indicate: - the title of the component as given in its detail specification or the name of the series, family; - the Executive Member; - the entering date; - the certificate number and its sequential suffix.

Box 1

shall provide details given in the table; in particular there shall be listed: - the variants or range of variants; - the range of components (the ESCC code is recommended to indicate the values or values range, the tolerance, the voltage, etc); the designation given in the detail specification as 'base on'; - under Test Vehicle enter either an ESCC code or the specific characteristic capable of identifying the component tested (e.g., voltage of coil for a relay); - under component similar enter a cross if relevant.

Box 2; 3 and 4

As per QPL entry; otherwise, an explanation of the changes must be supplied.

Box 5

Will show the ESCC Generic and Detail specifications, including issue number and revision letter, current at the time the tests reported were performed. If the specifications are different from those current on the date of the application, see Box 6.

Box 6

Will show the deviations from the Generic and Detail Specifications listed in Box 5, in particular deviations from testing. In case of deviations this must be listed in Box 15. In case the referenced specification in Box 5 have currently a different issue and/or revision indicate also whether the test data deviates or not from such current documents.

Box 7

Must reference the report(s) supplied in support of the application.

Box 8

Should provide details of procurement to the full ESCC System, documentation of all of which should already have been delivered to the ESCC Executive under the terms of the relevant Generic Specification. An appropriate table has been drawn in this box.

Box 9

If the PID evolved after the Original Qualification or after the last Extension of Qualification, adequate details of such evolution shall be provided together with the reasons for the changes. Major changes shall be clearly marked.

Box 10

Identify the current PID issue status, date and actual date of verification. The date of verification of the current PID should be arranged as close as possible to the required date of extension.

Box 11

This box can be completed only after a physical visit to the plant to confirm that no unexplained changes occurred and that the practices, procedures, material, etc. used in manufacturing the components are as described in the PID. This survey shall be carried out in accordance with the requirements of ESCC Basic Specification No. 20200 and its findings shall be recorded.

Box 12

Provide details of, or reference to, any Destructive Physical Analysis (DPA) and Failure Analysis reports as well as any Nonconformance(s) (NCCS) occurred during the qualification validity period, stating if established corrective action have produced satisfactory results.

Box 13

Enter only the name of the Executive Member (i.e., CNES, DLR, ESTEC, etc.) and the signature of the responsible Executive Coordinator.

Box 14

To be used when there is a need to expand any of the boxes from 1 through 12. Identify box affected and reference the Box 14 in the relevant Box. Box 14 can be broken into 14a, 14b, etc. if several boxes have to be expanded.

Box 15

State noncompliance with reference to specification(s) and paragraph(s). To simplify reference in Box 16 each nonconformance shall be sequentially numbered. If relevant state 'None'.

Box 16

Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.

Box 17

All Executive Manager recommendations on the application itself, special conditions or restrictions, modifications of the QPL entry, letters to the manufacturer, etc. shall be entered clearly in Box 17, signed by the representative for ESA, and dated.