




ESCC QUALIFIED PARTS LIST


REP005


Updated 15 July 2015






Document Custodian: European Space Agency - see <https://spacecomponents.org>


| | |
|---|--|
| | General Information |
| As affected | <i>This is the current QPL for July 2015</i> |
| Section/Page No. | Description |
| | |
|  | |
| Qualified Parts List DOCUMENT CHANGES | |
| Change Date: 15 July 2015 | |

| | General Information | |
|--|--|---|
| As affected | | |
| Section/Page No. | Description | |
| Section 01 01-02-001-1 01-02-002-1 | Index of Capacitors Type I from AVX/TPC Type II from AVX/TPC | Amended Extended Extended |
| Section 07 07-02-002 | Index of Inductors Types SESI and CMC from Microspire | Amended Extended |
| Section 10 10-08-007 | Index of Resistors Surface Mount, Type TNPS from Vishay Electronic (Selb) | Amended Extended |
| Section 12 12-01-002-3A-B 12-02-002-3A-B 12-05-003-2 12-06-03-1 | Index of Transistors Types NPN from STMicroelectronics Types PNP from STMicroelectronics Types BUY**SC*** from Infineon Type STRH40P10 from STMicroelectronics | Amended Revised Revised Extended Revised |
| Section 13 13-01-001-3 13-01-003-2 13-01-004-3 13-01-005-2 13-01-010-2 13-02-003-2 | Index of Wires and Cables Polyimide, Types 3901002**B from Axon' Cable PTFE/Polyimide, Types 3901013**B from Axon' Cable Polyimide, Types 3901019**B from Axon' Cable Crosslinked PTFE, Type Silver-Plated Copper from Axon' Cable Polyimide, Insulated, Shielded, Drain Wire,Types 3901021**B from Axon' Cable Symmertric, Quad, Spacewire from Axon' Cable | Amended Extended Extended Extended Extended Extended Extended |
|  | | <p align="center">Qualified Parts List</p> <p align="center">DOCUMENT CHANGES</p> <p align="center">Change Date: 15 June 2015</p> |

| | General Information |
|---|--|
| As affected | <i>This is the current QPL for May 2015</i> |
| Section/Page No. | Description |
| | |
|  | <p data-bbox="906 1883 1158 1912">Qualified Parts List</p> <p data-bbox="882 1939 1182 1968">DOCUMENT CHANGES</p> <p data-bbox="866 2031 1198 2060">Change Date: 15 May 2015</p> |

| | General Information | |
|---|--|-----------------------------------|
| As affected | <i>Eurofarad is now known as Exxelia Technologies</i> <i>RF2M Microwave s now known as API Technologies</i> | |
| Section/Page No. | Description | |
| Section 01 | Index of Capacitors | Amended |
| 01-01-005-1 | Type II, Types CNC31 to CHC34 from Exxelia Technologies | Amended |
| 01-01-007 | Type II, Types CNC53 to CNC56 from Exxelia Technologies | Amended |
| 01-02-001-2 | Type I, Types CEC2S to CEC14S from Exxelia Technologies | Amended |
| 01-02-002-2 | Type II, Types CNC23 to CNC14S from Exxelia Technologies | Amended |
| 01-02-004-2 | Type II, Types TTP , 0603,0805, 1206,1210,1812 from AVX N.I. | Added |
| 01-05-001-1 | Type HT86PS, High Voltage from Exxelia Technologies | Amended |
| 01-05-003-1 | Type PM94S from Exxelia Technologies | Amended |
| Section 04 | Index of Diodes | Amended |
| 04-13-003-1A-B | PIN and Varactors from API Technologies | Amended |
| Section 05 | Index of Filters | Amended |
| 05-01-001-A | Types SFC, SFL, SFP from Exxelia Technologies | Amended |
| Section 12 | Index of Transistors | Amended |
| 12-06-003-1 | Type STRH40P10 from STMicroelectronics | Extended |
|  | | |
| | | Qualified Parts List |
| | | DOCUMENT CHANGES |
| | | Change Date: 15 April 2015 |

| | General Information | |
|--|---|-----------------------------------|
| As affected | | |
| Section/Page No. | Description | |
| Section 01 01-01-007 | Index of Capacitors Type II, Types CNC53 to CNC56 from Eurofarad | Amended Extended |
| Section 04 04-01-003-2 04-13-003-1A-B | Index of Diodes Types 1N6640U and 1N6642U from STMicroelectronics PIN and Varactors from RF2M Microwave | Amended Extended Extended |
| Section 09 09-02-004-3 | Index of Relays Type M302 from Leach (Sarralbe) | Amended Extended |
| Section 13 13-01-004-1 | Index of Wires and Cables Polymide, Type SPC from WL Gore | Amended Extended |
|   | Qualified Parts List | |
| | DOCUMENT CHANGES | |
| | | Change Date: 15 March 2015 |


| | General Information | |
|---|--|--|
| As affected | | |
| Section/Page No. | Description | |
| Section 04 04-02-002-1 04-02-003-1 | Index of Diodes Type STPS20100 from STMicroelectronics Type BYW-81, BYV52, BYV54 from STMicroelectronics | Amended Revised Revised |
| Section 10 10-09-002 A to D 10-11-002 | Index of Resistors Type PHR;PFRR;PRAHR/CNWHR from Vishay S.A. Sfernice Single & Double Layer from Minco | Amended Extended Extended |
| Section 12 12-01-002-3A-B 12-02-002-3A-B | Index of Transistors Types NPN from STMicroelectronics Types PNP from STMicroelectronics | Amended Revised Revised |
|  | | |
| | | Qualified Parts List DOCUMENT CHANGES |
| | | Change Date: 15 February 2015 |



| | General Information | |
|-------------------------|---|----------|
| As affected | | |
| Section/Page No. | Description | |
| Section 01 | Index of Capacitors | Amended |
| 01-01-005 | Type II, High Capacitance from AVX (N.I.) | Extended |
| 01-01-006 | Type II, High Voltage from AVX (N.I.) | Extended |
| 01-02-004-1 | Type II, High Voltage from AVX (N.I.) | Extended |
| 01-11-001 | Type 101M, 201M, 400M and 401M from Cobham Microwave | Extended |
| Section 09 | Index of Relays | Amended |
| 09-01-004 | Type E215 from REL STPI | Extended |
| 09-02-004 | Type EL215 from REL STPI | Extended |
| 09-02-006 | Type D from LEACH | Deleted |
| Section 10 | Index of Resistors | Amended |
| 10-11-003 | Single & Double Layer from IRCA | Added |
| Section 13 | Index of Wires and Cables | Amended |
| 13-01-011-1 | Crosslinked, Modified ETFE, Type Silver-Plated Copper, Lightweight from Tyco Electronics UK | Extended |




Qualified Parts List
DOCUMENT CHANGES

Change Date: 15 January 2015

| | | General Information | |
|---|--|--|--|
| As affected | | | |
| Section/Page No. | Description | | |
| Section 04 04-02-002-1 04-02-003-1 | Index of Diodes Type STPS20100 from ST Microelectronics Type BYW-81, BYV52, BYV54 from ST Microelectronics | Amended Extended Extended | |
| Section 14 14-16-99-003 | Index of Miscellaneous Switches, Thermostatic, Bimetallic from Comepa | Amended Extended | |
|  | | Qualified Parts List DOCUMENT CHANGES | |
| | | Change Date: 15 December 2014 | |

| | General Information | |
|--|--|---|
| As affected | | |
| Section/Page No. | Description | |
| Section 01 01-02-001-2 01-02-002-2 | Index of Capacitors Type I, Types CEC2S to CEC14S from Eurofarad Type II, Types CNC2S to CNC14S from Eurofarad | Amended Extended Extended |
| Section 04 04-13-003-2A-B | Index of Diodes Multiplier and PIN, DH 2xx and DH 50xxx from Cobham Microwave | Amended Extended |
| Section 07 07-01-001 | Index of Inductors Type MSC1 10K and H01 from Microspire | Amended Extended |
| Section 10 10-08-007 10-09-002B | Index of Resistors Surface Mount, Type TNPS from Vishay Electronic (Selb) Type PHR; PFRR; PRAHR/CNWHR from Vihsay SA Sfernice | Amended Amended Amended |
| Section 12 12-05-003-1 | Index of Transistors Types STRH100N10, STRH400N6, SRH100N6 and STRH8N10 from STMicroelectronics | Amended Extended |
| Section 13 13-01-001-1 13-01-012-2 13-02-003-2 | Index of Wires and Cables Polyimide Types FA-3901, FA-3901-2 from Draka Fileca Fluoropolymer , Lightweight, Based on Type CSWL from W.L. Gore Symmetric, Quad, Spacewire from W.L. Gore | Amended Extended Extended Extended |
|   | Qualified Parts List | |
| | DOCUMENT CHANGES | |
| Change Date: 15 November 2014 | | |

| | General Information | |
|---|--|--|
| As affected | All validity dates of each Certificate have been removed as per October 2014. For more information please see ESCC Executive Public Notice (EEP-2014-2 issue 1) https://escies.org/webdocument/showArticle?id=933&groupid=6 | |
| Section/Page No. | Description | |
| Section 03 03-01-001-1 03-01-002 | Index of Crystals TO-5 Can from Rakon (Fr) TO-8 Can from Rakon (Fr) | Amended Extended Extended |
| Section 10 10-02-001 | Index of Resistors Type RNC 90 from Vishay S.A. Sfernice | Amended Deleted |
| Section 13 13-01-001-1 13-01-004-2 13-01-008 | Index of Wires and Cables Polyimide, Types FA-3901-1, FA 3901-2 from Draka Fileca Polyimide, Types SPL from WL Gore PTFE, Polyimide / PFA Insulated, Type SPP from WL Gore | Amended Amended Extended Extended |
| Section 14 14-30-10-002-2 14-30-10-004 | Index of Miscellaneous Coaxial Loads, 0 to 22 GHz from Radiall Attenuators, Type R413 from Radiall | Amended Extended Extended |
|  | Qualified Parts List | |
| | DOCUMENT CHANGES | |
| | Change Date: 15 October 2014 | |


| | General Information | |
|---|--|---------------------------------|
| As affected | | |
| Section/Page No. | Description | |
| Section 02 02-05-004-1 | Index of Connectors 8MCG, Rectangular from Souriau | Amended Extended |
| Section 04 04-02-001-4 | Index of Diodes Types 1N5819U and 1N5822U from STMicroelectronics | Amended Extended |
| Section 05 05-01-001-A-B | Index of Filters Types SFC, SFL, and SFP from Eurofarad | Amended Extended |
| Section 10 10-07-001 | Index of Resistors Types SM*-PW and SM*-PT from Isabellenhütte | Amended Extended |
| Section 12 12-01-002-3A-B 12-02-002-3A-B | Index of Transistors Types NPN from STMicroelectronics Types PNP from STMicroelectronics | Amended Extended Extended |
| Section 13 13-01-010-3 | Index of Wires and Cables Polyimide, Insulated, Shielded, Drain Wire, Type 3901021 from Leoni | Amended Extended |
|  | Qualified Parts List | |
| | DOCUMENT CHANGES | |
| | Change Date: 15 September 2014 | |

TABLE OF CONTENTS

| <u>SECTION</u> | <u>PAGE</u> |
|--------------------------------------|-------------|
| Document Changes | - |
| Table of Contents | 1 |
| 1 Foreword | 2 |
| 2 Procurors' Responsibility | 2 |
| 3 Use of Tables | 2 |
| 4 Revision Procedure | 2 |
| 5 Table of Qualified Component Types | 3 |
| Appendices | |
| 'A' Qualified Components List | 4 |

1. FOREWORD

This document contains a list of components that have been qualified to the rules of the ESCC System and are intended for use in ESA and other spacecraft and associated equipment in accordance with the requirements of the ECSS Standard ESCC-Q-ST-60.

It is permitted to advertise the ESCC qualification status of a product provided such publicity or advertisement does not state or imply that the product is the only qualified or capability approved one of that particular type, range or family.

2. PROCURORS' RESPONSIBILITY

When procuring ESCC qualified or capability approved components, the procurer is responsible for ensuring that the qualification or capability approval status is valid and that delivered components fulfill the specified requirements of the applicable ESCC specifications. The procurer is advised to utilise the ESCC non-conformance system in the event that a qualified or capability approved manufacturer delivers non-conforming components.

3. USE OF TABLES

3.1 Publication

The individual entries are published in sections within this document and are presented by manufacturer on the web. Please refer to our escies.org website.

3.2 Type Designation

The referenced type (style) designations are derived from industrial standards (i.e., JEDEC PRO-ELECTRON, MIL, IEC and CECC). The purpose is to identify the similarity of a listed qualified component to a standard type designation.

3.3 Components Characteristics

The electrical characteristics are listed for guidance only and, unless otherwise stated, are specified at +25°C. The precise characteristics of the qualified component are defined in the referenced ESCC specification.

3.4 Manufacturer

Plant locations are indicated in the individual listing; contact information is given in full on the appropriate web pages. Please refer to our escies.org website.

4. REVISION PROCEDURE

Amendments to earlier issues of the QPL implemented herein are indicated by the date on the front page and by the content of the "Document Changes" pages. The latter provides the changes over a one year period. The same issue date appears on the table at the start of each Section on the Appendix irrespective of whether changes have been made in a particular section. This indicates the information has been reviewed and is current. Finally, it should be noted that the ESA/SCC System is superseded by the ESCC (European Space Components Coordination) System.



5. TABLE OF QUALIFIED COMPONENTS

Components qualified to the ESCC System are grouped by component type designations. Individual components are listed within the relevant sections as indicated in Table 5.1

TABLE 5.1


| Section | Component Types |
|---------|------------------|
| 01 | Capacitors |
| 02 | Connectors |
| 03 | Crystals |
| 04 | Diodes |
| 05 | Filters |
| 06 | Fuses |
| 07 | Inductors |
| 08 | Microcircuits |
| 09 | Relays |
| 10 | Resistors |
| 11 | Thermistors |
| 12 | Transistors |
| 13 | Wires and Cables |
| 14 | Miscellaneous |
| 18 | Optoelectronics |


APPENDIX A


Qualified Components List


Section 01**Component Type: Capacitors**


| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|--------------|-------------|-------|---|----------------------|
| 01-01 | | | Ceramic, Fixed | |
| | 01-01-005 | 231 J | Type II, High Capacitance | AVX (N.I.) |
| | 01-01-005-1 | 315 A | Type II, Types CNC 31 to CNC 34 | Exxelia Technologies |
| | 01-01-006 | 262 F | Type II, High Voltage | AVX (N.I.) |
| | 01-01-007 | 306 B | Type II, Types CNC 53 to CNC 56 | Exxelia Technologies |
| 01-02 | | | Ceramic, Fixed, Chip | |
| | 01-02-001-1 | 109 M | Type I | AVX/TPC |
| | 01-02-001-2 | 323 A | Type I, Types CEC2S to CEC14S | Exxelia Technologies |
| | 01-02-002-1 | 110 M | Type II | AVX/TPC |
| | 01-02-002-2 | 324 A | Type II, Types CNC2S to CNC14S | Exxelia Technologies |
| | 01-02-004-1 | 264 F | Type II, High Voltage | AVX (N.I.) |
| | 01-02-004-3 | 331 | Type II, Types TTP 0603, 0805, 1206, 1210, 1812 | AVX (N.I.) |
| 01-03 | | | Tantalum, (Solid), Fixed, Electrolytic | |
| | 01-03-004 | 196 F | Type TAJ | AVX (CZ) |
| | 01-03-005 | 327 | Low ESR, Type TES | AVX (CZ) |
| 01-05 | | | Fixed, Film | |
| | 01-05-001-1 | 251 G | Type HT86PS, High Voltage | Exxelia Technologies |
| | 01-05-003-1 | 270 E | Type PM94S | Exxelia Technologies |
| 01-11 | | | Semiconductor | |
| | 01-11-001 | 286 C | Type 101M, 201M, 400M and 401M | Cobham Microwave |


| | | | | |
|---|--|---|-----------------------------------|------------------------------------|
| Types covered by similarity: ±20% tolerance | | Remarks: Capacitors no longer use a varnish finish. | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3001 Detail ESCC 3001/030 | AVX Limited Coleraine Northern Ireland | Qualification | UK Space Agency | Jul 1996 |
| <p>Characteristics: E12 series</p> <p>Qualified Range:</p> <p>Variants 01 to 74 capacitance range for 50V, 100V and 200V, as per Detail Specification Variants 01 to 52, and 59 to 60, for 500V are qualified ±10% tolerance</p> <p>Operating Temperature Range (°C): -55 to +125</p> | | | | |
|  | <p>CAPACITORS, CERAMIC, TYPE II, HIGH CAPACITANCE, BASED ON CASE STYLES BR, CV, AND CH</p> | | <p>Certificate 231 J</p> | <p>Page 01-01 005</p> |

| | | | | |
|---|--|--------------------|--------------------------|----------------------------|
| Types covered by similarity: E6 ±20% tolerance | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3001 Detail ESCC 3001/037 | Exxelia Technologies Chanteloup en Brie France | Qualification | CNES | Nov 2011 |
| Characteristics: E12 ±10% tolerance Qualified Range: Variants 01 to 16. 16V : 2.2 to 68 µF 25V: 1.2 to 39 µF DIL format with equal number of leads per side Lead material : type A with type 10 finish (electro-deposited 98% Ag min.) Operating Temperature Range (°C): -55 to +125 | | | | |
|  | CAPACITORS, CERAMIC, TYPE II, MULTIPLE LAYERS, BASED ON TYPES CNC 31 to 34, NE, PE AND PLE | | Certificate 315 A | Page 01-01 005-1 |

| | | | | |
|---|---|--------------------|-----------------------------------|------------------------------------|
| Types covered by similarity: ±20% tolerance | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3001 Detail ESCC 3001/034 | AVX Limited Coleraine Northern Ireland | Qualification | UK Space Agency | Sep 2000 |
| <p>Characteristics: E12 series</p> <p>Qualified Range:</p> <p>Variants 01 to 22 are qualified ±10% tolerance</p> <p>Operating Temperature Range (°C): -55 to +125</p> | | | | |
|  | <p>CAPACITORS, CERAMIC, TYPE II, HIGH VOLTAGE, 1.0 TO 5.0 KV, BASED ON CASE STYLES VR, CV, AND CH</p> | | <p>Certificate 262 F</p> | <p>Page 01-01 006</p> |

| | | | | |
|--|--|--------------------|--------------------------|----------------------------|
| Types covered by similarity: E6: ±20% tolerance | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3001 Detail ESCC 3001/038 | Exxelia Technologies Chanteloup en Brie France | Qualification | CNES | Mar 2011 |
| Characteristics: Qualified Range: Variants 01 to 04, 08 to 11, 15 to 18 and 22 to 25 are qualified All values 50V to 500V E12: ±10% tolerance Operating Temperature Range (°C): -55 to +125 | | | | |
|  | CAPACITORS, CERAMIC, TYPE II, 50V TO 500V, BASED ON TYPES CNC53 TO CNC56 | | Certificate 306 B | Page 01-01 007 |

| Types covered by similarity: Tolerance (\pm): 0.5pF; 2, 5, 20% | | | | | Remarks: Variant 01 removed | | | |
|---|-------|--------------|--|-------------------------------------|-----------------------------|--------------------------|------------------------|----------------------------|
| Procurement Specifications | | | | Manufacturer | | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3009 Detail ESCC 3009/003 3009/004 3009/005 3009/006 3009/022 | | | | AVX/TPC St Apollinaire France | | Qualification | CNES | Feb 1983 |
| Characteristics: Operating Temp. Range ($^{\circ}$ C), -55 to +125 Variants 03 and 06 are qualified Values covered by ESCC Specifications defined below. | | | | | | | | |
| Style | Model | Detail Spec. | Variants | Capacitance Range (pF) | Rated Volt. (V) | Tolerance (\pm %) | TC (ppm/ $^{\circ}$ C) | |
| 0805 | A_12C | 3009/003 | 03, 06 | 4.7 to 9.1 10 to 1 500 | 50, 100 50, 100 | 0.5pF 1, 2, 5, 10 | \pm 30 | |
| 1206 | A_20C | 3009/022 | 03, 06 | 10 to 3 900 | 50, 100 | 1, 2, 5, 10 | \pm 30 | |
| 1210 | A_13C | 3009/004 | 03, 06 | 22 to 6 800 8 200 to 10 000 | 50, 100 50 | 1, 2, 5, 10 | \pm 30 | |
| 1812 | A_14C | 3009/005 | 03, 06 | 100 to 15 000 | 50, 100 | 1, 2, 5, 10 | \pm 30 | |
| 2220 | A_15C | 3009/006 | 03, 06 | 470 to 33 000 | 50, 100 | 1, 2, 5, 10 | \pm 30 | |
|  | | | CAPACITORS, CERAMIC, FIXED, CHIP, TYPE I | | | Certificate 109 M | | Page 01-02 001-1 |

| | | | | |
|---|--|----------------------|-----------------------|----------------------------|
| Types covered by similarity: Tolerance (\pm): <10pF; 0.25– 0.5-1pF; \geq 10pF; 1, 2, 5, 10% | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3009 Detail ESCC 3009/003 3009/004 3009/005 3009/006 3009/022 3009/037 | Exxelia Technologies Chanteloup en Brie France | Qualification | CNES | Oct 2012 |
| Characteristics: Variant 06 is qualified See Table on next page Operating Temp. Range ($^{\circ}$ C), -55 to +125 | | | | |
|  | CAPACITORS, CERAMIC, FIXED, CHIP, TYPE I | Certificate 323 A | | Page 01-02 001-2A |

Characteristics:


| Style | Model | Detail Spec. | Variants | Capacitance Range (pF) | Rated Volt. (V) | Tol. (±%) | | |
|-------|--------|--------------|----------|------------------------|-----------------|---------------------------|----------------------|--|
| 0805 | CEC2S | 3009/003 | 06 | 10 to 2 700 | 16 | <10pF 0.25—0.5 -1 (pF) | | |
| | | | | 10 to 2 200 | 25 | | | |
| | | | | 1 to 1 800 | 50 | | | |
| | | | | 1 to 1 200 | 100 | | | |
| 1210 | CEC4S | 3009/004 | 06 | 10 to 15 000 | 16 | | ≥10pF 1, 2, 5, 10 | |
| | | | | 10 to 13 000 | 25 | | | |
| | | | | 10 to 12 000 | 50 | | | |
| | | | | 10 To 6 800 | 100 | | | |
| 1812 | CEC6S | 3009/005 | 06 | 100 to 33 000 | 16 | | | |
| | | | | 100 to 30 000 | 25 | | | |
| | | | | 100 to 22 000 | 50 | | | |
| | | | | 100 to 12 000 | 100 | | | |
| 2220 | CEC7S | 3009/006 | 06 | 470 to 68 000 | 16 | | | |
| | | | | 470 to 56 000 | 25 | | | |
| | | | | 470 to 47 000 | 50 | | | |
| | | | | 470 to 27 000 | 100 | | | |
| 1206 | CEC12S | 3009/022 | 06 | 10 to 6 800 | 16 | | | |
| | | | | 10 to 6 200 | 25 | | | |
| | | | | 1 to 5 600 | 50 | | | |
| | | | | 1 to 3 900 | 100 | | | |
| 0603 | CEC14S | 3009/037 | 06 | 10 to 1 000 | 16 | | | |
| | | | | 10 to 680 | 25 | | | |
| | | | | 1 to 560 | 50 | | | |
| | | | | 1 to 330 | 100 | | | |



CAPACITORS,
CERAMIC, FIXED,
CHIP, TYPE I

Certificate
323 A

Page
01-02
001-2B

| | | | | |
|--|---|-----------------------------|-----------------------------|----------------------------|
| Types covered by similarity: Tolerance ($\pm\%$): 10, 20% | | Remarks: Variant 01 deleted | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3009 Detail ESCC 3009/008 3009/009 3009/010 3009/011 3009/023 | AVX/TPC St Apollinaire France | Qualification | CNES | Feb 1983 |
| Characteristics: See Table on next page Operating Temperature Range ($^{\circ}\text{C}$), -55 to +125 | | | | |
|  The logo for ESCC QPL (European Space Components Coordination) features a stylized globe on the left, followed by the text 'ESCC' in large blue letters, 'European Space Components Coordination' in smaller text below it, and 'QPL' in large blue letters at the bottom. | CAPACITORS, CERAMIC, FIXED, CHIP, TYPE II | Certificate 110 M | Page 01-02 002-1A | |


| Characteristics: | Style | Model | Detail Spec. | Variants | Capacitance Range (pF) | | | Rated Volt. (V) | Tol. (±%) |
|------------------|-------|----------|--------------|----------|------------------------|-----------|---------|-----------------|-----------|
| | 0805 | A_12G | 3009/008 | 03, 06 | 10 000 | to | 47 000 | 25 | 5, 10, 20 |
| | | | | | 3 900 | to | 27 000 | 50 | 5, 10, 20 |
| | | | | | 820 | to | 10 000 | 100 | 5, 10, 20 |
| | 0805 | A612Z | 3009/008 | 07 | 27 000 | to | 100 000 | 25 | 5, 10, 20 |
| | | | | | 27 000 | to | 68 000 | 50 | |
| | | | | | 10 000 | to | 47 000 | 100 | |
| | 1210 | A_13G | 3009/009 | 03, 06 | 47 000 | to | 220 000 | 25 | 5, 10, 20 |
| | | | | | 33 000 | to | 120 000 | 50 | 5, 10, 20 |
| | | | | | 3 900 | to | 47 000 | 100 | 5, 10, 20 |
| 1210 | A613Z | 3009/009 | 07 | 100 000 | to | 470 000 | 25 | 5, 10, 20 | |
| | | | | 100 000 | to | 330 000 | 50 | | |
| | | | | 47 000 | to | 220 000 | 100 | | |
| 1812 | A_14G | 3009/010 | 03, 06 | 82 000 | to | 470 000 | 25 | 5, 10, 20 | |
| | | | | 56 000 | to | 270 000 | 50 | 5, 10, 20 | |
| | | | | 6 800 | to | 82 000 | 100 | 5, 10, 20 | |
| 1812 | A614Z | 3009/010 | 07 | 220 000 | to | 1 000 000 | 25 | 5, 10, 20 | |
| | | | | 220 000 | to | 680 000 | 50 | | |
| | | | | 82 000 | | 470 000 | 100 | | |
| 2220 | A_15G | 3009/011 | 03, 06 | 180 000 | to | 1 000 000 | 25 | 5, 10, 20 | |
| | | | | 100 000 | to | 680 000 | 50 | 5, 10, 20 | |
| | | | | 18 000 | to | 180 000 | 100 | 5, 10, 20 | |
| 2220 | A615Z | 3009/011 | 07 | 470 000 | to | 2 200 000 | 25 | 5, 10, 20 | |
| | | | | 470 000 | to | 1 500 000 | 50 | | |
| | | | | 180 000 | | 1 000 000 | 100 | | |
| 1206 | A_20G | 3009/023 | 03, 06 | 27 000 | to | 100 000 | 25 | 5, 10, 20 | |
| | | | | 12 000 | to | 68 000 | 50 | 5, 10, 20 | |
| | | | | 2 200 | to | 22 000 | 100 | 5, 10, 20 | |
| 1206 | A620Z | 3009/023 | 07 | 47 000 | to | 220 000 | 25 | 5, 10, 20 | |
| | | | | 47 000 | to | 150 000 | 50 | | |
| | | | | 27000 | to | 100 000 | 100 | | |



CAPACITORS,
 CERAMIC, FIXED,
 CHIP, TYPE II

Certificate
 110 M

Page
 01-02
 002-1B

| Types covered by similarity: Tolerance (±%): 10, 20% | | | | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|-------|----------|---|--|------------------------|--------------------|----------------------|-----------------------|----------------------------|------------------|-------|-------|--------------|----------|------------------------|--|--|-----------------|-----------|------------------------------|------|-------|----------|----|-------|----|---------|----|-----------|-------|----|---------|----|-----|----|--------|----|----|----|--------|-----|--|--|--|--|----|-------|----|---------|----|-------|----|---------|----|-----|----|---------|----|----|----|--------|-----|
| Procurement Specifications | | | | Manufacturer | | Nature of Approval | | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 3009 | | | | Exxelia Technologies Chanteloup en Brie France | | Qualification | | CNES | Oct 2012 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Detail ESCC | | 3009/008 | 3009/009 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 3009/010 | 3009/011 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 3009/023 | 3009/038 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 3009/039 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th colspan="1">Characteristics:</th> <th colspan="1">Style</th> <th colspan="1">Model</th> <th colspan="1">Detail Spec.</th> <th colspan="1">Variants</th> <th colspan="3">Capacitance Range (pF)</th> <th colspan="1">Rated Volt. (V)</th> <th colspan="1">Tol. (±%)</th> </tr> </thead> <tbody> <tr> <td colspan="1" rowspan="8">Table continues on next page</td> <td colspan="1" rowspan="4">0805</td> <td colspan="1" rowspan="4">CNC2S</td> <td colspan="1" rowspan="4">3009/008</td> <td colspan="1" rowspan="4">06</td> <td colspan="1">6 800</td> <td colspan="1">to</td> <td colspan="1">150 000</td> <td colspan="1">16</td> <td colspan="1" rowspan="4">5, 10, 20</td> </tr> <tr> <td colspan="1">6 800</td> <td colspan="1">to</td> <td colspan="1">100 000</td> <td colspan="1">25</td> </tr> <tr> <td colspan="1">100</td> <td colspan="1">to</td> <td colspan="1">47 000</td> <td colspan="1">50</td> </tr> <tr> <td colspan="1">68</td> <td colspan="1">to</td> <td colspan="1">10 000</td> <td colspan="1">100</td> </tr> <tr> <td colspan="1" rowspan="4"></td> <td colspan="1" rowspan="4"></td> <td colspan="1" rowspan="4"></td> <td colspan="1" rowspan="4"></td> <td colspan="1" rowspan="4">07</td> <td colspan="1">6 800</td> <td colspan="1">to</td> <td colspan="1">220 000</td> <td colspan="1">16</td> </tr> <tr> <td colspan="1">6 800</td> <td colspan="1">to</td> <td colspan="1">150 000</td> <td colspan="1">25</td> </tr> <tr> <td colspan="1">100</td> <td colspan="1">to</td> <td colspan="1">100 000</td> <td colspan="1">50</td> </tr> <tr> <td colspan="1">68</td> <td colspan="1">to</td> <td colspan="1">47 000</td> <td colspan="1">100</td> </tr> </tbody> </table> | | | | | | | | | | Characteristics: | Style | Model | Detail Spec. | Variants | Capacitance Range (pF) | | | Rated Volt. (V) | Tol. (±%) | Table continues on next page | 0805 | CNC2S | 3009/008 | 06 | 6 800 | to | 150 000 | 16 | 5, 10, 20 | 6 800 | to | 100 000 | 25 | 100 | to | 47 000 | 50 | 68 | to | 10 000 | 100 | | | | | 07 | 6 800 | to | 220 000 | 16 | 6 800 | to | 150 000 | 25 | 100 | to | 100 000 | 50 | 68 | to | 47 000 | 100 |
| Characteristics: | Style | Model | Detail Spec. | Variants | Capacitance Range (pF) | | | Rated Volt. (V) | Tol. (±%) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Table continues on next page | 0805 | CNC2S | 3009/008 | 06 | 6 800 | to | 150 000 | 16 | 5, 10, 20 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | 6 800 | to | 100 000 | 25 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | 100 | to | 47 000 | 50 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | 68 | to | 10 000 | 100 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | 07 | 6 800 | to | 220 000 | 16 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | 6 800 | to | 150 000 | 25 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | 100 | to | 100 000 | 50 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | 68 | to | 47 000 | 100 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Operating Temperature Range (°C), -55 to +125 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | | CAPACITORS, CERAMIC, FIXED, CHIP, TYPE II | | | | Certificate 324 A | | Page 01-02 002-2A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| Characteristics: | Style | Model | Detail Spec. | Variants | Capacitance Range (pF) | | | Rated Volt. (V) | Tol. (±%) |
|------------------|-------|----------|--------------|----------|--------------------------------|-----------------------------|--|--|-----------------------|
| | 0805 | | CNC2 04S | 3009/039 | 02 | 6 800 6 800 100 68 | to to to to | 150 000 100 000 47 000 10 000 | 16 25 50 100 |
| | | | | 14 | 6 800 6 800 100 68 | to to to to | 390 000 150 000 100 000 47 000 | 16 25 50 100 | 5, 10, 20 |
| 1210 | | CNC4S | 3009/009 | 06 | 33 000 33 000 | to to | 560 000 330 000 | 16 25 | 5, 10, 20 |
| | | CNC4 04S | 3009/039 | 04 | 2 200 2 200 | to to | 220 000 56 000 | 50 100 | |
| | | CNC4S | 3009/009 | 07 | 33 000 33 000 | to to | 820 000 560 000 | 16 25 | 5, 10, 20 |
| | | CNC4 04S | 3009/039 | 16 | 2 200 2 200 | to to | 390 000 220 000 | 50 100 | |
| 1812 | | CNC6S | 3009/010 | 06 | 100 000 100 000 | to to | 1 200 000 680 000 | 16 25 | 5, 10, 20 |
| | | CNC6 04S | 3009/039 | 05 | 3 900 3 900 | to to | 470 000 120 000 | 50 100 | |
| | | CNC6S | 3009/010 | 07 | 100 000 100 000 | to to | 1 800 000 1 200 000 | 16 25 | 5, 10, 20 |
| | | CNC6 04S | 3009/039 | 17 | 3 900 3 900 | to to | 820 000 470 000 | 50 100 | |
| 2220 | | CNC7S | 3009/011 | 06 | 150 000 150 22 000 | to to to | 2 700 000 1 500 000 1 000 000 | 16 25 50 | 5, 10, 20 |
| | | CNC7 04S | 3009/039 | 06 | 22 000 22 000 | to to | 270 000 1 000 000 | 100 50 | |
| | | CNC7S | 3009/011 | 07 | 150 000 150 000 | to to | 3 900 000 2 200 000 | 16 25 | 5, 10, 20 |
| | | CNC7 04S | 3009/039 | 18 | 22 000 22 000 | to to | 1 800 000 1 000 000 | 50 100 | |
| 1206 | | CNC12S | 3009/023 | 06 | 10 000 10 000 470 470 | to to to to | 270 000 180 000 82 000 27 000 | 16 25 50 100 | 5, 10, 20 |
| | | | | 07 | 10 000 10 000 470 470 | to to to to | 390 000 270 000 180 000 120 000 | 16 25 50 100 | 5, 10, 20 |



CAPACITORS,
CERAMIC, FIXED,
CHIP, TYPE II

Certificate
324 A

Page
01-02
002-2B

Characteristics:


| Style | Model | Detail Spec. | Variants | Capacitance Range (pF) | | | Rated Volt. (V) | Tol. (±%) |
|-------|-----------|--------------|----------|------------------------|----|-----------|-----------------|-----------|
| 1206 | CNC12 04S | 3009/039 | 03 | 10 000 | to | 270 000 | 16 | 5, 10, 20 |
| | | | | 10 000 | to | 180 000 | 25 | |
| | | | | 470 | to | 82 000 | 50 | |
| | | | | 470 | to | 27 000 | 100 | |
| | | | 15 | 10 000 | to | 1 000 000 | 16 | 5, 10, 20 |
| | | | | 10 000 | to | 270 000 | 25 | |
| | | | | 470 | to | 180 000 | 50 | |
| | | | | 470 | to | 120 000 | 100 | |
| 0603 | CNC14S | 3009/038 | 06 | 390 | to | 33 000 | 16 | 5, 10, 20 |
| | | | | 390 | to | 22 000 | 25 | |
| | | | | 10 | to | 10 000 | 50 | |
| | | | | 10 | to | 2 700 | 100 | |
| | | | 07 | 390 | to | 39 000 | 16 | 5, 10, 20 |
| | | | | 390 | to | 33 000 | 25 | |
| | | | | 10 | to | 22 000 | 50 | |
| | | | | 10 | to | 12 000 | 100 | |
| 0603 | CNC14 04S | 3009/039 | 01 | 390 | to | 33 000 | 16 | 5, 10, 20 |
| | | | | 390 | to | 22 000 | 25 | |
| | | | | 10 | to | 10 000 | 50 | |
| | | | | 10 | to | 2 700 | 100 | |
| | | | 13 | 390 | to | 100 000 | 16 | 5, 10, 20 |
| | | | | 390 | to | 33 000 | 25 | |
| | | | | 10 | to | 22 000 | 50 | |
| | | | | 10 | to | 12 000 | 100 | |





CAPACITORS,
 CERAMIC, FIXED,
 CHIP, TYPE II


Certificate
 324 A


Page
 01-02
 002-2C


| Types covered by similarity: ±20% tolerance | | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--------------------|--|-----------|---|-----------------------|--------------------------------------|-------|--------------------|------------------------|-----------|------|-----|-----------------|----|-----|----------------|----|-----|--------------|----|------|-----|------------------|----|-----|----------------|----|-----|--------------|----|
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 3009 Detail ESCC 3009/034 | | AVX Limited Coleraine Northern Ireland | | Qualification | UK Space Agency | Feb 2001 | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Characteristics: E12 series</p> <p>Qualified Range: Variants 01 to 12 are qualified</p> <p>Terminations: Variants 01 to 12: metallised pads</p> <p>Operating Temperature Range (°C):-55 to +125</p> | | | | <table border="1"> <thead> <tr> <th>Style</th> <th>Rated Voltage (kV)</th> <th>Capacitance Range (pF)</th> <th>Tol. (±%)</th> </tr> </thead> <tbody> <tr> <td rowspan="3">1812</td> <td>1.0</td> <td>3 900 to 22 000</td> <td>10</td> </tr> <tr> <td>2.0</td> <td>1 500 to 1 800</td> <td>10</td> </tr> <tr> <td>3.0</td> <td>820 to 1 000</td> <td>10</td> </tr> <tr> <td rowspan="3">1825</td> <td>1.0</td> <td>27 000 to 56 000</td> <td>10</td> </tr> <tr> <td>2.0</td> <td>2 200 to 6 800</td> <td>10</td> </tr> <tr> <td>3.0</td> <td>820 to 2 700</td> <td>10</td> </tr> </tbody> </table> | | | Style | Rated Voltage (kV) | Capacitance Range (pF) | Tol. (±%) | 1812 | 1.0 | 3 900 to 22 000 | 10 | 2.0 | 1 500 to 1 800 | 10 | 3.0 | 820 to 1 000 | 10 | 1825 | 1.0 | 27 000 to 56 000 | 10 | 2.0 | 2 200 to 6 800 | 10 | 3.0 | 820 to 2 700 | 10 |
| Style | Rated Voltage (kV) | Capacitance Range (pF) | Tol. (±%) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1812 | 1.0 | 3 900 to 22 000 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 2.0 | 1 500 to 1 800 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 3.0 | 820 to 1 000 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1825 | 1.0 | 27 000 to 56 000 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 2.0 | 2 200 to 6 800 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 3.0 | 820 to 2 700 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | <p>CAPACITORS, FIXED, CHIP, CERAMIC, TYPE II, HIGH VOLTAGE, BASED ON 1812 and 1825</p> | | <p>Certificate 264 F</p> | | <p>Page 01-02 004-1</p> | | | | | | | | | | | | | | | | | | | | | | | | |


| | | | | |
|--|---|--------------------|---------------------------------|--------------------------------------|
| Types covered by similarity: Capacitance tolerances 5%, 10%, 20% | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3009 Detail ESCC 3009/041 | AVX Limited Coleraine Northern Ireland | Qualification | ESA | April 2015 |
| <p>Characteristics: E12 value series</p> <p>Qualified Range: Variant 02 0603, Cn as in Detail specification, 5%, 10%, 20% tolerances, 16V, 25V, 50V, 100V rated Variant 03 0805, Cn as in Detail specification, 5%, 10%, 20% tolerances, 16V, 25V, 50V, 100V rated Variant 04 1206, Cn as in Detail specification, 5%, 10%, 20% tolerances, 16V, 25V, 50V, 100V rated Variant 05 1210, Cn as in Detail specification, 5%, 10%, 20% tolerances, 16V, 25V, 50V, 100V rated Variant 06 1812, Cn as in Detail specification, 5%, 10%, 20% tolerances, 16V, 25V, 50V, 100V rated</p> <p>Terminations: Cu and Ag-loaded epoxy + Ni barrier+ Sn/Pb plating finish (10% Pb minimum) Operating Temperature Range (°C):-55 to +125</p> | | | | |
|  | <p>CAPACITORS, FIXED, CHIP, BASE METAL ELECTRODE, CERAMIC DIELECTRIC TYPE II, BASED ON TYPE TTP, 0603, 0805, 1206, 1210, 1812</p> | | <p>Certificate 331</p> | <p>Page 01-02 004-2</p> |

| | | | | |
|---|---|--------------------------|-----------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3012 Detail ESCC 3012/001 | AVX Czech Republic sro Tantalum Division Lanskrout Czech Republic | Qualification | ESA | Jun 1993 |
| Characteristics: Variants 01 to 07 and 11 to 17 are qualified Termination finish: <ul style="list-style-type: none"> A and B case sizes are available in NILO only, e.g., <ul style="list-style-type: none"> Variant 01 (A case), Variant 02 (B case) C, D, E case sizes are available as Copper only, e.g., <ul style="list-style-type: none"> Variant 13 (C case), Variant 14 (D case), Variant 17 (E case) | | | | |
|  | CAPACITORS, LEADLESS SURFACE MOUNTED, TANTALUM, SOLID ELECTROLYTE, TYPE TAJ | Certificate 196 F | | Page 01-03 004 |

| Types covered by similarity: All CV product combinations allowed in 3012/004 are qualified | | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---------------------|--|------|--------------------|------------------------|----------------------------|------------------------------------|---------------------|--|--|--|--|--|--|--|------|-----|-----|-----|-----|-----|-----|-----|---|--|--|--|--|--|--------|--|--------|-----|--|--|--|--|--------|--|--------|--------|-----|--|--|--|--------|--|--------|-------|-------|----|--|--------|--|--|--------|-------|-------|--|----|-------|--|--|-------|-------|--|-------|--|----|--|-------|--|--|-------|------|------|--|----|-------|--|--|-------|------|------|--|--|-----|--|-------|--|------|------|--|--|--|-----|-------|------|--|------|--|--|--|--|-----|--|------|------|--|--|--|--|--|-----|------|------|--|--|--|--|--|--|-----|------|--|--|--|--|--|--|--|
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 3012 Detail ESCC 3012/004 | | AVX Czech Republic sro Tantalum Division Lanskrout Czech Republic | | Qualification | ESA | Oct 2013 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Variants 01 to 05. Case styles A (1206), B (1210), C (2312), D (2917), E (2917) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th rowspan="2">Capacitance C_n (μF)</th> <th colspan="8">Rated Voltage U_R</th> </tr> <tr> <th>6.3V</th> <th>10V</th> <th>12V</th> <th>16V</th> <th>20V</th> <th>25V</th> <th>35V</th> <th>50V</th> </tr> </thead> <tbody> <tr> <td>1</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>A 3000</td> <td></td> <td>B 2000</td> </tr> <tr> <td>3.3</td> <td></td> <td></td> <td></td> <td></td> <td>A 2500</td> <td></td> <td>B 1000</td> <td>C 1000</td> </tr> <tr> <td>4.7</td> <td></td> <td></td> <td></td> <td>A 2000</td> <td></td> <td>B 1000</td> <td>C 600</td> <td>D 200</td> </tr> <tr> <td>10</td> <td></td> <td>A 1800</td> <td></td> <td></td> <td>B 1000</td> <td>C 600</td> <td>D 120</td> <td></td> </tr> <tr> <td>22</td> <td>A 900</td> <td></td> <td></td> <td>B 600</td> <td>C 400</td> <td></td> <td>D 100</td> <td></td> </tr> <tr> <td>33</td> <td></td> <td>B 650</td> <td></td> <td></td> <td>C 300</td> <td>D 65</td> <td>E 65</td> <td></td> </tr> <tr> <td>47</td> <td>B 500</td> <td></td> <td></td> <td>C 350</td> <td>D 55</td> <td>E 65</td> <td></td> <td></td> </tr> <tr> <td>100</td> <td></td> <td>C 200</td> <td></td> <td>D 55</td> <td>E 45</td> <td></td> <td></td> <td></td> </tr> <tr> <td>150</td> <td>C 300</td> <td>D 45</td> <td></td> <td>E 40</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>220</td> <td></td> <td>D 35</td> <td>E 35</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>330</td> <td>D 35</td> <td>E 35</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>470</td> <td>E 30</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table> | | | | | | | Capacitance C_n (μ F) | Rated Voltage U_R | | | | | | | | 6.3V | 10V | 12V | 16V | 20V | 25V | 35V | 50V | 1 | | | | | | A 3000 | | B 2000 | 3.3 | | | | | A 2500 | | B 1000 | C 1000 | 4.7 | | | | A 2000 | | B 1000 | C 600 | D 200 | 10 | | A 1800 | | | B 1000 | C 600 | D 120 | | 22 | A 900 | | | B 600 | C 400 | | D 100 | | 33 | | B 650 | | | C 300 | D 65 | E 65 | | 47 | B 500 | | | C 350 | D 55 | E 65 | | | 100 | | C 200 | | D 55 | E 45 | | | | 150 | C 300 | D 45 | | E 40 | | | | | 220 | | D 35 | E 35 | | | | | | 330 | D 35 | E 35 | | | | | | | 470 | E 30 | | | | | | | |
| Capacitance C_n (μ F) | Rated Voltage U_R | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 6.3V | 10V | 12V | 16V | 20V | 25V | 35V | 50V | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | | | | | | A 3000 | | B 2000 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3.3 | | | | | A 2500 | | B 1000 | C 1000 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.7 | | | | A 2000 | | B 1000 | C 600 | D 200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10 | | A 1800 | | | B 1000 | C 600 | D 120 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 22 | A 900 | | | B 600 | C 400 | | D 100 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 33 | | B 650 | | | C 300 | D 65 | E 65 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 47 | B 500 | | | C 350 | D 55 | E 65 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 100 | | C 200 | | D 55 | E 45 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 150 | C 300 | D 45 | | E 40 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 220 | | D 35 | E 35 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 330 | D 35 | E 35 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 470 | E 30 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | CAPACITORS, LEADLESS SURFACE MOUNTED, TANTALUM, SOLID ELECTROLYTE, LOW ESR, TYPE TES | | | Certificate 327 | | Page 01-03 005 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| Types covered by similarity: | | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|----|-------|---|---------------------|--------------------|--------------------------|----------------------------|----------------------------|----|-------|----|-----|----|----|-------|----|-----|----|----|-------|----|-----|-----|----|-----|----|-----|-----|----|-----|----|-----|-----|----|-----|----|------|-----|----|----|----|------|-----|----|----|----|------|------|----|----|----|------|--|--|--|--|--|
| Procurement Specifications | | | Manufacturer | | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 3006 Detail ESCC 3006/022 | | | Exxelia Technologies Chanteloup en Brie France | | Qualification | CNES | Aug 1998 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics: Operating Temperature Range, (°C): -55 to +125 All values defined by the ESCC Detail Specification | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th colspan="3">Capacitance Range (nF)</th> <th>Tol. (±%)</th> <th>U_R(kV)</th> </tr> </thead> <tbody> <tr> <td>33</td> <td>to</td> <td>2 200</td> <td>10</td> <td>1.5</td> </tr> <tr> <td>15</td> <td>to</td> <td>1 500</td> <td>10</td> <td>2.5</td> </tr> <tr> <td>15</td> <td>to</td> <td>1 000</td> <td>10</td> <td>3.5</td> </tr> <tr> <td>6.8</td> <td>to</td> <td>470</td> <td>10</td> <td>5.0</td> </tr> <tr> <td>2.2</td> <td>to</td> <td>220</td> <td>10</td> <td>7.5</td> </tr> <tr> <td>1.0</td> <td>to</td> <td>100</td> <td>10</td> <td>10.0</td> </tr> <tr> <td>3.3</td> <td>to</td> <td>68</td> <td>10</td> <td>12.5</td> </tr> <tr> <td>1.5</td> <td>to</td> <td>33</td> <td>10</td> <td>15.0</td> </tr> <tr> <td>0.68</td> <td>to</td> <td>15</td> <td>10</td> <td>20.0</td> </tr> </tbody> </table> | | | Capacitance Range (nF) | | | Tol. (±%) | U _R (kV) | 33 | to | 2 200 | 10 | 1.5 | 15 | to | 1 500 | 10 | 2.5 | 15 | to | 1 000 | 10 | 3.5 | 6.8 | to | 470 | 10 | 5.0 | 2.2 | to | 220 | 10 | 7.5 | 1.0 | to | 100 | 10 | 10.0 | 3.3 | to | 68 | 10 | 12.5 | 1.5 | to | 33 | 10 | 15.0 | 0.68 | to | 15 | 10 | 20.0 | | | | | |
| Capacitance Range (nF) | | | Tol. (±%) | U _R (kV) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 33 | to | 2 200 | 10 | 1.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 15 | to | 1 500 | 10 | 2.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 15 | to | 1 000 | 10 | 3.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.8 | to | 470 | 10 | 5.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.2 | to | 220 | 10 | 7.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.0 | to | 100 | 10 | 10.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3.3 | to | 68 | 10 | 12.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5 | to | 33 | 10 | 15.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.68 | to | 15 | 10 | 20.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | | CAPACITORS, FIXED, RECONSTITUTED MICA, HIGH VOLTAGE, BASED ON TYPE HT86PS | | | Certificate 251 G | | Page 01-05 001-1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |


| Types covered by similarity: All values defined by the ESCC Detail Specification ±20% (E6 Series) tolerance by variant where applicable | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|--|--------------------------|----------------------------|------------------------|--|-----------|--------------------|-----|-------|----|----|-----|-------|----|----|------|-------|----|-----|------|--------|----|-----|------|--------|----|-----|------|--------|----|-----|
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 3006 Detail ESCC 3006/024 | Exxelia Technologies Marmoutier France | Qualification | CNES | Aug 2002 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics: E12 Series Sizes Available 01, 02, 03, 04 Maximum dimensions (mm): 01: 10.7 x 10.7 x B 02: 15.5 x 15.5 x B 03: 16.5 x 15.5 x B 04: 18.5 x 17.0 x B Where B= 6, 8, 10, 12, 14, 15 depending on capacitance value Operating Temperature Range, (°C): -55 to +125 | | <table border="1"> <thead> <tr> <th colspan="2">Capacitance Range (µF)</th> <th>Tol. (±%)</th> <th>U_R(V)</th> </tr> </thead> <tbody> <tr> <td>2.2</td> <td>to 47</td> <td>10</td> <td>50</td> </tr> <tr> <td>1.5</td> <td>to 22</td> <td>10</td> <td>63</td> </tr> <tr> <td>0.56</td> <td>to 12</td> <td>10</td> <td>100</td> </tr> <tr> <td>0.33</td> <td>to 5.6</td> <td>10</td> <td>200</td> </tr> <tr> <td>0.22</td> <td>to 4.7</td> <td>10</td> <td>250</td> </tr> <tr> <td>0.10</td> <td>to 1.8</td> <td>10</td> <td>400</td> </tr> </tbody> </table> | | | Capacitance Range (µF) | | Tol. (±%) | U _R (V) | 2.2 | to 47 | 10 | 50 | 1.5 | to 22 | 10 | 63 | 0.56 | to 12 | 10 | 100 | 0.33 | to 5.6 | 10 | 200 | 0.22 | to 4.7 | 10 | 250 | 0.10 | to 1.8 | 10 | 400 |
| Capacitance Range (µF) | | Tol. (±%) | U _R (V) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.2 | to 47 | 10 | 50 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5 | to 22 | 10 | 63 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.56 | to 12 | 10 | 100 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.33 | to 5.6 | 10 | 200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.22 | to 4.7 | 10 | 250 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.10 | to 1.8 | 10 | 400 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | CAPACITORS, FIXED, SURFACE MOUNT, D.C. SELF-HEALING, NON-INDUCTIVE, POLYTEREPH- THALATE DIELECTRIC, BASED ON TYPE PM94S | | Certificate 270 E | Page 01-05 003-1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |


| Types covered by similarity: Unless otherwise stated in Table 1(a) of the Detail Specification, 10% and 20% tolerance are available. | | Remarks: | | | | | | | | | | | | | | | | | | | |
|--|--|--|--|--------------------|-----------------------|----------------------------|----------------------|------------------------|--------------------|--|--|----|---|--|-----|--|--|-----|----------------------|--------------|-----|
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | |
| Generic ESCC 5010 Detail ESCC 5711/002 | | COBHAM MICROWAVE Les Ulis France | | Qualification | CNES | Dec 2008 | | | | | | | | | | | | | | | |
| Characteristics: Operating Temperature Range, (°C): -55 to +150 All variants defined by the ESCC Detail Specification. | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>Type</th> <th>Capacitance Range (pF)</th> <th>U_R(V)</th> </tr> </thead> <tbody> <tr> <td>400M106A & C 400M10xA & 107C 400M108A & C 400M110A & C 400M113J & 114J</td> <td>8.2, 10, 12, 15 18, 22, 27, 33, 39 47, 56, 68 81, 100 10</td> <td>40</td> </tr> <tr> <td>101M106A & C 101M10xA & 107C 101M108A & C</td> <td>3.9, 4.7, 5.6, 6.8 10, 12, 15 22, 27, 33, 39</td> <td>100</td> </tr> <tr> <td>201M106C 201M106A 201M10xA & 107C 201M108A & C 201M111J & 112J</td> <td>2.2, 2.7, 3.3 0.1X (201M106C, -107C, -108C) + 210M106C 3.9, 4.7, 5.6, 6.8, 8.2 10, 12, 15, 18 0.25 & 0.4</td> <td>200</td> </tr> <tr> <td>401M111J 401M112J</td> <td>0.125 0.2</td> <td>400</td> </tr> </tbody> </table> | | | | | | | Type | Capacitance Range (pF) | U _R (V) | 400M106A & C 400M10xA & 107C 400M108A & C 400M110A & C 400M113J & 114J | 8.2, 10, 12, 15 18, 22, 27, 33, 39 47, 56, 68 81, 100 10 | 40 | 101M106A & C 101M10xA & 107C 101M108A & C | 3.9, 4.7, 5.6, 6.8 10, 12, 15 22, 27, 33, 39 | 100 | 201M106C 201M106A 201M10xA & 107C 201M108A & C 201M111J & 112J | 2.2, 2.7, 3.3 0.1X (201M106C, -107C, -108C) + 210M106C 3.9, 4.7, 5.6, 6.8, 8.2 10, 12, 15, 18 0.25 & 0.4 | 200 | 401M111J 401M112J | 0.125 0.2 | 400 |
| Type | Capacitance Range (pF) | U _R (V) | | | | | | | | | | | | | | | | | | | |
| 400M106A & C 400M10xA & 107C 400M108A & C 400M110A & C 400M113J & 114J | 8.2, 10, 12, 15 18, 22, 27, 33, 39 47, 56, 68 81, 100 10 | 40 | | | | | | | | | | | | | | | | | | | |
| 101M106A & C 101M10xA & 107C 101M108A & C | 3.9, 4.7, 5.6, 6.8 10, 12, 15 22, 27, 33, 39 | 100 | | | | | | | | | | | | | | | | | | | |
| 201M106C 201M106A 201M10xA & 107C 201M108A & C 201M111J & 112J | 2.2, 2.7, 3.3 0.1X (201M106C, -107C, -108C) + 210M106C 3.9, 4.7, 5.6, 6.8, 8.2 10, 12, 15, 18 0.25 & 0.4 | 200 | | | | | | | | | | | | | | | | | | | |
| 401M111J 401M112J | 0.125 0.2 | 400 | | | | | | | | | | | | | | | | | | | |
|  | | CAPACITORS, MICROWAVE, SILICON, NAKED DIE, MOS, BASED ON TYPES 101M, 201M, 400M AND 401M | | | Certificate 286 C | | Page 01-11 001 | | | | | | | | | | | | | | |


Section 02


Component Type: Connectors


| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|--------------|-------------|-------|--|----------------|
| 02-01 | | | Multipin, Solder Contacts | |
| | 02-01-001-1 | 71 P | D*M Series, Rectangular | C&K COMPONENTS |
| | 02-01-001-2 | 155 L | D*M Series, Rectangular | SOURIAU |
| 02-02 | | | Multipin, Crimp Contacts | |
| | 02-02-001-1 | 72 P | D*MA Series, Rectangular | C&K COMPONENTS |
| | 02-02-001-2 | 156 K | D*MA Series, Rectangular | SOURIAU |
| | 02-02-003 | 25 N | DBAS Series, Circular | Deutsch |
| | 02-02-005 | 220 G | Series I, Circular, Crimp | SOURIAU |
| | 02-02-006 | 221 G | Series II, Circular, Crimp | SOURIAU |
| | 02-02-007-1 | 222 G | Series III, Circular, Miniature | SOURIAU |
| | 02-02-008 | 223 F | Series III, Hermetic | SOURIAU |
| | 02-02-009 | 288 B | ACB1 Series | Axon' Cables |
| 02-03 | | | Printed Circuit Board | |
| | 02-03-001-1 | 99 M | HE 801 Series | HYPERTAC |
| | 02-03-002-1 | 149 K | KMC Series | HYPERTAC |
| | 02-03-003-1 | 250 F | MHD Series | HYPERTAC |
| | 02-03-004-1 | 281 C | IHD INTERPOSER | HYPERTAC |
| 02-04 | | | R.F. Coaxial | |
| | 02-04-001 | 68 M | SMA Series | Radiall |
| | 02-04-002 | 283 C | SMA 2.9 | Radiall |
| | 02-04-003 | 329 | SMA, SMA 2.92, TNC and SMP | Rosenberger |
| 02-05 | | | Micro-miniature, Crimp Contacts | |
| | 02-05-001-1 | 140 M | MDM Series, Rectangular | C&K COMPONENTS |
| | 02-05-002-1 | 141 M | MTB Series, Rectangular | C&K COMPONENTS |
| | 02-05-003-1 | 290 B | MDMA, Rectangular | C&K COMPONENTS |
| | 02-05-004-1 | 301 B | 8MCG, Rectangular | SOURIAU |


| | | | | | |
|--|--|--|--------------------|--------------------------------|------------------------------------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| <p>Generic ESCC 3401</p> <p>Detail ESCC 3401/001 3401/004 3401/022 3401/040 3401/072 3401/080</p> | | C&K COMPONENTS Dole France | Qualification | CNES | Feb 1981 |
| <p>Characteristics: Shell Size: E, A, B, C, D, F</p> <p>Range of Contacts: 9, 15, 25, 37 and 50 size 20 contacts for standard density layout 3W3 to 8W8, 5W1 to 47W1 combined contact arrangements 15, 26, 44, 62, 78 and 104 size 22 contacts for high density layout</p> <p>Mounting Type: Blank: standard mounting holes; Y: floating mount; E: captive nuts</p> <p>Range of Connectors: 3401/001: Variants 01 & 02</p> <p>Range of Contacts: 3401/004: Variants 01 to 25; 3401/022: 01 to 95; 3401/040: 01 to 17; 3401/080: 01 3401/072: Variants 05 to 14, 25 to 39, 46 to 55, 61 to 65, 72, 73, 76 to 80</p> <p>Termination contacts: solder bucket, straight PCB, 90 ° PCB</p> <p>Gold-plated non-magnetic coating</p> <p>Coaxial contact arrangements: 3401/004 variants 01 to 25: Power contact arrangements: 3401/040 variants 01 to 17</p> <p>Operating Temperature Range (°C): -55 to +125</p> | | | | | |
|  | | <p>CONNECTORS, ELECTRICAL, SOLDER AND WIRE WRAP CONTACTS, RECTANGULAR RECEPTACLE AND PLUG, BASED ON TYPE D*M</p> | | <p>Certificate</p> <p>71 P</p> | <p>Page</p> <p>02-01 001-1</p> |


| | | | | | |
|---|--|---|--------------------|--------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3401 Detail ESCC 3401/001 3401/022 3401/072 | | SOURIAU Connection Technology Marolles en Brie France | Qualification | CNES | Sep 1988 |
| Characteristics: Complete range as defined in the Detail Specifications are qualified <u>except for</u> <ul style="list-style-type: none"> • high density 104 contacts arrangement • coaxial and power contacts and arrangement Range of Connectors: 3401/001: variants 01 to 02 Range of Contacts: Size 20 : 9, 15, 25, 37 and 50 contacts, Size 22: 15, 26, 44, 62, 78 contacts 3401/022: variants 01 to 16 & 44 to 57 & 65 to 80 3401/072: variants 01 to 65 Mounting Type= blank: standard mounting holes; Y: floating mount; E: captive nuts Gold-plated non-magnetic coating Operating Temperature Range (°C): -55 to +125 | | | | | |
|  | | CONNECTORS, ELECTRICAL, SOLDER AND WIRE WRAP CONTACTS, NON-REMOVABLE, RECTANGULAR RECEPTACLE AND PLUG, BASED ON TYPE D*M | | Certificate 155 L | Page 02-01 001-2 |


| | | | | | |
|--|--|--|--------------------|--------------------------------|------------------------------------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| <p>Generic ESCC 3401</p> <p>Detail ESCC 3401/002 3401/005 3401/020 3401/021</p> | | C&K COMPONENTS Dole France | Qualification | CNES | Feb 1981 |
| <p>Characteristics: Complete range defined in the corresponding Detail Specifications are qualified Shell Size: E, A, B, C, D, F</p> <p>Range of Connectors: 3401/002: variants 01 and 02 9, 15, 25, 37 and 50 size 20* contacts for standard density layout</p> <p>Range of Contacts: *Accepts wire sizes : AWG # 20 to 24 (standard bucket: variants 01 and 02) per 3401/005 3401/005: variants 01 to 08 : AWG # 26 and 28 (reduced bucket: variants 03 and 04) per 3401/005 3401/021 variants 01 & 02 :AWG # 18 and 20 (large bucket: variants 05 to 06) per 3401/005 3401/022: variants 01 & 02 15, 26, 44, 62, 78 and 104 size 22** contacts for high density layout ** Accepts wire sizes AWG # 22 to 26 (standard bucket: variants 07 to 08) per 3401/005</p> <p>Mounting Type: Blank: standard mounting holes; Y: floating mount; E: captive nuts Gold-plated non-magnetic coating Connector Savers: For usage with above connector range</p> <p>Operating Temperature Range (°C): -55 to +125</p> | | | | | |
|  | | <p>CONNECTORS, ELECTRICAL, CRIMP CONTACTS, RECTANGULAR RECEPTACLE AND PLUG, BASED ON TYPE D*MA</p> | | <p>Certificate</p> <p>72 P</p> | <p>Page</p> <p>02-02 001-1</p> |


| | | | | | | |
|--|--|--|--------------------|------------------------------|----------------------------|---------------------------------|
| Types covered by similarity: | | Remarks: | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | |
| <p>Generic ESCC 3401</p> <p>Detail ESCC 3401/002 3401/005 3401/020 3401/021 3401/022 3401/072</p> | | SOURIAU Connection Technology Marolles en Brie France | Qualification | CNES | Sep 1988 | |
| <p>Characteristics: Complete range as defined in the Detail Specifications <u>except</u> high density 104 contacts arrangement are qualified Accessories variants qualified: 3401/022: variants 01 to 16, 44 to 57, 65 to 80 3401/072: variants 01 to 65</p> <p>Range of Connectors:- 3401/002: variants 1 & 2 *Accepts wire sizes AWG # 20 to 24 (standard bucket: variants 01 and 02) 3401/005: variants 1 to 8 *Accepts wire sizes AWG # 26 and 28 (reduced bucket: variants 03 and 04) 3401/021 & 22: variants 1 & 2 *Accepts wire size AWG# 18 and 20 (large bucket: variants 05 and 06) *Accepts wire size AWG # 22, 24 and 26 (contact AWG # 22 for high density, contact arrangements, variants 07 and 08)</p> <p>Range of Contacts: 9, 15, 25, 37 and 50 contacts size 20 for standard contact arrangements 15, 26, 44, 62, 78 contacts size 22 for high density contact arrangements</p> <p>Gold-plated non-magnetic coating Connector Savers- For usage with connector range defined above</p> <p>Operating Temperature Range (°C): -55 to +125</p> | | | | | | |
|  | | <p>CONNECTORS AND CONNECTOR SAVER, ELECTRICAL, CRIMP CONTACTS, REMOVABLE RECTANGULAR RECEPTACLE AND PLUG, BASED ON TYPE D*MA</p> | | <p>Certificate 156 K</p> | | <p>Page 02-02 001-2</p> |


| | | | | | |
|---|--|--|--------------------|-------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3401 Detail ESCC 3401/008 3401/009 3401/012 3401/064 | | Cie DEUTSCH Evreux France | Qualification | CNES | Jul 1979 |
| Characteristics: 3401/008: Variant 01 3401/009: Variants 01 to 20; 3401/012: Variants 01 to 04; 3401/064: Variants 01 to 41 Circular Multicontact connectors Standard contact arrangements with 3, 7, 12, 19, 27, 37 or 61 contacts in wire size AWG # 20 Special contact arrangements with contacts size AWG 22, 20, 16, 12 and 8 Operating Temperature Range (°C): -65 to +200 | | | | | |
|  | | CONNECTORS, MINIATURE, ELECTRICAL, CIRCULAR, PUSH-PULL COUPLING, REMOVABLE CRIMP CONTACTS, BASED ON TYPE DBAS | | Certificate 25 N | Page 02-02 003 |


| Types covered by similarity: | | | Remarks: | | | | | | | | | | | | | | | | |
|--|-------------|---|--------------------|-----------------------|----------------------------|----|---|------|----|------|----|------|----|-----|----|-----|--|--|--|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | |
| Generic ESCC 3401 Detail ESCC 3401/052 3401/058 3401/062 | | SOURIAU Connection Technology Marolles en Brie France | Qualification | CNES | May 1995 | | | | | | | | | | | | | | |
| Characteristics: All connector variants are qualified For 3401/058, variants 01 to 14 are qualified For 3401/062, variants 01 to 27 are qualified | | <table border="1"> <thead> <tr> <th>Contact Size</th> <th>Ratings (A)</th> </tr> </thead> <tbody> <tr><td>4</td><td>80</td></tr> <tr><td>8</td><td>46.0</td></tr> <tr><td>12</td><td>23.0</td></tr> <tr><td>16</td><td>13.0</td></tr> <tr><td>20</td><td>7.5</td></tr> <tr><td>22</td><td>5.0</td></tr> </tbody> </table> | Contact Size | Ratings (A) | 4 | 80 | 8 | 46.0 | 12 | 23.0 | 16 | 13.0 | 20 | 7.5 | 22 | 5.0 | | | |
| Contact Size | Ratings (A) | | | | | | | | | | | | | | | | | | |
| 4 | 80 | | | | | | | | | | | | | | | | | | |
| 8 | 46.0 | | | | | | | | | | | | | | | | | | |
| 12 | 23.0 | | | | | | | | | | | | | | | | | | |
| 16 | 13.0 | | | | | | | | | | | | | | | | | | |
| 20 | 7.5 | | | | | | | | | | | | | | | | | | |
| 22 | 5.0 | | | | | | | | | | | | | | | | | | |
| Range: # 20 with standard contact arrangements 3, 6, 10, 19, 26, 32, 41, 53, 61 # 22 with high density arrangements 6, 13, 22, 37, 55, 66, 79, 100, 128 Other arrangements with contact sizes: 20, 16, 12, 8 Receptacle and Plug Shell Sizes: 09, 11, 13, 15, 17, 19, 21, 23, 25 Operating Temperature Range (°C): -65 to +200 | | | | | | | | | | | | | | | | | | | |
|  | | CONNECTORS, ELECTRICAL, CIRCULAR, BAYONET COUPLING, SCOOP-PROOF, REMOVABLE CRIMP CONTACTS, BASED ON TYPE MIL-C-38999, SERIES I | Certificate | | Page | | | | | | | | | | | | | | |
| | | | 220 G | | 02-02 005 | | | | | | | | | | | | | | |


| Types covered by similarity: | | Remarks: | | | | | | | | | | | | | |
|---|-------------|---|--------------------|--------------------------|----------------------------|----|------|----|------|----|-----|----|-----|--|--|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | |
| Generic ESCC 3401 Detail ESCC 3401/044 3401/045 3401/062 | | SOURIAU Connection Technology Marolles en Brie France | Qualification | CNES | May 1995 | | | | | | | | | | |
| Characteristics: For 3401/044, all variants are qualified For 3401/045, variants 01 to 08 are qualified For 3401/062, variants 01 to 27 are qualified | | <table border="1"> <thead> <tr> <th>Contact Size</th> <th>Ratings (A)</th> </tr> </thead> <tbody> <tr> <td>12</td> <td>23.0</td> </tr> <tr> <td>16</td> <td>13.0</td> </tr> <tr> <td>20</td> <td>7.5</td> </tr> <tr> <td>22</td> <td>5.0</td> </tr> </tbody> </table> | | Contact Size | Ratings (A) | 12 | 23.0 | 16 | 13.0 | 20 | 7.5 | 22 | 5.0 | | |
| Contact Size | Ratings (A) | | | | | | | | | | | | | | |
| 12 | 23.0 | | | | | | | | | | | | | | |
| 16 | 13.0 | | | | | | | | | | | | | | |
| 20 | 7.5 | | | | | | | | | | | | | | |
| 22 | 5.0 | | | | | | | | | | | | | | |
| Range: # 20 with standard contact arrangements 3, 6, 10, 18, 26, 32, 41, 55, 61 # 22 with high density arrangements 6, 13, 22, 37, 55, 66, 79, 100, 128 | | | | | | | | | | | | | | | |
| Other arrangements with contact sizes: 20, 16, 12 Receptacle and Plug Shell Sizes: 08, 10, 12, 14, 16, 18, 20, 22, 24 Operating Temperature Range (°C): -65 to +200 | | | | | | | | | | | | | | | |
|  | | CONNECTORS, ELECTRICAL, CIRCULAR, BAYONET COUPLING, REMOVABLE CRIMP CONTACTS, BASED ON TYPE MIL-C-38999, SERIES II | | Certificate 221 G | Page 02-02 006 | | | | | | | | | | |


| Types covered by similarity: | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|--|--------------------------|-----------------------|----------------------------|-------------|---|------|----|------|---|------|----|-----|----|------|----|-----|----|------|--|--|----|-----|--|--|----|-----|--|--|--|--|--|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 3401 Detail ESCC 3401/056 3401/058 3401/062 3401/066 3401/070 | | SOURIAU Connection Technology Marolles en Brie France | Qualification | CNES | May 1995 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Charac- 3401/056 all variants are qualified teristics: 3401/058 variants 01 to 14 are qualified 3401/062 variants 28 to 54 are qualified 3401/066 variants 01 and 02 are qualified 3401/058 crimp contacts and 3401/066 triax contacts to be mounted on 3401/056 connectors 3401/070 connector receptacles with PCB contacts | | <table border="1"> <thead> <tr> <th>Crimp Contact Size</th> <th>Ratings (A)</th> <th>PCB Contact Size</th> <th>Ratings (A)</th> </tr> </thead> <tbody> <tr> <td>4</td> <td>80.0</td> <td>16</td> <td>10.0</td> </tr> <tr> <td>8</td> <td>46.0</td> <td>20</td> <td>5.0</td> </tr> <tr> <td>12</td> <td>23.0</td> <td>22</td> <td>3.0</td> </tr> <tr> <td>16</td> <td>13.0</td> <td></td> <td></td> </tr> <tr> <td>20</td> <td>7.5</td> <td></td> <td></td> </tr> <tr> <td>22</td> <td>5.0</td> <td></td> <td></td> </tr> </tbody> </table> | Crimp Contact Size | Ratings (A) | PCB Contact Size | Ratings (A) | 4 | 80.0 | 16 | 10.0 | 8 | 46.0 | 20 | 5.0 | 12 | 23.0 | 22 | 3.0 | 16 | 13.0 | | | 20 | 7.5 | | | 22 | 5.0 | | | | | |
| Crimp Contact Size | Ratings (A) | PCB Contact Size | Ratings (A) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | 80.0 | 16 | 10.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 8 | 46.0 | 20 | 5.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 12 | 23.0 | 22 | 3.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16 | 13.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 20 | 7.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 22 | 5.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Range: # 20 with standard contact arrangements (3, 4, 5, 6, 7, 8, 10, 18, 19, 26, 32, 41, 53, 55, 61 contacts) # 22 with high density arrangements (6, 13, 22, 37, 55, 66, 79, 100, 128 contacts) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Other arrangements with contact sizes:# 20, 16, 12, 8, 4 Receptacle and Plug Shell Sizes: 09, 11, 13, 15, 17, 19, 21, 23, 25. Triax contacts Operating Temperature Range (°C): -65 to +200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | CONNECTORS, MINIATURE, ELECTRICAL, CIRCULAR, TRIPLE-START SELF-LOCKING COUPLING, SCOOP-PROOF, REMOVABLE AND NON-REMOVABLE CRIMP CONTACTS BASED ON TYPE MIL-C-38999, SERIES III | | Certificate 222 G | | Page 02-02 007-1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |


| Types covered by similarity: | | Remarks: | | | | | | |
|--|------------------------|--|--------------------|--------------------------|----------------------------|--|--|--|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | | | |
| Generic ESCC 3401 Detail ESCC 3401/057 | | SOURIAU Connection Technology Marolles en Brie France | Qualification | CNES | May 1995 | | | |
| Characteristics: All variants are qualified <table border="1"> <thead> <tr> <th>Contact Size</th> <th>Ratings (A)</th> </tr> </thead> <tbody> <tr> <td>8, 12, 16 20, 22D</td> <td>33, 17, 10 5.0, 3.0</td> </tr> </tbody> </table> Range: # 20 with standard contact arrangements (3, 6, 10, 19, 26, 32, 41, 53, 61 contacts) # 22 with high density arrangements (6, 13, 22, 37, 55, 66, 79, 100, 128 contacts) Receptacle Shell Sizes: 09, 11, 13, 15, 17, 19, 21, 23, 25 Receptacle (contacts # 8, 12, 16, 20, 22D) and Feedthrough (contacts # 8, 12, 16, 20, 22D) Operating Temperature Range (°C): -65 to +200 | | Contact Size | Ratings (A) | 8, 12, 16 20, 22D | 33, 17, 10 5.0, 3.0 | | | |
| Contact Size | Ratings (A) | | | | | | | |
| 8, 12, 16 20, 22D | 33, 17, 10 5.0, 3.0 | | | | | | | |
|  | | CONNECTORS, MINIATURE, ELECTRICAL, CIRCULAR, TRIPLE-START SELF-LOCKING COUPLING, SCOOP-PROOF, HERMETIC RECEPTACLE AND FEEDTHROUGH, BASED ON TYPE MIL-C-38999, SERIES III | | Certificate 223 F | Page 02-02 008 | | | |


| | | | | |
|---|---|--------------------------|-----------------------|----------------------------|
| Types covered by similarity: Variants 01, 03 to 05, 07 to 09, 11 to 13, 15 to 18 | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3401 Detail ESCC 3401/079 | AXON' CABLE S.A. Montmirail France | Qualification | CNES | May 2009 |
| <p>Characteristics:</p> <p>Variants 01 to 18 are qualified</p> <p>Variants 01 to 08: Plug 3 and 4 Lugs, Straight and Right Angle with pin contact Variants 09 to 18: Bulkhead Jacks, 3 and 4 Lugs, Straight and Right Angle with solder contact</p> <p>All cables are 77Ω MIL-STD-1553B Data Bus twisted shielded pairs</p> <p>Working Voltage: 200 Vrms Rated Current (contact): 1A</p> <p>Operating Temperature Range (°C): -55 to +150</p> | | | | |
|  | CONNECTORS, ELECTRICAL, TRIAXIAL, BAYONET COUPLING, NON-REMOVABLE CRIMP CONTACTS, MIL-STD-1553B DATABUS, BASED ON TYPE ACB1 SERIES | Certificate 288 B | | Page 02-02 009 |


| | | | | | |
|--|--|--|--------------------|-------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3401 Detail ESCC 3401/016 3401/017 | | HYPERTAC SA Saint-Aubin-Lès-Elbeuf France | Qualification | CNES | Nov 1982 |
| Characteristics: All variants are qualified Shell specifications and sizes: 3401/016 Contact: 3401/017 Crimp wire-wrap solder and savers, 1 to 22 and 64 to 70 2 rows: 17, 29, 41, 53, 65, 72, 84, 96, 120 contacts 3 rows: 62, 80, 98, 160 contacts Contact Ratings: 5 A (1 contact AWG 22) 1.5 A (>31 contacts, AWG 22) Operating Temperature Range (°C): -55 to +125 | | | | | |
|  | | CONNECTORS, ELECTRICAL, REMOVABLE CONTACTS, CRIMP WIRE-WRAP SOLDER AND SAVER, PRINTED CIRCUIT BOARD, BASED ON TYPE HE 801 | | Certificate 99 M | Page 02-03 001-1 |


| | | | | |
|--|---|--------------------------|-----------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3401 Detail ESCC 3401/039 | HYPERTAC SA Saint-Aubin-Lès-Elbeuf France | Qualification | CNES | Mar 1987 |
| Characteristics: 3 rows contacts: 26, 44, 62, 80, 98, 144 Contact codes: 10, 30, 31, 40, 50, 51 and 91 Guiding and locking devices codes: 110, 121, 143, 201, 202, 204, 206, 703 Contact Ratings: 2 A (1 contact) Operating Temperature Range (°C): -55 to +125 | | | | |
|  | CONNECTORS, ELECTRICAL, NON-REMOVABLE SOLDER AND WIRE-WRAP CONTACTS AND SAVERS, PRINTED CIRCUIT BOARD, BASED ON TYPE KMC | Certificate 149 K | | Page 02-03 002-1 |


| | | | | |
|--|--|--------------------------|----------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3401 Detail ESCC 3401/065 | HYPERTAC SA Saint-Aubin-Les-Elbeuf France | Qualification | CNES | Aug 1998 |
| Characteristics: Contact: 52, 100, 152, 200, 252, 300, 352 and 400 Contact Codes: 10, 11, 12, 30, 31, 43, 45, 47 and 91 Guiding and Locking Devices Codes: 110, 111, 121, 124, 134 and 201 Operating Temperature Range (°C): -55 to +125 | | | | |
|  | CONNECTORS AND SAVERS, ELECTRICAL, RECTANGULAR, NON-REMOVABLE, PRINTED CIRCUIT BOARD, BASED ON TYPE MHD | Certificate 250 F | Page 02-03 003-1 | |


| | | | | | |
|--|--|---|--------------------|--------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3401 Detail ESCC 3401/076 | | HYPERTAC SA Saint-Aubin-Les-Elbeuf France | Qualification | CNES | Aug 2007 |
| Characteristics: All design envelops specified in Table 1(a) of ESCC Detail Specification are qualified Max. number of rows 11 Max. number of contacts: 660 Locking and Guiding Devices: -Through holes only -M2 studs with locking nuts and washers -Locating pins not available Rated current: 1A each contact Total contact compression range: 0.1 to 0.65 mm per contact Compression force: 1.6N per contact Torque for locking devices: 10 N-cm Operating Temperature Range (°C): -55 to +125 | | | | | |
|  | | CONNECTORS, ELECTRICAL, CRIMP CONTACTS, Z-AXIS INTERPOSER, PRINTED CIRCUIT BOARD, BASED ON TYPE RX | | Certificate 281 C | Page 02-03 004-1 |


| | | | | | |
|--|--|---|--------------------|-------------------------|----------------------------|
| Types covered by similarity: - Hermetically sealed receptacle | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3402 Detail ESCC 3402/001 3402/002 3402/003 | | RADIALL Saint-Quentin-Fallavier France | Qualification | CNES | Feb 1981 |
| Characteristics: Frequency Range 0-18 GHz 3402/001 Pin contact (Plug). Variants 01 to 47 (except 11, 19, 31 –not in use) 3402/002 socket contact (Receptacle). Variants 01 to 85 (except 33, 35, 52 –not in use) 3402/003 Adapters. Variants 01 to 14 Crimp– or solder-type contact for flexible and semi-rigid cables, contacts for micro strip Shell material and finish: Beryllium copper gold plated, copper or nickel underplate; stainless steel, electro-passivated or gold plated. Operating Temperature Range (°C): See Detail Specifications | | | | | |
|  | | CONNECTORS, RF, COAXIAL, SOLDER AND CRIMP CONTACTS, MALE, FEMALE ADAPTORS AND CONNECTING PIECES, BASED ON TYPE SMA | | Certificate 68 M | Page 02-04 001 |


| | | | | | |
|--|--|---|--------------------|--------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3402 Detail ESCC 3402/021 3402/022 3402/023 | | RADIALL Saint-Quentin-Fallavier France | Qualification | CNES | Dec 2007 |
| Characteristics: Frequency Range 0-40 GHz 50 Ohms 3402/021 Pin contact (Plug). Variants 01 to 05 and 07 3402/022 Socket contact (Receptacle). Variants 01 to 05 3402/023 Adapters. Variants 01 to 06 Crimp– or solder-type contact for flexible and semi-rigid cables, contacts for micro strip Shell material and finish: passivated amagnetic stainless steel. Operating Temperature Range (°C): -65 to +165 | | | | | |
|  | | CONNECTORS, RF, COAXIAL, SOLDER AND CRIMP CONTACTS, MALE, FEMALE ADAPTORS AND CONNECTING PIECES, BASED ON TYPE SMA 2.9 | | Certificate 283 C | Page 02-04 002 |

| | | | | |
|--|--|--------------------|------------------------|----------------------------|
| Types covered by similarity: See below the range of qualified variants for each specification | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3402 Detail ESCC 3402/001, 3402/002, 3402/003 (SMA range) 3402/008, 3402/009, 3402/010 (TNC range) 3402/021, 3402/022, 3402/023 (SMA 2.9 range) 3402/024, 3402/025, 3402/026 (SMP range) | Rosenberger Fridolfing Germany | Qualification | DLR | Dec 2013 |
| Qualified variants: 3402/001: 1 to 10, 12 to 18, 20 to 30, 32 to 35, 37 to 47 3402/002: 1 to 24, 27 to 32, 34, 36 to 51, 53 to 61, 65 to 71 3402/003: 1 to 6, 8 to 14 3402/008: 1 to 7; 3402/009: 1 to 5; 3402/010: 1 to 5 3402/021: 1 to 5, 7; 3402/022: 1 to 5; 3402/023: 1 to 6 3402/024: 1 to 26, 28 to 35; 3402/025: 1 to 14; 3402/026: 1 to 13 | | | | |
|  | CONNECTORS, RF, COAXIAL, SOLDER AND CRIMP CONTACTS, MALE, FEMALE ADAPTORS AND CONNECTING PIECES, BASED ON TYPES SMA, SMA 2.92 TNC and SMP | | Certificate 329 | Page 02-04 003 |

| Types covered by similarity: | | Remarks: | | | | | | | | | | | | | | | |
|--|---|---|--------------------|--------------------------|----------------------------|----|---|-----|----|----------------------------|-----|----|----------------------------|-----|--|--|--|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | |
| Generic ESCC 3401 Detail ESCC 3401/029 3401/041 3401/032 | | C&K COMPONENTS Dole France | Qualification | CNES | Oct 1986 | | | | | | | | | | | | |
| Characteristics: Layout: 9 - 15 - 21- 25 - 31 - 37 - 51 Contacts Non removable crimp contacts Termination types: Nickel or Gold Plated Shells Operating Temperature Range (°C): -55 to +125 | | <table border="1"> <thead> <tr> <th>AWG #</th> <th>ESCC No.</th> <th>Max. Rated (A)</th> </tr> </thead> <tbody> <tr> <td>25</td> <td>Uninsulated rigid wire Bent and straight PCB</td> <td>2.5</td> </tr> <tr> <td>26</td> <td>3901 013 02 3901 002 56</td> <td>2.5</td> </tr> <tr> <td>28</td> <td>3901 013 01 3901 002 61</td> <td>1.5</td> </tr> </tbody> </table> | AWG # | ESCC No. | Max. Rated (A) | 25 | Uninsulated rigid wire Bent and straight PCB | 2.5 | 26 | 3901 013 02 3901 002 56 | 2.5 | 28 | 3901 013 01 3901 002 61 | 1.5 | | | |
| AWG # | ESCC No. | Max. Rated (A) | | | | | | | | | | | | | | | |
| 25 | Uninsulated rigid wire Bent and straight PCB | 2.5 | | | | | | | | | | | | | | | |
| 26 | 3901 013 02 3901 002 56 | 2.5 | | | | | | | | | | | | | | | |
| 28 | 3901 013 01 3901 002 61 | 1.5 | | | | | | | | | | | | | | | |
|  | | CONNECTORS, ELECTRICAL, RECTANGULAR, MICROMINIATURE, CRIMP CONTACT, BASED ON TYPE MDM | | Certificate 140 M | Page 02-05 001-1 | | | | | | | | | | | | |

| Types covered by similarity: | | Remarks: | | | | | | | | | | | | | | | |
|--|------------------------------------|--|--------------------|--------------------------|----------------------------|-------|----------|----------------|----|------------------------------------|-----|----|-------------|-----|----|-------------|-----|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | |
| Generic ESCC 3401 Detail ESCC 3401/031 | | C&K COMPONENTS Dole France | Qualification | CNES | Oct 1986 | | | | | | | | | | | | |
| Characteristics: Shell sizes: 5 through 81 contacts Non removable crimp contacts Termination Types: | | <table border="1"> <thead> <tr> <th>AWG #</th> <th>ESCC No.</th> <th>Max. Rated (A)</th> </tr> </thead> <tbody> <tr> <td>25</td> <td>Uninsulated rigid wire Bent PCB</td> <td>2.5</td> </tr> <tr> <td>26</td> <td>3901 013 02</td> <td>2.5</td> </tr> <tr> <td>28</td> <td>3901 013 01</td> <td>1.5</td> </tr> </tbody> </table> | | | | AWG # | ESCC No. | Max. Rated (A) | 25 | Uninsulated rigid wire Bent PCB | 2.5 | 26 | 3901 013 02 | 2.5 | 28 | 3901 013 01 | 1.5 |
| AWG # | ESCC No. | Max. Rated (A) | | | | | | | | | | | | | | | |
| 25 | Uninsulated rigid wire Bent PCB | 2.5 | | | | | | | | | | | | | | | |
| 26 | 3901 013 02 | 2.5 | | | | | | | | | | | | | | | |
| 28 | 3901 013 01 | 1.5 | | | | | | | | | | | | | | | |
| Operating Temperature Range (°C): -55 to +125 | | | | | | | | | | | | | | | | | |
|  | | CONNECTORS, ELECTRICAL, MICROMINIATURE, CRIMP CONTACT, SINGLE-IN-LINE, BASED ON TYPE MTB | | Certificate 141 M | Page 02-05 002-1 | | | | | | | | | | | | |


| | | | | | |
|--|--|---|--------------------|--------------------------|----------------------------|
| Types covered by similarity: Contact sizes 21, 31 | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3401 Detail ESCC 3401/077 3401/078 | | C&K COMPONENTS Dole France | Qualification | CNES | Jun 2009 |
| Characteristics: All variants are qualified Range of contacts: 9 - 15 - 21- 25 - 31 - 37 Accepts wires AWG 24 or 2x28 in crimping barrel AWG 24 Accepts wires AWG 26 and 28 in crimping barrel AWG 26 Max. rating for 1 isolated contact:- AWG 24 wire: 3.5 A AWG 26 wire and uninsulated AWG 25 solid wire: 2.5 A AWG 28 wire: 1.5 A Nickel or Gold Plated Shells Working Voltage (Max.) 150Vrms Operating Temperature Range (°C): -55 to +125 | | | | | |
|  | | CONNECTORS, ELECTRICAL, RECTANGULAR, MICROMINIATURE, REMOVABLE CRIMP CONTACT, BASED ON TYPE MDMA | | Certificate 290 B | Page 02-05 003-1 |


| | | | | | |
|--|--|--|--------------------|------------------------------|---------------------------------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| <p>Generic ESCC 3401</p> <p>Detail ESCC 3401/081 3401/082 3401/083 3401/084</p> | | <p>SOURIAU Connection Technology Marolles en Brie France</p> | Qualification | CNES | Jun 2010 |
| <p>Characteristics:</p> <p>3401/081: Shell variant 01 (glass-fibre reinforced thermoplastic), variant 02 (aluminium alloy). Contacts arrangements 7, 13, 25, 51, 104 contacts. Contacts termination OL3 (straight PCB), 1A7N (90° PCB 2.54mm spacing), 1B7N (90° PCB 2.54mm spacing). Gold-plated shells.</p> <p>3401/082: Shell variant 01 (glass-fibre reinforced thermoplastic), variant 02 (aluminium alloy). Contacts arrangements 7, 13, 25, 51, 104 contacts.</p> <p>3401/083: Contacts variant 01 (male crimp barrel 26), 02 (female crimp barrel 26), 03 (male crimp barrel 24), 04 (female crimp barrel 24). Accepts wires AWG 24, 26, 28</p> <p>3401/084: Accessories variants 01 to 62.</p> <p>Operating Temperature Range (°C): -55 to +125</p> | | | | | |
|  | | <p>CONNECTORS, ELECTRICAL, RECTANGULAR, MICROMINIATURE, REMOVABLE AND NON-REMOVABLE, GAUGE 26, PCB PIN CONTACT, BASED ON TYPE 8MCG</p> | | <p>Certificate 301 B</p> | <p>Page 02-05 004-1</p> |


Section 03**Component Type: Crystals**


| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|-------------|-------|------------------|--------------|
| 03-01 | | | Crystals | |
| | 03-01-001-1 | 33 M | TO-5 Can | RAKON (F) |
| | 03-01-001-3 | 308 A | TO-5 Can | KVG (D) |
| | 03-01-002 | 34 M | TO-8 Can | RAKON (F) |
| | 03-01-002-3 | 309 A | TO-8 Can | KVG (D) |

**SECTION 03-**: INDEX OF CRYSTALS****REP005 Updated on 15 Jul 2015**

| | | | | |
|---|--------------------------------------|--|----------------------------|----------------------------|
| Types covered by similarity: All variants previously specified in (retired) specifications: 3501/001, 3501/008, 3501/011, 3501/012 | | Remarks: Upon receipt of a request for any retired Variant, the Manufacturer will allocate a new Specific Crystal Identification Number in accordance with 3501/018. It will have identical crystal characteristics to those of the retired variant. | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3501 Detail ESCC 3501/018 | RAKON France Argenteuil France | Qualification | CNES | Oct 1979 |
| Characteristics: All variants are qualified. TO-8 Can (T 1507) Frequency Range: 2.5 - 26 MHz | | | | |
|  The logo for ESCC QPL (European Space Components Coordination Quality Plan) features a globe on the left, the acronym 'ESCC' in large blue letters, and 'QPL' in large blue letters below it. The full name 'European Space Components Coordination' is written in smaller text between the globe and 'ESCC'. | CRYSTALS, TO-5 CAN | Certificate 33 M | Page 03-01 001-1 | |

| | | | | |
|---|--|--|----------------------------|----------------------------|
| Types covered by similarity: All variants previously specified in (retired) specifications: 3501/001, 3501/008, 3501/011, 3501/012 | | Remarks: Upon receipt of a request for any retired Variant, the Manufacturer will allocate a new Specific Crystal Identification Number in accordance with 3501/018. It will have identical crystal characteristics to those of the retired variant. | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3501 Detail ESCC 3501/018 | KVG Quartz Crystal Technology GmbH Neckarbischofsheim Germany | Qualification | DLR | Apr 2011 |
| Characteristics: All variants are qualified. TO-5 Can (T 807) Frequency Range: 8 - 140 MHz | | | | |
|  The logo for ESCC (European Space Components Coordination) QPL (Qualified for Production in Lot) features a globe on the left and the text 'ESCC' in large blue letters above 'European Space Components Coordination' in smaller blue letters, with 'QPL' in large blue letters below. | CRYSTALS, TO-5 CAN | Certificate 308 A | Page 03-01 001-3 | |


| | | | | |
|--|--------------------------------------|--|--------------------------|----------------------------|
| Types covered by similarity: All variants previously specified in (retired) specifications: 3501/002 and 3501/009 | | Remarks: Upon receipt of a request for any retired Variant, the Manufacturer will allocate a new Specific Crystal Identification Number in accordance with 3501/019. It will have identical crystal characteristics to those of the retired variant. | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3501 Detail ESCC 3501/019 | RAKON France Argenteuil France | Qualification | CNES | Oct 1979 |
| Characteristics: All variants are qualified. TO-8 Can (T 1507) Frequency Range: 2.5 - 20 MHz | | | | |
|  | CRYSTALS, TO-8 CAN | Certificate 34 M | Page 03-01 002 | |


| | | | | |
|--|--|--|-----------------------|----------------------------|
| Types covered by similarity: All variants previously specified in (retired) specifications: 3501/002 and 3501/009 | | Remarks: Upon receipt of a request for any retired Variant, the Manufacturer will allocate a new Specific Crystal Identification Number in accordance with 3501/019. It will have identical crystal characteristics to those of the retired variant. | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3501 Detail ESCC 3501/019 | KVG Quartz Crystal Technology GmbH Neckarbischofsheim Germany | Qualification | DLR | Apr 2011 |
| Characteristics: All variants are qualified. TO-8 Can (T 1507) Frequency Range: 2.5 - 26 MHz | | | | |
|  The logo for ESCC QPL (European Space Components Coordination) features a globe on the left, the acronym 'ESCC' in large blue letters, and 'QPL' in a stylized blue font below it. The full name 'European Space Components Coordination' is written in small text between the globe and 'ESCC'. | CRYSTALS, TO-8 CAN | Certificate 309 A | | Page 03-01 002-3 |


Section 04


Component Type: Diodes


| | | | | |
|-------|----------------|---------------|--|-------------------------------------|
| 04-01 | | | Switching | |
| | 04-01-003-2 | 311 B | Types 1N6640U and 1N6642U | STMicroelectronics |
| | 04-01-003-3 | 316 A | Types BAY6642 | Infineon |
| 04-02 | | | Power Rectifier | |
| | 04-02-001-3 | 297 B | Types 1N5806U and 1N5811U | STMicroelectronics |
| | 04-02-001-4 | 302 B | Types 1N5819U and 1N5822U | STMicroelectronics |
| | 04-02-002-1 | 272 F rev1 | Type STPS20100 | STMicroelectronics |
| | 04-02-003-1 | 274 E rev1 | Types BYW-81, BYV52, BYV54 | STMicroelectronics |
| 04-05 | | | RF/Microwave, Silicon Schottky | |
| | 04-05-001-3 | 227 E | Schottky, BAS 70 | Infineon |
| 04-13 | | | RF/Microwave, Varactors | |
| | 04-13-003 1A-B | 200 G | PIN and Varactors | API Technologies - RF2M Division |
| | 04-13-003-2A-B | 225 F | Multiplier and PIN, DH 2xx and DH 50xxx | Cobham Microwave |
| | 04-13-003-3 | 273 D | Varactor, Tuning, DH 76xxx | Cobham Microwave |
| 04-16 | | | RF/Microwave, PIN | |
| | 04-16-002-2 | 224 F | PIN, BXY 42 | Infineon |
| | 04-16-003 | 236 F | PIN, BXY 43 and 44 | Infineon |

| Types covered by similarity: | | | | Remarks: | | | | | | | | | | | | | | | | | | | | |
|---|----------|---|----------------------|----------------------|--------------------------|----------------------------|----------------------------|----------|---------------------|----------------------|----------------------|------|---------|--------|----|----|---|--------|---------|--------|-----|-----|---|--------|
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5000 Detail ESCC 5101/026 5101/027 | | ST Microelectronics Rennes France | | Qualification | CNES | May 2011 | | | | | | | | | | | | | | | | | | |
| Characteristics: <table border="1" data-bbox="91 903 1341 1070"> <thead> <tr> <th>Type</th> <th>Variants</th> <th>V_{BR} (V)</th> <th>V_{RWM} (V)</th> <th>I_{FSM} (A)</th> <th>Case</th> </tr> </thead> <tbody> <tr> <td>1N6640U</td> <td>07, 08</td> <td>75</td> <td>75</td> <td>2</td> <td>LCC2-D</td> </tr> <tr> <td>1N6642U</td> <td>07, 08</td> <td>100</td> <td>100</td> <td>2</td> <td>LCC2-D</td> </tr> </tbody> </table> <p>Operating Temperature Range (°C): -65 to +175</p> | | | | | | | Type | Variants | V _{BR} (V) | V _{RWM} (V) | I _{FSM} (A) | Case | 1N6640U | 07, 08 | 75 | 75 | 2 | LCC2-D | 1N6642U | 07, 08 | 100 | 100 | 2 | LCC2-D |
| Type | Variants | V _{BR} (V) | V _{RWM} (V) | I _{FSM} (A) | Case | | | | | | | | | | | | | | | | | | | |
| 1N6640U | 07, 08 | 75 | 75 | 2 | LCC2-D | | | | | | | | | | | | | | | | | | | |
| 1N6642U | 07, 08 | 100 | 100 | 2 | LCC2-D | | | | | | | | | | | | | | | | | | | |
|  | | DIODES, SWITCHING, BASED ON TYPES 1N6640U AND 1N6642U | | | Certificate 311 B | | Page 04-01 003-2 | | | | | | | | | | | | | | | | | |

| Types covered by similarity: | | | | | | Remarks: | | | | | | | | | | | | | | | | | | | | | |
|--|---------|---------------------|---|--|---------------------------------------|-------------------------------------|----------------------|-----------------------|----------------------------|------|---------|---------------------|----------------------|-------------------------------------|---------------------------------------|-------------------------------------|--------|------|--------------|----|-----|---|----|-----|-----|-----|-----------|
| Procurement Specifications | | | | Manufacturer | | Nature of Approval | | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5000 Detail ESCC 5101/029 | | | | INFINEON Technologies AG Neubiberg Germany | | Qualification | | DLR | Dec 2011 | | | | | | | | | | | | | | | | | | |
| Characteristics: <table border="1"> <thead> <tr> <th>Type</th> <th>Variant</th> <th>V_{BR} (V)</th> <th>t_{rr} (ns)</th> <th>V_{RWM} (V_{pk})</th> <th>I_R (μA)@ V_{RWM}</th> <th>I_{FSM} (A_{pk})</th> <th>C (pF)</th> <th>Case</th> </tr> </thead> <tbody> <tr> <td>BAY6642 (ES)</td> <td>01</td> <td>100</td> <td>4</td> <td>75</td> <td>100</td> <td>2.5</td> <td>2.5</td> <td>HSL2-1808</td> </tr> </tbody> </table> <p>Operating Temperature Range (°C): -65 to +175</p> | | | | | | | | | | Type | Variant | V _{BR} (V) | t _{rr} (ns) | V _{RWM} (V _{pk}) | I _R (μA)@ V _{RWM} | I _{FSM} (A _{pk}) | C (pF) | Case | BAY6642 (ES) | 01 | 100 | 4 | 75 | 100 | 2.5 | 2.5 | HSL2-1808 |
| Type | Variant | V _{BR} (V) | t _{rr} (ns) | V _{RWM} (V _{pk}) | I _R (μA)@ V _{RWM} | I _{FSM} (A _{pk}) | C (pF) | Case | | | | | | | | | | | | | | | | | | | |
| BAY6642 (ES) | 01 | 100 | 4 | 75 | 100 | 2.5 | 2.5 | HSL2-1808 | | | | | | | | | | | | | | | | | | | |
|  | | | DIODES, SWITCHING, BASED ON TYPES BAY6642(ES) | | | | Certificate 316 A | | Page 04-01 003-3 | | | | | | | | | | | | | | | | | | |

| Types covered by similarity: | | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | |
|--|---------|---|--------------|--------------------|-----------------------|----------------------------|------------------------|------|----------|--------------|---------------|---------------|------|----------|---------|--------|-----|-----|----|--------|----------|---------|--------|-----|-----|-----|--------|
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5000 Detail ESCC 5101/013 5101/014 | | ST Microelectronics Rennes France | | Qualification | CNES | Nov 2009 | | | | | | | | | | | | | | | | | | | | | |
| Characteristics: <table border="1" data-bbox="103 884 1386 1046"> <thead> <tr> <th>ESCC</th> <th>Type</th> <th>Variants</th> <th>V_{BR} (V)</th> <th>V_{RWM} (V)</th> <th>I_{FSM} (A)</th> <th>Case</th> </tr> </thead> <tbody> <tr> <td>5101/014</td> <td>1N5806U</td> <td>13, 14</td> <td>160</td> <td>150</td> <td>33</td> <td>LCC2-A</td> </tr> <tr> <td>5101/013</td> <td>1N5811U</td> <td>11, 12</td> <td>160</td> <td>150</td> <td>100</td> <td>LCC2-B</td> </tr> </tbody> </table> <p>Operating Temperature Range (°C): -65 to +175</p> | | | | | | | ESCC | Type | Variants | V_{BR} (V) | V_{RWM} (V) | I_{FSM} (A) | Case | 5101/014 | 1N5806U | 13, 14 | 160 | 150 | 33 | LCC2-A | 5101/013 | 1N5811U | 11, 12 | 160 | 150 | 100 | LCC2-B |
| ESCC | Type | Variants | V_{BR} (V) | V_{RWM} (V) | I_{FSM} (A) | Case | | | | | | | | | | | | | | | | | | | | | |
| 5101/014 | 1N5806U | 13, 14 | 160 | 150 | 33 | LCC2-A | | | | | | | | | | | | | | | | | | | | | |
| 5101/013 | 1N5811U | 11, 12 | 160 | 150 | 100 | LCC2-B | | | | | | | | | | | | | | | | | | | | | |
|  | | DIODES, POWER RECTIFIER, BASED ON TYPES 1N5806U AND 1N5811U | | | Certificate 297 B | | Page 04-02 001-3 | | | | | | | | | | | | | | | | | | | | |

| Types covered by similarity: | | | Remarks: | | | | | | | | | | | | | | | | | | | | |
|--|---------------|---|-----------------------------|--------------------------|----------------------------|------|---------------|----------------------|-----------------------------|---------------|-----------------------|---------|----|--------|---------|----|---|---------|----|--------|------------|----|---|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5000 Detail ESCC 5106/020 5106/021 | | ST Microelectronics Rennes France | Qualification | CNES | Sep 2010 | | | | | | | | | | | | | | | | | | |
| Characteristics: Variants 01 and 02 of 5106/020 and Variants 02 and 03 of 5106/021 are qualified | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>Type</th> <th>V_{RWM} (V)</th> <th>dV/dt (V/μs)</th> <th>I_R (μA) @ $V_R=40$</th> <th>I_{FSM} (A)</th> <th>I_O (A) @ T_{amb}</th> </tr> </thead> <tbody> <tr> <td>1N5819U</td> <td>40</td> <td>10 000</td> <td>15 (DC)</td> <td>25</td> <td>1</td> </tr> <tr> <td>1N5822U</td> <td>40</td> <td>10 000</td> <td>80 (pulse)</td> <td>80</td> <td>3</td> </tr> </tbody> </table> | | | | | | Type | V_{RWM} (V) | dV/dt (V/ μ s) | I_R (μ A) @ $V_R=40$ | I_{FSM} (A) | I_O (A) @ T_{amb} | 1N5819U | 40 | 10 000 | 15 (DC) | 25 | 1 | 1N5822U | 40 | 10 000 | 80 (pulse) | 80 | 3 |
| Type | V_{RWM} (V) | dV/dt (V/ μ s) | I_R (μ A) @ $V_R=40$ | I_{FSM} (A) | I_O (A) @ T_{amb} | | | | | | | | | | | | | | | | | | |
| 1N5819U | 40 | 10 000 | 15 (DC) | 25 | 1 | | | | | | | | | | | | | | | | | | |
| 1N5822U | 40 | 10 000 | 80 (pulse) | 80 | 3 | | | | | | | | | | | | | | | | | | |
| Operating Temperature Range (°C): -65 to +150 Package Type: LCC2-B | | | | | | | | | | | | | | | | | | | | | | | |
|  | | DIODES, POWER SCHOTTKY, BASED ON TYPES 1N5819U AND 1N5822U | | Certificate 302 B | Page 04-02 001-4 | | | | | | | | | | | | | | | | | | |

| | | | | |
|--|---|---------------------------|-----------------------|----------------------------|
| Types covered by similarity: see next page | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 5000 Detail ESCC 5106/016 5106/017 5106/018 5106/019 | ST Microelectronics Rennes France | Qualification | CNES | Nov 2002 |
| Characteristics: Maximum Ratings for 5106/016: V_{RRM} : 100 V I_o : 2 x 20 A dV/dt : 10 000 V/ μ s T_j : + 175°C Package Types TO254, SMD.5 and SMD1 Operating Temperature Range (°C): -65 to +175 | | | | |
|  | DIODES, POWER, SCHOTTKY BARRIER, BASED ON TYPE STPS20100 | Certificate 272 F rev1 | | Page 04-02 002-1A |

Types covered by similarity:


| ESCC COMP. NO. | VARANTS | RANGE OF COMPONENTS | BASED ON |
|-------------------|---------|------------------------|----------------|
| 5106/016 | 01 | TO254 | STPS20100FSY |
| | 02 | TO254 | STPS20100AFSY |
| | 04 | TO254 | STPS20100SFSY |
| | 05 | SMD.5 | STPS20100S |
| | 06 | SMD1 | STPS20100SA |
| | 07 | SMD1 | STPS20100CSA |
| | 11 | TO254 | STPS20100C2FYT |
| 5106/017 | 01 | SMD.5 | STPS1045S |
| | 02 | SMD.5 | STPS1045CS |
| 5106/018 | 01 | TO254 | STPS6045CFSY |
| | 02 | SMD1 | STPS6045CSA |
| 5106/019 | 02 | TO254 | STPS40100C1FSY |
| | 03 | SMD1 | STPS40100CSA |
| | 05 | TO254 | STPS40100C2FYT |





DIODES, POWER, SCHOTTKY BARRIER,
BASED ON TYPE STPS20H100

Certificate
272 F rev1

Page
04-02
002-1B

| | | | | |
|---|---|--------------------|---------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 5000 Detail ESCC 5103/029 5103/030 5103/031 | ST Microelectronics Rennes France | Qualification | CNES | Aug 2003 |
| Characteristics: 5103/029 variants 01, 03, 04, 05 and 07 are qualified (types BYW81-200) 5103/030 variant 03 is qualified (types BYV52-200) 5103/031 variant 02 to 05 are qualified (types BYV54-200) Maximum Ratings: V_{RRM} : 200 V I_o : 40 A for BYV 54-200, 30 A for BYV52-200, 15 and 30 A for BYW-81-200 T_j : +150°C Package Types TO254, TO254AA and SMD.5 Operating Temperature Range (°C): -55 to +150 | | | | |
|  | DIODES, SILICON, POWER RECTIFIER, HIGH EFFICIENCY, FAST RECOVERY, BASED ON TYPES BYW81, BYV52 AND BYV54 | | Certificate 274 E rev1 | Page 04-02 003-1 |

| | | | | |
|---|---|--------------------------|-----------------------|----------------------------|
| Types covered by similarity: Variant 03 ($\bar{}$ 40 V) | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 5010 Detail ESCC 5512/020 | INFINEON Technologies AG Neubiberg Germany | Qualification | DLR | Sep 1995 |
| Characteristics: Variants 01 and 03 are qualified Maximum Ratings: BAS 70 V_{RR} : $\bar{}$ 70 V I_F : 70 mA I_{FSM} : 85 mA _{pk} @ t<10ms, duty cycle=10% D.C Parameters: $I_R = 100$ nA max @ $V_R = \bar{}$ 56 V $V_{F1} = 0.44$ V max. @ $I_F = 1.0$ mA At room temp. $V_{BR} = 70V$ min @ $I_R = \bar{}$ 10 μ A $V_{F2} = 0.78$ V max. @ $I_F = 10$ mA $V_{F3} = 1.00$ V max. @ $I_F = 15$ mA Package Type T1 P _{tot} =0.25W @ T _{case} = $\bar{}$ 125 °C Operating Temperature Range (°C): $\bar{}$ 55 to $\bar{}$ 150 | | | | |
|  | DIODES, MICROWAVE, SILICON, SCHOTTKY, GENERAL PURPOSE, BASED ON TYPE BAS 70 | Certificate 227 E | | Page 04-05 001-3 |

| | | | | |
|--|--|--------------------------|-----------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 5010 Detail ESCC See types covered by similarity | API Technologies - RF2M Milton Keynes England | Qualification | UK Space Agency | Dec 1993 |
| Characteristics: Operating Temperature Range (°C): -65 to +125 and 150 | | | | |
|  <p>ESCC European Space Components Coordination QPL</p> | DIODES, MICROWAVE, SILICON, PIN AND VARACTORS | Certificate 200 G | Page 04-13 003-1A | |

Types covered by similarity:


| ESCC Spec. No. | Component Type |
|----------------|---|
| 5513/007 | ML4207 to ML 4209, variants 01-03, 06, 08-13, 17, 19, 21-27, 30, 32-37, 41, 43, 45-51, 54, 56-61, 65, 67, 69-72 |
| 5513/009 | ML4610, ML4617 to ML4619, variants 01-03, 06, 08-13, 17, 19, 21-23, 25-28, 31, 33-38, 42, 44, 46-48, 50-53, 56, 58-63, 67, 69, 71-73, 75-78, 81, 83-88, 92, 94, 96-99 |
| 5513/010 | ML4611, ML4612, ML4614, ML4615, variants 01-03, 06, 08-13, 17, 19, 21-23, 25-28, 31, 33-38, 42, 44, 46-48, 50-53, 56, 58-63, 67, 69, 71-73, 75-78, 81, 83-88, 92, 94, 96-99 |
| 5513/014 | ML4622 to ML4624, variants 01-03, 06, 08-13, 17, 19, 21-23, 25-28, 31, 33-38, 42, 45-47, 49-52, 55, 57-58, 61, 63 |
| 5513/015 | ML4627 to ML4629, variants 01-03, 06, 08-13, 17, 19, 21-23, 25-28, 31, 33-38, 42, 45-47, 49-52, 55, 57-58, 61, 63 |
| 5512/001 | ML4402, ML4404 to ML4409 and ML40721, variants 01-03,05, 07-12, 14-18, 20, 22-27, 29-33, 35, 37-42, 44-48, 50, 52-57, 59-63, 65, 67-72, 74-78, 80, 82-84, 86, 88, 90-92 |
| 5512/003 | ML4310 to ML4319, variants 01-02, 05-06, 09-13, 16-17, 20-24, 27-28, 31-35, 38-39, 42-46, 49-50, 53-57, 60-61, 64-68, 71-72, 75-79, 83-85, 89-91, 95 |
| 5512/004 | ML4331 to ML4335, variants 01-02, 05-06, 09-13, 16-17, 20-24, 27-28, 31-35, 38-39, 42-46, 49-50, 53-55 |
| 5512/005 | ML4336 to ML4343, variants 01-02, 06-08, 12-14, 18-20, 24-26, 30-32, 36-38, 42-44, 48 |
| 5512/006 | ML4351 to ML4354, variants 01-02, 05-06, 09-13, 16-17, 20-24, 27-28, 31-35, 38-39, 42-44 |
| 5512/007 | ML4355 to ML4365, variants 01-02, 06-08, 12-14, 18-20, 24-26, 30-32, 36-38, 42-44, 47-48, 51-52, 55-56 |



DIODES,
MICROWAVE, SILICON, PIN AND VARACTORS

Certificate
200 G

Page
04-13
003-1B

| | | | | |
|--|--|---|-----------------------|----------------------------|
| Types covered by similarity: | | Remarks: Certificate 259C has been merged with this certificate beginning February 2012. | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 5010 Detail ESCC Please refer to the next page | COBHAM MICROWAVE Villebon Sur Yvette France | Qualification | CNES | Jun 1995 |
| Characteristics: Refer to the Detail Specifications Operating Temperature Range (°C): -55 to +125 | | | | |
|  | DIODES, MICROWAVE, SILICON, MULTIPLIER AND PIN, BASED ON TYPES DH 2XX AND DH 50XXX | | Certificate 225 F | Page 04-13 003-2A |

Types covered by similarity:


| ESCC Spec. No. | Component Type |
|----------------|---|
| 5513/031 | DH 50151 to DH 50157, Variants 01 to 56 |
| 5513/032 | DH 50033 to DH 50037, Variants 01 to 40 |
| 5513/033 | DH 50201 to DH 50209, Variants 01 to 70 |
| 5513/034 | DH 50251 to DH 50256, Variants 01 to 41 |
| 5513/036 | DH 50052 to DH 50057, Variants 01 to 48 |
| 5513/037 | DH 50071 to DH 50077, Variants 01 to 56 |
| 5513/038 | DH 50101 to DH 50107, Variants 01 to 56 |
| 5512/016 | DH 267, Variants 10 to 15 and 16 |
| 5512/016 | DH 292, Variants 20 to 25 and 26 |
| 5512/016 | DH 256, Variants 30 to 35 and 36 |
| 5512/016 | DH 252, Variants 40 to 45 and 46 |
| 5512/016 | DH 294, Variants 50 to 55 and 56 |





DIODES,
 MICROWAVE, SILICON, MULTIPLIER AND PIN,
 BASED ON TYPES DH 2XX AND DH 50XXX

Certificate
 225 F

Page
 04-13
 003-2B

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|---|--------------------|---|---|----------------------------|----------|---------|----------|----------|---------|----------|----------|---------|----------|----------|---------|----------|----------|---------|----------|----------|----------|----------|----------|----------|----------|--|--|--|--|--|
| Types covered by similarity: | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5010 Detail ESCC 5512/023 | | COBHAM MICROWAVE Villebon Sur Yvette France | Qualification | CNES | Jun 2003 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics: All variants are qualified. <table border="0"> <tr> <td>Maximum Ratings:</td> <td>$V_R = 20$ at $I_R = 10 \mu A$ and $T_{amb} = +25 \text{ }^\circ C$</td> </tr> <tr> <td>Operating Temperature Range ($^\circ C$):</td> <td>-55 to +155</td> </tr> </table> | | | Maximum Ratings: | $V_R = 20$ at $I_R = 10 \mu A$ and $T_{amb} = +25 \text{ }^\circ C$ | Operating Temperature Range ($^\circ C$): | -55 to +155 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Maximum Ratings: | $V_R = 20$ at $I_R = 10 \mu A$ and $T_{amb} = +25 \text{ }^\circ C$ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Operating Temperature Range ($^\circ C$): | -55 to +155 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="0"> <tr> <td>Variants</td> <td>C_j(typ.) (-4 V)</td> <td>Based on Type</td> </tr> <tr> <td>01 to 09</td> <td>1.0 pF</td> <td>DH 76010</td> </tr> <tr> <td>10 to 18</td> <td>1.50 pF</td> <td>DH 76015</td> </tr> <tr> <td>19 to 27</td> <td>2.20 pF</td> <td>DH 76022</td> </tr> <tr> <td>28 to 36</td> <td>2.30 pF</td> <td>DH 76033</td> </tr> <tr> <td>37 to 45</td> <td>4.70 pF</td> <td>DH 76047</td> </tr> <tr> <td>46 to 54</td> <td>6.80 pF</td> <td>DH 76068</td> </tr> <tr> <td>55 to 63</td> <td>10.00 pF</td> <td>DH 76100</td> </tr> <tr> <td>64 to 72</td> <td>15.00 pF</td> <td>DH 76150</td> </tr> </table> | Variants | C_j (typ.) (-4 V) | Based on Type | 01 to 09 | 1.0 pF | DH 76010 | 10 to 18 | 1.50 pF | DH 76015 | 19 to 27 | 2.20 pF | DH 76022 | 28 to 36 | 2.30 pF | DH 76033 | 37 to 45 | 4.70 pF | DH 76047 | 46 to 54 | 6.80 pF | DH 76068 | 55 to 63 | 10.00 pF | DH 76100 | 64 to 72 | 15.00 pF | DH 76150 | | | | | |
| Variants | C_j (typ.) (-4 V) | Based on Type | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 01 to 09 | 1.0 pF | DH 76010 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10 to 18 | 1.50 pF | DH 76015 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 19 to 27 | 2.20 pF | DH 76022 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 28 to 36 | 2.30 pF | DH 76033 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 37 to 45 | 4.70 pF | DH 76047 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 46 to 54 | 6.80 pF | DH 76068 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 55 to 63 | 10.00 pF | DH 76100 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 64 to 72 | 15.00 pF | DH 76150 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | DIODES, MICROWAVE, SILICON, HYPER-ABRUPT JUNCTION TUNING VARACTOR BASED ON TYPES DH 76xxx | | Certificate 273 D | | Page 04-13 003-3 | | | | | | | | | | | | | | | | | | | | | | | | | | |


| | | | | |
|--|---|--------------------------|-----------------------|----------------------------|
| Types covered by similarity: Variant 02 | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 5010 Detail ESCC 5513/017 | INFINEON Technologies AG Neubiberg Germany | Qualification | DLR | Jun 1995 |
| Characteristics: Variants 01 and 02 are qualified Maximum Ratings: V_R : 50 V I_{FM} : 5.0 A @ $t_p=1.0 \mu s$, duty cycle = 0.001% D.C Parameters: $I_{R1} = 10 \mu A$ max @ $V_R = 50 V$ $I_{R2} = 5 nA$ max @ $V_R = 40 V$ $V_F = 1.1 V$ max. @ $I_F = 100 mA$ Package Types T1 ($P_D= 350mW$) and T Operating Temperature Range (°C): -55 to +175 | | | | |
|  | DIODES, MICROWAVE, SILICON, PIN, BASED ON TYPE BXY 42- MESA | Certificate 224 F | | Page 04-16 002-2 |

| | | | | | |
|---|--|--|--------------------|--------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 5010 Detail ESCC 5513/030 | | INFINEON Technologies AG Neubiberg Germany | Qualification | DLR | Oct 1996 |
| Characteristics: Variants 01, 02, 05 and 06 are qualified. BXY 43 (variants 01-02) BXY 44 (variants 05-06) Maximum Ratings: $V_R = \overset{-}{\sim} 150 \text{ V}$ $\overset{-}{\sim} 200 \text{ V}$ $I_F = 400 \text{ mA}$ $P_D = 500 \text{ mW}$ D.C Parameters: $I_R = 100 \text{ nA max @ } V_R = \overset{-}{\sim} 150 \text{ V}$ $5 \text{ nA @ } V_R = \overset{-}{\sim} 100 \text{ V}$ $V_F = 1.0 \text{ V max.}$ $1.05 \text{ V max. @ } I_F = 100 \text{ mA}$ Package Type T, T1 Operating Temperature Range (°C): $\overset{-}{\sim} 55$ to $\overset{+}{\sim} 150$ | | | | | |
|  | | DIODES, MICROWAVE, SILICON, PIN, PLANAR BASED ON TYPES BXY 43 AND 44 | | Certificate 236 F | Page 04-16 003 |

Section 05**Component Type: Filters**

| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|---------------|-------|---------------------|----------------------|
| 05 | | | Feedthrough | |
| | 05-01-001-A-B | 252 G | Types SFC, SFL, SFP | Exxelia Technologies |

**SECTION 05-**: INDEX OF FILTERS****REP005 Updated on 15 Jul 2015**

| | | | | |
|---|---|--------------------------|-----------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3008 Detail ESCC Please refer to the next page | Exxelia Technologies Chanteloup en Brie France | Qualification | CNES | Aug 1998 |
| Characteristics: All variants specified in the Detail Specifications are qualified. Operating Temperature Range (°C): -55 to +125 | | | | |
|  | FILTERS, PI-, C-, AND L- TYPES, FEEDTHROUGH, ELECTROMAGNETIC INTERFERENCE SUPPRESSION, HERMETICALLY AND NON-HERMETICALLY SEALED, BASED ON TYPES SFC, SFL AND SFP | Certificate 252 G | Page 05-01 001-1A | |

Types covered by certificate:

| Domain | Style | Detail Specification | Variants | Capacitance Range (nF) | Rated Current (A) | Rated Voltage (V) |
|--------------------------------|----------|----------------------|----------|------------------------|-------------------|-------------------|
| SFC, Hermetic, Glass Fill | SFC 060 | 3008/026 | 01 to 06 | 0.68 to 220 | 10 | 25 to 200 |
| | SFC 100 | 3008/027 | 01 to 06 | 1.0 to 1000 | 10 | 25 to 200 |
| SFP, Hermetic, Glass Fill | SFP 060 | 3008/021 | 01 to 14 | 2.4 to 89.6 | 10 | 35 to 500 |
| | SFP 100 | 3008/028 | 01 to 06 | 0.16 to 1 312.0 | 10 | 50 to 300 |
| SFL, Hermetic, Glass Fill | SFL 100 | 3008/029 | 01 to 48 | 17.6 to 1 600 | 5, 10, 15 | 40 to 300 |
| Capacitance Range (pF) | | | | | | |
| SFC, Non-Hermetic, Resin Fill | SFC 035 | 3008/031 | 01 to 06 | 470 to 22 000 | 10 | 25 to 200 |
| | SFC 040 | 3008/032 | 01 to 12 | 470 to 22 000 | 10 | 25 to 200 |
| | SFC 060 | 3008/033 | 01 to 12 | 680 to 220 000 | 10 | 25 to 200 |
| SFP, Non-Hermetic, Resin Fill | SFP 035 | 3008/025 | 01 to 20 | 2 400 to 35 200 | 10 | 35 to 200 |
| | SFP 040 | 3008/014 | 01 to 40 | 750 to 4 800 | 10 (DC 7 LF) | 70 to 250 |
| | SFP 060 | 3008/030 | 01 to 28 | 2 400 to 89 600 | 10 | 35 to 500 |
| Capacitance Range (pF) | | | | | | |
| SFC, Mixed fill, for soldering | SFC 030V | 3008/020 | 01 to 12 | 470 to 22 000 | 1.0 to 5.0 | 25 to 200 |



CAPACITOR FILTERS, PI-, C-, AND L- TYPES, FEEDTHROUGH,
 ELECTROMAGNETIC INTERFERENCE SUPPRESSION,
 HERMETICALLY AND NON-HERMETICALLY SEALED,
 BASED ON TYPES SFC, SFL AND SFP


Certificate
 252 G

Page
 05-01
 001-1B

Section 06**Component Type: Fuses**

| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|-----------|-------|------------------|--------------|
| 06-01 | | | Thin film | |
| | 06-01-001 | 284 C | Type MGA-S | Schurter |


**SECTION 06-**: INDEX OF FUSES****REP005 Updated on 15 Jul 2015**


| | | | | |
|---|---|--------------------|-----------------------------------|------------------------------------|
| Types covered by similarity: Variants 02 to 07, 09, 10, 11 | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 4008 Detail ESCC 4008/001 | Schurter Lucerne Switzerland | Qualification | ESA | Jun 2008 |
| <p>Characteristics: Variants 01 to 12 are qualified.</p> <p>Rated Voltage (VAC or VDC): 125/125, 63/125 and 32/125 by variant</p> <p>Rated Current (VAC and VDC): 0.14 to 3.5 A by variant</p> <p>AC Interrupt Current (A): 50 at maximum rated voltage, power factor > 0.95</p> <p>DC Interrupt Current (A): at maximum rated voltage, time constant ≤ 1 ms</p> <p>Variants 01 to 10: 300, Variants 11 and 12: 50</p> <p>Operating Temperature Range, (°C): -50 to +125 (90% I_R to 107% I_R)</p> | | | | |
|  | <p>FUSES, SURFACE MOUNT, THIN FILM, 0.14 TO 3.5 AMPS, BASED ON TYPE MGA-S</p> | | <p>Certificate 284 C</p> | <p>Page 06-01 001</p> |

Section 07**Component Type: Inductors**

| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|-----------|-------|----------------------------------|--------------|
| 07-01 | | | Fixed, RF | |
| | 07-01-001 | 241 G | Types MSC1 10K, 12K, 20K and H01 | Microspire |
| 07-02 | | | Power | |
| | 07-02-002 | 276 E | Types SESI and CMC | Microspire |

**SECTION 07-**: INDEX OF INDUCTORS****REP005 Updated on 15 Jul 2015**


| | | | | | | | | | | |
|---|-------------------------|---|---------|---------------------------------|---------------------------------|--------------------------|-----------------------|----------------------------|------------------------------|--|
| Types covered by similarity: | | | | | | Remarks: | | | | |
| Procurement Specifications | | | | Manufacturer | | Nature of Approval | Supervising Authority | Initial Qualification Date | | |
| Generic ESCC 3201 Detail ESCC 3201/008 | | | | MICROSPIRE Illange France | | Qualification | CNES | Apr 1997 | | |
| Characteristics: Variants 01 to 05 are qualified | | | | | | | | | | |
| Series No. | Range (μH) | Tolerance ($\pm\%$) | Q min. | Min. SRF f_r (MHz) | Max. DCR, R_{dc} (Ω) | | | | Rated DC Current, I_R (mA) | |
| 10k | 0.010- 10 | 2.0, 5.0, 10 | 60 - 42 | 1000 - 33 | 0.025 - 3.3 | | | | 750 - 87 | |
| 12k | 12 - 1000 | 2.0, 5.0, 10 | 56 - 12 | 26 - 1.5 | 2.0 - 120 | | | | 110 - 15 | |
| 20k | 0.010 - 1000 | 10 | 75 - 30 | 1000 - 1.7 | 0.04 - 80 | | | | 1000 - 25 | |
| H01 | 0.380 - 100 | 15 | 30 | 8 | 0.029 - 3.8 | 1500 - 100 | | | | |
| Dielectric Withstanding Voltage (DWV): 200 Vrms | | | | | | | | | | |
| Operating Temperature Range ($^{\circ}\text{C}$): -55 to +125 | | | | | | | | | | |
|  | | INDUCTORS, FIXED, RF, MINIATURE, MOULDED, SURFACE MOUNT, BASED ON SERIES MSC1 10k, 12k, 20k and H01 | | | | Certificate 241 G | | Page 07-01 001 | | |

| | | | | | |
|--|--|--|--------------------|--------------------------|----------------------------|
| Types covered by similarity: | | Remarks: Termination finish shall be Sn90Pb10 | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3201 Detail ESCC 3201/009 3201/010 | | MICROSPIRE Illange France | Qualification | CNES | Apr 2004 |
| Characteristics: 3201/009 Variants 01 to 08 are qualified 3201/010 Variants 01, 03 and 05 are qualified 3201/009 SESI 14 15 15W 18 9.1 22 32WR 32PR Variant 01 02 03 04 05 06 07 08 3201/010 CMC 15 18 22 Variant 01 02 03 Operating Temperature Range (°C): -55 to +125 | | | | | |
|  | | INDUCTORS, POWER, MOULDED, SURFACE MOUNT, BASED ON SERIES SESI AND CMC | | Certificate 276 E | Page 07-02 002 |

Section 08**Component Type: Microcircuits**

| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|-----------------------|-------|------------------|---------------------|
| 08-80 | | | Digital C-MOS | |
| | 08-80-001-2 A to E | 73 P | 4000 B Series | ST Microelectronics |
| | 08-80-002-2 A to F | 190 K | 54HCMOS Series | ST Microelectronics |

**SECTION 08-**: INDEX OF MICROCIRCUITS****REP005 Updated on 15 Jul 2015**

| | | | | | |
|---|--|---|-------------------------|-----------------------|-----------------------------|
| Types covered by similarity: See next pages | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 9000 Detail ESCC See types covered by similarity | | ST Microelectronics Rennes France | Qualification | CNES | Apr 1981 |
| Characteristics: Package Types: Ceramic Dual-in-Line Ceramic Flat Pack | | | | | |
|  | MICROCIRCUITS, DIGITAL, C-MOS-B, 4000B SERIES | | Certificate 73 P | | Page 08-80 001-2A |

Types covered by similarity:

| ESCC Spec. No. | Component Type | Component Type |
|----------------|---|----------------|
| 9201/041 | Quad 2-input NOR gate | 4001B |
| 9201/042 | Dual 4-input NOR gate | 4002B |
| 9202/039 | 4-bit full adder | 4008B |
| 9201/043 | Quad 2-input NAND gate | 4011B |
| 9201/044 | Dual 4-input NAND gate | 4012B |
| 9203/023 | Dual D-type flip-flop | 4013B |
| 9306/014 | 8-stage synchronous static shift register | 4014B |
| 9306/015 | Dual 4-stage static shift register with serial input/parallel input | 4015B |
| | | |
| 9204/020 | Decade counter/divider | 4017B |
| 9204/021 | Presettable divide-by-N counter | 4018B |
| 9202/051 | Quad AND/OR select gate | 4019B |
| 9204/022 | 14-stage ripple carry binary counter/divider | 4020B |
| 9306/016 | 8-stage static shift register | 4021B |
| 9204/023 | Octal counter/divider | 4022B |
| 9201/045 | Triple 3-input NAND gates | 4023B |
| 9204/024 | 7-stage ripple carry binary counter/divider | 4024B |
| 9201/046 | Triple 3-input NOR gate | 4025B |
| | | |
| 9203/022 | Dual J-K master slave flip-flop | 4027B |



MICROCIRCUITS, DIGITAL,
C-MOS-B, 4000B SERIES

Certificate

73 P

Page

08-80
001-2B

Types covered by similarity:

| ESCC Spec. No. | Component Type | Component Type |
|----------------|--|----------------|
| 9205/010 | BCD-to-decimal or binary-to-octal decoder | 4028B |
| 9204/025 | Presettable up/down counter binary or BCD decade | 4029B |
| 9201/047 | Quad 2-input exclusive OR gates | 4030B |
| | | |
| 9306/025 | 8-stage static bidirectional parallel/serial input/output bus register with 3 state output | 4034B |
| | | |
| 9204/026 | 12-stage ripple carry binary counter/divider | 4040B |
| 9202/040 | Quad true/complement buffer with unbuffered outputs | 4041UB |
| 9202/041 | Quad clocked D latch | 4042B |
| 9202/042 | Quad NOR 3-state R/S latches | 4043B |
| 9202/043 | Quad NAND 3-state R/S latch | 4044B |
| 9202/044 | Micropower phase-locked loop | 4046B |
| 9207/003 | Low power monostable/astable multivibrator | 4047B |
| 9202/045 | Hex buffer/converter (inverting type) | 4049UB |
| 9202/046 | Hex buffer/converter (non-inverting type) | 4050B |
| 9202/047 | Analogue multiplexer/demultiplexer | 4051B |
| 9202/048 | Analogue multiplexer/demultiplexer | 4052B |
| 9202/049 | Triple 2-channel analogue multiplexer/demultiplexer | 4053B |
| 9209/001 | 4-bit magnitude comparator | 4063B |
| 9204/052 | 14-stage ripple-carry binary counter/divider and oscillator | 4060B |



MICROCIRCUITS, DIGITAL,
C-MOS-B, 4000B SERIES

Certificate

73 P

Page

08-80
001-2C

| Types covered by similarity: | | |
|------------------------------|--|----------------|
| ESCC Spec. No. | Component Type | Component Type |
| 9408/005 | Quad bilateral switch | 4066B |
| 9408/009 | Analogue multiplexer/demultiplexer | 4067B |
| 9201/061 | 8-input NAND gate | 4068B |
| 9401/010 | Hex inverter | 4069UB |
| 9201/048 | Quad exclusive OR gate | 4070B |
| 9201/063 | Quad 2-input OR gate | 4071B |
| 9201/082 | Dual 4-input OR gate | 4072B |
| 9201/064 | Triple 3-input AND gate | 4073B |
| 9201/065 | Triple 3-input OR gate | 4075B |
| 9306/022 | 4-bit D-type register with 3-state output | 4076B |
| 9201/055 | Quad exclusive NOR gate | 4077B |
| 9201/062 | 8-input OR/NOR gate | 4078B |
| 9201/052 | Quad 2-input AND gate | 4081B |
| 9201/066 | Dual 4-input AND gate | 4082B |
| | | |
| 9409/002 | Quad 2-input NAND gate with Schmitt trigger input | 4093B |
| 9306/026 | 8-stage shift and store bus register with synchronous serial outputs and 3-state parallel output | 4094B |
| 9206/003 | Dual monostable multivibrator | 4098B |
| | | |
| | | |



MICROCIRCUITS, DIGITAL,
C-MOS-B, 4000B SERIES

Certificate

73 P

Page

08-80
001-2D

Types covered by similarity:

| ESCC Spec. No. | Component Type | Component Type |
|----------------|--|----------------|
| 9401/030 | Hex non-inverting buffers with 3-state output | 4503B |
| 9408/006 | 8-channel multiplexer with 3-state output | 4512B |
| 9408/012 | 4-bit latch/4-to-16 decoder | 4514B |
| 9205/011 | 4-bit latch/4-to-16 line decoder | 4515B |
| 9204/045 | Synchronous quad presettable up/down binary counter | 4516B |
| 9204/028 | Dual binary up counter | 4520B |
| 9202/065 | 8-bit priority encoder | 4532B |
| 9207/007 | Dual monostable multivibrator with reset | 4538B |
| 9408/011 | Dual 1-of-4 decoder/demultiplexer | 4555B |
| 9408/025 | Dual 1-of-4 decoder/demultiplexer (output low on select) | 4556B |
| 9204/036 | Presettable 8-bit synchronous down-counter | 40103B |
| 9409/005 | Hex Schmitt-trigger | 40106B |
| 9401/013 | Dual 2-input NAND buffer/driffer | 40107B |
| 9407/003 | Quad low-to-high 3-state voltage level shifter | 40109B |
| 9204/054 | Programmable 4-bit binary counter with asynchronous clear | 40161B |
| 9203/038 | Hex D-type flip-flop | 40174B |
| 9204/041 | Presettable binary up/down counter (dual clock with reset) | 40193B |




MICROCIRCUITS, DIGITAL,
C-MOS-B, 4000B SERIES

Certificate

73 P

Page

08-80
001-2E

| | | | | | |
|---|--|---|--------------------|--------------------------|-----------------------------|
| Types covered by similarity: See next pages | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 9000 Detail ESCC See types covered by similarity | | ST Microelectronics Rennes France | Qualification | CNES | Nov 1992 |
| Characteristics: Qualified Packages: <ul style="list-style-type: none"> • Ceramic Dual-in-Line • Ceramic Flat Pack NOTES 1. These parts have successfully passed radiation testing to 50 kRads. | | | | | |
|  | | MICROCIRCUITS, DIGITAL, MONOLITHIC, HIGH SPEED CMOS, 54HC AND 54HCT SERIES | | Certificate 190 K | Page 08-80 002-2A |

Types covered by similarity:

| ESCC Spec. No. | Component Type | Component Type | Note |
|----------------|---|----------------|------|
| 9201/105 | Quad 2-input NAND gate | 54HC 00 | 1 |
| 9201/113 | Quad 2-input NOR gate | 02 | 1 |
| 9201/114 | Quad 2-input NAND gate with open drain output | 03 | 1 |
| 9401/033 | Hex inverter | 04 | 1 |
| 9201/106 | Quad 2-input positive AND gate | 08 | 1 |
| 9201/107 | Triple 3-input NAND gate | 10 | 1 |
| 9201/117 | Triple 3-input AND gate | 11 | 1 |
| 9409/007 | Hex Schmitt trigger inverter | 14 | 1 |
| 9201/118 | Dual 4-input NAND gate | 20 | 1 |
| 9201/108 | Dual 4-input AND gate | 21 | 1 |
| 9201/109 | Triple 3-input NOR gate | 27 | 1 |
| 9201/110 | 8-input NAND gate | 30 | 1 |
| 9201/111 | Quad 2-input OR gate | 32 | 1 |
| 9203/050 | Dual D-type flip-flop with preset and clear | 74 | 1 |
| 9209/004 | 4-bit magnitude comparator | 85 | 1 |
| 9201/119 | Quad 2-input exclusive OR gate | 86 | 1 |
| | | | |



MICROCIRCUITS, DIGITAL, MONOLITHIC,
HIGH SPEED CMOS, 54HC AND 54HCT SERIES

Certificate

190 K

Page

08-80
002-2B

Types covered by similarity:

| ESCC Spec. No. | Component Type | Component Type | Note |
|----------------|--|----------------|------|
| 9306/048 | Dual J-K positive edge triggered flip-flop with preset and clear | 54HC 109 | 1 |
| 9207/006 | Dual positive or negative edge Schmitt-retriggerable monostable multivibrator with clear | 123 | 1 |
| 9401/039 | Quad bus buffer with 3 state output | 125 | 1 |
| 9201/120 | Quad 2-input NAND gate with Schmitt-trigger input | 132 | 1 |
| 9205/013 | 3-to-8 line decoder/demultiplexer with address latch and inverted output | 137 | 1 |
| 9408/046 | 3-to-8 line decoder/demultiplexer with inverted output | 138 | 1 |
| 9205/017 | Dual 2-to-4 line decoder/demultiplexer with inverted output | 139 | 1 |
| 9410/017 | 8-line to 3-line priority encoder | 148 | 1 |
| 9408/054 | 8-line to 1-line data selector/multiplexer | 151 | 1 |
| 9408/038 | Dual 4-line to 1-line data selectors/multiplexer | 153 | 1 |
| 9205/023 | 4-to-16 line decoder/demultiplexer with inverted output | 154 | 1 |
| 9408/057 | Quad 2-line to 1-line data selector/multiplexer | 157 | 1 |
| 9408/059 | Quad 2-line to 1-line data selector/multiplexer with inverted output | 158 | 1 |
| 9204/062 | Synchronous presettable 4-bit decade counter with direct clear | 160 | 1 |
| 9204/059 | Asynchronous 4-bit binary counter | 161 | 1 |
| 9306/041 | 8-bit SIPO shift register | 164 | 1 |
| 9306/042 | 8-bit PISO shift register | 165 | 1 |



MICROCIRCUITS, DIGITAL, MONOLITHIC,
HIGH SPEED CMOS, 54HC AND 54HCT SERIES

Certificate

190 K

Page

08-80
002-2C

Types covered by similarity:

| ESCC Spec. No. | Component Type | Component Type | Note |
|----------------|---|----------------|------|
| 9306/043 | 8-bit PISO shift register | 54HC 166 | 1 |
| 9306/052 | Hex D-type edge-triggered flip-flop with clear | 174 | 1 |
| 9203/052 | Quad D-type edge-triggered flip-flop with clear | 175 | 1 |
| 9204/066 | Synchronous 4-bit up/down binary counter | 191 | 1 |
| 9204/065 | Synchronous 4-bit up/down binary counter (dual clock with clear) | 193 | 1 |
| 9306/047 | 4-bit PIPO shift register | 194 | 1 |
| 9205/021 | 3-line to 8-line decoder/demultiplexer with address latch | 237 | 1 |
| 9401/034 | Octal bus buffer with inverted 3-state output | 240 | 1 |
| 9401/048 | Octal bus buffer with 3-state output | 244 | 1 |
| 9405/013 | Octal bus transceiver with 3-state output | 245 | 1 |
| 9408/048 | 1-to-8 data selector/multiplexer with 3-state output | 251 | 1 |
| 9408/047 | Quad 2-line to 1-line data selector/multiplexer with 3-state output | 257 | 1 |
| 9203/073 | 8-bit addressable latch | 259 | 1 |
| 9203/053 | Octal D-type edge-triggered flip-flop with clear | 273 | 1 |
| 9208/003 | 9-bit odd/even parity generator/checker | 280 | 1 |



MICROCIRCUITS, DIGITAL, MONOLITHIC,
HIGH SPEED CMOS, 54HC AND 54HCT SERIES

Certificate

190 K

Page

08-80
002-2D

Types covered by similarity:

| ESCC Spec. No. | Component Type | Component Type | Note |
|----------------|--|----------------|------|
| 9202/075 | 4-bit binary full adder with fast carry | 54HC 283 | 1 |
| 9401/044 | Hex bus buffer with 3-state output | 367 | 1 |
| 9203/059 | Octal D-type transparent latch with 3-state output | 373 | 1 |
| 9203/060 | Octal D-type edge-triggered flip-flop with 3-state output | 374 | 1 |
| 9204/074 | Dual 4-bit negative edge-triggered binary counter | 393 | 1 |
| 9401/049 | Octal bus buffer with inverted 3-state output | 540 | 1 |
| 9401/047 | Octal bus buffer with 3-state output | 541 | 1 |
| 9202/072 | Octal D-type transparent latch with 3-state output | 573 | 1 |
| 9203/054 | Octal D-type edge-triggered flip-flop with 3-state output | 574 | 1 |
| 9204/071 | 8-bit binary counter with 3-state output register | 590 | 1 |
| 9306/051 | 8-bit shift register with 3-state output register | 595 | 1 |
| 9306/054 | 8-bit PISO shift register | 597 | 1 |
| 9209/005 | 8-bit identify comparator | 688 | 1 |
| 9204/070 | Asynchronous negative-edge-triggered 14-bit binary counter | 4020 | 1 |
| 9204/069 | Asynchronous negative edge-triggered 12-bit binary counter | 4040 | 1 |
| 9401/037 | Hex buffer/converter with inverted output | 4049 | 1 |
| 9401/038 | Hex buffer/converter | 4050 | 1 |



MICROCIRCUITS, DIGITAL, MONOLITHIC,
HIGH SPEED CMOS, 54HC AND 54HCT SERIES

Certificate

190 K

Page

08-80
002-2E

Types covered by similarity:

| ESCC Spec. No. | Component Type | Component Type | Note |
|----------------|---|----------------|------|
| 9408/064 | Analogue multiplexer/demultiplexer | 54HC 4051 | 1 |
| 9408/065 | Analogue multiplexer/demultiplexer (triple 2-channel) | 4053 | 1 |
| 9204/076 | Asynchronous negative-edge-triggered 14-bit binary counter and oscillator | 4060 | 1 |
| 9408/052 | Quad bilateral switch | 4066 | 1 |
| 9201/123 | 8-input OR/NOR gate | 4078 | 1 |
| 9306/050 | 8-bit SIPO shift latch register with 3-state output | 4094 | 1 |
| 9205/019 | 4-to-16 line decoder/latch | 4514 | 1 |
| 9203/070 | Dual D-type flip-flop with preset and clear | 54HCT 74 | 1 |
| 9402/009 | Octal bus buffer with 3-state output | 244 | 1 |
| 9405/014 | Octal bus transceiver with 3-state output | 245 | 1 |
| 9203/064 | Octal D-type transparent latch with 3-state output | 373 | 1 |



MICROCIRCUITS, DIGITAL, MONOLITHIC,
HIGH SPEED CMOS, 54HC AND 54HCT SERIES

Certificate

190 K

Page

08-80
002-2F

Section 09


Component Type: Relays


| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|-------------|-------|------------------------------------|----------------|
| 09-01 | | | Non-Latching, 28Vdc Contact Rating | |
| | 09-01-001 | 102 G | Type T** | REL STPI |
| | 09-01-002 | 02 M | Type GP5 | LEACH |
| | 09-01-004 | 205 E | Type E 215 | REL STPI |
| | 09-01-004-3 | 318 A | Type M300 | LEACH Sarralbe |
| 09-02 | | | Latching, 28Vdc Contact Rating | |
| | 09-02-001 | 88 H | Type TL | REL STPI |
| | 09-02-002 | 13 M | Type GP2 | LEACH |
| | 09-02-003 | 98 F | Type EL415 | REL STPI |
| | 09-02-003-3 | 317 A | Type M402 | LEACH Sarralbe |
| | 09-02-004 | 167 F | Type EL215 | REL STPI |
| | 09-02-004-3 | 310 B | Type M302 | LEACH Sarralbe |
| 09-03 | | | Latching, 50Vdc Contact Rating | |
| | 09-03-001 | 93 L | Type GP250 | LEACH |





SECTION 09-**: INDEX OF RELAYS


REP005 Updated on 15 Jul 2015


| | | | | | |
|--|--|---|--------------------|--------------------------|----------------------------|
| Types covered by similarity: Rated Coil Voltages 5, 6, 9, 12 and 18 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3601 Detail ESCC 3601/002 | | REL-STPI St Jean de la Ruelle France | Qualification | CNES | Feb 1983 |
| Characteristics: Variants 01 to 06 are qualified Contact Rating 1A at 28Vdc Contact Configuration 2PDT Package Type TO-5 Can Coil Voltage 5 - 26.5 Vdc Operating Temperature Range (°C): -65 to +125 | | | | | |
|  | | RELAY, NON-LATCHING, ELECTROMAGNETIC, TYPE T ** | | Certificate 102 G | Page 09-01 001 |


| | | | | | |
|---|--|---|--------------------|-------------------------|----------------------------|
| Types covered by similarity: Coil Voltages 6 and 12 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3601 Detail ESCC 3601/003 | | LEACH International Europe Niort France | Qualification | CNES | Apr 1978 |
| Characteristics: Variants 01 to 08 are qualified Contact Rating 2 A at 28 Vdc Contact Configuration 2 PDT Package Type Half-crystal can Coil Voltage 26.5 Vdc Operating Temperature Range (°C): -65 to +125 | | | | | |
|  | | RELAY, NON-LATCHING, ELECTROMAGNETIC, TYPE GP 5 | | Certificate 02 M | Page 09-01 002 |


| | | | | | |
|---|--|--|--------------------|--------------------------|----------------------------|
| Types covered by similarity: Coil Voltage 12 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3601 Detail ESCC 3601/007 | | REL STPI St Jean de la Ruelle France | Qualification | CNES | Jan 1994 |
| Characteristics: Variants 03, 04 and 06 are qualified Contact Rating 15 A at 28 Vdc Contact Configuration 2 PDT Package Type Half cubic inch can Coil Voltage 12 and 28 Vdc Operating Temperature Range (°C): -65 to +125 | | | | | |
|  | | RELAY, NON-LATCHING, ELECTROMAGNETIC, TYPE E 215 | | Certificate 205 E | Page 09-01 004 |


| | | | | | |
|---|--|---|--------------------|--------------------------|----------------------------|
| Types covered by similarity: Coil Voltage 12 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3601 Detail ESCC 3601/007 | | LEACH Sarralbe France | Qualification | CNES | Feb 2012 |
| Characteristics: Variants 03, 04 and 06 are qualified Contact Rating 15 A at 28 Vdc Contact Configuration 2 PDT Package Type Half cubic inch can Coil Voltage 12 and 28 Vdc Operating Temperature Range (°C): -65 to +125 | | | | | |
|  | | RELAY, NON-LATCHING, ELECTROMAGNETIC, TYPE M300 | | Certificate 318 A | Page 09-01 004-3 |


| | | | | | |
|---|--|---|--------------------|-------------------------|----------------------------|
| Types covered by similarity: Rated Coil Voltages 5, 6, 9, 12 and 18 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3602 Detail ESCC 3602/002 | | REL-STPI Saint Jean de la Ruelle France | Qualification | CNES | Jan 1982 |
| Characteristics: Variants 01 to 06 are qualified Contact Rating 1 A at 28 Vdc Contact Configuration 2 PDT Package Type TO-5 Can Coil Voltage 26.5 Vdc Operating Temperature Range (°C): -65 to +125 | | | | | |
|  | | RELAY, LATCHING, ELECTROMAGNETIC, TYPE TL | | Certificate 88 H | Page 09-02 001 |


| | | | | | |
|--|--|---|--------------------|-------------------------|----------------------------|
| Types covered by similarity: Coil Voltages 6 and 12 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3602 Detail ESCC 3602/003 | | LEACH International Europe Niort France | Qualification | CNES | Jan 1979 |
| Characteristics: Variants 01 to 08 are qualified Contact Rating 2 A at 28 Vdc Contact Configuration 2 PDT Package Type Half-size crystal can Coil Voltage 26.5 Vdc Operating Temperature Range (°C): -65 to +125 | | | | | |
|  | | RELAY, LATCHING, ELECTROMAGNETIC, TYPE GP 2 | | Certificate 13 M | Page 09-02 002 |

| | | | | | |
|---|--|---|--------------------|-------------------------|----------------------------|
| Types covered by similarity: Coil voltage : 12 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3602 | | REL STPI St Jean de la Ruelle France | Qualification | CNES | Nov 1982 |
| Detail ESCC 3602/004 | | | | | |
| Characteristics: Variants 04, 06 and 09 and 14, 16 and 19 are qualified Contact Rating 15 A at 28 Vdc Contact Configuration 4PDT Package Type Cubic inch can Coil Voltage 28 Vdc Operating Temperature Range (°C): -65 to +125 | | | | | |
|  | | RELAY, LATCHING, ELECTROMAGNETIC, TYPE EL 415 | | Certificate 98 F | Page 09-02 003 |

| | | | | | |
|--|--|---|--------------------|--------------------------|----------------------------|
| Types covered by similarity: Coil voltage : 12 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3602 | | LEACH Sarralbe France | Qualification | CNES | Feb 2012 |
| Detail ESCC 3602/004 | | | | | |
| Characteristics: Variants 04, 06 and 09 and 14, 16 and 19 are qualified Contact Rating 15 A at 28 Vdc Contact Configuration 4PDT Package Type Cubic inch can Coil Voltage 28 Vdc Operating Temperature Range (°C): -65 to +125 | | | | | |
|  | | RELAY, LATCHING, ELECTROMAGNETIC, TYPE M402 | | Certificate 317 A | Page 09-02 003-3 |

| | | | | | | |
|--|--|---|--------------------|--------------------------|----------------------------|--------------------------|
| Types covered by similarity: Coil voltage : 12 Vdc | | Remarks: | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | |
| Generic ESCC 3602 | | REL STPI St Jean de la Ruelle France | Qualification | CNES | Feb 1990 | |
| Detail ESCC 3602/009 | | | | | | |
| Characteristics: Variants 03, 04 and 06 and 13, 14 and 16 are qualified Contact Rating 15 A at 28 Vdc Contact Configuration 2PDT Package Type Half-cubic inch can Coil Voltage 28 Vdc Operating Temperature Range (°C): -65 to +125 | | | | | | |
|  | | RELAY, LATCHING, ELECTROMAGNETIC, TYPE EL 215 | | Certificate 167 F | | Page 09-02 004 |


| | | | | | |
|---|--|--|--------------------|--------------------------|----------------------------|
| Types covered by similarity: Coil voltage : 12 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3602 | | LEACH Sarralbe France | Qualification | CNES | Apr 2011 |
| Detail ESCC 3602/009 | | | | | |
| Characteristics: Variants 03, 04 and 06 and 13, 14 and 16 are qualified Contact Rating 15 A at 28 Vdc Contact Configuration 2PDT Package Type Half-cubic inch can Coil Voltage 28 Vdc Operating Temperature Range (°C): -65 to +125 | | | | | |
|  | | RELAY, LATCHING, ELECTROMAGNETIC, BASED ON TYPE M302 | | Certificate 310 B | Page 09-02 004-3 |


| | | | | | |
|---|--|---|--------------------|-------------------------|----------------------------|
| Types covered by similarity: Coil Voltage 12 Vdc | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3602 Detail ESCC 3602/010 | | LEACH International Europe Niort France | Qualification | CNES | Feb 1982 |
| Characteristics: Variants 01 to 06 are qualified Contact Rating 2 A at 50 Vdc (100000 ops) Contact Configuration 2 PDT Package Type Half-size crystal can Coil Voltage 26.5 Vdc Operating Temperature Range (°C): -65 to +125 | | | | | |
|  | | RELAY, LATCHING, ELECTROMAGNETIC, TYPE GP 250 | | Certificate 93 L | Page 09-03 001 |


Section 10


Component Type: Resistors

| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|---------------------|-------|-----------------------------|--------------------------|
| 10-07 | | | Shunts | |
| | 10-07-001 | 285 C | Types SMV-PW and SM*-PT | Isabellenhütte |
| 10-08 | | | Fixed, Film | |
| | 10-08-006 | 256 G | Surface Mount, Type MS1 | Vishay Electronic (Selb) |
| | 10-08-007 | 289 C | Surface Mount, Type TNPS | Vishay Electronic (Selb) |
| 10-09 | | | Chip | |
| | 10-09-002 A to D | 287 D | Type PHR; PFRR; PRAHR/CNWHR | Vishay S.A. Sfernice |
| | 10-09-003 | 314 A | Type CHP | Vishay S.A. Sfernice |
| 10-11 | | | Flexible, Foil, Heaters | |
| | 10-11-001-1 | 184 K | Single & Double Layer | IRCA |
| | 10-11-002 | 325 A | Single & Double Layer | Minco |
| | 10-11-003 | 330 | Single & Double Layer | IRCA |

| Types covered by similarity: Tolerance (%) = ±1 | | Remarks: the extension of qualification in 2014 did not maintain in the qualified scope the SMR type due to low sales. | | |
|--|--|--|--------------------------|----------------------------|
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 4001 Detail ESCC 4001/027 4001/028 | ISABELLENHÜTTE HEUSLER GmbH & Co. KG Dillenburg Germany | Qualification | DLR | Nov 2008 |
| Characteristics: ESCC 4001/027 variants 01, 02 and 03 are qualified (SMP-PW, SMS-PW, SMT-PW) ESCC 4001028 variant 02 is qualified (SMV-PW) Operating Temperature Range, (°C): -55 to 170C | | | | |
|  | RESISTORS, FIXED, CHIP, METAL FOIL, BASED ON TYPES SMV-PW AND SM*-PT | Certificate 285 C | Page 10-07 001 | |

| Types covered by similarity: Tolerance ($\pm\%$) = 0.1, 0.5, 1.0 | | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|------------------|---|------------------|-------------------------------|-----------------------|----------------------------|-----|----|-----|----------------|-----|----------------|-----|----------------|-----|----|-----|----------------|-----|----------------|-----|-----------------|-----|----|-----|-----------------|-----|---|--|--|--|
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 4001 Detail ESCC 4001/022 | | VISHAY Electronic GmbH Division Draloric Selb Germany | | Qualification | DLR | Oct 1999 | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics: Critical R = 160 k Ω | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>Range (Ω)</th> <th>Tol. ($\pm\%$)</th> <th>TC (\pmppm/$^{\circ}$C)</th> <th>Value Series</th> </tr> </thead> <tbody> <tr> <td>43.2 - 1.004 M</td> <td>0.1</td> <td rowspan="3">50</td> <td rowspan="3">E96</td> </tr> <tr> <td>10.0 - 1.004 M</td> <td>0.5</td> </tr> <tr> <td>2.20 - 5.114 M</td> <td>1.0</td> </tr> <tr> <td>43.2 - 1.004 M</td> <td>0.1</td> <td rowspan="3">25</td> <td rowspan="3">E96</td> </tr> <tr> <td>10.0 - 1.004 M</td> <td>0.5</td> </tr> <tr> <td>10.0 - 1.004 M</td> <td>1.0</td> </tr> <tr> <td>43.2 - 0.2213 M</td> <td>0.1</td> <td rowspan="2">15</td> <td rowspan="2">E96</td> </tr> <tr> <td>10.0 - 0.5113 M</td> <td>0.5</td> </tr> </tbody> </table> | | Range (Ω) | Tol. ($\pm\%$) | TC (\pm ppm/ $^{\circ}$ C) | Value Series | 43.2 - 1.004 M | 0.1 | 50 | E96 | 10.0 - 1.004 M | 0.5 | 2.20 - 5.114 M | 1.0 | 43.2 - 1.004 M | 0.1 | 25 | E96 | 10.0 - 1.004 M | 0.5 | 10.0 - 1.004 M | 1.0 | 43.2 - 0.2213 M | 0.1 | 15 | E96 | 10.0 - 0.5113 M | 0.5 | Operating Temperature Range, ($^{\circ}$ C): -55 to +125 | | | |
| Range (Ω) | Tol. ($\pm\%$) | TC (\pm ppm/ $^{\circ}$ C) | Value Series | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 43.2 - 1.004 M | 0.1 | 50 | E96 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10.0 - 1.004 M | 0.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.20 - 5.114 M | 1.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 43.2 - 1.004 M | 0.1 | 25 | E96 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10.0 - 1.004 M | 0.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10.0 - 1.004 M | 1.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 43.2 - 0.2213 M | 0.1 | 15 | E96 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10.0 - 0.5113 M | 0.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | RESISTORS, FILM, FIXED, SURFACE MOUNT, NON-HERMETICALLY SEALED, BASED ON TYPE MS1 | | Certificate 256 G | | Page 10-08 006 | | | | | | | | | | | | | | | | | | | | | | | | | |

| Types covered by similarity: Temperature Coefficient (\pm ppm/ $^{\circ}$ C): 25, 50 Tolerance (\pm %) = 0.5, 1.0 | | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|----------------|------------------------|--|----------------------|--------------------|--|-----------------------------------|--------------------------|----------------|------------------------|--|----------------------|--------------|--|-----------------------------------|----------------|------------------|-------------------|----|------|----|-------|-------------|-----|------------|-------|-------|----|------|----|-------|-------------|-----|------------|-----|-------|----|------|----|---|-------------|-----|------------|-----|-------|
| Procurement Specifications | | | Manufacturer | | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 4001 Detail ESCC 4001/029 | | | VISHAY Electronic Division Draloric Selb Germany | | Qualification | DLR | May 2009 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Characteristics: Variants 01 to 03 inclusive are qualified E96 Series</p> <table border="1"> <thead> <tr> <th rowspan="2">Variant Number</th> <th rowspan="2">Style (Note 1)</th> <th colspan="2">Resistance Range R_n</th> <th rowspan="2">Tolerance (\pm %)</th> <th rowspan="2">Value Series</th> <th rowspan="2">Temperature Coefficient TC ($\pm 10^{-6}/^{\circ}$C)</th> <th rowspan="2">Critical Resistance (kΩ)</th> <th rowspan="2">Weight max (g)</th> </tr> <tr> <th>Min (Ω)</th> <th>Max (MΩ)</th> </tr> </thead> <tbody> <tr> <td>01</td> <td>0603</td> <td>10</td> <td>0.221</td> <td>0.1, 0.5, 1</td> <td>E96</td> <td>15, 25, 50</td> <td>56.25</td> <td>0.002</td> </tr> <tr> <td>02</td> <td>0805</td> <td>10</td> <td>0.422</td> <td>0.1, 0.5, 1</td> <td>E96</td> <td>15, 25, 50</td> <td>180</td> <td>0.006</td> </tr> <tr> <td>03</td> <td>1206</td> <td>10</td> <td>1</td> <td>0.1, 0.5, 1</td> <td>E96</td> <td>15, 25, 50</td> <td>160</td> <td>0.008</td> </tr> </tbody> </table> <p>Operating Temperature Range, ($^{\circ}$C): -55 to +125</p> | | | | | | | | Variant Number | Style (Note 1) | Resistance Range R_n | | Tolerance (\pm %) | Value Series | Temperature Coefficient TC ($\pm 10^{-6}/^{\circ}$ C) | Critical Resistance (k Ω) | Weight max (g) | Min (Ω) | Max (M Ω) | 01 | 0603 | 10 | 0.221 | 0.1, 0.5, 1 | E96 | 15, 25, 50 | 56.25 | 0.002 | 02 | 0805 | 10 | 0.422 | 0.1, 0.5, 1 | E96 | 15, 25, 50 | 180 | 0.006 | 03 | 1206 | 10 | 1 | 0.1, 0.5, 1 | E96 | 15, 25, 50 | 160 | 0.008 |
| Variant Number | Style (Note 1) | Resistance Range R_n | | Tolerance (\pm %) | Value Series | Temperature Coefficient TC ($\pm 10^{-6}/^{\circ}$ C) | Critical Resistance (k Ω) | | | Weight max (g) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | Min (Ω) | Max (M Ω) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 01 | 0603 | 10 | 0.221 | 0.1, 0.5, 1 | E96 | 15, 25, 50 | 56.25 | 0.002 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 02 | 0805 | 10 | 0.422 | 0.1, 0.5, 1 | E96 | 15, 25, 50 | 180 | 0.006 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 03 | 1206 | 10 | 1 | 0.1, 0.5, 1 | E96 | 15, 25, 50 | 160 | 0.008 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | | RESISTORS, FILM, FIXED, SURFACE MOUNT, NON-HERMETICALLY SEALED, BASED ON TYPE TNPS | | | Certificate 289 C | | Page 10-08 007 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | | | |
|---|--|--|--------------------|--------------------------|----------------------------|
| Types covered by similarity: | | Remarks: Components under ESCC QML qualification. Refer to Technology Flow description in REF006. | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 4001 Detail ESCC 4001/023 ESCC 4001/025 | | VISHAY S.A. Division Sfernice Nice France | Qualification | CNES | Feb 2009 |
| Characteristics and qualified variants: Refer to tables on the next page. 4001/023 PHR High Stability and Precision Chip 4001/023 PFRR High Stability and Precision Chip with Established Reliability Level R 4001/025 PRA/CNWHR High Stability and Precision Surface Mount Array Operating Temperature Range, (°C): -55 to +155 Lead material is E with either Type 2 or Type 4 finish. The terminal material and finish of some of these variants makes them unsuitable for solder assembly methods . They shall be assembled using glue or wire bond techniques. See Detail specifications. | | | | | |
|  | | RESISTORS, FILM, FIXED, CHIP AND ARRAY, THIN FILM, BASED ON TYPES PHR; PFRR; PRAHR/CNWHR | | Certificate 287 D | Page 10-09 002A |

Characteristics: Type PHR, Variants 01 to 08, 13 and 14 are qualified:

| Detail Specification | Style | Critical R (kΩ) | Rated Dissipation (W) | Limiting Element Voltage (V) | Type Variant |
|----------------------|-------|-----------------|-----------------------|------------------------------|--------------|
| 4001/023 | 0402 | 18 | 0.050 | 30 | 13; 14 |
| | 0603 | 12.25 | 0.100 | 35 | 01; 05 |
| | 0805 | 45 | 0.125 | 75 | 02; 06 |
| | 1206 | 40 | 0.250 | 100 | 03; 07 |
| | 2010 | 45 | 0.500 | 150 | 04; 08 |

| Variant | Style | Resistance Range (Note 1) | | Tolerance (±%) (Note 2) | Temperature Coefficient (10 ⁻⁶ /°C) (Note 2) | Weight (g) |
|---------|-------|---------------------------|-------------------------------|-------------------------|---|------------|
| | | Min (Ω) | Max (MΩ) | | | |
| 01, 05 | 0603 | 10 | 0.200 (0.160 for TC « C ») | 0.01; 0.02; 0.05; 0.1 | ±5; ±10; ±25 | 0.003 |
| 02, 06 | 0805 | 10 | 0.250 | 0.01; 0.02; 0.05; 0.1 | ±5; ±10; ±25 | 0.004 |
| 03, 07 | 1206 | 10 | 1.000 | 0.01; 0.02; 0.05; 0.1 | ±5; ±10; ±25 | 0.01 |
| 04, 08 | 2010 | 10 | 3.000 | 0.01; 0.02; 0.05; 0.1 | ±5; ±10; ±25 | 0.03 |
| 13, 14 | 0402 | 10 | 0.100 (0.067 for TC « C ») | 0.01; 0.02; 0.05; 0.1 | ±5; ±10; ±25 | 0.002 |

NOTES

1.

| Variant | Style | Critical Resistance (KΩ) |
|---------|-------|--------------------------|
| 01 – 05 | 0603 | 12.25 |
| 02 – 06 | 0805 | 45 |
| 03 – 07 | 1206 | 40 |
| 04 – 08 | 2010 | 45 |
| 13 - 14 | 0402 | 18 |

2.

| Resistance (Ω) | Available Tolerances (±%) | Series |
|----------------|---------------------------|-----------------------------------|
| 10 ≤ R < 50 | 0,1 | Any value in the resistance range |
| 50 ≤ R < 100 | 0,05 and 0,1 | |
| 100 ≤ R < 250 | 0,02; 0,05 and 0,1 | |
| R ≥ 250 | 0,01; 0,02; 0,05 and 0,1 | |

| Resistance (Ω) | Temperature Coefficient (ppm/°C) | Series |
|----------------|----------------------------------|-----------------------------------|
| 10 ≤ R < 20 | E: 25 (-55 °C; +155 °C) | Any value in the resistance range |
| 20 ≤ R < 50 | Y: 10 (-55 °C; +155 °C) | |
| 20 ≤ R < 50 | Z: 5 (+22 °C; +70 °C) | |
| R ≥ 50 | C: 5 (-55 °C; +155 °C) | |



RESISTORS,
FILM, FIXED, CHIP AND ARRAY, THIN FILM,
BASED ON TYPES PHR; PFRR; PRAHR/CNWHR

Certificate

287 D

Page

10-09
002B

Characteristics: Type PFRR, Variants 09 to 12 and 15 are qualified

| Detail Specification | Style | Critical R (kΩ) | Rated Dissipation (W) | Limiting Element Voltage (V) | Type Variant |
|----------------------|-------|-----------------|-----------------------|------------------------------|--------------|
| 4001/023 | 0402 | 32 | 0.050 | 40 | 15 |
| | 0603 | 25 | 0.100 | 50 | 09 |
| | 0805 | 80 | 0.125 | 100 | 10 |
| | 1206 | 90 | 0.250 | 150 | 11 |
| | 2010 | 80 | 0.500 | 200 | 12 |

| Style | Resistance Range (Ω) | Tolerance (±%) | Temperature Coefficient TC(±10 ⁻⁶ /°C) |
|------------------------------|----------------------|----------------|---|
| 0402; 0603; 0805; 1206; 2010 | From 100 to ≤ 100K | 0.05; 0.1 | 10; 25 |
| 0603; 0805; 1206; 2010 | From 100 to ≤ 261K | 0.05; 0.1 | 10; 25 |
| 0805; 1206; 2010 | From 261K to ≤ 301K | 0.05; 0.1 | 10; 25 |
| 1206; 2010 | From 301K to ≤ 1M | 0.05; 0.1 | 10; 25 |
| 2010 | From 1M to 3M01 | 0.05; 0.1 | 10; 25 |

The Established Reliability Level R is evaluated according to the ESCC Basic Specification 26000.



RESISTORS,
FILM, FIXED, CHIP AND ARRAY, THIN FILM,
BASED ON TYPES PHR; PFRR; PRAHR/CNWHR

Certificate
287 D

Page
10-09
002C

Characteristics: Type PRAHR/CNWHR,, Variants 01 to 42 are qualified

| Detail Specification | Style | Critical R (KΩ) | Rated Dissipation (W/resistor) | Limiting Element Voltage (V/resistor) | Type Variant | |
|----------------------|--------|-----------------|--------------------------------|---------------------------------------|-------------------|------------------------|
| | | | | | Same Ohmic Values | Different Ohmic Values |
| 4001/025 | PRA100 | 12.25 | 0.100 | 35 | 01 to 07 | 22 to 28 |
| | PRA135 | 56.25 | 0.100 | 75 | 08 to 14 | 29 to 35 |
| | PRA182 | 100 | 0.100 | 100 | 15 to 21 | 36 to 42 |

| Style | Resistance Range (Ω) | Tolerance (±%) | | Temperature Coefficient TC(±10 ⁻⁶ /°C) | |
|------------------------|----------------------|----------------|-----------|---|----------|
| | | Absolute | Relative | Absolute | Relative |
| PRA100; PRA135; PRA182 | From 100 to 200K | 0.1; 0.5; 1 | 0.05; 0.1 | 10 | 3; 5 |
| PRA135; PRA182 | From 200K to 250K | 0.1; 0.5; 1 | 0.05; 0.1 | 10 | 3; 5 |
| PRA182 | From 250K to 1M | 0.1; 0.5; 1 | 0.05; 0.1 | 10 | 3; 5 |


Number of Resistors per Array: 2 to 8





RESISTORS,
FILM, FIXED, CHIP AND ARRAY, THIN FILM,
BASED ON TYPES PHR; PFRR; PRAHR/CNWHR


Certificate
287 D

Page
10-09
002D

| Types covered by similarity: | | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|-------------------------|--|------------------------------|--------------------|--------------------------|----------------------------|-------|-------------------------|-------------------|------------------------------|--------------------------|----------------|------|-------|--------------------------|-----------------|---------|----------|--------------------------|-----------------------|---------------|------|-----|-------|-----|---------------|------|-----|-------|-----|---------------|------|-------|-------|-----|---------------|
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 4001 Detail ESCC 4001/026 | | VISHAY S.A. Division Sfernice Nice France | | Qualification | CNES | Oct 2011 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics: Type CHPHR, Variants 01 to 10 are qualified. Type CHPFR, variants 11 to 20 are qualified. The qualified is range restricted as below: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>Style</th> <th>Critica R (KΩ)</th> <th>Rated Dissipation</th> <th>Limited Element Voltage (V)</th> <th>Type Variant</th> </tr> </thead> <tbody> <tr> <td>0603</td> <td>25</td> <td>0.100</td> <td>50</td> <td>01;06; 11, 16</td> </tr> <tr> <td>0805</td> <td>50</td> <td>0.200</td> <td>100</td> <td>02;07; 12, 17</td> </tr> <tr> <td>1206</td> <td>160</td> <td>0.250</td> <td>200</td> <td>03;08; 13, 18</td> </tr> <tr> <td>2010</td> <td>180</td> <td>0.500</td> <td>300</td> <td>04;09; 14, 19</td> </tr> <tr> <td>2512</td> <td>112.5</td> <td>0.800</td> <td>300</td> <td>05;10; 15, 20</td> </tr> </tbody> </table> | | | | | | | Style | Critica R (K Ω) | Rated Dissipation | Limited Element Voltage (V) | Type Variant | 0603 | 25 | 0.100 | 50 | 01;06; 11, 16 | 0805 | 50 | 0.200 | 100 | 02;07; 12, 17 | 1206 | 160 | 0.250 | 200 | 03;08; 13, 18 | 2010 | 180 | 0.500 | 300 | 04;09; 14, 19 | 2512 | 112.5 | 0.800 | 300 | 05;10; 15, 20 |
| Style | Critica R (K Ω) | Rated Dissipation | Limited Element Voltage (V) | Type Variant | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0603 | 25 | 0.100 | 50 | 01;06; 11, 16 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0805 | 50 | 0.200 | 100 | 02;07; 12, 17 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1206 | 160 | 0.250 | 200 | 03;08; 13, 18 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2010 | 180 | 0.500 | 300 | 04;09; 14, 19 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2512 | 112.5 | 0.800 | 300 | 05;10; 15, 20 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>Style</th> <th>Range(Ω)</th> <th>Tol. ($\pm\%$)</th> <th>TC(\pmppm/$^{\circ}$C)</th> </tr> </thead> <tbody> <tr> <td>0603;0805;1206;2010;2512</td> <td>From 1 to < 10</td> <td>2; 5</td> <td>200</td> </tr> <tr> <td>0603;0805;1206;2010;2512</td> <td>From 10 to < 1M</td> <td>1; 2; 5</td> <td>100; 200</td> </tr> <tr> <td>0603;0805;1206;2010;2512</td> <td>From 1M to \leq 10M</td> <td>2; 5</td> <td>200</td> </tr> </tbody> </table> | | | | | | | Style | Range(Ω) | Tol. ($\pm\%$) | TC(\pm ppm/ $^{\circ}$ C) | 0603;0805;1206;2010;2512 | From 1 to < 10 | 2; 5 | 200 | 0603;0805;1206;2010;2512 | From 10 to < 1M | 1; 2; 5 | 100; 200 | 0603;0805;1206;2010;2512 | From 1M to \leq 10M | 2; 5 | 200 | | | | | | | | | | | | | | |
| Style | Range(Ω) | Tol. ($\pm\%$) | TC(\pm ppm/ $^{\circ}$ C) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0603;0805;1206;2010;2512 | From 1 to < 10 | 2; 5 | 200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0603;0805;1206;2010;2512 | From 10 to < 1M | 1; 2; 5 | 100; 200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0603;0805;1206;2010;2512 | From 1M to \leq 10M | 2; 5 | 200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Operating Temperature Range, ($^{\circ}$ C): -55 to +155. Lead material is E with either Type 2 or Type 4 finish | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | RESISTORS, FIXED, CHIP, THICK FILM, BASED ON TYPE CHP | | | Certificate 314 A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | Page 10-09 003 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |


| | | | | |
|---|---|-----------------------------------|--------------------------------------|----------------------------|
| Types covered by similarity: Variants 01 through 48 are qualified | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 4009 Detail ESCC 4009/002 | IRCA RICA Division Vitorio Veneto Italy | Qualification | ESA | Apr 1992 |
| <p>Characteristics:</p> <p>Single, double layer and magnetically compensated heaters</p> <p>Maximum Ohmic density 200 Ω/cm²</p> <p>Tolerances ±2, 3, 5, 10 %</p> <p>Resistance 1 to 5000 Ω</p> <p>Heating Area 1.6 to 1300 cm²</p> <p>Terminal Lead 20, 22, 24, 26, 28, 30 AWG</p> <p>Temperature coefficient (10⁻⁶/°C): 175</p> <p>Operating Temperature Range, (°C): -65 to +200</p> | | | | |
|  | <p>RESISTORS, HEATERS, FLEXIBLE SINGLE AND DOUBLE LAYER</p> | <p>Certificate 184 K</p> | <p>Page 10-11 001-1</p> | |

| | | | | | |
|---|--|--|--------------------|--------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 4009 Detail ESCC 4009/003 | | Minco SAS Aston France | Qualification | CNES | Mar 2013 |
| Characteristics: Variants 01, 02 and 03 are qualified Single, double layer heaters Maximum Ohmic density 70 Ω/cm^2 Rated power density 0.38 (variants 01, 03), 0.54 (variant 02) W/cm^2 Resistance 1 to 5000 Ω Heating Area 0.26 to 1000 cm^2 Terminal Lead 20 to 30 AWG Resistance Tolerance (%): ± 1 to ± 10 Operating Temperature Range, ($^{\circ}\text{C}$): -65 to $+150$ for variants 01 and 03; 65 to $+200$ for variant 02 | | | | | |
|  | | RESISTORS, HEATERS, FLEXIBLE SINGLE AND DOUBLE LAYER | | Certificate 325 A | Page 10-11 002 |

| | | | | |
|--|--|--------------------|------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 4009 Detail ESCC 4009/004 | IRCA RICA Division Vitorio Veneto Italy | Qualification | ESA | Jan 2015 |
| <p>Characteristics: All variants are qualified</p> <p>Single, double layer heaters</p> <p>Maximum Ohmic density 200 Ω/cm^2</p> <p>Rated power density 0.38</p> <p>Resistance 1 to 5000 Ω</p> <p>Heating Area 1.66 to 1300 cm^2</p> <p>Terminal Lead 20 to 30 AWG</p> <p>Resistance Tolerance (%): ± 2 to ± 10</p> <p>Operating Temperature Range, ($^{\circ}\text{C}$): $^{-}65$ to $^{+}150$</p> | | | | |
|  | RESISTORS, HEATERS, FLEXIBLE SINGLE AND DOUBLE LAYER | | Certificate 330 | Page 10-11 003 |

Section 11**Component Type: Thermistors**


| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|-----------|-------|-----------------------------|----------------------------------|
| 11-01 | | | NTC | |
| | 11-01-001 | 266 G | Types G15K4D489 and *K3A35* | MEAS Ireland (Betatherm) Ltd. |

| | | | | | |
|--|--|---|--------------------|--------------------------|----------------------------|
| Types covered by similarity: | | Remarks: Refer to variants table 1(a) in the Detail Specifications for resistance to temperature characteristics. | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 4006 Detail ESCC 4006/013 4006/014 | | MEAS Ireland (Betatherm) Galway Ireland | Qualification | ESA | Jul 2001 |
| Characteristics: 4006/013: Variants 01 to 05 and 06 to 07 are qualified. 4006/014: Variants 08, 09, 12 and 13 are qualified. Operating Temperature Range, (°C): 4006/013 : -55 to +115 4006/014 : -60 to +160 Please refer to the relevant Detail Specification for complete information on the qualified variants. | | | | | |
|  | | THERMISTORS, (THERMALLY SENSITIVE RESISTORS), NTC, BASED ON TYPES G15K4D489 AND *K3A35* | | Certificate 266 G | Page 11-01 001 |

Section 12

Component Type: Transistors

| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|----------------|----------------|--|--------------------|
| 12-01 | | | Low Power, NPN | |
| | 12-01-002-3A-B | 233 K rev 2 | Types NPN | STMicroelectronics |
| 12-02 | | | Low Power, PNP | |
| | 12-02-002-3A-B | 234 K rev 2 | Types PNP | STMicroelectronics |
| 12-05 | | | MOSFET, Power, N-Channel | |
| | 12-05-003-1 | 303 B | Types STRH100N10, STRH40N6, SRH100N6 and STRH8N10 | STMicroelectronics |
| | 12-05-003-2 | 319 B | Type BUY**CS*** | Infineon |
| 12-06 | | | MOSFET, Power, P-Channel | |
| | 12-06-003-1 | 326 A Rev 1 | Type STRH40P10 | STMicroelectronics |
| 12-10 | | | RF/Microwave, NPN, Low Power, Low Noise | |
| | 12-10-001 | 230 F | Types BFY193 | Infineon |
| | 12-10-002 | 245 F | Types BFY405, -420 and -450 | Infineon |
| | 12-10-003 | 320 A | Type BFY640 | Infineon |
| | 12-10-004 | 321 A | Types BFY640B and BFY650B | Infineon |
| | 12-10-005 | 322 A | Type BFY740B | Infineon |
| 12-16 | | | Microwave, Gallium Arsenide | |
| | 12-16-001 | 213 F | Types CFY67, High Electron Mobility, Low Noise | Infineon |

| | | | | | | | | | | | |
|---|-------------------------------|--------|-----------------------|--|--------|--------------------|--------|-----------------------|-------------------------------|--|-----------------------------|
| Types covered by similarity: | | | | Remarks: | | | | | | | |
| Procurement Specifications | | | | Manufacturer | | Nature of Approval | | Supervising Authority | Initial Qualification Date | | |
| Generic ESCC 5000 Detail ESCC Please refer to the next page | | | | ST Microelectronics Rennes France | | Qualification | | CNES | Sep 1996 | | |
| Characteristics: Maximum Rating: | | | | | | | | | | | |
| | 2N2222A | 2N2484 | | 2N5551 | 2N3700 | 2N5154 | BUX 77 | 2N2920A | | | |
| V _{CB0} (V): | 75 | 60 | BV _{CB0} (V) | 180 | 140 | 100 | 100 | 60 | | | |
| V _{CE0} (V): | 40 | 60 | BV _{CE0} (V) | 160 | 80 | 80 | 80 | 60 | | | |
| Packages: | See next page | | | | | | | | | | |
| Operating Temperature Range (°C), -65 to +200 | | | | | | | | | | | |
|  | | | | TRANSISTORS, LOW AND HIGH POWER, NPN | | | | | Certificate 233 K rev2 | | Page 12-01 002-3A |


| ESCC Specification No. | Component Type | Package | Qualified Variants |
|------------------------|----------------|------------------------------------|---|
| 5201/001 | 2N 2484 | TO-18, LCCC3, LCCC3 +1 | 01, 02, 04, 05, 06, 07 |
| 5201/002 | 2N 2222A | TO-18, LCCC3, LCCC3 +1 | 01, 02, 04, 05, 11, 12 |
| 5201/019 | 2N 5551 | TO-18, LCCC3, LCCC3 +1 | 01, 02, 04, 05, 08, 09 |
| | | | |
| 5201/004 | 2N 3700 | TO-18, LCCC3, LCCC3 +1 | 01, 02, 04, 05, 06, 07 |
| 5203/010 | 2N 5154 | TO-257, SMD.5 | 04, 05, 06, 07 |
| 5203/016 | BUX 77ESY | TO-257 | 06, 07 |
| 5207/002 | 2N 2920A | TO-77, LCCC6, FP-8 | 03, 06, 12, 15, 16 , 17 |
| | | | |



TRANSISTORS,
LOW AND HIGH POWER,
NPN

Certificate
233 K rev2

Page
12-01
002-3B

| | | | | | | | | | | | | |
|---|-------------------------------|--------|--------|--------|--------|---|--|--------------------|--|-----------------------------------|----------------------------|----------------------------------|
| Types covered by similarity: | | | | | | Remarks: | | | | | | |
| Procurement Specifications | | | | | | Manufacturer | | Nature of Approval | | Supervising Authority | Initial Qualification Date | |
| Generic ESCC 5000 Detail ESCC Please refer to the next page | | | | | | ST Microelectronics Rennes France | | Qualification | | CNES | Sep 1996 | |
| Characteristics: | | | | | | | | | | | | |
| | 2N2907A | 2N3810 | 2N5153 | BUX 78 | 2N5401 | | | | | | | |
| BV _{CBO} (V) | 60 | 60 | 100 | 100 | 160 | | | | | | | |
| BV _{CEO} (V) | 60 | 60 | 80 | 80 | 150 | | | | | | | |
| Packages: | See next page | | | | | | | | | | | |
| Operating Temperature Range (°C), -65 to +200 | | | | | | | | | | | | |
|  | | | | | | <p>TRANSISTORS, LOW AND HIGH POWER, PNP</p> | | | | <p>Certificate 234 K rev2</p> | | <p>Page 12-02 002-3A</p> |


| ESCC Specification No. | Component Type | Package | Qualified Variants |
|---------------------------|----------------|------------------------------------|--|
| 5202/001 | 2N 2907A | TO-18, LCCC3, LCCC3 +1 | 01, 02, 04, 05,06, 07 |
| 5202/014 | 2N 5401 | TO-18, LCCC3, LCCC3 +1 | 01, 02, 04, 05, 06, 07 |
| 5204/002 | 2N 5153 | TO-257, SMD.5 | 04, 05, 06, 07 |
| 5204/006 | BUX 78ESY | TO-257 | 06, 07 |
| 5207/005 | 2N 3810 | TO-78, LCCC6, FP-8 | 01, 02, 07, 09, 10, 11 |
| | | | |





TRANSISTORS,
LOW AND HIGH POWER,
PNP


Certificate
234 K rev2


Page
12-02
002-3B


| | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|--|--|--|--|--|--|--|--|---|--|--|--|--|--|--|--|--|--|----------------------------|--|--|--|--|
| Types covered by similarity: Variant 01 in each Detail Specification is qualified. | | | | | Remarks: These devices have a TID tested capability of 100 kRad (Si) SEE tested : LET (MeV-cm ² /mg) 56 @ V _{GS} = -10V, V _{DS} = 250V SOA and SE SOA derating graphs are incorporated in the Detail Specifications. | | | | | | | | | | | | | | | | | | | |
| Procurement Specifications | | | | | Manufacturer | | | | | Nature of Approval | | | | | Supervising Authority | | | | | Initial Qualification Date | | | | |
| Generic ESCC 5000 | | | | | Infineon Technologies AG Neubiberg Germany | | | | | Qualification | | | | | DLR | | | | | Aug 2012 | | | | |
| Detail ESCC 5205/026 5205/027 5205/028, 5205/030 | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics: ESCC No. | | | | | 5205/026 | | | | | 5205/027 | | | | | 5205/028 | | | | | 5205/030 | | | | |
| r _{DS(ON)} (mΩ) @ 25 °C | | | | | 130 | | | | | 30 | | | | | 130 | | | | | 130 | | | | |
| Maximum Ratings: | | | | | | | | | | | | | | | | | | | | | | | | |
| I _{DS} (A) | | | | | 12.4 | | | | | 54 | | | | | 12.4 | | | | | 12.4 | | | | |
| V _{DS} (V) max. | | | | | 250 | | | | | 250 | | | | | 100 | | | | | 250 | | | | |
| V _{GS} (V) max. | | | | | ± 20 | | | | | ± 20 | | | | | ± 20 | | | | | ± 20 | | | | |
| P _{tot} (W) | | | | | 75 | | | | | 250 | | | | | 75 | | | | | 75 | | | | |
| R _{th(j-c)} (°C/W) | | | | | 1.66 | | | | | 0.5 | | | | | 1.66 | | | | | 1.66 | | | | |
| Package: | | | | | SMD0.5 | | | | | SMD2 | | | | | SMD0.5 | | | | | TO-257AA | | | | |
| Operating Temperature Range (°C): T _{op} = - 55 to +150 | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | | | | <p style="text-align: center;">TRANSISTORS, POWER, MOSFET, N-CHANNEL, BASED ON TYPE BUY **CS***</p> | | | | | <p style="text-align: center;">Certificate 319 B</p> | | | | | <p style="text-align: center;">Page 12-05 003-2</p> | | | | | | | | | |


| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|-----------|---|--|-----------------------------------|------------------------------------|---------------------------|--|----|--|--|--|--------------------------|--|----|--|--|--|--------------------------|--|--------|--|--|--|--------------|---------|-----|--|--|--|-------------------|---------|------|--|--|--|---------------------------|-----------|-----|--|--|--|
| Types covered by similarity: Variants 01 to 08. | | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5010 Detail ESCC 5611/006 | | Infineon Technologies AG Neubiberg Germany | Qualification | DLR | Jun 1996 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Characteristics for BFY 193</p> <table border="0"> <tr> <td>V_{CEO} (V) max.</td> <td></td> <td>12</td> <td></td> <td></td> <td></td> </tr> <tr> <td>V_{CBO} (V)max.</td> <td></td> <td>20</td> <td></td> <td></td> <td></td> </tr> <tr> <td>h_{FE} min/max.</td> <td></td> <td>50/175</td> <td>@ V_{CE} = 8.0 V, I_C = 30mA</td> <td></td> <td></td> </tr> <tr> <td>NF (dB) max.</td> <td>@ 2 GHz</td> <td>2.9</td> <td>@ V_{CE} = 5.0 V, I_C = 15mA</td> <td></td> <td></td> </tr> <tr> <td>MAG/MSG (dB) min.</td> <td>@ 2 GHz</td> <td>12.5</td> <td>@ V_{CE} = 5.0 V, I_C = 40mA</td> <td></td> <td></td> </tr> <tr> <td>f_T (GHz) min.</td> <td>@ 500 MHz</td> <td>6.5</td> <td>@ V_{CE} = 5.0 V, I_C = 40mA</td> <td></td> <td></td> </tr> </table> <p>Package: " Micro-X1"</p> <p>Total Power Dissipation (P_{tot}) = 580 mW</p> <p>Operating Temperature Range (°C): T_{op} = - 65 to +200</p> | | | | | | V _{CEO} (V) max. | | 12 | | | | V _{CBO} (V)max. | | 20 | | | | h _{FE} min/max. | | 50/175 | @ V _{CE} = 8.0 V, I _C = 30mA | | | NF (dB) max. | @ 2 GHz | 2.9 | @ V _{CE} = 5.0 V, I _C = 15mA | | | MAG/MSG (dB) min. | @ 2 GHz | 12.5 | @ V _{CE} = 5.0 V, I _C = 40mA | | | f _T (GHz) min. | @ 500 MHz | 6.5 | @ V _{CE} = 5.0 V, I _C = 40mA | | |
| V _{CEO} (V) max. | | 12 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| V _{CBO} (V)max. | | 20 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| h _{FE} min/max. | | 50/175 | @ V _{CE} = 8.0 V, I _C = 30mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| NF (dB) max. | @ 2 GHz | 2.9 | @ V _{CE} = 5.0 V, I _C = 15mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MAG/MSG (dB) min. | @ 2 GHz | 12.5 | @ V _{CE} = 5.0 V, I _C = 40mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| f _T (GHz) min. | @ 500 MHz | 6.5 | @ V _{CE} = 5.0 V, I _C = 40mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | <p>TRANSISTORS, MICROWAVE, SMALL SIGNAL, BIPOLAR, BASED ON TYPE BFY 193</p> | | <p>Certificate 230 F</p> | <p>Page 12-10 001</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|-----------|---|--|------------------------------------|----------------------------|---------------------------|-----|--|--|--|--|---------------------------|----|--|--|--|--|--------------------------|-----|--|--|--|--|--------------------------|----|--|--|--|--|--------------------------|--------|--|--|--|--|--------------|-----------|-----|--|--|--|---------------------------|-----------|----|--|--|--|
| Types covered by similarity: Variants 01, 02 and 03 are qualified. | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5010 Detail ESCC 5611/008 | | Infineon Technologies AG Neubiberg Germany | Qualification | DLR | Jun 1997 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Characteristics for BFY 450</p> <table> <tr> <td>V_{CEO} (V) max.</td> <td>4.5</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>V_{CBO} (V) max.</td> <td>15</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>I_C (mA) max.</td> <td>100</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>I_B (mA) max.</td> <td>10</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>h_{FE} min/max.</td> <td>50/150</td> <td>@ V_{CE} = 1.0 V, I_C = 20mA</td> <td></td> <td></td> <td></td> </tr> <tr> <td>NF (dB) max.</td> <td>@ 1.8 GHz</td> <td>2.0</td> <td>@ V_{CE} = 2.0 V, I_C = 10mA</td> <td></td> <td></td> </tr> <tr> <td>f_T (GHz) min.</td> <td>@ 1.0 GHz</td> <td>18</td> <td>@ V_{CE} = 3.0 V, I_C = 90mA</td> <td></td> <td></td> </tr> </table> <p>Package: "Micro-X"</p> <p>Total Power Dissipation (P_{tot}) = 450 mW</p> <p>Operating Temperature Range (°C): T_{op} = - 65 to +175</p> | | | | | | V _{CEO} (V) max. | 4.5 | | | | | V _{CBO} (V) max. | 15 | | | | | I _C (mA) max. | 100 | | | | | I _B (mA) max. | 10 | | | | | h _{FE} min/max. | 50/150 | @ V _{CE} = 1.0 V, I _C = 20mA | | | | NF (dB) max. | @ 1.8 GHz | 2.0 | @ V _{CE} = 2.0 V, I _C = 10mA | | | f _T (GHz) min. | @ 1.0 GHz | 18 | @ V _{CE} = 3.0 V, I _C = 90mA | | |
| V _{CEO} (V) max. | 4.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| V _{CBO} (V) max. | 15 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| I _C (mA) max. | 100 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| I _B (mA) max. | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| h _{FE} min/max. | 50/150 | @ V _{CE} = 1.0 V, I _C = 20mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| NF (dB) max. | @ 1.8 GHz | 2.0 | @ V _{CE} = 2.0 V, I _C = 10mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| f _T (GHz) min. | @ 1.0 GHz | 18 | @ V _{CE} = 3.0 V, I _C = 90mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | <p>TRANSISTORS, MICROWAVE, SMALL SIGNAL, BIPOLAR, BASED ON TYPE BFY 450</p> | | <p>Certificate 245 F</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | <p>Page 12-10 002</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|-----------|---|--------------------|-----------------------------------|------------------------------------|--|----|-----------------|--|------|-----------------|--|-----|------------------|--|------------------------------------|------------------|----------|--------------------------------|--|-----------|--------------------------------|-----------------|-----------|---------------------------------|-----------------|-----------|---------------------------------|--|--|--|
| Types covered by similarity: Variants 01, 02 and 03 are qualified. | | Remarks: - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5010 Detail ESCC 5611/009 | | Infineon Technologies AG Neubiberg Germany | Qualification | DLR | Sep 2012 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Characteristics for BFY 640 Variant 03</p> <table border="0"> <tr> <td>V_{CE0} (V) max.</td> <td></td> <td>4.0</td> </tr> <tr> <td>V_{CB0} (V) max.</td> <td></td> <td>13</td> </tr> <tr> <td>I_C (mA) max.</td> <td></td> <td>50.0</td> </tr> <tr> <td>I_B (mA) max.</td> <td></td> <td>3.0</td> </tr> <tr> <td>h_{FE} min/max</td> <td></td> <td>135/250 @ $V_{ce}=3V$ & $I_C=30mA$</td> </tr> <tr> <td>MSG/MAG min (dB)</td> <td>@ 1.8GHz</td> <td>23 @ $V_{ce}=3V$ & $I_C= 30mA$</td> </tr> <tr> <td></td> <td>@ 6.0 GHz</td> <td>12 @ $V_{ce}=3V$ & $I_C= 30mA$</td> </tr> <tr> <td>NF_{max} (dB)</td> <td>@ 1.8 GHz</td> <td>< 0.8 @ $V_{ce}=3V$ & $I_C=5mA$</td> </tr> <tr> <td>NF_{max} (dB)</td> <td>@ 6.0 GHz</td> <td>< 1.4 @ $V_{ce}=3V$ & $I_C=5mA$</td> </tr> </table> <p>Package: "Micro-X"</p> <p>Total Power Dissipation (P_{tot}) max. = 200 mW</p> <p>Operating Temperature Range (°C): $T_{op} = - 65$ to $+175$</p> | | V_{CE0} (V) max. | | 4.0 | V_{CB0} (V) max. | | 13 | I_C (mA) max. | | 50.0 | I_B (mA) max. | | 3.0 | h_{FE} min/max | | 135/250 @ $V_{ce}=3V$ & $I_C=30mA$ | MSG/MAG min (dB) | @ 1.8GHz | 23 @ $V_{ce}=3V$ & $I_C= 30mA$ | | @ 6.0 GHz | 12 @ $V_{ce}=3V$ & $I_C= 30mA$ | NF_{max} (dB) | @ 1.8 GHz | < 0.8 @ $V_{ce}=3V$ & $I_C=5mA$ | NF_{max} (dB) | @ 6.0 GHz | < 1.4 @ $V_{ce}=3V$ & $I_C=5mA$ | | | |
| V_{CE0} (V) max. | | 4.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| V_{CB0} (V) max. | | 13 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| I_C (mA) max. | | 50.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| I_B (mA) max. | | 3.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| h_{FE} min/max | | 135/250 @ $V_{ce}=3V$ & $I_C=30mA$ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MSG/MAG min (dB) | @ 1.8GHz | 23 @ $V_{ce}=3V$ & $I_C= 30mA$ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | @ 6.0 GHz | 12 @ $V_{ce}=3V$ & $I_C= 30mA$ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| NF_{max} (dB) | @ 1.8 GHz | < 0.8 @ $V_{ce}=3V$ & $I_C=5mA$ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| NF_{max} (dB) | @ 6.0 GHz | < 1.4 @ $V_{ce}=3V$ & $I_C=5mA$ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | <p>TRANSISTORS, MICROWAVE, SMALL SIGNAL, BIPOLAR, BASED ON TYPE BFY 640</p> | | <p>Certificate 320 A</p> | <p>Page 12-10 003</p> | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|-----------|---|--------------------|------------------------------|-------------------------------|--|----|--------------------------|--|-----|--------------------------|--|----|-------------------------|--|--|------------------|----------|---|------------------------|-----------|----|--|--|--|--|
| Types covered by similarity: Variants 01, 02, 03 and 04 are qualified. | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5010 Detail ESCC 5611/010 | | Infineon Technologies AG Neubiberg Germany | Qualification | DLR | Sep 2012 | | | | | | | | | | | | | | | | | | | | | |
| <p>Characteristics for BFY 650B Variant 04</p> <table border="0"> <tr> <td>V_{CEO} (V) max.</td> <td></td> <td>4.0</td> </tr> <tr> <td>V_{CBO} (V) max.</td> <td></td> <td>13</td> </tr> <tr> <td>I_C (mA) max.</td> <td></td> <td>150</td> </tr> <tr> <td>I_B (mA) max.</td> <td></td> <td>10</td> </tr> <tr> <td>h_{FE} min/max</td> <td></td> <td>100/250 @ V_{CE}=3V & I_C=80mA</td> </tr> <tr> <td>MSG/MAG min (dB)</td> <td>@1.8 GHz</td> <td>18 @ V_{CE}=3V & I_C=80mA</td> </tr> <tr> <td>P_{out} (dBm)</td> <td>@ 1.8 GHz</td> <td>16</td> </tr> </table> <p>Package: "Micro-X"</p> <p>Total Power Dissipation (P_{tot}) max. = 600 mW</p> <p>Operating Temperature Range (°C): T_{op} = - 65 to +175</p> | | V _{CEO} (V) max. | | 4.0 | V _{CBO} (V) max. | | 13 | I _C (mA) max. | | 150 | I _B (mA) max. | | 10 | h _{FE} min/max | | 100/250 @ V _{CE} =3V & I _C =80mA | MSG/MAG min (dB) | @1.8 GHz | 18 @ V _{CE} =3V & I _C =80mA | P _{out} (dBm) | @ 1.8 GHz | 16 | | | | |
| V _{CEO} (V) max. | | 4.0 | | | | | | | | | | | | | | | | | | | | | | | | |
| V _{CBO} (V) max. | | 13 | | | | | | | | | | | | | | | | | | | | | | | | |
| I _C (mA) max. | | 150 | | | | | | | | | | | | | | | | | | | | | | | | |
| I _B (mA) max. | | 10 | | | | | | | | | | | | | | | | | | | | | | | | |
| h _{FE} min/max | | 100/250 @ V _{CE} =3V & I _C =80mA | | | | | | | | | | | | | | | | | | | | | | | | |
| MSG/MAG min (dB) | @1.8 GHz | 18 @ V _{CE} =3V & I _C =80mA | | | | | | | | | | | | | | | | | | | | | | | | |
| P _{out} (dBm) | @ 1.8 GHz | 16 | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | <p>TRANSISTORS, MICROWAVE, SMALL SIGNAL, BIPOLAR, BASED ON TYPES BFY 640B and BFY650B</p> | | <p>Certificate 321 A</p> | <p>Page 12-10 004</p> | | | | | | | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|-----------|---|--------------------|--------------------------|----------------------------|--|----|--------------------------|--|------|--------------------------|--|-----|-------------------------|--|---|------------------|-----------|--|------------------|-----------|--|------------------------|-----------|---|------------------------|-----------|---|--|--|--|
| Types covered by similarity: | | Remarks: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 5010 Detail ESCC 5611/011 | | Infineon Technologies AG Neubiberg Germany | Qualification | DLR | Sep 2012 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Characteristics for BFY 740B Variant 01 <table border="0"> <tr> <td>V_{CEO} (V) max.</td> <td></td> <td>4.0</td> </tr> <tr> <td>V_{CBO} (V) max.</td> <td></td> <td>13</td> </tr> <tr> <td>I_C (mA) max.</td> <td></td> <td>30.0</td> </tr> <tr> <td>I_B (mA) max.</td> <td></td> <td>3.0</td> </tr> <tr> <td>h_{FE} min/max</td> <td></td> <td>185/380 @V_{CE}=3V & I_C=20mA</td> </tr> <tr> <td>MSG/MAG min (dB)</td> <td>@ 1.8 GHz</td> <td>24 @V_{CE}=3V & I_C=20mA</td> </tr> <tr> <td>MSG/MAG min (dB)</td> <td>@ 6.0 GHz</td> <td>17 @V_{CE}=3V & I_C=20mA</td> </tr> <tr> <td>NF_{max} (dB)</td> <td>@ 1.8 GHz</td> <td>≤ 0.75 @V_{CE}=3V & I_C=8mA</td> </tr> <tr> <td>NF_{max} (dB)</td> <td>@ 6.0 GHz</td> <td>≤ 1.15 @V_{CE}=3V & I_C=8mA</td> </tr> </table> Package: "Micro-X" Total Power Dissipation (P _{tot}) max. = 120 mW Operating Temperature Range (°C): T _{op} = - 65 to +175 | | V _{CEO} (V) max. | | 4.0 | V _{CBO} (V) max. | | 13 | I _C (mA) max. | | 30.0 | I _B (mA) max. | | 3.0 | h _{FE} min/max | | 185/380 @V _{CE} =3V & I _C =20mA | MSG/MAG min (dB) | @ 1.8 GHz | 24 @V _{CE} =3V & I _C =20mA | MSG/MAG min (dB) | @ 6.0 GHz | 17 @V _{CE} =3V & I _C =20mA | NF _{max} (dB) | @ 1.8 GHz | ≤ 0.75 @V _{CE} =3V & I _C =8mA | NF _{max} (dB) | @ 6.0 GHz | ≤ 1.15 @V _{CE} =3V & I _C =8mA | | | |
| V _{CEO} (V) max. | | 4.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| V _{CBO} (V) max. | | 13 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| I _C (mA) max. | | 30.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| I _B (mA) max. | | 3.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| h _{FE} min/max | | 185/380 @V _{CE} =3V & I _C =20mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MSG/MAG min (dB) | @ 1.8 GHz | 24 @V _{CE} =3V & I _C =20mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MSG/MAG min (dB) | @ 6.0 GHz | 17 @V _{CE} =3V & I _C =20mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| NF _{max} (dB) | @ 1.8 GHz | ≤ 0.75 @V _{CE} =3V & I _C =8mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| NF _{max} (dB) | @ 6.0 GHz | ≤ 1.15 @V _{CE} =3V & I _C =8mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | TRANSISTORS, MICROWAVE, SMALL SIGNAL, BIPOLAR, BASED ON TYPE BFY 740B | | Certificate 322 A | Page 12-10 005 | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | | | | |
|---|----------------|--|---------|--------------------|--------------------------|----------------------------|
| Types covered by similarity: | | | | Remarks: | | |
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 5010 Detail ESCC 5613/004 | | Infineon Technologies AG Neubiberg Germany | | Qualification | DLR | Apr 1994 |
| Characteristics (@ 12 GHz): All variants are qualified | | | | | | |
| | | NFmin. (dB) | Ga (dB) | | | |
| 5613/004 | variants 1 & 3 | 0.8 | 11 | | | |
| pseudo-morphic | Variants 2 & 4 | 1.0 | 10.5 | | | |
| Package: Micro-X Total Power Dissipation (P_{tot}) = 200 mW derated from $+31\text{ }^{\circ}\text{C } T_{amb}$ Operating Temperature Range ($^{\circ}\text{C}$): $T_{stg} = -65$ to $+150$ | | | | | | |
|  | | TRANSISTORS, HIGH ELECTRON MOBILITY, GALLIUM ARSENIDE, MICROWAVE, LOW NOISE, SMALL SIGNAL, BASED ON TYPE CFY 67 | | | Certificate 213 F | |
| | | | | | Page 12-16 001 | |

Section 13

Component Type: Wires and Cables

INDEX PAGE 1 of 2

| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|-------------|-------|--|------------------|
| 13-01 | | | Low Frequency | |
| | 13-01-001-1 | 07 Q | Polyimide, Types FA-3901-1, FA 3901-2 | Draka Fileca |
| | 13-01-001-2 | 09 P | Polyimide, Types 1871-1872 | Nexans |
| | 13-01-001-3 | 132 N | Polyimide, Types 3901002**B | Axon' Cable |
| | 13-01-003 | 08 Q | PTFE, Types MTV-BTV | Nexans |
| | 13-01-003-2 | 292 C | PTFE/Polyimide, Types 3901013**B | Axon' Cable |
| | 13-01-004-1 | 138 L | Polyimide, Type SPC | Gore |
| | 13-01-004-2 | 219 K | Polyimide, Types SPL | Gore |
| | 13-01-004-3 | 268 F | Polyimide, Types 3901019**B | Axon' Cable |
| | 13-01-004-4 | 295 B | Polyimide, Types 3901019 | Leoni |
| | 13-01-005-1 | 159 L | Crosslinked PTFE, Type Silver-Plated Copper | Tyco Electronics |
| | 13-01-005-2 | 267 G | Crosslinked PTFE, Type Silver-Plated Copper | Axon' Cable |
| | 13-01-008 | 215 K | PTFE, Polyimide / PFA Insulated, Type SPP | Gore |
| | 13-01-009 | 216 J | PTFE, Polyimide / PFA Insulated, Shielded, Type SPM | Gore |
| | 13-01-009-2 | 294 B | PTFE, Polyimide/PFA Insulated, Shielded, Type 3901018 | Leoni |
| | 13-01-009-3 | 300 B | PTFE, Polyimide / PFA Insulated, Shielded, Type SPM | Axon' Cable |
| | 13-01-010-1 | 229 J | Polyimide, Insulated, Shielded, Type SPLD, Drain Wire | Gore |
| | 13-01-010-2 | 293 C | Polyimide, Insulated, Shielded, Drain Wire, Types 3901021**B | Axon' Cable |
| | 13-01-010-3 | 296 B | Polyimide, Insulated, Shielded, Drain Wire, Type 3901021 | Leoni |
| | 13-01-011-1 | 257 G | Crosslinked, Modified ETFE, Type Silver-Plated Copper, Lightweight | Tyco Electronics |
| | 13-01-012-1 | 299 B | Fluoropolymer, Lightweight, Based on Type CSWL | Axon' Cable |
| | 13-01-012-2 | 305 B | Fluoropolymer, Lightweight, Based on Type CSWL | Gore |
| | 13-01-013-1 | 328 | Extra thin, fluorothermoplastic / polyimide, Based on Type CSC | Gore |




SECTION 13-**: INDEX OF WIRES AND CABLES


REP005 Updated on 15 Jul 2015


Section 13**Component Type: Wires and Cables
INDEX PAGE 2 of 2**


| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|-------------|-------|---|--------------|
| 13-02 | | | Coaxial, RF, Flexible | |
| | 13-02-001 | 24 R | PTFE/Polyimide, Type 50 CIS | Nexans |
| | 13-02-002-1 | 255 H | Coaxial, Triaxial, Balanced Shielded Line | Gore |
| | 13-02-002-2 | 298 B | Coaxial, Triaxial, Balanced Shielded Line | Axon' Cable |
| | 13-02-003-1 | 291 C | Symmetric, Quad, Spacewire | Axon' Cable |
| | 13-02-003-2 | 304 B | Symmetric, Quad, Spacewire | Gore |


**SECTION 13-**: INDEX OF WIRES AND CABLES****REP005 Updated on 15 Jul 2015**


| | | | | |
|---|---|--------------------|-------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3901 Detail ESCC 3901/001 3901/002 | Draka Fileca Ste-Genevieve France | Qualification | CNES | Jan 1979 |
| Characteristics: FA 3901-1 All Variants defined in the Detail Specification 3901/001 are qualified except those based on AWG 12-14 FA 3901-2 Variants 31 to 73 and 74 to 91 as defined in the Detail Specification 3901/002 are qualified Voltage Rating, maximum (Vrms):600 Temperature Range (°C): -100 to +200 | | | | |
|  | WIRES AND CABLES, LOW FREQUENCY, POLYIMIDE INSULATION BASED ON TYPES FA 3901-1, FA 3901-2 | | Certificate 07 Q | Page 13-01 001-1 |


| | | | | |
|--|---|--------------------|----------------------------------|--------------------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| <p>Generic ESCC 3901</p> <p>Detail ESCC 3901/001 3901/002</p> | Nexans Draveil France | Qualification | CNES | Jan 1979 |
| <p>Characteristics:</p> <p>Medium weight 1871 - n/1871 - 871 (3901/001) Variants 24 to 47 are qualified Light weight 1872 - n/1872 - 872 (3901/002) Variants 31 to 73 are qualified</p> <p>Voltage Rating, maximum (Vrms):600 Temperature Range (°C): -100 to +200</p> | | | | |
|  | <p>WIRES AND CABLES, LOW FREQUENCY, POLYIMIDE INSULATION BASED ON TYPES 1871 - 1872</p> | | <p>Certificate 09 P</p> | <p>Page 13-01 001-2</p> |


| | | | | |
|---|--|--------------------|-----------------------------------|--------------------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| <p>Generic ESCC 3901</p> <p>Detail ESCC 3901/001 3901/002</p> | <p>AXON' CABLE Montmirail France</p> | Qualification | CNES | Dec 1985 |
| <p>Characteristics:</p> <p>The following variants are qualified: 3901/001: variants 24 to 47 3901/002: variants 31 to 73</p> <p>Voltage Rating, maximum (Vrms):600 Temperature Range (°C): -100 to +200</p> | | | | |
|  | <p>WIRES AND CABLES, LOW FREQUENCY, POLYIMIDE INSULATION, BASED ON TYPES 3901001**B and 3901002**B</p> | | <p>Certificate 132 N</p> | <p>Page 13-01 001-3</p> |


| | | | | |
|---|--|--------------------|-------------------------|----------------------------|
| Types covered by similarity: -MTV - BTV -MTV/G - BTV/G -MTV/BF/G - BTV/BF/G | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3901 Detail ESCC 3901/013 | Nexans Draveil France | Qualification | CNES | Jan 1979 |
| Characteristics: Variants 01 to 77 are qualified Voltage Rating, maximum (Vrms):600 Temperature Range (°C): -100 to +200 | | | | |
|  | WIRES AND CABLES, LOW FREQUENCY, PTFE/POLYIMIDE INSULATION, BASED ON TYPES MTV-BTV | | Certificate 08 Q | Page 13-01 003 |


| | | | | |
|--|---|--------------------|--------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3901 Detail ESCC 3901/013 | AXON' CABLE Montmirail France | Qualification | CNES | Jun 2009 |
| Characteristics: All variants are qualified Voltage Rating, maximum (Vrms):600 Temperature Range (°C): -100 to +200 | | | | |
|  | WIRES AND CABLES, LOW FREQUENCY, PTFE/POLYIMIDE INSULATION, BASED ON TYPES 3901013**B | | Certificate 292 C | Page 13-01 003-2 |


| | | | | |
|--|--|--------------------|--------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3901 Detail ESCC 3901/009 | W.L. Gore & Co Pleinfeld Germany | Qualification | DLR | Aug 1986 |
| Characteristics: Variants 01-66 are qualified Voltage Rating, maximum (Vrms):600 Temperature Range (°C): -200 to +200 | | | | |
|  | WIRES AND CABLES, LOW FREQUENCY, POLYIMIDE INSULATION, BASED ON TYPES SPC 2110 | | Certificate 138 L | Page 13-01 004-1 |


| | | | | |
|--|---|--------------------|--------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3901 Detail ESCC 3901/019 | W.L. Gore & Co Pleinfeld Germany | Qualification | DLR | Nov 1994 |
| Characteristics: Variants 01-94 are qualified Voltage Rating, maximum (Vrms):600 Temperature Range (°C): -200 to +200 | | | | |
|  | WIRES AND CABLES, LOW FREQUENCY, POLYIMIDE INSULATION, BASED ON TYPES SPL | | Certificate 219 K | Page 13-01 004-2 |


| | | | | |
|---|---|---------------------------------|------------------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3901 Detail ESCC 3901/019 | AXON' CABLE Montmirail France | Qualification | CNES | Jun 2002 |
| <p>Characteristics:</p> <p>All variants are qualified</p> <p>Voltage Rating, maximum (Vrms):600</p> <p>Temperature Range (°C): -200 to +200</p> | | | | |
|  | <p>WIRES AND CABLES, LOW FREQUENCY, POLYIMIDE INSULATION, BASED ON TYPES 3901019**B</p> | <p>Certificate</p> <p>268 F</p> | <p>Page</p> <p>13-01 004-3</p> | |


| | | | | |
|---|--|--------------------------|-----------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3901 Detail ESCC 3901/019 | LEONI Special Cables GmbH Friesoythe Germany | Qualification | DLR | Oct 2009 |
| Characteristics: All variants are qualified with the exception of variants 01, 09, 17, 24, 25, 32, 48, 56, 64, 72, and 79 Conductor according to ISO 2635 (except AWG 28) AWG 12 to 28 inclusive are qualified For silver coated strands the silver thickness shall be 2.0µm minimum Voltage Rating, maximum (V_{rms}):600 | | | | |
|  | WIRES AND CABLES, LOW FREQUENCY, POLYIMIDE INSULATION, BASED ON TYPE 3901019 | Certificate 295 B | | Page 13-01 004-4 |


| | | | | |
|--|--|---|--------------------------|----------------------------|
| Types covered by similarity: | | Remarks: This product is not intended for human space flight applications. | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3901 Detail ESCC 3901/012 | Tyco Electronics Dorcan, Swindon England | Qualification | UK Space Agency | Feb 1989 |
| Characteristics: Variants 01 to 80 are qualified Maximum voltage: 600 Vrms Operating temperature range (°C): -100 to +200 | | | | |
|  | WIRES AND CABLES, LOW FREQUENCY, 600V, SILVER-PLATED COPPER, EXTRUDED CROSSLINKED FLUOROPOLYMER INSULATION, BASED ON TYPE 55/995X | | Certificate 159 L | Page 13-01 005-1 |


| | | | | |
|--|---|---|--------------------------|----------------------------|
| Types covered by similarity: | | Remarks: This product is not intended for human space flight applications. | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3901 Detail ESCC 3901/012 | AXON' CABLE Montmirail France | Qualification | CNES | Mar 2002 |
| Characteristics: All variants are qualified Wire code ISO 2635 Voltage Rating, maximum (Vrms) : 600 Temperature Range (°C): -100 to +200 | | | | |
|  | WIRES AND CABLES, LOW FREQUENCY, 600V, SILVER-PLATED COPPER, EXTRUDED CROSSLINKED FLUOROPOLYMER INSULATION, BASED ON TYPE 3901012**B | | Certificate 267 G | Page 13-01 005-2 |


| | | | | |
|---|---|--------------------|------------------------------|-------------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| <p>Generic ESCC 3901</p> <p>Detail ESCC 3901/017</p> | <p>W.L. Gore & Co. Pleinfeld Germany</p> | Qualification | DLR | Jul 1994 |
| <p>Characteristics:</p> <p>All variants are qualified</p> <p>Voltage Rating, maximum (Vrms) : 600 Temperature Range (°C): -200 to +200</p> <p>I_{max} (A): 45, 81 and 133 for AWG: 0, 4 and 8, respectively</p> | | | | |
|  <p>ESCC European Space Components Coordination QPL</p> | <p>POWER WIRES FOR CRIMPING, LOW FREQUENCY, BASED ON TYPE SPP</p> | | <p>Certificate 215 K</p> | <p>Page 13-01 008</p> |


| | | | | |
|---|---|---------------------------------|-----------------------|----------------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| <p>Generic ESCC 3901</p> <p>Detail ESCC 3901/018</p> | <p>W.L. Gore & Co. Pleinfeld Germany</p> | Qualification | DLR | Jul 1994 |
| <p>Characteristics:</p> <p>Variants 01 to 88 are qualified.</p> <p>Voltage Rating, maximum (V^{rms}) : 600 Temperature Range (°C): -200 to +200</p> <p>Expanded PTFE, extruded polyimide/ FEP, sintered PTFE insulated wires. Expanded PTFE, extruded polyimide/fluorothermoplast insulated cables, shielded and jacketed.</p> | | | | |
|  | <p>WIRES AND CABLES, LOW FREQUENCY, INSULATED, POLYIMIDE/FLUOROTHERMOPLAST, BASED ON TYPE SPM</p> | <p>Certificate</p> <p>216 J</p> | | <p>Page</p> <p>13-01 009</p> |


| | | | | |
|--|---|--------------------|---------------------------------|------------------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| <p>Generic ESCC 3901</p> <p>Detail ESCC 3901/018</p> | <p>LEONI Special Cables GmbH Friesoythe Germany</p> | Qualification | DLR | Oct 2009 |
| <p>Characteristics:</p> <p>Variants 01 to 88 are qualified.</p> <p>Voltage Rating, maximum (V_{rms}) : 600 Temperature Range (°C): -200 to +200</p> <p>Expanded PTFE, extruded polyimide/ FEP, sintered PTFE insulated wires. Expanded PTFE, extruded polyimide/fluorothermoplast insulated cables, shielded and jacketed.</p> <p>Conductor silver thickness shall be 2.0µm minimum</p> | | | | |
|  <p>ESCC European Space Components Coordination QPL</p> | <p>WIRES AND CABLES, LOW FREQUENCY, INSULATED, POLYIMIDE/FLUOROTHERMOPLAST, BASED ON TYPE 3901018</p> | | <p>Certificate</p> <p>294 B</p> | <p>Page</p> <p>13-01 009-2</p> |


| | | | | |
|--|---|--------------------|---------------------------------|------------------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| <p>Generic ESCC 3901</p> <p>Detail ESCC 3901/018</p> | <p>AXON' CABLE Montmirail France</p> | Qualification | CNES | Dec 2009 |
| <p>Characteristics:</p> <p>Variants 03 to 09, 12 to 38, 41 to 56, 59 to 65, 68 to 74, 77 to 81, 84 to 88 are qualified AWG 30 and 32 variants are not qualified.</p> <p>Voltage Rating, maximum (V_{rms}) : 600</p> <p>Temperature Range (°C): -200 to +200</p> <p>Expanded PTFE, extruded polyimide/ FEP, sintered PTFE insulated wires.</p> | | | | |
|  <p>ESCC European Space Components Coordination QPL</p> | <p>WIRES AND CABLES, LOW FREQUENCY, INSULATED, POLYIMIDE/FLUOROTHERMOPLAST, BASED ON TYPE SPM</p> | | <p>Certificate</p> <p>300 B</p> | <p>Page</p> <p>13-01 009-3</p> |


| | | | | |
|--|---|--------------------------|----------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3901 Detail ESCC 3901/021 | W.L. Gore & Co. Pleinfeld Germany | Qualification | DLR | Feb 1996 |
| Characteristics: All variants (01 to 41) are qualified Voltage Rating, maximum (Vrms) : 600 Temperature Range (°C): -200 to +200 . | | | | |
|  | POLYIMIDE INSULATED SHIELDED CABLES WITH DRAIN WIRE, LOW FREQUENCY, BASED ON TYPE SPLD | Certificate 229 J | Page 13-01 010-1 | |


| | | | | |
|---|--|--------------------------|----------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3901 Detail ESCC 3901/021 | AXON' CABLE Montmirail France | Qualification | CNES | Jun 2009 |
| Characteristics: All variants are qualified Voltage Rating, maximum (Vrms) : 600 Temperature Range (°C): -200 to +200 . | | | | |
|  | POLYIMIDE INSULATED SHIELDED CABLES WITH DRAIN WIRE, LOW FREQUENCY, BASED ON TYPES 3901021**B | Certificate 293 C | Page 13-01 010-2 | |


| | | | | |
|---|--|------------------------------|---------------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| <p>Generic ESCC 3901</p> <p>Detail ESCC 3901/021</p> | <p>LEONI Special Cables GmbH Friesoythe Germany</p> | Qualification | DLR | Oct 2009 |
| <p>Characteristics:</p> <p>All variants 01 to 41 are qualified</p> <p>Voltage Rating, maximum (Vrms) : 600 Temperature Range (°C): -200 to +200</p> | | | | |
|  <p>ESCC European Space Components Coordination QPL</p> | <p>POLYIMIDE INSULATED SHIELDED CABLES WITH DRAIN WIRE, LOW FREQUENCY, BASED ON TYPE 3901021</p> | <p>Certificate 296 B</p> | <p>Page 13-01 010-3</p> | |


| | | | | |
|--|---|--------------------|---------------------------------|------------------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| <p>Generic ESCC 3901</p> <p>Detail ESCC 3901/020 ESCC 3901/022</p> | <p>Tyco Electronics Dorcan, Swindon England</p> | Qualification | UK Space Agency | Oct 1999 |
| <p>Characteristics: 3901/020: All variants (01 - 80) are qualified 3901/022: All variants (01 - 72) are qualified.</p> <p>Wires and Cables variants consist of 1, 2, 3 and 4 cores with and without jackets and shields</p> <p>ESCC Detail Specification No. 3901/020 cables are silver-plated copper braided, and ESCC Detail Specification No. 3901/022 cables are silver-plated copper spiral shielded, Wire sizes are in accordance with ISO 2635.</p> <p>Maximum voltage: 600 Vrms Operating temperature range (°C): -100 to +200</p> | | | | |
|  | <p>WIRES AND CABLES, LOW FREQUENCY, 600V, SILVER-PLATED COPPER, EXTRUDED CROSSLINKED MODIFIED ETFE, LIGHTWEIGHT</p> | | <p>Certificate</p> <p>257 G</p> | <p>Page</p> <p>13-01 011-1</p> |


| | | | | |
|--|---|--------------------|-----------------------------------|--------------------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| <p>Generic ESCC 3901</p> <p>Detail ESCC 3901/024</p> | <p>AXON' CABLE Montmirail France</p> | Qualification | CNES | Dec 2009 |
| <p>Characteristics:</p> <p>Variants 02 to 08, 10 to 16, 18 to 24, 26 to 32, 34 to 40, 42 to 48, 50 to 56, 58 to 64 are qualified AWG 30 variants are not qualified</p> <p>Wires and Cables variants consist of 1, 2, 3 and 4 cores with and without jackets and shields</p> <p>Maximum voltage: 600 Vrms</p> | | | | |
|  | <p>WIRES AND CABLES, LOW FREQUENCY, FLUROPOLYMER INSULATION, 600V, BASED ON TYPE CSWL</p> | | <p>Certificate 299 B</p> | <p>Page 13-01 012-1</p> |


| | | | | |
|--|---|--------------------|-----------------------------------|--------------------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| <p>Generic ESCC 3901</p> <p>Detail ESCC 3901/024</p> | <p>W.L. Gore Pleinfeld Germany</p> | Qualification | DLR | Jan 2011 |
| <p>Characteristics:</p> <p>Variants 01 to 64 inclusive are qualified The specification contains 64 variants with several wire sizes, single wires and cables with several cores, either shielded or unshielded.</p> <p>Cable construction: 1, 2, 3 and 4 twisted wires are in one core with or without shield</p> <p>Maximum voltage: 600 Vrms</p> | | | | |
|  | <p>WIRES AND CABLES, LOW FREQUENCY, FLUROPOLYMER INSULATION, 600V, BASED ON TYPE CSWL</p> | | <p>Certificate 305 B</p> | <p>Page 13-01 012-2</p> |

| | | | | |
|---|--|--------------------|-------------------------------|------------------------------------|
| Types covered by similarity: All variants 01 to 21 are qualified | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3901 Detail ESCC 3901/025 | W.L. Gore Pleinfeld Germany | Qualification | DLR | June 2014 |
| <p>Characteristics:</p> <p>The specification contains 21 variants with several wire sizes, single wires and cables with several cores, either shielded or unshielded.</p> <p>Cable construction: 1, 2, 3 and 4 twisted wires are in one core with or without shield</p> <p>Maximum voltage: 600 Vrms Operating temperature range (°C): -200 to +200</p> | | | | |
|  | <p>WIRES AND CABLES, LIGHTWEIGHT, EXTRA THIN, FLUORTHHERMOPLASTIC / POLYIMIDE INSULATED WIRES AND CABLES BASED ON TYPE CSC</p> | | <p>Certificate</p> <p>328</p> | <p>Page</p> <p>13-01 013-1</p> |

| | | | | |
|--|---|-------------------------|-----------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3902 Detail ESCC 3902/001 | Nexans Draveil France | Qualification | CNES | July 1979 |
| Characteristics: Variants 01, 02, and 03 are qualified Miniature flexible 50 ohm coaxial cable PTFE Dielectric Polyimide Jacketed, Double Shield and Shielded / Jacketed Maximum voltage: 900 Vrms Operating temperature range (°C): -80 to +200 (-100 for variant 01) | | | | |
|  | WIRES AND CABLES, RF COAXIAL, PTFE/POLYIMIDE INSULATION, BASED ON TYPE 50 CIS | Certificate 24 R | | Page 13-02 001 |


| | | | | | | | | | | | | |
|--|---|-----------------------------------|--------------------------------------|----------------------------|-----|-----------------|-----|-------------------------|-----|--|--|--|
| Types covered by similarity: | | Remarks: | | | | | | | | | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | |
| Generic ESCC 3902 Detail ESCC 3902/002 | AXON' CABLE Montmirail France | Qualification | CNES | Dec 2009 | | | | | | | | |
| <p>Characteristics:</p> <p>Variants encompass coaxial, triaxial, and balanced shielded line</p> <p>Variants 03 to 06, 10 to 12 and 20 to 25 are qualified</p> <p>Operating Voltage (Continuous), maximum ratings, (Vrms):</p> <table> <tr> <td>Variants 03</td> <td>180</td> </tr> <tr> <td>Variants 04, 10, 21 to 24</td> <td>200</td> </tr> <tr> <td>Variants 06, 25</td> <td>250</td> </tr> <tr> <td>Variants 05, 11, 12, 20</td> <td>300</td> </tr> </table> <p>AWG Range: 20, 22, 24, 26, 28 dependent on variant</p> | | Variants 03 | 180 | Variants 04, 10, 21 to 24 | 200 | Variants 06, 25 | 250 | Variants 05, 11, 12, 20 | 300 | | | |
| Variants 03 | 180 | | | | | | | | | | | |
| Variants 04, 10, 21 to 24 | 200 | | | | | | | | | | | |
| Variants 06, 25 | 250 | | | | | | | | | | | |
| Variants 05, 11, 12, 20 | 300 | | | | | | | | | | | |
|  | <p>WIRES AND CABLES, RADIO FREQUENCY, FLEXIBLE, COAXIAL, TRIAXIAL AND SYMMETRIC, BASED ON TYPE 3902/002</p> | <p>Certificate 298 B</p> | <p>Page 13-02 002-2</p> | | | | | | | | | |


| Types covered by similarity: | | Remarks: | | | | | | | | | | | | | | |
|--|--|---|--------------------------|-----------------------|--|-------------|--|-------------|----|----------------|-----|-----|----|----------------|-----|-----|
| Procurement Specifications | | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | |
| Generic ESCC 3902 Detail ESCC 3902/003 | | AXON' CABLE Montmirail France | Qualification | CNES | Jun 2009 | | | | | | | | | | | |
| Characteristics: Variant 01 AWG 28/07 (white) and variant 02 AWG 26/07 (blue) are qualified | | <table border="1"> <thead> <tr> <th>Variant</th> <th>Data Rate</th> <th>Operating Voltage (Continuous), (Vrms)</th> <th>Current (A)</th> </tr> </thead> <tbody> <tr> <td>01</td> <td>100Mb/s—400MHz</td> <td>200</td> <td>1.5</td> </tr> <tr> <td>02</td> <td>200Mb/s—400MHz</td> <td>200</td> <td>1.5</td> </tr> </tbody> </table> | | | Variant | Data Rate | Operating Voltage (Continuous), (Vrms) | Current (A) | 01 | 100Mb/s—400MHz | 200 | 1.5 | 02 | 200Mb/s—400MHz | 200 | 1.5 |
| Variant | Data Rate | | | | Operating Voltage (Continuous), (Vrms) | Current (A) | | | | | | | | | | |
| 01 | 100Mb/s—400MHz | 200 | 1.5 | | | | | | | | | | | | | |
| 02 | 200Mb/s—400MHz | 200 | 1.5 | | | | | | | | | | | | | |
| Temperature range (°C): -200 to +180 | | | | | | | | | | | | | | | | |
|  | WIRES AND CABLES, SPACEWIRE, ROUND, QUAD SYMMETRIC, FLEXIBLE, BASED ON TYPE SPACEWIR | | Certificate 291 C | | Page 13-02 003-1 | | | | | | | | | | | |


| | | | | |
|--|---|--------------------|--------------------------|----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3902 Detail ESCC 3902/003 | W.L. Gore Pleinfeld Germany | Qualification | DLR | Jan 2011 |
| Characteristics: Variant 01 AWG 28/07 (white) and Variant 02 AWG 26/07 (blue) are qualified, 100 Ω Data Rate, Operating Voltage (Continuous), Current Variant 01 100Mb/s—400 MHz 200V—1.5A Variant 02 200Mb/s—400 MHz 200V— 2.5A Temperature range (°C): -200 to +180 | | | | |
|  | WIRES AND CABLES, SPACEWIRE, ROUND, QUAD SYMMETRIC, FLEXIBLE, BASED ON TYPE SPACEWIRE | | Certificate 304 B | Page 13-02 003-2 |

Section 14**Component Type: Miscellaneous**

| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|----------------|-------|----------------------------|--------------|
| 14-16-99 | | | Switches | |
| | 14-16-99-003 | 275 E | Thermostatic, Bimetallic | COMEPA |
| 14-30-10 | | | Passive Devices, RF | |
| | 14-30-10-002-2 | 185 G | Coaxial Loads, 0 to 22 GHz | Radiall |
| | 14-30-10-004 | 178 H | Attenuators, Type R413 | Radiall |

| | | | | |
|--|---|--------------------|-----------------------------------|---------------------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3702 Detail 3702/001 | COMEPA BAGNOLET France | Qualification | CNES | Mar 2004 |
| <p>Characteristics:</p> <p>Variants 01 to 03 are qualified</p> <p>Range of Components: Grade 1 and Grade Y</p> <p>Maximum Ratings:</p> <p>Rated Current (I_R): 4 A (30 Vdc resistive)</p> <p>Operating Temperature Range ($^{\circ}\text{C}$), -50 to $+150$</p> | | | | |
|  <p>ESCC European Space Components Coordination QPL</p> | <p>SWITCHES, THERMOSTATIC, BIMETALLIC, SPST, OPENING CONTACT, BASED ON TYPE TH 47</p> | | <p>Certificate 275 E</p> | <p>Page 14-16 99-003</p> |

| Types covered by similarity: | | | | Remarks: | | | | | | | | | | | | | | | | | | | | | |
|--|----------------------------|--|--------------------------------|------------------------------|-------------------------------|----------------------------|------|--------------|-----------------------|---------------|------------------------|----------------------------|-------------------------------|--------------------------------|------------------------------|----|------|------|------|------|---|------|------|------|------|
| Procurement Specifications | | Manufacturer | | Nature of Approval | Supervising Authority | Initial Qualification Date | | | | | | | | | | | | | | | | | | | |
| Generic ESCC 3403 Detail 3403/006 | | RADIALL Saint-Quentin-Fallavier France | | Qualification | CNES | Jul 1992 | | | | | | | | | | | | | | | | | | | |
| Characteristics: All variants are qualified. 50 ohms DC to 22 GHz | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>Type</th> <th>Detail Spec.</th> <th>Frequency Range (GHz)</th> <th>Rated Pin (W)</th> <th>Impedance (Ω)</th> </tr> </thead> <tbody> <tr> <td>3403/006</td> <td>3403/006</td> <td>0-22</td> <td>1</td> <td>50</td> </tr> </tbody> </table> | | | | | | | Type | Detail Spec. | Frequency Range (GHz) | Rated Pin (W) | Impedance (Ω) | 3403/006 | 3403/006 | 0-22 | 1 | 50 | | | | | | | | | |
| Type | Detail Spec. | Frequency Range (GHz) | Rated Pin (W) | Impedance (Ω) | | | | | | | | | | | | | | | | | | | | | |
| 3403/006 | 3403/006 | 0-22 | 1 | 50 | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th rowspan="2">Type</th> <th colspan="4">VSWR max</th> </tr> <tr> <th>$0 < f(\text{GHz}) \leq 4$</th> <th>$4 < f(\text{GHz}) \leq 12.4$</th> <th>$12.4 < f(\text{GHz}) \leq 18$</th> <th>$18 < f(\text{GHz}) \leq 22$</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>1.05</td> <td>1.15</td> <td>1.20</td> <td>1.30</td> </tr> <tr> <td>2</td> <td>1.05</td> <td>1.15</td> <td>1.20</td> <td>1.25</td> </tr> </tbody> </table> | | | | | | | Type | VSWR max | | | | $0 < f(\text{GHz}) \leq 4$ | $4 < f(\text{GHz}) \leq 12.4$ | $12.4 < f(\text{GHz}) \leq 18$ | $18 < f(\text{GHz}) \leq 22$ | 1 | 1.05 | 1.15 | 1.20 | 1.30 | 2 | 1.05 | 1.15 | 1.20 | 1.25 |
| Type | VSWR max | | | | | | | | | | | | | | | | | | | | | | | | |
| | $0 < f(\text{GHz}) \leq 4$ | $4 < f(\text{GHz}) \leq 12.4$ | $12.4 < f(\text{GHz}) \leq 18$ | $18 < f(\text{GHz}) \leq 22$ | | | | | | | | | | | | | | | | | | | | | |
| 1 | 1.05 | 1.15 | 1.20 | 1.30 | | | | | | | | | | | | | | | | | | | | | |
| 2 | 1.05 | 1.15 | 1.20 | 1.25 | | | | | | | | | | | | | | | | | | | | | |
| Operating Temperature Range ($^{\circ}\text{C}$), -55 to +125 | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | PASSIVE DEVICES, R.F. COAXIAL LOADS, 0-22 GHz BASED ON TYPE R404 | | | Certificate 185 G | | | | | | | | | | | | | | | | | | | | |
| | | | | | Page 14-30 10-002-2 | | | | | | | | | | | | | | | | | | | | |

| | | | | |
|---|--|--------------------|--------------------------|-----------------------------|
| Types covered by similarity: | | Remarks: | | |
| Procurement Specifications | Manufacturer | Nature of Approval | Supervising Authority | Initial Qualification Date |
| Generic ESCC 3403 Detail 3403/005 | RADIALL Saint-Quentin-Fallavier France | Qualification | CNES | Jan 1991 |
| Characteristics: Variants 01 to 31 Frequency range (GHz): 0 - 22 Attenuation (dB): 0 - 20 Operating Temperature Range (°C), -55 to +125 | | | | |
|  | R.F. ATTENUATORS FIXED, COAXIAL BASED ON TYPE R413 | | Certificate 178 H | Page 14-30 10-004 |

Section 18**Component Type: Optoelectronics**

| Sub-Section | Page No. | Cert. | Type Designation | Manufacturer |
|-------------|----------|-------|---|--------------|
| | | | Currently there are no qualified sources of Optoelectronics | |



SECTION 18-: INDEX OF OPTOELECTRONICS**

REP005 Updated on 15 Jul 2015