

		APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL			Page 1 Appl. No. 219 L
Component Title: Polymide Insulated wires & cables Low Frequency, 600V, -200°C to +200°C, based on type SPL according ESCC Det. Spec. 3901/019					
Executive Member: DLR			Date: 04.08.2016		
Components (including series and families) submitted for Qual. App. 1					
ESCC COMP. NO.	VARIANTS	RANGE OF COMPONENTS	BASED ON	TEST VEHICLE / S	COMPONENT SIMILAR
3901/019	01 to 94	All	SPL	3901/019-58B	
Component Manufacturer WL Gore & Associates GmbH		Location of manufacturing plant Nordring1 91785 Pleinfeld Germany		Date of original qualification approval November 1994 Certificate Ref. No. 219	
ESCC Specifications used for maintenance Generic: ESCC 3901 Issue 2 Details: ESCC 3901/019 Issue 3		Deviations for testing level B, LAT1 and Detail Spec. used: No <input checked="" type="checkbox"/> Yes <input type="checkbox"/> (supply details) (in Box 15) Deviation from current Spec. No <input checked="" type="checkbox"/> Yes <input type="checkbox"/> (supply details)		Qualification Extension Report ref. and date: T.D.R.-No. 6579-5 20.07.2016	
Summary of procurement or equivalent test results during current validity period in support of this application (those to ESCC EXECUTIVE listed first) 8					
Project Name	Testing Level	LAT	Date code	Quantity Delivered	
See Appendix "Order list space products ESCC 3901019 2016.pdf"	3901	CoC LAT 1&2	See appendix	See appendix	
PID Changes since Original Qual. or last extension of Qual. 9 None <input type="checkbox"/> Minor* <input checked="" type="checkbox"/> * provide detail Minor updates Major* <input type="checkbox"/>		Current PID Verified by: G. Joormann Name Executive Responsible Ref. No.: PLFWI-1491 (ESCC 3901/019) Issue: 2 Date: 04.08.2016 Rev. E Date: 13.06.2016			
Current Manufacturing Facilities surveyed by G. Joormann on 27.-28.10.2015 (Name Executive Responsible) (date) Satisfactory: Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Explain REF: GORE-AU-2015					

Component Title: **Polyimide Insulated wires & cables Low Frequency, 600V, -200°C to +200°C, based on type SPL according ESCC Det. Spec. 3901/019**

Date: 04.08.2016

219 L

Ref. No's and purpes:

12

i. A. G. Jean

I.A. G.Joormann

(Signature of the ESCC Executive Representative)

13

Continuation of Boxes above:

14

