

### APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component Title:

Polyimide Insulated Shielded Cables With Drain Wire, Low Frequency,

Appl. No.

Page 1

600V, -200 To +200°C Based On Type SPLD CNES 28/06/2017 Executive Member: 268G Components (including series and families) submitted for Extension of Qualification Approval: COMPONENT BASED TEST VARIANTS RANGE OF COMPONENTS VEHICLE / S SIMILAR COMP. NO ON SPLD 3901 019 66: 3901 009 3901 019 01 to 94 Voltage Rating, maximum (Vrms): 3 twisted AWG26 3901 018 Temperature Range (°C): -200 to wires, helical shielded, jacket All variants including AWG 30 are 3901 021 qualified 4 Component Manufacturer 2 Location of Manufacturing Plant 3 Axon'Cable SA Date of original qualification approval: Axon Route de Chalons enChampagne Date: 15/06/2002 51210 Montmirail Certificate Ref No. 268 6 7 5 ESCC Specifications used for Deviations to LVT testing and Detail Specification Qualification Extension Report Maintenance of qualification testing: used: reference and date: Generic: 3901 (supply details in Box TEST REPORT N°3929 Issue A, 27th March 2017 No Detail(s): 3901 019 Deviation from current Specifications: (Supply details) 8 Summary of procurement or equivalent test results during current validity period in support of this application (those to ESCC listed first) Quantity Delivered LAT Project Name **Testing Level** Date code See appendix 10 9 **CNES** PID changes since start of qualification Current PID Verified by: Name of Excutive Representative None Ref No: ESA-PID-01-AXON Minor\* X 01/12/2016 Date: Issue: 14 Major\* \*Provide detail 01/12/2016 Rev Date: 11 Current Manufacturing facilities surveyed by: CNES 09/06/2015 (Name of Executive Representative) (Date) Satisfactory: Explain Yes × No AXON-AU-2015

	APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL				Page 2			
<b>ESCC</b>	Component title:	Polyimide Insulated Shielded Cables With Drain Wire, Low Fred 600V, -200 To +200°C Based On Type SPLD			n Wire, Low Frequency,	Appl. No.		
	Executive Member:	CNES			Date:	28/06/2017	2680	3
Failure Analysis, DPA, NCCS ava	ilable: Yes		√lo ⊠	(Supply data)	Click h	nere to enter text.		12
The undersigned hereby certifies on behalf that the appropriate documentation has bee except as stated in box 15; - that the reports as the responsible Ex Date: Click here to enter a date.	en evaluated; - that ful s and data are availab	complian	ce to all ES	CC requirements i	s evidend applies of to the co	on behalf of emponent(s) listed herein.		13
28/6/2017					((\$	Signature of the Executive (	Coordinator)	
Continuation of Boxes above:								14

# ESCC

## APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component title: Polyimide Insulated Shielded Cables With Drain Wire, Low Frequency,

Page 3

TO SOUTH		~	600V, -200 To +200°C	Based On Type SPLD		Appl. No.	
100	A	Executive Me	ember: CNES	Date:	28/06/2017	268G	
Noncompliance t	to ESCC_requirements:	,				13	
No.: Specification			Paragraph		Non compliance		
				ľ			
Additional tasks	required to achieve full o	compliance for E	SCC qualification or rationale fo	r acceptability of		14	
noncompliance:							
Evenutive Mens	ace Disposition						
Executive Mana	~					15	
Application Appl		No 🗆					
Action / Remark	s:						
				*			
				3			
				×	11		
					W J	X.	
Date: Click h	ere to enter a date.						
				Sigr	ature, ESA Representation	/e	



### APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component title:

Polyimide Insulated Shielded Cables With Drain Wire, Low Frequency, 600V, -200 To +200°C Based On Type SPLD

Executive Member:

CNES

Date: 28/06/2017

Appl. No. 268G

Page 4

## NOTES ON THE COMPLETION OF THE APPLICATION FORM FOR ESCC QUALIFICATION EXTENSION APPROVAL

ENTRIES	
ENTRIES Form heading	shall indicate: - the title of the component as given in its detail specification or the name of the series, family; - the Executive Member; - the entering date; - the certificate number and its sequential suffix.
Box 1	shall provide details given in the table; in particular there shall be listed: - the variants or range of variants; - the range of components (the ESCC code is recommended to indicate the values or values range, the tolerance, the voltage, etc); the designation given in the detail specification as 'base on'; - under Test Vehicle enter either an ESCC code or the specific characteristic capable of identifying the component tested (e.g., voltage of coil for a relay); - under component similar enter a cross if relevant.
Box 2; 3 and 4	As per QPL entry; otherwise, an explanation of the changes must be supplied.
Box 5	Will show the ESCC Generic and Detail specifications, including issue number and revision letter, current at the time the tests reported were performed. If the specifications are different from those current on the date of the application, see Box 6.
Box 6	Will show the deviations from the Generic and Detail Specifications listed in Box 5, in particular deviations from testing. In case of deviations this must be listed in Box 15. In case the referenced specification in Box 5 have currently a different issue and/or revision indicate also whether the test data deviates or not from such current documents.
Box 7	Must reference the report(s) supplied in support of the application.
Box 8	Should provide details of procurement to the full ESCC System, documentation of all of which should already have been delivered to the ESCC Executive under the terms of the relevant Generic Specification. An appropriate table has been drawn in this box.
Box 9	If the PID evolved after the Original Qualification or after the last Extension of Qualification, adequate details of such evolution shall be provided together with the reasons for the changes. Major changes shall be clearly marked.
Box 10	Identify the current PID issue status, date and actual date of verification. The date of verification of the current PID should be arranged as close as possible to the required date of extension.
Box 11	This box can be completed only after a physical visit to the plant to confirm that no unexplained changes occurred and that the practices, procedures, material, etc. used in manufacturing the components are as described in the PID. This survey shall be carried out in accordance with the requirements of ESCC Basic Specification No. 20200 and its findings shall be recorded.
Box 12	Provide details of, or reference to, any Destructive Physical Analysis (DPA) and Failure Analysis reports as well as any Nonconformance(s) (NCCS) occurred during the qualification validity period, stating if established corrective action have produced satisfactory results.
Box 13	Enter only the name of the Executive Member (i.e., CNES, DLR, ESTEC, etc.) and the signature of the responsible Executive Coordinator.
Box 14	To be used when there is a need to expand any of the boxes from 1 through 12. Identify box affected and reference the Box 14 in the relevant Box. Box 14 can be broken into 14a, 14b, etc. if several boxes have to be expanded.
Box 15	State noncompliance with reference to specification(s) and paragraph(s). To simplify reference in Box 16 each nonconformance shall be sequentially numbered. If relevant state 'None'.
Box 16	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
Box 17	All Executive Manager recommendations on the application itself, special conditions or restrictions, modifications of the QPL entry, letters to the manufacturer, etc. shall be entered clearly in Box 17, signed by the representative for ESA, and dated.