

6.15.2 Attenuator and Load

PASSIVE DEVICES, R.F. COAXIAL LOADS, 0-22 GHZ BASED ON TYPE R404				185H
Procurement Specifications	Manufacturer	Nature of Approval	Supervising Authority	Initial Qualification Date
Generic ESCC 3403	RADIALL Saint-Quentin-Fallavier France	Qualification	CNES	Jul 1992
Detail ESCC 3403/006		Remarks		
Qualified range:				
All variants are qualified. 50 ohms DC to 22 GHz				
Type	Detail Spec.	Frequency Range (GHz)	Rated Pin (W)	Impedance (Ω)
3403/006	3403/006	0-22	1	50
Type	VSWR max			
	0<f(GHz)≤4	4<f(GHz)≤12.4	12.4<f(GHz)≤18	18<f(GHz)≤22
1	1.05	1.15	1.20	1.30
2	1.05	1.15	1.20	1.25
Operating Temperature Range (°C), -50 to +150				

R.F. ATTENUATORS FIXED, COAXIAL BASED ON TYPE R413				178J
Procurement Specifications	Manufacturer	Nature of Approval	Supervising Authority	Initial Qualification Date
Generic ESCC 3403 Detail ESCC 3403/005	RADIALL Saint-Quentin- Fallavier France	Qualification	CNES	Jan 1991
Remarks				
Qualified range: Variants 01 to 31 Frequency range (GHz): 0 - 22 Attenuation (dB): 0 - 20 Operating Temperature Range (°C), -55 to +125				