

LATEST NEWS



[ESCC QPL June 2018](#)

The ESCC QPL June was published with 7 extensions, 1 revision and 1 new certificate

For more information, please click [HERE](#)

[EPPL \(European Preferred Parts List \) issue 35](#)

The ESCC EPPL issue 35 was published February 2018.

[ESCC QML January 2018](#)

The ESCC QML issue 16 was published in January 2018 to include: Addition of Process Capability Approval of 3D PLUS (France)



[NEW ESCC Process Capability Approval](#)

3D Plus is now certified in accordance with ESCC 2566001 for its 3D Staking Technology Modules!!



NEW ESCC Specification Published:9012/003

June 2018: 9012/003:Monolithic Microwave Integrated Circuit (MMIC) InGaP HBT HB20M Process from UMS, Voltage Controlled Oscillator 2.75-3GHz (CHV1203-98S)

Issue 1. Please click [HERE](#) for more information.



NEW ESCC Specification Published:9012/004

June 2018: 9012/004:Monolithic Microwave Integrated Circuit (MMIC) InGaP HBT HB20M Process from UMS, Voltage Controlled Oscillator 5.5-6.1 GHz (CHV1206-98S)

Issue 1. Please click [HERE](#) for more information.

UPCOMING EVENTS



[NSREC 2018](#)

NSREC 2018 will take place in Kona, Hawaii from 16 - 20 of July 2018. For more information, please click [HERE](#)



[Radecs 2018](#)

Radecs will take place in Gothenburg, Sweden from 16th to 21st of September 2018. For more information, please click [HERE](#)

RECENTLY PUBLISHED ESCC SPECIFICATION

New ESCC Specifications published since 15th May 2018

Number	Title	I
<u>3401/088</u>	CONNECTOR SAVERS, ELECTRICAL, RECTANGULAR, MICROMINIATURE, NON-REMOVABLE GAUGE 26 CONTACTS, BASED ON TYPE 8MCG	1
<u>9012/003</u>	Monolithic Microwave Integrated Circuit (MMIC) InGaP HBT HB20M Process from UMS, Voltage Controlled Oscillator 2.75-3GHz (CHV1203-98S)	1
<u>9012/004</u>	Monolithic Microwave Integrated Circuit (MMIC) InGaP HBT HB20M Process from UMS, Voltage Controlled Oscillator 5.5-6.1 GHz (CHV1206-98S)	1

Up-Issued ESCC Specifications published since 15th May 2018

Number	Title
<u>3010/005</u>	Capacitors Variable Concentric Trimmer Air Dielectric 1 to 10 pF Body Diameter 9.8 mm
<u>3010/006</u>	Capacitors Variable Concentric Trimmer Air Dielectric 1.4 to 14 pF Body Diameter 7.6 mm
<u>3010/007</u>	Capacitors Variable Concentric Trimmer Air Dielectric 1.4 to 16 pF Body Diameter 7.6 mm
<u>3010/008</u>	Capacitors Variable Concentric Trimmer Air Dielectric 1 to 20 pF Body Diameter 8 mm
<u>3010/009</u>	Capacitors Variable Concentric Trimmer Air Dielectric 1 to 30 pF Body Diameter 8 mm
<u>3010/010</u>	Capacitors Variable Concentric Trimmer Air Dielectric 0.8 to 6 pF Body Diameter 6.2 mm
<u>3010/011</u>	Capacitors Variable Concentric Trimmer Air Dielectric 1 to 10 pF Body Diameter 6.2 mm
<u>3010/012</u>	Capacitors Variable Concentric Trimmer Air Dielectric 0.6 to 3.5 pF Body Diameter 4.6 mm
<u>3010/013</u>	Capacitors Variable Concentric Trimmer Air Dielectric 0.6 to 5 pF Body Diameter 4.6 mm
<u>3010/014</u>	Capacitors Variable Concentric Trimmer Sapphire Dielectric 0.8 to 8 pF Body Diameter 3.0 mm

3010/015	Capacitors Variable Concentric Trimmer Sapphire Dielectric 0.6 to 4.5 pF Body Diameter 3.0mm
3010/016	Capacitors Variable Concentric Trimmer Sapphire Dielectric 0.4 to 2.5 pF Body Diameter 3.0 mm
3010/017	Capacitors Variable Concentric Trimmer Sapphire Dielectric 0.2 to 1.2 pF Body Diameter 1.9 mm
3403	Generic Specification for Attenuators and Loads RF Coaxial Fixed
3403/004	Load, RF, Coaxial, Type SMA, DC-18GHz
3403/005	Attenuator, RF Coaxial, Type SMA, DC-22GHz
3403/006	Load RF Coaxial Type SMA, DC-22GHz
3403/008	Attenuator, RF Coaxial, Type SMA 2.9, DC-31.5GHz
3403/009	Load, RF, Coaxial, type SMA 2.9, DC-31.5 GHz
3403/010	Load, RF, Coaxial, Type TNC, DC-18GHz