Component Title:

Integrated Circuits, Pulse Width Modulator, based on types ST1843 and ST1845

Page 1

Appl. No.

			xecutive Memi	ber:	CNES				C	ate: 07/12/2018		344A	
Components (including	ng series and famili	es) s	ubmitted for Ex	xtension	n of Qualifica	ation	Approval:						1
ESCC COMPONENT NO.	VARIANTS		RANGE OF COMPONENTS					BASED ON				OMPONEN SIMILAR	Т
9108/020	01, 02		Flat Pack 8 ST1843										
9108/021	01, 02		Flat Pack 8			ST1845			Lot 3344600FZW Lot 33311003Z5	ST1843			
									HCC4071BKG (Lot 333218001Z7) FP16	Similar Box 16	rity with FP8 5)	(se	
Component Ma	ınufacturer	2			anufacturing			3					4
STMicroelectronics		3, rue de Suisse BP4199, 35041 Rennes Cedex					Date of original qualification approval: Date: 14/11/2016 Certificate Ref No. 344						
ESCC Specifications	upad for	5	6						Name and the same of the same			7	
Maintenance of qualif			Deviations to LVT testing and Detail Specification used:						fication Extension Report ence and date:				
Generic: 9000	Issue: 8		No ⊠ Yes □ (supply details in Box 15)				Full F4-3344600ZW DC 1627A ST1845FKG 9/05/18 F4-SG2-33311003Z5 DC1734A ST1845FKG 16/02/17				8		
Detail(s): 9108/020 9108/021			Deviation from current Specifications:				Full F	4-333218001Z7 DC 1701	1A HCC4	071BKG 3/7	/17		
			No ⊠ Yes □ (Supply details)										
			V-18										8
					alidity period	l in s	upport of this	s ap	plicatio	n (those to ESCC listed fi	irst)		
Project Name See in appendix	Testing Lev	/el	ļ	AT	-		Date code	315		Quantity	Delivered	t	
			ļ										
					ĺ								
PID changes since sta	rt of qualification			9	Current P	ID \	Verified by:						10
None								Name of Excutive Representative					
Minor* ⊠ Major* □ *	Provide details in t			Ref No: Issue:			11/2	018 (P	MM) & 8097046 18/9/18 ((generic)			
	Frovide details in t	JUX.			Rev Date:		6 & 20			Date:			
Current Manufacturing	facilities our reveal				011								11
Odirent Mandractoring	racililes surveyed	by.	-	(Name	CNI e of Executiv		epresentative	-)	on on		(10/2018 (Date)		
Satisfactory:	Yes ⊠		No 🗆		olain			-/		,	, outo,		
Report Reference:	CR-Activités	STC	Octobre 2018	_									

		APPLICAT	ION F	OR EXT	ENSION	OF ESCC QUAI	LIFICATI	ON APPROVAL	Page	2
P. W.	ESCC	Component title:		grated Ci ST1845	rcuits, F	Pulse Width Modu	lator, bas	ed on types ST1843	Appl.	
		Executive Member:	CI	NES			Date:	07/12/2018	344	A
Failure	e Analysis, DPA, NCCS a	vailable: Yes		No	\boxtimes	(Supply data)				12
Ref. No	s and purposes:									
that the (except CNES	lersigned hereby certifies on beha appropriate documentation has b as stated in box 15;) - that the re as the responsible Executive Me	een evaluated; - that fu ports and data are avail	ll comp	oliance to	all ESC	CC requirements i	is eviden	s on hehalf of	- When	13
Date:	11/12/2018						-/9	JP. BUSSENO		
Continua	ation of Boxes above:									14

Component title:

Integrated Circuits, Pulse Width Modulator, based on types ST1843 and ST1845

Executive Member: CNES

Date: 07/12/2018

B. Schade, Head of ESA Product Assurance and Safety Department

Page 3 Appl. No.

344A

				-
Non com	pliance to ESCC requirements:			15
No.:	Specification	Paragraph	Non compliance	
Additiona	I tasks required to achieve full compliance for liance:	ESCC qualification or rationale for acceptability	of	16
lo accum flat pack	nulate data on a recent date code lot, F4 SG1 and ST18 same die attach is used Same backside Same metal layer Same wire bonding diameter	& SG3 tests (environmental/mechanical/assemi 43 product can be considerered as similar for ti	bly capability) are performed on HCC4071 productive tests performed for the following reasons:	et in
	e Manager Disposition on Approval: Yes 🖬 No 🗆 demarks:			17
Date:			3.21	



Component Title: Integrated Circuits, Pulse Width Modulator, based on types ST1843 and ST1845

Executive Member: CNES Date: 07/12/2018

Page 4 Appl. No.

344A

18

ANNEX 1: LIST OF TESTS DONE TO SUPPORT EXTENSION OF QUALIFICATION

Tests conducted in compliance with:

ESCC 9000 generic specification; Chart F4 (for ESCC/QPL parts);

Or PID-TFD

(for ESCC/QML parts)

Tests vehicle identification/description:

3344600ZW DC 1627A ST1845FKG (Full F4)	33311003Z5 DC1734A ST1845FKG (SG2)
333218001Z7 DC 1701A HCC4071BKG (Full F4)	

Detail Specification reference:

Chart F4	Test	Tick when done	Conditions	Date Code Diffusion Lot	Tested Qty	No. of Rejects	Comments if not performed. Comments on Rejection
	Mechanical Shock		MIL-STD-883, Test Method 2002	1627 1701	15 + 15	0	
	Vibration		MIL-STD-883, Test Method 2007	1627 1701	15 + 15	0	
	Constant Acceleration	\boxtimes	MIL-STD-883, Test Method 2001	1627 1701	15 + 15	0	
<u>o</u>	Seal (Fine and Gross Leak)		MIL-STD-883, Test Method 1014	1627 1701	15 + 15	0	
Environmental/Mechanical Subgroup	Intermediate and End-Point Electrical Measurements	×	Intermediate and End-Point Electrical Measurements in the Detail Specification	1627 1701	15 + 15	0	
	External Visual Inspection	\boxtimes	ESCC Basic Specification No. 20500	1627 1701	15 + 15	0	
	Thermal Shock	\boxtimes	MIL-STD-883. Test Method 1011	1627 1701	15 + 15	0	
	Moisture Resistance	×	MIL-STD-883, Test Method 1004	1627 1701	15 + 15	0	
	Seal (Fine and Gross Leak)	\boxtimes	MIL-STD-883, Test Method 1014	1627 1701	15 + 15	0	
	Intermediate and End-Point Electrical Measurements	×	Intermediate and End-Point Electrical Measurements in the Detail Specification	1627 1701	15 + 15	0	
	External Visual Inspection	×	ESCC Basic Specification No. 20500	1627 1701	15 + 15	0	



Component title:

Integrated Circuits, Pulse Width Modulator, based on types ST1843 and ST1845 $\,$

Executive Member: **CNES**

Date: 07/12/2018

Page 5 Appl. No.

344A

Chart F4	Test	Tick when done	Conditions	Date Code Diffusion Lot	Tested Qty	No. of Rejects	Comments if not performed. Comments on Rejection
e Subgroup	Operating Life	×	MIL-STD-883, Test Method 1005	1734 1627	15 + 15	0	
	Intermediate and End-Point Electrical Measurements	M	Intermediate and End-Point Electrical Measurements in the Detail Specification	1734 1627	15 + 15	0	
Endurance	Seal (Fine and Gross Leak)	×	MIL-STD-883, Test Method 1014	1734 1627	15 + 15	0	
Enc	External Visual Inspection	×	ESCC Basic Specification No. 20500	1734 1627	15 + 15	0	
roup	Permanence of Marking		ESCC Basic Specification No. 24800				Not applicable
Subg	Terminal Strength	⊠	MIL-STD-883, Test Method 2004	1627 1701	5 + 5	0	
Assembly Capability Subgroup	Internal Visual Inspection		ESCC Basic Specification No. 20400	1627 1701	5 + 5	0	
mply (Bond Strength	⊠	MIL-STD-883 Test Method 2011	1627 1701	2 + 2	0	
Assei	Die Shear or Substrate Attach Strength	×	MIL-STD-883 Test Method 2019 or 2027	1627 1701	2+2	0	
onal Is	RGA	Ø	MIL-STD-883 Test Method 1018.7	1627	3	0	
Additional Tests							
Ă							



Box 22

Additional Comments.

APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Integrated Circuits, Pulse Width Modulator, based on types ST1843 and ST1845 $\,$ Component title:

Executive Member: CNES Date: 07/12/2018 Page 7

Appl. No. 344A

NOTES ON THE COMPLETION OF THE APPLICATION FORM FOR ESCC QUALIFICATION EXTENSION APPROVAL

1	NOTES ON THE COMPLETION OF THE APPLICATION FORM FOR ESCC QUALIFICATION EXTENSION APPROVAL
ENTRIES Form heading	shall indicate: - the title of the component as given in its detail specification or the name of the series, family; - the Executive Member; - the entering date; - the certificate number and its sequential suffix.
Box 1	shall provide details given in the table; in particular there shall be listed: - the variants or range of variants; - the range of components (the ESCC code is recommended to indicate the values or values range, the tolerance, the voltage, etc); the designation given in the detail specification as 'base on'; - under Test Vehicle enter either an ESCC code or the specific characteristic capable of identifying the component tested (e.g., voltage of coil for a relay); - under component similar enter a cross if relevant.
Box 2; 3 and 4	As per QPL entry; otherwise, an explanation of the changes must be supplied.
Box 5	Will show the ESCC Generic and Detail specifications, including issue number and revision letter, current at the time the tests reported were performed. If the specifications are different from those current on the date of the application, see Box 6.
Box 6	Will show the deviations from the Generic and Detail Specifications listed in Box 5, in particular deviations from testing. In case of deviations this must be listed in Box 15. In case the referenced specification in Box 5 have currently a different issue and/or revision indicate also whether the test data deviates or not from such current documents.
Box 7	Must reference the report(s) supplied in support of the application.
Box 8	Should provide the details of procurement to the full ESCC System, documentation of all of which should already have been delivered to the ESCC Executive under the terms of the relevant Generic Specification. An appropriate table has been drawn in this box.
Box 9	If the PID evolved after the Original Qualification or after the last Extension of Qualification, adequate details of such evolution shall be provided together with the reasons for the changes. Major changes shall be clearly marked.
Box 10	Identify the current PID issue status, date and actual date of verification. The date of verification of the current PID should be arranged as close as possible to the required date of extension.
Box 11	This box can be completed only after a physical visit to the plant to confirm that no unexplained changes occurred and that the practices, procedures, material, etc. used in manufacturing the components are as described in the PID. This survey shall be carried out in accordance with the requirements of ESCC Basic Specification No. 20200 and its findings shall be recorded.
Box 12	Provide details of, or reference to, any Destructive Physical Analysis (DPA) and Failure Analysis reports as well as any Nonconformance(s) (NCCS) occurred during the qualification validity period, stating if established corrective action have produced satisfactory results.
Box 13	Enter only the name of the Executive Member (i.e., CNES, DLR, ESTEC, etc.) and the signature of the responsible Executive Coordinator.
Box 14	To be used when there is a need to expand any of the boxes from 1 through 12. Identify box affected and reference the Box 14 in the relevant Box. Box 14 can be broken into 14a, 14b, etc. if several boxes have to be expanded.
Box 15	Fill in Table as requested.
Box 16	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
Box 17	All Executive Manager recommendations on the application itself, special conditions or restrictions, modifications of the QPL or QML entry, letters to the manufacturer, etc. shall be entered clearly in Box 19, signed by the representative for ESA, and dated.
Box 18	Fill in Table as requested.
Box 19	Confidential Details of PID changes including those of a confidential nature, shall be provided.
Box 20	State noncompliance with reference to specification(s) and paragraph(s). To simplify reference in Box 16 each nonconformance shall be sequentially numbered. If relevant state 'None'.
Box 21	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.