

Component Title: Schottky Barrier Power Diodes based on type STPS

Executive Member: CNES Date: 04/02/2020

Appl. No. 272H-rev1

Page 1

Components (including series and families) submitted for Extension of Qualification Approval:

		0, 0	Jennica for Exterioral	or addinioation	· / ippiov	u.,					
ESCC COMPONENT NO.	VARIANTS		RANGE OF COMPONENTS			BASED ON		TEST VEHICLE / S	COMPONENT SIMILAR	7	
5106/016	05, 06, 07, 11		TO-254, SMD0.5, SMD1		STP	STPS20100		33420006ZM TO254			
5106/017	01,02		SMD0.5		-	STPS1045		33510003ZE SMD.5	i		
5106/018	02	i	SMD1		4 -55	\$6045	1	33652003ZU SMD.5	i -		
5106/019	03, 05		TO254, SMD1		0.00	\$40100		33633001ZZ SMD1			
5106/023	01, 02		SMD.5			STPS60A150 STPS80A150		33648006ZZ SMD.5			
5106/024 01, 02, 03		SMD.5, TO-254AA			STPS80A45C STPS40A45C		ID33652003ZU SMD.5				
Component Ma	anufacturer	2	Location of Manufacturing Plant(s)			3				4	
STMicroelectronics	_		3, rue de Suisse BP4199, 35041 Rennes				Date	of original qualification ap	proval:		
						Date: 01/11/2002 Certificate Ref No. 272					
		1000				_					
	L	5				6				7	
ESCC Specifications Maintenance of quali			Deviations to LVT testing and Detail Specification used:				Qualification Extension Report reference and date:				
Generic: 5000	Issue: 3		No ⊠ Yes	(supply	details i	n Box	10.0.0	and date.			
Detail(s): 5106/01	Detail(s): 5106/016 Issue: 8			15) Deviation from current Specifications:				STPS1045 Lot ID33510003ZE_Chart F4 9/2/18 STPS60A45 Lot ID33652003ZU_Chart F4 (PINK hoven			
5106/01 5106/01							STPS	qualification) 12/7/18 STPS80150 Lot ID33633001ZZ_Chart F4 Sg1&3			
5106/01	9 7						12/7/	18 20100 Lot ID33420006Z	M Chart E4 21/2/17		
5106/02 5106/02								ation report STPS40170:		g	
3100/02			No ⊠ Yes	□ /Suppl	u dotaile\		Iss.2	(equivalent to STPS80A1	50 but single die)	rec.	
			No 🛭 Yes	☐ (Suppl	y details)	,		fication report STPS60A1 348006ZZ Chart F4 sg28			
							Evalu	ation report STPS3045: I			
							Iss.1	fication report STPS60A4	5 (same die as		
							STPS	880A45) Lot ID336520032	ZU Chart F4		
									3 - 1		
									11//2	Τ,	
Summany of procurer	ment or equivalent to	et re	sculte during ourrent vo	lidity period in	cupport 4	of this on	nlication	n (those to ESCC listed 6	rot\	8	
Summary of procurement or equivalent test re Project Name Testing Level			LAT	lidity period in	Date co		plication		Delivered		
1 Tojoot Hume	resulty Lev	Ci	1		Date co	oue	-	Quantity	Delivered		
				i			i				
	1		Ĭ	1			- 1				
PID changes since at	art of qualification		9	Current PID	Vorifical	bur		CNEC		40	
PID changes since st	art or qualification		[a	Current PID	veniled		ame of	CNES	l	10	
None 🗵				D-CN-	00075			Excutive Representative	Net of the same of		
Minor* □				Ref No:		16 (gener v Diodes		21 and 8122351 (specific	c Power Rectifier and		
Major* □	*Provide details in b	OY.		Issue:		.,	,,,,,,	Date:	04/02/2020		
,	1 TOVIGE GETAILS III E	OA.		Rev Date:	12/02/2	2019			0 //02/2020		
11											
Current Manufacturing facilities surveyed by:			CNES			on 20/05/2019		ւ /05/2019			
						(Data)					
(Name of Executive Representative Agency) (Date)											
Satisfactory: Yes ☑ No □ Explain											
Report Reference:	CR-Etude SMI	05 S	T Mai 2019								

APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL Page 2 Schottky Barrier Power Diodes based on type STPS Appl. No. Component title: 272H-rev1 04/02/2020 Date: CNES Executive Member: 12 (Supply data) \boxtimes Yes No Failure Analysis, DPA, NCCS available: Ref. No's and purposes: 13 The undersigned hereby certifies on behalf of the ESCC Executive - that the above information is correct; - that the appropriate documentation has been evaluated; - that full compliance to all ESCC requirements is evidence (except as stated in box 15;) - that the reports and data are available at the ESCC Executive and therefore applies on behalf of CNES as the responsible Executive Member for ESCC qualification status to be extended to the component(s) listed herein. JP. BUSSENOT 06/02/2020 Date: (Signature of the Executive Coordinator) 14 Continuation of Boxes above:



Component title:

Schottky Barrier Power Diodes based on type STPS

Page 3 Appl. No.

Executive Member:

CNES

Date: 04/02/2020

272H-rev1

Non comp	pliance to ESCC requirements:			15			
No.:	Specification	Paragraph	Non compliance				
Additiona	Il tasks required to achieve full compliance for	ESCC qualification or rationale for acceptability	of	16			
noncomp	liance:						
-	Environmental/mechanical subgroup and a SMD1 package covered by tests on STPS SMD.5 package covered by tests on STPS TO254 package covered by tests on STPS	80150 1045					
-	- Endurance subgroup: STPS40100 covered by tests on STPS6045 STPS80A150 covered by tests on STPS60A150 STPS40100 covered by tests on STPS20100 STPS6045 covered by tests on STPS1045						
i e i	Process modification : Soft solder die attach modification covered	by tests on STPS60A45					
Executive	e Manager Disposition			17			
Application	on Approval: Yes 🔯 No 🗆						
Action / F	Remarks:						
Deta			3.01				
Date:			B. Schade: Head of ESA Produce Assuran and Safety Department	ce			



Component Title: Schottky Barrier Power Diodes based on type STPS

CNES

Date: 272H-rev1

ANNEX 1: LIST OF TESTS DONE TO SUPPORT EXTENSION OF QUALIFICATION

04/02/2020

Tests conducted in compliance with:

ESCC 5000 generic specification; Chart F4 (for ESCC/QPL parts); or PID-TFD (for ESCC/QML parts)

Tests vehicle identification/description:

STPS1045 Lot ID33510003ZE_Full Chart F4	STPS60A150 Lot ID33648006ZZ_Chart F4 sg2&3
DC1731	DC1725
STPS20100 Lot ID33420006ZM_Full Chart F4 DC1627	STPS60A45 (same die as STPS80A45) Lot ID33652003ZU_Full Chart F4 DC1749

Executive Member:

Detail Specification reference:

Chart F4	Test	Tick when done	Conditions	Date Code Diffusion Lot	Tested Qty	N° of Rejects	Comments if not performed. Comments on Rejection
Environmental/Mechanical Subgroup	Mechanical shock	×	MIL-STD-750 TM2016	1731 1627 1749	45	0	
	Vibration	⊠	MIL-STD-750 TM2056	1731 1627 1749	45	0	
	Constant acceleration	×	MIL-STD-750 TM2006	1731 1627 1749	45	0	
	Seal Fine leak Gross leak	×	MIL-STD-750 TM1071	1731 1627 1749	45	0	
	Electrical Measurement	×	Intermediate and End- Point Electrical Measurements	1731 1627 1749	45	0	
nanica	External Visual	×	ESCC Basic Spec 20500	1731 1627 1749	45	0	
tal/Mech	Thermal shock		MIL-STD-750 TM1056	Click here to enter text			Only applicable to axial lead glass diodes
nmen	Temperature Cycling	×	MIL-STD-750 TM1051	1731 1627 1749	45	0	
Enviror	Moisture Resistance	Ø	MIL-STD-750 TM1021	1731 1627 1749	45	0	
	Seal Fine leak Gross leak	×	MIL-STD-750 TM1071	1731 1627 1749	45	0	
	Electrical Measurement	⊠	Intermediate and End- Point Electrical Measurements	1731 1627 1749	45	0	
	External Visual	⊠	ESCC Basic Spec 20500	1731 1627 1749	45	0	
Endurance Subgroup	Operating Life	⊠	ESCC 5000 Para. 8.19	1731 1627 1725 1749	60	0	
	Electrical Measurement	⊠	Intermediate and End- Point Electrical Measurements	1731 1627 1725 1749	60	0	
	Seal Fine leak Gross leak	⊠	MIL-STD-750 TM1071	1731 1627 1725 1749	60	0	
	External Visual Inspection	⊠	ESCC Basic Spec 20500	1731 1627 1725 1749	60	0	
Assembly Capability Subgroup	Permanence of Marking		ESCC Basic Spec 24800				Not applicable on Laser marking
	Terminal Strength	⊠	ESCC 5000 Para. 8.18	1731 1627 1725 1749	20	0	
	Internal Visual	⊠	ESCC Basic Spec 20400	1731 1627 1725 1749	20	0	
	Bond Strength	×	MIL-STD-750 TM 2037	1731 1627 1725 1749	12	0	
	Die Shear	⊠	MIL-STD-750 TM 2017	1731 1627 1725 1749	12	0	

Appl. No.

18

Page 4



Component title: Schottky Barrier Power Diodes based on type STPS

Page 7
Appl. No.

Executive Member:

CNES

Date: 04/02/2020

272H-rev1

NOTES ON THE COMPLETION OF THE APPLICATION FORM FOR ESCC QUALIFICATION EXTENSION APPROVAL

ENTRIES Form heading	shall indicate: - the title of the component as given in its detail specification or the name of the series, family; - the Executive Member; - the entering date; - the certificate number and its sequential suffix.
Box 1	shall provide details given in the table; in particular there shall be listed: - the variants or range of variants; - the range of components (the ESCC code is recommended to indicate the values or values range, the tolerance, the voltage, etc); the designation given in the detail specification as 'base on'; - under Test Vehicle enter either an ESCC code or the specific characteristic capable of identifying the component tested (e.g., voltage of coil for a relay); - under component similar enter a cross if relevant.
Box 2; 3 and 4	As per QPL entry; otherwise, an explanation of the changes must be supplied.
Box 5	Will show the ESCC Generic and Detail specifications, including issue number and revision letter, current at the time the tests reported were performed. If the specifications are different from those current on the date of the application, see Box 6.
Box 6	Will show the deviations from the Generic and Detail Specifications listed in Box 5, in particular deviations from testing. In case of deviations this must be listed in Box 15. In case the referenced specification in Box 5 have currently a different issue and/or revision indicate also whether the test data deviates or not from such current documents.
Box 7	Must reference the report(s) supplied in support of the application.
Box 8	Should provide the details of procurement to the full ESCC System, documentation of all of which should already have been delivered to the ESCC Executive under the terms of the relevant Generic Specification. An appropriate table has been drawn in this box.
Box 9	If the PID evolved after the Original Qualification or after the last Extension of Qualification, adequate details of such evolution shall be provided together with the reasons for the changes. Major changes shall be clearly marked.
Box 10	Identify the current PID issue status, date and actual date of verification. The date of verification of the current PID should be arranged as close as possible to the required date of extension.
Box 11	This box can be completed only after a physical visit to the plant to confirm that no unexplained changes occurred and that the practices, procedures, material, etc. used in manufacturing the components are as described in the PID. This survey shall be carried out in accordance with the requirements of ESCC Basic Specification No. 20200 and its findings shall be recorded.
Box 12	Provide details of, or reference to, any Destructive Physical Analysis (DPA) and Failure Analysis reports as well as any Nonconformance(s) (NCCS) occurred during the qualification validity period, stating if established corrective action have produced satisfactory results.
Box 13	Enter only the name of the Executive Member (i.e., CNES, DLR, ESTEC, etc.) and the signature of the responsible Executive Coordinator.
Box 14	To be used when there is a need to expand any of the boxes from 1 through 12. Identify box affected and reference the Box 14 in the relevant Box. Box 14 can be broken into 14a, 14b, etc. if several boxes have to be expanded.
Box 15	Fill in Table as requested.
Box 16	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
Box 17	All Executive Manager recommendations on the application itself, special conditions or restrictions, modifications of the QPL or QML entry, letters to the manufacturer, etc. shall be entered clearly in Box 19, signed by the representative for ESA, and dated.
Box 18	Fill in Table as requested.
Box 19	Confidential Details of PID changes including those of a confidential nature, shall be provided.
Box 20	State noncompliance with reference to specification(s) and paragraph(s). To simplify reference in Box 16 each nonconformance shall be sequentially numbered. If relevant state 'None'.
Box 21	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
Box 22	Additional Comments.