LOCU

APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component Title: POLYIMIDE INSULATED WIRES AND CABLES, LOW FREQUENCY,

Page 1 Appl. No.

			60	0V, -100 to 200	0°C				Арр	i. NO.
		Executive Member: CNES			Date: 05/02/2020			0	07T	
Components (includi	ing series and familie	s) submitted for	Extension	of Qualification	n Approval:					1
ESCC COMP. NO.	VARIANTS	RANG	GE OF COM	MPONENTS BASE ON			TEST VEHICLE / S		COMPON SIMILA	
3901 001	24 to 29, 32, 35, 3 41, 44, 47	8, All variant AWG12-1		ose based on			3901 0	02 46 B3		
3901 002	31 to 91	All variant	s							
Component M	lanufacturer	2 Loc	cation of M	anufacturing P	lant	3				4
PRYSMIAN DRAKA	_		730 Saint 0	_	•		Date of origina	al qualification ap	proval:	
T TO COMP AT DIVAC		2100100	roo oanie c	3011011010			Date:	15/01/1979	provai.	
							Date.	13/01/1979		
							Certificate Ref No. 07			
		5				6				7
ESCC Specifications Maintenance of qual	Deviations used:	Deviations to LVT testing and Detail Specification				Qualification Extension Report reference and date:				
Generic: 3901 Is:	No ⊠					FE19332 05/02/2020				
				15)						
Detail(s): 3901-00	2 Deviation	Deviation from current Specifications:								
		No ⊠	Yes	☐ (Suppl	y details)					
Summary of procure	ment or equivalent to	et results during	n current va	alidity period in	support of th	is an	nlication (those	to ESCC listed fi	rst)	8
Project Name	Testing Level	ot roodito daring	LAT	many poriod in	Date				antity Delivered	
See appendix 1										
PID changes since start of qualification			9	Current PID	Verified by:			NES		10
None							_	ency Represen		
Minor* ⊠				Ref No:	RD01-01 E	D. 3	Rev. E and RD	01-02 ED.4 Rev.	E	
Major* □	*Provide detail			Issue:				Date:	05/02/2020	
	(See appendix 2)			Rev Date:	06/01/2020)				
Current Manufacturi	ng facilities surveyed	by:		CNES			on	05.	/02/2020	11
Current Manufacturii	ng racillues surveyed		••				on			
			Name	of Agency Re	epresentativ	/e		•	(Date)	
Satisfactory:	Yes ⊠	No		See	MoM DSO/A	AQ/C	Q-2020.0024329	9		

	APPLICATI	ON FOR EXTEN	SION OF ESCC QUAL	IFICATION APPROVAL	Page 2	
ESCC	Component title: POLYIMIDE INSULATED WIRES AND CABLES, LOW FREQUENCY 600V, -100 to 200°C				Appl. No.	
	Executive Member:	CNES		Date: 05/02/2020	07T	
Failure Analysis, DPA, NCCS ava	ilable: Yes	□ No		Click here to enter text.	12	
Ref. No's and purposes: Click here to	o enter text.					
The undersigned hereby certifies on behalf that the appropriate documentation has bee except as stated in box 15; - that the report CNES as the responsible Executive Memb	en evaluated; - that full s and data are availab	compliance to all le at the ESCC E	I ESCC requirements is xecutive and therefore	s evidence applies on behalf of	13	
Date: 19/02/2020				JP. BUSSENOT		
				((Signature of the Executive	Coordinator)	
Continuation of Boxes above:					14	

ESCC

APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

POLYIMIDE INSULATED WIRES AND CABLES, LOW FREQUENCY, 600V, -100 to 200°C Component title:

Executive Member: **CNES** Date: 05/02/2020 Page 3

Appl. No. 07T

Noncompliance to ESCC requirements: No.: Specification Paragraph Non compliance Additional tasks required to achieve full compliance for ESCC qualification or rationale for acceptability of 14 noncompliance: **Executive Manager Disposition** 15 Application Approval: Yes 🖺 No Action / Remarks: Date: Click here to enter a date. B.Schade: Head of ESA Product Assurance and Safety Department



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

POLYIMIDE INSULATED WIRES AND CABLES, LOW FREQUENCY, 600V, -100 to 200°C Component title:

Executive Member: CNES Date: 05/02/2020 Page 4

Appl. No. 07T

N	OTES ON THE COMPLETION OF THE APPLICATION FORM FOR ESCC QUALIFICATION EXTENSION APPROVAL
ENTRIES Form heading	shall indicate: - the title of the component as given in its detail specification or the name of the series, family; - the Executive Member;
	- the entering date; - the certificate number and its sequential suffix.
Box 1	shall provide details given in the table; in particular there shall be listed: - the variants or range of variants; - the range of components (the ESCC code is recommended to indicate the values or values range, the tolerance, the voltage, etc); the designation given in the detail specification as 'base on'; - under Test Vehicle enter either an ESCC code or the specific characteristic capable of identifying the component tested (e.g., voltage of coil for a relay); - under component similar enter a cross if relevant.
Box 2; 3 and 4	As per QPL entry; otherwise, an explanation of the changes must be supplied.
Box 5	Will show the ESCC Generic and Detail specifications, including issue number and revision letter, current at the time the tests reported were performed. If the specifications are different from those current on the date of the application, see Box 6.
Box 6	Will show the deviations from the Generic and Detail Specifications listed in Box 5, in particular deviations from testing. In case of deviations this must be listed in Box 15. In case the referenced specification in Box 5 have currently a different issue and/or revision indicate also whether the test data deviates or not from such current documents.
Box 7	Must reference the report(s) supplied in support of the application.
Box 8	Should provide details of procurement to the full ESCC System, documentation of all of which should already have been delivered to the ESCC Executive under the terms of the relevant Generic Specification. An appropriate table has been drawn in this box.
Box 9	If the PID evolved after the Original Qualification or after the last Extension of Qualification, adequate details of such evolution shall be provided together with the reasons for the changes. Major changes shall be clearly marked.
Box 10	Identify the current PID issue status, date and actual date of verification. The date of verification of the current PID should be arranged as close as possible to the required date of extension.
Box 11	This box can be completed only after a physical visit to the plant to confirm that no unexplained changes occurred and that the practices, procedures, material, etc. used in manufacturing the components are as described in the PID. This survey shall be carried out in accordance with the requirements of ESCC Basic Specification No. 20200 and its findings shall be recorded.
Box 12	Provide details of, or reference to, any Destructive Physical Analysis (DPA) and Failure Analysis reports as well as any Nonconformance(s) (NCCS) occurred during the qualification validity period, stating if established corrective action have produced satisfactory results.
Box 13	Enter only the name of the Executive Member (i.e., CNES, DLR, ESTEC, etc.) and the signature of the responsible Executive Coordinator.
Box 14	To be used when there is a need to expand any of the boxes from 1 through 12. Identify box affected and reference the Box 14 in the relevant Box. Box 14 can be broken into 14a, 14b, etc. if several boxes have to be expanded.
Box 15	State noncompliance with reference to specification(s) and paragraph(s). To simplify reference in Box 16 each nonconformance shall be sequentially numbered. If relevant state 'None'.
Box 16	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
Box 17	All Executive Manager recommendations on the application itself, special conditions or restrictions, modifications of the QPL entry, letters to the manufacturer, etc. shall be entered clearly in Box 17, signed by the representative for ESA, and dated.