6.9 RELAYS (09)

6.9.1 Non-Latching

RELAY, NON-LATCHING, ELECTROMAGNETIC, TYPE T **				**102K**
Procurement Specifications	Manufacturer	Nature of Approval	Supervising Authority	Initial Qualification Date
Generic ESCC 3601 Detail ESCC 3601/002	REL-STPI St Jean de la Ruelle France	Qualification	CNES	Feb 1983
		Remarks		

Qualified range:

Variants 01 to 06 are qualified

Contact Rating	1 A at 28 Vdc
Contact Configuration	2 PDT
Package Type	TO-5 Can
Coil Voltage	5 - 26.5 Vdc

Operating Temperature Range (°C): -65 to +125

RELAY, NON-LATCHING, ELECTROMAGNETIC, TYPE E 215				**205Grev1**
Procurement Specifications	Manufacturer	Nature of Approval	Supervising Authority	Initial Qualification Date
Generic ESCC 3601 Detail ESCC 3601/007	REL-STPI St Jean de la Ruelle France	Qualification	CNES	Jan 1994
		Remarks		

Qualified range:

Variants 03, 04 and 06 are qualified

Contact Rating	15 A at 28 Vdc
Contact Configuration	2 PDT
Package Type	Half cubic inch can
Coil Voltage	12 and 28Vdc

Operating Temperature Range (°C): -65 to +125

6.9.2 Latching, 28Vdc Contact Rating

RELAY, LATCHING, ELECTROMAGNETIC, TYPE TL				**88K**
Procurement Specifications	Manufacturer	Nature of Approval	Supervising Authority	Initial Qualification Date
Generic ESCC 3602 Detail ESCC 3602/002	REL-STPI Saint Jean de la Ruelle France	Qualification	CNES	Jan 1982
		Remarks As from September 2015, in relation to NCCS 2STPI501 , each delivery of TL26 parts shall be subject to an official prior agreement by the ESCC Executive during a MRB.		

Qualified range:

Variants 01 to 06 are qualified

Contact Rating	1 A at 28 Vdc
Contact Configuration	2 PDT
Package Type	TO-5 can
Coil Voltage	26.5 Vdc

Operating Temperature Range (°C): -65 to +125

RELAY, LATCHING, ELECTROMAGNETIC, TYPE EL415				**98Jrev2**
Procurement Specifications	Manufacturer	Nature of Approval	Supervising Authority	Initial Qualification Date
Generic ESCC 3602 Detail ESCC 3602/004	REL-STPI Saint Jean de la Ruelle France	Qualification	CNES	Jan 1982
		Remarks		

Qualified range:

Variants 04, 06 and 09 and 14, 16 and 19 are qualified

Contact Rating	15A at 28Vdc
Contact Configuration	4PDT Package
Package Type	Cubic inch can
Coil Voltage	28Vdc

Operating Temperature Range (°C): -65 to +125

RELAY, LATCHING, ELECTROMAGNETIC, TYPE EL215				**167Hrev1**
Procurement Specifications	Manufacturer	Nature of Approval	Supervising Authority	Initial Qualification Date
Generic ESCC 3602 Detail ESCC 3602/009	REL STPI St Jean de la Ruelle France	Qualification	CNES	Feb 1990
		Remarks		

Qualified range:

Variants 03, 04, 06 and 13, 14 and 16 are qualified

Contact Rating	15A at 28Vdc
Contact Configuration	2PDT Package
Package Type	Half-cubic inch can
Coil Voltage	28Vdc

Operating Temperature Range (°C): -65 to +125