

Component Title: Relays, latching, Type EL 215

Appl. No.

Page 1

Executive Member: **CNES** 13/05/2020 Date: 167H rev1 1 Components (including series and families) submitted for Extension of Qualification Approval: **ESCC** COMPONENT BASED TEST COMPONENT **VARIANTS** RANGE OF COMPONENTS VEHICLE / S SIMILAR ON NO. 3602 009 01, 02, 03, 04 and 06, Coil voltage: 12 and 28 V Type EL 215 SCC 3602 009 05 All variants 13,14 and 16 03, 04, 05,06 12V 2 4 3 Component Manufacturer Location of Manufacturing Plant(s) REL - STPI Date of original qualification approval: 22, rue des chaises 01/02/1990 45140 St Jean de la Ruelle - France Certificate Ref No. 167 7 5 Qualification Extension Report ESCC Specifications used for Deviations to LVT testing and Detail Specification Maintenance of qualification testing: used: reference and date: 3602 3627.09.18 Rapport de CHART F4 EL215, 25/09/2018 Generic: Issue: 4 Nο Yes (supply details in Box 3579.03.17 Rapport de Chart F4 (f) EL 215, 20/03/2017 Detail(s): 3602 009 Issue: Deviation from current Specifications: ☐ (Supply details) and approved DCR 1332 Yes \boxtimes 3690.02.20 Rapport Validation Bertin Aubert, 11/02/2020 8 Summary of procurement or equivalent test results during current validity period in support of this application (those to ESCC listed first) Project Name Testing Level LAT Date code Quantity Delivered Data livraisons E & EL SCC 2012 -MAJ 09102018 9 10 PID changes since start of qualification Current PID Verified by: **CNES** None Name of Agency Representative Ref No: PID EL 210 EL 215 Minor* \boxtimes Issue: Date: 13/05/2020 Major* *Provide details in box: Rev Date: 11/05/2020 11 Current Manufacturing facilities surveyed by: ESA and CNES 14/09/2016 οn (Name of Agency Representative) (Date) Satisfactory: No Explain Yes \boxtimes 2019-0001074 -0115_CRR-Visite- STPI Report Reference:

APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL Page 2 Component title: Relays, latching, Type EL 215 Appl. No. **CNES** 13/05/2020 Executive Member: Date: 167H rev1 12 Failure Analysis, DPA, NCCS available: Yes No (Supply data) Ref. No's and purposes: 13 The undersigned hereby certifies on behalf of the ESCC Executive - that the above information is correct; that the appropriate documentation has been evaluated; - that full compliance to all ESCC requirements is evidence (except as stated in box 15;) - that the reports and data are available at the ESCC Executive and therefore applies on behalf of CNES as the responsible Executive Member for ESCC qualification status to be extended to the component(s) listed herein. 13/05/2020 JP. BUSSENOT Date: (Signature of the Executive Coordinator) Continuation of Boxes above: 14 PID's Changes: Add of the new final finish supplier and details about SnPb alloy rate and thickness. Applicable from date code 2020. Change in coil manufacturing flow chart (Implementation of Cu doped brazing material in the same way as for TL26 relays per NCCS 2CSTPI501 revA closed in May 2019) Update of coil manufacturing lot travelers (addition of Cu doped brazing solution reference) Update of plans and documents Update of the in-process control flow (add. of recorded RVT test; NOT APPLICABLE to EL215 relays) NB: Implementation of SnCuAg brazing material for coils has been validated on TL26 relays which have been agreed to represent a worst case in terms of risk since the wire diameter is the smallest in STPI space production.



Component title: Relays, latching, Type EL 215

Executive Member: CNES Date: 13/05/2020

Page 3

Appl. No. 167H rev1

Non compliance to ESCC requirements:

15

No.:	Specification	Paragraph	Non compliance	
Additional	tasks required to achieve full compliance for l	ESCC qualification or rationale for acceptability	of	
noncompl	iance:	2000 qualification of rationale for acceptability	01	16
				_
Executive	Manager Disposition			17
Applicatio	n Approval: Yes □x No □			
Action / R				
Action / IX	enars.			
			Digitally signed	
			by Britta Schade	
			Digitally signed by Britta Schade Date: 2020.06.09	
Date:			09:36:39 +02'00'	
			B. Schade: Head of ESA Product Assurance	e
			and Safety Department	



Component Title: Relays, latching, Type EL 215

Page 4 Appl. No. 167H rev1

18

CNES 13/05/2020 Executive Member: Date:

ANNEX 1: LIST OF TESTS DONE TO SUPPORT EXTENSION OF QUALIFICATION

Tests conducted in compliance with:

ESCC 3602 generic specification; Chart F4 (for ESCC/QPL parts);
Or PID-TFD (for ESCC/QML parts)

Tests vehicle identification/description:

ESCC 3602 009 05 12V (EL 215 127 E F70)	ESCC 3602 009 13 28V (EL 215 143 E M09 F70)			
DC 18-26	DC 17-05			

ESCC 3602 009 Detail Specification reference:

		Tick			T	No. 5	O
Chart F4	Test	when done	Conditions	Date Code	Tested Qty	No. of Rejects	Comments if not performed. Comments on Rejection
Subgroup	Thermal Shock		MIL-STD-202, Test Method 107	18-26	6	0	
	Low Level Sine Vibration	\boxtimes	MIL-STD-202, Test Method 204	18-26	6	0	
	Random Vibration		MIL-STD-202, Test Method 214				
Environmental / Mechanical (Column 1)	Low Level Mechanical Shock	\boxtimes	MIL-STD-202, Test Method 213	18-26	6	0	
ental / N (Co	Resistance to Soldering Heat		MIL-STD-202, Test Method 210	18-26	6	0	
vironm	Seal (Fine and Gross Leak)		MIL-STD-202, Test Method 112	18-26	6	0	
Ē	External Visual Inspection		ESCC Basic Specification No. 20500	18-26	6	0	
nental Subgroup ın 2)	High Level Sine Vibration		MIL-STD-202, Test Method 204	18-26	6	0	
	High Level Mechanical Shock		MIL-STD-202, Test Method 213	18-26	6	0	
Environmental hanical Subg (Column 2)	Seal (Fine and Gross Leak)		MIL-STD-202, Test Method 112	18-26	6	0	
Environ / Mechanical (Colur	External Visual Inspection	\boxtimes	ESCC Basic Specification No. 20500	18-26	6	0	
Endurance Subgroup 1 (Column 1)	Low Level Life		ESCC 3602 Para. 8.11.1	18-26	3	0	
	Inductive Life	\boxtimes	ESCC 3602 Para. 8.11.2	18-26	3	0	
	Seal (Fine and Gross Leak)	\boxtimes	MIL-STD-202, Test Method 112	18-26	3	0	
	External Visual Inspection		ESCC Basic Specification No. 20500	18-26	3	0	



Component title: Relays, latching, Type EL 215

Executive Member: CNES Date: 13/05/2020

Page 5

Appl. No. 167H rev1

Chart F4	Test	Tick when done	Conditions	Date Code	Tested Qty	No. of Rejects	Comments if not performed. Comments on Rejection
Endurance Subgroup 1 (Column 2)	Coil Life		ESCC 3602 Para. 8.12				
	Seal (Fine and Gross Leak)		MIL-STD-202, Test Method 112				
	External Visual Inspection		ESCC Basic Specification No. 20500				
dno	Intermediate Current		ESCC 3602 Para. 8.13	18-26	3	0	
Endurance Subgroup 1 (Column 3)	Mechanical Life		ESCC 3602 Para. 8.14	18-26	3	0	
ance (Colur	Seal (Fine and Gross Leak)		MIL-STD-202, Test Method 112	18-26	3	0	
Endura 1	External Visual Inspection		ESCC Basic Specification No. 20500	18-26	3	0	
о 2	Resistive Life	\boxtimes	ESCC 3602 Para. 8.11.3	18-26 , 17-05	12	0	
Endurance Subgroup 2	Seal (Fine and Gross Leak)		MIL-STD-202, Test Method 112	18-26 , 17-05	12	0	
	External Visual Inspection		ESCC Basic Specification No. 20500	18-26 , 17-05	12	0	
Assembly Capability Subgroup	Solderability	\boxtimes	MIL-STD-202, Test Method 208	18-26 , 17-05	6	0	
	Overload	\boxtimes	ESCC 3602 Para. 8.16	18-26, 17-05	6	0	
	Permanence of Marking		ESCC Basic Specification No. 24800	18-26 , 17-05	6	0	
	Terminal Strength		MIL-STD-202, Test Method 211	18-26, 17-05	6	0	
	Seal (Fine and Gross Leak)		MIL-STD-202, Test Method 112	18-26, 17-05	6	0	
Additional Tests							



Component title: Relays, latching, Type EL 215

Page 7
Appl. No.
167H rev1

Executive Member: CNES Date: 13/05/2020

NOTES ON THE COMPLETION OF THE APPLICATION FORM FOR ESCC QUALIFICATION EXTENSION APPROVAL

	NOTES ON THE COMPLETION OF THE APPLICATION FORM FOR ESCE QUALIFICATION EXTENSION APPROVAL
ENTRIES Form heading	shall indicate: - the title of the component as given in its detail specification or the name of the series, family; - the Executive Member; - the entering date; - the certificate number and its sequential suffix.
Box 1	shall provide details given in the table; in particular there shall be listed: - the variants or range of variants; - the range of components (the ESCC code is recommended to indicate the values or values range, the tolerance, the voltage, etc); the designation given in the detail specification as 'base on'; - under Test Vehicle enter either an ESCC code or the specific characteristic capable of identifying the component tested (e.g., voltage of coil for a relay); - under component similar enter a cross if relevant.
Box 2; 3 and 4	As per QPL entry; otherwise, an explanation of the changes must be supplied.
Box 5	Will show the ESCC Generic and Detail specifications, including issue number and revision letter, current at the time the tests reported were performed. If the specifications are different from those current on the date of the application, see Box 6.
Box 6	Will show the deviations from the Generic and Detail Specifications listed in Box 5, in particular deviations from testing. In case of deviations this must be listed in Box 15. In case the referenced specification in Box 5 have currently a different issue and/or revision indicate also whether the test data deviates or not from such current documents.
Box 7	Must reference the report(s) supplied in support of the application.
Box 8	Should provide the details of procurement to the full ESCC System, documentation of all of which should already have been delivered to the ESCC Executive under the terms of the relevant Generic Specification. An appropriate table has been drawn in this box.
Box 9	If the PID evolved after the Original Qualification or after the last Extension of Qualification, adequate details of such evolution shall be provided together with the reasons for the changes. Major changes shall be clearly marked.
Box 10	Identify the current PID issue status, date and actual date of verification. The date of verification of the current PID should be arranged as close as possible to the required date of extension.
Box 11	This box can be completed only after a physical visit to the plant to confirm that no unexplained changes occurred and that the practices, procedures, material, etc. used in manufacturing the components are as described in the PID. This survey shall be carried out in accordance with the requirements of ESCC Basic Specification No. 20200 and its findings shall be recorded.
Box 12	Provide details of, or reference to, any Destructive Physical Analysis (DPA) and Failure Analysis reports as well as any Nonconformance(s) (NCCS) occurred during the qualification validity period, stating if established corrective action have produced satisfactory results.
Box 13	Enter only the name of the Executive Member (i.e., CNES, DLR, ESTEC, etc.) and the signature of the responsible Executive Coordinator.
Box 14	To be used when there is a need to expand any of the boxes from 1 through 12. Identify box affected and reference the Box 14 in the relevant Box. Box 14 can be broken into 14a, 14b, etc. if several boxes have to be expanded.
Box 15	Fill in Table as requested.
Box 16	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
Box 17	All Executive Manager recommendations on the application itself, special conditions or restrictions, modifications of the QPL or QML entry, letters to the manufacturer, etc. shall be entered clearly in Box 19, signed by the representative for ESA, and dated.
Box 18	Fill in Table as requested.
Box 19	Confidential Details of PID changes including those of a confidential nature, shall be provided.
Box 20	State noncompliance with reference to specification(s) and paragraph(s). To simplify reference in Box 16 each nonconformance shall be sequentially numbered. If relevant state 'None'.

Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.

Box 22 Additional Comments.

Box 21