# ESCC

## APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component Title:

Executive Member:

RESISTANCE TEMPERATURE DETECTOR THIN FILM PLATINUM SENSOR, PTC, RANGE 100 TO 2000 OHMS AT 0°C, WITH A TEMPERATURE RANGE OF -200°C TO +200°C

ESA Date: 19/01/2020

Appl. No.

352A

Page 1

Components (includi	ng series and families) s	ubmitted for Extens	sion of Q	ualification	Approval:							
ESCC COMPONENT NO.	VARIANTS RANGE OF CO			NENTS	BASED ON			TEST VEHICLE / S	COMPONENT SIMILAR			
4006015	02	100 Ohms							01, 03, 04, 05, 0	6		
4006015	08	1000 Ohms							07, 09,10			
Component Ma	anufacturer 2	Location of	f Manufac	turing Plan	t(e)	3		I		4		
Innovative Sensor Te		Stegrütistrasse 1		•	` '		Date	Date of original qualification approval:				
Illiovative Selisor Te	scillology 151 AG	Switzerland	14 3042 L	.biiat-itapp	GI .		Date of original qualification approval.  Date: 20/02/2018					
							Date	. 20/02/2010				
							Certi	Certificate Ref No. 352				
	T _					Ι.						
F000 0 ifi ti	5	D	(T 4 4		0	6	-	7				
ESCC Specifications Maintenance of quali		Deviations to LV used:	1 testing	and Detail	Specificati	ion		Qualification Extension Report reference and date:				
Generic: 4006	Issue: 4	No ⊠ Ye	s $\sqcap$	(supply	details in E	Rox	P1K0.232.7W.B.010.S Requalification 202003					
			_	15)		, , ,		1.232.7W.B.010.S_Req				
Detail(s): 4006/01	5 Issue: 3	Deviation from c	urrent Sp	ecifications	:		26.04	3.2020				
		No ⊠ Yes	s 🗆	(Supply	details)		20.0	3.2020				
Summary of procure	ment or equivalent test r	esults during curre	nt validity	neriod in s	upport of t	his an	nlicatio	on (those to ESCC listed	l first)	8		
Project Name	Testing Level	LAT	ric validity	period iii s	Date code		piloatio	,	ity Delivered			
									.,			
							İ					
PID changes since s	tart of qualification		9 Cu	rrent PID	Verified by	/:		A. Pesce, ES	SA	10		
None							N	lame of Agency Repres	entative			
Minor* ⊠			Re	f No:	PID_01							
Major* □	*Provide details in box:		lss	ue:	4			Dat	e: 14/01/2021			
Major =	Click here to enter text			v Date:	14/01/202	1						
	Olloit Here to effect text		INC	v Date.	14/01/202					11		
Current Manufacturing facilities surveyed by: D.			D. Lacom	ıbe, F. Mar	tinez, ESA	١	or	n 2	27/09/2017			
		(N	Name of A	Agency Rep	resentativ	e)			(Date)			
Satisfactory:	Yes ⊠	No □	Evoloin									
Galisiaciory:	Yes ⊠	No 🗆	Explain									
Report Reference:	IST-AUD	-2017										
raport raidicionos.	101-400	2011										

# **ESCC**

### APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component title: RESISTANCE TEMPERATURE DETECTOR THIN FILM PLATINUM

SENSOR, PTC, RANGE 100 TO 2000 OHMS AT 0°C, WITH A TEMPERATURE RANGE OF -200°C TO +200°C

Appl. No.

Page 2

ESA Date: 19/01/2020 Executive Member: 352A 12 Failure Analysis, DPA, NCCS available:  $\boxtimes$ (Supply data) Yes No Ref. No's and purposes: 13 The undersigned hereby certifies on behalf of the ESCC Executive - that the above information is correct; - that the appropriate documentation has been evaluated; - that full compliance to all ESCC requirements is evidence (except as stated in box 15;) - that the reports and data are available at the ESCC Executive and therefore applies for ESCC qualification status to be extended to the component(s) listed herein. Digitally signed by Anastasia Pesce Date: 2021.01.19 14:44:54 +01'00' Date: 19/01/2020 (Signature of the Executive Coordinator) Continuation of Boxes above: 14



RESISTANCE TEMPERATURE DETECTOR THIN FILM PLATINUM SENSOR, PTC, RANGE 100 TO 2000 OHMS AT 0°C, WITH A TEMPERATURE RANGE OF -200°C TO +200°C Component title:

Appl. No.

B. Schade: Head of the Product Assurance and Safety Department

Page 3

		Executive N	Member: ESA	Date: 19	9/01/2020	352A
Non compliance to E	SCC requirements:					15
No.:	Specification		Paragraph		Non compliance	<b>;</b>
Additional tasks requ	ired to achieve full o	compliance for E	ESCC qualification or rationale for acc	ceptability of		16
noncompliance:						
Executive Manager D	Disposition					17
Application Approval:	Yes ⊠	No 🗆				
Action / Remarks:	103	140				
					Digita	ally signed
				64	O / by Br	itta Schade
				21		2021.02.03 0:13 +01'00'
Doto:					// 11.30	

RESISTANCE TEMPERATURE DETECTOR THIN FILM PLATINUM SENSOR, PTC, RANGE 100 TO 2000 OHMS AT 0°C, WITH A TEMPERATURE RANGE OF -200°C TO +200°C Component Title:

Date: 19/01/2020 ESA

Page 4 Appl. No.

18

352A

# ANNEX 1: LIST OF TESTS DONE TO SUPPORT EXTENSION OF QUALIFICATION

Tests conducted in compliance with:

ESCC 4006 generic specification; Chart F4 (for ESCC/QPL parts); Or PID-TFD (for ESCC/QML parts)

Tests vehicle identification/description:

P0K1.232.7W	400601502
P1K0.232.7W	400601508

Executive Member:

Detail Specification reference: 4006015

Chart F4	Test	Tick when done	Conditions	Date Code	Tested Qty	No. of Rejects	Comments if not performed. Comments on Rejection
	Shock (Specified Pulse)		MIL-STD-202, Test Method 213				ESCC Detail Specification 4006/015
	Vibration		MIL-STD-202, Test Method 204				ESCC Detail Specification 4006/015
	Dielectric Withstanding Voltages	$\boxtimes$	ESCC 4006 Para. 8.9	0920	24	0	
sdno	External Visual Inspection		ESCC Basic Specification No. 20500	1120	24	0	
Subgro	Thermal Shock		MIL-STD-202, Test Method 107	0520	24	0	
Environmental / Mechanical Subgroups	Resistance to Soldering Heat		MIL-STD-202, Test Method 210				ESCC Detail Specification 4006/015
	Moisture Resistance		MIL-STD-202, Test Method 106	0720	24	0	
	External Visual Inspection		ESCC Basic Specification No. 20500	0820	24	0	
nviron	Dissipation Constant		ESCC 4006 Para. 8.3.1.2				ESCC Detail Specification 4006/015
Ш	Thermal Time Constant		ESCC 4006 Para. 8.3.1.3				ESCC Detail Specification 4006/015
	Solderability		MIL-STD-202, Test Method 208				ESCC Detail Specification 4006/015
	Terminal Strength		MIL-STD-202, Test Method 211	1020	24	0	
	External Visual Inspection		ESCC Basic Specification No. 20500				ESCC Detail Specification 4006/015



RESISTANCE TEMPERATURE DETECTOR THIN FILM PLATINUM SENSOR, PTC, RANGE 100 TO 2000 OHMS AT 0°C, WITH A TEMPERATURE RANGE OF -200°C TO +200°C Component Title:

Date: 19/01/2020 Executive Member:

Page 5

Appl. No. 352A

Chart F4	Test	Tick when done	Conditions	Date Code	Tested Qty	No. of Rejects	Comments if not performed. Comments on Rejection
	Short Time Load	$\boxtimes$	ESCC 4006 Para. 8.16	3319	40	0	
Sc	Low Temperature Storage		ESCC 4006 Para. 8.17	3619	40	0	
	Operating Life		MIL-STD-202, Test Method 108	4319	40	0	
bgroul	Permanence of Marking		ESCC Basic Specification No. 24800				ESCC Detail Specification 4006/015
Endurance Subgroups	External Visual Inspection		ESCC Basic Specification No. 20500	0520	40	0	
	Short Time load		ESCC 4006 Para. 8.16	4319	40	0	
	Low Temperature Storage		ESCC 4006 Para. 8.17	4319	40	0	
	High Temperature Storage		ESCC 4006 Para. 8.20	4319	40	0	
	External Visual Inspection		ESCC Basic Specification No. 20500	0520	40	0	
Additional Tests	Thermal Cycles		TN4_1 Evaluation_Qualification Testplan Group 10	4719	20	0	
,							



RESISTANCE TEMPERATURE DETECTOR THIN FILM PLATINUM SENSOR, PTC, RANGE 100 TO 2000 OHMS AT 0°C, WITH A TEMPERATURE RANGE OF -200°C TO +200°C Component title:

ESA Executive Member: Date: 19/01/2020 Page 7

Appl. No. 352A

## NOTES ON THE COMPLETION OF THE APPLICATION FORM FOR ESCC QUALIFICATION EXTENSION APPROVAL

ENTRIES	
Form heading	shall indicate: - the title of the component as given in its detail specification or the name of the series, family; - the Executive Member; - the entering date; - the certificate number and its sequential suffix.
Box 1	shall provide details given in the table; in particular there shall be listed: - the variants or range of variants; - the range of components (the ESCC code is recommended to indicate the values or values range, the tolerance, the voltage, etc); the designation given in the detail specification as 'base on'; - under Test Vehicle enter either an ESCC code or the specific characteristic capable of identifying the component tested (e.g., voltage of coil for a relay); - under component similar enter a cross if relevant.
Box 2; 3 and 4	As per QPL entry; otherwise, an explanation of the changes must be supplied.
Box 5	Will show the ESCC Generic and Detail specifications, including issue number and revision letter, current at the time the tests reported were performed. If the specifications are different from those current on the date of the application, see Box 6.
Box 6	Will show the deviations from the Generic and Detail Specifications listed in Box 5, in particular deviations from testing. In case of deviations this must be listed in Box 15. In case the referenced specification in Box 5 have currently a different issue and/or revision indicate also whether the test data deviates or not from such current documents.
Box 7	Must reference the report(s) supplied in support of the application.
Box 8	Should provide the details of procurement to the full ESCC System, documentation of all of which should already have been delivered to the ESCC Executive under the terms of the relevant Generic Specification. An appropriate table has been drawn in this box.
Box 9	If the PID evolved after the Original Qualification or after the last Extension of Qualification, adequate details of such evolution shall be provided together with the reasons for the changes. Major changes shall be clearly marked.
Box 10	Identify the current PID issue status, date and actual date of verification. The date of verification of the current PID should be arranged as close as possible to the required date of extension.
Box 11	This box can be completed only after a physical visit to the plant to confirm that no unexplained changes occurred and that the practices, procedures, material, etc. used in manufacturing the components are as described in the PID. This survey shall be carried out in accordance with the requirements of ESCC Basic Specification No. 20200 and its findings shall be recorded.
Box 12	Provide details of, or reference to, any Destructive Physical Analysis (DPA) and Failure Analysis reports as well as any Nonconformance(s) (NCCS) occurred during the qualification validity period, stating if established corrective action have produced satisfactory results.
Box 13	Enter only the name of the Executive Member (i.e., CNES, DLR, ESTEC, etc.) and the signature of the responsible Executive Coordinator.
Box 14	To be used when there is a need to expand any of the boxes from 1 through 12. Identify box affected and reference the Box 14 in the relevant Box. Box 14 can be broken into 14a, 14b, etc. if several boxes have to be expanded.
Box 15	Fill in Table as requested.
Box 16	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
Box 17	All Executive Manager recommendations on the application itself, special conditions or restrictions, modifications of the QPL or QML entry, letters to the manufacturer, etc. shall be entered clearly in Box 19, signed by the representative for ESA, and dated.
Box 18	Fill in Table as requested.
Box 19	Confidential Details of PID changes including those of a confidential nature, shall be provided.
Box 20	State noncompliance with reference to specification(s) and paragraph(s). To simplify reference in Box 16 each nonconformance shall be sequentially numbered. If relevant state 'None'.
Box 21	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
Box 22	Additional Comments.