

APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component Title: Polyimide Insulated Shielded Cables With Drain Wire, Low Frequency,

600V, -200 To +200°C Based On Type SPLD

Page 1 Appl. No.

Executive Member: CNES 26/05/2021 Date: 268.1 1 Components (including series and families) submitted for Extension of Qualification Approval: **ESCC** BASED TEST COMPONENT RANGE OF COMPONENTS **VARIANTS** COMP. NO VEHICLE / S ON SIMILAR 3901 019 01 to 94 Voltage Rating, maximum (Vrms): **SPLD** 3901 019 05 Click here to enter text. 600 Temperature Range (°C): -200 to Click here to enter Click here to enter text. +200 text. All variants including AWG 30 are Click here to enter text. qualified 2 3 4 Component Manufacturer Location of Manufacturing Plant Axon'Cable SA Route de Chalons enChampagne Axon Date of original qualification approval: 15/06/2002 Date: 51210 Montmirail Certificate Ref No. 268 7 5 6 ESCC Specifications used for Deviations to LVT testing and Detail Specification Qualification Extension Report Maintenance of qualification testing: reference and date: TEST REPORT N°4699 Issue A, 1th April 2021 3901 (supply details in Box Generic: No Ì5) 3901 019 Detail(s): Deviation from current Specifications: (Supply details) \boxtimes Yes П 8 Summary of procurement or equivalent test results during current validity period in support of this application (those to ESCC listed first) Project Name Testing Level LAT Date code Quantity Delivered See appendix 9 Current PID Verified by: 10 PID changes since start of qualification F.Nouals, CNES Name of Excutive Representative None \Box ESA-PID-01-AXON Ref No: Minor* \boxtimes Major* Issue: 16 Date: 26/05/2021 *Provide detail Rev Date: 17/12/2020 11 Current Manufacturing facilities surveyed by: JB Sauveplane, CNES and F. Martinez, ESA on 09/06/2015 (Name of Agency Representative) (Date) Satisfactory: Nο Explain AXON-AU-2015 Yes |X|

	APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL			Page 2	
Component title: Polyimide Insulated Shielded Cables With Drain Wire, Low Frequency, 600V, -200 To +200°C Based On Type SPLD				Appl. No.	
	Executive Member:	CNES		Date: 26/05/2021	268J
Failure Analysis, DPA, NCCS ava	illable: Yes	□ No	⊠ (Supply data)	Click here to enter text.	12
The undersigned hereby certifies on behalf that the appropriate documentation has bee except as stated in box 15; - that the report CNES as the responsible Executive Memb	en evaluated; - that full s and data are availab	I compliance to le at the ESCC	all ESCC requirements Executive and therefore	is evidence e applies on behalf of nent(s) listed herein.	13
Date: 27/05/2021				JP BUSSENOT	0 " ()
				((Signature of the Executive	Coordinator)
Continuation of Boxes above:					14



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Polyimide Insulated Shielded Cables With Drain Wire, Low Frequency, 600V, -200 To +200 $^{\circ}\text{C}$ Based On Type SPLD Component title:

Executive Member: Date: 26/05/2021 Page 3

Appl. No. 268J

Noncomp	oliance to ESCC_requirements:				13
No.:	Specification	Paragraph		Non compliance	
A -1 -1141	l Angle de mine d'Angle de la complete de faut				
noncomp	il tasks required to achieve full compliance for pliance:	ESCC qualification or rationale for acceptability	OT		14
Executive	e Manager Disposition				15
Δnnlicatio	on Approval: Yes ☑ No □				13
Action / F					
			7	Digitally signed	
			S. H 2	Digitally signed by Britta Schade Date: 2021.06.30	
Date:	Click here to enter a date			17:35:06 +02'00'	

B. Schade: Head of the Product Assurance and Safety Department



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Polyimide Insulated Shielded Cables With Drain Wire, Low Frequency, 600V, -200 To +200 $^{\circ}\text{C}$ Based On Type SPLD Component title:

Date: 26/05/2021 Executive Member:

Page 4 Appl. No.

268J

NOTES ON THE COMPLETION OF THE APPLICATION FORM FOR ESCC QUALIFICATION EXTENSION APPROVAL

	NOTES ON THE COMPLETION OF THE APPLICATION FORM FOR ESCC QUALIFICATION EXTENSION APPROVAL
ENTRIES	
Form heading	shall indicate: - the title of the component as given in its detail specification or the name of the series, family; - the Executive Member; - the entering date; - the certificate number and its sequential suffix.
Box 1	shall provide details given in the table; in particular there shall be listed: - the variants or range of variants; - the range of components (the ESCC code is recommended to indicate the values or values range, the tolerance, the voltage, etc); the designation given in the detail specification as 'base on'; - under Test Vehicle enter either an ESCC code or the specific characteristic capable of identifying the component tested (e.g., voltage of coil for a relay); - under component similar enter a cross if relevant.
Box 2; 3 and 4	As per QPL entry; otherwise, an explanation of the changes must be supplied.
Box 5	Will show the ESCC Generic and Detail specifications, including issue number and revision letter, current at the time the tests reported were performed. If the specifications are different from those current on the date of the application, see Box 6.
Box 6	Will show the deviations from the Generic and Detail Specifications listed in Box 5, in particular deviations from testing. In case of deviations this must be listed in Box 15. In case the referenced specification in Box 5 have currently a different issue and/or revision indicate also whether the test data deviates or not from such current documents.
Box 7	Must reference the report(s) supplied in support of the application.
Box 8	Should provide details of procurement to the full ESCC System, documentation of all of which should already have been delivered to the ESCC Executive under the terms of the relevant Generic Specification. An appropriate table has been drawn in this box.
Box 9	If the PID evolved after the Original Qualification or after the last Extension of Qualification, adequate details of such evolution shall be provided together with the reasons for the changes. Major changes shall be clearly marked.
Box 10	Identify the current PID issue status, date and actual date of verification. The date of verification of the current PID should be arranged as close as possible to the required date of extension.
Box 11	This box can be completed only after a physical visit to the plant to confirm that no unexplained changes occurred and that the practices, procedures, material, etc. used in manufacturing the components are as described in the PID. This survey shall be carried out in accordance with the requirements of ESCC Basic Specification No. 20200 and its findings shall be recorded.
Box 12	Provide details of, or reference to, any Destructive Physical Analysis (DPA) and Failure Analysis reports as well as any Nonconformance(s) (NCCS) occurred during the qualification validity period, stating if established corrective action have produced satisfactory results.
Box 13	Enter only the name of the Executive Member (i.e., CNES, DLR, ESTEC, etc.) and the signature of the responsible Executive Coordinator.
Box 14	To be used when there is a need to expand any of the boxes from 1 through 12. Identify box affected and reference the Box 14 in the relevant Box. Box 14 can be broken into 14a, 14b, etc. if several boxes have to be expanded.
Box 15	State noncompliance with reference to specification(s) and paragraph(s). To simplify reference in Box 16 each nonconformance shall be sequentially numbered. If relevant state 'None'.
Box 16	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
Box 17	All Executive Manager recommendations on the application itself, special conditions or restrictions, modifications of the QPL entry, letters to the manufacturer, etc. shall be entered clearly in Box 17, signed by the representative for ESA, and dated.