

6.1.5 Semiconductor

CAPACITORS, MICROWAVE, SILICON, NAKED DIE, MOS, BASED ON TYPES 101M, 201M, 400M AND 401M				286F																																					
Procurement Specifications	Manufacturer	Nature of Approval	Supervising Authority	Initial Qualification Date																																					
Generic ESCC 5010 Detail ESCC 5711/002	COBHAM MICROWAVE Les Ulis France	Qualification	CNES	Dec 2008																																					
		Remarks:																																							
Qualified range:																																									
All variants defined by the ESCC Detail Specification																																									
<table><tr><th>Type</th><th>Capacitance Range (pF)</th><th>U_R(V)</th></tr><tr><td>400M106A & C</td><td>8.2, 10, 12, 15</td><td rowspan="5">40</td></tr><tr><td>400M10xA & 107C</td><td>18, 22, 27, 33, 39</td></tr><tr><td>400M108A & C</td><td>47, 56, 68</td></tr><tr><td>400M110A & C</td><td>81, 100</td></tr><tr><td>400M113J & 114J</td><td>10</td></tr><tr><td>101M106A & C</td><td>3.9, 4.7, 5.6, 6.8</td><td rowspan="3">100</td></tr><tr><td>101M10xA & 107C</td><td>10, 12, 15</td></tr><tr><td>101M108A & C</td><td>22, 27, 33, 39</td></tr><tr><td>201M106C</td><td>2.2, 2.7, 3.3</td><td rowspan="5">200</td></tr><tr><td>201M106A</td><td>0.1X (201M106C, -107C, -108C) + 210M106C</td></tr><tr><td>201M10xA & 107C</td><td>3.9, 4.7, 5.6, 6.8, 8.2</td></tr><tr><td>201M108A & C</td><td>10, 12, 15, 18</td></tr><tr><td>201M111J & 112J</td><td>0.25 & 0.4</td></tr><tr><td>401M111J</td><td>0.125</td><td rowspan="2">400</td></tr><tr><td>401M112J</td><td>0.2</td></tr></table>					Type	Capacitance Range (pF)	U _R (V)	400M106A & C	8.2, 10, 12, 15	40	400M10xA & 107C	18, 22, 27, 33, 39	400M108A & C	47, 56, 68	400M110A & C	81, 100	400M113J & 114J	10	101M106A & C	3.9, 4.7, 5.6, 6.8	100	101M10xA & 107C	10, 12, 15	101M108A & C	22, 27, 33, 39	201M106C	2.2, 2.7, 3.3	200	201M106A	0.1X (201M106C, -107C, -108C) + 210M106C	201M10xA & 107C	3.9, 4.7, 5.6, 6.8, 8.2	201M108A & C	10, 12, 15, 18	201M111J & 112J	0.25 & 0.4	401M111J	0.125	400	401M112J	0.2
Type	Capacitance Range (pF)	U _R (V)																																							
400M106A & C	8.2, 10, 12, 15	40																																							
400M10xA & 107C	18, 22, 27, 33, 39																																								
400M108A & C	47, 56, 68																																								
400M110A & C	81, 100																																								
400M113J & 114J	10																																								
101M106A & C	3.9, 4.7, 5.6, 6.8	100																																							
101M10xA & 107C	10, 12, 15																																								
101M108A & C	22, 27, 33, 39																																								
201M106C	2.2, 2.7, 3.3	200																																							
201M106A	0.1X (201M106C, -107C, -108C) + 210M106C																																								
201M10xA & 107C	3.9, 4.7, 5.6, 6.8, 8.2																																								
201M108A & C	10, 12, 15, 18																																								
201M111J & 112J	0.25 & 0.4																																								
401M111J	0.125	400																																							
401M112J	0.2																																								
Operating Temperature Range, (°C): -55 to +150																																									

6.4.4 RF/Microwave, Varactors

DIODES, MICROWAVE, SILICON, MULTIPLIER AND PIN, BASED ON TYPES DH 2XX, DH 50XXX and DH76XXX				225J																																																															
Procurement Specifications	Manufacturer	Nature of Approval	Supervising Authority	Initial Qualification Date																																																															
Generic ESCC 5010 Detail ESCC	COBHAM MICROWAVE Villebon Sur Yvette France	Qualification	CNES	Jun 1995																																																															
		Remarks Certificate 259C has been merged with this certificate in February 2012. Certificate 273F has been merged with this certificate in September 2019.																																																																	
5513/031, 5513/032, 5513/033, 5513/034, 5513/036, 5513/037, 5513/038, 5512/016, 5512/023																																																																			
Qualified range:																																																																			
<table><tr><th>ESCC Spec No.</th><th>Variants</th><th>Component type</th></tr><tr><td>5513/031</td><td>01 to 56</td><td>DH 50151 to DH 50157</td></tr><tr><td>5513/032</td><td>01 to 40</td><td>DH 50033 to DH 50037</td></tr><tr><td>5513/033</td><td>01 to 70</td><td>DH 50201 to DH 50209</td></tr><tr><td>5513/034</td><td>01 to 41</td><td>DH 50251 to DH 50256</td></tr><tr><td>5513/036</td><td>01 to 48</td><td>DH 50052 to DH 50057</td></tr><tr><td>5513/037</td><td>01 to 56</td><td>DH 50071 to DH 50077</td></tr><tr><td>5513/038</td><td>01 to 56</td><td>DH 50101 to DH 50107</td></tr><tr><td>5512/016</td><td>10 to 16</td><td>DH 267</td></tr><tr><td>5512/016</td><td>20 to 26</td><td>DH 292</td></tr><tr><td>5512/016</td><td>30 to 36</td><td>DH 256</td></tr><tr><td>5512/016</td><td>40 to 46</td><td>DH 252</td></tr><tr><td>5512/016</td><td>50 to 56</td><td>DH 294</td></tr><tr><td>5512/023</td><td>01 to 09</td><td>DH 76010</td></tr><tr><td>5512/023</td><td>10 to 18</td><td>DH 76015</td></tr><tr><td>5512/023</td><td>19 to 27</td><td>DH 76022</td></tr><tr><td>5512/023</td><td>28 to 36</td><td>DH 76033</td></tr><tr><td>5512/023</td><td>37 to 45</td><td>DH 76047</td></tr><tr><td>5512/023</td><td>46 to 54</td><td>DH 76068</td></tr><tr><td>5512/023</td><td>55 to 63</td><td>DH 76100</td></tr><tr><td>5512/023</td><td>64 to 72</td><td>DH 76150</td></tr></table>					ESCC Spec No.	Variants	Component type	5513/031	01 to 56	DH 50151 to DH 50157	5513/032	01 to 40	DH 50033 to DH 50037	5513/033	01 to 70	DH 50201 to DH 50209	5513/034	01 to 41	DH 50251 to DH 50256	5513/036	01 to 48	DH 50052 to DH 50057	5513/037	01 to 56	DH 50071 to DH 50077	5513/038	01 to 56	DH 50101 to DH 50107	5512/016	10 to 16	DH 267	5512/016	20 to 26	DH 292	5512/016	30 to 36	DH 256	5512/016	40 to 46	DH 252	5512/016	50 to 56	DH 294	5512/023	01 to 09	DH 76010	5512/023	10 to 18	DH 76015	5512/023	19 to 27	DH 76022	5512/023	28 to 36	DH 76033	5512/023	37 to 45	DH 76047	5512/023	46 to 54	DH 76068	5512/023	55 to 63	DH 76100	5512/023	64 to 72	DH 76150
ESCC Spec No.	Variants	Component type																																																																	
5513/031	01 to 56	DH 50151 to DH 50157																																																																	
5513/032	01 to 40	DH 50033 to DH 50037																																																																	
5513/033	01 to 70	DH 50201 to DH 50209																																																																	
5513/034	01 to 41	DH 50251 to DH 50256																																																																	
5513/036	01 to 48	DH 50052 to DH 50057																																																																	
5513/037	01 to 56	DH 50071 to DH 50077																																																																	
5513/038	01 to 56	DH 50101 to DH 50107																																																																	
5512/016	10 to 16	DH 267																																																																	
5512/016	20 to 26	DH 292																																																																	
5512/016	30 to 36	DH 256																																																																	
5512/016	40 to 46	DH 252																																																																	
5512/016	50 to 56	DH 294																																																																	
5512/023	01 to 09	DH 76010																																																																	
5512/023	10 to 18	DH 76015																																																																	
5512/023	19 to 27	DH 76022																																																																	
5512/023	28 to 36	DH 76033																																																																	
5512/023	37 to 45	DH 76047																																																																	
5512/023	46 to 54	DH 76068																																																																	
5512/023	55 to 63	DH 76100																																																																	
5512/023	64 to 72	DH 76150																																																																	
Operating Temperature Range (°C): -55 to +155																																																																			