

		APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL				Page 1
		Component Title: CONNECTORS,RF, COAXIAL, SOLDER AND CRIMP CONTACTS, MALE, FEMALE ADAPTORS AND CONNECTING PIECES,BASED ON TYPE SMA 2.9 Executive Member: CNES Date: 28/06/2022				Appl. No. 283 G rev.1
Components (including series and families) submitted for Extension of Qualification Approval: 1						
ESCC COMPONENT NO.	VARIANTS	RANGE OF COMPONENTS	BASED ON	TEST VEHICLE / S	COMPONENT SIMILAR	
3402/021	01 to 05 & 07	Frequency Range 0-40 GHz	SMA 2.9	340202101B301 340202102B301		
3402/022	01 to 05	Solder type contact for flexible and semi rigid cables, contacts for micro strip		340202203B301 340202205B301		
3402/023	01 to 06	Shell material and finish: passivated amafnetic stainless steel, Operating temperature range (°C): -65 to +165		340202301B301 340202302B301 340202305B301		
Component Manufacturer Radial		Location of Manufacturing Plant(s) RADIALL (Centr'alp), 641 Rue Emile Romanet, 38340 Voreppe (France)		Date of original qualification approval: Date: 01/12/2007 Certificate Ref No. 283		
ESCC Specifications used for Maintenance of qualification testing: Generic: 3402 Issue 5: Detail(s): 3402/021 Issue 4 3402/022 Issue 5 3402/023 Issue 7		Deviations to LVT testing and Detail Specification used: No <input type="checkbox"/> Yes <input checked="" type="checkbox"/> (supply details in Box 15) Deviation from current Specifications: No <input type="checkbox"/> Yes <input checked="" type="checkbox"/> (Supply details)		Qualification Extension Report reference and date: TEST REPORT n° 2022.17.6100 Rev1, 16/06/2022 TEST REPORT n°2022.18.6110, 09/05/2022 TEST REPORT N° CHR_C2021.25.0102 Rev2, 24/05/2022		
Summary of procurement or equivalent test results during current validity period in support of this application (those to ESCC listed first) 8						
Project Name	Testing Level	LAT	Date code	Quantity Delivered		
See PID Annex 4						
PID changes since start of qualification		Current PID Verified by: <u>G. Quadri, CNES</u>		Name of Excutive Representative		
None <input type="checkbox"/>		Ref No: PAQP-VOR 0064 (F)		Issue: 01 rev. A Date: 06/06/2022		
Minor* <input type="checkbox"/>		Rev Date: 28/06/2022				
Major* <input checked="" type="checkbox"/> *Provide details in box: see box 14						
Current Manufacturing facilities surveyed by: <u>CNES/ESA</u> on <u>12/04/2022</u> (Name of Executive Representative Agency) (Date)						
Satisfactory: Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Explain Two actions remain to be fulfilled						
Report Reference: <u>DTN/QE/CQ-2022.0005817</u>						



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component title: CONNECTORS,RF, COAXIAL, SOLDER AND CRIMP CONTACTS, MALE, FEMALE ADAPTORS AND CONNECTING PIECES,BASED ON TYPE SMA 2.9
Executive Member: CNES Date: 28/06/2022

Page 2

Appl. No.

283 G rev.1

12

Failure Analysis, DPA, NCCS available: Yes No (Supply data)

Ref. No's and purposes: 2CRAD026-deviations about ESCC qualification (see box 14) CLOSED

13

The undersigned hereby certifies on behalf of the ESCC Executive - that the above information is correct; - that the appropriate documentation has been evaluated; - that full compliance to all ESCC requirements is evidence (except as stated in box 15;) - that the reports and data are available at the ESCC Executive and therefore applies on behalf of CNES as the responsible Executive Member for ESCC qualification status to be extended to the component(s) listed herein.

G.QUADRI

Date: 28/06/2022

(Signature of the Executive Coordinator)

14

Continuation of Boxes above:

Box 5, box 6 and Box 9:

PID refers to the generic specification ESCC 3402 issue 4 (no screening, i.e. chart F3, only chart 2 of issue 4) except for qualification chart which deals with chart F4 of the issue 5. Test vehicles were manufactured in compliance with ESCC3402 issue 4 to allow a comparison with the qualification extension performed at IDA (n.283G)

Box 11

This revised application refers to the new manufacturing site of Centralp that takes the place of IDA

Box 12

NCCS 2CRAD206;several deviations are listed hereafter:

1/The screening of final production tests was carried out in accordance with chart II of the specification ESCC3402 Issue 4 to allow a comparison with the qualification extension performed on Isle d'Arbeu

2/ The detail specifications applied for the qualification are the draft versions associated with the update of the ESCC 3402 issue 5

3/ For the qualification of connectors to be wired, A RFD S21023 REV A has been applied



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component title: CONNECTORS,RF, COAXIAL, SOLDER AND CRIMP CONTACTS, MALE, FEMALE ADAPTORS AND CONNECTING PIECES,BASED ON TYPE SMA 2.9
Executive Member: CNES Date: 28/06/2022

Page 3
Appl. No.
283 G rev.1

Non compliance to ESCC requirements:

15

No.:	Specification	Paragraph	Non compliance
1	ESCC 3402 issue 5	12.4	Deviation from Chart F4 Sequence

Additional tasks required to achieve full compliance for ESCC qualification or rationale for acceptability of non-compliance

16

The justification for the deviation is described hereafter:

For the following categories which refer to connector to be cabled on semirigid cables or flexible cables:
ESCC3402/021 Variants 01 and 02
ESCC3402/022 Variants 01 and 02
ESCC3402/021 Variants 03 to 05

A RFD S2103 rev.A has been applied and consists in the following steps:
In Lot Validation testing Flow Chart (F4) of ESCC3402 issue 5, Random vibration and Electrical measurement are required: cable assembly is needed to electrically characterize the connectors.
Being not sustainable the random vibration level (50 grms) required by the ESCC3402 issue 5 for the concerned cable assemblies, additional pigtailed have been dedicated to this purpose. In parallel taking advantage of a renewal of a capability approval under CNES control for cable assemblies, ESCC3408 chart F4B has been deployed only for connectors in these specific configurations (i.e. the ones to be crimped and brazed for cables).

This same logic was prior applied to the IDA site before the transfer to Centralp (see application 283 G)

Executive Manager Disposition

17

Application Approval: Yes No

Action / Remarks:

Date:


B. Schade: Head of the Product Assurance and Safety Department



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component Title: CONNECTORS, RF, COAXIAL, SOLDER AND CRIMP CONTACTS, MALE, FEMALE ADAPTORS AND CONNECTING PIECES, BASED ON TYPE SMA 2.9
 Executive Member: CNES Date: 28/06/2022

Page 4

Appl. No.

283 G rev.1

ANNEX 1: LIST OF TESTS DONE TO SUPPORT EXTENSION OF QUALIFICATION

18

Tests conducted in compliance with:

- ESCC 3402 generic specification; Chart V (for ESCC/QPL parts);
- Or PID-TFD PAQP-A 0014 (F) issue 11 (for ESCC/QML parts)

Tests vehicle identification/description:

ESCC 340202102B301 (DC2209A) ESCC 340202101B301 (DC2209A)	
ESCC340202205B301 (DC2209A) ESCC340202301B301 (DC2209A) ESCC 340202302B301 (DC2210A), ESCC 340202305B301 (DC2111A) ESCC 340202203B301 (DC2210A)	ESCC 340202101B301 (DC2101), ESCC 340202102B301 (DC2051)

Detail Specification reference: [REDACTED]

Chart	Test	Tick when done	Conditions	Date Code	Tested Qty	No. of Rejects	Comments if not performed. Comments on Rejection
ESCC 3402 issue 5 chart F4	Mating and unmating Force	<input checked="" type="checkbox"/>	ESCC 3402, Para. 8.11	2209A 2209A 2210A 2211A 2210A	2,1,1,1,2	0	
	Random Vibration	<input checked="" type="checkbox"/>	ESCC 3402, Para. 8.15	2209A 2209A 2210A 2211A 2210A	2,1,1,1,2	0	
	Mechanical shock	<input checked="" type="checkbox"/>	ESCC 3402, Para. 8.16	2209A 2209A 2210A 2211A 2210A	2,1,1,1,2	0	
	Temperature cycling	<input checked="" type="checkbox"/>	ESCC 3402, Para. 8.8	2209A 2209A 2210A 2211A 2210A	2,1,1,1,2	0	
	Thermal Stability of insertion loss	<input checked="" type="checkbox"/>	ESCC 3402, Para. 8.17	2209A 2210A 2211A	1,1,1	0	Only applicable to connector transition, adaptor and connecting piece components
	Shielding effectiveness	<input checked="" type="checkbox"/>	ESCC 3402, Para. 8.18	2209A 2210A 2211A	1,1,1	0	Only applicable to connector transition, adaptor and connecting piece components
	Electrical measurements at room temperature	<input checked="" type="checkbox"/>	ESCC 3402, Para. 8.9.9	2209A 2209A 2210A 2211A 2210A	2,1,1,1,2	0	
	Endurance	<input checked="" type="checkbox"/>	ESCC 3402, Para. 8.19	2209A 2209A 2210A 2211A 2210A	2,1,1,1,2	0	

	Seal	<input type="checkbox"/>	ESCC 3402, Para. 8.13	Click here to enter text.	Click here to enter text.		Only applicable to hermetically sealed, barrier-sealed or panel-sealed components
	Coupling Proof Torque	<input checked="" type="checkbox"/>	ESCC 3402, Para. 8.10	2209A 2209A 2210A 2211A 2210A	2.1,1,1,2	0	
	External Visual Inspection	<input checked="" type="checkbox"/>	ESCC 3402, Para. 8.14	2209A 2209A 2210A 2211A 2210A	2.1,1,1,2	0	
	Destructive Physical Analysis	<input checked="" type="checkbox"/>	ESCC 3402, Para. 8.17	2210A, 2211A	2	0	
	External visual inspection initial	<input checked="" type="checkbox"/>	ESCC 3402, Para. 8.14	2209A 2209A	3,3	0	
	Random vibration	<input checked="" type="checkbox"/>	ESCC 3402, Para. 8.15	2209A 2209A	3,3	0	
	External visual inspection final	<input checked="" type="checkbox"/>	ESCC 3402, Para. 8.14	2209A 2209A	3,3	0	
ESCC 3408 issue chart F4B	VISUAL INSPECTION	<input checked="" type="checkbox"/>	ESCC 3408, Para. 8.15	2101 2051	10,10	0	
	RF MEASUREMENT (room temperature)	<input checked="" type="checkbox"/>	ESCC 3408, Para. 8.14	2101 2051	10,10	0	
	SHIELDING EFFECTIVENESS	<input checked="" type="checkbox"/>	ESCC 3408, Para. 8.15	2101 2051	10,10	0	
	RF MEASUREMENT (room temperature)	<input checked="" type="checkbox"/>	ESCC 3408, Para. 8.14	2101 2051	10,10	0	
	THERMAL STABILITY OF INSERTION LOSS	<input checked="" type="checkbox"/>	ESCC 3408, Para. 8.15	2101 2051	10,10	0	
	RF MEASUREMENT (room temperature)	<input checked="" type="checkbox"/>	ESCC 3408, Para. 8.14	2101 2051	10,10	0	
	THERMAL CYCLING	<input checked="" type="checkbox"/>	ESCC 3408, Para. 8.15	2101 2051	10,10	0	
	RF MEASUREMENT (room temperature)	<input checked="" type="checkbox"/>	ESCC 3408, Para. 8.14	2101 2051	10,10	0	
	THERMAL STABILITY OF INSERTION LOSS	<input checked="" type="checkbox"/>	ESCC 3408, Para. 8.15	2101 2051	10,10	0	
	RF MEASUREMENT (room temperature)	<input checked="" type="checkbox"/>	ESCC 3408, Para. 8.14	2101 2051	10,10	0	
	SHIELDING EFFECTIVENESS	<input checked="" type="checkbox"/>	ESCC 3408, Para. 8.15	2101 2051	10,10	0	
	VISUAL INSPECTION	<input checked="" type="checkbox"/>	ESCC 3408, Para. 8.14	2101 2051	10,10	0	
	RF MEASUREMENT AT HIGH AND LOW TEMPERATURE	<input checked="" type="checkbox"/>	ESCC 3408, Para. 8.14	2101 2051	10,10	0	
	RF MEASUREMENT (room temperature)	<input checked="" type="checkbox"/>	ESCC 3408, Para. 8.15	2101 2051	10,10	0	
	COUPLING PROOF TORQUE	<input checked="" type="checkbox"/>	ESCC 3408, Para. 8.14	2101 2051	10,10	0	
	VISUAL INSPECTION	<input checked="" type="checkbox"/>	ESCC 3408, Para. 8.15	2101 2051	10,10	0	
X-RAY	<input checked="" type="checkbox"/>	ESCC 3408, Para. 8.14	2101 2051	10,10	0		
MICROSECTIONING	<input checked="" type="checkbox"/>	ESCC 3402, Para. 8.15	2101 2051	10,10	0		



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component title: CONNECTORS,RF, COAXIAL, SOLDER AND CRIMP CONTACTS, MALE, FEMALE ADAPTORS AND CONNECTING PIECES,BASED ON TYPE SMA 2.9

Executive Member: CNES

Date: 28/06/2022

Page 6

Appl. No.

283 G rev.1

NOTES ON THE COMPLETION OF THE APPLICATION FORM FOR ESCC QUALIFICATION EXTENSION APPROVAL

ENTRIES

- Form heading shall indicate: - the title of the component as given in its detail specification or the name of the series, family; - the Executive Member; - the entering date; - the certificate number and its sequential suffix.
- Box 1 shall provide details given in the table; in particular there shall be listed: - the variants or range of variants; - the range of components (the ESCC code is recommended to indicate the values or values range, the tolerance, the voltage, etc); the designation given in the detail specification as 'base on'; - under Test Vehicle enter either an ESCC code or the specific characteristic capable of identifying the component tested (e.g., voltage of coil for a relay); - under component similar enter a cross if relevant.
- Box 2; 3 and 4 As per QPL entry; otherwise, an explanation of the changes must be supplied.
- Box 5 Will show the ESCC Generic and Detail specifications, including issue number and revision letter, current at the time the tests reported were performed. If the specifications are different from those current on the date of the application, see Box 6.
- Box 6 Will show the deviations from the Generic and Detail Specifications listed in Box 5, in particular deviations from testing. In case of deviations this must be listed in Box 15. In case the referenced specification in Box 5 have currently a different issue and/or revision indicate also whether the test data deviates or not from such current documents.
- Box 7 Must reference the report(s) supplied in support of the application.
- Box 8 Should provide the details of procurement to the full ESCC System, documentation of all of which should already have been delivered to the ESCC Executive under the terms of the relevant Generic Specification. An appropriate table has been drawn in this box.
- Box 9 If the PID evolved after the Original Qualification or after the last Extension of Qualification, adequate details of such evolution shall be provided together with the reasons for the changes. Major changes shall be clearly marked.
- Box 10 Identify the current PID issue status, date and actual date of verification. The date of verification of the current PID should be arranged as close as possible to the required date of extension.
- Box 11 This box can be completed only after a physical visit to the plant to confirm that no unexplained changes occurred and that the practices, procedures, material, etc. used in manufacturing the components are as described in the PID. This survey shall be carried out in accordance with the requirements of ESCC Basic Specification No. 20200 and its findings shall be recorded.
- Box 12 Provide details of, or reference to, any Destructive Physical Analysis (DPA) and Failure Analysis reports as well as any Nonconformance(s) (NCCS) occurred during the qualification validity period, stating if established corrective action have produced satisfactory results.
- Box 13 Enter only the name of the Executive Member (i.e., CNES, DLR, ESTEC, etc.) and the signature of the responsible Executive Coordinator.
- Box 14 To be used when there is a need to expand any of the boxes from 1 through 12. Identify box affected and reference the Box 14 in the relevant Box. Box 14 can be broken into 14a, 14b, etc. if several boxes have to be expanded.
- Box 15 Fill in Table as requested.
- Box 16 Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
- Box 17 All Executive Manager recommendations on the application itself, special conditions or restrictions, modifications of the QPL or QML entry, letters to the manufacturer, etc. shall be entered clearly in Box 19, signed by the representative for ESA, and dated.
- Box 18 Fill in Table as requested.
- Box 19 Confidential Details of PID changes including those of a confidential nature, shall be provided.
- Box 20 State noncompliance with reference to specification(s) and paragraph(s). To simplify reference in Box 16 each nonconformance shall be sequentially numbered. If relevant state 'None'.
- Box 21 Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
- Box 22 Additional Comments.