

6.10.2 Fixed, Film

RESISTORS, FILM, FIXED, SURFACE MOUNT, NON-HERMETICALLY SEALED, BASED ON TYPE MS1				256N		
Procurement Specifications	Manufacturer	Nature of Approval	Supervising Authority	Initial Qualification Date		
Generic ESCC 4001 Detail ESCC 4001/022	VISHAY Electronic GmbH Division Draloric Selb Germany	Qualification	DLR	Oct 1999		
Remarks						
Qualified range:						
Temperature coefficient, TCR (10 <sup>-6</sup> /K)	Tolerance (%)	Resistance Range R <sub>n</sub>				Value Series
		Min		Max		
		Resistance (Ω)	Code	Resistance (MΩ)	Code	
±50	±0.1	43.2	43R2	1	1004	E96
	±0.5	10	10R0	1	1004	E96
	±1	2.21	2R21	5.11	5114	E96
±25	±0.1	43.2	43R2	1	1004	E96
	±0.5	10	10R0	1	1004	E96
	±1	10	10R0	1	1004	E96
±15	±0.1	43.2	43R2	0.221	2213	E96
	±0.5	10	10R0	0.511	5113	E96
Critical R = 160 kΩ						
Operating Temperature Range (°C): -55 to +125						

RESISTORS, FILM, FIXED, SURFACE MOUNT, NON-HERMETICALLY SEALED, BASED ON TYPE TNPS					<b>289G</b>																																									
Procurement Specifications	Manufacturer	Nature of Approval	Supervising Authority	Initial Qualification Date																																										
Generic ESCC 4001 Detail ESCC 4001/029	VISHAY Electronic GmbH Division Draloric Selb Germany	Qualification	DLR	May 2009																																										
Remarks																																														
<p>Qualified range:</p> <p>Variants 01, 02 and 03 are qualified</p> <table border="1"> <thead> <tr> <th rowspan="2">Variant Number</th> <th rowspan="2">Style (Note 1)</th> <th colspan="2">Resistance Range <math>R_n</math></th> <th rowspan="2">Tolerance (<math>\pm</math> %)</th> <th rowspan="2">Value Series</th> <th rowspan="2">Temperature Coefficient TC (<math>\pm 10^{-6}/^{\circ}\text{C}</math>)</th> <th rowspan="2">Critical Resistance (k<math>\Omega</math>)</th> <th rowspan="2">Weight max (g)</th> </tr> <tr> <th>Min (<math>\Omega</math>)</th> <th>Max (M<math>\Omega</math>)</th> </tr> </thead> <tbody> <tr> <td>01</td> <td>0603</td> <td>10</td> <td>0.221</td> <td>0.1, 0.5, 1</td> <td>E96</td> <td>15, 25, 50</td> <td>56.25</td> <td>0.002</td> </tr> <tr> <td>02</td> <td>0805</td> <td>10</td> <td>0.422</td> <td>0.1, 0.5, 1</td> <td>E96</td> <td>15, 25, 50</td> <td>180</td> <td>0.006</td> </tr> <tr> <td>03</td> <td>1206</td> <td>10</td> <td>1</td> <td>0.1, 0.5, 1</td> <td>E96</td> <td>15, 25, 50</td> <td>160</td> <td>0.008</td> </tr> </tbody> </table> <p>Operating Temperature Range (<math>^{\circ}\text{C}</math>): -55 to +125</p>									Variant Number	Style (Note 1)	Resistance Range $R_n$		Tolerance ( $\pm$ %)	Value Series	Temperature Coefficient TC ( $\pm 10^{-6}/^{\circ}\text{C}$ )	Critical Resistance (k $\Omega$ )	Weight max (g)	Min ( $\Omega$ )	Max (M $\Omega$ )	01	0603	10	0.221	0.1, 0.5, 1	E96	15, 25, 50	56.25	0.002	02	0805	10	0.422	0.1, 0.5, 1	E96	15, 25, 50	180	0.006	03	1206	10	1	0.1, 0.5, 1	E96	15, 25, 50	160	0.008
Variant Number	Style (Note 1)	Resistance Range $R_n$		Tolerance ( $\pm$ %)	Value Series	Temperature Coefficient TC ( $\pm 10^{-6}/^{\circ}\text{C}$ )	Critical Resistance (k $\Omega$ )	Weight max (g)																																						
		Min ( $\Omega$ )	Max (M $\Omega$ )																																											
01	0603	10	0.221	0.1, 0.5, 1	E96	15, 25, 50	56.25	0.002																																						
02	0805	10	0.422	0.1, 0.5, 1	E96	15, 25, 50	180	0.006																																						
03	1206	10	1	0.1, 0.5, 1	E96	15, 25, 50	160	0.008																																						