



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component Title: RESISTANCE TEMPERATURE DETECTOR THIN FILM PLATINUM SENSOR, PTC, RANGE 100 TO 2000 OHMS AT 0°C, WITH A TEMPERATURE RANGE OF -200°C TO +200°C

Executive Member: _____ Date: _____

Page 1
Appl. No. 352D

Components (including series and families) submitted for Extension of Qualification Approval: 1

ESCC COMPONENT NO.	VARIANTS	RANGE OF COMPONENTS	BASED ON	TEST VEHICLE / S	COMPONENT SIMILAR
4006 015 02 00		100 Ohms			4006 015 01 00 4006 015 03 00 4006 015 04 00 4066 015 05 00 4006 015 06 00
4006 015 08 00		1000 Ohms			4006 015 07 00 4006 015 09 00 4006 015 10 00

Component Manufacturer Innovative Sensor Technology IST AG 2	Location of Manufacturing Plant(s) Stegrütistrasse 14 9642 Ebnat-Kappel 3	Date of original qualification approval: Date: 20/02/2018 4
		Certificate Ref No. 352

ESCC Specifications used for Maintenance of qualification testing: Generic: 4006 Issue: 5 Detail(s): 4006/015 Issue: 7 5	Deviations to LVT testing and Detail Specification used: No <input checked="" type="checkbox"/> Yes <input type="checkbox"/> (supply details in Box 15) Deviation from current Specifications: No <input checked="" type="checkbox"/> Yes <input type="checkbox"/> (Supply details) 6	Qualification Extension Report reference and date: 2025_Requalification_1K0.pdf 2025_Requalification_OK1.pdf Dec. 2025 7
---	---	--

Summary of procurement or equivalent test results during current validity period in support of this application (those to ESCC listed first) 8

Project Name	Testing Level	LAT	Date code	Quantity Delivered

PID changes since start of qualification 9	Current PID Verified by: Denis Lacombe 10
None <input type="checkbox"/> Minor* <input checked="" type="checkbox"/> Major* <input checked="" type="checkbox"/> *Provide details in box: Refer to ANNEX 2	Name of Executive Representative Ref No: PID_01 Issue: 6 Date: 19/01/2024 Rev Date: 16/12/2025

Current Manufacturing facilities surveyed by: Guiseppa Badolato / Leo Farhat on 17/09/2025 11
(Name of Executive Representative) (Date)
Satisfactory: Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Explain Click here to enter text.
Report Reference: <u>ESA-TECEDC-AUD-RP-2025-002885</u>



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component Title: RESISTANCE TEMPERATURE DETECTOR THIN FILM PLATINUM SENSOR, PTC, RANGE 100 TO 2000 OHMS AT 0°C, WITH A TEMPERATURE RANGE OF -200°C TO +200°C (with wire extension)
 Executive Member: _____ Date: _____

Page 2
 Appl. No. 352D

Components (including series and families) submitted for Extension of Qualification Approval: 1

ESCC COMPONENT NO.	VARIANTS	RANGE OF COMPONENTS	BASED ON	TEST VEHICLE / S	COMPONENT SIMILAR
4006 015				4006 015 02 05 0100	equivalent subvariants
				4006 015 02 05 1000	equivalent subvariants
				4006 015 02 04 0100	equivalent subvariants
				4006 015 02 04 1000	equivalent subvariants

Component Manufacturer Innovative Sensor Technology IST AG	2	Location of Manufacturing Plant(s) Stegrütistrasse 14 9642 Ebnat-Kappel	3	Date of original qualification approval: Date: 20/02/2018 Certificate Ref No. 352	4
---	---	--	---	---	---

ESCC Specifications used for Maintenance of qualification testing: Generic: 4006 Issue: 5 Detail(s): 4006/015 Issue: 7	5	Deviations to LVT testing and Detail Specification used: No <input checked="" type="checkbox"/> Yes <input type="checkbox"/> (supply details in Box 15) Deviation from current Specifications: No <input checked="" type="checkbox"/> Yes <input type="checkbox"/> (Supply details)	6	Qualification Extension Report reference and date: 2025_Requalification_Wire_Extension.pdf Dec. 2025	7
--	---	--	---	--	---

Summary of procurement or equivalent test results during current validity period in support of this application (those to ESCC listed first) 8

Project Name	Testing Level	LAT	Date code	Quantity Delivered

PID changes since start of qualification None <input type="checkbox"/> Minor* <input checked="" type="checkbox"/> Major* <input type="checkbox"/> *Provide details in box: Refer to ANNEX 2	9	Current PID Verified by: <u>Denis Lacombe</u> Name of Executive Representative Ref No: PID_02 Issue: 2 Date: 19/01/2024 Rev Date: 09/12/2025	10
--	---	---	----

Current Manufacturing facilities surveyed by:	Guiseppe Badolato / Leo Farhat	on	17/09/2025	11
	(Name of Executive Representative)		(Date)	
Satisfactory:	Yes <input checked="" type="checkbox"/>	No <input type="checkbox"/>	Ex pla in	
Report Reference:	<u>ESA-TECEDC-AUD-RP-2025-002885</u>			



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component title: RESISTANCE TEMPERATURE DETECTOR THIN FILM PLATINUM
SENSOR, PTC, RANGE 100 TO 2000 OHMS AT 0°C, WITH A
TEMPERATURE RANGE OF -200°C TO +200°C
Executive Member: _____ Date: _____

Page 3
Appl. No.
352D

Failure Analysis, DPA, NCCS available: Yes No (Supply data)

12

Ref. No's and purposes:

The undersigned hereby certifies on behalf of the ESCC Executive - that the above information is correct; - that the appropriate documentation has been evaluated; - that full compliance to all ESCC requirements is evidence (except as stated in box 15;) - that the reports and data are available at the ESCC Executive and therefore applies on behalf of _____ ESA _____ as the responsible Executive Member for ESCC qualification status to be extended to the component(s) listed herein.

13

Date: **Denis Lacombe** Digitally signed by Denis Lacombe
Date: 2026.01.22 17:27:05 +01'00' _____
(Signature of the Executive Coordinator)

Continuation of Boxes above:

14



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component title: RESISTANCE TEMPERATURE DETECTOR THIN FILM PLATINUM SENSOR, PTC, RANGE 100 TO 2000 OHMS AT 0°C, WITH A TEMPERATURE RANGE OF -200°C TO +200°C

Executive Member:

Date:

Page 4

Appl. No.

352D

Non compliance to ESCC requirements:

15

No.:	Specification	Paragraph	Non compliance

Additional tasks required to achieve full compliance for ESCC qualification or rationale for acceptability of noncompliance:

16

Executive Manager Disposition

17

Application Approval: Yes No

Action / Remarks:

Date: 31-Jan-2026

A. Zadeh - Head of the Avionics and EEE Division



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component Title: RESISTANCE TEMPERATURE DETECTOR THIN FILM PLATINUM SENSOR, PTC, RANGE 100 TO 2000 OHMS AT 0°C, WITH A TEMPERATURE RANGE OF -200°C TO +200°C
 Executive Member: _____ Date: _____

Page 5
 Appl. No. 352D

ANNEX 1: LIST OF TESTS DONE TO SUPPORT EXTENSION OF QUALIFICATION

18

Tests conducted in compliance with:

- ESCC 4006 generic specification; Chart F4 (for ESCC/QPL parts);
- Or PID-TFD _____ (for ESCC/QML parts)

Tests vehicle identification/description:

ESCC Component Number	4006 015 02 00
ESCC Component Numer	4006 015 08 00

Detail Specification reference: 4006 015

Chart F4	Test	Tick when done	Conditions	Date Code	Tested Qty	No. of Rejects	Comments if not performed. Comments on Rejection
Environmental / Mechanical Subgroups	Shock (Specified Pulse)	<input type="checkbox"/>	MIL-STD-202, Test Method 213				ESCC Detail Specification 4006/015
	Vibration	<input type="checkbox"/>	MIL-STD-202, Test Method 204				ESCC Detail Specification 4006/015
	Dielectric Withstanding Voltages	<input checked="" type="checkbox"/>	ESCC 4006 Para. 8.9	4725	24	0	
	External Visual Inspection	<input checked="" type="checkbox"/>	ESCC Basic Specification No. 20500	4825	24	0	
	Thermal Shock	<input checked="" type="checkbox"/>	MIL-STD-202, Test Method 107	3225	24	0	
	Resistance to Soldering Heat	<input type="checkbox"/>	MIL-STD-202, Test Method 210				ESCC Detail Specification 4006/015
	Moisture Resistance	<input checked="" type="checkbox"/>	MIL-STD-202, Test Method 106	3925	24	0	
	External Visual Inspection	<input checked="" type="checkbox"/>	ESCC Basic Specification No. 20500	4425	24	0	
	Dissipation Constant	<input type="checkbox"/>	ESCC 4006 Para. 8.3.1.2				ESCC Detail Specification 4006/015
	Thermal Time Constant	<input type="checkbox"/>	ESCC 4006 Para. 8.3.1.3				ESCC Detail Specification 4006/015
	Solderability	<input type="checkbox"/>	MIL-STD-202, Test Method 208				ESCC Detail Specification 4006/015
	Terminal Strength	<input checked="" type="checkbox"/>	MIL-STD-202, Test Method 211	4725	24	0	
External Visual Inspection	<input type="checkbox"/>	ESCC Basic Specification No. 20500				ESCC Detail Specification 4006/015	



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component Title: RESISTANCE TEMPERATURE DETECTOR THIN FILM PLATINUM SENSOR, PTC, RANGE 100 TO 2000 OHMS AT 0°C, WITH A TEMPERATURE RANGE OF -200°C TO +200°C

Executive Member:

Date:

Page 6

Appl. No.

352D

Chart F4	Test	Tick when done	Conditions	Date Code	Tested Qty	No. of Rejects	Comments if not performed. Comments on Rejection
Endurance Subgroups	Short Time Load	<input checked="" type="checkbox"/>	ESCC 4006 Para. 8.16	2825	40	0	
	Low Temperature Storage	<input checked="" type="checkbox"/>	ESCC 4006 Para. 8.17	3225	40	0	
	Operating Life	<input checked="" type="checkbox"/>	MIL-STD-202, Test Method 108	3325	40	0	
	Permanence of Marking	<input type="checkbox"/>	ESCC Basic Specification No. 24800				ESCC Detail Specification 4006/015
	External Visual Inspection	<input checked="" type="checkbox"/>	ESCC Basic Specification No. 20500	4725	40	0	
	Short Time load	<input checked="" type="checkbox"/>	ESCC 4006 Para. 8.16	2825	40	0	
	Low Temperature Storage	<input checked="" type="checkbox"/>	ESCC 4006 Para. 8.17	3225	40	0	
	High Temperature Storage	<input checked="" type="checkbox"/>	ESCC 4006 Para. 8.20	3225	40	0	
	External Visual Inspection	<input checked="" type="checkbox"/>	ESCC Basic Specification No. 20500	4725	40	0	
Additional Tests		<input type="checkbox"/>					
		<input type="checkbox"/>					
		<input type="checkbox"/>					



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component Title: RESISTANCE TEMPERATURE DETECTOR THIN FILM PLATINUM SENSOR, PTC, RANGE 100 TO 2000 OHMS AT 0°C, WITH A TEMPERATURE RANGE OF -200°C TO +200°C (with wire extension)
 Executive Member: _____ Date: _____

Page 8
 Appl. No. 352D

ANNEX 1: LIST OF TESTS DONE TO SUPPORT EXTENSION OF QUALIFICATION

18

Tests conducted in compliance with:

- ESCC 4006 generic specification; Chart F4 (for ESCC/QPL parts);
- Or PID-TFD _____ (for ESCC/QML parts)

Tests vehicle identification/description:

ESCC Component Number	4006 015 02 05 0100
ESCC Component Numer	4006 015 02 05 1000
ESCC Component Numer	4006 015 02 04 0100
ESCC Component Numer	4006 015 02 04 1000

Detail Specification reference: 4006015

Chart F4	Test	Tick when done	Conditions	Date Code	Tested Qty	No. of Rejects	Comments if not performed. Comments on Rejection
Environmental / Mechanical Subgroups	Shock (Specified Pulse)	<input checked="" type="checkbox"/>	MIL-STD-202, Test Method 213	3925	12	0	
	Vibration	<input checked="" type="checkbox"/>	MIL-STD-202, Test Method 204	3425	12	0	
	Dielectric Withstanding Voltages	<input checked="" type="checkbox"/>	ESCC 4006 Para. 8.9	3325	12	0	
	External Visual Inspection	<input checked="" type="checkbox"/>	ESCC Basic Specification No. 20500	4725	12	0	
	Thermal Shock	<input checked="" type="checkbox"/>	MIL-STD-202, Test Method 107	3725	12	0	
	Resistance to Soldering Heat	<input type="checkbox"/>	MIL-STD-202, Test Method 210				ESCC Detail Specification 4006/015
	Moisture Resistance	<input checked="" type="checkbox"/>	MIL-STD-202, Test Method 106	3925	12	0	
	External Visual Inspection	<input checked="" type="checkbox"/>	ESCC Basic Specification No. 20500	4725	12	0	
	Dissipation Constant	<input type="checkbox"/>	ESCC 4006 Para. 8.3.1.2				ESCC Detail Specification 4006/015
	Thermal Time Constant	<input type="checkbox"/>	ESCC 4006 Para. 8.3.1.3				ESCC Detail Specification 4006/015
	Solderability	<input type="checkbox"/>	MIL-STD-202, Test Method 208				ESCC Detail Specification 4006/015
	Terminal Strength	<input checked="" type="checkbox"/>	MIL-STD-202, Test Method 211	4725	12	0	
	External Visual Inspection	<input checked="" type="checkbox"/>	ESCC Basic Specification No. 20500	4725	12	0	



APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Component Title: RESISTANCE TEMPERATURE DETECTOR THIN FILM PLATINUM SENSOR, PTC, RANGE 100 TO 2000 OHMS AT 0°C, WITH A TEMPERATURE RANGE OF -200°C TO +200°C (with wire extension)
 Executive Member: _____ Date: _____

Page 9
 Appl. No. 352D

Chart F4	Test	Tick when done	Conditions	Date Code	Tested Qty	No. of Rejects	Comments if not performed. Comments on Rejection
Endurance Subgroups	Short Time Load	<input checked="" type="checkbox"/>	ESCC 4006 Para. 8.16				ESCC Detail Specification 4006/015
	Low Temperature Storage	<input checked="" type="checkbox"/>	ESCC 4006 Para. 8.17				ESCC Detail Specification 4006/015
	Operating Life	<input checked="" type="checkbox"/>	MIL-STD-202, Test Method 108				ESCC Detail Specification 4006/015
	Permanence of Marking	<input type="checkbox"/>	ESCC Basic Specification No. 24800				ESCC Detail Specification 4006/015
	External Visual Inspection	<input checked="" type="checkbox"/>	ESCC Basic Specification No. 20500			0	ESCC Detail Specification 4006/015
	Short Time load	<input checked="" type="checkbox"/>	ESCC 4006 Para. 8.16	2825	20	0	
	Low Temperature Storage	<input checked="" type="checkbox"/>	ESCC 4006 Para. 8.17	2825	20	0	
	High Temperature Storage	<input checked="" type="checkbox"/>	ESCC 4006 Para. 8.20	3225	20	0	
	External Visual Inspection	<input checked="" type="checkbox"/>	ESCC Basic Specification No. 20500	3225	20	0	
Additional Tests		<input type="checkbox"/>					
		<input type="checkbox"/>					
		<input type="checkbox"/>					

	APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL		Page 10
	Component Title: RESISTANCE TEMPERATURE DETECTOR THIN FILM PLATINUM SENSOR, PTC, RANGE 100 TO 2000 OHMS AT 0°C, WITH A TEMPERATURE RANGE OF -200°C TO +200°C (with wire extension)	Executive Member:	Date:

ANNEX 2 : CONFIDENTIAL DATA

PID changes details		19
None <input type="checkbox"/> Minor <input checked="" type="checkbox"/> Major <input type="checkbox"/>	General: - iST AG company logo changed and replaced company designation "IST AG" by "iST" (following iST corporate identity rules) §1.4: Added issue to supplier's documents §2: New responsible persons §5.1, 5.2, 5.3: New operating procedures (QVM_116, QVS_167), List of applicable SOP's updated	

Noncompliance to ESCC requirements: 20

No.:	Specification	Paragraph	Non compliance

Additional tasks required to achieve full compliance for ESCC qualification or rationale for acceptability of noncompliance: <div style="background-color: #cccccc; height: 15px; width: 100%; margin-top: 5px;"></div>	21
--	----

Additional Comments <div style="background-color: #cccccc; height: 15px; width: 100%; margin-top: 5px;"></div>	22
---	----

	APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL		Page 11
	Component title: RESISTANCE TEMPERATURE DETECTOR THIN FILM PLATINUM SENSOR, PTC, RANGE 100 TO 2000 OHMS AT 0°C, WITH A TEMPERATURE RANGE OF -200°C TO +200°C (with wire extension)	Executive Member:	Date:

NOTES ON THE COMPLETION OF THE APPLICATION FORM FOR ESCC QUALIFICATION EXTENSION APPROVAL

ENTRIES

Form heading	shall indicate: - the title of the component as given in its detail specification or the name of the series, family; - the Executive Member; - the entering date; - the certificate number and its sequential suffix.
Box 1	shall provide details given in the table; in particular there shall be listed: - the variants or range of variants; - the range of components (the ESCC code is recommended to indicate the values or values range, the tolerance, the voltage, etc); the designation given in the detail specification as 'base on'; - under Test Vehicle enter either an ESCC code or the specific characteristic capable of identifying the component tested (e.g., voltage of coil for a relay); - under component similar enter a cross if relevant.
Box 2; 3 and 4	As per QPL entry; otherwise, an explanation of the changes must be supplied.
Box 5	Will show the ESCC Generic and Detail specifications, including issue number and revision letter, current at the time the tests reported were performed. If the specifications are different from those current on the date of the application, see Box 6.
Box 6	Will show the deviations from the Generic and Detail Specifications listed in Box 5, in particular deviations from testing. In case of deviations this must be listed in Box 15. In case the referenced specification in Box 5 have currently a different issue and/or revision indicate also whether the test data deviates or not from such current documents.
Box 7	Must reference the report(s) supplied in support of the application.
Box 8	Should provide the details of procurement to the full ESCC System, documentation of all of which should already have been delivered to the ESCC Executive under the terms of the relevant Generic Specification. An appropriate table has been drawn in this box.
Box 9	If the PID evolved after the Original Qualification or after the last Extension of Qualification, adequate details of such evolution shall be provided together with the reasons for the changes. Major changes shall be clearly marked.
Box 10	Identify the current PID issue status, date and actual date of verification. The date of verification of the current PID should be arranged as close as possible to the required date of extension.
Box 11	This box can be completed only after a physical visit to the plant to confirm that no unexplained changes occurred and that the practices, procedures, material, etc. used in manufacturing the components are as described in the PID. This survey shall be carried out in accordance with the requirements of ESCC Basic Specification No. 20200 and its findings shall be recorded.
Box 12	Provide details of, or reference to, any Destructive Physical Analysis (DPA) and Failure Analysis reports as well as any Nonconformance(s) (NCCS) occurred during the qualification validity period, stating if established corrective action have produced satisfactory results.
Box 13	Enter only the name of the Executive Member (i.e., CNES, DLR, ESTEC, etc.) and the signature of the responsible Executive Coordinator.
Box 14	To be used when there is a need to expand any of the boxes from 1 through 12. Identify box affected and reference the Box 14 in the relevant Box. Box 14 can be broken into 14a, 14b, etc. if several boxes have to be expanded.
Box 15	Fill in Table as requested.
Box 16	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
Box 17	All Executive Manager recommendations on the application itself, special conditions or restrictions, modifications of the QPL or QML entry, letters to the manufacturer, etc. shall be entered clearly in Box 19, signed by the representative for ESA, and dated.
Box 18	Fill in Table as requested.
Box 19	Confidential Details of PID changes including those of a confidential nature, shall be provided.
Box 20	State noncompliance with reference to specification(s) and paragraph(s). To simplify reference in Box 16 each nonconformance shall be sequentially numbered. If relevant state 'None'.
Box 21	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
Box 22	Additional Comments.