APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Page 1

Component Title: **CONNECTORS, ELECTRICAL, CIRCULAR, BAYONET COUPLING, SCOOP-PROOF, REMOVABLE CRIMP CONTACTS, BASED ON TYPE MIL-DTL-38999, SERIES I**

Appl. No. **220N**

Executive Member: CNES Date: 17/08/2026

1

Components (including series and families) submitted for Extension of Qualification Approval:

ESCC COMPONENT NO.	VARIANTS	RANGE OF COMPONENTS	BASED ON	TEST VEHICLE / S	COMPONENT SIMILAR
3401/052	01	# 20 with standard contact arrangements 3, 6, 10, 19, 26, 32, 41, 53, 61 # 22 with high density arrangements 6, 13, 22, 37, 55, 66, 79, 100, 128 Operating Temperature Range ("C): - 65 to +200	MIL-DTL-38999 Sérei I	340105201B001335SN 340105201B061335PN 340105201B071726SN 340105201B061726PN	
3401/058	01 to 14	Other arrangements with contact sizes: 22, 20, 16, 12, 8	3401058	340105802B 340105804B 340105806B 340105808B 340105801B 340105803B 340105805B 340105807B	
3401/062	01 to 27	Operating temperature (°C) : -65 to +200	3401062	3401 062 12 B-3401 062 03B-3401 062 23B-3401 062 14B.	

2 Component Manufacturer

SOURIAU

3 Location of Manufacturing Plant(s)

3 Rue du Vallon
94440 Marolles en Brie, FRANCE

4

Date of original qualification approval:
Date: 01/05/1995

Certificate Ref No. 220

5

ESCC Specifications used for Maintenance of qualification testing:

Generic: 3401 Issue: 5

Detail(s): 3401/052 Issue: 3
3401/058 5
3401/062 3

6

Deviations to LVT testing and Detail Specification used:

No ☒ Yes ☐ (supply details in Box 15)

Deviation from current Specifications:

No ☒ Yes ☐ (Supply details)

7

Qualification Extension Report reference and date:

PV8975-25-045 Issue A 28/05/26

8

Summary of procurement or equivalent test results during current validity period in support of this application (those to ESCC listed first)

Project Name	Testing Level	LAT	Date code	Quantity Delivered
Synthèse Historique des Ventes 38999 2024-2025				

9

PID changes since start of qualification

None ☐
Minor* ☒
Major* ☐

*Provide details in box: 19

10

Current **PID** Verified by: CNES
Name of Executive Representative

Ref No: ZQU 92 M 256
Issue: S Date: 25/05/2026
Rev Date: 16/03/2026

11

Current Manufacturing facilities surveyed by: François NOUALS on 07/07/2026
(Name of Executive Representative) (Date)

Satisfactory: Yes ☐ No ☐ Explain

Report Reference: Compt rendu Visite de Souriau 2026

Component title: CONNECTORS, ELECTRICAL, CIRCULAR, BAYONET COUPLING, SCOOP-PROOF, REMOVABLE CRIMP CONTACTS, BASED ON TYPE MIL-DTL-38999, SERIES I

Executive Member: CNES Date: 17/08/2026

Appl. No. 220N

12

Failure Analysis, DPA, NCCS available: Yes ☒ No ☐ (Supply data)

Ref. No's and purposes: 2CSOU601 – MOQ Delays

13

The undersigned hereby certifies on behalf of the ESCC Executive - that the above information is correct; - that the appropriate documentation has been evaluated; - that full compliance to all ESCC requirements is evidence (except as stated in box 15;) - that the reports and data are available at the ESCC Executive and therefore applies on behalf of ..... as the responsible Executive Member for ESCC qualification status to be extended to the component(s) listed herein.

Date: 17/08/2026

Fontaine Lya

L. FONTAINE

(Signature of the Executive Coordinator)

Continuation of Boxes above:

14

15

Non compliance to ESCC requirements:

No.:	Specification	Paragraph	Non compliance

16

Additional tasks required to achieve full compliance for ESCC qualification or rationale for acceptability of noncompliance:

17

Executive Manager Disposition

Application Approval: Yes ☒ No ☐

Action / Remarks:

Date: 30/09/2029

A. Zadeh: Head of the Avionics and EEE Division

ANNEX 1: LIST OF TESTS DONE TO SUPPORT EXTENSION OF QUALIFICATION

18

Tests conducted in compliance with:

- ESCC 3401 generic specification; Chart V (for ESCC/QPL parts);
- Or PID-TFD [Click here to enter text.] (for ESCC/QML parts)

Tests vehicle identification/description:

Série	Référence	Désignation	Brochage	Répartition GROUPE 1	Répartition GROUPE 2	Raccord 3401062xxB	Désignation	Service Rating
Série 1 (3401/052)	340105201B001335SN	Embase Collerette Carrée taille 13	13-35 (22 Cts #22)	1 Couple	1 Couple	3401 062 12B	Raccord s/c Droit	M
	340105201B061335PN	Fiche taille 13				3401 062 03B	Raccord simple	
	340105201B071726SN	Embase Fixation par Ecrou taille 17	17-26(26 Cts #20)	1 Couple	1 Couple	3401 062 23B	Raccord s/c 90°	I
	340105201B061726PN	Fiche taille 17				3401 062 14B	Raccord s/c droit	

340105802B	Douille # 22 pour séries 1 et 3	10
340105804B	Douille # 20 pour séries 1 et 3	10
340105806B	Douille # 16 pour séries1 et 3	10
340105808B	Douille # 12 pour séries 1 et 3	10

Detail Specification reference: 3401/052, 3401/058, 3401/062

Chart V	Test	Tick when done	Conditions	Date Code	Tested Qty	No. of Rejects	Comments if not performed. Comments on Rejection
Environmental and Mechanical Subgroup	Wiring	☒	ESCC 3401 Para. 9.10	2604	4	0	
	Climatic Sequence	☒	ESCC 3401 Para. 9.13	2604	4	0	
	Permanence of Marking	☒	ESCC 24800	2604	4	0	
	Corrosion	☒	IEC Publication No. 68-2-11	2604	4	0	
	Seal Test	☐	ESCC 3401 Para. 9.9				NA
	Plating Thickness	☒	ESCC 3401 Para. 5.2.3	2604	4	0	
Endurance Subgroups	Wiring	☒	ESCC 3401 Para. 9.10	2604	4	0	
	Rapid change of Temperature	☒	ESCC 3401 Para. 9.16	2604	4	0	
	Contact Retention	☒	ESCC 3401 Para. 9.17	2604	4	0	
	Maintenance Ageing	☒	ESCC 3401 Para. 9.27	2604	4	0	
	Endurance	☒	ESCC 3401 Para. 9.18	2604	4	0	
	Seal Test	☐	ESCC 3401 Para. 9.9				NA
	Joint Stength	☒	ESCC 3401 Para. 9.15	2604	4	0	
	Engage/Separ. Forces	☒	ESCC 3401 Para. 9.28	2604	4	0	
	Oversize Pin Exclusion	☒	ESCC 3401 Para. 9.29	2604	4	0	
	Probe Damage	☒	IEC Publication No. 512-8	2604	4	0	
Additional Tests		☐					
		☐					
		☐					

NOTES ON THE COMPLETION OF THE APPLICATION FORM FOR ESCC QUALIFICATION EXTENSION APPROVAL

ENTRIES

Form heading	shall indicate: - the title of the component as given in its detail specification or the name of the series, family; - the Executive Member; - the entering date; - the certificate number and its sequential suffix.
Box 1	shall provide details given in the table; in particular there shall be listed: - the variants or range of variants; - the range of components (the ESCC code is recommended to indicate the values or values range, the tolerance, the voltage, etc); the designation given in the detail specification as 'base on'; - under Test Vehicle enter either an ESCC code or the specific characteristic capable of identifying the component tested (e.g., voltage of coil for a relay); - under component similar enter a cross if relevant.
Box 2; 3 and 4	As per QPL entry; otherwise, an explanation of the changes must be supplied.
Box 5	Will show the ESCC Generic and Detail specifications, including issue number and revision letter, current at the time the tests reported were performed. If the specifications are different from those current on the date of the application, see Box 6.
Box 6	Will show the deviations from the Generic and Detail Specifications listed in Box 5, in particular deviations from testing. In case of deviations this must be listed in Box 15. In case the referenced specification in Box 5 have currently a different issue and/or revision indicate also whether the test data deviates or not from such current documents.
Box 7	Must reference the report(s) supplied in support of the application.
Box 8	Should provide the details of procurement to the full ESCC System, documentation of all of which should already have been delivered to the ESCC Executive under the terms of the relevant Generic Specification. An appropriate table has been drawn in this box.
Box 9	If the PID evolved after the Original Qualification or after the last Extension of Qualification, adequate details of such evolution shall be provided together with the reasons for the changes. Major changes shall be clearly marked.
Box 10	Identify the current PID issue status, date and actual date of verification. The date of verification of the current PID should be arranged as close as possible to the required date of extension.
Box 11	This box can be completed only after a physical visit to the plant to confirm that no unexplained changes occurred and that the practices, procedures, material, etc. used in manufacturing the components are as described in the PID. This survey shall be carried out in accordance with the requirements of ESCC Basic Specification No. 20200 and its findings shall be recorded.
Box 12	Provide details of, or reference to, any Destructive Physical Analysis (DPA) and Failure Analysis reports as well as any Nonconformance(s) (NCCS) occurred during the qualification validity period, stating if established corrective action have produced satisfactory results.
Box 13	Enter only the name of the Executive Member (i.e., CNES, DLR, ESTEC, etc.) and the signature of the responsible Executive Coordinator.
Box 14	To be used when there is a need to expand any of the boxes from 1 through 12. Identify box affected and reference the Box 14 in the relevant Box. Box 14 can be broken into 14a, 14b, etc. if several boxes have to be expanded.
Box 15	Fill in Table as requested.
Box 16	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
Box 17	All Executive Manager recommendations on the application itself, special conditions or restrictions, modifications of the QPL or QML entry, letters to the manufacturer, etc. shall be entered clearly in Box 19, signed by the representative for ESA, and dated.
Box 18	Fill in Table as requested.
Box 19	Confidential Details of PID changes including those of a confidential nature, shall be provided.
Box 20	State noncompliance with reference to specification(s) and paragraph(s). To simplify reference in Box 16 each nonconformance shall be sequentially numbered. If relevant state 'None'.
Box 21	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
Box 22	Additional Comments.