APPLICATION FOR EXTENSION OF ESCC QUALIFICATION APPROVAL

Page 1

Component Title: RF FLEXIBLE CABLE ASSEMBLY TNC, VERY HIGH POWER, 50 OHMs, DC TO 8 GHz

Appl. No. 348D

Executive Member: CNES Date: 17/08/2026

1

Components (including series and families) submitted for Extension of Qualification Approval:

ESCC COMPONENT NO.	VARIANTS	RANGE OF COMPONENTS	BASED ON	TEST VEHICLE / S	COMPONENT SIMILAR
3408/001	4, 5 and 6	Frequency range 0-8 GHz Right angle and straight cable assembly for flexible 7.6mm cableTemperature range -165/+165°C	TNC Type	Variant 5, TNC VHP Straight Plug/TNC VHP Right Angle Plug, cable assemblies R23008808100007	

2 Component Manufacturer

RADIALL

3 Location of Manufacturing Plant(s)

RADIALL
39 RUE VELPEAU
BP30-37110 CHATEAU-RENAULT
(FRANCE)

4

Date of original qualification approval:
Date: 16/04/2018

Certificate Ref No. 348

5

ESCC Specifications used for Maintenance of qualification testing:

Generic: 3408 Issue: 4

Detail(s): 3408/001 Issue : 3

6

Deviations to LVT testing and Detail Specification used:

No ☒ Yes ☐ (supply details)

Deviation from current Specifications:

No ☒ Yes ☐ (Supply details)

7

Qualification Extension Report reference and date:

CHR_C2025.27.0103; date : 22/01/2026

8

Summary of procurement or equivalent test results during current validity period in support of this application (those to ESCC listed first)

Project Name	Testing Level	LAT	Date code	Quantity Delivered
See document « Données ventes SHF 8MS TNC VHP_2025 »				

9

PID changes since start of qualification

None ☐

Minor* ☐

Major* ☒ *Provide details in box: 19

10

Current **PID** Verified by: Audrey Bonzi, CNES
Name of Excutive Representative

Ref No: PAQ CHR 0014

Issue: I Date:

Rev Date: 29/06/2026

11

Current Manufacturing facilities surveyed by: François Nouals on
(Name of Executive Representative) 09/10/2024

Satisfactory: Yes ☒ No ☐ Explain CNES visit on Radiall CHR site on 09/10/2024

Report Reference: CR CNES_Visite du 09/10/2024

12

Failure Analysis, DPA, NCCS available: Yes ☐ No ☒ (Supply data)

Ref. No's and purposes:

13

The undersigned hereby certifies on behalf of the ESCC Executive - that the above information is correct; - that the appropriate documentation has been evaluated; - that full compliance to all ESCC requirements is evidence (except as stated in box 15;) - that the reports and data are available at the ESCC Executive and therefore applies on behalf of CNES as the responsible Executive Member for ESCC qualification status to be extended to the component(s) listed herein.

Date: 17/08/2026

Fontaine Lya

Lya Fontaine

(Signature of the Executive Coordinator)

Continuation of Boxes above:

14

No

15

Non compliance to ESCC requirements:

No.:	Specification	Paragraph	Non compliance

16

Additional tasks required to achieve full compliance for ESCC qualification or rationale for acceptability of noncompliance:
.

17

Executive Manager Disposition

Application Approval: Yes ☒ No ☐

Action / Remarks:

Date: 30/09/2026

A. Zadeh: Head of the Avionics and EEE Division

ANNEX 1: LIST OF TESTS DONE TO SUPPORT EXTENSION OF QUALIFICATION

Tests conducted in compliance with:

- ESCC 3408 generic specification; Chart F4 (for ESCC/QPL parts);
- Or PID-TFD Click here to enter text. (for ESCC/QML parts)

Tests vehicle identification/description:

TNC VHP Straight Plug/TNC VHP Right Angle Plug, cable assemblies R23008808100007 datecode 2521	

Detail Specification reference: ESCC3408/001 issue 3

Chart F4B	Test	Tick when done	Conditions	Date Code	Tested Qty	No. of Rejects	Comments if not performed. Comments on Rejection
Column 1 Sequence as detailed in ESCC 3408 chart F4B	Visual inspection (added)	☒	ESCC 3408 §8.24 ESCC 20500 § 4.4	2521	5	0	
	Interface dimension (added)	☒	ESCC 3408 §8.23 ESCC 3408/001 §1.6.3	2521	5	0	
	VSWR & insertion loss (added)	☒	ESCC3408 Issue 4 §8.20.1.3 §8.20.1.4 ESCC 3408/001 §2.4	2521	5	0	
	Shielding Effectiveness	☒	ESCC 3408 §8.25 ESCC 3408/001 §2.5	2521	5	0	
	Thermal stability of Insertion Loss	☒	ESCC 3408 §8.35	2521	4	0	
	Thermal cycles 100 cycles	☒	ESCC 3408 §8.17.3 ESCC 3408/001 §2.5 & 2.4	2521	4	0	
	Thermal Stability of Insertion Loss	☒	ESCC 3408 §8.35	2521	4	0	
	Shielding effectiveness	☒	ESCC 3408 §8.25 ESCC 3408/001 §2.5	2521	4	0	
	RF Power handling	☒	ESCC 3408 §8.33 ESCC 3408/001 §2.4	2521	4	0	
	RF Power cycling	☒	ESCC 3408 §8.34 ESCC 3408/001 §2.4	2521	4	0	
	Electrical measurements at room high and low temperature	☒	ESCC 3408 §8.20.4 ESCC 3408/001 §2.5	2521	4	0	
	Coupling Proof torque and connector interface dimensions	☒	ESCC 3408 §8.18 ESCC 3402 §8.10 ESCC3408/001 §1.5	2521	4	0	
	Mating and unmating forces	☒	ESCC 3408 §8.19.2 ESCC3408/001 §2.3	2521	4	0	
	External visual inspection	☒	ESCC 3408 §8.24 ESCC 20500 § 4.4	2521	4	0	
	Permanence of marking	☒	ESCC 3408 §8.37 ESCC 24800	2521	4	0	
	Radiographic inspection	☒	ESCC 3408 §8.22 ESCC 20900	2521	3	0	
	Destructive Physical Analysis	☒	ESCC 3408 §8.38 ESCC 21001	2521	3	0	

NOTES ON THE COMPLETION OF THE APPLICATION FORM FOR ESCC QUALIFICATION EXTENSION APPROVAL

ENTRIES

Form heading	shall indicate: - the title of the component as given in its detail specification or the name of the series, family; - the Executive Member; - the entering date; - the certificate number and its sequential suffix.
Box 1	shall provide details given in the table; in particular there shall be listed: - the variants or range of variants; - the range of components (the ESCC code is recommended to indicate the values or values range, the tolerance, the voltage, etc); the designation given in the detail specification as 'base on'; - under Test Vehicle enter either an ESCC code or the specific characteristic capable of identifying the component tested (e.g., voltage of coil for a relay); - under component similar enter a cross if relevant.
Box 2; 3 and 4	As per QPL entry; otherwise, an explanation of the changes must be supplied.
Box 5	Will show the ESCC Generic and Detail specifications, including issue number and revision letter, current at the time the tests reported were performed. If the specifications are different from those current on the date of the application, see Box 6.
Box 6	Will show the deviations from the Generic and Detail Specifications listed in Box 5, in particular deviations from testing. In case of deviations this must be listed in Box 15. In case the referenced specification in Box 5 have currently a different issue and/or revision indicate also whether the test data deviates or not from such current documents.
Box 7	Must reference the report(s) supplied in support of the application.
Box 8	Should provide the details of procurement to the full ESCC System, documentation of all of which should already have been delivered to the ESCC Executive under the terms of the relevant Generic Specification. An appropriate table has been drawn in this box.
Box 9	If the PID evolved after the Original Qualification or after the last Extension of Qualification, adequate details of such evolution shall be provided together with the reasons for the changes. Major changes shall be clearly marked.
Box 10	Identify the current PID issue status, date and actual date of verification. The date of verification of the current PID should be arranged as close as possible to the required date of extension.
Box 11	This box can be completed only after a physical visit to the plant to confirm that no unexplained changes occurred and that the practices, procedures, material, etc. used in manufacturing the components are as described in the PID. This survey shall be carried out in accordance with the requirements of ESCC Basic Specification No. 20200 and its findings shall be recorded.
Box 12	Provide details of, or reference to, any Destructive Physical Analysis (DPA) and Failure Analysis reports as well as any Nonconformance(s) (NCCS) occurred during the qualification validity period, stating if established corrective action have produced satisfactory results.
Box 13	Enter only the name of the Executive Member (i.e., CNES, DLR, ESTEC, etc.) and the signature of the responsible Executive Coordinator.
Box 14	To be used when there is a need to expand any of the boxes from 1 through 12. Identify box affected and reference the Box 14 in the relevant Box. Box 14 can be broken into 14a, 14b, etc. if several boxes have to be expanded.
Box 15	Fill in Table as requested.
Box 16	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
Box 17	All Executive Manager recommendations on the application itself, special conditions or restrictions, modifications of the QPL or QML entry, letters to the manufacturer, etc. shall be entered clearly in Box 19, signed by the representative for ESA, and dated.
Box 18	Fill in Table as requested.
Box 19	Confidential Details of PID changes including those of a confidential nature, shall be provided.
Box 20	State noncompliance with reference to specification(s) and paragraph(s). To simplify reference in Box 16 each nonconformance shall be sequentially numbered. If relevant state 'None'.
Box 21	Any additional action deemed necessary by the Executive Member to bring the submitted data to a standard likely to be accepted by the ESCC Executive should be listed herein or the reason(s) to accept the noncompliance.
Box 22	Additional Comments.